Application to: US Coast Guard & American Bureau of Shipping

Submitted to US EPA by: Lake Michigan Carferry Service Dated: February 25, 2014

ALL CONFIDENTIAL BUSINESS INFORMATION REDACTED BY LAKE MICHIGAN CARFERRY SERVICE

THIS PAGE

INTENTIONALLY LEFT BLANK

CONTAINS CONFIDENTIAL BUSILESS INFORMATION

From: Sent: To: Cc: Subject: Attachments: Marine Shop [engineering@ssbadger.com] Thursday, February 20, 2014 9:14 AM Bklages@eagle.org cleonard@pmship.com Badger 2013-12-20_Stoker_Front_PDF.zip; Stee, boiler fronts.tif; DSCo_Feeder_Mounting.pdf; Over_Fire_Air_PDF.zip

Good morning Brian,

We are now positioned for replacement of the boiler fronts and feeders aboard *Badger*, one part of the combustion control renewal program as agreed to in the consent decree between Lake Michigan Carferry and the DOJ.

I have attached PDF files of the drawings for the new boiler fronts, also attached is a file with mill certificates for the 0.750" ABS Grade A/A-36 steel plate we will use to fabricate the new fronts. We will fabricate the four new boiler fronts in our shop here in Ludington and are currently laying them out in preparation for drilling and cutting.

While we have the old boiler fronts removed we are taking the opportunity to repair any wasted material we may find in the grate support structure.

We have the final drawings of the new feeders, which have been manufactured by **Education and Second Second**

The new constraints of feeders will be controlled via Variable Frequency Drive units by the combustion control automation being designed for us by G.R. Bowler company. The automation portion of the package will be submitted by them under a separate cover. You may recognize **Constraints** the company that designed the propulsion controls for the S.S. Cason J. Calloway and other improvements for her fleet mates.

While we have the boiler fronts off we have also removed the refractory brick from the 'knee wall' between the lower drum and the furnace and intend to replace the existing wasted over-fire air manifold and nozzles. We have changed the spacing of the nozzles along this header to improve the delivery of combustion air above the fuel bed. In this pursuit we have also designed a second manifold to be installed in the 'filler wall' that was added along the back of the furnace in the early 1960's. These new and additional over-fire air nozzles will be positioned to introduce oxygen and turbulence above the fuel bed to enhance combustion. The existing over-fire air fan will be replaced with a new fan of larger capacity manufactured by the **Combustion** automation, an improvement over the former system that ran at a fixed volume.

The combustion control system will require more ships service air volume than we can currently supply with our existing air compressor so we propose to upgrade to a larger machine and relocate it. We have contacted in Sturgeon Bay to provide drawings for this sub-system and will include them in the scope of our work as soon as we have them.

As none of these are a significant change from original equipment we would like to consider them as a replacement in kind, I have requested thru our USCG Inspector, Richard Baker, to have American Bureau of Shipping review everything as allowed in in NVIC 10-82.

If I can answer any questions or provide further information, please do contact me at any time.

Best regards,

Chuck .



CONTAINS CONFIDENTIAL BUSINESS INFORMATION

Chuck Leonard

 From:
 Marine Shop [engineering@ssbadger.com]

 Sent:
 Wednesday, February 19, 2014 6:54 PM

 To:
 Baker, Richard (Richard.A.Baker@uscg.mil)

 Cc:
 cleonard@pmship.com

 Subject:
 Badger

 Attachments:
 2013-12-20_Stoker_Front_PDF.zip; AB-2793-D1-1L_REV_0_(FUEL SUPPLY EQUIPMENT ARR AUXILIARY VIEWS).pdf; Over_Fire_Air_PDF.zip; Stee, boiler fronts.tif; Charles Cart.vcf

Good afternoon Rich,

We are now positioned for replacement of the boiler fronts and feeders aboard *Badger*, one part of the combustion control renewal program as agreed to in the consent decree between Lake Michigan Carferry and the DOJ.

I have attached PDF files of the drawings for the new boiler fronts, also attached is a file with mill certificates for the 0.750" ABS Grade A/A-36 steel plate we will use to fabricate the new fronts. We will fabricate the four new boiler fronts in our shop here in Ludington and are currently laying them out in preparation for drilling and cutting.

While we have the old boiler fronts removed we are taking the opportunity to repair any wasted material we may find in the grate support structure.

We have the final drawings of the new feeders, which have been manufactured by the second sec

The new Control automation being designed for us by the controlled via Variable Frequency Drive units by the combustion control automation being designed for us by the company. The automation portion of the package will be submitted by them under a separate cover. You may recognize the company has the company that designed the propulsion controls for the S.S. Cason J. Calloway and other improvements for her fleet mates.

While we have the boiler fronts off we have also removed the refractory brick from the 'knee wall' between the lower drum and the furnace and intend to replace the existing wasted over-fire air manifold and nozzles. We have changed the spacing of the nozzles along this header to improve the delivery of combustion air above the fuel bed. In this pursuit we have also designed a second manifold to be installed in the 'filler wall' that was added along the back of the furnace in the early 1960's. These new and additional over-fire air nozzles will be positioned to introduce oxygen and turbulence above the fuel bed to enhance combustion. The existing over-fire air fan will be replaced with a new fan of larger capacity manufactured by the **Composition of the set of**

The combustion control system will require more ships service air volume than we can currently supply with our existing air compressor so we propose to upgrade to a larger machine and relocate it. We have contacted to be supply with our existing sturgeon to provide drawings for this sub-system and will include them in the scope of our work as soon as we have them.

As none of these are a significant change from our existing equipment we would like to consider them as a replacement in kind, and while we would be happy to have MSC review our drawings I do feel it would be expeditious to have American Bureau of Shipping review everything as allowed in in NVIC 10-82, and I would like to formally request that here if I may.


If I can answer any questions or provide further information, please do contact me at any time.


Best regards,


Chuck

-











47¹⁰⁰

at al



. .


. .




-

.


a . . .



-10.



-



.....




NUCOR STEEL TUSCALDOSA, INC.

MILL TEST CERTIFICATE 1700 HOLT RD N.E. Tuscaloosa, AL 35404-1000 800-827-8872


Page #:1 of 1


							<u> </u>		Line												<u> </u>	-	<u></u>	,
Load Number Tally Mill Order Number								ON O	Part Number					Cert	Certificate Number					Prepared				
R045384 0000000525341 N-125271-001								HI-859						S198	S198456-2					11/15/2013 12:19				
Grade								Customer:													ŀ			
Order Description: A36, 0.7500 IN x 96:000 IN x 240.000 IN Quality Plan Description: ABS A / A36: ASTM A36-08/ABS GR A 13/A709-36-11/ASME \$A					\$A36-	•03	Sold TO: CHAPEL STEEL Bourbonnais IL Ship TO: CHAPEL STEEL CO. INDIAN OAKS IL																	
Shipped Item	Heat/S1 Number		Certifie By	d (C	Mn	Ρ	S	Si	Cu	N'	i	Cr	Mo	Сь	٧	ΓA	Ti	N2		B	Ca	Sn	CEV
3J0992F	B3W8586-02	***	B3W8586	0.	18 (0.84 0	.007	0.009	0.04	0.16	0.0	05 0	.05	0.018	0.000	0.001	0.032	0.001	0.009	0.0	000	0.0034	0.006	0.34
3J0993D	B3W8586-03	***	B3W8586	0.	1.8 (0.84 0	.007	0.009	0.04	0.16	0.0	05 0	.05	0.018	0.000	0.001	0.032	0.001	0.009	0.0	000	0.0034	0.006	0.34
Shipped	Certified Heat		Yield Ten		sile	¥/T	ELONG	LONGATION		aT	Hard		Charpy Imp		acts (ft-]bs)	Sh(Shea	r %	T T	Test	
Item	By	/ Number		ksi	k	si	%	2"	8"	OK		HB _	Siz	e nin	1	2	3	Avg	1		2	3	Avg	Temp
3J0992F	\$330992FTT	83W8	\$\$86 ***	51.S	69	0.0	4.6	36.7																
330992F	S330992MTT	B3W8	586 ***	48-5	64	.5 7	5.2	33.3							_	ſ						· .		
3J0993D	\$300993FTT	83W8	1586 ***	47.8	68	.8 (9.5	37.0														:	<u> </u>	
3J0993D	S300993MTT	83W8	1586 ***	49.9	65	.3 7	6.4	34.6																
									•									: : : : : : : : : : : : : : : : : : :						
manufacturing Manufactured Information he requirements (PASSED plate ISO 9001:200	ot come in cont process. Certif under the ABS i rein has been in of the ABS rule from coil 8 Registered, PI Heats metted an	ied in ad Quality / nade to s with sa ED Certi	coordance with Assurance Pro the applicable atisfactory res ified	h EÑ 10 ogram, 10 a specific ulls, Ma	0204 3. Cerlific cations anufact	.1. No w cate num s by the f	elo rej iber 10 EAF pi	oair has t D-MMPQ/ rocess a	een per A-634 W nd tester	formed o Ve hereb d in acco	on this y cert ordance	s mate lify that ce with	rial. the the		e nereby	ceruly t		by th	eschoed e specific - // in Yu - M	2 2	15.	ed all of U		


CONTAINS CONFIDENTIAL BUSINESS INFORMATION




CONTAINS CONFIDENTIAL BUSINESS INFORMATION











No.





.

