

Region 4
U.S. Environmental Protection Agency
Science and Ecosystem Support Division
Athens, Georgia

OPERATING PROCEDURE


Title: Groundwater Sampling

Effective Date: March 6, 2013

Number: SESDPROC-301-R3

Authors


Name: Jonathan Vail
Title: Environmental Scientist, Regional Expert

Signature: 

Date: 3/4/2013


Approvals

Name: Danny France
Title: Chief, Enforcement and Investigations Branch

Signature: 

Date: 3/4/13

Name: Bobby Lewis
Title: Field Quality Manager, Science and Ecosystem Support Division

Signature: 

Date: 3/4/13

Revision History

The top row of this table shows the most recent changes to this controlled document. For previous revision history information, archived versions of this document are maintained by the SESD Document Control Coordinator on the SESD local area network (LAN).

History	Effective Date
<p>SESDPROC-301-R3, Groundwater Sampling, replaces SESDPROC-301-R2.</p> <p>General: Corrected any typographical, grammatical and/or editorial errors.</p> <p>Title Page: Changed author from Donald Hunter to Jonathan Vail. Changed Enforcement and Investigations Branch Chief from Archie Lee to Danny France.</p> <p>Revision History: Changes were made to reflect the current practice of only including the most recent changes in the revision history.</p> <p>Section 2.3: Item 4 was revised to reflect practice of using individual single-use preservative vials instead of preservatives prepared by ASB.</p>	<p>March 6, 2013</p>
<p>SESDPROC-301-R2, Groundwater Sampling, replaces SESDPROC-301-R1.</p>	<p>October 28, 2011</p>
<p>SESDPROC-301-R1, Groundwater Sampling, replaces SESDPROC-301-R0.</p>	<p>November 1, 2007</p>
<p>SESDPROC-301-R0, Groundwater Sampling, Original Issue</p>	<p>February 05, 2007</p>

TABLE OF CONTENTS

1	General Information	6
1.1	Purpose.....	6
1.2	Scope/Application	6
1.3	Documentation/Verification.....	6
1.4	References	6
1.5	General Precautions.....	8
1.5.1	Safety	8
1.5.2	Procedural Precautions.....	8
2	Special Sampling Considerations	10
2.1	Volatile Organic Compounds (VOC) Analysis.....	10
2.2	Special Precautions for Trace Contaminant Groundwater Sampling.....	10
2.3	Sample Handling and Preservation Requirements.....	11
2.4	Quality Control	12
2.5	Records.....	12
3	Groundwater Sampling Methods – Purging	13
3.1	General.....	13
3.2	Purging Methods and Strategies.....	13
3.2.1	Traditional Multiple Volume Purge	13
3.2.1.1	<i>Purging and Purge Adequacy</i>	13
3.2.1.1.1	<i>Purge Volume Determination</i>	13
3.2.1.1.2	<i>Chemical Parameter Stabilization Criteria</i>	15
3.2.1.1.3	<i>Purge Adequacy Considerations</i>	16
3.2.2	“Tubing-in-Screened-Interval” Method.....	16
3.2.2.1	<i>Purge Criteria</i>	17
3.2.2.1.1	<i>Placement of Pump Tubing or Intake</i>	17
3.2.2.1.2	<i>Conditions of Pumping</i>	17
3.2.2.1.3	<i>Stability of Chemical Parameters</i>	17

3.3	Equipment Considerations for Purging.....	17
3.3.1	Wells without Plumbing or In-Place Pumps	18
3.3.1.1	<i>Purging with Pumps</i>	18
3.3.1.1.1	<i>Peristaltic Pumps</i>	18
3.3.1.1.2	<i>Submersible Pumps</i>	19
3.3.1.2	<i>Purging with Bailers</i>	20
3.3.2	Wells with In-Place Plumbing	20
3.3.2.1	<i>Continuously Running Pumps</i>	20
3.3.2.2	<i>Intermittently or Infrequently Running Pumps</i>	21
3.3.3	Temporary Monitoring Wells.....	21
3.3.3.1	<i>General Considerations</i>	21
3.3.3.2	<i>Purging When Water Level Is Within Limit of Suction</i>	21
3.3.3.3	<i>Purging When Water Level Is Greater Than Limit of Suction</i>	22
3.3.3.4	<i>Considerations for Direct Push Groundwater Sampling</i>	22
3.4	Field Care of Purging Equipment	22
3.5	Investigation Derived Waste	23
4	Groundwater Sampling Methods – Sampling.....	24
4.1	General.....	24
4.2	Sampling Wells with In-Place Plumbing	24
4.3	Sampling Wells without Plumbing, Within the Limit of Suction.....	24
4.3.1	Equipment Available	24
4.3.1.1	<i>Peristaltic Pump, Direct from Pump Head Tubing</i>	24
4.3.1.2	<i>Peristaltic Pump/Vacuum Jug</i>	25
4.3.1.3	<i>RediFlo2® Electric Submersible Pump (with Teflon® Tubing)</i>	26
4.3.1.4	<i>Bailers</i>	26
4.4	Sampling Wells without Plumbing, Exceeding the Limit of Suction	26
4.5	Micro-Purge or No-Purge Sampling Procedures.....	27
4.5.1	Sampling with Pumps.....	27
4.5.2	HydraSleeves™	27
4.5.3	Passive Diffusion Bags	28
4.5.4	General Considerations for Micro-Purge or No-Purge Sampling	28

4.6	Sample Preservation	28
4.7	Special Sample Collection Procedures	29
4.7.1	Trace Organic Compounds and Metals.....	29
4.7.2	Order of Sampling with Respect to Analytes	29
4.7.3	Filtering.....	29
4.8	Specific Sampling Equipment Quality Assurance Techniques.....	31
4.9	Auxiliary Data Collection.....	31
4.9.1	Well Pumping Rate – Bucket/Stop Watch Method	31

1 General Information

1.1 Purpose

This document describes general and specific procedures, methods and considerations to be used and observed when collecting groundwater samples for field screening or laboratory analysis.

1.2 Scope/Application

The procedures contained in this document are to be used by field personnel when collecting and handling groundwater samples in the field. On the occasion that SESD field personnel determine that any of the procedures described are either inappropriate, inadequate or impractical and that another procedure must be used to obtain a groundwater sample, the variant procedure will be documented in the field logbook, along with a description of the circumstances requiring its use. Mention of trade names or commercial products in this operating procedure does not constitute endorsement or recommendation for use.

1.3 Documentation/Verification

This procedure was prepared by persons deemed technically competent by SESD management, based on their knowledge, skills and abilities and has been tested in practice and reviewed in print by a subject matter expert. The official copy of this procedure resides on the SESD Local Area Network (LAN). The Document Control Coordinator (DCC) is responsible for ensuring the most recent version of the procedure is placed on the LAN and for maintaining records of review conducted prior to its issuance.

1.4 References

Columbia Analytical Services, Lab Science News, Passive Diffusion Devices & Polyethylene Diffusion Bag (PDB) Samplers.

International Air Transport Authority (IATA). Dangerous Goods Regulations, Most Recent Version

Puls, Robert W., and Michael J. Barcelona. 1989. Filtration of Ground Water Samples for Metals Analysis. Hazardous Waste and Hazardous Materials 6(4), pp.385-393.

Puls, Robert W., Don A. Clark, and Bert Bledsoe. 1992. Metals in Ground Water: Sampling Artifacts and Reproducibility. Hazardous Waste and Hazardous Materials 9(2), pp. 149-162.

SESD Guidance Document, Design and Installation of Monitoring Wells, SESDGUID-001, Most Recent Version

SESD Operating Procedure for Control of Records, SESDPROC-002, Most Recent Version

SESD Operating Procedure for Sample and Evidence Management, SESDPROC-005, Most Recent Version

SESD Operating Procedure for Logbooks, SESDPROC-010, Most Recent Version

SESD Operating Procedure for Field Sampling Quality Control, SESDPROC-011, Most Recent Version

SESD Operating Procedure for Field pH Measurement, SESDPROC-100, Most Recent Version

SESD Operating Procedure for Field Specific Conductance Measurement, SESDPROC-101, Most Recent Version

SESD Operating Procedure for Field Temperature Measurement, SESDPROC-102, Most Recent Version

SESD Operating Procedure for Field Turbidity Measurement, SESDPROC-103, Most Recent Version

SESD Operating Procedure for Groundwater Level and Well Depth Measurement, SESDPROC-105, Most Recent Version

SESD Operating Procedure for Management of Investigation Derived Waste, SESDPROC-202, Most Recent Version

SESD Operating Procedure for Pump Operation, SESDPROC-203, Most Recent Version

SESD Operating Procedure for Field Equipment Cleaning and Decontamination, SESDPROC-205, Most Recent Version

SESD Operating Procedure for Field Equipment Cleaning and Decontamination at the FEC, SESDPROC-206, Most Recent Version

SESD Operating Procedure for Potable Water Supply Sampling, SESDPROC-305, Most Recent Version

The Interstate Technology & Regulatory Council, Technology Overview of Passive Sampler Technologies, Prepared by The Interstate Technology & Regulatory Council Diffusion Sampler Team, March 2006.

United States Environmental Protection Agency (US EPA). 1975. Handbook for Evaluating Water Bacteriological Laboratories. Office of Research and Development (ORD), Municipal Environmental Research Laboratory, Cincinnati, Ohio.

US EPA. 1977. Sampling for Organic Chemicals and Microorganisms in the Subsurface. EPA-600/2-77/176.

US EPA. 1978. Microbiological Methods for Monitoring the Environment, Water and Wastes. ORD, Municipal Environmental Research Laboratory, Cincinnati, Ohio.

US EPA. 1981. "Final Regulation Package for Compliance with DOT Regulations in the Shipment of Environmental Laboratory Samples," Memo from David Weitzman, Work Group Chairman, Office of Occupational Health and Safety (PM-273), April 13, 1981.

US EPA. 1995. Ground Water Sampling - A Workshop Summary. Proceedings from the Dallas, Texas November 30 – December 2, 1993 Workshop. ORD, Robert S. Kerr Environmental Research Laboratory. EPA/600/R-94/205, January 1995.

US EPA. Analytical Support Branch Laboratory Operations and Quality Assurance Manual. Region 4 SESD, Athens, GA, Most Recent Version

US EPA. Safety, Health and Environmental Management Program Procedures and Policy Manual. Region 4 SESD, Athens, GA, Most Recent Version

1.5 General Precautions

1.5.1 Safety

Proper safety precautions must be observed when collecting groundwater samples. Refer to the SESD Safety, Health and Environmental Management Program (SHEMP) Procedures and Policy Manual and any pertinent site-specific Health and Safety Plans (HASPs) for guidelines on safety precautions. These guidelines should be used to complement the judgment of an experienced professional. Address chemicals that pose specific toxicity or safety concerns and follow any other relevant requirements, as appropriate.

1.5.2 Procedural Precautions

The following precautions should be considered when collecting groundwater samples.

- Special care must be taken not to contaminate samples. This includes storing samples in a secure location to preclude conditions which could alter the properties of the sample. Samples shall be custody sealed during long-term storage or shipment.
- Always sample from the anticipated cleanest, i.e., least contaminated location, to the most contaminated location. This minimizes the opportunity for cross-contamination to occur during sampling.
- Collected samples must remain in the custody of the sampler or sample custodian until the samples are relinquished to another party.

- If samples are transported by the sampler, they will remain under his/her custody or be secured until they are relinquished.
- Shipped samples shall conform to all U.S. Department of Transportation (DOT) rules of shipment found in Title 49 of the Code of Federal Regulations (49 CFR parts 171 to 179), and/or International Air Transportation Association (IATA) hazardous materials shipping requirements found in the current edition of IATA's Dangerous Goods Regulations.
- Documentation of field sampling is done in a bound logbook.
- Chain-of-custody documents shall be filled out and remain with the samples until custody is relinquished.
- All shipping documents, such as air bills, bills of lading, etc., shall be retained by the project leader and placed in the project files.

2 Special Sampling Considerations

2.1 Volatile Organic Compounds (VOC) Analysis

Groundwater samples for VOC analysis must be collected in 40 ml glass vials with Teflon® septa. The vial may be either preserved with concentrated hydrochloric acid or they may be unpreserved. Preserved samples have a two-week holding time, whereas unpreserved samples have only a seven-day holding time. In the great majority of cases, the preserved vials are used to take advantage of the extended holding time. In some situations, however, it may be necessary to use the unpreserved vials. For example, if the groundwater has a high amount of dissolved limestone, i.e., is highly calcareous, there will most likely be an effervescent reaction between the hydrochloric acid and the water, producing large numbers of fine bubbles. This will render the sample unacceptable. In this case, unpreserved vials should be used and arrangements must be confirmed with the laboratory to ensure that they can accept the unpreserved vials and meet the shorter sample holding times.

The samples should be collected with as little agitation or disturbance as possible. The vial should be filled so that there is a meniscus at the top of the vial and absolutely no bubbles or headspace should be present in the vial after it is capped. After the cap is securely tightened, the vial should be inverted and tapped on the palm of one hand to see if any undetected bubbles are dislodged. If a bubble or bubbles are present, the vial should be topped off using a minimal amount of sample to re-establish the meniscus. Care should be taken not to flush any preservative out of the vial during topping off. If, after topping off and capping the vial, bubbles are still present, a new vial should be obtained and the sample re-collected.

Samples for VOC analysis must be collected using either stainless steel or Teflon® equipment, such as:

- Bailers must be constructed of stainless steel or Teflon®
- RediFlo2® submersible pumps used for sampling should be equipped with Teflon® sample delivery tubing
- Peristaltic pump/vacuum jug assemblies should be outfitted with Teflon® tubing from the water column to the transfer cap, which should also be constructed of Teflon®

2.2 Special Precautions for Trace Contaminant Groundwater Sampling

- A clean pair of new, non-powdered, disposable gloves will be worn each time a different location is sampled and the gloves should be donned immediately prior to sampling. The gloves should not come in contact with the media being sampled and should be changed any time during sample collection when their cleanliness is compromised.
- Sample containers for samples suspected of containing high concentrations of contaminants shall be stored separately.

- Sample collection activities shall proceed progressively from the least suspected contaminated area to the most suspected contaminated area if sampling devices are to be reused. Samples of waste or highly contaminated media must not be placed in the same ice chest as environmental (i.e., containing low contaminant levels) or background samples.
- If possible, one member of the field sampling team should take all the notes and photographs, fill out tags, etc., while the other members collect the samples.
- Clean plastic sheeting will be placed on the ground at each sample location to prevent or minimize contaminating sampling equipment by accidental contact with the ground surface.
- Samplers must use new, verified certified-clean disposable or non-disposable equipment cleaned according to procedures contained in SESD Operating Procedure for Field Equipment Cleaning and Decontamination (SESDPROC-205) or SESD Operating Procedure for Field Equipment Cleaning and Decontamination at the FEC (SESDPROC-206) for collection of samples for trace metals or organic compound analyses.

2.3 Sample Handling and Preservation Requirements

1. Groundwater samples will typically be collected from the discharge line of a pump or from a bailer, either from the pour stream of an up-turned bailer or from the stream from a bottom-emptying device. Efforts should be made to reduce the flow from either the pump discharge line or the bailer during sample collection to minimize sample agitation.
2. During sample collection, make sure that the pump discharge line or the bailer does not contact the sample container.
3. Place the sample into appropriate, labeled containers. Samples collected for VOC, acidity and alkalinity analysis must not have any headspace. All other sample containers must be filled with an allowance for ullage.
4. All samples requiring preservation must be preserved as soon as practically possible, ideally immediately at the time of sample collection. If preserved VOC vials are used, these will be preserved with concentrated hydrochloric acid by ASB personnel prior to departure for the field investigation. For all other chemical preservatives, SESD will use the appropriate chemical preservative generally stored in an individual single-use vial as described in the SESD Operating Procedure for Field Sampling Quality Control (SESDPROC-011). The adequacy of sample preservation will be checked after the addition of the preservative for all samples except for the samples collected for VOC analysis. If additional preservative is needed, it should be added to achieve adequate preservation. Preservation requirements for groundwater samples are found in the USEPA Region 4 Analytical Support Branch Laboratory Operations and Quality Assurance Manual (ASBLOQAM).

2.4 Quality Control

If possible, a control sample should be collected from a location not affected by the possible contaminants of concern and submitted with the other samples. This control sample should be collected as close to the sampled area as possible and from the same water-bearing formation. Equipment blanks should be collected if equipment is field cleaned and re-used on-site or if necessary to document that low-level contaminants were not introduced by pumps, bailers or other sampling equipment.

2.5 Records

Information generated or obtained by SESD personnel will be organized and accounted for in accordance with SESD records management procedures found in SESD Operating Procedure for Control of Records, SESDPROC-002. Field notes, recorded in a bound field logbook, will be generated, as well as chain-of-custody documentation in accordance with SESD Operating Procedure for Logbooks, SESDPROC-010 and SESD Procedure for Sample and Evidence Management, SESDPROC-005.

3 Groundwater Sampling Methods – Purging

3.1 General

Purging is the process of removing stagnant water from a well, immediately prior to sampling, causing its replacement by groundwater from the adjacent formation that is representative of actual aquifer conditions. In order to determine when a well has been adequately purged, field investigators should monitor, at a minimum, the pH, specific conductance and turbidity of the groundwater removed during purging and, in the case of permanent monitoring wells, observe and record the volume of water removed.

There are several purging strategies that may be used, depending on specific conditions encountered for given well sampling situations. When a specific well is characterized, based on the field investigators experience and knowledge, as having fairly typical water levels, depths and purge volumes, as determined according to the procedures in Section 3.2.1, below, SESD will normally use the multiple volume purging procedures and equipment described in Sections 3.2.1 and 3.3 of this procedure for purging the well.

When the traditional multiple volume purge method is considered and it is determined that excessive quantities of IDW would be generated using this method, it may be appropriate, under very limited and specific circumstances, to use an alternate method that reduces the time and amount of purge water to be removed prior to sampling the well. The field project leader will select the alternate method only after careful consideration of the conditions presented by the well and the impact these conditions have on all aspects of the sampling event (time required to sample, quantities of IDW requiring management, etc.).

The alternate purge procedures or sampling strategies available are the “Tubing-in-Screened Interval” method and the MicroPurge or No-Purge methods. These are described and discussed in Sections 3.2.2 and 4.5 of this operating procedure, respectively.

3.2 Purging Methods and Strategies

3.2.1 Traditional Multiple Volume Purge

3.2.1.1 Purging and Purge Adequacy

3.2.1.1.1 Purge Volume Determination

Prior to initiating the purge, the amount of water standing in the water column (water inside the well riser and screen) should be determined, if possible. To do this, the diameter of the well should be determined and the water level and total depth of the well should be measured and recorded. Specific methodology for obtaining these measurements is found in SESD Operating Procedure for Groundwater Level and Well Depth Measurement (SESDPROC-105).

Once this information is obtained, the volume of water to be purged can be determined using one of several methods. One is the equation:

$$V = 0.041 d^2h$$

Where: h = depth of water in feet

d = diameter of well in inches

V = volume of water in gallons

Alternatively, the volume of standing water in the well and the volume of three water columns may be determined using a casing volume per foot factor for the appropriate diameter well, similar to that in Table 3.2.1. The water level is subtracted from the total depth, providing the length of the water column. This length is multiplied by the appropriate factor in the Table 3.2.1, corresponding to either the single well volume or the triple well volume, to determine both the single well volume and triple well volumes, in gallons, for the well in question. Other acceptable methods include the use of nomographs or other equations or formulae.

TABLE 3.2.1: WELL CASING DIAMETER VOLUME FACTORS

Casing Diameter (inches)	Gallons/ft, One Water Column	Gallons/ft, Three Water Columns
1	0.04	0.12
2	0.16	0.48
3	0.37	1.11
4	0.65	1.98
5	1.02	3.06
6	1.47	4.41
7	1.99	5.97
8	2.61	7.83
9	3.30	9.90
10	4.08	12.24
11	4.93	14.79
12	5.87	17.61

With respect to volume, an adequate purge is normally achieved when three to five well volumes have been removed. The field notes should reflect the single well volume calculations or determinations, according to one of the above methods, and a reference to the appropriate

multiplication of that volume, i.e., a minimum three well volumes, clearly identified as a purge volume goal.

3.2.1.1.2 Chemical Parameter Stabilization Criteria

With respect to the ground water chemistry, an adequate purge is achieved when the pH and specific conductance of the ground water have stabilized and the turbidity has either stabilized or is below 10 Nephelometric Turbidity Units (NTUs) (twice the Primary Drinking Water Standard of 5 NTUs). Although 10 NTUs is normally considered the minimum goal for most ground water sampling objectives, lower turbidity has been shown to be easily achievable in most situations and reasonable attempts should be made to achieve these lower levels. (Note: Because groundwater temperature is subject to rapid changes when collected for parameter measurement, its usefulness is subject to question for the purpose of determining parameter stability. As such, it has been removed from the list of parameters used for stability determination. Even though temperature is not used to determine stability during well purging, it is still advisable to record the sample temperature, along with the other groundwater chemistry parameters during well purging, as it may be needed to interpret other chemical parameter results in some situations.)

Stabilization occurs when, for at least three consecutive measurements, the pH remains constant within 0.1 Standard Unit (SU) and specific conductance varies no more than approximately 5 percent. Other parameters, such as dissolved oxygen (DO), may also be used as a purge adequacy parameter. Normal goals for DO are 0.2 mg/L or 10% saturation, whichever is greater. DO measurements must be conducted using either a flow-through cell or an over-topping cell to minimize or reduce any oxygenation of the sample during measurement. Oxidation Reduction Potential (ORP) should not be used as a purge stabilization parameter but may be measured during purging to obtain the measurement of record for ORP for the sampling event.

There are no set criteria for establishing how many total sets of measurements are adequate to document stability of parameters. If the calculated purge volume is small, the measurements should be taken frequently enough to provide a sufficient number of measurements to evaluate stability. If the purge volume is large, measurements taken every 15 minutes, for example, may be sufficient. See the SESD Operating Procedures for Field pH Measurement (SESDPROC-100), Field Specific Conductance Measurement (SESDPROC-101), Field Temperature Measurement (SESDPROC-102), Field Turbidity Measurement (SESDPROC-103), Field Measurement of Dissolved Oxygen (SESDPROC-106) and Field Measurement of Oxidation-Reduction Potential (SESDPROC-113) for procedures for conducting these measurements.

If, after three well volumes have been removed, the chemical parameters have not stabilized according to the above criteria, additional well volumes (up to five well volumes), should be removed. If the parameters have not stabilized within five volumes, it is at the discretion of the project leader whether or not to collect a sample or to continue purging. If, after five well volumes, pH and conductivity have stabilized and the turbidity is still decreasing and approaching an acceptable level, additional purging should be considered to obtain the best sample possible, with respect to turbidity. The conditions of sampling should be noted in the field log.

3.2.1.1.3 Purge Adequacy Considerations

In some situations, even with slow purge rates, a well may be pumped or bailed dry (evacuated). In these situations, this generally constitutes an adequate purge and the well can be sampled following sufficient recovery (enough volume to allow filling of all sample containers). ***It is not necessary that the well be evacuated three times before it is sampled.*** The pH, specific conductance, temperature, and turbidity should be measured and recorded, during collection of the sample from the recovered volume, as the measurements of record for the sampling event.

For wells with slow recovery, attempts should be made to avoid purging them to dryness. This can be accomplished, for example, by slowing the purge rate. As water enters a well that has been purged to dryness, it may cascade down the sand pack and/or the well screen, stripping volatile organic constituents that may be present and/or introducing soil fines into the water column.

It is particularly important that wells be sampled as soon as possible after purging. If adequate volume is available immediately upon completion of purging, the well must be sampled immediately. If not, sampling should occur as soon as adequate volume has recovered. If possible, sampling of wells which have a slow recovery should be scheduled so that they can be purged and sampled in the same day, after adequate volume has recovered. Wells of this type should, unless it is unavoidable, not be purged at the end of one day and sampled the following day.

3.2.2 “Tubing-in-Screened-Interval” Method

The “Tubing-in-Screen” method, sometimes referred to as the “Low Flow” method, is used primarily when calculated purge volumes for the traditional purging method are excessive and present issues related to timely completion of the project and/or management of investigation derived waste.

3.2.2.1 Purge Criteria

3.2.2.1.1 Placement of Pump Tubing or Intake

The peristaltic pump tubing or intake point of the submersible pump is placed in the approximate mid-portion of the screened interval of the well. By definition, this method cannot be applied for purging with a bailer.

3.2.2.1.2 Conditions of Pumping

Prior to initiation of pumping, a properly decontaminated well sounder should be lowered into the well being sampled to monitor the static water level prior to and during the purging process. Ideally, there should be only a slight and stable drawdown of the water column after pumping begins. If this condition cannot be met, then one of the other methods should be employed.

3.2.2.1.3 Stability of Chemical Parameters

As with the traditional purging method described in Section 3.2.1, it is important that all chemical parameters be stable as defined in Section 3.2.1.1 prior to sampling.

3.3 Equipment Considerations for Purging

Monitoring well purging is accomplished by using in-place plumbing and dedicated pumps or by using portable pumps/equipment when dedicated systems are not present. The equipment utilized by Branch personnel will usually consist of peristaltic pumps and variable speed electric submersible pumps, but may also include bladder pumps or inertial pumps. The pump of choice is usually a function of the well diameter, the depth to water, the depth of the well and the amount of water that is to be removed during purging. Whenever the head difference between the sampling location and the water level is less than the limit of suction and the volume to be removed is reasonably small, a peristaltic pump should be used for purging. For wells where the water level is below the limit of suction (approximately 25' to 30', and/or where there is a large volume of water to be purged), the variable speed electric submersible pump would be the pump of choice. SESD Operating Procedure for Pump Operation (SESDPROC-203) contains the use and operating instructions for all pumps commonly used during SESD ground water investigations.

Bailers may also be used for purging in appropriate situations, however, their use is discouraged. Bailers tend to disturb any sediment that may be present in the well, creating or increasing sample turbidity. Bailers, if improperly used, may also strip volatile organic compounds from the water column being sampled. If a bailer is used, it should be a closed-top Teflon® bailer.

3.3.1 Wells Without Plumbing or In-Place Pumps

For permanent monitoring wells, the depth to water (water level) and depth of the well (total depth) should be determined before purging. Caution should be exercised during this procedure to prevent cross-contamination between wells. This is a critical concern when samples for trace organic compounds or metals analyses are collected. See SESD Operating Procedure for Field Equipment Cleaning and Decontamination (SESDPROC-205) for cleaning procedures for well sounders. After cleaning, the well sounding device should be protected to keep it clean until its next use.

3.3.1.1 Purging with Pumps

3.3.1.1.1 Peristaltic Pumps

The following step-by-step procedures describe the process of purging with a peristaltic pump:

1. Cut a length of standard-cleaned (SESD Operating Procedure for Field Equipment Cleaning and Decontamination at the FEC (SESDPROC-206)) Teflon® tubing, equal to the well depth plus an additional five to ten feet. Enough tubing is needed to run from the ground surface up to the top of the well casing and back down to the bottom of the well. This will allow for operation of the pump at all possible water level conditions in the well.
2. Place one end of the tubing into the vacuum side of the peristaltic pump head. Proper sizing of the Teflon® and Silastic® or Tygon® tubing should allow for a snug fit of the Teflon® tubing inside the flexible tubing mounted in the pump head.
3. Run a short section of tubing (does not have to be Teflon®) from the discharge side of the pump head to a graduated bucket.
4. Place the free end of the Teflon® tubing into the well until the end of the tubing is just below the surface of the water column.
5. Secure the Teflon® tubing to the well casing or other secure object using electrician's tape or other suitable means. This will prevent the tubing from being lost in the well should the tubing detach from the pump head.
6. Turn on the pump to produce a vacuum on the well side of the pump head and begin the purge. Observe pump direction to ensure that a vacuum is being applied to the purge line. If the purge line is being pressurized, either switch the tubing at the pump head or reverse the polarity of the cables on the pump or on the battery.

7. If the pumping rate exceeds the recovery rate of the well, continue to lower the tubing into the well, as needed, until the drawdown stabilizes or the well is evacuated to dryness. If the pump is a variable speed peristaltic pump, and the water level in the well is being drawn down, reduce the speed of the pump in an attempt to stabilize the drawdown. If the well can be purged without evacuating the well to dryness, a sample with greater integrity can be obtained.
8. For wells which are not evacuated to dryness, particularly those with recovery rates equal to or very nearly equal to the purge rate, there may not be a complete exchange and removal of stagnant water in that portion of the water column above the tubing intake. For this reason, it is important that the tubing intake be placed in the very uppermost portion of the water column while purging. Standard field measurements should frequently be taken during this process to verify adequacy of the purge and readiness for sampling, as described in Section 3.

3.3.1.1.2 Submersible Pumps

When a submersible pump is used for well purging, the pump itself is lowered into the water column. The pump must be cleaned as specified in SESD Operating Procedure for Field Equipment Cleaning and Decontamination (SESDPROC-205).

The pump/hose assembly used in purging should be lowered into the top of the standing water column and not deep into the column. This is done so that the purging will "pull" water from the formation into the screened area of the well and up through the casing so that the entire static volume can be removed. If the pump is placed deep into the water column, the water above the pump may not be removed, and the subsequent samples, particularly if collected with a bailer, may not be representative of the aquifer conditions. It is recommended that the pump not be lowered more than three to five feet into the water column. If the recovery rate of the well is faster than the pump rate and no observable draw down occurs, the pump should be raised until the intake is within one foot of the top of the water column for the duration of purging. If the pump rate exceeds the recovery rate of the well, the pump will have to be lowered, as needed, to accommodate the drawdown. After the pump is removed from the well, the hose and the pump should be cleaned as outlined in SESD Operating Procedure for Field Equipment Cleaning and Decontamination (SESDPROC-205).

3.3.1.2 Purging with Bailers

Standard-cleaned (SESD Operating Procedure for Field Equipment Cleaning and Decontamination (SESDPROC-205) or SESD Operating Procedure for Field Equipment Cleaning and Decontamination at the FEC (SESDPROC-206)), closed top Teflon® bailers with Teflon® coated stainless steel leaders and new nylon rope are lowered into the top of the water column, allowed to fill, and removed. It is critical that bailers be slowly and gently immersed into the top of the water column, particularly during final stages of purging, to minimize turbidity and disturbance of volatile organic constituents. The use of bailers for purging and sampling is discouraged because the correct technique is highly operator dependent and improper use may result in an unrepresentative sample.

3.3.2 Wells With In-Place Plumbing

Wells with in-place plumbing are commonly found at municipal water treatment plants, industrial water supplies, private residences, etc. Many permanent monitoring wells at active facilities are also equipped with dedicated, in-place pumps. The objective of purging wells with in-place pumps is the same as with monitoring wells without in-place pumps, i.e., to ultimately collect a ground water sample representative of aquifer conditions. Among the types of wells identified in this section, two different approaches are necessary.

A permanent monitoring well with an in-place pump should, in all respects, be treated like a monitoring well without a pump. One limitation is that in most cases the in-place pump is “hard” mounted, that is, the pump is suspended in the well at a pre-selected depth and cannot be moved up or down during purging and sampling. In these cases, well volumes are calculated, parameters are measured and the well is sampled from the pump discharge, after volume removal and parameter conditions have been met.

In the case of the other types of wells, i.e., municipal, industrial and residential supply wells, however, not enough is generally known about the construction aspects of the wells to apply the same criteria as used for monitoring wells, i.e., 3 to 5 well volumes. The volume to be purged in these situations, therefore, depends on several factors: whether the pumps are running continuously or intermittently and whether or not any storage/pressure tanks are located between the sampling point and the pump. The following considerations and procedures should be followed when purging wells with in-place plumbing under the conditions described.

3.3.2.1 Continuously Running Pumps

If the pump runs more or less continuously, no purge (other than opening a valve and allowing it to flush for a few minutes) is necessary. If a storage tank is present, a spigot, valve or other sampling point should be located between the

pump and the storage tank. If not, locate the valve closest to the tank. Measurements of pH, specific conductance, temperature, and turbidity are recorded at the time of sampling.

3.3.2.2 Intermittently or Infrequently Running Pumps

If the pump runs intermittently or infrequently, best judgment should be utilized to remove enough water from the plumbing to flush standing water from the piping and any storage tanks that might be present. Generally, under these conditions, 15 to 30 minutes will be adequate. Measurements of pH, specific conductance, temperature and turbidity should be made and recorded at intervals during the purge and the final measurements made at the time of sampling should be considered the measurements of record for the event.

3.3.3 Temporary Monitoring Wells

3.3.3.1 General Considerations

Procedures used to purge temporary ground water monitoring wells differ from permanent wells because temporary wells are installed for immediate sample acquisition. Wells of this type may include standard well screen and riser placed in boreholes created by hand augering, power augering, or by drilling. They may also consist of a rigid rod and screen that is pushed, driven, or hammered into place to the desired sampling interval, such as a direct push Wellpoint®, a Geoprobe® Screen Point 15/16 sampler or a Hydropunch® sampler. As such, the efforts to remove several volumes of water to replace stagnant water do not necessarily apply because stagnant water is not present. It is important to note, however, that the longer a temporary well is in place and not sampled, the more stagnant the water column becomes and the more appropriate it becomes to apply, to the extent possible, standard permanent monitoring well purging criteria to it to re-achieve aquifer conditions.

In cases where the temporary well is to be sampled immediately after installation, purging is conducted primarily to mitigate the impacts of installation. In most cases, temporary well installation procedures disturb the existing aquifer conditions, resulting primarily in increased turbidity. Therefore, the goal of purging is to reduce the turbidity and remove the volume of water in the area directly impacted by the installation procedure. Low turbidity conditions in these types of wells that are completed within the limit of suction are typically and routinely achieved by the use of low-flow/low stress purging techniques using variable speed peristaltic pumps.

3.3.3.2 Purging When Water Level Is Within Limit of Suction

In situations where the elevation of the top of the water column is within the limit of suction (no greater than about 25 feet head difference between the pump and the water level), a variable speed peristaltic pump may be used to purge

temporary wells. Enough tubing is deployed to reach the bottom of the temporary well screen. At the onset of purging, the tubing is slowly lowered to the bottom of the screen and is used to remove any formation material which may have entered the well screen during installation. This is critical to ensuring rapid achievement of low turbidity conditions. After the formation material is removed from the bottom of the screen, the tubing is slowly raised through the water column to near the top of the column. The tubing can be held at this level to determine if the pump rate is drawing down the water level in the well. If the water level remains the same, secure the tubing at the surface to maintain this pumping level.

If drawdown is observed on initiation of pumping, reduce the pump speed and attempt to match the drawdown of the well. Sustained pumping at these slow rates will usually result in a relatively clear, low turbidity sample. If the drawdown stabilizes, maintain that level, however, if it continues to lower, "chase" the water column until the well is evacuated. In this case, the recovered water column may be relatively free of turbidity and can be sampled. It may take several episodes of recovery to provide enough volume for a complete sample.

3.3.3.3 Purging When Water Level Is Greater Than Limit of Suction

In situations where the elevation of the water table is greater than the limit of suction, peristaltic pumps cannot be used to purge temporary wells. If the temporary well is a ScreenPoint15® sampler with small diameter probe rod riser, the only practical choices for water removal are a small diameter bailer, a small diameter bladder pump or an inertial pump. If the well is to be used strictly for VOC screening, it may be acceptable to use the bailer to bail as much sediment from the well as possible prior to sampling. If metals are the analytes of concern, the bladder pump is the best choice for lowering the turbidity of the water column prior to sampling, followed next by the inertial pump. For larger diameter temporary wells, two-inch diameter or greater, bailers and the Grundfos® RediFlo2 may be used although excessive silt or other "fines" may present problems with the operation of the pump.

3.3.3.4 Considerations for Direct Push Groundwater Sampling

With many of the direct push sampling techniques, purging is either not practical or possible, therefore, no purging is conducted. The sampling device is simply pushed or driven to the desired depth and opened and the sample is collected and retrieved. As a result, some samples collected in this way may not be satisfactory or acceptable for certain analyses, i.e., the subject procedure may yield a turbid sample that is not appropriate for metals analyses.

3.4 Field Care of Purging Equipment

New plastic sheeting should be placed on the ground surface around the well casing to prevent contamination of the pumps, hoses, ropes, etc., in the event they accidentally

come into contact with the ground surface or, for some reason, they need to be placed on the ground during the purging event. It is preferable that hoses used in purging that come into contact with the ground water be kept on a spool or contained in a large wash tub lined with plastic sheeting, both during transportation and during field use, to further minimize contamination by the transporting vehicle or the ground surface.

Careful consideration shall be given to using submersible pumps to purge wells which are excessively contaminated with oily compounds, because it may be difficult to adequately decontaminate severely contaminated pumps under field conditions. When wells of this type are encountered, alternative purging methods, such as bailers, should be considered.

3.5 Investigation Derived Waste

Purging generates quantities of purge water or investigation derived waste (IDW), the disposition of which must be considered. See SESD Operating Procedure for Management of Investigation Derived Waste (SESDPROC-202) for guidance on management or disposal of this waste.

4 Groundwater Sampling Methods – Sampling

4.1 General

Sampling is the process of obtaining, containerizing, and preserving (if required) a ground water sample after the purging process is complete. Non-dedicated pumps for sample collection generally should not be used. Many pumps are made of materials such as brass, plastic, rubber, or other elastomeric products which may cause chemical interferences with the sample. Their principle of operation may also render them unacceptable as a sample collection device. It is recognized that there are situations, such as industrial or municipal supply wells or private residential wells, where a well may be equipped with a dedicated pump from which a sample would not normally be collected. Discretion should always be used in obtaining a sample.

4.2 Sampling Wells With In-Place Plumbing

Samples should be collected following purging from a valve or cold water tap as near to the well as possible, preferably prior to any storage/pressure tanks or physical/chemical treatment system that might be present. Remove any hose that may be present before sample collection and reduce the flow to a low level to minimize sample disturbance, particularly with respect to volatile organic constituents. Samples should be collected directly into the appropriate containers as specified in the ASBLOQAM. It may be necessary to use a secondary container, such as a clean 8 oz. or similar size sample jar or a stainless steel scoop, to obtain and transfer samples from spigots with low ground clearance. Also, refer to the discussion in the SESD Operating Procedure for Potable Water Supply Sampling (SESDPROC-305), Sec. 4.2, Potable Water Samples Collected from Wells with In-Place Plumbing. Potable well measurements for pH, specific conductance and turbidity and possibly temperature, if warranted, should be recorded at the time of sample collection.

4.3 Sampling Wells Without Plumbing, Within the Limit of Suction

4.3.1 Equipment Available

The pump of choice for sampling ground water within the limit of suction is the variable-speed peristaltic pump. Its use is described in the following sections. Other acceptable alternatives that may be used under these conditions are the RediFlo2® electric submersible pump (with Teflon® tubing) and a closed-top Teflon® bailer.

4.3.1.1 Peristaltic Pump, Direct from Pump Head Tubing

Samples for some constituents, primarily inorganic analytes such as metals and cyanide, may be collected directly from the pump head tubing. This method is acceptable under the following conditions:

- The pump head tubing must be changed between sampling locations;

- The pump head tubing must be either be certified clean according to SESD's internal quality control program described in Section 3.2 of the SESD Operating Procedure for Field Sampling Quality Control (SESDPROC-011) or
- An equipment rinsate blank is collected by pumping de-ionized water through a piece of the tubing.

4.3.1.2 Peristaltic Pump/Vacuum jug

It is not acceptable to collect samples for organic compound analyses through the flexible tubing used in the pump head. When collecting samples for organic compound analyses it is necessary to use a vacuum container, placed between the pump and the well for sample collection. The following step-by-step procedures describe the process of sampling with a peristaltic pump and vacuum jug (see note following these procedures for collection of VOC samples):

1. Disconnect the purge tubing from the pump. Make sure the tubing is securely attached to the protective casing or other secure object.
2. Insert the tubing into one of the ferrule nut fittings of a Teflon® vacuum container transfer cap assembly.
3. Place a suitable length of Teflon® tubing between the remaining transfer cap assembly ferrule nut fitting and the vacuum side of the flexible tubing in the peristaltic pump head. Securely hand-tighten both fittings.
4. Turn the pump on. Water should begin to collect in the transfer container (typically a 1-liter sample container) within a few minutes. If water does not begin to flow into the container within several minutes, check the transfer cap fittings and make sure the assembly is tightly attached to the container. It may be necessary to tighten the ferrule nuts with a wrench or pliers to achieve a vacuum in the system, particularly when approaching the maximum head difference between the pump and water table (limit of suction).
5. When the transfer container is nearly full, turn off the pump, remove the transfer cap assembly, and pour the sample into the appropriate containers. Because the 1-liter containers used by the Branch are rinsed with nitric acid during cleaning, they cannot be used for collecting samples to be analyzed for nitrogen sensitive parameters.
6. If additional sample volume is needed, replace the transfer cap assembly, turn the pump on, and collect additional volume. The use of Teflon® valves or ball check devices to retain the water column in the sample delivery tubing during the transfer phase, when large volumes of sample are required, is acceptable. These devices, however, must be constructed so that they may be completely disassembled and cleaned according to the procedures in SESD

Operating Procedure for Field Equipment Cleaning and Decontamination (SESDPROC-205).

7. When sampling is completed, all Teflon® tubing should be discarded.

NOTE: Samples for volatile organic compound analyses cannot be collected using this method. If samples for VOC analyses are required, they must be collected with a Teflon® or stainless steel bailer or by other approved methods, such as the “soda straw” method. The “soda straw” method involves allowing the tubing to fill, by either lowering it into the water column (A) or by filling it via suction applied by the pump head (B). If method (A) is used, the tubing is removed from the well after filling and the captured sample is allowed to drain into the sample vial. If method (B) is used, after running the pump and filling the tubing with sample, the pump speed is reduced and the direction reversed to push the sample out of the tubing into the vials. Avoid completely emptying the tubing when filling the sample vials when using method (B) to prevent introducing water that was in contact with the flexible pump head tubing. Either method is repeated, as necessary, until all vials are filled.

4.3.1.3 RediFlo2® Electric Submersible Pump (with Teflon® Tubing)

After purging has been accomplished with RediFlo2® electric submersible pump, the sample may be obtained directly from the pump discharge, provided that Teflon® tubing was used for the sample delivery line. The discharge rate of the pump should be reduced during volatile organic compound sample collection to minimize sample disturbance. Note, if the RediFlo2® electric submersible pump is used for sampling, the pump must undergo a full external and internal cleaning. In addition, pump rinsate blanks must be collected, at the appropriate frequency, to demonstrate that the pump has been adequately cleaned between wells.

4.3.1.4 Bailers

New bailer rope should be attached to the bailer via a Teflon® coated stainless steel wire. (If a bailer was used to purge the well, it may also be used to sample the well and new bailer rope is not required between purging and sampling). The bailer should be gently immersed in the top of the water column until just filled. At this point, the bailer should be slowly removed and the contents emptied into the appropriate sample containers.

4.4 Sampling Wells without Plumbing, Exceeding the Limit of Suction

All methods described previously in Section 4.3.2.1.3, RediFlo2® Electric Submersible Pumps, and Section 4.3.2.1.4, Bailers, are suitable sample methods where the water table is too deep to consider the use of a peristaltic pump for sampling.

4.5 Micro-Purge or No Purge Sampling Procedures

The Micro-Purge or No Purge sampling procedures are usually employed when it necessary to keep purge volumes to an absolute minimum. Among the Micro-Purge or No Purge procedures that might be employed are:

- Low pump rate sampling with peristaltic or submersible pumps (typical Micro-Purge sampling),
- HydraSleeve™ or
- Passive diffusion bag (PDB) sampling

The use of these procedures is acceptable only when the site hydrogeology is well understood, with respect to the hydraulic conductivity of geologic materials within the well screen interval. The underlying assumption, when employing these procedures, is that the formation in which the well is screened has a high hydraulic conductivity ($K > 10^{-5}$ cm/sec, for example), resulting in a state of equilibrium existing between the water standing in the screened interval and the formation water in which the well is screened. In this situation, the well is considered to be in a perpetually “purged” state and purging is not required.

These procedures are generally impractical for SESD to implement because of the general lack of hydrogeologic information for the sampled wells and the real necessity, in some cases, that the pumps be pre-deployed to overcome issues related to turbidity resulting from pump placement prior to sampling.

4.5.1 Sampling with Pumps

The peristaltic pump tubing or intake point of the submersible pump is placed in the approximate mid-portion of the screened interval of the well or other interval selected by the field team leader. If turbidity and its impact on metals analyses are a concern, a period of time sufficient should be allowed to mitigate effects of pump or tubing placement. After it has been determined that sampling may proceed, the pump is turned on and operated at a rate that does not cause significant drawdown of the water column, as measured using a water level sounder. During sampling, sufficient water to supply enough volume for the analytes of concern and the purge parameters is pumped. Purging should continue until purge parameters stabilize, generally three consecutive stable sets of readings, before samples are collected.

4.5.2 HydraSleeves™

HydraSleeves™ are grab sampling devices that are deployed in a closed configuration then opened in the desired interval for sample collection. The following is a summary of its operation:

1. Sampler placement - Reusable weight is attached and the HydraSleeve™ is lowered and placed at the desired position in the well screen. In-situ water pressure keeps the reed valve closed, preventing water from entering the sampler. Well is allowed to return to equilibrium.

2. Sample collection - The reed valve opens to allow filling when the sampler is moved upward faster than 1 foot per second, either in one continuous upward pull or by cycling the sampler up and down to sample a shorter interval. There is no change in water level, and only minimal agitation during collection.
3. Sample retrieval - When the flexible sleeve is full, the reed valve closes and the sampler can be recovered without entry of extraneous overlying fluids. Samples are removed by puncturing the sleeve with the pointed discharge tube and draining the contents into containers for sampling or field measurement.

4.5.3 Passive Diffusion Bags

Passive diffusion bag (PDB) samplers are bags comprised of low-density polyethylene (LDPE) plastic and containing analyte-free water, preferably with no headspace. The bags are deployed, with stainless steel weights, to the desired sample interval and are allowed to equilibrate with the water at the point of deployment in the well. A deployment period of a minimum of 14 days is recommended to ensure equilibration prior to removal.

After 14 days, the bags are opened with a puncture device or other cutting implement and the contents transferred to containers for sampling or field measurement.

4.5.4 General Considerations for Micro-Purge or No-Purge Sampling

When using the Micro-Purge method, it may be advisable to deploy the tubing or pump in advance of sample collection. Introducing the tubing or pump into the screened interval is likely to dislodge sediment and other fines that have settled or bridged on the well screen material and the gravel pack media behind the screen. If sampling is conducted immediately, turbidity issues may render this method impractical from a parameter stability standpoint.

HydraSleeves™ and PDBs must be evaluated for appropriateness for analytes of concern.

4.6 Sample Preservation

After sample collection, all samples requiring preservation must be preserved as soon as practical. Consult the ASBLOQAM for the correct preservative for the particular analytes of interest. All samples preserved using a pH adjustment (except VOCs) must be checked, using pH strips, to ensure that they were adequately preserved. This is done by pouring a small volume of sample over the strip. Do not place the strip in the sample. Samples requiring reduced temperature storage should be placed on ice immediately.

4.7 Special Sample Collection Procedures

4.7.1 Trace Organic Compounds and Metals

Special sample handling procedures should be instituted when trace contaminant samples are being collected. All sampling equipment, including pumps, bailers, water level measurement equipment, etc., which comes into contact with the water in the well must be cleaned in accordance with the cleaning procedures described in the SESD Operating Procedure for Field Equipment Cleaning and Decontamination (SESDPROC-205) or SESD Operating Procedure for Field Equipment Cleaning and Decontamination at the FEC (SESDPROC-206). Pumps should not be used for sampling unless the interior and exterior portions of the pump and the discharge hoses are thoroughly cleaned. Blank samples should be collected to determine the adequacy of cleaning prior to collection of any sample using a pump other than a peristaltic pump.

4.7.2 Order of Sampling with Respect to Analytes

In many situations when sampling permanent or temporary monitoring wells, an adequate purge, with respect to turbidity, is often difficult to achieve. Removal and insertion of equipment after the purge and prior to actual sampling may negate the low turbidities achieved during purging and elevate turbidity back to unacceptable levels. For this reason, it is important that special efforts be used to minimize any disturbance of the water column after purging and to collect the aliquot for metals first. Therefore, the preferred order of sampling is metals first, followed by other inorganic analytes, extractable organic compounds and volatile organic compounds.

4.7.3 Filtering

As a standard practice, ground water samples will not be filtered for routine analysis. Filtering will usually only be performed to determine the fraction of major ions and trace metals passing the filter and used for flow system analysis and for the purpose of geochemical speciation modeling. Filtration is not allowed to correct for improperly designed or constructed monitoring wells, inappropriate sampling methods, or poor sampling technique.

When samples are collected for routine analyses and are filtered, both filtered and non-filtered samples will be submitted for analyses. Samples for organic compounds analysis should not be filtered. Prior to filtration of the ground water sample for any reason other than geochemical speciation modeling, the following criteria must be demonstrated to justify the use of filtered samples for inorganic analysis:

1. The monitoring wells, whether temporary or permanent, have been constructed and developed in accordance with the SESD Guidance Document, Design and Installation of Monitoring Wells (SESDGUID-001).

2. The ground water samples were collected using sampling techniques in accordance with this section, and the ground water samples were analyzed in accordance with USEPA approved methods.
3. Efforts have been undertaken to minimize any persistent sample turbidity problems. These efforts may consist of the following:
 - Redevelopment or re-installation of permanent ground water monitoring wells.
 - Implementation of low flow/low stress purging and sampling techniques.
4. Turbidity measurements should be taken during purging and sampling to demonstrate stabilization or lack thereof. These measurements should be documented in the field notes. If the ground water sample appears to have either a chemically-induced elevated turbidity, such as would occur with precipitate formation, or a naturally elevated colloid or fine, particulate-related turbidity, filtration will not be allowed.

If filtration is necessary for purposes of geochemical modeling or other **pre-approved** cases, the following procedures are suggested:

1. Accomplish in-line filtration through the use of disposable, high capacity filter cartridges (barrel-type) or membrane filters in an in-line filter apparatus. The high capacity, barrel-type filter is preferred due to the higher surface area associated with this configuration. If a membrane filter is utilized, a minimum diameter of 142 mm is suggested.
2. Use a 5 μm pore-size filter for the purpose of determining the colloidal constituent concentrations. A 0.1 μm pore-size filter should be used to remove most non-dissolved particles.
3. Rinse the cartridge or barrel-type filter with 500 milliliters of the solute (groundwater to be sampled) prior to collection of sample. If a membrane filter is used, rinse with 100 milliliters of solute prior to sample collection.

Potential differences could result from variations in filtration procedures used to process water samples for the determination of trace element concentrations. A number of factors associated with filtration can substantially alter "dissolved" trace element concentrations; these include filter pore size, filter type, filter diameter, filtration method, volume of sample processed, suspended sediment concentration, suspended sediment grain-size distribution, concentration of colloids and colloiddally-associated trace elements, and concentration of organic matter. Therefore, consistency is critical in the comparison of short-term and long-term results. Further guidance on filtration may be obtained from the following: 1) Metals in Ground Water: Sampling Artifacts and Reproducibility; 2) Filtration of Ground Water Samples for Metals Analysis; and 3) Ground Water Sampling - A Workshop Summary. See Section 1.4, References, for complete citation for these documents.

Bacterial Sampling

Whenever wells (normally potable wells) are sampled for bacteriological parameters, care must be taken to ensure the sterility of all sampling equipment and all other equipment entering the well. Further information regarding bacteriological sampling is available in the following: 1) Sampling for Organic Chemicals and Microorganisms in the Subsurface; 2) Handbook for Evaluating Water Bacteriological Laboratories; and 3) Microbiological Methods for Monitoring the Environment, Water and Wastes. See Section 1.4, References, for complete citation for these documents.

4.8 Specific Sampling Equipment Quality Assurance Techniques

All equipment used to collect ground water samples shall be cleaned as outlined in the SESD Operating Procedure for Field Equipment Cleaning and Decontamination (SESDPROC-205) or SESD Operating Procedure for Field Equipment Cleaning and Decontamination at the FEC (SESDPROC-206) and repaired, if necessary, before being stored at the conclusion of field studies. Cleaning procedures utilized in the field or field repairs shall be thoroughly documented in field records.

4.9 Auxiliary Data Collection

During ground water sample collection, it is important to record a variety of ground water related data. Included in the category of auxiliary data are water levels measured according to the SESD Operating Procedure for Groundwater Level and Well Depth Measurement (SESDPROC-105), well volume determinations (Section 3.1.1, Purging and Purge Adequacy), pumping rates during purging (see below), and occasionally, drillers or boring logs. This information should be documented in the field records.

4.9.1 Well Pumping Rate – Bucket/Stop Watch Method

The pumping rate for a pump can be determined by collecting the discharge from the pump in a bucket of known volume and timing how long it takes to fill the bucket. The pumping rate should be in gallons per minute. This method shall be used primarily with pumps with a constant pump rate, such as gasoline-powered or electric submersible pumps. Care should be taken when using this method with some battery-powered pumps. As the batteries' charge decreases, the pump rate also decreases so that pumping rate calculations using initial, high pump rates may be erroneously high. If this method is used with battery-powered pumps, the rate should be re-checked frequently to ensure accuracy of the pumping rate calculations.