NEW CHEMICALS ENVIRONMENTAL TECHNOLOGY INITIATIVE

CONTROL TECHNOLOGIES IN THE AUTOMATIVE REFINISHING INDUSTRY

DRAFT REPORT

Submitted to:

U.S. Environmental Protection Agency
Office of Pollution Prevention and Toxics
401 M Street, S.W.
Washington, D.C. 20460

Submitted by:

Science Applications International Corporation
11251 Roger Bacon Drive
Reston, Virginia 20190

August, 1996

EPA Contract No. 68-D2-0157
SAIC Project No. 01-0813-07-5367-000

CONTROL TECHNOLOGIES IN THE AUTOMATIVE REFINISHING INDUSTRY

Introduction

The objective of this report was to develop information on the innovative technologies and control methods used in automotive refinishing operations. This information will be used to prepare outreach materials for the subject industry. Technologies and control methods were evaluated on several merits such as minimizing worker exposure, controlling environmental releases, waste minimization, cost, and current industry use. The sections below detail information specific to background information, paint spray equipment, spray booths, low volatile organic compound (VOC) paint, computerized paint mixing, other related refinishing operations, and respirator protection. Summary tables have been included to summarize performance characteristics of both paint spray equipment and spray booths.

Background

Automotive refinishing includes operations in auto body repair/paint shops, production auto body paint shops, new car dealer repair/paint shops, fleet operator repair/paint shops, and custom-made car fabrication facilities. Refinishing work typically consists of structural repair, surface preparation and painting. Surface preparation includes grinding the paint off sheet metal, and applying, smoothing, shaping and sanding polyester resin body fillers. Painting involves matching paint colors, mixing paint formulations, and painting the repaired area using custom and conventional painting techniques. Workers involved in auto body repair, and refinishing can potentially be exposed to a wide range of air contaminants. During structural repair, activities such as sanding, grinding, and welding generate aerosols that are released into the worker's breathing zone. If the surface of the vehicle being repaired contains toxic metals such as lead, cadmium, or chromium, exposure to these metals is possible. Automobile painters can be exposed to organic solvents, hardeners that may contain isocyanate resins, and pigments that may contain toxic components. Within the automobile refinishing industry, the major air contaminant exposure appears to be to polyisocyanate (Heitbrink, 1995).

A range of control methods and technologies have been developed and are being widely used to control occupational exposures for spray painting in this industry. The most effective controls are engineering controls, particularly high volume low pressure spray guns and downdraft spray paint booths. New paint formulations have been developed to meet regulatory requirements in reducing solvent emissions in the industry. Other controls such as personal protective equipment including respiratory protection are also used to reduce employee exposures. The technologies and controls being used in the auto body refinishing industry are discussed in the following sections of this paper. This information can be used to prepare outreach materials and to try to leverage the available resources to improve the availability of these technologies.

Paint Spray Equipment

Spray painting in auto body shops is a manual process in which automotive painters use spray guns to apply successive coats of paint until the finish of the repaired sections of the vehicle matches that of the original undamaged portions. To speed drying between coats or for coatings which must be heated to cure, the painted vehicle surface is heated with heat lamps, in special infrared ovens, or in heated spray paint booths. After each coat of primer dries, the surface is sanded to remove any irregularities and to improve the adhesion of the next coat. Final sanding of primers may be done with a fine grade of sandpaper. A sealer is then applied and allowed to dry, followed by the final topcoat. When lacquer is used, the finished surface is usually polished after the final coat has dried, whereas enamel dries to a high gloss and is usually not polished.

Spray guns used in refinishing automobiles atomize paint with compressed air and project a paint mist onto the surface of the vehicle. The mechanism used in atomization and delivery of the paint directly affects the efficiency of the painting process. Transfer efficiency is the ratio of the amount of coating solids deposited onto the surface of the coated part to the total amount of coating solids that exit the spray gun nozzle. The waste paint directed outside the main spray pattern and not deposited onto the vehicle surface is referred to as overspray. In addition, atomized paint can be pulled away from the car surface by compressed air currents deflected by the car surface and the painting technician, and appears to "bounce back". The bounce back can account for 20% of the 60% of the paint which does not reach the car surface when conventional spray guns are used (Fettis, 1995).

Conventional Air Spray Guns

Conventional air spray guns have been the standard spray equipment used to apply coatings in the automotive refinishing industry. With this type of spray gun, a low volume (2 to 10 cfm) of air is pressurized and forced through a nozzle; the paint or coating is atomized in the air at the nozzle throat. Conventional spray guns are usually operated with air pressures of 30 to 90 pounds per square inch (psi) at a fluid pressure of 10 to 20 psi. Air is supplied by an air compressor during spraying operations. There are two basic types of conventional spray guns: syphon-feed and gravity feed. In syphon-feed guns the paint cup is attached below the spray gun, and the rapid flow of air through the gun creates a vacuum that siphons the coating out of the cup. Gravity-feed guns, have the paint cup above the gun and require less air pressure to move the coating through the gun (USEPA, 1994; Schrantz, 1992). The advantage of conventional spray guns is their capability to achieve very fine atomization. The disadvantages of this equipment is that it develops excessive spray mist and overspray fog. Conventional spray guns equipment has a transfer efficiency in the range of 20% to 40%, and therefore most of the paint becomes an overspray that may contaminate the air in the worker's breathing zone (Heitbrink, 1996).

High Volume Low Pressure Spray Guns

High Volume Low Pressure (HVLP) spray guns are systems which use a high volume (30 cfm to 200 cfm) of low pressure (pressure at the gun of between 0.1 and 10.0 psi) and at a fluid pressure of 50.0 psi. The lower velocity of the atomizing air stream results in a more controlled spray pattern, less bounce back, and enhanced transfer efficiency. HVLP guns are estimated to have a transfer efficiency of at least 65% (Heitbrink, 1996). Some disadvantages to this equipment are higher initial cost, inability to atomize coatings as finely as can be achieved with conventional spray guns, slower application speed, and the need for operator training. Conventional spray guns cost up to $350 while HVLP guns cost from $500 to $1000 (Brown, 1996). HVLP guns can be used with some existing air compressors, however capital costs for HVLP systems including compressors are about $1,000 to $22,000 (CARB, 1991). HVLP technology has become commonplace in auto body stops because of reduced paint usage and acceptable finish quality provided by the guns on the market (BAAQMD, 1995). In 1995, approximately 64% of U.S. auto body shops reported owning HVLP equipment. Approximately 49% of small auto body shops (<$124,999 annual sales) and approximately 68% of very large (>$1 million annual sales) owned HVLP spray painting equipment. In 1995, approximately 12% of auto body shops surveyed planned to purchase HVLP spray equipment (BSB, 1995).

Testing conducted by the National Institute for Occupational Safety and Health (NIOSH) in an equipment manufacturer's test facility, demonstrated that particulate overspray concentration was reduced by a factor of 2, and there was a 30% increase in the ratio of paint film thickness to mass of paint applied when a HVLP spray gun was used. These results indicate that using an HVLP spray-painting gun can reduce paint usage and overspray production, resulting in noticeably lower worker exposures (Heitbrink, 1996).

Low Volume Low Pressure Spray Guns

Other guns used in the industry include low volume, low pressure (LVLP) guns. LVLP spray guns, like HVLP guns atomize coatings at lower velocity (9.5 to 10 psi) and lower velocity than conventional spray guns but use an approximately 45 to 60 percent smaller volume of air than HVLP guns. Energy costs for air compression are reported to be less than with HVLP guns (USEPA, 1994).

Electrostatic Spray Guns

Electrostatic spraying systems, which have deposition efficiencies of between 60% and 90% are widely used in U.S. automotive assembly plants. Electrostatic spray systems are typically pressure-feed. A large amount of coating is contained in the hose that connects the spray guns to be paint pot, and the paint must be removed before the next coating can be applied with the spray gun. Because of this design and the prohibitively high cost of electrostatic spray systems, this type of equipment is impractical for the automotive refinishing

industry. However, high technology manufacturing processes utilizing electrostatic spray painting equipment and robotics have eliminated or greatly reduced potential occupational exposures during spray application of OEM coating systems (USEPA, 1994).

Powder Coating Systems

Air-powered, electrostatic spray guns function in essentially the same way as electrostatic spray guns. Compressed air propels the power from the gun to the part. An electric field is generated between the spray gun and the workpiece. Powder is passing through the electric field picks up the charge and is directed by the field. When the operator moves the gun, the charged particles follow as they are carried forward by compressed air. When the powder particle strikes the oppositely charged workpiece, the charged particle adheres. Powder is delivered to the spray gun by compressed air. Typically, transfer efficiencies for powder spray guns are similar to wet paint spray guns. However, powder overspray can be reused, and powder systems can therefore operate with powder utilization rates of up to 98%. After the powder is applied, the workpiece must be cured in a curing oven.

Table 6 summarizes the information discussed on paint spray equipment.

Table 6

COMPARISON OF CHARACTERISTICS OF PAINT SPRAY EQUIPMENT FOR AUTOMOTIVE REFINISHERS

Type of Painting System	Performance Characteristics		System Transfer Efficiency (%)	Cost Range ($)	Population of Shops Using Equipment
	Advantages	Disadvantages			
Conventional	Low cost Low maintenance Excellent material atomization Excellent operator control Quick color change capabilities Coating can be applied by syphon or under pressure	Uses high volume of air Develops excessive spray dust and overspray fog Does not adapt to high volume material output (economies of scale) Low transfer efficiency Pressure fed systems require high volumes of coatings	20 to 40	up to 350	Specific population data is unknown. Some states have mandated the use of HVLP systems by automotive refinishers.
High Volume Low Pressure	Low blowback and spray fog Will apply high-viscosity high solid coatings (low VOC coatings) Relatively easy to clean Can be used for intricate parts Good operator controls	High initial cost Slower application speed with some coatings Does not fully atomize some coatings Higher maintenance costs Requires operator training Still relatively new to the market	at least 65	500-1000	64% of all shops

F28

Table 6 (Cont'd)

COMPARISON OF CHARACTERISTICS OF PAINT SPRAY EQUIPMENT FOR AUTOMOTIVE REFINISHERS

Type of Painting System	Performance Characteristics		System Transfer Efficiency (%)	Cost Range ($)	Population of Shops Using Equipment
	Advantages	Disadvantages			
Low Volume Low Pressure	Low blowback and spray fog Will apply high-viscosity high solid coatings Easy to clean Can be used for intricate parts Good operator controls Needs less air compression then HVLP Lower energy requirements	High initial cost Slower application speed than HVLP Does not fully atomize some coatings Higher maintenance costs Requires operator training Still relatively new to the market	at least 65	500-1000	Population data is unknown
Electrostatic	Coating wrap on edges and parts Material savings through superior transfer High production output ideally adapts to automation Reduced manpower requirements Lower spray booth velocity Can be used with both solvent and water based coatings Can be used with a wide range of application processes	High equipment and maintenance costs Parts hangers hooks must be conductive and require frequent cleaning Automated lines must be adapted to long runs of similarly shaped parts Will not properly coat recessed areas Faraday Cage affects coating of corners, cavities, etc Electrical shock hazard Operator training is required	usually greater than 90	Unknown	Population data is unknown Electrostatic systems are more appropriate for OEM operations

Table 6 (Cont'd)

COMPARISON OF CHARACTERISTICS OF PAINT SPRAY EQUIPMENT FOR AUTOMOTIVE REFINISHERS

Type of Painting System	Performance Characteristics		System Transfer Efficiency (%)	Cost Range ($)	Population of Shops Using Equipment
	Advantages	Disadvantages			
Powder Coating	Almost zero VOC emissions Excess or waste powder can often be melted Powder can be applied to hot or cold parts Ideal for robotic application Applied in single coat system Economical for long runs of a few colors	Generally, capital equipment outlay is greater than for conventional coatings High energy usage due to high temperature ovens Some powders require temperatures as high as 500°F for curing Not suited for every application (parts that can not high temperature plastics, rubber, upholstery	Up to 95	5000-100000	Population data is unknown Powder coating systems are used primarily in OEM operations.

Sources: EPA, 1994 and BSB, 1995

F30

Spray Booths

Automobile spray painting operations produce aerosols containing droplets and solvent vapors to which workers may be exposed. Spray booths, which are power-ventilated structures enclosing a spraying operation, can confine and limit the escape of spray, vapor, and residue, and safely conduct or direct overspray and vapors to an exhaust system. Automobile painting activities are usually performed inside a spray booth to ensure good finish, to reduce employee exposures to inhalation of solvent vapors and paint solids, and to reduce the hazards of fire and explosion arising from components used in paints and varnishes (Goyer, 1995). After painting, spray booths are used for ambient air drying or for drying at elevated temperatures. Evaluations of controls in the auto body refinishing industry, conducted by NIOSH, indicate that currently available spray-painting booths do not completely control worker exposure to paint overspray (Heitbrink, 1995).

Dry-type booths use filters to intercept and trap particles of overspray while water-wash booths use a flow of water over a solid surface to accomplish the same thing. Filters become clogged over time and must be replaced or the volume of air exhausted through the booth will diminish to the point where excessive amounts of overspray and solvent vapor or both reach the breathing zone of the worker and/or escape from the booth. Dry filters are commonly used for low to intermediate volume spray operations. (NFPA, 1981) Waterwash booths are spray booths equipped with a water-washing system designed to minimize concentrations of dusts or residues entering exhaust ducts and to permit the collection of dusts or residues. Where high volume spray coating operations are conducted for several hours a day, waterfall or cascade scrubbers are commonly used (NFPA, 1981). Either type can be used successfully in almost all applications, however in general dry-type booths are most often used in automotive refinishing shops. Water-wash booths are rarely used in auto body refinishing shops (Garcia, 1996).

Many spray-painting booths of the type used in the automobile refinishing industry have a painting cycle and a curing cycle. These booths are equipped with supply air fans and exhaust air fans. The supply air fan moves air from outside the shop through a heat exchanger or natural gas burners, through a bank of filters, and into the spray painting booth. The exhaust air moves out of the booth through filters and out of the building (Heitbrink, 1995). Many spray booths have painting and curing cycles. To cure paint and polyisocyanate hardeners, the booths are operated at temperatures as high as 79° C (175° F), although curing temperatures are typically 49°C to 60° C (120° to 140°F). Purchase costs of small basic spray paint booths range from $5,400 to $23,000 (Spray Systems, 1996). A medium-size repair shop in Maryland installed two booths in 1992 for a total cost of approximately $400,000. The purchase cost of each booth was approximately $60,000 but the installation of these booths required extensive foundation construction costs to accommodate the ventilation system for the booths (CCC, 1996).

Three types of commercially available spray-painting booths found in auto body shops include downdraft, semi-downdraft, and crossdraft spray painting booths. The characteristics of these booths are discussed in the following sections.

Crossdraft Spray Booths

In a crossdraft booth, the air enters through filters in the front of the booth and is exhausted through filters in the back of the booth (Heitbrink, 1995). Approximately 50% of U.S. auto body shops have cross draft booths. An industry profile study, which provides data for 1995, indicates that approximately 42% of small(<$124,999 annual sales) auto body shops had downdraft spray booths and approximately 25% of very large firms (>$1 million annual sales) owned cross draft spray booths (BSB, 1995).

Downdraft Spray Booths

Downdraft spray-painting booths are designed so air enters through filters in the ceiling of the booth and leaves through a metal grate in the floor of the book. In most U.S. automotive assembly plants, painting is done in a downdraft paint spray booth. During the painting process, conditioned ambient air is introduced to the paint spray booth through the roof. The air and paint pass downward over the parts to be painted. The paint overspray and solvent fumes exit with the exhaust air from the painting area through grates on the floor (Eklund, 1995).

Approximately 30% of U.S. auto body shops in 1995 reported having downdraft spray-painting booths, including approximately 8% of very small firms and 83% of very large shops. Approximately 19% of auto body shops planned to purchase downdraft booths (BSB, 1995).

Semi-Downdraft Spray Booths

In a semi-downdraft booth, air enters through filters in the ceiling of the booth and is exhausted through filters in the back of the booth. During the painting process, conditioned ambient air is introduced to the paint spray booth through the roof. The air and paint pass down and across over the parts to be painted. The paint overspray and solvent fumes exit with the exhaust air from the painting area through openings usually on a side of the booth (EPA, 1994).

Approximately 30% of U.S. auto body shops in 1995 reported having downdraft spray-painting booths, including approximately 8% of very small firms and 83% of very large shops. Approximately 19% of auto body shops planned to purchase downdraft booths (BSB, 1995). The BSB industry profile did not specify if the downdraft spray paint booth data represented semi-downdraft models.

Table 7 summarizes the information presented above on spray booths.

Table 7

COMPARISON OF CHARACTERISTICS OF PAINT SPRAY BOOTHS

Paint Booth System	Performance Characteristics [1]		Cost Range[2]	Population of Shops Using Equipment [3]
	Functional Advantages	Disadvantages		
Downdraft	State of the Art worker protection Air movement - enters the booth through the ceiling and passes out the floor of the unit Lowest air turbulence of the three systems available Best system for preventing paint deformities	May cost more than other systems May require extensive renovation at existing facilities Operator training necessary Extra energy needed for heated systems	$12,000-$60,000	30% of all body shops use downdraft or semi-downdraft paint booth systems Most common paint booth system in shops with sales greater than $750,000 annually
Semi-Downdraft	Low air turbulence Air movement - enters the booth through the ceiling and passes out the back of the unit Installation may not require as much site renovation as downdraft	More air turbulence than downdraft May require extensive construction at existing facilities Operator training necessary Extra energy needed for heated systems	$10,000-$23,000	30% of all body shops use downdraft or semi-downdraft paint booth systems Most common paint booth system in shops with sales greater than $750,000 annually
Crossdraft	Most affordable system Air movement - enters the booth through one side and passes out the other Installation may not require as much site renovation as semi-downdraft or downdraft	Highest air turbulence of three available models Least effective model for preventing paint deformities Operator safety Extra energy needed for heated systems	$5,500-$23,000	50% of all body shops have a cross draft paint booth system Most common paint booth in body shops with sales less than $750,000 annually

Sources: 1 - EPA, 1994, 2 - Spray Systems and CCC, 1996, 3 - BSB, 1995)

Low VOC Coatings

This section of the report will detail the types of coatings used by auto body refinishers, the difference between OEM and refinisher coatings, some state regulatory trends for auto body refinishers, and alternative low volatile organic compound (VOC) coatings available. Low VOC coatings have two distinct advantages when compared to higher VOC coatings. These two advantages are reduced occupational exposures to and environmental releases of VOCs.

Conventional coatings are typically made up of three major components; a pigment for color, a polymer that acts as binder, and a liquid carrier-generally a solvent. In some coating formulations the solvent portion can account for two-thirds of the coating. VOCs are solvents that evaporate or volatilize during the painting process. Examples are thinners, reducers and cleaning solvents. Mixed in coatings, solvents provide proper viscosity, flow, and drying characteristics. For the automotive refinishing industry the paints can be set into distinct groups including primers, sealers, precoats, pretreatments, and specialty coatings.

Primers are base coats, sealers, or interim coats which are applied prior to colorant or aesthetics coats. In most cases, the primer is the most important coat upon which the remaining coats will adhere. Sealers are coatings that are formulated with resins, which when dried, are not readily soluble in solvents. These coats act as a shield for primers by resisting the penetration of solvents which are in the topcoat.

Automotive Precoats are any coating that is applied to bare metal to deactivate the metal surface for corrosion resistance to a subsequent water-based primer. This coating is applied to bare metal solely for the prevention of flash rusting caused by the water in water-based primers. Automotive pretreatments are any coating which contains a minimum of 0.5% acid by weight that is applied directly to bare metal surfaces to etch the metal surface for corrosion resistance and primer adhesion. Specialty coatings include coatings which are used to perform unusual job requirements such as helping to prevent surface defects and improve desired coating properties. Examples include coatings for plastic parts, anti-glare coatings, and gloss flatteners (Kirk-Othmer, 1992 and TNRCC, 1995).

The spray coatings applied by body shops differ from those applied by original equipment manufacturer's (OEM's). OEM facilities use coatings that require temperatures up to 400°F (204°C) to cure the coating. This is possible because no temperature-sensitive materials have yet been installed in the automobile. Body shops, on the other hand, must use coatings that cure at temperatures less than 150°F (66°C) to avoid damaging the vehicle's upholstery, glass, wiring or plastic components.

A driving force behind the automotive refinishing industry converting to the use of low VOC coatings has been the introduction of state regulatory requirements reducing the amount of VOCs in paints. Some states have regulated the auto body refinishing industry

while others have not, so information is not representative. States like Texas, California, and Maryland have taken initiatives to require automotive refinishers to register for air permits and adopt new technologies within industry. Texas, for example, has specific guidelines established for the auto body coating industry. Table 8 details Texas VOC guidelines for coatings used in the auto body refinishing industry.

Table 8

TEXAS VOC GUIDELINES FOR COATINGS USED IN AUTOMOTIVE REFINISHING

Coating Type	VOC Allowance (Pounds/gallon) minus water and exempt solvents
Primers	5.0
Precoats	5.5
Pretreatment	6.5
Basecoat/Clearcoat	5.0
Specialty Coating	7.0
Sealers	6.0

(TNRCC, 1995)

The California Air Resources Board (CARB) has been developing low VOC coatings since the late 1980's. In 1989, California issued several rules which required coating manufactures to produce coatings with little or no VOCs. At that time however, industry was not effective in creating the new compounds to meet the required deadlines. Revisions to the regulations were made and consequently, today there are several paint vendors in California that offer a variety of low and no VOC coatings. In 1992, additional regulations were issued requiring auto body shops in most CARB districts to incorporate the low VOC coatings. CARB will be completing a comprehensive survey of the auto body industry in California in May of 1996. The data will be used to develop generic chemical formulations for different categories of automotive coatings. These generic formulation will be used to track and evaluate emissions from auto body shops state wide (Watkins, 1996).

The cost for low VOC coatings are slightly higher because of their higher solids content. Costs of paint can range significantly and are influenced by a number of factors. These can include percent solids in the paint mixture, coverage, or required coating thickness.

Base coats can range from $13 to $35 per pint. Clearcoats can range from $100 to $175 per gallon, and primers can range from $75 to $150 per gallon (Brown, 1996).

One manufacturer has developed a coating which utilizes low molecular weight volatile dimethysiloxanes as solvents in protective paint systems. The manufacturer claims that the product's lifetime in the atmosphere is 10 to 30 days, so there will be little chance of reactions with nitrous oxide and affecting the ozone. The new paint formulation can reduce VOCs by about ½ a lb /gal in some cases (Anon., 1995). Two other manufacturers, located in Rockville, Maryland and Exto, Pennsylvania, respectively, have teamed up to develop a new class of ultraviolet-cure coatings that requires no photo initiators. The manufacturers claim that these new coatings will be low cost alternatives for several large markets including the automotive market. The coatings polymerize in the presences of UV-light (Paint and Powder, 1996).

An example of new waterborne coatings applications includes a waterborne acrylic wash primer with a VOC content of 1.26 lbs/gallon. The wash can be used to wash and prime a variety of steel surfaces. The primer sets rapidly and reportedly is tack free after 15 minutes (Paint and Powder 1996). Current applicability of this material to the automotive refinishing industry is unknown.

Waterborne basecoats and primers have been developed and are currently being used at the OEM facilities. Many OEM facilities have switched to waterborne basecoats and primers to improve leveling and metallic/mica flake. One manufacturer has approximately 70% of the waterborne basecoat market.

Significant advances have been made in clearcoat chemistry. Clearcoats are specialty top coats and are used to provide improved gloss, durability and overall appearance to the basecoat. The ideal clearcoat will be able to resist environmental fallout (acid rain, bird droppings, and soot) for ten years and have VOC range comparable to waterborne primers and basecoats below 3.0 lbs per gallon VOC. (Anon., 1991a)

Computerized Mixing of Paints

During manual mixing operations to formulate a desired coating, workers and the environment may be exposed to the chemical constituents which make up the coatings. Most coatings are mixed with additional solvents and catalysts prior to application to ensure proper drying time, adhesion, appearance, and color-match. Topcoats in particular must be exactly mixed according to the manufacturer's instructions because even a slight deviation may result in unacceptable finish quality. The automobile refinishing industry is very concerned with color control. Of all appearance variables, color is the most noticeable, and, therefore extremely important. If a customer sees a subtle color variance in a repaired component of a vehicle, then this is perceived as poor quality.

Aside from offering precise formulations for coating, computerized mixing can decrease worker exposures, reduce environmental emissions, and minimize waste.

New car manufacturers (OEMs) are now using computerized equipment in an effort to standardize colors used in automotive finishing. One such system employing a spectrophotometer, operates by measuring the "reflectance of light beamed at a color sample placed in a measurement port" (Mueller, 1988). By adding the speed and accuracy of a computer to the color measurement instrument, formulas can be generated to match the target color. This formula specifies the mix of colorants, the closeness of the match, and the costs associated with producing the color formula. But the one drawback of this equipment is that "both finisher and coatings manufacturer must use the same color measurement scale" (Mueller, 1988). Currently, there are a number of color scales being used in the industry.

Another piece of equipment which has taken the number of scales currently on the market into consideration uses a spectrocolorimeter. It measures "light reflectance according to color and appearance" (Anon., 1988). It is used in measuring values of color standards, trouble-shooting finishing problems, and inspecting the final product prior to shipment. The system can calculate various color scales under a broad set of conditions and replicate measurements under different light sources. Although the readings are still adjusted by a technician for metamerism (the visual differences due to lighting variances), the system has the ability to include the observer and light source data into its final computations.

A paint manufacturer's representative indicated he was aware of two systems that the paint manufacturers used to help determine colors. The instruments are referred to as spectra-photometers. The first system uses light from a halogen bulb to detect the color scheme. The system can match colors to a 16 color spectrum wavelength. The other system uses light from a xenon bulb to detect the color scheme. This system can match colors to a 256 color spectrum wavelength. The representative stated that these instruments work better in theory than in the field, and that color flop (mica content and flatness) can drastically reduce the instruments effectiveness at creating correct color match. Not many shops have invested in these instruments because of the cost, which is above $20,000 per unit, and the lack of effectiveness (Brown, 1996).

Many shops order topcoats to match the automobile being refinished from local automotive paint distributors. Others mix their own colors using mixing stations. A mixing station typical consists of a microfiche viewer or a computer that contains the manufacturer's mixing instructions, a digital scale, and a mixing machine. Shops that use mixing stations typically stock only a few primary colors, from which almost any OEM color can be produced (USEPA, 1994).

A manufacturer developed a system that can be used in tinting paint. A carousel is provided that carries 80 different tints and a set of microfiche that provides the formulas. Once the correct car model and color are found, the necessary ingredients are added precisely by weight and proper amounts of hardener and reducer are added (Anon., 1986).

A shop visited for this project did not have any computerized mixing system on site, but relies on OEM paint codes, which are found on every model car, and then hand mixes the colors to match as closely as possible. True color matching is difficult, if not impossible and often auto body shops do what is known as blending. Blending is done when slight differences exist in colors and the painter covers area of the vehicle that may not need repainting in order to hide the color change. This allows the color difference to be spread out over a larger surface thus creating the illusion that the colors are the same (CCC, 1996).

Other Related Operations

Preparation Stations

Preparation of the surface for painting and application of primers or small spot painting is conducted in open areas of the body shops; however, in some shops these steps are performed in preparation stations. Preparation stations typically are ventilated and equipped with plastic curtains to control dust and coating overspray. Unlike spray-painting booths, preparation stations do not have walls and may involve recycled air. A study of engineering controls in auto body shops indicated that preparation stations evaluated did not appear to control worker exposure to air contaminants (Heitbrink, 1995). Many shops and preparation stations are equipped with portable infrared heating units to facilitate drying of primers during cool or humid shop conditions (USEPA, 1994 and Heitbrink 1995). In 1995, approximately 16% of U.S. auto body shops reported owning preparation stations, including approximately 7% of very small and 25% of very large shops. Approximately 19% of U.S. auto body shops planned to purchase preparation stations (BSB, 1995).

Local Exhaust Ventilation Systems

Rotary/orbital and straight line/reciprocating sanders are used during auto body repair operations to remove paint and to smooth body panels repaired with body filling compounds. Airborne dusts produced during these operations may contain a variety of hazardous substances including metal dusts, paint dusts, and abrasives from sanding media. Local exhaust ventilation for sanders, including High Velocity, Low Volume (HVLV) have been found to be effective in reducing total dust concentrations to one-tenth levels produced using unventilated sanders (NIOSH, 1996).

Respiratory Protection

Because potential occupational exposures can exceed OSHA PELs during spray painting operations, respiratory protection is normally required for spray operations. Many types of respirators are available for such operations. If properly selected and used respirators can reduce worker exposure significantly. However, data from a NIOSH study indicates that respirator usage at five of six auto body repair shops evaluated was inappropriate. (Heitbrink, 1996) The author reported that, respirators were in poor shape and not maintained properly. All of the shops included in the study were lacking a formal, written respiratory program. An Australian auto body study indicated that only 32% of the auto body repair workers had half-facepiece air purifying respirators that did not leak. (Heitbrink, 1996). As expected, surveys have found that breathing resistance and physical discomfort, such as pressure on the face and head, sweat on the face, and tightness of harness are often cited as the main reasons workers do not use respirators or use them properly. A trend toward increased use of airline respirators in the auto body repair shops has been reported (Janko, 1992). This type of respirators typically causes less physical discomfort and should offer better protection.

ATTACHMENT A

SITE VISIT REPORT

ATTACHMENTS A
Site Visit
Chevy Chase Chevrolet-Geo-Oldsmobile
7725 Wisconsin Ave.
Bethesda, Md 29814
April 26, 1996

On April 26, 1996, SAIC conducted a site visit to Chevy Chase Chevrolet-Geo-Oldsmobile. The facility is located directly off Wisconsin Ave two blocks north of East West Highway in Bethesda, Maryland. It is a new/used/auto body repair shop/ dealership that has been in the area for over 50 years. The auto body repair shop is located in the rear of the new car dealership and is split into several distinct areas. The purpose of the site visit was to gather information specifically concerning the painting and refinishing operations.

Information was obtained related to spray booths at the facility. The auto body shop has two floor drawing heated paint booths. Each spray booth is equipped with a separate air supply system for the painter and for overspray recovery. Outside air is drawn in from a vent on the west side of each booth. Air passes through heating coils and a series of filter and enters the paint booth at the ceiling level. The inside air is drawn toward the floor via a fan and is vented to an exhaust duct located outside and above the paint booth. Cars are driven into the booth and the garage door is lowered. The painters dons an air supplied protective hood and plastic like coveralls and begins painting. After the painting is completed the painter exits the booth and the coating is heated to 140-150° F and allowed to dry. Drying time varies from coating to coating, but on average the new low VOC coatings take anywhere from about 20 to 40 minutes to dry.

This shop had these booths installed three years ago at a cost of approximately $400,000. Each booth cost approximately $60,000 and the installation of these booths required extensive foundation construction due to the nature of the booth (Floor draw). The manager indicated the facility would install a third booth sometime in the future.

The manager also indicated that the booths use quite a bit of natural gas to maintain the curing heat at 140-150° F. All supplied air was drawn from the outside.

HVLP Spray Guns

This shop had 6 different models of HVLP spray guns. The manager confirmed that paint spray efficiency had increased to almost a 70% transfer rate, although some of the new low VOC paint formulations would not spray as well as some of the older lacquer paints. The high solid, low VOC paints often required more than 10 PSI nozzle pressure to atomize. A paint manufacture's vendor indicated that HVLP technology has come a long way in the last three years. He said that he could line up 6 HVLP guns, all with similar ratings and supply 40 PSI into each gun, but the nozzle spray would not be uniform. Often the output would range from 6 - 10

PSI. The representative indicated that true atomization of low VOC paint formulations often occurs at nozzle pressures higher than 10 PSI.

A closed container HVLP gun cleaner was seen on site. Both the shop manager and the paint vendor indicated that this equipment was purchased in response to a new regulation in Maryland.

LOW VOC Paint

Maryland State regulations concerning the use of low VOC paint began on April 15, 1996. These new regulations limited the types of paints shops like this can use. Specific VOC concentrations are spelled out for specific types of paint. The vendor indicated that there is a trend toward the use of low VOC paints. He stated that the new paints are not as easy to apply and have a slower drying time than some of the older lacquer paints. Many of the older paints have been regulated and cannot be used in Maryland.

The paint vendor stated that he would like to see uniform VOC regulations. At this time state regulation vary significantly and paint manufacturers have to run more batches of the same colors in order to meet state requirements. While some states have no regulations others have set standards which vary from coating to coating. This shop stated that they had moved to the low VOC paints over a year ago and the supplier has been very helpful for the shop. The supplier in this case even supplied monthly usage updates for the shop. This helps the body shop conform to the record keeping requirements.

The shop manager said the new paints work well, but the drying time has drastically reduced the amount of work that can be done. He said the old lacquer paints would dry at ambient temperatures in ten minutes, while the newer paints need to be heated and can take up to 30 minutes to dry.

Computerized Mixing

The paint vendor said he was aware of two systems that the paint manufacturers used to help determine colors. This shop did not have any computerized mixing system on site, rather they relied on OEM paint codes, which are on every model car, and hand mixed the colors to match as closely as possible. True color matching is difficult if not impossible, and often auto body shops do what is known as blending. Blending is done when slight differences exist in colors and the painter covers areas of the auto that may not need repainting in order to hide the color change. This allows for the color differences to be spread out over a larger surface thus creating the illusion that the colors are the same.

The paint vendor said that even at the OEM level hoods on cars painted with the same color on the same day in the same batch runs can not be exchanged because of the slight color differences. The vendor went on to say that one color standard can have up to 30 different variations and still be considered the same color standard.

There are two instruments available that act as a human eye to identify auto paint color. The instruments are referred to as spectra-photometers. One system uses light from a halogen bulb to detect the color scheme. It can match colors to a 16 color spectrum wavelength. The other system uses light from a xenon bulb to detect the color scheme. This system can match colors to a 256 color spectrum wavelength. The vendor stated these instruments work better in theory than in the field and that color flop (mica content and flatness) can drastically reduce the instruments effectiveness at creating correct color match.

Not many shops have invested in these instruments because of the cost, which may be above $20,000, and the lack of effectiveness.

Other Comments of Relevance

The shop manager presented his opinion about the insurance industry. Eighty-five percent of the work done at this shop is driven by insurance claims. The insurance companies have contractual rates which are established within various regions. The auto body shops therefore can only charge set rates for refinishing (work time and materials). These rates are established by the insurance companies and range significantly from locality to locality. This pricing drastically reduces the shops ability to pass along costs of capital such as spending $400,000 on new spray paint booths. When regulations are issued, shops have little choice but to comply and compliance becomes a real cost issue as in this case the shop can not just pass on the costs of major upgrades. For a shop of this size upgrades are possible, but for smaller shops who also rely on insurance claims for the majority of their work costly upgrades may not be possible because the volume of work may not be enough to recover the costs of capital improvement. The shop manager predicted that within a few years many of the medium size shops will go out of business because of non-compliance. He said real small shops will be ignored and the larger shops like his will expand to meet additional capacity. They can afford to make the upgrades and many medium sized shops will not be able to.

The shop manager said he would be converting over to all waterbased paint systems in a few years. He believes the industry will have no other choice. The waterbased paint systems can be sprayed just as the old solvent based systems, but the drying time is significantly longer. Areas in the country which have high humidity will have to make upgrades before they move to waterbased paints systems. The manager said he liked the paint booth upgrades primarily because of the added safety margins.

REFERENCES

(Anon., 1986) Auto Refinish Paint Tinted Automatically. Industrial Finishing

(Anon., 1988) Color Matching is Serious Business at AMCO. Industrial Finishing.

(Anon., 1991a) Paint Manufacturing Quality Control. Industrial Finishing. July 1991.

(Anon., 1991b) Measuring Metallic Colors Accurately. Industrial Finishing. July 1991.

(Anon., 1992) Color Control. Automotive Industries. June 1992

(Anon., 1995) More Options Available for Low-VOC Coatings. Modern Paints and Coatings, 1995, p. 6.

(Anon, 1996) "New UV-Cure System Needs no Photoinitiator", Industrial Paint and Powder, 1996 page 10.

(BAAQMD, (1995) Bay Area Quality Management District (BAAQMD), 1995. Technical Review Group Report: Reconsideration of Best Available Retrofit Control Technology and Reasonably Available Control Technology Guidelines for Automobile Refinishing Operations. February 24, 1995.

(Bailey, 1988) The Quality Connection in Paint Manufacturing. Industrial Finishing.

(Bailey, 1992) Bailey, J.M., "VOC Regs Drive Auto Paint Line Design", Industrial Finishing, 1992.

(Brown, 1996) Telecon, Tom Brown, ICI Paints, with Christopher Sweet SAIC, May 1, 1996. Low VOC Paints.

(BSB, 1995) 1995 Body Shop Industry Profile, prepared by MarketScope for Body Shop Business Magazine.

(CARB, 1991) California Air Resources Board (CARB), 1991. Determination of Reasonably Available Control Technology and Best Available Retrofit Control Technology for Automotive Refinishing Operations. January 8, 1991.

(CCC, 1996) Site Visit to Chevy Chase Chevrolet-Geo-Oldsmobile by SAIC, April 26, 1996. Current auto body industry practices.

(Chan, 1986) T.L. Chan et al., "High-Solids Paint Overspray Aerosols in a Spray Painting Booth: Particle Size and Scrubber Efficiency," American Industrial Hygiene Association Journal, 47(7): 441-417 (July 1986).

(Eklund, 1995) Eklund, B.M., Nelson, T.P., Evaluation of VOC Emission Measurement Methods for Paint Spray Booths, Journal of the Air and Waste Management Association, 45:196-205, 1995.

(Fettis, 1995) Fettis, G. Automotive Paints and Coatings. VCH Publishers, 1995.

(Garcia, 1996) Telecon, Bill Garcia, DeVilbiss Corporation, with John Vierow, SAIC, April 4, 1996. Spray booth design in automobile refinish industry.

(Heitbrink, 1994) WA. Heitbrink, ME Wallace: Control of Paint Overspray in Auto body Repair Shops, American Industrial Hygiene Association Journal, 56(10):1023-1032.

(Heitbrink, 1996) W.A.Heitbrink, R.H. Verb, T.J. Fishbach, and M.E. Wallace: A Comparison of Conventional and High Volume-Low Pressure Spray-Painting Guns,. American Industrial Hygiene Association Journal, 57(3):304-310.

(Janko, 1992) Janko, M., McCarthy K., Fajer M., and van Raalte. Occupational Exposure to 1,6,-Hexamethylene Diisocyanate-Based Polyisocyanates in the State of Oregon, 1980-1990. American Industrial Hygiene Association Journal 53(5):331-338 (1992).

(Kirk-Othmer, 1992) Kirk-Othmer, Encyclopedia of Chemical Technology, 1992, Volume 6, pp. 635-709.

(Marg, 1992) K. Marg, "The Basics of HVLP," Industrial Finishing, November 1992, pp. 29-31.

(Montville, 1985) Montville, V.L. 1985.Sherwin-Williams Stores Equipped with computerized Color Equipment. Industrial Finishing

(Muller, 1988) Mueller, J. 1988. Computer Color Control Trends. Industrial Finishing.

(NFPA, 1995) NFPA 33. Standard for Spray Application Using Flammable of Combustible Materials, 1995 edition.

(NIOSH, 1993) National Institute for Occupational Safety and Health (NIOSH): Control Technology for Auto body Repair and Painting Shops at Valley Paint and Body Shop, Amelia, Ohio, Report CT-179-14a, by W.A. Heitbrink, T.C. Cooper, M.A. Edmonds, C.J. Bryant, and W.E. Ruch. Springfield, VA: National Technical Information Service, 1993.

(NIOSH, 1996) Hazard Controls, NIOSH Publication No. 96-105, U.S. Department of Health and Human Services, Public Health Service Centers for Disease Control and Prevention, National Institute for Occupational Safety and Health, January 1996

(Schrantz, 1991) J. Schrantz, "Automotive Coatings: What's Happening?", Industrial Finishing, July 1991, pp 14-15.

(Schrantz, 1992) J. Schrantz, "What's New in HVLP Spray Guns?" Industrial Finishing, June 1992, pp 34-38.

(Spray-Systems, (1996) Product Literature, Spray-Systems, 1996

(TNRCC, 1995) Small Business Technical Assistance Program of the Texas Natural Resource Conservation Commission and Clean Texas 2000 Publication, 1995.

(USEPA, 1979) U.S. EPA, "Automobile and Light Duty Truck Surface Coating Operations - Background Information for Proposed Standards, September 1979, EPA-450/3-79-030.

(USEPA, 1994) U.S.EPA, Alternative Control Techniques Document: Automobile Refinishing. April 1994, EPA-453/R-94-031.

(Watkins, 1996) Telecon, Mark Watkins and Janis Lakey, California Air Resources Board, with Christopher Sweet SAIC, April 24, 1996. Low VOC Paints.

Spray Coating Generic Scenario - Automotive
Chemical Engineering Branch
January 1992

Note: All numerical estimates in this document are taken from reference (1).

Number of Sites:
Assume: New cars: 40 to 50; New trucks: 15 to 20
Refinishing: 1000s

Days/yr operation:
Assume: New (cars or trucks): 250 (3 shifts/day)
Refinishing: 200 to 250 (1 shift/day)

Number of Workers/site:
Assume: New: total 50 to 200; manual spraying 2 to 8/shift at 1 to 20 stations/site
Refinishing: 1 to 5

Working Days/yr:
Assume: same as days/yr operation (1 8-hr shift/day)

Inhalation exposures:
Assume: For manual spraying, new vehicles or refinishing, 50 mg/day (total mist) x PMN concentration in mist. (basis: NIOSH field studies)
Lower exposures expected for other workers.

Dermal exposures:
Assume: Use standard assumptions

Water releases:
If waterwall-type or water-washed booth, assume:
(3.77 to 7.54) x (PMN solubility in H2O in g/L) kg/site/day for N days/yr where
N = 1 if solvent-based coating; or 4 if water-based coating; or 50 if paint sludge removal efficiency may be low;
(basis 1,000 to 2,000 gallon system)
otherwise, assume no release to water.

Air releases:
Assume: use standard assumptions for volatiles

Incineration releases:
Assume: none

Land releases:
Assume: 50% to 90% x kg PMN produced/yr (air-atomized)
5% to 50% x kg PMN produced/yr (electrostatic)
(essentially 100% of overspray; includes sludge from water-overspray recovery systems)