



**FIRST FIVE-YEAR REVIEW REPORT
FOR THE
IOWA CITY FORMER MANUFACTURED GAS PLANT SUPERFUND SITE
JOHNSON COUNTY, IOWA**



Prepared by

**U.S. Environmental Protection Agency
Region 7
Lenexa, Kansas**


**Robert W. Jackson, Acting Director
Superfund Division**


Date

30285447



Superfund

Table of Contents

List of Abbreviations	5
Executive Summary	7
Five-Year Review Summary Form	10
I. Introduction.....	11
A. Site Chronology.....	12
B. Background	12
Physical Characteristics	12
Land and Resource Use	12
History of Contamination	13
Initial Response.....	14
Basis for Taking Action.....	15
C. Remedial Actions	16
Remedy Selection	16
Remedy Implementation.....	19
System Operations/Operation and Maintenance (O&M)	21
II. Progress Since the Last Five-Year Review	21
III. Five-Year Review Process.....	22
Administrative Components	22
Community Notification and Involvement	22
Document Review.....	22
Data Review.....	22
Site Inspection.....	28
IV. Technical Assessment	28
<i>Question A:</i> Is the remedy functioning as intended by the decision documents?	28
<i>Question B:</i> Are the exposure assumptions, toxicity data, cleanup levels, and remedial action objectives (RAOs) used at the time of the remedy selection still valid?.....	30
<i>Question C:</i> Has any other information come to light that could call into question the protectiveness of the remedy?	33
Technical Assessment Summary	33
V. Issues, Recommendations and Follow-up Actions	34
VI. Protectiveness Statement(s).....	34
VII. Next Review	34

Tables

Table 1 – Chronology of Site Events ...	12
Table 2 – Action Levels for Groundwater ...	18
Table 3 – Ralston Creek Sediment Performance Standards ...	19
Table 4 – Operation and Maintenance Costs ...	21
Table 5 – Air Monitoring Results ...	27

Figures

1. Current Site Layout
2. Site Vicinity and Current Groundwater Monitoring Network
3. Ralston Creek Sediment Sampling Location and Tile Liner Inspection Area
4. Air Sampling Locations

Attachments

1. List of Documents Reviewed
2. Groundwater Monitoring Results
3. Sediment Sampling Results
4. Groundwater Contaminants of Concern Trend Analysis Summary
5. Five-Year Review Inspection Form

LIST OF ABBREVIATIONS

AOC	Administrative Order on Consent
ARAR	Applicable or Relevant and Appropriate Requirement
BTEX	Benzene, Toluene, Ethylbenzene and Xylenes
CERCLA	Comprehensive Environmental Response, Compensation and Liability Act
COC	Contaminant of Concern
DNAPL	Dense Nonaqueous Phase Liquid
EPA	United States Environmental Protection Agency
FMGP	Former Manufactured Gas Plant
FYR	Five-Year Review
IIGE	Iowa-Illinois Gas and Electric Company
IDNR	Iowa Department of Natural Resources
LLC	Limited Liability Company
LNAPL	Light Nonaqueous Phase Liquid
MCL	Maximum Contaminant Level
NPL	National Priorities List
OU	Operable Unit
O&M	Operation and Maintenance
PAHs	Polynuclear Aromatic Hydrocarbons
PECs	Probable Effects Concentrations
PQL	Practical Quantitation Limit
RAO	Remedial Action Objective
RBC	Risk Based Concentration
ROD	Record of Decision
RSL	Regional Screening Level
TBCs	To Be Considereds
TI	Technical Impracticability
UCL	Upper Confidence Limit
VOC	Volatile Organic Compound
µg/kg	Microgram per kilogram
µg/L	Microgram per Liter
µg/m ³	Microgram per cubic meter

EXECUTIVE SUMMARY

This is the first Five-Year Review (FYR) for the Iowa City Former Manufactured Gas Plant (FMGP) Superfund site located in Iowa City, Johnson County, and Iowa. The purpose of this FYR is to review information to determine if the remedy is and will continue to be protective of human health and the environment. The triggering action for this statutory review is the date of the start of on-site construction of the remedial action.

The site is located east of downtown Iowa City at 505 East Burlington Street in a mixed commercial and residential area and is approximately 1.5 acres in size. The site property is currently occupied by the Iowa-Illinois Square (formerly known as the Iowa-Illinois Manor) apartment building, which contains 54 units, occupied by approximately 150 residents. The apartment building and paved parking areas cover the majority of the site.

Ralston Creek runs parallel to Van Buren Street, which is located on the west side of the site, and adjacent to the site. This reach of the creek is tile lined and heavily vegetated. The city owns the creek in this area.

Manufactured coal gas was produced at the site beginning in approximately 1857 until approximately 1937, when natural gas became available in the area. The production of manufactured gas created waste products that are resistant to natural decay and typically remain at FMGP sites for decades. The primary waste is a dense, oily liquid known as "coal tar", which condensed out of the gas during various stages of its production, leading to contamination of soil, groundwater and sediment which came into contact with the coal tar. Coal tar is a mixture of chemicals known as polynuclear aromatic hydrocarbons (PAHs) and volatile organic compounds (VOCs), specifically benzene, toluene, ethylbenzene and xylenes (BTEX). Other contaminants frequently associated with the production of manufactured gas are arsenic, cyanides and some metals.

In 1983, during the design and construction of the apartment building, an investigation was conducted by the property owner due to the discovery of oily wastes at the site. During this investigation, it was determined that fill material containing what was believed to be manufactured gas plant refuse was present in the subsurface. As a result of the discovery of this material in the subsurface and vapors encountered during the investigation, the design of the foundation of the apartment building was modified, a liner was placed under a portion of the building and a passive venting system was installed in the crawl space.

In March 1999, the EPA, MidAmerican Energy Company and the Iowa-Illinois Manor Partnership entered into an Administrative Order on Consent (AOC) for site characterization activities. In December 2003, when the EPA determined that a time-critical removal action was necessary to remove contamination associated with the FMGP along the northern edge of the site, MidAmerican and the Manor Partnership entered into a second AOC to conduct this work. In January 2004, MidAmerican removed the contents of the underground tank, filled it with inert material, and recovered groundwater and light nonaqueous phase liquid (LNAPL) from two monitoring wells.

In August 2004, MidAmerican and the Manor Partnership entered into a third AOC with the EPA to conduct a feasibility study. MidAmerican conducted some additional limited field investigations, completed a treatability study involving the removal of LNAPL, and completed a Feasibility Study Report dated June 2006.

In September 2006 the EPA signed a Record of Decision (ROD) that selected the remedy for the site. The major components of the selected remedy are:

- Implementation of institutional controls to prohibit the installation of water wells, maintain conditions in Ralston Creek, and maintain conditions within the Iowa-Illinois Square apartment building.
- Implementation of a technical impracticability (TI) waiver of applicable or relevant and appropriate requirements (ARARs) within the identified TI zone.
- Groundwater monitoring for contaminants of concern (COCs) and natural attenuation parameters.
- Evaluation of potential indoor air exposure at off-site locations from groundwater within the TI zone.
- Sediment monitoring for COCs in Ralston Creek.
- Indoor air monitoring for COCs in the Iowa-Illinois Square apartment building.
- Recovery of LNAPL from the unconsolidated aquifer.

On November 26, 2008, MidAmerican Energy Company and Iowa-Illinois Manor, LLC, entered into a Consent Decree to perform a remedial design and remedial actions at the site. Remedial actions include recovery of LNAPL from monitoring wells; monitored natural attenuation of groundwater; monitoring of air, sediment, and groundwater; and implementation of ICs, including environmental covenants. The remedial design was started on July 10, 2008, and concluded on January 29, 2010. On-site construction of the remedial action began on February 17, 2010.

The remedy is performing as expected, with natural attenuation processes continuing to occur in the contaminated groundwater plume as demonstrated through evaluation of contaminant concentrations and natural attenuation parameters. Groundwater outside of the TI zone is meeting the action levels except for elevated levels of manganese at MW-7 and intermittent elevated levels of naphthalene at MW-35. MW-7 is upgradient of the contamination source so it is likely that the manganese is naturally occurring and not the result of contamination from the site.

Sediment sampling results have been quite variable, with six of the nine COCs exceeding the performance standards in one downstream sample in 2011, compared to one COC performance standard exceedance in 2012 and none exceeded in 2013. As additional samples are collected, the statistical analysis of this data will become more robust. The condition of the tile lining has not degraded significantly during the remedial action but there are areas of damage, which was discussed with representatives of the city during the five-year review inspection.

LNAPL gauging and recovery continues consistent with the LNAPL Recovery Plan. LNAPL recovery has been minimal since the beginning of the remedial action.

Air in the crawlspace beneath the Iowa-Illinois Square apartment building is monitored through annual sampling for benzene and naphthalene, the COCs present at the site that are sufficiently volatile to potentially move from groundwater into air. While low levels of benzene have been detected in air in the crawlspace that exceeded the indoor air action level on two occasions, these wells were within the acceptable cancer risk range and remain protective of human health for indoor air for apartment dwellers. Naphthalene has not been detected above the analytical detection limit.

An institutional control in the form of an environmental covenant was filed with the Johnson County Recorder on June 4, 2009, on the site property, currently occupied by the Iowa-Illinois Square

apartments. The environmental covenant prohibits installation of wells on the site, other than monitoring wells, restricts excavation deeper than six feet below grade without prior notification and approval of the EPA except in cases of emergency, and requires notification to the EPA a minimum of 60 calendar days prior to transfer of title of the property or change in use.

An institutional control in the form of an environmental covenant was filed with the Johnson County Recorder on December 15, 2010, on the stretch of Ralston Creek located west of the site. The environmental covenant prohibits installation of wells on the property, other than monitoring wells and restricts excavation or other disturbance to the tile lining without prior notification and approval of the EPA, except in cases of emergency.

Additional institutional controls in the form of a state rule governing installation of wells in areas of contamination, a city code requiring connection to the public water supply and a county ordinance requiring notification regarding setbacks from contamination for groundwater well installation remain in force and provide additional layers of protection.

The remedy for the Iowa City FMGP site is protective of human health and the environment.

Five-Year Review Summary Form

SITE IDENTIFICATION		
Site Name: Iowa City Former Manufactured Gas Plant Site		
EPA ID: IAD 984591172		
Region: 7	State: IA	City/County: Iowa City/Johnson County
SITE STATUS		
NPL Status: Non-NPL		
Multiple OUs? No	Has the site achieved construction completion? Yes	
REVIEW STATUS		
Lead agency: EPA <i>If "Other Federal Agency", enter Agency name:</i> Click here to enter text.		
Author name (Federal or State Project Manager): Diana Engeman		
Author affiliation: EPA-Region 7		
Review period: 1/28/2014 - 1/12/2015		
Date of site inspection: 7/7/2014		
Type of review: Statutory		
Review number: 1		
Triggering action date: 2/17/2010		
Due date (five years after triggering action date): 2/17/2015		
Issues/Recommendations		
OU(s) without Issues/Recommendations Identified in the Five-Year Review:		
OU 00. There are no issues or recommendations identified in the Five-Year Review.		
Sitewide Protectiveness Statement		
Protectiveness Determination: Protective	Addendum Due Date (if applicable): Click here to enter a date.	
Protectiveness Statement: The remedy at the Iowa City Former Manufactured Gas Plant site is protective of human health and the environment.		

I. INTRODUCTION

The purpose of conducting a five-year review (FYR) is to evaluate the implementation and performance of a remedy to determine if the remedy continues to be protective of human health and the environment. The methods, findings and conclusions of a FYR are documented in a FYR report. In addition, a FYR report identifies any issues found during the review, and documents any recommendations to address the issues.

The U.S. Environmental Protection Agency conducts a FYR and prepares a FYR report pursuant to the Comprehensive Environmental Response, Compensation and Liability Act, section 121, and the National Contingency Plan. CERCLA 121 states:

If the President selects a remedial action that results in any hazardous substances, pollutants, or contaminants remaining at the site, the President shall review such remedial action no less often than each five years after the initiation of such remedial action to assure that human health and the environment are being protected by the remedial action being implemented. In addition, if upon such review it is the judgment of the President that action is appropriate at such site in accordance with section [104] or [106], the President shall take or require such action. The President shall report to the Congress a list of facilities for which such review is required, the results of all such reviews, and any actions taken as a result of such reviews.

The EPA interpreted this requirement further in the National Contingency Plan, 40 Code of Federal Regulations section 300.430(f)(4)(ii), which states:

If a remedial action is selected that results in hazardous substances, pollutants, or contaminants remaining at the site above levels that allow for unlimited use and unrestricted exposure, the lead agency shall review such actions no less often than every five years after the initiation of the selected remedial action.

The EPA conducted a FYR on the remedy implemented at the Iowa City Former Manufactured Gas Plant (FMGP) Superfund site in Iowa City, Johnson County, Iowa. The EPA is the lead agency for developing and implementing the remedy for the site. The Iowa Department of Natural Resources (IDNR), as the support agency representing the state of Iowa, has reviewed the supporting documentation and provided input to the EPA during the FYR process.

This is the first FYR for the Iowa City FMGP Superfund site. The triggering action for this statutory review is the date of the start of on-site construction of the remedial action. The FYR is required because hazardous substances, pollutants or contaminants remain at the site above levels that allow for unlimited use and unrestricted exposure. The site is addressed as one Operable Unit (OU). This OU is the subject of this FYR.

A. SITE CHRONOLOGY

Table 1

Event	Date
Initial discovery of problem or contamination	12/12/1990
Preliminary Assessment completed	4/19/1991
Site Investigation completed	8/7/1996
Expanded Site Investigation completed	9/9/1998
Administrative Order on Consent (AOC) for Site Characterization signed	3/29/1999
AOC for Removal Action signed	12/16/2003
Removal Action completed	7/26/2004
AOC for Feasibility Study signed	8/13/2004
Remedial Investigation/Feasibility Study complete and Record of Decision (ROD) signed	9/26/2006
ROD modified by memorandum	6/17/2008
Consent Decree entered	11/26/2008
Remedial Design start	7/10/2008
Remedial Design complete	1/19/2010
On-site Remedial Action construction start	2/17/2010
Construction completion date	8/2/2010

B. BACKGROUND

Physical Characteristics

The site is located east of downtown Iowa City at 505 East Burlington Street in a mixed commercial and residential area and is approximately 1.5 acres in size. The site property is currently occupied by the Iowa-Illinois Square apartment building. Nearby commercial enterprises include the L&M Mighty Shop, a convenience store and gas station, to the north; an apartment building to the south on the property previously occupied by two auto garages. To the west, across Ralston Creek, the Burlington Commons apartment building was constructed on property previously occupied by Hanson Auto Body Shop. The Iowa City Recreation Center and municipal parking lot are located northwest of the site. The current site layout is shown in Figure 1. The site vicinity and current groundwater monitoring network is depicted in Figure 2.

Land and Resource Use

The site property is currently occupied by the Iowa-Illinois Square (formerly known as the Iowa-Illinois Manor) apartment building, which contains 54 units, occupied by approximately 150 residents. As shown in Figure 1, the apartment building and paved parking areas cover the majority of the site. Grass-covered and landscaped areas are located along the adjacent streets and along the margins of the building with the exception of the eastern side of the building, which is covered with landscaping rock. Ralston Creek runs parallel to Van Buren Street, which is located on the west side, and adjacent to the site. This reach of the creek is tile lined and heavily vegetated. The city owns the creek in this area.

A survey of water wells and potential groundwater usage within a one-mile radius of the site was conducted. Eleven water wells were identified within the search radius and four of these are potentially

used as a source of drinking water. None of the existing water wells are located in the contaminated plume area or are likely to ever be impacted by the site.

The city supplies potable water to the University of Iowa, residences and businesses within the city limits of Iowa City. The municipal water supply is drawn from intakes located on the Iowa River and a well field located north of Iowa City, outside the one-mile search radius. Wells screened in the Silurian and Cambro-Ordovician aquifers within the one-mile radius and owned by the University were utilized by the city primarily for blending with the surface water supply during spring runoff. However, with the completion of a new city water treatment plant, the city no longer uses these wells as a blending source.

The University also supplies some of its own water. The University-owned wells described in the previous paragraph are on standby as a potential blending source for times when the University's surface water supply is not of suitable quality. The other water wells located within the one-mile radius are not utilized for drinking water.

The potential for new water well installations within the search radius is low. The city enforces a municipal ordinance (City Code Section 14-3C-10) that prohibits the installation of private water wells where a municipal water supply line is available within 300 feet. Additionally, the ordinance provides the city authority to require owners of existing private wells to connect to the municipal water supply if a water supply line exists within 300 feet. The Iowa City well ordinance has been approved for use as an institutional control by the IDNR for leaking underground storage tank sites and other state-lead projects.

Ralston Creek is a perennial stream with highly variable flow. It is managed primarily for storm water drainage rather than for recreational use. Buried utility lines run beside and beneath Ralston Creek near the site. In the immediate vicinity of Ralston Creek, it appears that groundwater discharges to the creek under base-flow conditions. It is not anticipated that the use or management of the creek will change in the future. The stretch of the creek adjacent to the site is owned by the city.

Ralston Creek ultimately discharges in the Iowa River several miles downstream of the site. The confluence of Ralston Creek and the Iowa River is a fishery and likely a nursery for fish. The Iowa River is used as a source of drinking water for the city of Iowa City and the University. It is not anticipated that this usage will change in the future.

History of Contamination

Manufactured coal gas was produced at the site beginning in approximately 1857 until approximately 1937, when natural gas became available in the area. After ceasing gas production, the facilities were used into the 1950s for distribution of natural gas. The layout of the FMGP facilities as they existed in 1926 is shown in blue in Figure 1.

The production of manufactured gas created waste products that are resistant to natural decay and typically remain at FMGP sites for decades. The primary waste is a dense, oily liquid known as "coal tar", which condensed out of the gas during various stages of its production. Although some of this coal tar was sold, substantial amounts leaked from storage and processing facilities or was discharged at the site. Soil, groundwater and sediment which came into contact with the coal tar became contaminated, and in many cases, continues to be contaminated. Coal tar was a mixture of chemicals known as

polynuclear aromatic hydrocarbons (PAHs) and volatile organic compounds (VOCs), specifically benzene, toluene, ethylbenzene and xylenes (BTEX). Other contaminants frequently associated with the production of manufactured gas are arsenic, cyanides and some metals.

The Iowa City FMGP operated under several names throughout its period of operation. For the majority of the years it was operated by Tri-City Railway and Light Company, a subsidiary of United Light and Power Company. In the early 1940s Iowa-Illinois Gas and Electric Company (IIGE) purchased Tri-City Railway and Light Company.

Following closure of the manufactured gas plant operations, the site was utilized by IIGE as a service facility until approximately 1971. At some point after 1971, the property was sold to Ron Shank, who operated a bar on the property. The property was purchased from Ron Shank on December 31, 1982, by the Iowa-Illinois Manor Partnership. The buildings on the property were demolished and the Iowa-Illinois Manor apartments were constructed in 1983. The property is currently owned by Iowa-Illinois Square, following its June 18, 2009, purchase from the Iowa-Illinois Manor Partnership.

In 1983, during the design and construction of the apartment building, an investigation was conducted by the property owner due to the discovery of oily wastes at the site. During this investigation, it was determined that fill material containing what was believed to be manufactured gas plant refuse was present in the subsurface. As a result of the discovery of this material in the subsurface and vapors encountered during the investigation, the design of the foundation of the apartment building was modified, a liner was placed under a portion of the building and a passive venting system was installed in the crawl space.

Based on historical maps, Ralston Creek has been relocated twice during development of the area. The portion of Ralston Creek located near the site has been relocated and channelized from its native location. An 1839 map of Iowa City shows Ralston Creek meandering across the current location of the site. Based on a review of Sanborn® maps, it appears the meander at the site was eliminated prior to 1888, and then Ralston Creek was further straightened and tile-lined at some time between 1948 and 1970 to place it in its current location. Ralston Creek is currently located approximately 40 feet west of the site.

The EPA conducted investigations at the site and issued an Expanded Site Investigation Report in 1998 in which it was determined further investigation was warranted due to the presence of elevated levels of BTEX, PAHs, cyanides, arsenic and lead. Contamination was found in soil and groundwater.

Initial Response

In March 1999, the EPA, MidAmerican Energy Company (a successor to IIGE) and the Manor Partnership entered into an Administrative Order on Consent (AOC) for site characterization activities. From October 1999 through March 2004 MidAmerican conducted this investigative work. The final Site Characterization Report, dated August 2003, including the baseline risk assessment and all amendments to the Report, constitute the final Remedial Investigation Report for the site.

In December 2003, the EPA determined that a time-critical removal action was necessary to remove contamination associated with the FMGP along the northern edge of the site. This work was necessary to minimize exposure to city and utility workers doing construction work in the area, and to address an underground tank in the area. MidAmerican and the Manor Partnership entered into an AOC to conduct

this work. In January 2004, MidAmerican removed the contents of the underground tank, filled it with inert material, and recovered groundwater and light nonaqueous phase liquid (LNAPL) from two monitoring wells.

In August 2004, MidAmerican and the Manor Partnership entered into a third AOC with the EPA to conduct a feasibility study. MidAmerican conducted some additional limited field investigations, completed a treatability study involving the removal of LNAPL, and completed a Feasibility Study Report dated June 2006. The Site Characterization Report, the Feasibility Study Report and other documents in the Administrative Record file may be reviewed for a more complete source of information regarding the history of the site.

Basis for Taking Action

A baseline risk assessment was conducted as part of the site characterization. It included a human health baseline risk assessment and a screening level ecological risk assessment. The following lists the contaminants that were identified as contaminants of concern (COCs) for each media affected:

Soil

Arsenic
Cyanide
Iron
Manganese
Aroclor 1254
Aroclor 1260
Acenaphthylene
Benzo(a)anthracene
Benzo(b)fluoranthene
Benzo(k)fluoranthene
Benzo(a)pyrene
Chrysene
Dibenzo(a,h)anthracene
Indeno(1,2,3-c,d)pyrene
2-Methylnaphthalene
Naphthalene
Benzene
Ethylbenzene

Indoor Air

Benzene
Naphthalene

Surface Water

Benzene

Groundwater

Aluminum
Arsenic
Chromium
Cyanide
Iron
Lead
Manganese
Acenaphthene
Acenaphthylene
Benzo(a)anthracene
Benzo(a)pyrene
Benzo(b)fluoranthene
Benzo(k)fluoranthene
Chrysene
Dibenzo(a,h)anthracene
Fluorene
Indeno(1,2,3-c,d)pyrene
2-Methylnaphthalene
Naphthalene
Phenanthrene
Benzene
Ethylbenzene
Toluene
Xylenes, total

Sediment

Arsenic
Iron
Benzo(a)anthracene
Benzo(b)fluoranthene
Benzo(a)pyrene

Although there were no current exposures to groundwater for residents, it was determined that potential future exposures through consumption of contaminated groundwater or through inhalation of the vapor from showering or cooking could present a significant carcinogenic risk as well as noncarcinogenic health effects if exposure were to occur. The contaminants posing the greatest carcinogenic risks in groundwater were benzo(a)pyrene, benzene and dibenzo(a,h)anthracene. The majority of the noncarcinogenic health effects due to exposure to groundwater were posed by naphthalene and benzene.

Contaminants in soil and indoor air did not pose a significant threat provided exposure to subsurface soil contamination did not occur in the future and site conditions preventing indoor air exposures did not change in the future.

Exposure to contaminants in surface water did not pose an unacceptable level of risk to humans or ecological receptors. The significant ecological resource to be protected is the fishery located at the confluence of Ralston Creek and the Iowa River. It was determined that in the future, comparing sediment samples from Ralston Creek in the vicinity of the site to consensus-based probable effects concentrations of PAHs for freshwater ecosystems would serve as an indicator of possible new contribution of contamination from the site into the creek.

C. REMEDIAL ACTIONS

Remedy Selection

The ROD for the Iowa City FMGP site was signed on September 26, 2006. Remedial action objectives (RAOs) were developed during the Feasibility Study, utilizing data collected during the remedial investigation, to aid in the development and screening of remedial alternatives that were considered for the ROD. Separate RAOs were developed for soil, groundwater, indoor air and Ralston Creek. The RAOs for the site are to:

- Prevent and/or reduce human exposure to groundwater containing COCs that exceed applicable or relevant and appropriate requirements (ARARs) or health-based levels.
- Prevent and/or reduce future soil exposure risks to acceptable levels by maintaining the existing land use. The future soil RAO may be reevaluated if the building is removed or its use changed.
- Prevent and/or reduce future human exposure to indoor air containing COCs that exceed health-based levels.
- Maintain the existing ecological steady state and prevent and/or reduce future unacceptable risks to human health and the environment in Ralston Creek.

The major components of the selected remedy are:

- Implementation of institutional controls to prohibit the installation of water wells, maintain conditions in Ralston Creek, and maintain conditions within the Iowa-Illinois Square apartment building.
- Implementation of a technical impracticability (TI) waiver of ARARs within the identified TI zone.
- Monitored natural attenuation of groundwater.
- Groundwater monitoring for COCs and natural attenuation parameters.

- Evaluation of potential indoor air exposure at off-site locations from groundwater within the TI zone.
- Sediment monitoring for COCs in Ralston Creek.
- Indoor air monitoring for COCs in the Iowa-Illinois Square apartment building.
- Recovery of LNAPL from the unconsolidated aquifer.

Action levels are the concentrations of the COCs in the affected media that must not be exceeded to ensure that the RAOs will be met. These levels were initially developed for this site during the Feasibility Study. The processes for doing so for each media are described below.

The action levels for groundwater were determined based upon the following hierarchy:

- The maximum contaminant level (MCL) pursuant to the Safe Drinking Water Act for the contaminant when an MCL is available.
- For contaminants without an MCL, the action level is calculated based on an excess lifetime cancer risk of 1×10^{-6} and/or a target hazard quotient of 1.
- When the calculated risk-based action level is below the laboratory practical quantitation limit (PQL), the PQL is used as the action level, provided it falls within the acceptable risk range of 1×10^{-4} to 1×10^{-6} excess lifetime cancer risk.

The action levels for groundwater at the site, and the rationale for their selection, as described in the ROD, are as listed in Table 2.

Table 2
ACTION LEVELS FOR GROUNDWATER
in µg/L

Contaminant of Potential Concern	Chemical-Specific ARARs (MCLs)	Risk-Based Concentration (RBC)	PQL	Selected Groundwater Action Level (Basis for Selection)
2-methylnaphthalene	-	61.2	-	61.2 (RBC)
Acenaphthene	-	914	-	914 (RBC)
Acenaphthylene	-	362	-	362 (RBC)
Benzene	5	-	-	5 (MCL)
Benzo(a)anthracene	-	0.009	0.13	0.13 (PQL)
Benzo(a)pyrene	0.2	-	-	0.2 (MCL)
Benzo(b)fluoranthene	-	0.005	0.1	0.1 (PQL)
Benzo(k)fluoranthene	-	0.05	0.14	0.14 (PQL)
Chrysene	-	0.85	-	0.85 (RBC)
Cyanide	200	-	-	200 (MCL)
Dibenzo(a,h)anthracene	-	0.0003	0.033	0.033 (PQL)
Ethylbenzene	700	-	-	700 (MCL)
Fluorene	-	490	-	490 (RBC)
Indeno(1,2,3-cd)pyrene	-	0.005	0.1	0.1 (PQL)
Naphthalene	-	6.2	-	6.2 (RBC)*
Phenanthrene	-	294	-	294 (RBC)
Toluene	1,000	-	-	1,000 (MCL)
Xylenes, total	10,000	-	-	10,000 (MCL)
Manganese	-	775	-	775 (RBC)
Cyanide	200	-	-	200 (MCL)

Note:

* The groundwater action level for naphthalene was 6.2 µg/L in the 2006 ROD. It was changed to 1.1 µg/L based on a change from health-based levels for noncancer health effects to humans to health-based levels due to cancer risk to humans. This change was documented in a June 17, 2008, Memorandum for Record.

Soil action levels were not established as surface soil at the site does not pose an unacceptable level of risk. Prevention of future exposure to subsurface soil is addressed through institutional controls.

Action levels for indoor air were calculated for benzene and naphthalene based on an excess cancer risk of 1×10^{-6} and/or a target hazard quotient of 1. The action levels for benzene and naphthalene in indoor air, established in the ROD, were 0.8 microgram per cubic meter ($\mu\text{g}/\text{m}^3$) and 1.3 $\mu\text{g}/\text{m}^3$, respectively. The action level for naphthalene in indoor air was changed from 1.3 $\mu\text{g}/\text{m}^3$ to 0.056 $\mu\text{g}/\text{m}^3$ in a June 17,

2008 Memorandum for Record. The action level was modified due to a change from health-based levels for noncancer health effects to human beings to health-based levels due to cancer risk in humans.

Sediment samples from Ralston Creek were compared against consensus-based probable effects concentrations (PECs) of PAHs for freshwater ecosystems (nonhuman receptors) as indicators of possible contribution of contaminants from the site into the creek. PECs are contaminant concentrations that have been developed for specific compounds above which the inhabitants of a body of freshwater could be negatively affected. The PECs are listed in Table 3. These levels are significantly lower than any concentration that would pose a threat to human health, so they are sufficiently low to be protective of human exposure to creek sediment.

Table 3
RALSTON CREEK SEDIMENT PERFORMANCE STANDARDS
in micrograms per kilogram ($\mu\text{g}/\text{kg}$) dry weight

Contaminant of Potential Concern	Performance Standards
Anthracene	845
Benzo(a)anthracene	1,050
Benzo(a)pyrene	1,450
Chrysene	1,290
Fluoranthene	2,230
Fluorene	536
Naphthalene	561
Phenanthrene	1,170
Pyrene	1,520
Total PAHs	22,800

Remedy Implementation

On November 26, 2008, MidAmerican Energy Company and Iowa-Illinois Manor, LLC, entered into a Consent Decree to perform a remedial design and remedial actions at the site. Remedial actions include recovery of LNAPL from monitoring wells; monitored natural attenuation of groundwater; monitoring of air, sediment, and groundwater; and implementation of institutional controls, including environmental covenants. The remedial design was started on July 10, 2008, and concluded on January 29, 2010. On-site construction of the remedial action began on February 17, 2010.

A groundwater monitoring program was designed to monitor groundwater for COCs and natural attenuation parameters. Groundwater monitoring events have occurred semiannually, generally in April and October, since October 2009. These data are used to evaluate compliance with groundwater action levels, groundwater plume stability and remedial action progress via natural attenuation over time.

It was noted in the ROD that the extent of groundwater contamination in bedrock downgradient of the site had not been fully characterized during the remedial investigation but that this lack of information would not change the decision regarding the appropriate remedy. It was further noted that determining this extent of contamination might necessitate a change in the boundaries of the TI zone. In 2011, two additional monitoring wells were installed to delineate the downgradient extent of contamination in bedrock and the TI zone. Those wells are MW-56 and MW-57. Based on sampling of those wells, it was determined that there was no need to change the boundaries of the TI zone as described in the ROD.

An LNAPL recovery plan was developed to manage the recovery of free product from the unconsolidated aquifer in the vicinity of monitoring well MW-8 on the northern edge of the site. Per the LNAPL Recovery Plan, LNAPL recovery and gauging will continue in the wells near MW-8 until the recovery rate is less than or equal to 0.1 gallon per month and the LNAPL thickness remains less than 0.02 foot for 12 consecutive months. LNAPL is recovered through the placement of absorbent "socks" in the affected wells to passively recover free product.

In October 2009, at the request of the EPA, the dense nonaqueous phase liquid (DNAPL) thickness was measured and then the DNAPL was removed in two monitoring wells, MW-26 and MW-27, so that a recovery rate could be determined. Since that time, the DNAPL has been gauged and removed from those wells at least semiannually.

An indoor air monitoring program was designed to monitor benzene and naphthalene in the crawlspace beneath the Iowa-Illinois Square apartment building. Air monitoring is conducted in the crawlspace as this area is directly over the source of contamination and should be unaffected by sources of the contaminants other than the site. Benzene and naphthalene can be found in many other sources routinely found in indoor living spaces, such as cigarette smoke. Air samples are collected annually at three locations, generally in March. The action levels were established in the ROD for indoor air in living spaces. Since the air that is sampled is not in the actual living space, the indoor air monitoring program assumed that there was an attenuation factor of 0.01 for samples collected in the crawlspace so established that as long as the contaminant levels measured in the crawlspace do not exceed 80 $\mu\text{g}/\text{m}^3$ for benzene or 5.6 $\mu\text{g}/\text{m}^3$ for naphthalene it is assumed that the indoor air in the apartments does not exceed the indoor air action levels and remains protective of human health.

In addition to air monitoring at the Iowa-Illinois Square apartment building, subslab soil gas at another off-site building located over the contaminated groundwater plume was sampled in 2010 to determine whether there were potential off-site impacts to indoor air. It was determined that there were no off-site indoor air impacts due to the site.

A sediment monitoring program was designed to determine whether there are measurable changes in the concentrations of contaminants entering Ralston Creek sediment from subsurface soil or groundwater. Sediment samples are collected annually, generally in October, from two locations near the site. One is at the upstream end of the site and the other is at the downstream end of the site. During the sampling event, the tile liner of the creek is inspected to determine whether its condition is remaining relatively the same. It is recognized that the tile liner has not been completely intact since investigations began at the site but it has served as a barrier to movement of contamination from the site into the creek in the condition that it was in at the time the remedy for the site was selected.

An institutional control in the form of an environmental covenant has been placed on the site property (currently occupied by the Iowa-Illinois Square apartment building) and was filed with the Johnson

County Recorder on June 4, 2009. The environmental covenant prohibits installation of wells on the site, other than monitoring wells, restricts excavation deeper than six feet below grade without prior notification and approval of the EPA except in cases of emergency, and requires notification to the EPA a minimum of 60 calendar days prior to transfer of title of the property or change in use.

An institutional control in the form of an environmental covenant has been placed on the stretch of Ralston Creek located west of the site and was filed with the Johnson County Recorder on December 15, 2010. The environmental covenant prohibits installation of wells on the site, other than monitoring wells and restricts excavation or other disturbance to the tile lining without prior notification and approval of the EPA, except in cases of emergency.

System Operations/Operation and Maintenance

Operation and maintenance activities at the site include semiannual groundwater monitoring, periodic LNAPL and DNAPL gauging and recovery, annual inspection of the Ralston Creek tile liner, annual sediment sampling, annual inspection of the liner and venting system beneath the Iowa-Illinois Square apartment building and annual sampling of the crawlspace air beneath the building. The condition of all monitoring wells is noted during each sampling event. The condition of the tile liner in Ralston Creek is noted during annual sediment sampling and during the last two years representatives of the city have been present to discuss maintenance of the creek banks. LNAPL recovery has occurred consistent with the LNAPL Recovery Plan in the Remedial Design.

The operation and maintenance (O&M) costs are shown in the following table. The actual costs were provided by MidAmerican Energy Company.

**Table 4
O&M COSTS**

Year	Approximate Cost
2010	\$87,000
2011	\$282,000
2012	\$61,000
2013	\$91,000
2014 (January-October)	\$65,000
TOTAL	\$586,000

These costs are consistent with the O&M costs for this remedy in the ROD, which are estimated to be approximately \$82,000 per year during this period. Not included in that estimate was the additional air monitoring that occurred in a building over the groundwater plume in 2010 and the installation of two deep monitoring wells in 2011. These activities account for the elevated costs in 2011.

II. PROGRESS SINCE THE LAST REVIEW

This is the first FYR for this site.

III. FIVE YEAR REVIEW PROCESS

Administrative Components

MidAmerican Energy Company, the property owner, the city and the state were notified of the initiation of the FYR. The FYR team was led by Diana Engeman, the EPA Remedial Project Manager for the site. EPA support personnel on the FYR team included a hydrogeologist, human health and ecological risk assessors, the site attorney and the community engagement specialist. A representative of the Iowa Department of Natural Resources reviewed the FYR Report.

The review, which began on January 28, 2014, consisted of the following components:

- Community Involvement
- Document Review
- Data Review
- Site Inspection
- Five-Year Review Report Development and Review

Community Notification and Involvement

Activities to involve the community in the five-year review process were initiated with a notice that was published in the local newspaper, the *Iowa City Press Citizen* on April 18, 2014, stating that the EPA was conducting a review of the remedy at the site and inviting the public to submit any comments to the EPA. The results of the review and the report will be made available at the site information repository located at Iowa City Public Library, 123 South Linn Street, Iowa City, Iowa. The EPA did not receive any comments from the public during the FYR.

Document Review

This FYR consisted of a review of relevant documents including annual progress reports and monitoring data. Applicable groundwater, sediment and air cleanup standards as listed in the September 2006 ROD, as modified by a memorandum dated June 17, 2008, were reviewed. A list of documents reviewed is in Attachment 1.

Data Review

Groundwater

Groundwater sampling has occurred semiannually, in April and October, since the start of the remedial action in 2010. Several of the wells have been sampled periodically since 1999. Sampling is conducted to determine if COC concentrations in groundwater outside the TI zone comply with the action levels and natural attenuation processes are sufficient to maintain COC compliance with action levels outside the TI zone. During each sampling event, water levels are measured in wells so that groundwater flow direction may be determined in each of the water-bearing units. The unconsolidated aquifer at the site is an unconfined unit that has been divided into two units, referred to as the water table zone and the bedrock surface zone, to facilitate evaluation. The groundwater flow at the water table is westerly at the site with an overall southwesterly flow in this zone, toward the Ralston Creek channel. Groundwater flow at the bedrock surface is consistently in a southwesterly direction at the site. Groundwater flow in the Devonian and Silurian bedrock aquifers is southwesterly at the site.

Compliance with action levels outside of the TI zone is evaluated by sampling seven compliance monitoring wells: MW-7, MW-29, MW-33, MW-35 MW-41, MW-56 and MW-57, for the COCs listed in Table 2. Well locations can be referenced in Figure 2. Compliance with the action levels is determined by performing a statistical hypothesis test. A 95-percent upper confidence level (UCL) of the true mean concentration for each COC is calculated using data from the site. By definition, the 95-percent UCL of the true mean concentration of a COC at a monitoring well is a value that, when calculated repeatedly for randomly drawn data sets, equals or exceeds the true mean concentration of the COC 95-percent of the time.

Thirteen of the seventeen COCs have not been detected in any of the seven compliance monitoring wells during the remedial action monitoring events. The 13 COCs that have not been detected are benzene, toluene, ethylbenzene, xylenes, acenaphthylene, benzo(a)anthracene, benzo(a)pyrene, benzo(b)fluoranthene, benzo(k)fluoranthene, chrysene, debenzo(a,h)anthracene, indeno(1,2,3-cd)pyrene and cyanide. In the unconsolidated aquifer, only manganese at MW-7 exceeded the action level. Manganese levels have fluctuated above the risk-based level during sampling events since the implementation of the remedial action. Because MW-7 is upgradient of the TI zone and the site, and manganese is not present in other compliance wells in the unconsolidated aquifer, it is probable that elevated levels of manganese in this well are naturally occurring and not site-related.

In the bedrock aquifer, the action level for naphthalene was exceeded at MW-35 in October 2010 and April 2013. However, the April 2013 detection of naphthalene at 1.11 µg/L only exceeded the action level of 1.1 µg/L by a very small amount and was also detected in the associated method blank, bringing into question the validity of this value. Manganese exceeded the action level at MW-33 in April 2010. The exceedances of naphthalene and manganese have been sporadic and do not indicate any plume stability issues. There have been no other exceedances of an action level in the compliance monitoring wells in the bedrock aquifer. Attachment 2 lists the groundwater monitoring results.

Containment of the contaminated groundwater plume within the TI zone through natural attenuation processes is evaluated through analysis of COC concentrations and plume stability. Trends in contaminant mass and plume stability provide the primary line of evidence of the natural attenuation of COCs. Geochemical data provide a secondary line of evidence of natural attenuation by indicating destruction of COC mass through biodegradation processes. Concentrations of COCs are measured at wells within the TI zone as well as at the compliance wells outside the TI zone to evaluate the COC distribution throughout the plume. The Mann-Kendall trend test analysis is used to identify increasing and decreasing concentration trends at the 90-percent confidence level for each COC detected in each monitoring well. Detailed analyses of each COC at each monitoring well is included in each Remedial Action Annual Report. Numerous field measurements and laboratory analyses were performed to evaluate the destruction of COC mass through biodegradation processes. Detailed analyses of these data are reported in each Remedial Action Annual Report.

Attachment 4 is a table that shows the most recent summary of this trend analysis. The contaminated groundwater plume appears to be stable, however, 8 of 13 wells sampled within the TI zone has at least one COC with a statistically significant increasing concentration trend. These data also indicate that 17 of 19 COCs exhibit no statistically significant trend or a statistically significant decreasing concentration for each of the seven compliance monitoring wells which are outside of the TI zone. Naphthalene was determined to be statistically increasing at MW-35 at the 90-percent confidence level. Manganese was determined to be statistically increasing at MW-35 but has not exceeded the action level since October 2003. The furthest downgradient monitoring wells within the TI zone are MW-36 and MW-37, which

are located approximately 75 feet from the southwest boundary of the TI zone. Benzene exceeded the MCL in samples from these wells in 2013. In addition, six COCs have statistically significant increasing concentration trends at these wells but have not ever exceeded the action level. Compliance wells MW-56 and MW-57 are over 500 feet downgradient of MW-36 and MW-37 therefore it is possible for elevated levels of benzene to exist in groundwater in the area between these monitoring points.

Locations of the monitoring wells were determined based on the ability to obtain access to the property for well installation and continue to have access for long-term monitoring. It is difficult to place monitoring wells in technically optimal locations in an area as highly developed as the one where this plume is located.

It has been concluded that natural attenuation of organic COCs is occurring as depth increases through various microbial degradation processes along the groundwater flow path to the southwest.

Based on limited exceedances of COCs in compliance monitoring wells, and the evidence that biodegradation is occurring within the TI zone, it is concluded that the plume is stable and the TI zone established in the 2006 ROD is still appropriate.

LNAPL Gauging and Recovery

Significant quantities of LNAPL were observed in monitoring wells LMW-4, MW-2, MW-8, MW-44, MW-47 and MW-48 during the course of investigations at the site. Prior to completion of the feasibility study, a treatability study was conducted to assess vacuum extraction for recovery of LNAPL. During the course of that treatability study, which took place from April through August 2005, approximately 105 gallons of LNAPL were removed from LMW-4, MW-8 and MW-48 through vacuum extraction, with the rate decreasing significantly with each recovery event. It was determined through data gathered during that study that the use of absorbent socks would be the most effective method to remediate residual LNAPL.

Six monitoring wells that are within the TI zone were originally designated as LNAPL recovery wells in the LNAPL Recovery Plan. The wells are LMW-4, MW-2, MW-8, MW-44, MW-47 and MW-48. Monitoring wells MW-3, MW-45, MW-46, MW-49, MW-50 and MW-51 were gauged to monitor for potential migration of LNAPL. In general, the plan was to place absorbent socks into wells that had a measurable amount of LNAPL of greater than 0.02 foot. A sock would remain in the well until a recovery rate is less than or equal to 0.1 gallon per month and the LNAPL thickness is less than 0.02 foot for 12 consecutive months. Gauging and recovery was to occur every two weeks to begin with and eventually move to a quarterly basis when the rate of LNAPL recovery warranted the reduced frequency.

LNAPL gauging and recovery began in March 2010. Biweekly events ended after one month because the absorbent socks were not fully saturated. Gauging and recovery continued on a monthly basis for three months and then decreased to a quarterly basis because, once again, the socks were not fully saturated. LNAPL gauging and recovery continues on a quarterly basis except at MW-46 and LMW-4. MW-46 was abandoned in 2013 due to an obstruction in the well. LNAPL greater than 0.02 foot in thickness had not ever been measured in that well. In 2013, LMW-4 met the criteria for termination of LNAPL recovery and monitoring, as stated in the LNAPL Recovery Plan. That well was re-designated as a monitoring well.

LNAPL recovery rates at all recovery wells were less than 0.1 gallon per month from March 2010 through 2014 and recovery rates have been very low. LNAPL gauging and recovery will continue as described in the LNAPL Recovery Plan, with the addition and deletion of recovery wells occurring as the plan describes and with the approval of the EPA.

DNAPL Gauging and Recovery

DNAPL recovery was not a component of the remedy selected in the ROD but in 2011 the EPA requested that MidAmerican Energy add semiannual DNAPL gauging and recovery at MW-26 and MW-27. This request was made by the EPA due to investigative work done in 2009 and 2010 to determine the rate of DNAPL recovery that could be achieved in these two wells which had historically been found to have significant amounts on DNAPL in them. DNAPL gauging and recovery was conducted semiannually in 2011 and quarterly since 2012. Since 2009, 25.5 gallons of DNAPL have been removed from MW-26 and 6.1 gallons from MW-27. While the rate of DNAPL recovery has decreased in both wells over this time period, significant quantities of DNAPL continue to be recovered and current plans are to continue to do so in the future.

Ralston Creek Sediment Sampling and Liner Inspection

Sediment sampling and creek liner inspection have been conducted annually since 2010 to determine whether changes have occurred that may result in movement of contamination from the subsurface at the site into the sediment of Ralston Creek. It was recognized at the time the ROD was written that there were multiple off-site sources of the same contaminants found at the site making their way into the creek but the levels of those contaminants were found at higher levels in sediment adjacent to the site. Ensuring that the levels of those contaminants did not increase over time would ensure that the sediment in the creek did not pose an unacceptable level of risk to ecological receptors or humans. In the ROD, it was recognized that the liner, while not fully intact, does provide a physical barrier between contamination at the site and the creek sediment.

Sediment is sampled at one upstream and one downstream location annually and analyzed for total PAHs and nine COCs: anthracene, benzo(a)anthracene, benzo(a)pyrene, chrysene, fluoranthene, fluorene, naphthalene, phenanthrene and pyrene. Figure 3 shows the sediment sampling locations. Attachment 3 lists the sediment sampling results. At the upstream sampling location, RC-4, only one COC, naphthalene, exceeded the performance standard during one sampling event in April 2010. At the downstream sampling location, RC-5, naphthalene has exceeded the performance standard in 2010, 2011 and 2012. In November 2011, benzo(a)anthracene, chrysene, fluoranthene, phenanthrene and pyrene were also above their respective performance standards at RC-5. The concentrations of COCs have been highly variable over time, likely due to the transient nature of sediment in creek channels. It will be more valuable to evaluate trends in the data rather than relying on the assessment of individual data points. The Mann-Kendall analysis has been used to evaluate trends but to date, no statistical trends at the 90-percent confidence level were evident. In addition to review of trends, statistical testing using a 95-percent UCL of the true mean concentration for each COC will be conducted once the minimum of eight samples needed have been collected. Data will continue to be collected annually and those results will provide a more robust data set with which to conduct the statistical trend and mean analyses.

The creek liner is inspected annually when the sediment samples are collected. One of the most significant observations during these inspections has been the amount of vegetation growing along the steep creek banks. Small vegetation is needed to maintain the stability of the creek bank but large trees growing along the bank, with roots pushing into the liner, are likely to damage the liner. This has been

brought to the attention of the city and they have made a commitment to remove the woody growth. The tile liner has never been in particularly good condition and it has been noted during the annual inspections that further degradation appears to be occurring, likely due to freeze-thaw cycles. This was also discussed with representatives of the city during the five-year review inspection and they acknowledged that it was in the city's best interest to maintain the stability of the creek bank. They said they were willing to look into whether there was anything they might be able to do to provide at least minimal maintenance of the liner.

Air Monitoring and Building Inspection

Air sampling of the air in the crawlspace of the Iowa-Illinois Square apartment building has been conducted annually since March 2010. Air samples are collected from three locations and analyzed for naphthalene and benzene, the two contaminants in groundwater that are sufficiently volatile to move from the subsurface soil or groundwater into the crawlspace air. The air monitoring results are shown in Table 5. The air sampling locations are shown in Figure 4.

Table 5
AIR MONITORING RESULTS
in $\mu\text{g}/\text{m}^3$

Sample Location	Sample Date	Parameter ($\mu\text{g}/\text{m}^3$)	
		Benzene	Naphthalene
SP-N	March 15-16, 2010	ND*	ND
SP-N	March 10-11, 2011	0.65	ND
SP-N	March 15-16, 2012	0.68	ND
SP-N	March 12-13, 2013	ND	ND
SP-N	March 13-14, 2014	0.60	ND
SP-C	March 15-16, 2010	ND	ND
SP-C	March 10-11, 2011	0.81	ND
SP-C	March 15-16, 2012	0.81	ND
SP-C	March 12-13, 2013	ND	ND
SP-C	March 13-14, 2014	0.81	ND
SP-S	March 15-16, 2010	ND	ND
SP-S	March 10-11, 2011	0.74	ND
SP-S	March 15-16, 2012	0.79	ND
SP-S	March 12-13, 2013	0.66	ND
SP-S	March 13-14, 2014	1.0	ND
DUPLICATE SP-S	March 15-16, 2010	ND	ND
DUPLICATE SP-S	March 10-11, 2011	0.75	ND
DUPLICATE SP-C	March 15-16, 2012	0.85	ND
DUPLICATE SP-N	March 12-13, 2013	ND	ND
DUPLICATE SP-N	March 13-14, 2014	0.58	ND

* ND—Non-detect

As described previously, since the air that is sampled is not in the actual living space, the Air Monitoring Plan established that as long as the contaminant levels measured in the crawlspace do not exceed performance standards of $80 \mu\text{g}/\text{m}^3$ for benzene or $5.6 \mu\text{g}/\text{m}^3$ for naphthalene it could be assumed that the indoor air in the apartments would not exceed the action levels. This was based on an assumption that an attenuation factor of 0.01 for the crawlspace was appropriate. During the past five years naphthalene has not been detected in crawlspace air above the detection limit of $2.6 \mu\text{g}/\text{m}^3$. Benzene has been detected on several occasions with concentrations ranging from 0.58 to $1.0 \mu\text{g}/\text{m}^3$, well below the performance standard of $80 \mu\text{g}/\text{m}^3$.

Recently the EPA has revised guidance pertaining to vapor intrusion sampling that establishes an attenuation factor of 1.0 when using crawlspace samples to predict indoor air levels, rather than an attenuation factor of 0.01. This means that the air sampling results obtained in the crawlspace should be compared to the indoor air action levels to determine protectiveness. The benzene levels that have been

detected in the crawlspace air, in Table 5, exceeded the established indoor air action levels of 0.85 $\mu\text{g}/\text{m}^3$ in 2014. Although the action level was exceeded, the sampling result is still within the acceptable cancer risk range of 1×10^{-4} to 1×10^{-1} . Changes to the Air Monitoring Plan need to be made to reflect the change in attenuation factor for the crawlspace air sampling. It would also be advisable to determine whether an analytical method exists that could achieve lower detection limits for both compounds.

During each air sampling event, the condition of the passive venting system and the liner that is under a portion of the crawlspace is observed. The venting system has always been unobstructed and the liner, with a thick layer of gravel over the top, has been undisturbed.

Site Inspection

The inspection of the site was conducted on July 7 and 8, 2014. In attendance were Diana Engeman, EPA project manager; Venessa Madden, EPA ecological risk assessor; Bryan Clark, property owner; Jennifer McIvor, Environmental Manager for MidAmerican Energy Company; Kevin Armstrong, MWH, project manager for MidAmerican's environmental consultant; Ron Knoche, City Engineer, city of Iowa City; and Ben Clark, Senior Civil Engineer, city of Iowa City. The purpose of the inspection was to assess the protectiveness of the remedy. The Site Inspection Report is Attachment 5.

The building owner provided access to the crawlspace beneath the Iowa-Illinois Square apartment building so that conditions there could be observed. There is nothing stored in the crawlspace that could impact air sampling. The area with the liner cover with gravel was undisturbed.

The members of the city engineering office were present to discuss maintenance of the eastern bank of Ralston Creek. The city provides maintenance of the creek bank and earlier in the summer had done some trimming of vegetation on the eastern bank. However, the woody growth along the eastern bank was not removed and several trees have grown up over the years in that area. While vegetation of the creek banks helps to maintain the stability of the steep slope, tree roots will tend to have a destructive effect on the tile liner. The EPA asked that trees and woody growth be removed and continue to be removed periodically. The city engineer agreed that they could do that. The site inspection also included an examination of the tile liner conditions, to the extent that it was possible to do so because the water level was a bit higher than normal and vegetation covered a lot of the liner. The EPA requested that the city consider more aggressive maintenance to improve or maintain the condition of the liner on the eastern bank of the stretch of the creek adjacent to the site as it is a physical barrier that limits the movement of site contaminants into the surface water and sediment in that area.

The city inquired whether the EPA had any grants available that might assist them in their liner maintenance effort. At this time there are no EPA grant monies available to fund the tile liner and creek bank maintenance efforts. The city engineer confirmed that maintaining a stable creek bank is something that the city recognizes as important.

IV. TECHNICAL ASSESSMENT

Question A: Is the remedy functioning as intended by the decision documents?

Remedial Action Performance

The remedy is performing as expected, with natural attenuation processes continuing to occur in the contaminated groundwater plume within the TI zone as demonstrated through evaluation of the

contaminant concentrations and natural attenuation parameters that are sampled. Groundwater outside of the TI zone in the unconsolidated aquifer is meeting the action levels except for sporadic exceedances of manganese at MW-7. This well is upgradient of the site contamination source so it is likely that the manganese is naturally occurring and not the result of contamination from the site. In the bedrock aquifer, the action level for naphthalene was exceeded at MW-35 in October 2010 and April 2013. However, the April 2013 detection of naphthalene at 1.11 µg/L only exceeded the action level of 1.1 µg/L by a very small amount and was also detected in the associated method blank, bringing into question the validity of this value. Due to the sporadic exceedances and recent sampling results, it was determined that these results were not indicative of a remedy issue. Manganese exceeded the action level at MW-33 in April 2010 but has not exceeded risk-based levels since that sampling event in the bedrock aquifer. There have no other exceedances of an action level in the compliance monitoring wells in the bedrock aquifer.

Data for each COC in groundwater were statistically evaluated annually for concentration trends using the Mann-Kendall test. This test is used to identify increasing and decreasing concentration trends at the 90-percent confidence level for each COC detected at each monitoring well. Based on this analysis for COCs in each well, the contaminated groundwater plume appears to be stable.

Numerous geochemical parameters are measured to determine the presence and identity of biodegradation processes occurring within the groundwater plume. A detailed description of these processes are included in each Remedial Action Annual Report. In general, the data analysis supports the conclusion that intrinsic bioremediation is occurring to some degree throughout the contaminated groundwater plume.

Sediment sampling results have been quite variable, with six of the nine COCs exceeding the performance standards in one downstream sample in 2011, compared to one COC exceedance in 2012 and none exceeded in 2013. As additional samples are collected, the statistical analysis of this data will become more robust. The condition of the tile lining has not degraded significantly during the remedial action but there are areas of damage, which was discussed with representatives of the city during the five-year review inspection.

LNAPL gauging and recovery continues consistent with the LNAPL Recovery Plan. Six wells are identified as recovery wells and an additional six wells were gauged. One of the wells that was gauged, MW-46, was plugged and abandoned in 2013 due to an obstruction in the well. One recovery well, LMW-4, was reclassified as a monitoring well in 2013 because it met the criteria for termination of LNAPL recovery as laid out in the LNAPL Recovery Plan. LNAPL recovery continues at a very low rate in the remaining five recovery wells. Since implementation of the remedy, the PRP have been recovering DNAPL from two additional bedrock wells where DNAPL has historically been found in recoverable quantities. DNAPL recovery will continue from these two wells.

The vapor intrusion mitigation system components (liner and passive venting) are operating as intended in the crawlspace. Air in the crawlspace beneath the Iowa-Illinois Square apartment building is monitored through annual sampling for benzene and naphthalene, the COCs present at the site that are sufficiently volatile to potentially move from groundwater into air. While benzene has been detected in air in the crawlspace and has exceeded the indoor air action level action level in March 2014 and in a duplicate sample in March 2012, these levels did not exceed the acceptable cancer risk range that would indicate it could pose a health threat for indoor air for apartment dwellers. Naphthalene has not been detected above the analytical detection limit. In the future it will be advisable to determine whether an analytical method is available that can achieve lower detection limits for both compounds.

System Operations/O&M

The operating procedures, as currently implemented, continue to maintain the effectiveness of the remedy and are expected to do so in the future. Requests to modify the operating procedures will be reviewed by the EPA when any requests are made. The process for DNAPL recovery will be added to the LNAPL Recovery Plan. In addition, the EPA is working with the city to develop a more robust maintenance plan for woody vegetation and tile integrity in Ralston Creek.

Implementation of ICs and Other Measures

An institutional control in the form of an environmental covenant was filed with the Johnson County Recorder on June 4, 2009, on the site property, currently occupied by the Iowa-Illinois Square apartments. The environmental covenant prohibits installation of wells on the site, other than monitoring wells, restricts excavation deeper than six feet below grade without prior notification and approval of the EPA except in cases of emergency, and requires notification to the EPA a minimum of 60 calendar days prior to transfer of title of the property or change in use. This institutional control remains protective, and has resulted in notification to the EPA twice in the past five years that excavation was required in areas that were potentially contaminated, ensuring that appropriate measures were taken to protect workers and the public from exposure and proper disposal of contaminated soil.

An institutional control in the form of an environmental covenant was filed with the Johnson County Recorder on December 15, 2010, on the stretch of Ralston Creek located west of the site. The environmental covenant prohibits installation of wells on the property, other than monitoring wells and restricts excavation or other disturbance to the tile lining without prior notification and approval of the EPA, except in cases of emergency. This institutional control continues to be protective.

Institutional controls in the form of a state rule governing installation of wells in areas of contamination, a city code requiring connection to the public water supply and a county ordinance requiring notification regarding setbacks from contamination for groundwater well installation remain in force and provide additional layers of protection.

Question B: Are the exposure assumptions, toxicity data, cleanup levels and RAOs used at the time of the remedy section still valid?

Changes in Standards and To-Be-Considereds (TBCs)

- *Have there been changes to risk-based cleanup levels or standards identified as ARARs in the ROD that call into question the protectiveness of the remedy?*

In 2008, the ROD was modified by memorandum to change the action levels for naphthalene in groundwater and indoor air because a significant change was made to the toxicity values for that compound which made the previous action levels not sufficiently protective. The revised action levels in the ROD are protective and reflect the latest science and toxicity information.

No other changes to ARARs or the ROD have been made, and the action levels remain protective of potential current/future land and resource uses.

- *Are there newly promulgated standards that call into question the protectiveness of the remedy?*

No new standards have been promulgated.

- *Have TBCs used in selecting cleanup levels at the site changed in way that could affect the protectiveness of the remedy?*

Ecological TBCs are based on Probable Effect Levels (MacDonald et al., 2000), which have not changed.

Changes in Exposure Pathways

- *Has land use or expected land use on or near the site changed (e.g., industrial to residential, commercial to residential)?*

Land use of the site remains unchanged but the use of two parcels of property adjacent to or very near the site have changed since implementation of the remedial action. An apartment building has been constructed to the south of the site on property previously occupied by two auto garages. According to the owner of this building, it was constructed on a slab with the garages occupying the ground level of the building. To the west, across Ralston Creek, the Burlington Commons apartment building was constructed on property previously occupied by Hanson Auto Body Shop.

- *Have any human health or ecological routes of exposure or receptors changed or been newly identified (e.g., dermal contact where none previously existed, new populations or species identified on site or near the site) that could affect the protectiveness of the remedy?*

No new contaminants, exposure pathways or receptors have been identified.

- *Are there newly identified contaminants or contaminant sources?*

We are not aware of any new contaminants.

- *Are there unanticipated toxic byproducts of the remedy not previously addressed by the decision documents (e.g., byproducts not evaluated at the time of remedy selection)?*

No toxic by-products of the remedy have been identified.

- *Have physical site conditions or the understanding of these conditions changed in a way that could affect the protectiveness of the remedy?*

The tile lining of Ralston Creek is deteriorating partially due to vegetation growing through the tiles. This lining provides a protective barrier for the creek, as it blocks migration of some of the site-related waste. If the liner continues to deteriorate, contaminant concentrations in the sediment may increase. Therefore, the EPA has requested that the city assist with the maintenance of the liner by removing the woody vegetation that has become established along the eastern bank of the creek. The city engineer said they were agreeable to this request.

Changes in Toxicity and Other Contaminant Characteristics

- *Have toxicity factors for contaminants of concern at the site changed in a way that could affect the protectiveness of the remedy?*

There have been some changes to the toxicity factors which have changed the regional screening levels (RSLs) found in the Regional Screening Levels Summary Table (<http://www.epa.gov/region9/superfund/prg/>), however none of the changes rise to the level of significance that would call into question the protectiveness of the remedy. The default exposure factors were modified in February 2014, therefore some RSLs may have increased based on current information, while others decreased. The overall impact of those changes may make a particular RSL increase or decrease, however, the overall effect on the contaminants for this site does not call into question the protectiveness of the remedy.

- *Have other contaminant characteristics changed in a way that could affect protectiveness of the remedy?*

No.

Changes in Risk Assessment Methods

- *Have standardized risk assessment methodologies changed in a way that could affect the protectiveness of the remedy?*

There were no changes to the human health or ecological standardized risk assessment methodologies that would affect the protectiveness of the remedy.

Recently, vapor intrusion guidance has modified the attenuation factor to 1.0 when using crawlspace samples to predict indoor air levels, rather than an attenuation factor of 0.01. This means that the air sampling results obtained in the crawlspace should be compared to the indoor air action levels to determine protectiveness. The most recent sampling events were analyzed using the 1.0 attenuation factor and both benzene and naphthalene concentrations remain within the acceptable risk range for both contaminants. Due to this change, it is recommended that changes to the Air Monitoring Plan be made to reflect the change in attenuation factor for the crawlspace air sampling. It would also be advisable to determine whether an analytical method exists that could achieve lower detection limits for both compounds.

Expected Progress Toward Meeting RAOs

The remedy is progressing as expected toward meeting the RAOs.

- The remedy is preventing human exposure to groundwater containing COCs that exceed applicable or relevant and appropriate requirements (ARARs) or health-based levels.
- The remedy is preventing soil exposure risks to acceptable levels by maintaining the existing land use. If necessary, the future soil RAO may be reevaluated if the building is removed or its use changed.
- The remedy is preventing human exposure to indoor air containing COCs that exceed health-based levels.

- The remedy continues to maintain the existing ecological steady state and prevent and/or reduce future unacceptable risks to human health and the environment in Ralston Creek.

Question C: Has any other information come to light that could call into question the protectiveness of the remedy? No.

- *Have newly found ecological risks been found?*

No.

- *Are there impacts from natural disasters (e.g., a 100-year flood)?*

No.

- *Has any other information come to light which could affect the protectiveness of the remedy?*

There have been changes in the use of properties near the site but it is not believed that these changes in land use impact the protectiveness of the remedy. The property directly south of the site was originally an auto repair facility. That building and another garage to the south of that building were demolished and a multi-unit residential building was built on the property. It is owned by the owner of the Iowa-Illinois Square apartment building. Since they were aware of the potential for contamination related to the site, the building was constructed on a slab with garage space on the ground level and living spaces above. This should minimize any potential for vapor intrusion from the site.

The other property where the land use has changed is across Ralston Creek to the west of the site. Formerly that property was the location of an automotive body shop. That building was demolished and a multi-unit apartment building was constructed on the property. Previous sampling of that property did not indicate that this change in use should be of concern.

Technical Assessment Summary

Based upon a review of the analytical data, an inspection of the site and a review of the institutional controls for the site, the remedy is performing as intended by the ROD. There is no exposure to groundwater contamination due to the institutional controls that are in place for the plume within the TI zone. Groundwater monitoring confirms that water outside the TI zone is not exceeding action levels. Natural attenuation continues to occur within the contaminated groundwater plume.

The LNAPL recovery system has been effective in reducing the volume of LNAPL in the subsurface and continues to function as designed. DNAPL recovery from two bedrock wells has been implemented. This activity is planned to continue and will be incorporated into the LNAPL Recovery Plan.

The implementation of institutional controls for Ralston Creek and maintenance of the creek bank and liner have been effective in maintaining the ecological steady state in the creek. Improved maintenance of the eastern creek bank and liner by the city will aid in the future protectiveness of the element of the remedy.

The crawlspace liner and passive venting system continue to prevent exposure to indoor air containing contaminants above health-based levels as has been demonstrated by air monitoring in the crawlspace. In the future, levels of air contaminants measured in the crawlspace will be compared to the indoor air action levels due to a change in the attenuation factor from 0.01 to 1.0 when comparing crawlspace air samples to indoor air levels. The EPA will work with the PRP to determine if the analytical methods for indoor air should be modified to allow for lower detection limits.

V. ISSUES/RECOMMENDATIONS AND FOLLOW-UP ACTIONS

There are no issues that adversely affect current or future protectiveness of the remedy.

The following recommendations are technical improvements but do not affect the protectiveness of the remedy were identified:

- The analytical method utilized for air samples should be reviewed to determine whether a method is available with detection limits below the indoor air action levels.
- Since the attenuation factor for comparison of crawlspace air samples to indoor air levels is now 1.0, crawlspace air samples should be compared to the air action levels rather than performance standards that are two orders of magnitude greater than the action levels. The Air Monitoring Plan should be modified to document this change to the data evaluation protocol and action levels.
- DNAPL recovery has begun from two monitoring wells with significant product recovery. DNAPL recovery from these wells will continue and the LNAPL Recovery Plan should be modified to reflect this change.

During the site inspection, evidence of deterioration of the tile liner in Ralston Creek was identified. The EPA will work with the city to develop plans for removal of woody vegetation and alternatives to improve tile liner integrity.

VI. PROTECTIVENESS STATEMENT


Sitewide Protectiveness Statement	
<i>Protectiveness Determination:</i> Protective	<i>Addendum Due Date (if applicable):</i> Click here to enter a date.
<i>Protectiveness Statement:</i> The remedy for the Iowa City FMGP is protective of human health and the environment.	

VII. NEXT REVIEW

The next FYR report for the Iowa City Former Manufactured Gas Plant Superfund site is required five years from the completion date of this review.

FIGURE 1

Current Site Layout



DEIGNED BY	JANET BALDWIN
DRAWN BY	NORA DAY
CHECKED BY	KEVIN ARMSTRONG
APPROVED BY	KEVIN ARMSTRONG
PROJECT MANAGER	KEVIN ARMSTRONG

0 40 80
SCALE IN FEET


PROJECT
MIDAMERICAN ENERGY COMPANY
FORMER MANUFACTURED GAS PLANT SITE
IOWA CITY, IOWA
TITLE
SITE LAYOUT



FIGURE
1-2

FIGURE 2

Site Vicinity and Current Groundwater Monitoring Network




3013

卷之三

FIGURE 3

Ralston Creek Sediment Sampling Location & Tile Liner Inspection Area



Feb 11, 2014 - 10:14am

C:\twoworld\dm\12425\RCSS\Iowa-2.dwg

LEGEND:

- LMW • WATER TABLE MONITORING WELL
- BEDROCK MONITORING WELL
- ◆ BEDROCK SURFACE MONITORING WELL
- ABANDONED WELL

RC ♦ RALSTON CREEK SEDIMENT SAMPLING LOCATION

— — — TILE LINER INSPECTION AREA

DESIGNED BY	KEVIN ARMSTRONG
DRAWN BY	KAI CRICK
CHECKED BY	KEVIN ARMSTRONG
APPROVED BY	KEVIN ARMSTRONG
PROJECT MANAGER	KEVIN ARMSTRONG

0 40 80
SCALE IN FEET

PROJECT MIDAMERICAN ENERGY COMPANY
FORMER MANUFACTURED GAS PLANT SITE
IOWA CITY, IOWA
TITLE RALSTON CREEK
SEDIMENT SAMPLING LOCATIONS
AND TILE LINER INSPECTION AREA




2-2

FIGURE 4

Air Sampling Locations

Figure 4

BURLINGTON STREET



ATTACHMENT 1

List of Documents Reviewed

ATTACHMENT 1

DOCUMENTS REVIEWED

Record of Decision, Iowa City Former Manufactured Gas Plant Site, Iowa City, Iowa, prepared by USEPA, September 26, 2006.

Letter regarding Further Evaluation of Metals in Groundwater, from MWH to USEPA, January 17, 2008.

Letter regarding Approval of Elimination of Some Metals from List of COCs, USEPA to MidAmerican Energy Company, April 10, 2008.

Memorandum for Record regarding Record of Decision Modification, Change to Action Levels for Naphthalene in Groundwater and Indoor Air, prepared by USEPA, June 17, 2008.

Consent Decree, Docket Number 3:08-cv-0133-JAJ, November 26, 2008.

Quality Assurance Project Plan for Air Monitoring, prepared by Stanley Consultants, Inc., April 2009.

Air Monitoring Program, prepared by Stanley Consultants, Inc., April 2009.

Environmental Covenant, Iowa-Illinois Manor, LLC, May 21, 2009.

Remedial Design Report, prepared by MWH, November 11, 2009.

Air Sampling Report, prepared by Stanley Consultants, Inc., May 2010.

Air Annual Progress Report, prepared by Stanley Consultants, Inc., July 2010.

Environmental Covenant, City of Iowa City, December 15, 2010.

Remedial Action Annual Report 2010, prepared by MWH, March 2011.

Air Sampling Report, prepared by Stanley Consultants, Inc., April 2011.

Air Annual Progress Report, prepared by Stanley Consultants, Inc., June 2011.

Remedial Action Annual Report 2011, prepared by MWH, February 2012.

Air Sampling Report, prepared by Stanley Consultants, Inc., April 2012.

Air Annual Progress Report, prepared by Stanley Consultants, Inc., August 2012.

Remedial Action Annual Report 2012, prepared by MWH, February 2013.

Air Annual Progress Report, prepared by Stanley Consultants, Inc., July 2013.

Remedial Action Annual Report 2013, prepared by MWH, February 2014.

Air Sampling Report, prepared by Stanley Consultants, Inc., May 2014.

Air Annual Progress Report, prepared by Stanley Consultants, Inc., December 2014.

ATTACHMENT 2

Groundwater Monitoring Results

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW03-GW-001 25-Oct-1999	MW03-GW-002 22-Jun-2000	MW03-GW-003 11-Jul-2001	MW03-GW-004 12-Dec-2001	MW03-GW-0410 09-Apr-2010	MW03-GW-1010 06-Oct-2010	MW03-GW-0411 13-Apr-2011
							DV	
VOCs	Units							
Benzene	µg/L	5	175	56	139	125	1540	134
Toluene	µg/L	1000	38.8	7.6	74.3	19.7	934	29.0
Ethylbenzene	µg/L	700	363	113	382	355	1460	C9 J+
Xylenes, Total	µg/L	10000	278	96.6	259	286	1280	492
								298
								285
								206
PAHs								
Acenaphthene	µg/L	914	25.6	8.89	23.8	26.4	209	76.5
Acenaphthylene	µg/L	362	37.5	9.43	20.4	0.19	U 177	11.8
Anthracene	µg/L	---	0.69	0.54	0.65	1.03	136	2.47
Benzo(a)anthracene	µg/L	0.13	0.10	U 0.10	U 0.10	U 0.10	51.7	0.100 U
Benzo(a)pyrene	µg/L	0.2	0.10	U 0.10	U 0.10	U 0.10	35.3	0.100 U
Benzo(b)fluoranthene	µg/L	0.1	0.10	U 0.10	U 0.10	U 0.10	29.1	0.100 U
Benzo(ghi)perylene	µg/L	---	0.10	U 0.10	U 0.10	U 0.10	9.36	0.100 U
Benzo(k)fluoranthene	µg/L	0.14	0.10	U 0.10	U 0.10	U 0.10	7.16	0.100 U
Chrysene	µg/L	0.85	0.10	U 0.10	U 0.10	U 0.10	40.9	0.100 U
Dibenz(a,h)anthracene	µg/L	0.033	0.10	U 0.10	U 0.10	U 0.22	2.67	MDL 0.00810 U,MDL
Fluoranthene	µg/L	---	0.10	U 0.23	U 0.10	U 0.10	110	0.337
Fluorene	µg/L	490	11.5	3.22	11.7	18.4	184	28.4
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.10	U 0.10	U 0.10	U 0.10	8.49	10.2
Naphthalene	µg/L	1.1	493	2.83	J 438	501	5370	0.100 U
Phenanthrene	µg/L	294	7.6	0.58	6.59	12	348	309
Pyrène	µg/L	---	0.19	U 0.19	U 0.19	U 0.19	97.7	8.18
1-Methylnaphthalene	µg/L	---	na	na	na	208	793	3.80
2-Methylnaphthalene	µg/L	61.2	7.1	0.72	6.13	7.82	132	288
								149
								0.931
								0.216
Inorganics								
Cyanide, Total	mg/L	---	8.4	3.21	5.63	J 3.2	na	na
Cyanide, WAD	mg/L	0.2	na	na	na	0.0100	U	0.0100
Manganese, Total	mg/L	0.775	4	2.8	2.52	2.77	2.45	U,CN5 2.54
								0.0100 1.71
Natural Attenuation Parameters								
Nitrate	mg/L	---	1.0	U 1.0	U 1.0	UJ na	na	na
Nitrite	mg/L	---	na	na	na	na	na	na
Ammonia	mg/L	---	18	5.27	13.6	na	na	na
Manganese, Dissolved	mg/L	---	na	na	2.08	2.5	na	na
Iron, Dissolved	mg/L	---	na	na	0.20	0.14	na	na
Sulfate	mg/L	---	110	440	120	na	na	na
Sulfide	mg/L	---	7.5	0.69	5.6	na	na	na
Methane	µg/L	---	na	na	na	na	na	na
Alkalinity, Total	mg/L	---	na	na	na	na	na	na
Total Kjeldahl Nitrogen	mg/L	---	na	na	na	na	na	na
Orthophosphate	mg/L	---	na	na	na	na	na	na
Total Organic Carbon	mg/L	---	na	na	na	na	na	na
Chloride	mg/L	---	na	na	na	na	na	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW03-GW-1011 25-Oct-2011	DV	MW03-GW-0412 12-Apr-2012	DV	MW3-GW-1012 10-Oct-2012	DV	MW3-GW-0413 11-Apr-2013	DV	MW3-GW-1013 23-Oct-2013	DV	MW12-GW-001 25-Oct-1999
VOCs												
Benzene	µg/L	5	82.2		77.2		91.8		20.1		86.1	
Toluene	µg/L	1000	29.7		23.6		29.7		8.90		26.8	
Ethylbenzene	µg/L	700	344		340		435		76.2		360	
Xylenes, Total	µg/L	10000	230		218		266		68.1		238	
PAHs												
Acenaphthene	µg/L	914	41.1	RL1	J-	59.2	J-	60.4	J-	26.1	J-	54.5
Acenaphthylene	µg/L	362	14.3	RL1	J-	7.47	J-	5.62	J-	5.46	J-	5.58
Anthracene	µg/L	---	2.84	RL1	J-	1.07	J-	0.928	J-	0.900	J-	1.01
Benzo(a)anthracene	µg/L	0.13	1.00	U,RL1	UJ	0.100	U	0.100	U	0.128	U UJ	1.01
Benzo(a)pyrene	µg/L	0.2	1.00	U,RL1	UJ	0.100	U	0.100	U	0.149	U UJ	1.01
Benzo(b)fluoranthene	µg/L	0.1	1.00	U,RL1	UJ	0.100	U	0.100	U	0.287	U UJ	1.01
Benzo(ghi)perylene	µg/L	---	1.00	U,RL1	UJ	0.100	U	0.100	U	0.181	U UJ	1.01
Benzo(k)fluoranthene	µg/L	0.14	1.00	U,RL1	UJ	0.100	U	0.100	U	0.191	U UJ	1.01
Chrysene	µg/L	0.85	1.00	U,RL1	UJ	0.100	U	0.100	U	0.117	U UJ	1.01
Dibenz(a,h)anthracene	µg/L	0.033	0.289	RL1,J,MDL	J-	0.0170	U,MDL	UJ	0.0130	U,MDL	UJ	0.172
Fluoranthene	µg/L	---	1.00	U,RL1	UJ	0.135	J-	0.258	J-	0.521	U UJ	1.01
Fluorene	µg/L	490	10.4	RL1	J-	20.8	J-	19.1	J-	8.57	J-	17.4
Indeno(1,2,3-cd)pyrene	µg/L	0.1	1.00	U,RL1	UJ	0.100	U	0.100	U	0.181	U UJ	1.01
Naphthalene	µg/L	1.1	270	RL1	J-	212	B1,B	B, J-	227	J-	2.62	B B,J-
Phenanthrene	µg/L	294	12.2	RL1	J-	10.4	J-	10.9	J-	3.00	J-	9.7
Pyrene	µg/L	---	1.00	U,RL1	UJ	0.118	J-	0.176	J-	0.585	U UJ	1.01
1-Methylnaphthalene	µg/L	---	237	RL1	J-	232	J-	234	J-	57.8	J-	177
2-Methylnaphthalene	µg/L	61.2	1.32	RL1	J-	0.414	J-	0.574	J-	0.143	J-	1.01
Inorganics												
Cyanide, Total	mg/L	---	na		na		na		na		na	0.0694
Cyanide, WAD	mg/L	0.2	0.0100	U	0.0264		0.0100	U	0.0730		0.0233	na
Manganese, Total	mg/L	0.775	1.70		2.40		2.00		1.010		1.2	4
Natural Attenuation Parameters												
Nitrate	mg/L	---	na		na		na		na		na	1.0
Nitrite	mg/L	---	na		na		na		na		na	0.10
Ammonia	mg/L	---	na		na		na		na		na	2.5
Manganese, Dissolved	mg/L	---	na		na		na		na		na	na
Iron, Dissolved	mg/L	---	na		na		na		na		na	na
Sulfate	mg/L	---	na		na		na		na		na	150
Sulfide	mg/L	---	na		na		na		na		na	5.2
Methane	µg/L	---	na		na		na		na		na	59
Alkalinity, Total	mg/L	---	na		na		na		na		na	460
Total Kjeldahl Nitrogen	mg/L	---	na		na		na		na		na	2.9
Orthophosphate	mg/L	---	na		na		na		na		na	0.10
Total Organic Carbon	mg/L	---	na		na		na		na		na	26.33
Chloride	mg/L	---	na		na		na		na		na	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW12-GW-002 21-Jun-2000	MW12-GW-003 11-Jul-2001	MW12-GW-004 12-Dec-2001	MW12-GW-005 16-Apr-2002	MW12-GW-1002 01-Nov-2002	MW12-GW-0103 07-Jan-2003	MW12-GW-1003 22-Oct-2003	MW12-GW-0404 06-Apr-2004
VOCs									
Benzene	µg/L	5	2.5	15.5	7	1.0	U	2.1	11.0
Toluene	µg/L	1000	1.0	U	1.0	U	1.0	U	1.0
Ethylbenzene	µg/L	700	1.0	U	1.8	1.0	U	2	U
Xylenes, Total	µg/L	10000	3.0	U	7.3	3.0	U	3.0	U
PAHs									
Acenaphthene	µg/L	914	4.80	40.4	21.9	1.48	21	52	22
Acenaphthylene	µg/L	362	11.1	82.6	27.3	1.29	1	U	100
Anthracene	µg/L	---	0.10	U	0.13	0.39	0.19	U	0.17
Benzo(a)anthracene	µg/L	0.13	0.10	U	0.10	U	0.19	U	0.10
Benzo(a)pyrene	µg/L	0.2	0.10	U	0.10	U	0.19	U	0.10
Benzo(b)fluoranthene	µg/L	0.1	0.10	U	0.10	U	0.10	U	0.10
Benzo(ghi)perylene	µg/L	---	0.10	U	0.10	U	0.10	U	0.10
Benzo(k)fluoranthene	µg/L	0.14	0.10	U	0.10	U	0.10	U	0.10
Chrysene	µg/L	0.85	0.10	U	0.10	U	0.10	U	0.10
Dibenz(a,h)anthracene	µg/L	0.033	0.10	U	0.10	U	0.10	U	0.10
Fluoranthene	µg/L	---	0.10	U	0.10	U	0.19	U	0.18
Fluorene	µg/L	490	1.71	22.8	3.51	0.35	5	5.3	1.0
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.10	U	0.10	U	0.10	U	0.10
Naphthalene	µg/L	1.1	0.33	J	2.05	0.11	0.10	U	1
Phenanthren	µg/L	294	0.47	13.6	1.1	0.26	5.4	5.1	8.3
Pyrene	µg/L	---	0.19	U	0.19	U	0.19	U	0.10
1-Methylnaphthalene	µg/L	---	na	na	0.19	U	0.19	U	na
2-Methylnaphthalene	µg/L	61.2	0.19	U	0.19	U	0.19	U	na
Inorganics									
Cyanide, Total	mg/L	---	0.0217	0.016	0.022	0.010	U	0.009	0.0166
Cyanide, WAD	mg/L	0.2	na	na	na	na	na	na	na
Manganese, Total	mg/L	0.775	4.2	3.04	4.39	3	3.41	3.4	2.6
Natural Attenuation Parameters									
Nitrate	mg/L	---	1.0	UJ	1.0	U	na	na	na
Nitrite	mg/L	---	na	na	na	na	na	na	na
Ammonia	mg/L	---	1.29	2.73	na	na	na	na	na
Manganese, Dissolved	mg/L	---	na	2.97	4.69	2.8	3.2	2.92	2.6
Iron, Dissolved	mg/L	---	na	3.84	4.74	4.9	6.48	6.89	6.0
Sulfate	mg/L	---	140	130	na	na	na	na	na
Sulfide	mg/L	---	0.05	U	0.12	na	na	na	na
Methane	µg/L	---	na	na	na	na	na	na	na
Alkalinity, Total	mg/L	---	na	na	na	na	na	na	na
Total Kjeldahl Nitrogen	mg/L	---	na	na	na	na	na	na	na
Orthophosphate	mg/L	---	na	na	na	na	na	na	na
Total Organic Carbon	mg/L	---	na	na	na	na	na	na	na
Chloride	mg/L	---	na	na	na	na	na	na	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW12-GW-1004 20-Oct-2004	MW12-GW-0405 15-Apr-2005	MW12-GW-1005 11-Oct-2005	MW12-GW-0406 10-Apr-2006	MW12-GW-1006 10-Oct-2006	MW12-GW-0407 17-Apr-2007	MW12-GW-1007 09-Oct-2007	MW12-GW-0408 15-Apr-2008
VOCs									
Benzene	µg/L	5	6.0	1.0	U*	3.8	1	U	2.27
Toluene	µg/L	1000	1.0	U	1.0	U	1	U	1
Ethylbenzene	µg/L	700	1.0	U	1.0	U	1	U	1
Xylenes, Total	µg/L	10000	1.9	2.0	U*	1.6	J	3	U
PAHs									
Acenaphthene	µg/L	914	29	1.2	Ja	50	1.68	33.1	0.915
Acenaphthylene	µg/L	362	110	6.7		180	1.17	49	0.6
Anthracene	µg/L	---	0.80	0.032	Ja	1.2	0.0585	1.94	0.01
Benzo(a)anthracene	µg/L	0.13	0.13	U	0.12	U	0.042	Ja	0.019
Benzo(a)pyrene	µg/L	0.2	0.13	U	0.12	U	0.034	Ja	0.019
Benzo(b)fluoranthene	µg/L	0.1	0.050	U	0.047	U	0.037	Ja	0.037
Benzo(ghi)perylene	µg/L	---	0.20	U	0.19	U	0.20	U	0.032
Benzo(k)fluoranthene	µg/L	0.14	0.050	U	0.047	U	0.051	U	0.023
Chrysene	µg/L	0.85	0.13	U	0.12	U	0.027	Ja	0.02
Dibenz(a,h)anthracene	µg/L	0.033	0.30	U	0.28	U	0.31	U	0.033
Fluoranthene	µg/L	---	1.5		0.050	Ja	4.2	0.0813	1.68
Fluorene	µg/L	490	14	0.28		21	0.718	29	0.328
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.13	U	0.12	U	0.13	U	0.038
Naphthalene	µg/L	1.1	0.58	Ja	1.2	U	1.3	U	0.104
Phenanthrene	µg/L	294	15	0.20		24	0.271	24	0.0328
Pyrene	µg/L	---	0.34		0.23	Ua	1.8	0.271	6.93
1-Methylnaphthalene	µg/L	---	na		na		na	na	na
2-Methylnaphthalene	µg/L	61.2	na		na		na	0.052	U
Inorganics									
Cyanide, Total	mg/L	---	0.013		0.012		0.0066	B	0.01
Cyanide, WAD	mg/L	0.2	na		na		na	U	0.01
Manganese, Total	mg/L	0.775	2.6	2.2		2.9	1.77		2.15
Natural Attenuation Parameters									
Nitrate	mg/L	---	na		0.10	U	0.10	U	0.1
Nitrite	mg/L	---	na		0.020	U	0.020	U	0.1
Ammonia	mg/L	---	na		0.14	B	3.4	0.84	0.84
Manganese, Dissolved	mg/L	---	2.6		2.2		2.7	1.68	na
Iron, Dissolved	mg/L	---	6.6		5.4		6.9	3.55	3.55
Sulfate	mg/L	---	na		53		140	87.9	87.9
Sulfide	mg/L	---	na		1.0	U	0.50	B	1
Methane	µg/L	---	na		36		59	329	329
Alkalinity, Total	mg/L	---	na		380		350	347	347
Total Kjeldahl Nitrogen	mg/L	---	na		0.73		3.8	1.27	1.27
Orthophosphate	mg/L	---	na		0.015	B	0.050	U	0.1
Total Organic Carbon	mg/L	---	na		3.6		3.3	3.46	3.46
Chloride	mg/L	---	na		na		na	144	144

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW12-GW-0410 08-Apr-2010	DV	MW12-GW-1010 05-Oct-2010	DV	MW12-GW-0411 13-Apr-2011	DV	MW12-GW-1011 26-Oct-2011	DV	MW12-GW-0412 12-Apr-2012	DV	MW12-GW-1012 10-Oct-2012
VOCs												
Benzene	µg/L	5	2.07		15.2	1.00	U	2.52		1.00	U	1.00
Toluene	µg/L	1000	1.00	U	1.00	U	1.00	U	1.00	U	1.00	U
Ethylbenzene	µg/L	700	1.00	U	1.00	U	1.00	U	1.00	U	1.00	U
Xylenes, Total	µg/L	10000	6.00	U	7.77	3.00	U	5.15		3.00	U	3.00
PAHs												
Acenaphthene	µg/L	914	20.4	J+	65.0	6.32		27.4	J-	5.73		29.8
Acenaphthylene	µg/L	362	15.4	J+	37.5	3.43		21.6	J-	5.11		31.6
Anthracene	µg/L	---	0.409	J+	1.40	0.100	U	0.340	J-	0.100	U	0.173
Benzo(a)anthracene	µg/L	0.13	0.100	U	0.100	U	0.100	U	0.100	U	0.100	U
Benzo(a)pyrene	µg/L	0.2	0.100	U	0.100	U	0.100	U	0.100	U	0.100	U
Benzo(b)fluoranthene	µg/L	0.1	0.100	U	0.100	U	0.100	U	0.100	U	0.100	U
Benzo(ghi)perylene	µg/L	---	0.100	U	0.100	U	0.100	U	0.100	U	0.100	U
Benzo(k)fluoranthene	µg/L	0.14	0.100	U	0.100	U	0.100	U	0.100	U	0.100	U
Chrysene	µg/L	0.85	0.100	U	0.100	U	0.100	U	0.100	U	0.100	U
Dibenz(a,h)anthracene	µg/L	0.033	0.00810	U,MDL	0.00810	U,MDL	0.100	U	0.0207	J,MDL	J-	0.0170
Fluoranthene	µg/L	---	0.552	J+	2.78	0.155		0.927	J-	0.15		0.702
Fluorene	µg/L	490	10.1	J+	30.3	2.00		14.5	J-	1.28		14.7
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.100	U	0.100	U	0.100	U	0.100	U	0.100	U
Naphthalene	µg/L	1.1	0.569	J+	1.89	0.102		0.683	J-	0.186	B	0.420
Phenanthrene	µg/L	294	7.68	J+	23.9	0.741		8.46	J-	0.452		1.46
Pyrene	µg/L	---	0.270	J+	1.56	0.100	U	0.656	J-	0.112		0.488
1-Methylnaphthalene	µg/L	---	1.46	J+	9.14	0.185		0.975	J-	0.153		0.455
2-Methylnaphthalene	µg/L	61.2	0.100	U	0.125	0.100	U	0.100	U	0.100		0.171
Inorganics												
Cyanide, Total	mg/L	---	na		na	na		na		na		na
Cyanide, WAD	mg/L	0.2	0.0100	U	0.0100	U	0.0100	U	0.0100	U	0.0100	U
Manganese, Total	mg/L	0.775	1.82		2.55	1.90		2.33		1.65		2.19
Natural Attenuation Parameters												
Nitrate	mg/L	---	na		na	na		na		na		na
Nitrite	mg/L	---	na		na	na		na		na		na
Ammonia	mg/L	---	na		na	na		na		na		na
Manganese, Dissolved	mg/L	---	na		na	na		na		na		na
Iron, Dissolved	mg/L	---	na		na	na		na		na		na
Sulfate	mg/L	---	na		na	na		na		na		na
Sulfide	mg/L	---	na		na	na		na		na		na
Methane	µg/L	---	na		na	na		na		na		na
Alkalinity, Total	mg/L	---	na		na	na		na		na		na
Total Kjeldahl Nitrogen	mg/L	---	na		na	na		na		na		na
Orthophosphate	mg/L	---	na		na	na		na		na		na
Total Organic Carbon	mg/L	---	na		na	na		na		na		na
Chloride	mg/L	---	na		na	na		na		na		na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW12-GW-0413 11-Apr-2013	DV	MW12-GW-1013 23-Oct-2013	DV	MW16-GW-001 26-Oct-1999	MW16-GW-002 22-Jun-2000	MW16-GW-003 11-Jul-2001	MW16-GW-004 12-Dec-2001	MW16-GW-005 18-Apr-2002
<u>VOCs</u>										
Benzene	µg/L	5	0.500	U	82.7	24.1	8.1	10.2	8.7	6.2
Toluene	µg/L	1000	1.00	U	5.24	56.9	10.6	3.5	2.8	1.7
Ethylbenzene	µg/L	700	1.00	U	17.3	14.5	5.9	11.7	8.7	4
Xylenes, Total	µg/L	10000	3.00	U	39.8	111	33.0	28.9	18.6	9.7
<u>PAHs</u>										
Acenaphthene	µg/L	914	2.82	J-	78	12.7	6.36	2.57	6.37	2.3
Acenaphthylene	µg/L	362	1.39	J-	26	41.7	13.1	3.12	17	6.88
Anthracene	µg/L	---	0.100	U	UJ	1.91	9.5	11.3	3.83	1.57
Benzo(a)anthracene	µg/L	0.13	0.100	U	UJ	0.100	U	3.7	5.46	2.86
Benzo(a)pyrene	µg/L	0.2	0.100	U	UJ	0.100	U	1.88	3.75	1.62
Benzo(b)fluoranthene	µg/L	0.1	0.100	U	UJ	0.100	U	0.58	1.53	0.45
Benzo(ghi)perylene	µg/L	---	0.100	U	UJ	0.100	U	0.79	1.81	0.65
Benzo(k)fluoranthene	µg/L	0.14	0.100	U	UJ	0.100	U	0.14	0.10	U
Chrysene	µg/L	0.85	0.100	U	UJ	0.100	U	1.9	2.98	1.3
Dibenzo(a,h)anthracene	µg/L	0.033	0.0177	U	UJ	0.0173	U	0.14	0.11	0.10
Fluoranthene	µg/L	---	0.100	U	UJ	3.04	6.5	15.8	6.44	2.64
Fluorene	µg/L	490	0.490	J-	30.5	28.3	22.6	4.11	10.1	3.85
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.100	U	UJ	0.100	U	0.78	1.30	0.69
Naphthalene	µg/L	1.1	0.310	B	J-	18.2	B*	J+,B	190	83.6
Phenanthrene	µg/L	294	0.100	U	UJ	27.7	28.6	9.71	2.86	12.6
Pyrene	µg/L	---	0.100	U	UJ	1.13	2.18	7.94	2.16	0.39
1-Methylnaphthalene	µg/L	---	0.100	U	UJ	89.3	na	na	na	22
2-Methylnaphthalene	µg/L	61.2	0.100	U	UJ	0.192	55.1	0.19	U	0.19
<u>Inorganics</u>										
Cyanide, Total	mg/L	---	na		na	0.3917	0.217	0.176	J	0.216
Cyanide, WAD	mg/L	0.2	0.0100	U	0.0100	U	na	na	na	na
Manganese, Total	mg/L	0.775	2.120		2.53	4	1.7	0.623	0.694	0.249
<u>Natural Attenuation Parameters</u>										
Nitrate	mg/L	---	na		na	1.0	U	1.0	UJ	na
Nitrite	mg/L	---	na		na	0.10	U	na	na	na
Ammonia	mg/L	---	na		na	1.2	0.93	0.63	na	na
Manganese, Dissolved	mg/L	---	na		na	na	na	0.231	0.225	0.181
Iron, Dissolved	mg/L	---	na		na	na	na	2.19	2.35	2
Sulfate	mg/L	---	na		na	310	370	300	na	na
Sulfide	mg/L	---	na		na	1.8	0.18	1.0	U	na
Methane	µg/L	---	na		na	279	na	na	na	na
Alkalinity, Total	mg/L	---	na		na	350	na	na	na	na
Total Kjeldahl Nitrogen	mg/L	---	na		na	1.6	na	na	na	na
Orthophosphate	mg/L	---	na		na	0.10	U	na	na	na
Total Organic Carbon	mg/L	---	na		na	35.64	na	na	na	na
Chloride	mg/L	---	na		na	na	na	na	na	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW16-GW-1002 28-Oct-2002	MW16-GW-0103 08-Jan-2003	MW16-GW-0404 06-Apr-2004	MW16-GW-0405 15-Apr-2005	MW16-GW-0406 12-Apr-2006	MW16-GW-1006 11-Oct-2006	MW16-GW-0407 17-Apr-2007	MW16-GW-1007 10-Oct-2007
VOCs									
Benzene	µg/L	5	6.6	9.8	3.2	7.8	*	3.5	5.01
Toluene	µg/L	1000	2	U	2.0	0.66	Ja	1.6	*
Ethylbenzene	µg/L	700	5.1	9.4	2.3	7.6	*	2.45	1
Xylenes, Total	µg/L	10000	11	15	4.7	13	*	3	U
PAHs									
Acenaphthene	µg/L	914	11	U	6.3	J	4.1	5.7	3.07
Acenaphthylene	µg/L	362	11	U	10	U	28	78	7.83
Anthracene	µg/L	---	2.6	U	6.0	J	2.2	4.4	14.4
Benzo(a)anthracene	µg/L	0.13	2.5	U	10	J	0.63	1.9	2.16
Benzo(a)pyrene	µg/L	0.2	1.7	U	6.4	J	0.53	1.2	0.35
Benzo(b)fluoranthene	µg/L	0.1	2.4	U	8.9	J	0.3	0.271	0.232
Benzo(ghi)perylene	µg/L	---	0.36	U	2.2	J	0.19	Ja	0.032
Benzo(k)fluoranthene	µg/L	0.14	0.68	U	2.5	J	0.17	M	0.013
Chrysene	µg/L	0.85	1.6	U	6.7	J	0.46	1.2	0.015
Dibenz(a,h)anthracene	µg/L	0.033	1.20	U	3.3	J	0.29	0.25	0.033
Fluoranthene	µg/L	---	8.8	U	19	J	4.8	9.8	2.78
Fluorene	µg/L	490	8.2	U	13	J	7.1	12	9.31
Indeno(1,2,3-cd)pyrene	µg/L	0.1	1.1	U	1.0	U	0.16	0.46	0.132
Naphthalene	µg/L	1.1	26	U	16	J	7.6	44	3.53
Phenanthrene	µg/L	294	6.1	U	21	J	3.1	13	6.17
Pyrene	µg/L	---	5.4	U	15	J	1.9	4.8	8
1-Methylnaphthalene	µg/L	---	na	U	na	na	na	na	na
2-Methylnaphthalene	µg/L	61.2	na	U	na	na	na	na	1.27
Inorganics									
Cyanide, Total	mg/L	---	0.217	U	0.137	0.12	0.17	0.198	0.287
Cyanide, WAD	mg/L	0.2	na	U	na	na	na	na	0.132
Manganese, Total	mg/L	0.775	0.21	U	1.27	0.15	0.18	0.124	0.174
Natural Attenuation Parameters									
Nitrate	mg/L	---	na	U	na	na	0.061	B	0.1
Nitrite	mg/L	---	na	U	na	na	0.012	B	0.1
Ammonia	mg/L	---	na	U	na	na	0.2	U	0.257
Manganese, Dissolved	mg/L	---	0.182	U	0.268	0.14	0.16	0.13	na
Iron, Dissolved	mg/L	---	1.64	U	2.71	1.7	2.3	2.19	na
Sulfate	mg/L	---	na	U	na	na	240	241	na
Sulfide	mg/L	---	na	U	na	na	1.5	1	na
Methane	µg/L	---	na	U	na	na	48	26	na
Alkalinity, Total	mg/L	---	na	U	na	na	360	428	na
Total Kjeldahl Nitrogen	mg/L	---	na	U	na	na	0.72	1	na
Orthophosphate	mg/L	---	na	U	na	na	0.017	B	0.1
Total Organic Carbon	mg/L	---	na	U	na	na	3.3	4.6	na
Chloride	mg/L	---	na	U	na	na	na	54.3	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW16-GW-0408 15-Apr-2008	MW16-GW-0410 08-Apr-2010	MW16-GW-1010 06-Oct-2010	MW16-GW-0411 12-Apr-2011	MW16-GW-1011 25-Oct-2011	MW16-GW-0412 11-Apr-2012	DV	DV
VOCs									
Benzene	µg/L	5	9.14	30.2	41.4	16.8	10.9	6.62	
Toluene	µg/L	1000	1.06	5.40	3.29	5.09	1.00	U	1.00 U
Ethylbenzene	µg/L	700	6.62	21.0	33.4	12.8	10.8	6.12	
Xylenes, Total	µg/L	10000	5.56	24.8	33.7	14.3	8.67	4.75	
PAHs									
Acenaphthene	µg/L	914	4.63	5.75	5.14	102	4.54	J-	4.10 RL1 J-
Acenaphthylene	µg/L	362	14.4	16.2	10.0	108	12.9	J-	9.05 RL1 J-
Anthracene	µg/L	---	1.44	3.19	3.06	2.51	2.31	J-	1.72 RL1 J-
Benzo(a)anthracene	µg/L	0.13	0.34	0.588	2.55	1.96	4.46	J-	3.39 RL1 J-
Benzo(a)pyrene	µg/L	0.2	0.25	0.575	2.90	1.62	3.64	J-	2.59 RL1 J-
Benzo(b)fluoranthene	µg/L	0.1	0.218	0.501	2.62	1.51	3.17	J-	2.31 RL1 J-
Benzo(ghi)perylene	µg/L	---	0.148	0.157	0.923	0.623	1.34	J-	1.00 U,RL1 UJ
Benzo(k)fluoranthene	µg/L	0.14	0.121	J	0.2	0.920	0.559	J-	1.14 RL1 J-
Chrysene	µg/L	0.85	0.336	0.520	2.27	1.75	3.64	J-	2.75 RL1 J-
Dibenz(a,h)anthracene	µg/L	0.033	0.0349	J	0.0547	J,MDL	0.326	MDL	0.207 J,MDL J
Fluoranthene	µg/L	---	3.98	3.03	6.94	4.80	5.84	J-	7.85 RL1 J-
Fluorene	µg/L	490	12.5	13.6	7.96	21.5	7.85	J-	4.99 RL1 J-
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.138	0.155	0.999	0.612	1.36	J-	1.00 U,RL1 UJ
Naphthalene	µg/L	1.1	2.77	42.4	39.3	310	6.91	J-	4.18 RL1 J-
Phenanthrene	µg/L	294	5.84	8.38	5.20	35.4	3.82	J-	2.46 RL1 J-
Pyrene	µg/L	---	2.55	2.30	6.23	4.00	10.7	J-	8.36 RL1 J-
1-Methylnaphthalene	µg/L	---	na	9.24	21.9	595	7.29	J-	4.19 RL1 J-
2-Methylnaphthalene	µg/L	61.2	0.855	0.194	0.326	8.82	0.349	J-	1.00 U,RL1 UJ
Inorganics									
Cyanide, Total	mg/L	---	0.131	na	na	na	na	na	
Cyanide, WAD	mg/L	0.2	na	0.0198	0.0100	U	0.0100	U	0.0100 U
Manganese, Total	mg/L	0.775	0.171	0.153	0.102	0.128	0.142	0.29	
Natural Attenuation Parameters									
Nitrate	mg/L	---	na	0.10	U	0.10	U	0.10	U
Nitrite	mg/L	---	na	0.100	U	0.100	U	0.100	U
Ammonia	mg/L	---	na	0.461	0.613	0.468	0.535	0.509	
Manganese, Dissolved	mg/L	---	na	0.156	0.0797	S3	0.106	0.104	0.146
Iron, Dissolved	mg/L	---	na	1.59	0.906	1.73	1.23	2.38	
Sulfate	mg/L	---	na	243	385	244	206	183	
Sulfide	mg/L	---	na	5.00	U	5.00	U	10	U
Methane	µg/L	---	na	261	274	87	120	120	
Alkalinity, Total	mg/L	---	na	319	201	269	266	306	
Total Kjeldahl Nitrogen	mg/L	---	na	1.00	U	1.19	1.00	U	1.00 U
Orthophosphate	mg/L	---	na	0.1	U	0.100	U	0.100	U
Total Organic Carbon	mg/L	---	na	2.59	1.93	ET	na	2.50	na
Chloride	mg/L	---	na	33.6	28.8	na	na	na	

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW16-GW-1012 10-Oct-2012	MW16-GW-0413 10-Apr-2013	MW16-GW-1013 23-Oct-2013	MW18-GW-001 04-Apr-2000	MW18-GW-002 21-Jun-2000	MW18-GW-003 10-Jul-2001	MW18-GW-004 12-Dec-2001
DV								
<u>VOCs</u>	<u>Units</u>							
Benzene	µg/L	5	8.21	4.14	6.12	0.5	0.5	1.0
Toluene	µg/L	1000	1.24	1.00	U	1.0	1.0	1.0
Ethylbenzene	µg/L	700	8.05	3.64	5.7	1.0	1.0	1.0
Xylenes, Total	µg/L	10000	7.74	5.25	5.31	3.0	3.0	3.0
<u>PAHs</u>								
Acenaphthene	µg/L	914	6.18	3.06	5.75	0.19	0.19	0.19
Acenaphthylene	µg/L	362	16.5	8.08	10.8	0.19	0.19	0.19
Anthracene	µg/L	---	1.69	1.12	0.969	0.10	0.10	0.10
Benzo(a)anthracene	µg/L	0.13	1.38	1.57	0.449	0.10	0.10	0.10
Benzo(a)pyrene	µg/L	0.2	0.650	1.76	0.219	0.10	0.10	0.10
Benzo(b)fluoranthene	µg/L	0.1	0.708	1.66	0.199	0.10	0.10	0.10
Benzo(ghi)perylene	µg/L	---	0.168	0.650	0.10	U	0.10	0.10
Benzo(k)fluoranthene	µg/L	0.14	0.23	0.724	0.138	0.10	0.10	0.10
Chrysene	µg/L	0.85	1.05	1.57	0.439	0.10	0.10	0.10
Dibenz(a,h)anthracene	µg/L	0.033	0.0666	J,MDL	0.288	0.0332	0.10	0.10
Fluoranthene	µg/L	---	5.57	4.78	4.03	0.10	0.10	0.10
Fluorene	µg/L	490	10.6	4.92	8.48	0.19	0.19	0.19
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.170	0.629	0.10	U	0.10	0.10
Naphthalene	µg/L	1.1	6.70	7.90	4.28	B* J+,B	0.10	0.10
Phenanthrene	µg/L	294	4.39	2.18	3.33	0.10	0.10	0.10
Pyrene	µg/L	---	6.21	4.63	1.61	0.19	0.19	0.19
1-Methylnaphthalene	µg/L	---	7.56	6.56	4.02	na	na	0.19
2-Methylnaphthalene	µg/L	61.2	0.231	0.258	0.312	0.19	U	0.19
<u>Inorganics</u>								
Cyanide, Total	mg/L	---	na	na	na	0.0148	0.0158	0.028
Cyanide, WAD	mg/L	0.2	0.0100	U	0.0100	U	na	na
Manganese, Total	mg/L	0.775	0.234	0.0974	0.142	2.8	4	3.26
<u>Natural Attenuation Parameters</u>								
Nitrate	mg/L	---	0.100	U	0.471	na	1.0	1.0
Nitrite	mg/L	---	0.100	U	0.100	U	na	na
Ammonia	mg/L	---	0.492	0.238	na	0.20	0.44	0.20
Manganese, Dissolved	mg/L	---	0.125	0.0704	na	na	4.72	2.91
Iron, Dissolved	mg/L	---	1.74	0.505	na	na	1.18	2.7
Sulfate	mg/L	---	169	114	na	310	300	230
Sulfide	mg/L	---	10	U	12.0	na	5.0	1.0
Methane	µg/L	---	180	44.4	na	na	na	na
Alkalinity, Total	mg/L	---	316	255	na	na	na	na
Total Kjeldahl Nitrogen	mg/L	---	1.00	U	1.00	U	na	na
Orthophosphate	mg/L	---	0.100	U	0.100	U	na	na
Total Organic Carbon	mg/L	---	na	na	na	na	na	na
Chloride	mg/L	---	na	na	na	na	na	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW18-GW-005 16-Apr-2002	MW18-GW-1002 30-Oct-2002	MW18-GW-0103 08-Jan-2003	MW18-GW-1003 22-Oct-2003	MW18-GW-0404 07-Apr-2004	MW18-GW-1004 19-Oct-2004	MW18-GW-0405 14-Apr-2005	MW18-GW-1005 12-Oct-2005	
VOCs										
Benzene	µg/L	5	1.0	U	2.0	U	1.0	U	1.0	U
Toluene	µg/L	1000	1.0	U	2.0	U	1.0	U	1.0	U
Ethylbenzene	µg/L	700	1.0	U	2.0	U	1.0	U	1.0	U
Xylenes, Total	µg/L	10000	3.0	U	7.0	U	3.0	U	1.0	U
PAHs										
Acenaphthene	µg/L	914	0.19	U	0.51	U	0.55	U	2.9	U
Acenaphthylene	µg/L	362	0.19	U	1	U	1.1	U	1.5	U
Anthracene	µg/L	---	0.19	U	0.051	U	0.055	U	0.057	U
Benzo(a)anthracene	µg/L	0.13	0.19	U	0.1	U	0.11	U	0.15	U
Benzo(a)pyrene	µg/L	0.2	0.19	U	0.1	U	0.11	U	0.15	U
Benzo(b)fluoranthene	µg/L	0.1	0.10	U	0.1	U	0.11	U	0.057	U
Benzo(ghi)perylene	µg/L	---	0.10	U	0.1	U	0.11	U	0.23	U
Benzo(k)fluoranthene	µg/L	0.14	0.10	U	0.1	U	0.11	U	0.057	U
Chrysene	µg/L	0.85	0.10	U	0.1	U	0.11	U	0.15	U
Dibenz(a,h)anthracene	µg/L	0.033	0.11	U	0.1	U	0.11	U	0.34	U
Fluoranthene	µg/L	---	0.19	U	0.1	U	0.11	U	0.15	U
Fluorene	µg/L	490	0.19	U	0.1	U	0.11	U	0.29	U
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.10	U	0.1	U	0.11	U	0.15	U
Naphthalene	µg/L	1.1	0.10	U	0.51	U	0.55	U	1.5	U
Phenanthrene	µg/L	294	0.10	U	0.10	U	0.11	U	0.11	U
Pyrene	µg/L	---	0.19	U	0.1	U	0.11	U	0.29	U
1-Méthylnaphthalene	µg/L	---	0.19	U	na	na	na	na	na	na
2-Methylnaphthalene	µg/L	61.2	0.19	U	na	na	na	na	na	na
Inorganics										
Cyanide, Total	mg/L	---	0.013		0.005	U	0.00983		0.018	
Cyanide, WAD	mg/L	0.2	na		na		na		na	
Manganese, Total	mg/L	0.775	3.4		2.4		2.65		2.4	
Natural Attenuation Parameters										
Nitrate	mg/L	---	na		na		na		na	
Nitrite	mg/L	---	na		na		na		na	
Ammonia	mg/L	---	na		na		na		na	
Manganese, Dissolved	mg/L	---	2.9		2.44		2.18		2.0	
Iron, Dissolved	mg/L	---	1.3		2.89		2.53		3.1	
Sulfate	mg/L	---	na		na		na		na	
Sulfide	mg/L	---	na		na		na		na	
Methane	µg/L	---	na		na		na		na	
Alkalinity, Total	mg/L	---	na		na		na		na	
Total Kjeldahl Nitrogen	mg/L	---	na		na		na		na	
Orthophosphate	mg/L	---	na		na		na		na	
Total Organic Carbon	mg/L	---	na		na		na		na	
Chloride	mg/L	---	na		na		na		na	

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW18-GW-0406 12-Apr-2006	MW18-GW-1006 10-Oct-2006	MW18-GW-0407 17-Apr-2007	MW18-GW-1007 10-Oct-2007	MW18-GW-0408 15-Apr-2008	MW18-GW-0410 08-Apr-2010	MW18-GW-1010 06-Oct-2010	MW18-GW-0411 12-Apr-2011
VOCs									
Benzene	µg/L	5	1	U	1.00	U	1	U	1.00
Toluene	µg/L	1000	1	U	1.00	U	1	U	1.00
Ethylbenzene	µg/L	700	1	U	1.00	U	1	U	1.00
Xylenes, Total	µg/L	10000	3	U	3.00	U	3	U	3.00
PAHs									
Acenaphthene	µg/L	914	0.13	U	0.0490	U	0.049	U	0.100
Acenaphthylene	µg/L	362	0.17	U	0.0850	U	0.085	U	0.100
Anthracene	µg/L	---	0.0093	U	0.0100	U	0.0111	U	0.0100
Benzo(a)anthracene	µg/L	0.13	0.019	U	0.0030	U	0.003	U	0.100
Benzo(a)pyrene	µg/L	0.2	0.019	U	0.0320	U	0.032	U	0.100
Benzo(b)fluoranthene	µg/L	0.1	0.037	U	0.0130	U	0.013	U	0.100
Benzo(ghi)perylene	µg/L	---	0.032	U	0.0090	U	0.009	U	0.100
Benzo(k)fluoranthene	µg/L	0.14	0.023	U	0.0150	U	0.0157	U	0.100
Chrysene	µg/L	0.85	0.02	U	0.0050	U	0.005	U	0.100
Dibenz(a,h)anthracene	µg/L	0.033	0.033	U	0.0100	U	0.0111	U	0.0100
Fluoranthene	µg/L	---	0.032	U	0.0100	U	0.01	U	0.100
Fluorene	µg/L	490	0.029	U	0.0100	U	0.01	U	0.100
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.038	U	0.0070	U	0.00778	U	0.007
Naphthalene	µg/L	1.1	0.23		0.0540	U	0.054	U	0.100
Phenanthrene	µg/L	294	0.015	U	0.0202	J	0.007	U	0.100
Pyrene	µg/L	---	0.036	U	0.0190	U	0.019	U	0.100
1-Methylnaphthalene	µg/L	---	na		na		na	U	0.919
2-Methylnaphthalene	µg/L	61.2	na		0.0520	U	0.052	U	0.123
Inorganics									
Cyanide, Total	mg/L	---	0.021		0.0255		0.0208		na
Cyanide, WAD	mg/L	0.2	na		na		na	U	0.0100
Manganese, Total	mg/L	0.775	1.87		na		na	U	0.0113
Natural Attenuation Parameters									
Nitrate	mg/L	---	na		na		na		na
Nitrite	mg/L	---	na		na		na		na
Ammonia	mg/L	---	na		na		na		na
Manganese, Dissolved	mg/L	---	1.86		na		na		na
Iron, Dissolved	mg/L	---	3		na		na		na
Sulfate	mg/L	---	na		na		na		na
Sulfide	mg/L	---	na		na		na		na
Methane	µg/L	---	na		na		na		na
Alkalinity, Total	mg/L	---	na		na		na		na
Total Kjeldahl Nitrogen	mg/L	---	na		na		na		na
Orthophosphate	mg/L	---	na		na		na		na
Total Organic Carbon	mg/L	---	na		na		na		na
Chloride	mg/L	---	na		na		na		na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW18-GW-1011 25-Oct-2011	MW18-GW-0412 11-Apr-2012	DV	MW18-GW-1012 10-Oct-2012	DV	MW18-GW-0413 10-Apr-2013	DV	MW18-GW-1013 23-Oct-2013	DV
VOCs										
Benzene	µg/L	5	1.00	U	1.00	U	1.00	U	0.500	U
Toluene	µg/L	1000	1.00	U	1.00	U	1.00	U	1.00	U
Ethylbenzene	µg/L	700	1.00	U	1.00	U	1.00	U	1.00	U
Xylenes, Total	µg/L	10000	3.00	U	3.00	U	3.00	U	3.00	U
PAHs										
Acenaphthene	µg/L	914	0.100	U	UJ	0.225	0.100	U	UJ	0.455
Acenaphthylene	µg/L	362	0.100	U	UJ	0.100	U	UJ	0.450	1.09
Anthracene	µg/L	---	0.100	U	UJ	1.250	0.100	U	UJ	0.100
Benzo(a)anthracene	µg/L	0.13	0.100	U	UJ	0.100	U	UJ	0.100	U
Benzo(a)pyrene	µg/L	0.2	0.100	U	UJ	0.100	U	UJ	0.100	U
Benzo(b)fluoranthene	µg/L	0.1	0.100	U	UJ	0.100	U	UJ	0.100	U
Benzo(ghi)perylene	µg/L	---	0.100	U	UJ	0.100	U	UJ	0.100	U
Benzo(k)fluoranthene	µg/L	0.14	0.100	U	UJ	0.100	U	UJ	0.100	U
Chrysene	µg/L	0.85	0.100	U	UJ	0.100	U	UJ	0.100	U
Dibenz(a,h)anthracene	µg/L	0.033	0.0170	U,MDL	UJ	0.0170	U,MDL	UJ	0.0172	U
Fluoranthene	µg/L	---	0.100	U	UJ	0.100	U	UJ	0.100	U
Fluorene	µg/L	490	0.100	U	UJ	0.990	0.100	U	UJ	0.106
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.100	U	UJ	0.100	U	UJ	0.100	U
Naphthalene	µg/L	1.1	0.157	J-	1.71	0.339	J-	1.42	3.27	B* J+,B
Phenanthrene	µg/L	294	0.100	U	UJ	0.416	0.100	U	UJ	0.172
Pyrene	µg/L	---	0.100	U	UJ	0.105	0.100	U	UJ	0.100
1-Methylnaphthalene	µg/L	---	0.142	J-	0.71	0.114	J-	2.52	1.09	U
2-Methylnaphthalene	µg/L	61.2	0.100	U	UJ	0.162	0.100	U	UJ	0.100
Inorganics										
Cyanide, Total	mg/L	---	na		na		na		na	
Cyanide, WAD	mg/L	0.2	0.0100	U		0.0100	U		0.0100	U
Manganese, Total	mg/L	0.775	1.22		1.64		1.22		1.410	1.34
Natural Attenuation Parameters										
Nitrate	mg/L	---	na		na		na		na	
Nitrite	mg/L	---	na		na		na		na	
Ammonia	mg/L	---	na		na		na		na	
Manganese, Dissolved	mg/L	---	na		na		na		na	
Iron, Dissolved	mg/L	---	na		na		na		na	
Sulfate	mg/L	---	na		na		na		na	
Sulfide	mg/L	---	na		na		na		na	
Methane	µg/L	---	na		na		na		na	
Alkalinity, Total	mg/L	---	na		na		na		na	
Total Kjeldahl Nitrogen	mg/L	---	na		na		na		na	
Orthophosphate	mg/L	---	na		na		na		na	
Total Organic Carbon	mg/L	---	na		na		na		na	
Chloride	mg/L	---	na		na		na		na	

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW07-GW-001 26-Oct-1999	MW07-GW-002 21-Jun-2000	MW07-GW-003 10-Jul-2001	MW07-GW-004 11-Dec-2001	MW07-GW-005 16-Apr-2002	MW07-GW-1002 28-Oct-2002	MW07-GW-0103 07-Jan-2003	MW07-GW-0404 08-Apr-2004
VOCs									
Benzene	µg/L	5	0.5	U	0.5	U	0.5	U	1.0
Toluene	µg/L	1000	1.0	U	1.0	U	1.0	U	2.0
Ethylbenzene	µg/L	700	1.0	U	1.0	U	1.0	U	2.0
Xylenes, Total	µg/L	10000	3.0	U	3.0	U	3.0	U	7.0
PAHs									
Acenaphthene	µg/L	914	0.19	U	0.19	U	0.19	U	0.53
Acenaphthylene	µg/L	362	0.19	U	0.19	U	0.19	U	1.1
Anthracene	µg/L	---	0.10	U	0.10	U	0.10	U	0.053
Benzo(a)anthracene	µg/L	0.13	0.10	U	0.10	U	0.10	U	0.051
Benzo(a)pyrene	µg/L	0.2	0.10	U	0.10	U	0.10	U	0.11
Benzo(b)fluoranthene	µg/L	0.1	0.10	U	0.10	U	0.10	U	0.11
Benzo(ghi)perylene	µg/L	---	0.10	U	0.10	U	0.10	U	0.11
Benzo(k)fluoranthene	µg/L	0.14	0.10	U	0.10	U	0.10	U	0.11
Chrysene	µg/L	0.85	0.10	U	0.10	U	0.10	U	0.11
Dibenz(a,h)anthracene	µg/L	0.033	0.10	U	0.10	U	0.10	U	0.11
Fluoranthene	µg/L	---	0.10	U	0.10	U	0.10	U	0.10
Fluorene	µg/L	490	0.19	U	0.19	U	0.19	U	0.11
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.10	U	0.10	U	0.10	U	0.11
Naphthalene	µg/L	1.1	0.10	UJ	0.10	U	0.17	U	0.10
Phenanthrene	µg/L	294	0.10	U	0.10	U	0.10	U	0.11
Pyrene	µg/L	---	0.19	U	0.19	U	0.19	U	0.11
1-Methylnaphthalene	µg/L	---	na	na	na	0.19	U	0.19	U
2-Methylnaphthalene	µg/L	61.2	0.25	U	0.19	U	0.19	U	0.19
Inorganics									
Cyanide, Total	mg/L	---	0.0085		0.0050	UJ	0.010	U	0.010
Cyanide, WAD	mg/L	0.2	na		na		na	U	0.00500
Manganese, Total	mg/L	0.775	13		10	4.37	3.96	3.6	9.28
Natural Attenuation Parameters									
Nitrate	mg/L	---	1.0	U	2.4		na	na	na
Nitrite	mg/L	---	0.10	U	na		na	na	na
Ammonia	mg/L	---	0.20	U	0.20	U	na	na	na
Manganese, Dissolved	mg/L	---	na		na	2.80	3.37	0.838	2.65
Iron, Dissolved	mg/L	---	na		na	0.10	U	0.10	1.88
Sulfate	mg/L	---	330		200	180	na	na	1.2
Sulfide	mg/L	---	1.00	U	0.05	U	0.41	na	na
Methane	µg/L	---	26		na	na	na	na	na
Alkalinity, Total	mg/L	---	370		na	na	na	na	na
Total Kjeldahl Nitrogen	mg/L	---	1.0	U	na	na	na	na	na
Orthophosphate	mg/L	---	0.10	U	na	na	na	na	na
Total Organic Carbon	mg/L	---	26.48		na	na	na	na	na
Chloride	mg/L	---	na		na	na	na	na	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW7-GW-0405 13-Apr-2005	MW7-GW-0406 12-Apr-2006	MW7-GW-0407 17-Apr-2007	MW7-GW-0408 15-Apr-2008	MW7-GW-0410 08-Apr-2010	MW7-GW-0411 12-Apr-2011	MW7-GW-0412 11-Apr-2012	MW7-GW-0413 09-Apr-2013
<i>VOCs</i>	<i>Units</i>							DV	
Benzene	µg/L	5	1.0	U	1	U	1	U	1.00
Toluene	µg/L	1000	1.0	U	1	U	1	U	1.00
Ethylbenzene	µg/L	700	1.0	U	1	U	1	U	1.00
Xylenes, Total	µg/L	10000	2.0	U	3	U	3	U	6.00
<i>PAHs</i>									
Acenaphthene	µg/L	914	2.3	U	0.13	U	0.049	U	0.100
Acenaphthylene	µg/L	362	1.2	U	0.17	U	0.085	U	0.100
Anthracene	µg/L	---	0.047	U	0.0093	U	0.01	U	0.100
Benzo(a)anthracene	µg/L	0.13	0.12	U	0.019	U	0.003	U	0.100
Benzo(a)pyrene	µg/L	0.2	0.12	U	0.019	U	0.032	U	0.100
Benzo(b)fluoranthene	µg/L	0.1	0.047	U	0.037	U	0.013	U	0.100
Benzo(ghi)perylene	µg/L	---	0.19	U	0.032	U	0.009	U	0.100
Benzo(k)fluoranthene	µg/L	0.14	0.047	U	0.023	U	0.015	U	0.100
Chrysene	µg/L	0.85	0.12	U	0.02	U	0.005	U	0.100
Dibenzo(a,h)anthracene	µg/L	0.033	0.28	U	0.033	U	0.01	U	0.0081
Fluoranthene	µg/L	---	0.12	U	0.032	U	0.01	U	0.100
Fluorene	µg/L	490	0.23	U	0.029	U	0.01	U	0.100
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.12	U	0.038	U	0.007	U	0.100
Naphthalene	µg/L	1.1	1.2	U	0.1	U	0.054	U	0.100
Phenanthrene	µg/L	294	0.093	U	0.015	U	0.007	U	0.100
Pyrene	µg/L	---	0.23	U	0.036	U	0.019	U	0.100
1-Methylnaphthalene	µg/L	---	na		na		na		0.100
2-Methylnaphthalene	µg/L	61.2	na		na		0.052	U	0.100
<i>Inorganics</i>									
Cyanide, Total	mg/L	---	0.010	U	0.01	U	0.01	U	na
Cyanide, WAD	mg/L	0.2	na		na		0.01	U	0.0100
Manganese, Total	mg/L	0.775	2.3		16		na		1.350
<i>Natural Attenuation Parameters</i>									
Nitrate	mg/L	---	1.8		3.69		na		3.28
Nitrite	mg/L	---	0.020	U	0.1	U	na		0.100
Ammonia	mg/L	---	0.20	U	0.2	U	na		0.200
Manganese, Dissolved	mg/L	---	2.0		1.19		na		1.18
Iron, Dissolved	mg/L	---	0.10	U	0.1	U	na		0.100
Sulfate	mg/L	---	180		139		na		118
Sulfide	mg/L	---	1.0	U	1	U	na		12.8
Methane	µg/L	---	na		26		na		0.580
Alkalinity, Total	mg/L	---	370		399		na		432
Total Kjeldahl Nitrogen	mg/L	---	0.34	B	1	U	na		1.39
Orthophosphate	mg/L	---	0.099		0.1	U	na		0.100
Total Organic Carbon	mg/L	---	2.0		2.19		na		na
Chloride	mg/L	---	na		138		na		na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW13-GW-001 25-Oct-1999	MW13-GW-002 .21-Jun-2000	MW13-GW-003 11-Jul-2001	MW13-GW-004 12-Dec-2001	MW13-GW-0410 09-Apr-2010	MW13-GW-1010 05-Oct-2010	MW13-GW-0411 13-Apr-2011
						DV		
<u>VOCs</u>								
Benzene	µg/L	5	62.8	18.5	97.2	68.9	5.65	5.85
Toluene	µg/L	1000	122	1.5	3.0	5.0	U	1.00
Ethylbenzene	µg/L	700	261	16.4	68.9	41.6	2.55	2.58
Xylenes, Total	µg/L	10000	374	19.1	60.3	25	6.00	U
<u>PAHs</u>								
Acenaphthene	µg/L	914	43.6	54.9	63.0	35.8	17.0	J+
Acenaphthylene	µg/L	362	246	177	223	12.6	70.1	J+
Anthracene	µg/L	---	13.5	18.9	19.7	13.7	5.01	J+
Benzo(a)anthracene	µg/L	0.13	5.1	5.0	U	8.5	1.27	J+
Benzo(a)pyrene	µg/L	0.2	2.27	2.36	3.9	3.77	1.00	U
Benzo(b)fluoranthene	µg/L	0.1	0.58	0.86	1.0	U	1.00	U
Benzo(ghi)perylene	µg/L	---	1.08	0.10	U	1.0	1.88	1.00
Benzo(k)fluoranthene	µg/L	0.14	0.43	0.16	1.0	U	1.00	U
Chrysene	µg/L	0.85	2.04	5.0	U	2.8	2.95	1.16
Dibenz(a,h)anthracene	µg/L	0.033	0.2	0.20	1.0	U	1.0	U,MDL
Fluoranthene	µg/L	---	0.10	U	11.8	12.6	10.7	4.97
Fluorene	µg/L	490	77.2	121	129	47.2	26.7	J+
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.9	0.79	1.9	1.0	U	1.00
Naphthalene	µg/L	1.1	943	8.19	J	175	13.9	1.44
Phenanthrene	µg/L	294	46.9	70.4	87.3	39.1	36.8	J+
Pyrene	µg/L	---	0.19	U	0.19	U	1.9	4.23
1-Methylnaphthalene	µg/L	---	na	na	na	81.5	12.1	J+
2-Methylnaphthalene	µg/L	61.2	346	70.9	53.9	7.66	1.00	U
<u>Inorganics</u>								
Cyanide, Total	mg/L	---	0.0143	0.0099	0.010	UJ	0.010	na
Cyanide, WAD	mg/L	0.2	na	na	na	U	0.0100	U
Manganese, Total	mg/L	0.775	15	6.3	5.35	2.99	0.0100	2.21
<u>Natural Attenuation Parameters</u>								
Nitrate	mg/L	---	1.0	U	1	UJ	1.0	na
Nitrite	mg/L	---	na	na	na	U	na	na
Ammonia	mg/L	---	0.91	1.49	1.14	na	na	na
Manganese, Dissolved	mg/L	---	na	na	2.87	3.03	na	na
Iron, Dissolved	mg/L	---	na	na	9.60	10.2	na	na
Sulfate	mg/L	---	190	170	140	na	na	na
Sulfide	mg/L	---	1.00	U	1	U	na	na
Methane	µg/L	---	na	na	na	na	na	na
Alkalinity, Total	mg/L	---	na	na	na	na	na	na
Total Kjeldahl Nitrogen	mg/L	---	na	na	na	na	na	na
Orthophosphate	mg/L	---	na	na	na	na	na	na
Total Organic Carbon	mg/L	---	na	na	na	na	na	na
Chloride	mg/L	---	na	na	na	na	na	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW13-GW-1011 26-Oct-2011 DV	MW13-GW-0412 12-Apr-2012 DV	MW13-GW-1012 10-Oct-2012 DV	MW13-GW-0413 11-Apr-2013 DV	MW13-GW-1013 23-Oct-2013 DV	MW19-GW-001 04-Apr-2000 DV	MW19-GW-002 21-Jun-2000
<i>VOCs</i>	<i>Units</i>							
Benzene	µg/L	5	3.84	3.17	3.68	3.29	4.59	915
Toluene	µg/L	1000	1.00 U	1.00 U	1.00 U	1.00 U	1.00 U	91.5
Ethylbenzene	µg/L	700	1.28	1.08	1.00 U	1.00 U	1.00 U	225
Xylenes, Total	µg/L	10000	3.00 U	3.00 U	3.00 U	3.00 U	3.00 U	457
<i>PAHs</i>								
Acenaphthene	µg/L	914	7.08	7.37	J-	10.6	J-	13.8
Acenaphthylene	µg/L	362	48.7	29.9	J-	44.9	J-	47.8
Anthracene	µg/L	---	1.92	1.04	J-	0.900	J-	1.29
Benzo(a)anthracene	µg/L	0.13	0.908	0.294	J-	0.363	J-	0.709
Benzo(a)pyrene	µg/L	0.2	0.526	0.100 U	UJ	0.100 U	UJ	0.314
Benzo(b)fluoranthene	µg/L	0.1	0.489	0.100 U	UJ	0.100 U	UJ	0.288
Benzo(ghi)perylene	µg/L	---	0.194	0.100 U	UJ	0.100 U	UJ	0.123
Benzo(k)fluoranthene	µg/L	0.14	0.112	0.100 U	UJ	0.100 U	UJ	0.112
Chrysene	µg/L	0.85	0.743	0.250	J-	0.265	J-	0.715
Dibenz(a,h)anthracene	µg/L	0.033	0.0695 J,MDL UB	0.0170 U,MDL UJ	0.0130 U,MDL UJ	0.172 U UJ	0.0425	5.0 U 0.10 U
Fluoranthene	µg/L	---	2.59	2.52	J-	2.55	J-	4.47
Fluorene	µg/L	490	15.4	12	J-	16.8	J-	20.1
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.150	0.100 U	UJ	0.100 U	UJ	0.1 U
Naphthalene	µg/L	1.1	0.579	0.362 B	UB,J-	0.572	UB,J-	1.43 B UB,J-
Phenanthrene	µg/L	294	16.1	17.8	J-	19.0	J-	22.9
Pyrene	µg/L	---	3.83	2.73	J-	3.66	J-	2.14
1-Methylnaphthalene	µg/L	---	4.59	2.47	J-	3.55	J-	3.13
2-Methylnaphthalene	µg/L	61.2	0.100 U	0.100 U	UJ	0.122	J-	0.106
<i>Inorganics</i>								
Cyanide; Total	mg/L	---	na	na	na	na	na	0.0100
Cyanide, WAD	mg/L	0.2	0.0100 U	0.0100 U	0.0100 U	0.0100 U	0.0100 U	na
Manganese, Total	mg/L	0.775	2.13	2.16	2.28	2.260	2.34	10 9.4
<i>Natural Attenuation Parameters</i>								
Nitrate	mg/L	---	na	na	na	na	na	1.0 U 1.0 U
Nitrite	mg/L	---	na	na	na	na	na	na
Ammonia	mg/L	---	na	na	na	na	na	2.03 2.34
Manganese, Dissolved	mg/L	---	na	na	na	na	na	na
Iron, Dissolved	mg/L	---	na	na	na	na	na	na
Sulfate	mg/L	---	na	na	na	na	na	53 48
Sulfide	mg/L	---	na	na	na	na	na	5.0 UJ 0.05 U
Methane	µg/L	---	na	na	na	na	na	na
Alkalinity, Total	mg/L	---	na	na	na	na	na	na
Total Kjeldahl Nitrogen	mg/L	---	na	na	na	na	na	na
Orthophosphate	mg/L	---	na	na	na	na	na	na
Total Organic Carbon	mg/L	---	na	na	na	na	na	na
Chloride	mg/L	---	na	na	na	na	na	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW19-GW-003 10-Jul-2001	MW19-GW-004 12-Dec-2001	MW19-GW-005 17-Apr-2002	MW19-GW-1002 30-Oct-2002	MW19-GW-0103 08-Jan-2003	MW19-GW-1003 22-Oct-2003	MW19-GW-0404 07-Apr-2004	MW19-GW-1004 19-Oct-2004
VOCs									
Benzene	µg/L	5	867	868	829	760	J 34	J 960	1100
Toluene	µg/L	1000	108	122	94	89	J 4.4	J 110	150
Ethylbenzene	µg/L	700	258	250	196	190	J 12	J 270	270
Xylenes, Total	µg/L	10000	528	450	419	410	J 25	J 540	500
PAHs									
Acenaphthene	µg/L	914	3.8	U	58.1	79.4	140	J 280	120
Acenaphthylene	µg/L	362	9.3		206	122	10	U 10	1900
Anthracene	µg/L	---	2.0	U	3.68	9.5	U 7	J 6.6	7.3
Benzo(a)anthracene	µg/L	0.13	0.10		0.11	0.19	U 1	U 1.0	U 1.3
Benzo(a)pyrene	µg/L	0.2	0.10	U	0.10	U 0.19	U 1	U 1.0	U 1.3
Benzo(b)fluoranthene	µg/L	0.1	0.10	U	0.10	U 0.10	U 1	U 1.0	U 0.51
Benzo(ghi)perylene	µg/L	---	0.10	U	0.10	U 0.10	U 1	U 1.0	U 2.0
Benzo(k)fluoranthene	µg/L	0.14	0.10	U	0.10	U 0.10	U 1	U 1.0	U 0.51
Chrysene	µg/L	0.85	0.10	U	0.10	U 0.10	U 0.16	U 1.0	U 1.3
Dibenz(a,h)anthracene	µg/L	0.033	0.10	U	0.10	U 0.11	U 1	U 1.0	U 3.0
Fluoranthene	µg/L	---	0.10	U	0.81	1.78	4.9	J 4.6	J 5.6
Fluorene	µg/L	490	3.8	U	28.5	50.8	27	J 30	J 28
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.10	U	0.10	U 0.10	U 1.00	U 1.0	U 1.3
Naphthalene	µg/L	1.1	998		1,160	1,530		J 1,600	J 2200
Phenanthrene	µg/L	294	2.0	U	22.3	29.6	39	J 43	J 45
Pyrene	µg/L	---	0.19	U	0.19	U 1.61	2.6	J 2.3	J 2.5
1-Methylnaphthalene	µg/L	---	na		388	510	na	na	na
2-Methylnaphthalene	µg/L	61.2	3.8	U	31	35.6	na	na	na
Inorganics									
Cyanide, Total	mg/L	---	0.011		0.010	U 0.010	U 0.005	U 0.006	U 0.012
Cyanide, WAD	mg/L	0.2	na		na	na	na	na	na
Manganese, Total	mg/L	0.775	6.63		5.52	5.3	5.09	5.08	5.7
Natural Attenuation Parameters									
Nitrate	mg/L	---	1.0	U	na	na	na	na	na
Nitrite	mg/L	---	na		na	na	na	na	na
Ammonia	mg/L	---	2.07		na	na	na	na	na
Manganese, Dissolved	mg/L	---	5.45		5.52	4.9	5.06	5.21	5.0
Iron, Dissolved	mg/L	---	5.14		5.59	5.0	6.87	7.42	5.6
Sulfate	mg/L	---	80		na	na	na	na	na
Sulfide	mg/L	---	1.0	U	na	na	na	na	na
Methane	µg/L	---	na		na	na	na	na	na
Alkalinity, Total	mg/L	---	na		na	na	na	na	na
Total Kjeldahl Nitrogen	mg/L	---	na		na	na	na	na	na
Orthophosphate	mg/L	---	na		na	na	na	na	na
Total Organic Carbon	mg/L	---	na		na	na	na	na	na
Chloride	mg/L	---	na		na	na	na	na	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW19-GW-0405 14-Apr-2005	MW19-GW-1005 12-Oct-2005	MW19-GW-0406 12-Apr-2006	MW19-GW-1006 10-Oct-2006	MW19-GW-0407 17-Apr-2007	MW19-GW-1007 10-Oct-2007	MW19-GW-0408 15-Apr-2008	MW19-GW-0410 08-Apr-2010
VOCs									
Benzene	µg/L	5	2000	*	1000	1130	1290	1180	538
Toluene	µg/L	1000	150	*	120	48.4	82.2	112	179
Ethylbenzene	µg/L	700	300	*	220	173	211	184	112
Xylenes, Total	µg/L	10000	550	*	380	312	368	331	293
PAHs									
Acenaphthene	µg/L	914	160	170	135	147	155	158	146
Acenaphthylene	µg/L	362	2200	2200	125	148	120	201	156
Anthracene	µg/L	---	7.7	9.1	7.32	7.88	7.19	7.88	6.86
Benzo(a)anthracene	µg/L	0.13	0.12	0.36	Ja	0.704	0.167	0.0784	J
Benzo(a)pyrene	µg/L	0.2	0.12	U	0.16	Ja	0.019	U	0.0356
Benzo(b)fluoranthene	µg/L	0.1	0.047	U	0.23	U	0.037	U	0.0702
Benzo(ghi)perylene	µg/L	---	0.19	U	0.93	U	0.032	U	0.0144
Benzo(k)fluoranthene	µg/L	0.14	0.047	U	0.23	U	0.023	U	0.0381
Chrysene	µg/L	0.85	0.067	Ja	0.24	Ja	0.02	U	0.0409
Dibenz(a,h)anthracene	µg/L	0.033	0.28	U	1.4	U	0.033	U	0.0839
Fluoranthene	µg/L	---	5.9	6.1	0.032	U	0.01	U	0.0111
Fluorene	µg/L	490	27	25	69.2	86.5	3.95	3.11	2.89
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.12	U	0.60	U	0.038	U	0.00778
Naphthalene	µg/L	1.1	1700	1300	1030	1060	967	871	737
Phenanthrene	µg/L	294	48	49	45.8	48.6	47.1	60.3	62.1
Pyrene	µg/L	---	0.57	1.4	M	23.8	16.8	16	14.3
1-Methylnaphthalene	µg/L	---	na	na	na	na	na	na	900
2-Methylnaphthalene	µg/L	61.2	na	na	na	46.5	43.1	29.9	40
Inorganics									
Cyanide, Total	mg/L	---	0.010	U	0.0058	B	0.01	U	0.01
Cyanide, WAD	mg/L	0.2	na	na	na	na	na	na	0.0100
Manganese, Total	mg/L	0.775	4.9	4.8	7.63	na	na	na	3.84
Natural Attenuation Parameters									
Nitrate	mg/L	---	na	na	na	na	na	na	0.10
Nitrite	mg/L	---	na	na	na	na	na	na	0.100
Ammonia	mg/L	---	na	na	na	na	na	na	2.31
Manganese, Dissolved	mg/L	---	4.9	4.3	4.3	na	na	na	3.70
Iron, Dissolved	mg/L	---	6.3	6.0	4.77	na	na	na	5.31
Sulfate	mg/L	---	na	na	na	na	na	na	34.4
Sulfide	mg/L	---	na	na	na	na	na	na	5.00
Methane	µg/L	---	na	na	na	na	na	na	68.0
Alkalinity, Total	mg/L	---	na	na	na	na	na	na	389
Total Kjeldahl Nitrogen	mg/L	---	na	na	na	na	na	na	2.61
Orthophosphate	mg/L	---	na	na	na	na	na	na	0.100
Total Organic Carbon	mg/L	---	na	na	na	na	na	na	3.01
Chloride	mg/L	---	na	na	na	na	na	na	182

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW19-GW-1010 06-Oct-2010	MW19-GW-0411 12-Apr-2011	MW19-GW-1011 25-Oct-2011	MW19-GW-0412 11-Apr-2012	DP02-GW-0412 11-Apr-2012	MW19-GW-1012 10-Oct-2012
				DV		DV	DV
<u>VOCs</u>							
Benzene	µg/L	5	1060	864	964	968	984
Toluene	µg/L	1000	161	170	152	173	176
Ethylbenzene	µg/L	700	256	217	208	212	212
Xylenes, Total	µg/L	10000	406	347	328	319	315
<u>PAHs</u>							
Acenaphthene	µg/L	914	126	99.5	56.5	J-	89.2
Acenaphthylene	µg/L	362	127	99.9	129	J-	98.3
Anthracene	µg/L	---	13.3	10.3	6.50	J-,J-	8.05
Benzo(a)anthracene	µg/L	0.13	0.144	0.120	0.147	J-,J-	0.145
Benzo(a)pyrene	µg/L	0.2	0.100	U	0.100	U	0.100
Benzo(b)fluoranthene	µg/L	0.1	0.100	U	0.100	U	0.100
Benzo(ghi)perylene	µg/L	---	0.100	U	0.100	U	0.100
Benzo(k)fluoranthene	µg/L	0.14	0.100	U	0.100	U	0.100
Chrysene	µg/L	0.85	0.122	0.106	0.127	J-,J-	0.125
Dibenzo(a,h)anthracene	µg/L	0.033	0.00810	U,MDL	0.017	U,MDL	0.0170
Fluoranthene	µg/L	---	1.66	1.46	2.62	J-,J-	1.93
Fluorene	µg/L	490	28.8	24.8	8.07	J-	20.5
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.100	U	0.100	U	0.100
Naphthalene	µg/L	1.1	488	384	416	J-	292
Phenanthrene	µg/L	294	53.5	37.7	29.8	J-	37.1
Pyrene	µg/L	---	1.03	1.47	5.55	J-,J-	1.85
1-Methylnaphthalene	µg/L	---	733	619	652	J-	483
2-Methylnaphthalene	µg/L	61.2	10.8	5.84	9.71	J-,J-	8.85
<u>Inorganics</u>							
Cyanide, Total	mg/L	---	na	na	na	na	na
Cyanide, WAD	mg/L	0.2	0.0100	U	0.0100	U	0.0100
Manganese, Total	mg/L	0.775	3.63	4.11	3.59	3.89	3.67
<u>Natural Attenuation Parameters</u>							
Nitrate	mg/L	---	0.10	U,M1	0.10	U	0.100
Nitrite	mg/L	---	0.100	U	0.100	U	0.100
Ammonia	mg/L	---	2.23	2.26	2.14	2.22	na
Manganese, Dissolved	mg/L	---	3.64	3.51	3.76	3.99	na
Iron, Dissolved	mg/L	---	5.46	4.37	5.21	5.56	5.76
Sulfate	mg/L	---	31.4	34.4	36.5	36.8	na
Sulfide	mg/L	---	5.00	U	10.00	U	10
Methane	µg/L	---	74.6	21	28	31	na
Alkalinity, Total	mg/L	---	376	351	345	311	na
Total Kjeldahl Nitrogen	mg/L	---	2.90	2.85	2.85	2.4	na
Orthophosphate	mg/L	---	0.100	U	0.100	U	0.100
Total Organic Carbon	mg/L	---	2.65	na	2.32	ET	na
Chloride	mg/L	---	193	na	na	na	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW19-GW-0413 10-Apr-2013	DV	MW19-GW-1013 23-Oct-2013	DV	MW20-GW-001 02-Apr-2001	MW20-GW-003 10-Jul-2001	MW20-GW-004 12-Dec-2001	MW20-GW-005 18-Apr-2002	MW20-GW-1002 30-Oct-2002	MW20-GW-0103 09-Jan-2003
VOCs	Units										
Benzene	µg/L	5	977	J-	840	2300	2800	3000	3140	1.7	2000 J
Toluene	µg/L	1000	134		99.9	906	1130	1430	1270	0.79	1300 J
Ethylbenzene	µg/L	700	186		179	969	987	1220	1050	0.67	1300
Xylenes, Total	µg/L	10000	316		296	997	1010	1220	1170	0.78	450
PAHs											
Acenaphthene	µg/L	914	134		112	71.9	65.5	95.7	54.6	0.041	420 J
Acenaphthylene	µg/L	362	134		111	198	250	443	240	11 U	10 U
Anthracene	µg/L	---	9.27		5.31	10	U	5.91	10	U	7.8 6.4 J
Benzo(a)anthracene	µg/L	0.13	0.147		1.02	U	0.39	0.13	0.4	0.56	0.71 0.45 J
Benzo(a)pyrene	µg/L	0.2	0.100	U	1.02	U	0.22	0.10	U	0.17	0.22 0.34 0.18 J
Benzo(b)fluoranthene	µg/L	0.1	0.100	U	1.02	U	0.10	U	0.10	U	0.10 U 0.45 0.24 J
Benzo(ghi)perylene	µg/L	---	0.100	U	1.02	U	0.10	U	0.10	U	0.10 U 1.1 U 1.0 U
Benzo(k)fluoranthene	µg/L	0.14	0.100	U	1.02	U	0.10	U	0.10	U	0.10 U 1.1 U 1.0 U
Chrysene	µg/L	0.85	0.137		1.02	U	0.26	0.10	U	0.10	U 0.21 0.34 0.24 J
Dibeno(a,h)anthracene	µg/L	0.033	0.0173	U	0.173	U	0.10	U	0.10	U	0.10 U 1.1 U 1.0 U
Fluoranthene	µg/L	---	1.55		1.29		1.5		2.07	0.10	U 0.10 U 6.4 3.8 J
Fluorene	µg/L	490	31.7		25.8		56.9		58.3	74.3	64.7 29 41 J
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.100	U	1.02	U	0.10	U	0.1	U	0.10 U 1.1 U 1.0 U
Naphthalene	µg/L	1.1	400		352	B* J+B	1880	1940	3220	1830	2700 2700 J
Phenanthrene	µg/L	294	38.2		60.1		29.4		26.3	40.1	27.8 43 43 J
Pyrene	µg/L	---	1.59		1.83		0.19	U	0.19	U	1.52 3.8 2.1 J
1-Methylnaphthalene	µg/L	---	770		665		na	na	662	na	na na
2-Methylnaphthalene	µg/L	61.2	13.4		11.1		353		303	485	277 na na
Inorganics											
Cyanide, Total	mg/L	---	na		na		0.021	0.17	0.02	0.015	0.005 U 0.00574
Cyanide, WAD	mg/L	0.2	0.0100	U	0.0100	U	na	na	na	na	na na
Manganese, Total	mg/L	0.775	4.05		3.61		1.07	0.918	0.94	0.986	0.897 0.953
Natural Attenuation Parameters											
Nitrate	mg/L	---	0.100	U	na		1.0	U	1.0	U	na na na
Nitrite	mg/L	---	0.100	U	na		na	na	na	na	na na
Ammonia	mg/L	---	2.25		na		0.20	UJ	0.20	U	na na na
Manganese, Dissolved	mg/L	---	4.11		na		na	0.884	0.94	0.926	0.824 0.906
Iron, Dissolved	mg/L	---	5.56		na		na	14.9	15.5	16	14.6 15.8
Sulfate	mg/L	---	34.9		na		120	130	na	na	na na
Sulfide	mg/L	---	10.0	U	na		2.0	U	0.10	U	na na na
Methane	µg/L	---	28.8		na		na	na	na	na	na na
Alkalinity, Total	mg/L	---	365		na		na	na	na	na	na na
Total Kjeldahl Nitrogen	mg/L	---	2.83		na		na	na	na	na	na na
Orthophosphate	mg/L	---	0.100	U	na		na	na	na	na	na na
Total Organic Carbon	mg/L	---	na		na		na	na	na	na	na na
Chloride	mg/L	---	na		na		na	na	na	na	na na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW20-GW-1003 22-Oct-2003	MW20-GW-0404 08-Apr-2004	MW20-GW-1004 20-Oct-2004	MW20-GW-0405 14-Apr-2005	MW20-GW-1005 11-Oct-2005	MW20-GW-0406 12-Apr-2006	MW20-GW-1006 10-Oct-2006	MW20-GW-0407 17-Apr-2007
VOCs	Units								
Benzene	µg/L	5	2800	2800	1700	4700	2700	2830	2140
Toluene	µg/L	1000	1500	1400	920	3500	1500	1860	1180
Ethylbenzene	µg/L	700	1300	1300	830	1900	1200	1540	1170
Xylenes, Total	µg/L	10000	1400	1400	900	2500	1800	1730	1260
PAHs									
Acenaphthene	µg/L	914	96	140	100	120	160	205	141
Acenaphthylene	µg/L	362	2000	1900	1400	1900	1900	168	119
Anthracene	µg/L	---	7.0	5.6	5.4	6.7	17	38	5.75
Benzo(a)anthracene	µg/L	0.13	0.62	Ja	0.54	Ja	0.16	6.6	17
Benzo(a)pyrene	µg/L	0.2	1.4	Ua	0.37	Ja	1.3	U	0.018
Benzo(b)fluoranthene	µg/L	0.1	0.53	U	0.53	U	0.047	U	1.6
Benzo(ghi)perylene	µg/L	---	2.1	U	2.1	U	0.19	U	1.0
Benzo(k)fluoranthene	µg/L	0.14	0.53	U	0.53	U	0.047	U	0.90
Chrysene	µg/L	0.85	0.33	Ja	0.43	Ja	0.090	Ja	4.6
Dibenz(a,h)anthracene	µg/L	0.033	3.2	U	3.2	U	0.28	U	3.0
Fluoranthene	µg/L	---	7.2	7.0	5.5	6.3	23	42.6	4.42
Fluorene	µg/L	490	34	40	29	37	44	140	88.6
Indeno(1,2,3-cd)pyrene	µg/L	0.1	1.4	U	1.4	U	0.12	U	1.2
Naphthalene	µg/L	1.1	3800	3700	2400	3400	3400	3340	2640
Phenanthrene	µg/L	294	41	48	33	43	64	120	40.8
Pyrene	µg/L	---	2.6	Ua	2.3	Ja	0.72	13	234
1-MethylNaphthalene	µg/L	---	na						
2-MethylNaphthalene	µg/L	61.2	na	na	na	na	na	na	428
Inorganics									
Cyanide, Total	mg/L	---	0.011	0.0079	B	0.010	0.0099	B	0.0085
Cyanide, WAD	mg/L	0.2	na						
Manganese, Total	mg/L	0.775	1.2	0.88	0.79	0.78	0.89	1.18	na
Natural Attenuation Parameters									
Nitrate	mg/L	---	na	na	na	0.10	U	0.020	U
Nitrite	mg/L	---	na	na	na	0.020	U	0.020	U
Ammonia	mg/L	---	na	na	na	0.20	U	0.22	0.2
Manganese, Dissolved	mg/L	---	0.85	0.81	0.79	0.80	0.74	0.698	na
Iron, Dissolved	mg/L	---	15	15	14	15	14	13.4	na
Sulfate	mg/L	---	na	na	na	88	130	112	na
Sulfide	mg/L	---	na	na	na	1.0	U	0.90	B
Methane	µg/L	---	na	na	na	26	63	151	na
Alkalinity, Total	mg/L	---	na	na	na	430	380	456	na
Total Kjeldahl Nitrogen	mg/L	---	na	na	na	0.26	B	0.50	1
Orthophosphate	mg/L	---	na	na	na	0.019	B	0.050	U
Total Organic Carbon	mg/L	---	na	na	na	6.7	9.5	6.66	na
Chloride	mg/L	---	na	na	na	na	na	134	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW20-GW-1007 09-Oct-2007	MW20-GW-0408 15-Apr-2008	MW20-GW-0410 08-Apr-2010	DV	MW20-GW-1010 06-Oct-2010	MW20-GW-0411 12-Apr-2011	MW20-GW-1011 25-Oct-2011	DV	MW20-GW-0412 11-Apr-2012	DV	
VOCs												
Benzene	µg/L	5	1800	1920		549		637	919	1250	2490	
Toluene	µg/L	1000	1120	1070		272		247	353	361	846	
Ethylbenzene	µg/L	700	1100	1100	C9		J+	947	865	974	1180	
Xylenes, Total	µg/L	10000	1170	1240		929		1010	1160	1090	1190	
PAHs												
Acenaphthene	µg/L	914	149	123		79.5	RL1	92.9	94.0	39.3	J-	
Acenaphthylene	µg/L	362	301	77.1		82.5	RL1	133	96.9	91.9	J-	
Anthracene	µg/L	---	5.67	6.07		10.0	U,RL1	8.98	7.13	6.51	J- 2.37 RL1 J-	
Benzo(a)anthracene	µg/L	0.13	0.22	0.348		10.0	U,RL1	0.161	0.100 U	1.00 U	UJ 1.00 U,RL1 UJ	
Benzo(a)pyrene	µg/L	0.2	0.156	J	0.304	10.0	U,RL1	0.100 U	0.100 U	1.00 U	UJ 1.00 U,RL1 UJ	
Benzo(b)fluoranthene	µg/L	0.1	0.013	U	0.203	10.0	U,RL1	0.100 U	0.100 U	1.00 U	UJ 1.00 U,RL1 UJ	
Benzo(ghi)perylene	µg/L	---	1.18	0.137		10.0	U,RL1	0.100 U	0.100 U	1.00 U	UJ 1.00 U,RL1 UJ	
Benzo(k)fluoranthene	µg/L	0.14	0.015	U	0.015	U	10.0	U,RL1	0.100 U	0.100 U	1.00 U	UJ 1.00 U,RL1 UJ
Chrysene	µg/L	0.85	0.18	0.0649	J	10.0	U,RL1	0.140	0.100 U	1.00 U	UJ 1.00 U,RL1 UJ	
Dibenzo(a,h)anthracene	µg/L	0.033	0.01	U	0.01	U	0.81	U,RL1,MDL	0.00810 U,MDL	0.0170 U,MDL	0.276 J,MDL J-	
Fluoranthene	µg/L	---	2.14	3.87		10	U,RL1	3.25	1.37	2.23	J- 1.14 RL1 J-	
Fluorene	µg/L	490	152	88.2		41.1	RL1	49.8	48.5	19.6	J- 30.6 RL1 J-	
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.007	U	0.14	10.0	U,RL1	0.100 U	0.100 U	1.00 U	UJ 1.00 U,RL1 UJ	
Naphthalene	µg/L	1.1	3210	2180		1940	RL1	2100	1890	1690	J- 1510 B1 B J-	
Phenanthrene	µg/L	294	42.7	44.4		42.4	RL1	42.2	37.4	22.9	J- 28.4 RL1 J-	
Pyrene	µg/L	---	13	0.019	U	10.0	U,RL1	2.52	1.48	3.77	J- 1.23 RL1 J-	
1-Methylnaphthalene	µg/L	---	na	na		457	RL1	637	497	430	J- 328 RL1 J-	
2-Methylnaphthalene	µg/L	61.2	482	362		154	RL1	164	146	158	J- 176 RL1 J-	
Inorganics												
Cyanide, Total	mg/L	---	0.0109	0.01	U	na		na	na	na		
Cyanide, WAD	mg/L	0.2	na	na		0.0100 U		0.0100 U	0.0100 U	0.0100 U		
Manganese, Total	mg/L	0.775	na	na		0.592		0.557	0.616	0.581	0.584	
Natural Attenuation Parameters												
Nitrate	mg/L	---	na	na		na		na	na	na		
Nitrite	mg/L	---	na	na		na		na	na	na		
Ammonia	mg/L	---	na	na		na		na	na	na		
Manganese, Dissolved	mg/L	---	na	na		na		na	na	na		
Iron, Dissolved-	mg/L	---	na	na		na		na	na	na		
Sulfate	mg/L	---	na	na		na		na	na	na		
Sulfide	mg/L	---	na	na		na		na	na	na		
Methane	µg/L	---	na	na		na		na	na	na		
Alkalinity, Total	mg/L	---	na	na		na		na	na	na		
Total Kjeldahl Nitrogen	mg/L	---	na	na		na		na	na	na		
Orthophosphate	mg/L	---	na	na		na		na	na	na		
Total Organic Carbon	mg/L	---	na	na		na		na	na	na		
Chloride	mg/L	---	na	na		na		na	na	na		

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW20-GW-1012 10-Oct-2012	MW20-GW-0413 10-Apr-2013	MW20-GW-1013 23-Oct-2013	MW23-GW-005 17-Apr-2002	MW23-GW-1002 31-Oct-2002	MW23-GW-0103 08-Jan-2003	MW23-GW-1003 21-Oct-2003	MW23-GW-0404 06-Apr-2004
		DV	DV	DV					
VOCs									
Benzene	µg/L	5	3640		2770	14.1	10	16	22
Toluene	µg/L	1000	1360	1440	1320	1.0	U	1.0	U
Ethylbenzene	µg/L	700	1600	1510	1460	1.0	U	2.0	4.1
Xylenes, Total	µg/L	10000	1620	1610	1530	6.9	7.9	11	8.8
PAHs									
Acenaphthene	µg/L	914	75.0	J-	143	J+	88.3	J-	0.19
Acenaphthylene	µg/L	362	40.2	J-	50.5	J+	40.4	J-	52.6
Anthracene	µg/L	---	1.77	J-	29.6	U	2.38	J-	0.26
Benzo(a)anthracene	µg/L	0.13	0.111	J-	12.2	U	1.02	U UJ	0.19
Benzo(a)pyrene	µg/L	0.2	0.100	U	UJ	14.3	U	1.02	U UJ
Benzo(b)fluoranthene	µg/L	0.1	0.100	U	UJ	27.6	U	1.02	U UJ
Benzo(ghi)perylene	µg/L	---	0.100	U	UJ	17.3	U	1.02	U UJ
Benzo(k)fluoranthene	µg/L	0.14	0.100	U	UJ	18.4	U	1.02	U UJ
Chrysene	µg/L	0.85	0.100	U	UJ	11.2	U	1.02	U UJ
Dibenz(a,h)anthracene	µg/L	0.033	0.0130	U,MDL	UJ	17.3	U	0.173	U UJ
Fluoranthene	µg/L	---	1.14	J-	50	U	1.02	U UJ	0.19
Fluorene	µg/L	490	26.1	J-	47.7	J+	29.3	J-	7.38
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.100	U	UJ	17.3	U	1.02	U UJ
Naphthalene	µg/L	1.1	2380	J-	3870	B	B,J+,B	2290	B* J-,J+,B
Phenanthrene	µg/L	294	19.3	J-	43.5	J+	32.1	J-	2.88
Pyrene	µg/L	---	1.23	J-	56.1	U	1.09	J-	0.19
1-Methylnaphthalene	µg/L	---	371	J-	604	J+	412	J-	14.4
2-Methylnaphthalene	µg/L	61.2	262	J-	505	J+	307	J-	0.19
Inorganics									
Cyanide, Total	mg/L	---	na		na		0.010	U	0.005
Cyanide, WAD	mg/L	0.2	0.0100	U	0.189	0.0100	U	na	na
Manganese, Total	mg/L	0.775	0.607		0.587	0.603	0.302	0.299	0.309
Natural Attenuation Parameters									
Nitrate	mg/L	---	na		na		na		na
Nitrite	mg/L	---	na		na		na		na
Ammonia	mg/L	---	na		na		na		na
Manganese, Dissolved	mg/L	---	na		na		0.295	0.272	0.296
Iron, Dissolved	mg/L	---	na		na		4	3.63	4.61
Sulfate	mg/L	---	na		na		na		na
Sulfide	mg/L	---	na		na		na		na
Methane	µg/L	---	na		na		na		na
Alkalinity, Total	mg/L	---	na		na		na		na
Total Kjeldahl Nitrogen	mg/L	---	na		na		na		na
Orthophosphate	mg/L	---	na		na		na		na
Total Organic Carbon	mg/L	---	na		na		na		na
Chloride	mg/L	---	na		na		na		na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW23-GW-1004 20-Oct-2004	MW23-GW-0405 15-Apr-2005	MW23-GW-1005 11-Oct-2005	MW23-GW-0406 11-Apr-2006	MW23-GW-1006 11-Oct-2006	MW23-GW-0407 18-Apr-2007	MW23-GW-1007 10-Oct-2007	MW23-GW-0408 16-Apr-2008
VOCs									
Benzene	µg/L	5	21	22	21	8.7	5.91	9.25	13.3
Toluene	µg/L	1000	1	U	1.0	U*	1	U	1
Ethylbenzene	µg/L	700	1	U	1.0	U*	1	U	1
Xylenes, Total	µg/L	10000	7.4	8.2	*	5.9	7.12	6.08	5.84
PAHs									
Acenaphthene	µg/L	914	25	36	32	27.3	24.7	21.3	28.2
Acenaphthylene	µg/L	362	240	340	270	48.1	41.6	38.9	35.8
Anthracene	µg/L	---	0.47	0.72	0.40	0.0106	U	0.706	0.592
Benzo(a)anthracene	µg/L	0.13	0.13	U	0.12	U	0.0216	U	0.003
Benzo(a)pyrene	µg/L	0.2	0.13	U	0.12	U	0.0216	U	0.032
Benzo(b)fluoranthene	µg/L	0.1	0.050	U	0.047	U	0.046	U	0.013
Benzo(ghi)perylene	µg/L	---	0.20	U	0.19	U	0.0364	U	0.009
Benzo(k)fluoranthene	µg/L	0.14	0.050	U	0.047	U	0.046	U	0.015
Chrysene	µg/L	0.85	0.13	U	0.12	U	0.0227	U	0.005
Dibenz(a,h)anthracene	µg/L	0.033	0.30	U	0.28	U	0.0375	U	0.01
Fluoranthene	µg/L	---	0.73	1.1	0.63	0.0364	U	0.603	0.466
Fluorene	µg/L	490	9.6	14	10	24.8	24	19.7	37.3
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.13	U	0.12	U	0.0432	U	0.007
Naphthalene	µg/L	1.1	1.3	U	1.2	U	1.04	1.34	1.6
Phenanthrene	µg/L	294	6.6	10	5.9	8.74	7.94	6.8	8.41
Pyrene	µg/L	---	0.25	U	0.23	U	3.44	2.62	2.21
1-Methylnaphthalene	µg/L	---	na						
2-Methylnaphthalene	µg/L	61.2	na	na	na	na	0.513	0.378	0.052
Inorganics									
Cyanide, Total	mg/L	---	0.01	U	0.0027	B	0.0027	B	0.01
Cyanide, WAD	mg/L	0.2	na						
Manganese, Total	mg/L	0.775	0.35	0.29	0.54	0.257	na	na	na
Natural Attenuation Parameters									
Nitrate	mg/L	---	na						
Nitrite	mg/L	---	na						
Ammonia	mg/L	---	na						
Manganese, Dissolved	mg/L	---	0.29	0.30	0.28	0.294	na	na	na
Iron, Dissolved	mg/L	---	3.7	3.8	0.17	4.29	na	na	na
Sulfate	mg/L	---	na						
Sulfide	mg/L	---	na						
Methane	µg/L	---	na						
Alkalinity, Total	mg/L	---	na						
Total Kjeldahl Nitrogen	mg/L	---	na						
Orthophosphate	mg/L	---	na						
Total Organic Carbon	mg/L	---	na						
Chloride	mg/L	---	na						

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW23-GW-0410 08-Apr-2010	DUP2-GW-0410 08-Apr-2010	MW23-GW-1010 05-Oct-2010	MW23-GW-0411 12-Apr-2011	MW23-GW-1011 24-Oct-2011	MW23-GW-0412 11-Apr-2012	MW23-GW-1012 09-Oct-2012
						DV	DV	
VOCs								
Benzene	µg/L	5	11.4	13.2	13.2	15.3	16.8	10.8
Toluene	µg/L	1000	1.00 U					
Ethylbenzene	µg/L	700	1.00 U,C9	1.00 U,C9	1.00 U	1.00 U	1.00 U	1.00 U
Xylenes, Total	µg/L	10000	6.00 U	6.00 U	4.11	5.22	4.44	4.43
PAHs								
Acenaphthene	µg/L	914	19.3	21.4	17.7	22.5	9.14	J- 16.5
Acenaphthylene	µg/L	362	39.2	45.0	34.1	41.0	31.6	J- 30.5
Anthracene	µg/L	---	0.778	0.705	0.479	0.485	0.252	J- 0.225
Benzo(a)anthracene	µg/L	0.13	0.100 U	UJ 0.100 U				
Benzo(a)pyrene	µg/L	0.2	0.100 U	UJ 0.100 U				
Benzo(b)fluoranthene	µg/L	0.1	0.100 U	UJ 0.100 U				
Benzo(ghi)perylene	µg/L	---	0.100 U	UJ 0.100 U				
Benzo(k)fluoranthene	µg/L	0.14	0.100 U	UJ 0.100 U				
Chrysene	µg/L	0.85	0.100 U	UJ 0.100 U				
Dibenzo(a,h)anthracene	µg/L	0.033	0.00810 U,MDL	0.00810 U,MDL	0.00810 U,MDL	0.0170 U,MDL	0.0170 U,MDL	UJ 0.0170 U,MDL
Fluoranthene	µg/L	---	0.425	0.430	0.299	0.400	0.247	J- 0.208
Fluorene	µg/L	490	13.1	15.4	11.5	14.2	5.43	J- 9.75
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.100 U	0.100 U	0.100 U	0.100 U	UJ 0.100 U	UJ 0.100 U
Naphthalene	µg/L	1.1	0.701	0.614	0.407	0.449	0.514	J- 0.491 B
Phenanthrene	µg/L	294	8.66	11.6	8.18	8.68	7.37	J- 5.55
Pyrene	µg/L	---	0.311	0.299	0.327	0.428	0.253	J- 0.229
1-MethylNaphthalene	µg/L	---	1.86	1.56	1.25	1.34	0.934	J- 0.933
2-MethylNaphthalene	µg/L	61.2	0.100 U	UJ 0.100 U				
Inorganics								
Cyanide, Total	mg/L	---	na	na	na	na	na	na
Cyanide, WAD	mg/L	0.2	0.0100 U	0.01 U	0.0100 U	0.0100 U	0.0100 U	0.0100 U
Manganese, Total	mg/L	0.775	0.323	0.325	0.464	0.397	0.316	0.339
Natural Attenuation Parameters								
Nitrate	mg/L	---	na	na	na	na	na	na
Nitrite	mg/L	---	na	na	na	na	na	na
Ammonia	mg/L	---	na	na	na	na	na	na
Manganese, Dissolved	mg/L	---	na	na	na	na	na	na
Iron, Dissolved	mg/L	---	na	na	na	na	na	na
Sulfate	mg/L	---	na	na	na	na	na	na
Sulfide	mg/L	---	na	na	na	na	na	na
Methane	µg/L	---	na	na	na	na	na	na
Alkalinity, Total	mg/L	---	na	na	na	na	na	na
Total Kjeldahl Nitrogen	mg/L	---	na	na	na	na	na	na
Orthophosphate	mg/L	---	na	na	na	na	na	na
Total Organic Carbon	mg/L	---	na	na	na	na	na	na
Chloride	mg/L	---	na	na	na	na	na	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW23-GW-0413 10-Apr-2013 DV	MW23-GW-1013 22-Oct-2013 DV	MW25-GW-005 17-Apr-2002 DV	MW25-GW-1002 29-Oct-2002	MW25-GW-0103 08-Jan-2003	MW25-GW-1003 21-Oct-2003	MW25-GW-0404 06-Apr-2004	MW25-GW-1004 20-Oct-2004
VOCs									
Benzene	µg/L	5	5.35	8.41	39.9	19	31	5.9	2.2
Toluene	µg/L	1000	1.00	U	1.0	U	2.0	U	1.0
Ethylbenzene	µg/L	700	1.00	U	1.0	U	2.0	U	1.0
Xylenes, Total	µg/L	10000	4.11	3.72	6.4	J	7	U	3.0
PAHs									
Acenaphthene	µg/L	914	24.1	17	3.81	J	6.4	9.0	4.4
Acenaphthylene	µg/L	362	39.9	24.6	7.4	J	1	U	53
Anthracene	µg/L	---	0.336	0.206	0.19	U	0.051	U	0.049
Benzo(a)anthracene	µg/L	0.13	0.121	U	0.100	U	0.1	U	0.13
Benzo(a)pyrene	µg/L	0.2	0.141	U	0.100	U	0.19	U	0.13
Benzo(b)fluoranthene	µg/L	0.1	0.273	U	0.100	U	0.10	U	0.049
Benzo(ghi)perylene	µg/L	---	0.172	U	0.100	U	0.10	U	0.19
Benzo(k)fluoranthene	µg/L	0.14	0.182	U	0.100	U	0.10	U	0.049
Chrysene	µg/L	0.85	0.111	U	0.100	U	0.10	U	0.13
Dibenz(a,h)anthracene	µg/L	0.033	0.172	U	0.0173	U	0.10	U	0.29
Fluoranthene	µg/L	---	0.495	U	0.223	U	0.19	U	0.13
Fluorene	µg/L	490	15.4	9.47	0.19	U	0.1	U	0.25
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.172	U	0.100	U	0.10	U	0.13
Naphthalene	µg/L	1.1	0.923	B	UB	0.451	0.10	U	0.8
Phenanthrene	µg/L	294	10.2	4.02	0.10	U	0.10	U	1.3
Pyrene	µg/L	---	0.556	U	0.236	U	0.19	U	0.14
1-Methylnaphthalene	µg/L	---	1.33	U	0.841	U	na	U	na
2-Methylnaphthalene	µg/L	61.2	0.118	U	0.100	U	0.19	U	na
Inorganics									
Cyanide, Total	mg/L	---	na	na	0.010	U	0.005	U	0.009
Cyanide, WAD	mg/L	0.2	0.0100	U	0.0100	U	na	U	na
Manganese, Total	mg/L	0.775	0.318	J-	0.303	U	0.406	U	0.41
Natural Attenuation Parameters									
Nitrate	mg/L	---	na	na	na	na	na	na	na
Nitrite	mg/L	---	na	na	na	na	na	na	na
Ammonia	mg/L	---	na	na	na	na	na	na	na
Manganese, Dissolved	mg/L	---	na	na	0.382	0.488	0.41	0.38	0.38
Iron, Dissolved	mg/L	---	na	na	3.7	3.84	3.92	3.3	3.2
Sulfate	mg/L	---	na	na	na	na	na	na	na
Sulfide	mg/L	---	na	na	na	na	na	na	na
Methane	µg/L	---	na	na	na	na	na	na	na
Alkalinity, Total	mg/L	---	na	na	na	na	na	na	na
Total Kjeldahl Nitrogen	mg/L	---	na	na	na	na	na	na	na
Orthophosphate	mg/L	---	na	na	na	na	na	na	na
Total Organic Carbon	mg/L	---	na	na	na	na	na	na	na
Chloride	mg/L	---	na	na	na	na	na	na	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW25-GW-0405 14-Apr-2005	MW25-GW-1005 11-Oct-2005	MW25-GW-0406 13-Apr-2006	MW25-GW-1006 11-Oct-2006	MW25-GW-0407 18-Apr-2007	MW25-GW-1007 10-Oct-2007	MW25-GW-0408 15-Apr-2008
<u>VOCs</u>								
Benzene	µg/L	5	11	1.8	25.8	10.7	27	14.4
Toluene	µg/L	1000	1.0	U	1	U	1	U
Ethylbenzene	µg/L	700	1.0	U	1	U	1	U
Xylenes, Total	µg/L	10000	2.3	1.1	J	7.81	5.15	4.39
<u>PAHs</u>								
Acenaphthene	µg/L	914	6.2	5.2	7.58	8.71	7.32	12.5
Acenaphthylene	µg/L	362	57	48	13.5	16.5	12.2	0.085
Anthracene	µg/L	---	0.047	Ua	0.051	U	0.0395	J
Benzo(a)anthracene	µg/L	0.13	0.12	U	0.13	U	0.019	U
Benzo(a)pyrene	µg/L	0.2	0.12	U	0.13	U	0.019	U
Benzo(b)fluoranthene	µg/L	0.1	0.047	U	0.051	U	0.037	U
Benzo(ghi)perylene	µg/L	---	0.19	U	0.20	U	0.032	U
Benzo(k)fluoranthene	µg/L	0.14	0.047	U	0.051	U	0.023	U
Chrysene	µg/L	0.85	0.12	U	0.13	U	0.02	U
Dibenz(a,h)anthracene	µg/L	0.033	0.28	U	0.30	U	0.033	U
Fluoranthene	µg/L	---	0.12	U	0.13	U	0.032	U
Fluorene	µg/L	490	0.37	0.29	2.77	3.31	2.79	10.6
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.12	U	0.13	U	0.038	U
Naphthalene	µg/L	1.1	1.2	U	1.3	U	0.401	U
Phenanthrene	µg/L	294	0.093	U	0.10	U	0.161	U
Pyrene	µg/L	---	0.23	Ua	0.25	U	0.036	U
1-Methylnaphthalene	µg/L	---	na	na	na	na	na	na
2-Methylnaphthalene	µg/L	61.2	na	na	na	0.171	J	0.17
<u>Inorganics</u>								
Cyanide, Total	mg/L	---	0.010	U	0.010	U	0.01	U
Cyanide, WAD	mg/L	0.2	na	na	na	na	na	na
Manganese, Total	mg/L	0.775	0.42	0.40	0.305	na	na	na
<u>Natural Attenuation Parameters</u>								
Nitrate	mg/L	---	0.10	U	0.10	U	0.1	U
Nitrite	mg/L	---	0.020	U	0.020	U	0.1	U
Ammonia	mg/L	---	0.15	B	0.20	U	0.2	U
Manganese, Dissolved	mg/L	---	0.39	0.37	0.336	na	na	na
Iron, Dissolved	mg/L	---	2.7	3.0	2.89	na	na	na
Sulfate	mg/L	---	120	120	112	M1	na	na
Sulfide	mg/L	---	1.0	U	1	U	na	na
Methane	µg/L	---	4	4.2	26	U	na	na
Alkalinity, Total	mg/L	---	360	330	385	na	na	na
Total Kjeldahl Nitrogen	mg/L	---	0.18	B	0.17	B	1	U
Orthophosphate	mg/L	---	0.008	B	0.050	U	0.1	U
Total Organic Carbon	mg/L	---	1.4	1.5	1.42	na	na	na
Chloride	mg/L	---	na	na	99.4	M1	na	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW25-GW-0410 08-Apr-2010	MW25-GW-1010 05-Oct-2010	MW25-GW-0411 12-Apr-2011	MW25-GW-1011 25-Oct-2011	DP02-GW-1011 25-Oct-2011	MW25-GW-0412 10-Apr-2012	DP01-GW-0412 10-Apr-2012
					DV	DV	DV	DV
VOCs								
Benzene	µg/L	5	139	131	46.4	88.6	88.4	82.2
Toluene	µg/L	1000	1.76	1.00 U				
Ethylbenzene	µg/L	700	1.72	1.00 U				
Xylenes, Total	µg/L	10000	19.2	13.2	4.32	3.41	3.01	3.00 U
PAHs								
Acenaphthene	µg/L	914	18.5	16.6	10.1	8.95	J- 8.94	J- 6.19
Acenaphthylene	µg/L	362	22.1	18.3	9.94	9.21	J- 9.50	J- 6.56
Anthracene	µg/L	---	0.359	0.322	0.118	0.100 U	UJ 0.100 U	UJ 0.100 U
Benzo(a)anthracene	µg/L	0.13	0.100 U	0.100 U	0.100 U	0.100 U	UJ 0.100 U	UJ 0.100 U
Benzo(a)pyrene	µg/L	0.2	0.100 U	0.100 U	0.100 U	0.100 U	UJ 0.100 U	UJ 0.100 U
Benzo(b)fluoranthene	µg/L	0.1	0.100 U	0.100 U	0.100 U	0.100 U	UJ 0.100 U	UJ 0.100 U
Benzo(ghi)perylene	µg/L	---	0.100 U	0.100 U	0.100 U	0.100 U	UJ 0.100 U	UJ 0.100 U
Benzo(k)fluoranthene	µg/L	0.14	0.100 U	0.100 U	0.100 U	0.100 U	UJ 0.100 U	UJ 0.100 U
Chrysene	µg/L	0.85	0.100 U	0.100 U	0.100 U	0.100 U	UJ 0.100 U	UJ 0.100 U
Dibenz(a,h)anthracene	µg/L	0.033	0.00810	U,MDL	0.00810	U,MDL	0.0170 U,MDL	UJ 0.0170 U,MDL
Fluoranthene	µg/L	---	0.150	0.163	0.123	0.100 U	UJ 0.100 U	UJ 0.100 U
Fluorene	µg/L	490	4.64	5.09	2.35	1.56	J- 1.60	J- 0.804
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.100 U	0.100 U	0.100 U	0.100 U	UJ 0.100 U	UJ 0.100 U
Naphthalene	µg/L	1.1	1.87	0.738	0.789	0.240	J- 0.162	J- 0.12
Phenanthrene	µg/L	294	2.70	2.59	1.74	1.19	J- 1.25	J- 0.381
Pyrene	µg/L	---	0.112	0.183	0.145	0.100 U	UJ 0.100 U	UJ 0.100 U
1-Methylnaphthalene	µg/L	---	26.3	18.0	2.2	0.938	J- 0.863	J- 0.332
2-Methylnaphthalene	µg/L	61.2	0.100 U	0.100 U	0.100 U	0.100 U	UJ 0.100 U	J- 0.426
Inorganics								
Cyanide, Total	mg/L	---	na	na	na	na	na	na
Cyanide, WAD	mg/L	0.2	0.0100 U					
Manganese, Total	mg/L	0.775	0.354	0.336	0.373	0.315	0.312	0.325 R
Natural Attenuation Parameters								
Nitrate	mg/L	---	0.10 U	0.10 U	0.10 U	0.10 U	0.100 U	0.100 U
Nitrite	mg/L	---	0.100 U	0.100 U,H				
Ammonia	mg/L	---	0.200 U					
Manganese, Dissolved	mg/L	---	0.343	0.324	0.317	0.333	0.328	0.311
Iron, Dissolved	mg/L	---	2.76	2.78	2.54	2.81	2.82	2.68
Sulfate	mg/L	---	81.4	81.4	103	91.6	36.8	86.8
Sulfide	mg/L	---	5.00 U	5.00 U	10.00 U	10 U	10 U	10 U
Methane	µg/L	---	43.0	39.8	10	16	14	31
Alkalinity, Total	mg/L	---	394	371	341	340	336	321
Total Kjeldahl Nitrogen	mg/L	---	1.00 U					
Orthophosphate	mg/L	---	0.100 U					
Total Organic Carbon	mg/L	---	1.00 U	1.00 U	na	1.00 U,ET	1.00 U,ET	na
Chloride	mg/L	---	83.5	89.1	na	na	na	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW25-GW-1012 10-Oct-2012	DP02-GW-1012 10-Oct-2012	MW25-GW-0413 10-Apr-2013	DP02-GW-0413 10-Apr-2013	MW25-GW-1013 23-Oct-2013	DP02-GW-1013 23-Oct-2013
		DV		DV		DV	
VOCs							
Benzene	µg/L	5	120	126	1140	J-	10.3
Toluene	µg/L	1000	1.00 U	1.00 U	161	U	1.00 U
Ethylbenzene	µg/L	700	1.00 U	1.00 U	22.4	U	1.85
Xylenes, Total	µg/L	10000	4.65	4.95	317	U	5.24
PAHs							
Acenaphthene	µg/L	914	8.33	8.64	10.1	U	10.8
Acenaphthylene	µg/L	362	11.2	11.6	8.56	U	11
Anthracene	µg/L	---	0.100 U	0.100 U	0.100 U	U	0.100 U
Benzo(a)anthracene	µg/L	0.13	0.100 U	0.100 U	0.100 U	U	0.100 U
Benzo(a)pyrene	µg/L	0.2	0.100 U	0.100 U	0.100 U	U	0.100 U
Benzo(b)fluoranthene	µg/L	0.1	0.100 U	0.100 U	0.100 U	U	0.100 U
Benzo(ghi)perylene	µg/L	---	0.100 U	0.100 U	0.100 U	U	0.100 U
Benzo(k)fluoranthene	µg/L	0.14	0.100 U	0.100 U	0.100 U	U	0.100 U
Chrysene	µg/L	0.85	0.100 U	0.100 U	0.100 U	U	0.100 U
Dibenz(a,h)anthracene	µg/L	0.033	0.0130 U,MDL	0.0130 U,MDL	0.0173 U	U	0.0179 U
Fluoranthene	µg/L	---	0.100 U	0.100 U	0.100 U	U	0.100 U
Fluorene	µg/L	490	0.795	0.882	0.807	U	0.77
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.100 U	0.100 U	0.100 U	U	0.100 U
Naphthalene	µg/L	1.1	0.185	0.220	0.989	U	0.218
Phenanthrene	µg/L	294	0.331	0.400	0.158	U	0.107
Pyrene	µg/L	---	0.100 U	0.100 U	0.100 U	U	0.100 U
1-Methylnaphthalene	µg/L	---	0.479	0.542	1.60	U	0.756
2-Methylnaphthalene	µg/L	61.2	0.100 U	0.225	0.100 U	U	0.100 U
Inorganics							
Cyanide, Total	mg/L	---	na	na	na	U	na
Cyanide, WAD	mg/L	0.2	0.0100 U	0.0100 U	0.0100 U	U	0.0100 U
Manganese, Total	mg/L	0.775	0.343	0.332	0.343	U	0.355
Natural Attenuation Parameters							
Nitrate	mg/L	---	0.100 U	0.100 U	0.100 U	U	na
Nitrite	mg/L	---	0.100 U	0.100 U	0.100 U	U	na
Ammonia	mg/L	---	0.200 U	0.200 U	0.200 U	U	na
Manganese, Dissolved	mg/L	---	0.318	0.326	0.353	U	0.36
Iron; Dissolved	mg/L	---	2.81	2.85	3.030	U	2.980
Sulfate	mg/L	---	80.7	82.6	92.2	U	92.7
Sulfide	mg/L	---	10 U	10 U	16.9	U	20.9
Methane	µg/L	---	28	28	5.65	U	8.01
Alkalinity, Total	mg/L	---	355	350	365	U	na
Total Kjeldahl Nitrogen	mg/L	---	1.00 U	1.00 U	1.00 U	U	na
Orthophosphate	mg/L	---	0.100 U	0.100 U	0.100 U	U	na
Total Organic Carbon	mg/L	---	na	na	na	U	na
Chloride	mg/L	---	na	na	na	U	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW29-GW-1002 28-Oct-2002	MW29-GW-0103 07-Jan-2003	MW29-GW-1003 20-Oct-2003	MW29-GW-0404 07-Apr-2004	MW29-GW-1004 18-Oct-2004	MW29-GW-0405 14-Apr-2005	MW29-GW-1005 11-Oct-2005	MW29-GW-0406 12-Apr-2006
VOCS									
Benzene	µg/L	5	2	U	1.0	U	1.0	U	1.0
Toluene	µg/L	1000	2	U	1.0	U	1.0	U	1.0
Ethylbenzene	µg/L	700	2	U	1.0	U	1.0	U	1
Xylenes, Total	µg/L	10000	7	U	3.0	U	1.0	U	2.0
PAHs									
Acenaphthene	µg/L	914	0.52	U	0.54	U	2.6	U	2.4
Acenaphthylene	µg/L	362	1	U	1.1	U	1.3	U	1.2
Anthracene	µg/L	---	0.052	U	0.054	U	0.051	U*	0.047
Benzo(a)anthracene	µg/L	0.13	0.1	U	0.11	U	0.13	U	0.12
Benzo(a)pyrene	µg/L	0.2	0.1	U	0.11	U	0.13	U	0.12
Benzo(b)fluoranthene	µg/L	0.1	0.1	U	0.11	U	0.051	U	0.047
Benzo(ghi)perylene	µg/L	---	0.1	U	0.11	U	0.20	U	0.19
Benzo(k)fluoranthene	µg/L	0.14	0.1	U	0.11	U	0.051	U	0.047
Chrysene	µg/L	0.85	0.1	U	0.11	U	0.13	U	0.12
Dibenzo(a,h)anthracene	µg/L	0.033	0.1	U	0.11	U	0.31	U	0.28
Fluoranthene	µg/L	---	0.1	U	0.11	U	0.13	U	0.12
Fluorene	µg/L	490	0.1	U	0.11	U	0.26	U	0.24
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.1	U	0.11	U	0.13	U	0.12
Naphthalene	µg/L	1.1	0.52	U	0.54	U	1.3	U	1.2
Phenanthrene	µg/L	294	0.1	U	0.11	U	0.10	U	0.094
Pyrene	µg/L	---	0.1	U	0.11	U	0.26	U	0.24
1-Methylnaphthalene	µg/L	---	na						
2-Methylnaphthalene	µg/L	61.2	na						
Inorganics									
Cyanide, Total	mg/L	---	0.005	U	0.00500	U	0.010	U	0.010
Cyanide, WAD	mg/L	0.2	na						
Manganese, Total	mg/L	0.775	0.19	---	0.0871	0.17	0.065	0.10	0.050
Natural Attenuation Parameters									
Nitrate	mg/L	---	na	na	na	na	na	0.10	U
Nitrite	mg/L	---	na	na	na	na	na	0.020	U
Ammonia	mg/L	---	na	na	na	na	na	0.45	0.27
Manganese, Dissolved	mg/L	---	0.0541	---	0.0445	0.043	0.044	0.040	0.041
Iron, Dissolved	mg/L	---	0.807	---	1.16	1.1	1.2	1.1	1.0
Sulfate	mg/L	---	na	na	na	na	na	110	120
Sulfide	mg/L	---	na	na	na	na	na	1.0	U
Methane	µg/L	---	na	na	na	na	na	2	2
Alkalinity, Total	mg/L	---	na	na	na	na	na	330	320
Total Kjeldahl Nitrogen	mg/L	---	na	na	na	na	na	0.43	0.71
Orthophosphate	mg/L	---	na	na	na	na	na	0.011	B
Total Organic Carbon	mg/L	---	na	na	na	na	na	1.3	1.4
Chloride	mg/L	---	na	na	na	na	na	na	24.8

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW29-GW-1006 11-Oct-2006	MW29-GW-0407 17-Apr-2007	MW29-GW-1007 09-Oct-2007	MW29-GW-0408 14-Apr-2008	MW29-GW-0410 08-Apr-2010	MW29-GW-0411 12-Apr-2011	MW29-GW-0412 11-Apr-2012	MW29-GW-0413 09-Apr-2013
VOCs									
Benzene	µg/L	5	1	U	1	U	1	U	0.500
Toluene	µg/L	1000	1	U	1	U	1	U	1.00
Ethylbenzene	µg/L	700	1	U	1	U	1	U	1.00
Xylenes, Total	µg/L	10000	3	U	3	U	3	U	3.00
PAHs									
Acenaphthene	µg/L	914	0.049	U	0.049	U	0.049	U	0.100
Acenaphthylene	µg/L	362	0.085	U	0.085	U	0.085	U	0.100
Anthracene	µg/L	---	0.01	U	0.01	U	0.01	U	0.100
Benzo(a)anthracene	µg/L	0.13	0.003	U	0.003	U	0.003	U	0.100
Benzo(a)pyrene	µg/L	0.2	0.032	U	0.032	U	0.032	U	0.100
Benzo(b)fluoranthene	µg/L	0.1	0.013	U	0.013	U	0.013	U	0.100
Benzo(ghi)perylene	µg/L	---	0.009	U	0.009	U	0.009	U	0.100
Benzo(k)fluoranthene	µg/L	0.14	0.015	U	0.015	U	0.015	U	0.100
Chrysene	µg/L	0.85	0.005	U	0.005	U	0.005	U	0.100
Dibenz(a,h)anthracene	µg/L	0.033	0.01	U	0.01	U	0.01	U	0.0183
Fluoranthene	µg/L	---	0.01	U	0.01	U	0.01	U	0.100
Fluorene	µg/L	490	0.01	U	0.01	U	0.01	U	0.100
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.007	U	0.007	U	0.007	U	0.100
Naphthalene	µg/L	1.1	1.37	U	0.054	U	0.054	U	0.100
Phenanthrene	µg/L	294	0.007	U	0.007	U	0.007	U	0.100
Pyrene	µg/L	---	0.019	U	0.019	J	0.019	U	0.100
1-Methylnaphthalene	µg/L	---	na	na	na	na	0.100	U	0.100
2-Methylnaphthalene	µg/L	61.2	0.129	J	0.052	U	0.052	U	0.100
Inorganics									
Cyanide, Total	mg/L	---	0.01	U	0.01	U	0.01	U	na
Cyanide, WAD	mg/L	0.2	na	na	na	na	0.0100	U	0.0100
Manganese, Total	mg/L	0.775	na	na	na	na	0.0444	U	0.0942
Natural Attenuation Parameters									
Nitrate	mg/L	---	na	na	na	na	0.10	U,R	0.100
Nitrite	mg/L	---	na	na	na	na	0.100	U	0.100
Ammonia	mg/L	---	na	na	na	na	0.322	U	0.35
Manganese, Dissolved	mg/L	---	na	na	na	na	0.0381	U	0.338
Iron, Dissolved	mg/L	---	na	na	na	na	1.43	U	1.57
Sulfate	mg/L	---	na	na	na	na	94.5	U	96.5
Sulfide	mg/L	---	na	na	na	na	5.00	U	10.0
Methane	µg/L	---	na	na	na	na	26.0	U	0.61
Alkalinity, Total	mg/L	---	na	na	na	na	389	U	0.76
Total Kjeldahl Nitrogen	mg/L	---	na	na	na	na	1.00	U	316
Orthophosphate	mg/L	---	na	na	na	na	0.100	U	365
Total Organic Carbon	mg/L	---	na	na	na	na	1.00	U	1.00
Chloride	mg/L	---	na	na	na	na	28.3	U	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW31-GW-1002 01-Nov-2002	MW31-GW-0103 07-Jan-2003	MW31-GW-1003 21-Oct-2003	MW31-GW-0404 06-Apr-2004	MW31-GW-1004 18-Oct-2004	MW31-GW-0405 13-Apr-2005	MW31-GW-1005 11-Oct-2005	MW31-GW-0406 11-Apr-2006
VOCs									
Benzene	µg/L	5	370	190	380	300	180	350	360
Toluene	µg/L	1000	7.5	8.7	9.0	7.1	Ja	8.6	8.1
Ethylbenzene	µg/L	700	420	180	370	320	200	380	350
Xylenes, Total	µg/L	10000	220	250	250	210	130	250	240
PAHs									
Acenaphthene	µg/L	914	140	180	J	79	71	73	78
Acenaphthylene	µg/L	362	1	U	1.1	U	730	560	670
Anthracene	µg/L	--	1.4	J	1.6	J	1.8	1.9	2.1
Benzo(a)anthracene	µg/L	0.13	0.1	U	3	J	0.027	Ja	0.020
Benzo(a)pyrene	µg/L	0.2	0.1	U	0.11	U	0.13	U	0.13
Benzo(b)fluoranthene	µg/L	0.1	0.1	U	0.11	U	0.051	U	0.051
Benzo(ghi)perylene	µg/L	--	0.1	U	0.11	U	0.20	U	0.19
Benzo(k)fluoranthene	µg/L	0.14	0.1	U	0.11	U	0.051	U	0.049
Chrysene	µg/L	0.85	0.1	U	0.11	U	0.13	U	0.13
Dibenz(a,h)anthracene	µg/L	0.033	0.1	U	0.11	U	0.31	U	0.29
Fluoranthene	µg/L	--	0.88		0.82	J	1.5	1.7	1.6
Fluorene	µg/L	490	16		20	J	16	15	15
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.1	U	0.11	U	0.13	U	0.13
Naphthalene	µg/L	1.1	280		260	J	360	230	280
Phenanthrene	µg/L	294	11		11	J	14	14	12
Pyrene	µg/L	--	0.38		0.34	J	0.26	U	0.28
1-Methylnaphthalene	µg/L	--	na		na		na	na	na
2-Methylnaphthalene	µg/L	61.2	na		na		na	na	na
Inorganics									
Cyanide, Total	mg/L	--	0.005	U	0.00500	U	0.010	U	0.010
Cyanide, WAD	mg/L	0.2	na		na		na	na	na
Manganese, Total	mg/L	0.775	0.146		0.158		0.16		0.15
Natural Attenuation Parameters									
Nitrate	mg/L	--	na		na		na	0.10	U
Nitrite	mg/L	--	na		na		na	0.020	U
Ammonia	mg/L	--	na		na		na	0.17	B
Manganese, Dissolved	mg/L	--	0.144	U	0.165		0.15	0.15	0.15
Iron, Dissolved	mg/L	--	0.552	U	0.625		0.57	0.45	0.52
Sulfate	mg/L	--	na		na		na	24	31
Sulfide	mg/L	--	na		na		na	1.5	1.2
Methane	µg/L	--	na		na		na	16	27
Alkalinity, Total	mg/L	--	na		na		na	460	430
Total Kjeldahl Nitrogen	mg/L	--	na		na		na	0.22	B
Orthophosphate	mg/L	--	na		na		na	0.13	0.016
Total Organic Carbon	mg/L	--	na		na		na	2.5	2.6
Chloride	mg/L	--	na		na		na	na	69.9

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW31-GW-1006 10-Oct-2006	MW31-GW-0407 18-Apr-2007	MW31-GW-1007 09-Oct-2007	MW31-GW-0408 15-Apr-2008	MW31-GW-0409 22-Apr-2009	MW31-GW-1009 14-Oct-2009	MW31-GW-0110 14-Jan-2010
<u>VOCs</u>								
Benzene	µg/L	5	360	326	304	334	157	150
Toluene	µg/L	1000	9.46	8.37	7.47	8.82	4.27	3.96
Ethylbenzene	µg/L	700	376	369	321	319	17.9	164
Xylenes, Total	µg/L	10000	237	241	201	219	117	105
<u>PAHs</u>								
Acenaphthene	µg/L	914	81.2	71.9	63.6	78.5	27.2	29.6
Acenaphthylene	µg/L	362	0.085	U	53.4	0.085	U	12.5
Anthracene	µg/L	---	2.25	2.01	1.24	2.21	0.903	2.32
Benzo(a)anthracene	µg/L	0.13	0.0336	J	0.0198	J	0.0167	J
Benzo(a)pyrene	µg/L	0.2	0.032	U	0.032	U	0.032	U
Benzo(b)fluoranthene	µg/L	0.1	0.0542	J	0.0538	J	0.013	U
Benzo(ghi)perylene	µg/L	---	0.009	U	0.0203	J	0.009	U
Benzo(k)fluoranthene	µg/L	0.14	0.015	U	0.0366	J	0.015	U
Chrysene	µg/L	0.85	0.0407	J	0.0376	J	0.0265	0.0418
Dibenzo(a,h)anthracene	µg/L	0.033	0.01	U	0.01	U	0.01	U
Fluoranthene	µg/L	---	1.34	1.13	0.549	1.72	0.407	0.618
Fluorene	µg/L	490	36.2	35.4	61.2	49.2	6.40	9.87
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.007	U	0.0448	J	0.007	U
Naphthalene	µg/L	1.1	270	202	238	274	93.0	121
Phenanthrene	µg/L	294	13.5	13.1	13.7	17.8	5.41	6.98
Pyrene	µg/L	---	5.35	5.05	2.97	0.019	U	0.434
1-Methylnaphthalene	µg/L	---	na	na	na	na	na	0.618
2-Methylnaphthalene	µg/L	61.2	15.7	11.1	11.2	15.7	2.69	5.41
<u>Inorganics</u>								
Cyanide, Total	mg/L	---	0.01	U	0.01	U	0.01	U
Cyanide, WAD	mg/L	0.2	na	na	na	na	na	0.0100
Manganese, Total	mg/L	0.775	na	na	na	na	na	0.159
<u>Natural Attenuation Parameters</u>								
Nitrate	mg/L	---	na	na	na	na	na	na
Nitrite	mg/L	---	na	na	na	na	na	na
Ammonia	mg/L	---	na	na	na	na	na	na
Manganese, Dissolved	mg/L	---	na	na	na	na	na	na
Iron, Dissolved	mg/L	---	na	na	na	na	na	na
Sulfate	mg/L	---	na	na	na	na	na	na
Sulfide	mg/L	---	na	na	na	na	na	na
Methane	µg/L	---	na	na	na	na	na	na
Alkalinity, Total	mg/L	---	na	na	na	na	na	na
Total Kjeldahl Nitrogen	mg/L	---	na	na	na	na	na	na
Orthophosphate	mg/L	---	na	na	na	na	na	na
Total Organic Carbon	mg/L	---	na	na	na	na	na	na
Chloride	mg/L	---	na	na	na	na	na	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW31-GW-0410 07-Apr-2010		Dup1-GW-0410 07-Apr-2010		MW31-GW-0710 07-Jul-2010		DP01-GW-0710 07-Jul-2010		MW31-GW-1010 05-Oct-2010		MW31(DP)-GW-1010 05-Oct-2010	
			DV		DV		DV		DV		DV		DV
VOCs	Units												
Benzene	µg/L	5	206	M1	198	M1	237		220		299		293
Toluene	µg/L	1000	7.35		6.6		5.73		5.45		8.17		7.86
Ethylbenzene	µg/L	700	340	C9	316	C9	288		263		357		341
Xylenes, Total	µg/L	10000	241	M1	224	M1	174		162		202		194
PAHs													
Acenaphthene	µg/L	914	68.9		J+	68.5		J+	35.6	H2	J-	37	H2
Acenaphthylene	µg/L	362	26.6		J+	25.0		J+	10.2		9.93		9.41
Anthracene	µg/L	---	2.69	M1	J+	2.35		J+	1.36		1.2		1.60
Benzo(a)anthracene	µg/L	0.13	0.151		J+	0.113		J+	0.100	U	0.100	U	1.00
Benzo(a)pyrene	µg/L	0.2	0.230		J+	0.160		J+	0.100	U	0.100	U	1.00
Benzo(b)fluoranthene	µg/L	0.1	0.410		J+	0.288		J+	0.104		0.114		1.00
Benzo(ghi)perylene	µg/L	---	0.250		J+	0.175		J+	0.100	U	0.100	U	1.00
Benzo(k)fluoranthene	µg/L	0.14	0.162		J+	0.130		J+	0.100	U	0.100	U	1.00
Chrysene	µg/L	0.85	0.234		J+	0.175		J+	0.100	U	0.100	U	1.00
Dibenzo(a,h)anthracene	µg/L	0.033	0.0414	J, MDL	J+	0.0142	J,MDL	J+	0.00994	J,MDL	0.0103	J, MDL	0.0810
Fluoranthene	µg/L	---	0.832		J+	0.764		J+	0.406		0.397		1.00
Fluorene	µg/L	490	19.4		J+	18.8		J+	7.69		7.24		6.80
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.208		J+	0.147		J+	0.100	U	0.100	U	1.00
Naphthalene	µg/L	1.1	217		J+	223		J+	120	H2	J-	130	H2
Phenanthrene	µg/L	294	9.03	M1	J+	9.06		J+	6.09		5.43		5.30
Pyrene	µg/L	---	0.767		J+	0.647		J+	0.464		0.448		1.00
1-Methylnaphthalene	µg/L	---	267		J+	273		J+	135	H2	J-	145	H2
2-Methylnaphthalene	µg/L	61.2	4.61	M1	J+	4.38		J+	3.09		3.14		3.44
Inorganics													
Cyanide, Total	mg/L	---	na			na			na		na		na
Cyanide, WAD	mg/L	0.2	0.0100	U,M1, R		0.0100	U		0.0100	U	0.0100	U	0.0100
Manganese, Total	mg/L	0.775	0.149			0.145			0.152		0.154		0.148
Natural Attenuation Parameters													
Nitrate	mg/L	---	0.10	U		0.10	U		na		na		0.10
Nitrite	mg/L	---	0.100	U,M1		0.100	U		na		0.100		0.100
Ammonia	mg/L	---	0.200	U		0.200	U		na		0.200		0.200
Manganese, Dissolved	mg/L	---	0.134			0.144			na		0.141		0.141
Iron, Dissolved	mg/L	---	0.860			0.934			na		1.11		1.11
Sulfate	mg/L	---	37.5			40.7			na		51.4		50.6
Sulfide	mg/L	---	5.00	U		5.00	U		na		5.00	U	5.00
Methane	µg/L	---	87			101			na		109		103
Alkalinity, Total	mg/L	---	497			497			na		453		458
Total Kjeldahl Nitrogen	mg/L	---	1.00	U,M1		1.00	U		na		1.00	U	1.00
Orthophosphate	mg/L	---	0.100	U		0.100	U		na		0.100	U	0.100
Total Organic Carbon	mg/L	---	1.23			1.27			na		1.21		1.21
Chloride	mg/L	---	56.4			54.2			na		50.0		50.6

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW31-GW-0411 12-Apr-2011	MW31-GW-1011 25-Oct-2011	DV	MW31-GW-0412 10-Apr-2012	DV	MW31-GW-1012 09-Oct-2012	MW31-GW-0413 10-Apr-2013	MW31-GW-1013 22-Oct-2013	MW33-GW-1002 29-Oct-2002	DV
<u>VOCs</u>											
Benzene	µg/L	5	264	MHA	213		229	218	255	289	2 U
Toluene	µg/L	1000	6.06		5.97		7.62	6.49	345	10.1	2 U
Ethylbenzene	µg/L	700	284	MHA	262		313	296	7.19	367	2 U
Xylenes, Total	µg/L	10000	175	MHA	J-	162	180	172	206	236	7 U
<u>PAHs</u>											
Acenaphthene	µg/L	914	28.2	M1	16.6	J-	37.9	31.5	52.4	34.1	0.52 U
Acenaphthylene	µg/L	362	8.63	M1	14.0	J-	14.4	15.0	18.8	12.9	1 U
Anthracene	µg/L	---	1.26		1.46	J-	1.49	1.24	1.74	1.69	0.052 U
Benzo(a)anthracene	µg/L	0.13	0.100	U	0.100	U	0.100	U	0.100	U	0.1 U
Benzo(a)pyrene	µg/L	0.2	0.100	U	0.100	U	0.100	U	0.100	U	0.1 U
Benzo(b)fluoranthene	µg/L	0.1	0.106		0.100	U	0.100	U	0.100	U	0.1 U
Benzo(ghi)perylene	µg/L	---	0.100	U	0.100	U	0.100	U	0.100	U	0.1 U
Benzo(k)fluoranthene	µg/L	0.14	0.100	U	0.100	U	0.100	U	0.100	U	0.1 U
Chrysene	µg/L	0.85	0.100	U	0.100	U	0.100	U	0.100	U	0.1 U
Dibenz(a,h)anthracene	µg/L	0.033	0.0170	U,MDL	0.0170	U,MDL	0.0170	U,MDL	0.013	U,MDL	0.0191 U 0.0179 U 0.1 U
Fluoranthene	µg/L	---	0.387		0.420	J-	0.515	0.389	0.59	0.654	0.1 U
Fluorene	µg/L	490	7.06	M1	J-	9.90	J-	9.60	10.3	15.6	9.91 0.1 U
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.100		0.100	U	0.100	U	0.100	U	0.1 U
Naphthalene	µg/L	1.1	88.5	M1		128	J-	154	122	180	166 J- 0.52 U
Phenanthrene	µg/L	294	5.67	M1	J-	8.07	J-	9.32	7.14	8.27	6.09 0.1 U
Pyrene	µg/L	---	0.413		0.416	J-	0.516	0.395	0.643	0.846	0.1 U
1-Methylnaphthalene	µg/L	---	108	M1		117	J-	164	121	198	145 J- na
2-Methylnaphthalene	µg/L	61.2	2.96	M1	J-	4.89	J-	5.21	5.99	9.15	7.5 na
<u>Inorganics</u>											
Cyanide, Total	mg/L	---	na		na		na	na	na	na	0.00637
Cyanide, WAD	mg/L	0.2	0.0100	U,M1	UJ	0.0100	U	0.0100	U	0.0100	U na
Manganese, Total	mg/L	0.775	0.152		0.145		0.151	0.150	0.108	0.143	0.295
<u>Natural Attenuation Parameters</u>											
Nitrate	mg/L	---	0.10	U	0.100	U	0.100	U	0.100	U	na
Nitrite	mg/L	---	0.100	U	0.100	U	0.100	U	0.100	U	na
Ammonia	mg/L	---	0.200	U	0.200	U	0.200	U	0.200	U	na
Manganese, Dissolved	mg/L	---	0.136		0.152		0.145	0.152	0.148	na	0.23
Iron, Dissolved	mg/L	---	0.949		1.23		1.15	1.32	0.951	na	1.79
Sulfate	mg/L	---	50.7		18.3		44.2	55.8	26.8	na	na
Sulfide	mg/L	---	43		10	U	10	U	10	21.7	na
Methane	µg/L	---	32		26		71	71	49	na	na
Alkalinity, Total	mg/L	---	444		444		434	429	487	na	na
Total Kjeldahl Nitrogen	mg/L	---	1.00	U,M1	1.00	U	1.00	U	1.00	U	na
Orthophosphate	mg/L	---	0.100	U	0.100	U	0.100	U	0.100	U	na
Total Organic Carbon	mg/L	---	na		1.29		na	na	na	na	na
Chloride	mg/L	---	na		na		na	na	na	na	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW33-GW-0103 06-Jan-2003	MW33-GW-0103 09-Jan-2003	MW33-GW-1003 21-Oct-2003	MW33-GW-0404 05-Apr-2004	MW33-GW-1004 19-Oct-2004	MW33-GW-0405 12-Apr-2005	MW33-GW1005 10-Oct-2005
VOCs								
Benzene	µg/L	5	1.0	U	ns	1.0	U	1.0
Toluene	µg/L	1000	1.0	U	ns	1.0	U	1.0
Ethylbenzene	µg/L	700	1.0	U	ns	1.0	U	1.0
Xylenes, Total	µg/L	10000	3.0	U	ns	1.0	U	2.0
PAHs								
Acenaphthene	µg/L	914	0.51	U	0.52	U	2.5	U*
Acenaphthylene	µg/L	362	1.0	U	1	U	1.3	U*
Anthracene	µg/L	---	0.051	U	0.052	U	0.050	U
Benzo(a)anthracene	µg/L	0.13	0.10	U	0.1	U	0.14	U
Benzo(a)pyrene	µg/L	0.2	0.10	U	0.1	U	0.14	U
Benzo(b)fluoranthene	µg/L	0.1	0.10	U	0.1	U	0.052	U
Benzo(ghi)perylene	µg/L	---	0.10	U	0.1	U	0.21	U
Benzo(k)fluoranthene	µg/L	0.14	0.10	U	0.1	U	0.052	U
Chrysene	µg/L	0.85	0.10	U	0.1	U	0.14	U
Dibenzo(a,h)anthracene	µg/L	0.033	0.10	U	0.1	U	0.31	U
Fluoranthene	µg/L	---	0.10	U	0.1	U	0.14	U
Fluorene	µg/L	490	0.10	U	0.1	U	0.26	U
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.10	U	0.1	U	0.14	U
Naphthalene	µg/L	1.1	0.51	U	0.52	U	1.4	U
Phenanthrene	µg/L	294	0.10	U	0.1	U	0.10	U
Pyrene	µg/L	---	0.10	U	0.1	U	0.26	U
1-Methylnaphthalene	µg/L	---	na		na		na	
2-Methylnaphthalene	µg/L	61.2	na		na		na	
Inorganics								
Cyanide, Total	mg/L	---	0.00595		ns	0.0086	B	0.0087
Cyanide, WAD	mg/L	0.2	na		ns	na	na	na
Manganese, Total	mg/L	0.775	0.247		ns	0.24	0.21	0.25
Natural Attenuation Parameters								
Nitrate	mg/L	---	na		ns	na	na	na
Nitrite	mg/L	---	na		ns	na	na	na
Ammonia	mg/L	---	na		ns	na	na	na
Manganese, Dissolved	mg/L	---	0.233		ns	0.22	0.21	0.21
Iron, Dissolved	mg/L	---	2.09		ns	2.1	2.0	1.9
Sulfate	mg/L	---	na		ns	na	na	na
Sulfide	mg/L	---	na		ns	na	na	na
Methane	µg/L	---	na		ns	na	na	na
Alkalinity, Total	mg/L	---	na		ns	na	na	na
Total Kjeldahl Nitrogen	mg/L	---	na		ns	na	na	na
Orthophosphate	mg/L	---	na		ns	na	na	na
Total Organic Carbon	mg/L	---	na		ns	na	na	na
Chloride	mg/L	---	na		ns	na	na	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW33-GW-0406 10-Apr-2006	MW33-GW-0410 07-Apr-2010	MW33-GW-0411 11-Apr-2011	MW33-GW-0412 10-Apr-2012	MW33-GW-0413 09-Apr-2013	MW35-GW-1002 28-Oct-2002	MW35-GW-0103 07-Jan-2003	MW35-GW-1003 22-Oct-2003
VOCs									
Benzene	µg/L	5	1	U	1.00	U	1.0	U	0.50
Toluene	µg/L	1000	1	U	1.00	U	1.0	U	2
Ethylbenzene	µg/L	700	1	U	1.00	U	1.0	U	1.00
Xylenes, Total	µg/L	10000	3	U	6.00	U	3.00	U	1.00
PAHs									
Acenaphthene	µg/L	914	0.13	U	0.100	U	0.100	U	0.52
Acenaphthylene	µg/L	362	0.17	U	0.100	U	0.100	U	1
Anthracene	µg/L	---	0.0093	U	0.100	U	0.100	U	0.052
Benzo(a)anthracene	µg/L	0.13	0.019	U	0.100	U	0.100	U	0.1
Benzo(a)pyrene	µg/L	0.2	0.019	U	0.100	U	0.100	U	0.1
Benzo(b)fluoranthene	µg/L	0.1	0.037	U	0.100	U	0.100	U	0.1
Benzo(ghi)perylene	µg/L	---	0.032	U	0.100	U	0.100	U	0.1
Benzo(k)fluoranthene	µg/L	0.14	0.023	U	0.100	U	0.100	U	0.1
Chrysene	µg/L	0.85	0.02	U	0.100	U	0.100	U	0.1
Dibenz(a,h)anthracene	µg/L	0.033	0.033	U	0.00810	U,J,MDL	0.0170	U,MDL	0.0172
Fluoranthene	µg/L	---	0.032	U	0.100	U	0.100	U	0.1
Fluorene	µg/L	490	0.029	U	0.100	U	0.100	U	0.1
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.038	U	0.100	U	0.100	U	0.1
Naphthalene	µg/L	1.1	0.1	U	0.100	U	0.100	U	0.52
Phenanthrene	µg/L	294	0.015	U	0.100	U	0.100	U	0.1
Pyrene	µg/L	---	0.036	U	0.100	U	0.100	U	0.1
1-Methylnaphthalene	µg/L	---	na		0.100	U	0.100	U	na
2-Methylnaphthalene	µg/L	61.2	na		0.100	U	0.100	U	na
Inorganics									
Cyanide, Total	mg/L	---	0.01	U	na	na	na	U	0.00500
Cyanide, WAD	mg/L	0.2	na		0.0100	U	0.0100	U	na
Manganese, Total	mg/L	0.775	0.208		1.06	2.18	0.188	0.205	0.0251
Natural Attenuation Parameters									
Nitrate	mg/L	---	na		na	na	na	na	na
Nitrite	mg/L	---	na		na	na	na	na	na
Ammonia	mg/L	---	na		na	na	na	na	na
Manganese, Dissolved	mg/L	---	0.204		na	na	na		0.0137
Iron, Dissolved	mg/L	---	2.26		na	na	na	U	0.00744
Sulfate	mg/L	---	na		na	na	na	na	0.0094
Sulfide	mg/L	---	na		na	na	na	na	0.050
Methane	µg/L	---	na		na	na	na	na	na
Alkalinity, Total	mg/L	---	na		na	na	na	na	na
Total Kjeldahl Nitrogen	mg/L	---	na		na	na	na	na	na
Orthophosphate	mg/L	---	na		na	na	na	na	na
Total Organic Carbon	mg/L	---	na		na	na	na	na	na
Chloride	mg/L	---	na		na	na	na	na	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW35-GW-0404 07-Apr-2004	MW35-GW-1004 20-Oct-2004	MW35-GW-0405 13-Apr-2005	MW35-GW1005 12-Oct-2005	MW35-GW-0406 11-Apr-2006	MW35-GW-1006 10-Oct-2006	MW35-GW-0407 16-Apr-2007
VOCs								
Benzene	µg/L	5	1.0	U	1.0	U	1.0	U
Toluene	µg/L	1000	1.0	U	1.0	U	1.0	U
Ethylbenzene	µg/L	700	1.0	U	1.0	U	1	U
Xylenes, Total	µg/L	10000	1.0	U	1.0	U	3	U
PAHs								
Acenaphthene	µg/L	914	2.4	U	2.7	U	2.3	U
Acenaphthylene	µg/L	362	1.2	U	1.4	U	1.2	U
Anthracene	µg/L	---	0.048	U	0.0089	Ja	0.050	U
Benzo(a)anthracene	µg/L	0.13	0.12	U	0.14	U	0.13	U
Benzo(a)pyrene	µg/L	0.2	0.12	U	0.14	U	0.13	U
Benzo(b)fluoranthene	µg/L	0.1	0.048	U	0.055	U	0.050	U
Benzo(ghi)perylene	µg/L	---	0.19	U	0.22	U	0.20	U
Benzo(k)fluoranthene	µg/L	0.14	0.048	U	0.055	U	0.050	U
Chrysene	µg/L	0.85	0.12	U	0.14	U	0.13	U
Dibenz(a,h)anthracene	µg/L	0.033	0.29	U	0.33	U	0.30	U
Fluoranthene	µg/L	---	0.12	U	0.14	U	0.13	U
Fluorene	µg/L	490	0.24	U	0.27	U	0.25	U
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.12	U	0.14	U	0.13	U
Naphthalene	µg/L	1.1	1.2	U	1.4	U	1.3	U
Phenanthrene	µg/L	294	0.095	U	0.048	Ja	0.10	U
Pyrene	µg/L	---	0.24	U	0.27	U	0.25	U
1-Methylnaphthalene	µg/L	---	na	na	na	na	na	na
2-Methylnaphthalene	µg/L	61.2	na	na	na	na	0.052	U
Inorganics								
Cyanide, Total	mg/L	---	0.0061	B	0.010	U	0.010	B
Cyanide, WAD	mg/L	0.2	na	na	na	na	na	na
Manganese, Total	mg/L	0.775	0.040	na	0.14	0.22	0.23	0.264
Natural Attenuation Parameters								
Nitrate	mg/L	---	na	na	na	na	na	na
Nitrite	mg/L	---	na	na	na	na	na	na
Ammonia	mg/L	---	na	na	na	na	na	na
Manganese, Dissolved	mg/L	---	0.0084	B	0.044	U	0.19	0.25
Iron, Dissolved	mg/L	---	0.050	U	0.050	U	0.10	U
Sulfate	mg/L	---	na	na	na	na	na	na
Sulfide	mg/L	---	na	na	na	na	na	na
Methane	µg/L	---	na	na	na	na	na	na
Alkalinity, Total	mg/L	---	na	na	na	na	na	na
Total Kjeldahl Nitrogen	mg/L	---	na	na	na	na	na	na
Orthophosphate	mg/L	---	na	na	na	na	na	na
Total Organic Carbon	mg/L	---	na	na	na	na	na	na
Chloride	mg/L	---	na	na	na	na	na	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW35-GW-1007 09-Oct-2007	MW35-GW-0408 15-Apr-2008	MW35-GW-0410 08-Apr-2010	MW35-GW-1010 06-Oct-2010	MW35-GW-0411 11-Apr-2011	MW35-GW-1011 24-Oct-2011	MW35-GW-0412 11-Apr-2012
								DV
VOCs								
Benzene	µg/L	5	1.00	U	1.00	U,L1	1.00	U
Toluene	µg/L	1000	1.00	U	1.00	U,L1	1.00	U
Ethylbenzene	µg/L	700	1.00	U	1.00	U,L1	1.00	U
Xylenes, Total	µg/L	10000	3.00	U	3.00	U,L1	6.00	U
PAHs								
Acenaphthene	µg/L	914	0.057	U	0.0995	J	0.100	U
Acenaphthylene	µg/L	362	0.0988	U	0.0850	U	0.100	U
Anthracene	µg/L	---	0.0116	U	0.0351	J	0.100	U
Benzo(a)anthracene	µg/L	0.13	0.00349	U	0.0030	U	0.100	U
Benzo(a)pyrene	µg/L	0.2	0.0372	U	0.0320	U	0.100	U
Benzo(b)fluoranthene	µg/L	0.1	0.0151	U	0.0130	U	0.100	U
Benzo(ghi)perylene	µg/L	---	0.0105	U	0.00900	U	0.100	U
Benzo(k)fluoranthene	µg/L	0.14	0.0174	U	0.0150	U	0.100	U
Chrysene	µg/L	0.85	0.00581	U	0.00500	U	0.100	U
Dibenz(a,h)anthracene	µg/L	0.033	0.0116	U	0.0100	U	0.0081	U,MDL
Fluoranthene	µg/L	---	0.0116	U	0.0100	U	0.100	U
Fluorene	µg/L	490	0.0116	U	0.249	0.100	U	0.180
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.00814	U	0.00700	U	0.100	U
Naphthalene	µg/L	1.1	0.0628	U	0.312	0.100	U	2.18
Phenanthrene	µg/L	294	0.00814	U	0.175	0.100	U	0.145
Pyrene	µg/L	---	0.0221	U	0.0190	U	0.100	U
1-Methylnaphthalene	µg/L	---	na		na	0.100	U	0.632
2-Methylnaphthalene	µg/L	61.2	0.0605	U	0.0520	U	0.100	U
Inorganics								
Cyanide, Total	mg/L	---	0.0100	U	0.0100	U	na	na
Cyanide, WAD	mg/L	0.2	na		0.0100	U	0.0100	U
Manganese, Total	mg/L	0.775	na		0.354	U	0.355	0.326
Natural Attenuation Parameters								
Nitrate	mg/L	---	na		na		na	na
Nitrite	mg/L	---	na		na		na	na
Ammonia	mg/L	---	na		na		na	na
Manganese, Dissolved	mg/L	---	na		na		na	na
Iron, Dissolved	mg/L	---	na		na		na	na
Sulfate	mg/L	---	na		na		na	na
Sulfide	mg/L	---	na		na		na	na
Methane	µg/L	---	na		na		na	na
Alkalinity, Total	mg/L	---	na		na		na	na
Total Kjeldahl Nitrogen	mg/L	---	na		na		na	na
Orthophosphate	mg/L	---	na		na		na	na
Total Organic Carbon	mg/L	---	na		na		na	na
Chloride	mg/L	---	na		na		na	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW35-GW-1012 09-Oct-2012	DV	MW35-GW-0413 11-Apr-2013	DV	MW35-GW-1013 22-Oct-2013	DV	MW36-GW-1002 29-Oct-2002	MW36-GW-0103 06-Jan-2003	MW36-GW-1003 21-Oct-2003	MW36-GW-0404 06-Apr-2004
VOCs	<u>Units</u>										
Benzene	µg/L	5	1.00	U	0.500	U	0.500	U	110	120	150
Toluene	µg/L	1000	1.00	U	1.00	U	1.00	U	2.5	3.1	1.1
Ethylbenzene	µg/L	700	1.00	U	1.00	U	1.00	U	100	140	140
Xylenes, Total	µg/L	10000	3.00	U	3.00	U	3.00	U	58	87	38
PAHs											
Acenaphthene	µg/L	914	0.100	U	UJ	0.100	U	0.100	U	60	0.5
Acenaphthylene	µg/L	362	0.100	U	UJ	0.100	U	0.100	U	1.1	U
Anthracene	µg/L	---	0.100	U	UJ	0.100	U	0.100	U	0.24	J
Benzo(a)anthracene	µg/L	0.13	0.100	U	UJ	0.100	U	0.100	U	0.11	U
Benzo(a)pyrene	µg/L	0.2	0.100	U	UJ	0.100	U	0.100	U	0.11	U
Benzo(b)fluoranthene	µg/L	0.1	0.100	U	UJ	0.100	U	0.100	U	0.11	U
Benzo(ghi)perylene	µg/L	---	0.100	U	UJ	0.100	U	0.100	U	0.11	U
Benzo(k)fluoranthene	µg/L	0.14	0.100	U	UJ	0.100	U	0.100	U	0.11	U
Chrysene	µg/L	0.85	0.100	U	UJ	0.100	U	0.100	U	0.11	U
Dibeno(a,h)anthracene	µg/L	0.033	0.0130	U,MDL	UJ	0.0185	U	0.0173	U	0.11	U
Fluoranthene	µg/L	---	0.100	U	UJ	0.100	U	0.100	U	0.14	J
Fluorene	µg/L	490	0.100	U	UJ	0.100	U	0.100	U	7	0.22
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.100	U	UJ	0.100	U	0.100	U	0.11	U
Naphthalene	µg/L	1.1	0.100	U	UJ	1.11	B	0.12	U	54	J
Phenanthrene	µg/L	294	0.100	U	UJ	0.100	U	0.100	U	1.7	J
Pyrene	µg/L	---	0.100	U	UJ	0.100	U	0.100	U	0.11	U
1-Methylnaphthalene	µg/L	---	0.100	U	UJ	0.154		0.100	U	na	na
2-Methylnaphthalene	µg/L	61.2	0.100	U	UJ	0.135		0.100	U	na	na
Inorganics											
Cyanide, Total	mg/L	---	na		na		na		0.005	0.00500	U
Cyanide, WAD	mg/L	0.2	0.0100	U	0.0100	U	0.0100	U	na	na	na
Manganese, Total	mg/L	0.775	0.361		0.371		0.313		0.146	0.166	0.18
Natural Attenuation Parameters											
Nitrate	mg/L	---	na		na		na		na	na	na
Nitrite	mg/L	---	na		na		na		na	na	na
Ammonia	mg/L	---	na		na		na		na	na	na
Manganese, Dissolved	mg/L	---	na		na		na		0.151	0.158	0.16
Iron, Dissolved	mg/L	---	na		na		na		1.47	1.39	1.4
Sulfate	mg/L	---	na		na		na		na	na	na
Sulfide	mg/L	---	na		na		na		na	na	na
Methane	µg/L	---	na		na		na		na	na	na
Alkalinity, Total	mg/L	---	na		na		na		na	na	na
Total Kjeldahl Nitrogen	mg/L	---	na		na		na		na	na	na
Orthophosphate	mg/L	---	na		na		na		na	na	na
Total Organic Carbon	mg/L	---	na		na		na		na	na	na
Chloride	mg/L	---	na		na		na		na	na	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW36-GW-1004 20-Oct-2004	MW36-GW-0405 13-Apr-2005	MW36-GW-1005 12-Oct-2005	MW36-GW-0406 12-Apr-2006	MW36-GW-1006 09-Oct-2006	MW36-GW-0407 18-Apr-2007	MW36-GW-1007 10-Oct-2007	MW36-GW-0408 16-Apr-2008
VOCs									
Benzene	µg/L	5	140	120	120	91.6	60.7	30.8	82.9
Toluene	µg/L	1000	1.1	0.78	Ja	1.0	U	1	U
Ethylbenzene	µg/L	700	160	130	120	92.6	36	15.7	84
Xylenes, Total	µg/L	10000	51	39	19	10.2	11.6	3	U
PAHs									
Acenaphthene	µg/L	914	37	41	42	28.9	28.8	24.9	37.8
Acenaphthylene	µg/L	362	320	380	350	0.17	U	0.085	U
Anthracene	µg/L	---	0.87	1.1	1.1	0.815	0.792	0.447	0.567
Benzo(a)anthracene	µg/L	0.13	0.13	U	0.12	U	0.019	U	0.003
Benzo(a)pyrene	µg/L	0.2	0.13	U	0.12	U	0.019	U	0.032
Benzo(b)fluoranthene	µg/L	0.1	0.052	U	0.047	U	0.048	U	0.037
Benzo(ghi)perylene	µg/L	---	0.21	U	0.19	U	0.19	U	0.009
Benzo(k)fluoranthene	µg/L	0.14	0.052	U	0.047	U	0.048	U	0.023
Chrysene	µg/L	0.85	0.13	U	0.12	U	0.12	U	0.005
Dibenz(a,h)anthracene	µg/L	0.033	0.31	U	0.28	U	0.29	U	0.01
Fluoranthene	µg/L	---	0.78	0.82	0.54	0.651	0.424	0.237	0.382
Fluorene	µg/L	490	7.7	9.1	8.6	10.4	13.8	11	33.3
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.13	U	0.12	U	0.038	U	0.007
Naphthalene	µg/L	1.1	19	7.9	5.2	2.77	3.78	1.93	4.89
Phenanthrene	µg/L	294	5.7	6.6	5.9	6.2	4.67	3.05	5.61
Pyrene	µg/L	---	0.29	0.099	Ja	0.28	2.69	1.7	0.964
1-Methylnaphthalene	µg/L	---	na						
2-Methylnaphthalene	µg/L	61.2	na	na	na	na	0.052	U	0.052
Inorganics									
Cyanide, Total	mg/L	---	0.010	U	0.010	U	0.0027	B	0.01
Cyanide, WAD	mg/L	0.2	na						
Manganese, Total	mg/L	0.775	0.18	0.18	0.25	0.154	na	na	na
Natural Attenuation Parameters									
Nitrate	mg/L	---	na						
Nitrite	mg/L	---	na						
Ammonia	mg/L	---	na						
Manganese, Dissolved	mg/L	---	0.17	0.17	0.17	0.161	na	na	na
Iron, Dissolved	mg/L	---	1.2	1.3	1.6	1.44	na	na	na
Sulfate	mg/L	---	na						
Sulfide	mg/L	---	na						
Methane	µg/L	---	na						
Alkalinity, Total	mg/L	---	na						
Total Kjeldahl Nitrogen	mg/L	---	na						
Orthophosphate	mg/L	---	na						
Total Organic Carbon	mg/L	---	na						
Chloride	mg/L	---	na						

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW36-GW-0409 22-Apr-2009	MW36-GW-1009 14-Oct-2009	MW36-GW-0110 14-Jan-2010	DP01-GW-0110 14-Jan-2010	MW36-GW-0410 07-Apr-2010	MW36-GW-0710 07-Jul-2010	MW36-GW-1010 05-Oct-2010
								DV
VOCs								
Benzene	µg/L	5	1	U	25.6	1.00	U	1.00
Toluene	µg/L	1000	1	U	1	1.00	U	1.00
Ethylbenzene	µg/L	700	1	U	7.13	1.00	U	1.00
Xylenes, Total	µg/L	10000	3	U	3	3.00	U	3.00
PAHs								
Acenaphthene	µg/L	914	7.75		15.5	10.5	10.3	16.0
Acenaphthylene	µg/L	362	1.85		4.6	2.01	2.04	3.28
Anthracene	µg/L	---	0.0551	J	0.143	0.0487	J	0.120
Benzo(a)anthracene	µg/L	0.13	0.0250	J	0.0216	J	0.0125	J
Benzo(a)pyrene	µg/L	0.2	0.0186	J	0.016	U	0.0160	U
Benzo(b)fluoranthene	µg/L	0.1	0.0211	J	0.0158	J	0.00760	U
Benzo(ghi)perylene	µg/L	---	0.0121	J	0.00887	J	0.00810	U
Benzo(k)fluoranthene	µg/L	0.14	0.00790	U	0.0077	U	0.00770	U
Chrysene	µg/L	0.85	0.0136	J	0.0101	J	0.00700	U
Dibenz(a,h)anthracene	µg/L	0.033	0.00760	U	0.0081	U	0.00810	U
Fluoranthene	µg/L	---	0.0727	J	0.107	0.0386	J	0.0434
Fluorene	µg/L	490	1.95		4.34	2.25	2.33	3.55
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.0101	J	0.011	U	0.0110	U
Naphthalene	µg/L	1.1	0.00590	U	0.488	0.0290	U	0.290
Phenanthrene	µg/L	294	0.555		0.858	0.170	0.144	0.357
Pyrene	µg/L	---	0.068	J	0.111	0.0808	J	0.0831
1-Methylnaphthalene	µg/L	---	na		na	na	na	0.54
2-Methylnaphthalene	µg/L	61.2	0.0195	J	0.0531	J	0.0310	U
Inorganics								
Cyanide, Total	mg/L	---	na		na	na	na	na
Cyanide, WAD	mg/L	0.2	na		0.0100	U	0.0100	U
Manganese, Total	mg/L	0.775	na		0.120	0.120	0.125	0.144
Natural Attenuation Parameters								
Nitrate	mg/L	---	na		na	na	na	na
Nitrite	mg/L	---	na		na	na	na	na
Ammonia	mg/L	---	na		na	na	na	na
Manganese, Dissolved	mg/L	---	na		na	na	na	na
Iron, Dissolved	mg/L	---	na		na	na	na	na
Sulfate	mg/L	---	na		na	na	na	na
Sulfide	mg/L	---	na		na	na	na	na
Methane	µg/L	---	na		na	na	na	na
Alkalinity, Total	mg/L	---	na		na	na	na	na
Total Kjeldahl Nitrogen	mg/L	---	na		na	na	na	na
Orthophosphate	mg/L	---	na		na	na	na	na
Total Organic Carbon	mg/L	---	na		na	na	na	na
Chloride	mg/L	---	na		na	na	na	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW36-GW-0411 11-Apr-2011	MW36-GW-1011 25-Oct-2011	DV	MW36-GW-1011-DUP-01 25-Oct-2011	DV	MW36-GW-0412 10-Apr-2012	DV	MW36-GW-1012 09-Oct-2012	DV	DP01-GW-1012 09-Oct-2012	DV	
VOCs													
Benzene	µg/L	5	4.24		21.4		20.9		8.76		21.8		22.8
Toluene	µg/L	1000	1.00	U	1.00	U	1.00	U	1.0	U	1.00	U	1.00
Ethylbenzene	µg/L	700	1.00	U	4.95		4.72		1.0	U	2.53		2.75
Xylenes, Total	µg/L	10000	3.00	U	4.09		4.22		3.0	U	3.00	U	3.00
PAHs													
Acenaphthene	µg/L	914	10.6		8.33	J-	7.57	J-	14.3		16.2	J-	15.7
Acenaphthylene	µg/L	362	2.66		3.39		3.40		2.71		3.34	J-	3.48
Anthracene	µg/L	---	0.100	U	0.100	U	0.100	U	0.100	U	0.100	UJ	0.100
Benzo(a)anthracene	µg/L	0.13	0.100	U	0.100	U	0.100	U	0.100	U	0.100	UJ	0.100
Benzo(a)pyrene	µg/L	0.2	0.100	U	0.100	U	0.100	U	0.100	U	0.100	UJ	0.100
Benzo(b)fluoranthene	µg/L	0.1	0.100	U	0.100	U	0.100	U	0.100	U	0.100	UJ	0.100
Benzo(ghi)perylene	µg/L	---	0.100	U	0.100	U	0.100	U	0.100	U	0.100	UJ	0.100
Benzo(k)fluoranthene	µg/L	0.14	0.100	U	0.100	U	0.100	U	0.100	U	0.100	UJ	0.100
Chrysene	µg/L	0.85	0.100	U	0.100	U	0.100	U	0.100	U	0.100	UJ	0.100
Dibenzo(a,h)anthracene	µg/L	0.033	0.0170	U,MDL	0.0170	U,MDL	0.0170	U,MDL	0.0170	U,MDL	0.0130	U,MDL	0.0130
Fluoranthene	µg/L	---	0.100	U	0.100	U	0.100	U	0.100	U	0.100	UJ	0.100
Fluorene	µg/L	490	2.88		3.49		3.53		2.63		3.28	J-	3.38
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.100	U	0.100	U	0.100	U	0.100	U	0.100	UJ	0.100
Naphthalene	µg/L	1.1	0.745		0.741		0.427		0.158		0.287	J-	0.246
Phenanthrene	µg/L	294	0.162		0.178		0.167		0.132		0.164	J-	0.160
Pyrene	µg/L	---	0.100	U	0.100	U	0.100	U	0.100	U	0.100	UJ	0.100
1-Methylnaphthalene	µg/L	---	1.33		6.47		6.25		0.435		1.58	J-	1.46
2-Methylnaphthalene	µg/L	61.2	0.100	U	0.100	U	0.100	U	0.100	U	0.100	UJ	0.100
Inorganics													
Cyanide, Total	mg/L	---	na						na		na		na
Cyanide, WAD	mg/L	0.2	0.0100	U	0.0100	U	0.0100	U	0.0100	U	0.0100	U	0.0100
Manganese, Total	mg/L	0.775	0.127		0.159		0.147		0.12		0.141		0.144
Natural Attenuation Parameters													
Nitrate	mg/L	---	na		na		na		na		na		na
Nitrite	mg/L	---	na		na		na		na		na		na
Ammonia	mg/L	---	na		na		na		na		na		na
Manganese, Dissolved	mg/L	---	na		na		na		na		na		na
Iron, Dissolved	mg/L	---	na		na		na		na		na		na
Sulfate	mg/L	---	na		na		na		na		na		na
Sulfide	mg/L	---	na		na		na		na		na		na
Methane	µg/L	---	na		na		na		na		na		na
Alkalinity, Total	mg/L	---	na		na		na		na		na		na
Total Kjeldahl Nitrogen	mg/L	---	na		na		na		na		na		na
Orthophosphate	mg/L	---	na		na		na		na		na		na
Total Organic Carbon	mg/L	---	na		na		na		na		na		na
Chloride	mg/L	---	na		na		na		na		na		na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW36-GW-0413 09-Apr-2013	DV	DP01-GW-0413 09-Apr-2013	DV	MW36-GW-1013 22-Oct-2013	DV	DP01-GW-1013 22-Oct-2013	DV	MW37-GW-1002 29-Oct-2002	DV	MW37-GW-0103 06-Jan-2003	DV	MW37-GW-1003 21-Oct-2003	DV	MW37-GW-0404 06-Apr-2004		
VOCs																		
Benzene	µg/L	5	5.18		5.16	45.8		43.9		6.7		52		87		73		
Toluene	µg/L	1000	1.00	U	1.00	U	1.00	U	1.00	U	2	U	1.3		1.0	U	1.0	U
Ethylbenzene	µg/L	700	1.00	U	1.00	U	21.3		20.7		4.9		56		8.1		6.2	
Xylenes, Total	µg/L	10000	3.00	U	3.00	U	5.19		5.09		7	U	26		6.4		5.8	
PAHs																		
Acenaphthene	µg/L	914	22.4		21	22.6		24.6		3.4		17		15		19	*	
Acenaphthylene	µg/L	362	3.51	J+	3.41	5.19		5.34		1.1	U	1.0	U	150		200	*	
Anthracene	µg/L	---	0.100	U	0.100	U	0.16		0.149		0.053	U	0.051	U	0.14		0.17	
Benzo(a)anthracene	µg/L	0.13	0.100	U	0.100	U	0.100	U	0.100	U	0.11	U	0.10	U	0.13	U	0.13	U
Benzo(a)pyrene	µg/L	0.2	0.100	U	0.100	U	0.100	U	0.100	U	0.11	U	0.10	U	0.13	U	0.13	U
Benzo(b)fluoranthene	µg/L	0.1	0.100	U	0.100	U	0.100	U	0.100	U	0.11	U	0.10	U	0.050	U	0.050	U
Benzo(ghi)perylene	µg/L	---	0.100	U	0.100	U	0.100	U	0.100	U	0.11	U	0.10	U	0.20	U	0.20	U
Benzo(k)fluoranthene	µg/L	0.14	0.100	U	0.100	U	0.100	U	0.100	U	0.11	U	0.10	U	0.050	U	0.050	U
Chrysene	µg/L	0.85	0.100	U	0.100	U	0.100	U	0.100	U	0.11	U	0.10	U	0.13	U	0.13	U
Dibenz(a,h)anthracene	µg/L	0.033	0.0173	U	0.0173	U	0.0173	U	0.0175	U	0.11	U	0.10	U	0.30	U	0.30	U
Fluoranthene	µg/L	---	0.12	J+	0.113	0.125		0.118		0.11	U	0.10	U	0.074	Ja	0.12	Ja	
Fluorene	µg/L	490	4.13	J+	3.95	5.88		5.88		0.36		1.6		2.5		3.4	*	
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.100	U	0.100	U	0.100	U	0.100	U	0.11	U	0.10	U	0.13	U	0.13	U
Naphthalene	µg/L	1.1	0.136	J+	0.142	0.653		0.739		1.4		9.7		1.6		1.0	Ja*	
Phenanthrene	µg/L	294	0.100	U	0.100	U	0.739		0.73		0.11	U	0.23		1.0		1.5	*
Pyrene	µg/L	---	0.126	J+	0.12	0.145		0.133		0.11	U	0.10	U	0.25	U	0.25	U	
1-Methylnaphthalene	µg/L	---	0.305	J+	0.311	13.9		15.4		na		na		na		na		
2-Methylnaphthalene	µg/L	61.2	0.100	U	0.100	U	0.100	U	0.100	U	na		na		na			
Inorganics																		
Cyanide, Total	mg/L	---	na		na	na		na		0.005	U	0.00500	U	0.010	U	0.010	U	
Cyanide, WAD	mg/L	0.2	0.0100	U	0.0100	U	0.0100	U	0.0100	U	na		na		na		na	
Manganese, Total	mg/L	0.775	0.129		0.131	0.145		0.141		0.0435		0.0476		0.058		0.062		
Natural Attenuation Parameters																		
Nitrate	mg/L	---	na		na	na		na		na		na		na		na		
Nitrite	mg/L	---	na		na	na		na		na		na		na		na		
Ammonia	mg/L	---	na		na	na		na		na		na		na		na		
Manganese, Dissolved	mg/L	---	na		na	na		na		0.0381		0.0419		0.050		0.058		
Iron, Dissolved	mg/L	---	na		na	na		na		1.89		2.03		2.3		2.3		
Sulfate	mg/L	---	na		na	na		na		na		na		na		na		
Sulfide	mg/L	---	na		na	na		na		na		na		na		na		
Methane	µg/L	---	na		na	na		na		na		na		na		na		
Alkalinity, Total	mg/L	---	na		na	na		na		na		na		na		na		
Total Kjeldahl Nitrogen	mg/L	---	na		na	na		na		na		na		na		na		
Orthophosphate	mg/L	---	na		na	na		na		na		na		na		na		
Total Organic Carbon	mg/L	---	na		na	na		na		na		na		na		na		
Chloride	mg/L	---	na		na	na		na		na		na		na		na		

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW37-GW-1004 19-Oct-2004	MW37-GW-0405 13-Apr-2005	MW37-GW-1005 12-Oct-2005	MW37-GW-0406 12-Apr-2006	MW37-GW-1006 09-Oct-2006	MW37-GW-0407 18-Apr-2007	MW37-GW-1007 09-Oct-2007	MW37-GW-0408 16-Apr-2008
VOCs									
Benzene	µg/L	5	70	40	19	8.83	2.07	1	U
Toluene	µg/L	1000	1.0	U	1.0	U	1.00	U	1.11
Ethylbenzene	µg/L	700	4.3		1.0	U	1.00	U	1
Xylenes, Total	µg/L	10000	4.3	2.0	J	2.0	U	3	U
PAHs									
Acenaphthene	µg/L	914	18	23	24	20.6	19.6	16.8	25.3
Acenaphthylene	µg/L	362	190	210	230	0.17	U	0.0944	U
Anthracene	µg/L	---	0.24	0.31	0.32	0.24	0.205	0.133	J
Benzo(a)anthracene	µg/L	0.13	0.12	U	0.054	Ja	0.12	U	0.00333
Benzo(a)pyrene	µg/L	0.2	0.12	U	0.044	Ja	0.12	U	0.032
Benzo(b)fluoranthene	µg/L	0.1	0.048	U	0.097	0.046	U	0.037	U
Benzo(ghi)perylene	µg/L	---	0.19	U	0.079	Ja	0.19	U	0.032
Benzo(k)fluoranthene	µg/L	0.14	0.048	U	0.092	..	0.046	U	0.015
Chrysene	µg/L	0.85	0.12	U	0.090	Ja	0.12	U	0.005
Dibenz(a,h)anthracene	µg/L	0.033	0.29	U	0.090	Ja	0.28	U	0.033
Fluoranthene	µg/L	---	0.15	0.22	0.18	0.182	J	0.133	J
Fluorene	µg/L	490	3.2	4.1	3.9	6.11	7.43	5.88	16.7
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.12	U	0.085	Ja	0.12	U	0.00778
Naphthalene	µg/L	1.1	1.2	U	0.45	Ja	1.2	U	0.385
Phenanthrene	µg/L	294	1.4	1.6	1.5	1.62	1.27	0.741	1.93
Pyrene	µg/L	---	0.24	U	0.24	U	0.036	U	0.339
1-Methylnaphthalene	µg/L	---	na	na	na	na	na	0.202	J
2-Methylnaphthalene	µg/L	61.2	na	na	na	na	0.0715	J	0.457
Inorganics									
Cyanide, Total	mg/L	---	0.010	U	0.010	U	0.0032	B	0.01
Cyanide, WAD	mg/L	0.2	na						
Manganese, Total	mg/L	0.775	0.074		0.073	0.070	0.07	na	na
Natural Attenuation Parameters									
Nitrate	mg/L	---	na	0.10	U	0.10	U	0.1	na
Nitrite	mg/L	---	na	0.020	U	0.0096	B	0.025	U
Ammonia	mg/L	---	na	0.67	0.50	0.622	U	na	na
Manganese, Dissolved	mg/L	---	0.062	0.069	0.068	0.0635	..	na	na
Iron, Dissolved	mg/L	---	2.4	2.3	2.6	2.55	na	na	na
Sulfate	mg/L	---	na	69	75	52.8	na	na	na
Sulfide	mg/L	---	na	1.0	U	1.0	U	1	na
Methane	µg/L	---	na	9.6	9.1	26	U	na	na
Alkalinity, Total	mg/L	---	na	410	400	480	na	na	na
Total Kjeldahl Nitrogen	mg/L	---	na	0.56	0.80	1	U	na	na
Orthophosphate	mg/L	---	na	0.012	B	0.0090	B	0.1	U,M1
Total Organic Carbon	mg/L	---	na	1.8	1.9	1.67	..	na	na
Chloride	mg/L	---	na	na	na	61.7	M1	na	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW37-GW-0409 22-Apr-2009	MW37-GW-1009 14-Oct-2009	MW37-GW-0110 14-Jan-2010	MW37-GW-0410 07-Apr-2010	MW37-GW-0710 07-Jul-2010	MW37-GW-1010 05-Oct-2010	MW37-GW-0411 11-Apr-2011
VOCs								
Benzene	µg/L	5	1	U	1	U	1.00	U
Toluene	µg/L	1000	1	U	1	U	1.00	U
Ethylbenzene	µg/L	700	1	U	1	U	1.00	U
Xylenes, Total	µg/L	10000	3	U	3	U	3.00	U
PAHs								
Acenaphthene	µg/L	914	4.41	9.39	9.49	10.4	8.52	10.3
Acenaphthylene	µg/L	362	0.313	0.709	0.834	0.843	0.577	0.867
Anthracene	µg/L	---	0.00826	J	0.0364	J	0.0259	J
Benzo(a)anthracene	µg/L	0.13	0.00944	J	0.0134	J	0.0104	J
Benzo(a)pyrene	µg/L	0.2	0.00850	U	0.016	U	0.0160	U
Benzo(b)fluoranthene	µg/L	0.1	0.00990	U	0.0076	U	0.00760	U
Benzo(ghi)perylene	µg/L	---	0.00550	U	0.0081	U	0.00810	U
Benzo(k)fluoranthene	µg/L	0.14	0.00790	U	0.0077	U	0.00770	U
Chrysene	µg/L	0.85	0.00530	U	0.007	U	0.00700	U
Dibenz(a,h)anthracene	µg/L	0.033	0.00760	U	0.0081	U	0.00810	U,MDL
Fluoranthene	µg/L	---	0.0129	J	0.0285	J	0.0283	J
Fluorene	µg/L	490	0.876	1.9	1.82	2.09	1.53	1.87
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.00690	U	0.011	U	0.0110	U
Naphthalene	µg/L	1.1	0.00590	U	0.029	U	0.0290	U
Phenanthrene	µg/L	294	0.0337	J	0.113	0.0554	J	0.100
Pyrene	µg/L	---	0.0134	J	0.0347	J	0.0546	J
1-Methylnaphthalene	µg/L	---	na	na	na	0.223	0.239	0.734
2-Methylnaphthalene	µg/L	61.2	0.00708	J	0.031	U	0.0310	U
Inorganics								
Cyanide, Total	mg/L	---	na	na	na	na	na	na
Cyanide, WAD	mg/L	0.2	na	na	0.0100	U	0.0100	U
Manganese, Total	mg/L	0.775	na	na	0.0619	U	0.0639	U
Natural Attenuation Parameters								
Nitrate	mg/L	---	na	na	na	0.10	U	na
Nitrite	mg/L	---	na	na	na	0.100	U	0.100
Ammonia	mg/L	---	na	na	na	0.627	na	0.560
Manganese, Dissolved	mg/L	---	na	na	na	0.065	na	0.0621
Iron, Dissolved	mg/L	---	na	na	na	2.6	na	0.0546
Sulfate	mg/L	---	na	na	na	41.8	na	2.80
Sulfide	mg/L	---	na	na	na	na	44.3	2.29
Methane	µg/L	---	na	na	na	48	na	5.00
Alkalinity, Total	mg/L	---	na	na	na	470	na	10
Total Kjeldahl Nitrogen	mg/L	---	na	na	na	1.00	U	143
Orthophosphate	mg/L	---	na	na	na	0.100	U	46.3
Total Organic Carbon	mg/L	---	na	na	na	1.00	U	15
Chloride	mg/L	---	na	na	na	30.7	na	424
								424
								1.13

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW37-GW-1011 25-Oct-2011	DV	MW37-GW-0412 10-Apr-2012	DV	MW37-GW-1012 09-Oct-2012	DV	MW37-GW-0413 09-Apr-2013	DV	MW37-GW-1013 22-Oct-2013	DV	MW41-GW-1002 31-Oct-2002	DV	MW41-GW-0103 07-Jan-2003		
VOCs																
Benzene	µg/L	5	1.03		1.00	U		1.48		0.500	U		9.11		2	
Toluene	µg/L	1000	1.00	U	1.00	U		1.00	U	1.00	U		1.00	U	2	
Ethylbenzene	µg/L	700	1.00	U	1.00	U		1.00	U	1.00	U		1.00	U	1.0	
Xylenes, Total	µg/L	10000	3.00	U	3.00	U		3.00	U	3.00	U		3.00	U	7	
PAHs																
Acenaphthene	µg/L	914	5.22	J-	12.4		J-	11.3	M1	J-	15.3		14.8		0.55	
Acenaphthylene	µg/L	362	0.696		0.823			1.07			1.22		2.02		1.1	
Anthracene	µg/L	---	0.100	U	0.100	U		0.100	U	0.100	U		0.100	U	0.055	
Benzo(a)anthracene	µg/L	0.13	0.100	U	0.100	U		0.100	U	0.100	U		0.100	U	0.11	
Benzo(a)pyrene	µg/L	0.2	0.100	U	0.100	U		0.100	U	0.100	U		0.100	U	0.11	
Benzo(b)fluoranthene	µg/L	0.1	0.100	U	0.100	U		0.100	U	0.100	U		0.100	U	0.11	
Benzo(ghi)perylene	µg/L	---	0.100	U	0.100	U		0.100	U,M1	UJ	0.100	U	UJ	0.100	U	
Benzo(k)fluoranthene	µg/L	0.14	0.100	U	0.100	U		0.100	U	0.100	U		0.100	U	0.11	
Chrysene	µg/L	0.85	0.100	U	0.100	U		0.100	U	0.100	U		0.100	U	0.11	
Dibenzo(a,h)anthracene	µg/L	0.033	0.0170	U,MDL	0.0170	U,MDL		0.0267	J, M1	J-	0.0173	U	UJ	0.0173	U	0.11
Fluoranthene	µg/L	---	0.100	U	0.100	U		0.100	U	0.100	U		0.100	U	0.11	
Fluorene	µg/L	490	1.77		2.13			2.00			2.91		3.27		0.11	
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.100	U	0.100	U		0.100	U,M1	UJ	0.100	U	UJ	0.100	U	
Naphthalene	µg/L	1.1	0.100	U	0.100	U		0.119		0.100	U		0.244		0.55	
Phenanthrene	µg/L	294	0.100	U	0.100	U		0.100	U	0.100	U		0.100	U	0.11	
Pyrene	µg/L	---	0.100	U	0.100	U		0.100	U	0.100	U		0.100	U	0.11	
1-Methylnaphthalene	µg/L	---	0.623		0.126			0.345		0.164			2.48		na	
2-Methylnaphthalene	µg/L	61.2	0.100	U	0.100	U		0.100	U	0.100	U		0.100	U	na	
Inorganics																
Cyanide, Total	mg/L	---	na		na			na		na			na		0.00592	
Cyanide, WAD	mg/L	0.2	0.0100	U	0.0100	U		0.0100	U	0.0100	U		0.0100	U	na	
Manganese, Total	mg/L	0.775	0.0654		0.0606			0.0715		0.0685			0.0716		0.229	
Natural Attenuation Parameters																
Nitrate	mg/L	---	0.10	U	0.10	U		0.100	U	0.100	U		na		na	
Nitrite	mg/L	---	0.100	U	0.10	U		0.100	U	0.100	U		na		na	
Ammonia	mg/L	---	0.647		0.623			0.579	M1	0.655			na		na	
Manganese, Dissolved	mg/L	---	0.0649		0.0709			0.0715		0.0656			na		0.0372	
Iron, Dissolved	mg/L	---	2.88		3.08			3.16		3.130			na		0.985	
Sulfate	mg/L	---	42.1		44.4			45.1		40.3			na		na	
Sulfide	mg/L	---	10	U	10	U		10	U	11.1			na		na	
Methane	µg/L	---	17		42			41		29.7			na		na	
Alkalinity, Total	mg/L	---	444		414			444		459			na		na	
Total Kjeldahl Nitrogen	mg/L	---	1.00	U	1.00	U		1.00	U	1.00	U		na		na	
Orthophosphate	mg/L	---	0.100	U	0.100	U		0.100	U,M1	0.100	U		na		na	
Total Organic Carbon	mg/L	---	1.00		na			na		na			na		na	
Chloride	mg/L	---	na		na			na		na			na		na	

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW41-GW-1003 20-Oct-2003	MW41-GW-0404 06-Apr-2004	MW41-GW-1004 19-Oct-2004	MW41-GW-0405 14-Apr-2005	MW41-GW-1005 13-Oct-2005	MW41-GW-0406 10-Apr-2006	MW41-GW-0410 07-Apr-2010	MW41-GW-0411 11-Apr-2011					
VOCs														
Benzene	µg/L	5	1.0	U	1.0	U	1.0	U	1.00	U	1.00	U		
Toluene	µg/L	1000	1.0	U	1.0	U	1.0	U	1.00	U	1.00	U		
Ethylbenzene	µg/L	700	1.0	U	1.0	U	1.0	U	1.00	U	1.00	U		
Xylenes, Total	µg/L	10000	1.0	U	1.0	U	2.0	U	2.0	U	6.00	U		
PAHs														
Acenaphthene	µg/L	914	2.5	U	2.4	U*	2.6	U	2.3	U	0.13	U	0.100	U
Acenaphthylene	µg/L	362	1.3	U	1.2	U*	1.3	U	1.2	U	0.17	U	0.100	U
Anthracene	µg/L	---	0.050	U*	0.048	U	0.051	U	0.047	U	0.049	U	0.0093	U
Benzo(a)anthracene	µg/L	0.13	0.13	U	0.12	U	0.13	U	0.12	U	0.13	U	0.019	U
Benzo(a)pyrene	µg/L	0.2	0.13	U	0.12	U	0.13	U	0.12	U	0.13	U	0.019	U
Benzo(b)fluoranthene	µg/L	0.1	0.050	U	0.048	U	0.051	U	0.047	U	0.049	U	0.037	U
Benzo(ghi)perylene	µg/L	---	0.20	U	0.19	U	0.20	U	0.19	U	0.20	U	0.032	U
Benzo(k)fluoranthene	µg/L	0.14	0.050	U	0.048	U	0.051	U	0.047	U	0.049	U	0.023	U
Chrysene	µg/L	0.85	0.13	U	0.12	U	0.13	U	0.12	U	0.13	U	0.02	U
Dibenz(a,h)anthracene	µg/L	0.033	0.30	U	0.29	U	0.31	U	0.28	U	0.29	U	0.033	U
Fluoranthene	µg/L	---	0.13	U	0.12	U	0.13	U	0.12	U	0.13	U	0.032	U
Fluorene	µg/L	490	0.25	U	0.24	U*	0.26	U	0.23	U	0.25	U	0.029	U
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.13	U	0.12	U	0.13	U	0.12	U	0.13	U	0.038	U
Naphthalene	µg/L	1.1	1.3	U	1.2	U*	1.3	U	1.2	U	1.3	U	0.1	U
Phenanthrene	µg/L	294	0.099	U	0.095	U*	0.10	U	0.093	U	0.098	U	0.015	U
Pyrene	µg/L	---	0.25	U	0.24	U	0.26	U	0.23	U	0.25	U	0.036	U
1-Methylnaphthalene	µg/L	---	na	na	na	na	0.100	U						
2-Methylnaphthalene	µg/L	61.2	na	na	na	na	0.100	U						
Inorganics														
Cyanide, Total	mg/L	---	0.010	U	0.010	U	0.010	U	0.010	U	0.01	U	na	na
Cyanide, WAD	mg/L	0.2	na	na	0.0100	U	0.0100	U						
Manganese, Total	mg/L	0.775	0.045	---	0.027	0.053	---	0.032	0.046	0.046	0.08	0.0316	0.0428	
Natural Attenuation Parameters														
Nitrate	mg/L	---	na	na	na	na								
Nitrite	mg/L	---	na	na	na									
Ammonia	mg/L	---	na	na	na									
Manganese, Dissolved	mg/L	---	0.028	0.027	0.027	0.027	0.027	0.026	0.026	0.0266	na	na		
Iron, Dissolved	mg/L	---	1.3	1.2	1.2	1.0	1.3	1.43	1.43	na	na			
Sulfate	mg/L	---	na	na	na									
Sulfide	mg/L	---	na	na	na									
Methane	µg/L	---	na	na	na									
Alkalinity, Total	mg/L	---	na	na	na									
Total Kjeldahl Nitrogen	mg/L	---	na	na	na									
Orthophosphate	mg/L	---	na	na	na									
Total Organic Carbon	mg/L	---	na	na	na									
Chloride	mg/L	---	na	na	na									

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW41-GW-0412 10-Apr-2012	MW41-GW-0413 09-Apr-2013	MW55-GW-1005 13-Oct-2005	MW55-GW-0406 11-Apr-2006	MW55-GW-1006 11-Oct-2006	MW55-GW-0407 17-Apr-2007	MW55-GW-1007 10-Oct-2007	MW55-GW-0408 15-Apr-2008
VOCs									
Benzene	µg/L	5	1.00	U	0.500	U	1.0	U	1
Toluene	µg/L	1000	1.00	U	1.00	U	1.0	U	1
Ethylbenzene	µg/L	700	1.00	U	1.00	U	1	U	1
Xylenes, Total	µg/L	10000	3.00	U	3.00	U	2.0	U	3
PAHs									
Acenaphthene	µg/L	914	0.100	U	0.100	U	2.4	U	0.13
Acenaphthylene	µg/L	362	0.100	U	0.100	U	1.2	U	0.17
Anthracene	µg/L	---	0.100	U	0.100	U	0.047	U	0.0093
Benzo(a)anthracene	µg/L	0.13	0.100	U	0.100	U	0.12	U	0.019
Benzo(a)pyrene	µg/L	0.2	0.100	U	0.100	U	0.12	U	0.019
Benzo(b)fluoranthene	µg/L	0.1	0.100	U	0.100	U	0.047	U	0.037
Benzo(ghi)perylene	µg/L	---	0.100	U	0.100	U	0.19	U	0.032
Benzo(k)fluoranthene	µg/L	0.14	0.100	U	0.100	U	0.047	U	0.023
Chrysene	µg/L	0.85	0.100	U	0.100	U	0.12	U	0.02
Dibenz(a,h)anthracene	µg/L	0.033	0.0170	U,MDL	0.0172	U	0.28	U	0.033
Fluoranthene	µg/L	---	0.100	U	0.100	U	0.12	U	0.032
Fluorene	µg/L	490	0.100	U	0.100	U	0.24	U	0.029
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.100	U	0.100	U	0.12	U	0.038
Naphthalene	µg/L	1.1	0.100	U	0.100	U	1.2	U	0.1
Phenanthrene	µg/L	294	0.100	U	0.100	U	0.094	U	0.015
Pyrene	µg/L	---	0.100	U	0.100	U	0.24	U	0.036
1-Methylnaphthalene	µg/L	---	0.100	U	0.100	U	na	na	na
2-Methylnaphthalene	µg/L	61.2	0.100	U	0.100	U	na	na	0.052
Inorganics									
Cyanide, Total	mg/L	---	na	na	0.011	0.01	U	0.01	U
Cyanide, WAD	mg/L	0.2	0.0100	U	0.0100	U	na	na	na
Manganese, Total	mg/L	0.775	0.193	0.204	0.046	0.0249	na	na	na
Natural Attenuation Parameters									
Nitrate	mg/L	---	na						
Nitrite	mg/L	---	na						
Ammonia	mg/L	---	na						
Manganese, Dissolved	mg/L	---	na	na	0.045	0.017	na	na	na
Iron, Dissolved	mg/L	---	na	na	0.042	B	0.1	U	na
Sulfate	mg/L	---	na						
Sulfide	mg/L	---	na						
Methane	µg/L	---	na						
Alkalinity, Total	mg/L	---	na						
Total Kjeldahl Nitrogen	mg/L	---	na						
Orthophosphate	mg/L	---	na						
Total Organic Carbon	mg/L	---	na						
Chloride	mg/L	---	na						

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW55-GW-0410 08-Apr-2010	MW55-GW-1010 05-Oct-2010	MW55-GW-0411 12-Apr-2011	MW55-GW-1011 25-Oct-2011	MW55-GW-0412 11-Apr-2012	MW55-GW-1012 09-Oct-2012	MW55-GW-0413 10-Apr-2013	MW55-GW-1013 22-Oct-2013
								DV	DV
VOCs									
Benzene	µg/L	5	1.00 U	0.500 U	0.500 U				
Toluene	µg/L	1000	1.00 U						
Ethylbenzene	µg/L	700	1.00 U						
Xylenes, Total	µg/L	10000	6.00 U	3.00 U					
PAHs									
Acenaphthene	µg/L	914	0.100 U	0.202	0.422	0.100 U	0.100 U	0.100 U	0.100 U
Acenaphthylene	µg/L	362	0.100 U	0.100 U	0.608	0.100 U	0.100 U	0.100 U	0.100 U
Anthracene	µg/L	---	0.100 U						
Benzo(a)anthracene	µg/L	0.13	0.100 U						
Benzo(a)pyrene	µg/L	0.2	0.100 U						
Benzo(b)fluoranthene	µg/L	0.1	0.100 U						
Benzo(ghi)perylene	µg/L	---	0.100 U						
Benzo(k)fluoranthene	µg/L	0.14	0.100 U						
Chrysene	µg/L	0.85	0.100 U						
Dibenz(a,h)anthracene	µg/L	0.033	0.100 U	0.00810 U,MDL	0.170 U,MDL	0.0170 U,MDL	0.0170 U,MDL	0.0130 U,MDL	0.0173 U
Fluoranthene	µg/L	---	0.100 U						
Fluorene	µg/L	490	0.0380 J,MDL	0.100 U					
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.100 U						
Naphthalene	µg/L	1.1	0.100 U	0.672	1.20	0.100 U	0.172	0.100 U	0.113 J+
Phenanthrene	µg/L	294	0.100 U	0.100 U	0.195	0.100 U	0.100 U	0.100 U	0.100 U
Pyrene	µg/L	---	0.100 U						
1-Methylnaphthalene	µg/L	---	0.100 U	0.704	2.91 U	0.100 U	0.100 U	0.100 U	0.131 J+
2-Methylnaphthalene	µg/L	61.2	0.100 U						
Inorganics									
Cyanide, Total	mg/L	---	na						
Cyanide, WAD	mg/L	0.2	0.0100 U						
Manganese, Total	mg/L	0.775	0.0187	0.0100 U	0.0135	0.0103	0.0214	0.0128	0.0107
Natural Attenuation Parameters									
Nitrate	mg/L	---	0.10 U	0.10 U	0.10 U	0.10 U	0.100 U	0.100 U	na
Nitrite	mg/L	---	0.100 U	na					
Ammonia	mg/L	---	1.43	1.41	1.49	1.44	1.48	1.41	1.54
Manganese, Dissolved	mg/L	---	0.0184	0.0100 U	0.0129	0.0100 U	0.0130 R	0.0112	0.0100 U
Iron, Dissolved	mg/L	---	0.380	0.234	0.127	0.100 U	0.103	0.108	0.100 U
Sulfate	mg/L	---	89.5	36.2	89.6	86.7	90.3	94.8	87.2
Sulfide	mg/L	---	5.00 U	5.00 U	16	10 U	10 U	10.0 U	na
Methane	µg/L	---	26.0 U	26.0 U	1.5	2.1	1.9	3.1	2.58
Alkalinity, Total	mg/L	---	432	402	393	390	385	375	410
Total Kjeldahl Nitrogen	mg/L	---	1.77	1.54	1.83	1.92	1.58	1.70	1.79
Orthophosphate	mg/L	---	0.100 U	na					
Total Organic Carbon	mg/L	---	1.00 U	1.00 U	na	1.00 U	na	na	na
Chloride	mg/L	---	2.00 U,RL1	2.00 U,RL1	na	na	na	na	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW56-GW-1011 27-Jul-2011	MW56-GW-1011 24-Oct-2011	MW56-GW-0412 10-Apr-2012	MW56-GW-1012 09-Oct-2012	MW56-GW-0413 09-Apr-2013	MW56-GW-1013 22-Oct-2013	MW57-GW-1011 27-Jul-2011
				DV	DV	DV	DV	DV
<u>VOCs</u>								
Benzene	µg/L	5	1.00 U	1.00 U	1.00 U	0.500 U UJ	0.500 U	1.00 U
Toluene	µg/L	1000	1.00 U	1.00 U	1.00 U	1.00 U UJ	1.00 U	1.00 U
Ethylbenzene	µg/L	700	1.00 U	1.00 U	1.00 U	1.00 U UJ	1.00 U	1.00 U
Xylenes, Total	µg/L	10000	3.00 U	3.00 U	3.00 U	3.00 U UJ	3.00 U	3.00 U
<u>PAHs</u>								
Acenaphthene	µg/L	914	0.100 U					
Acenaphthylene	µg/L	362	0.100 U					
Anthracene	µg/L	---	0.100 U					
Benzo(a)anthracene	µg/L	0.13	0.100 U					
Benzo(a)pyrene	µg/L	0.2	0.100 U					
Benzo(b)fluoranthene	µg/L	0.1	0.100 U					
Benzo(ghi)perylene	µg/L	---	0.100 U					
Benzo(k)fluoranthene	µg/L	0.14	0.100 U					
Chrysene	µg/L	0.85	0.100 U					
Dibenz(a,h)anthracene	µg/L	0.033	0.0170 U,MDL	0.0170 U,MDL	0.0170 U,MDL	0.0130 U,MDL	0.0172 U	0.0173 U
Fluoranthene	µg/L	---	0.100 U					
Fluorene	µg/L	490	0.100 U					
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.100 U					
Naphthalene	µg/L	1.1	0.100 U	0.287				
Phenanthrene	µg/L	294	0.100 U					
Pyrene	µg/L	---	0.100 U					
1-Methylnaphthalene	µg/L	---	0.100 U	0.105				
2-Methylnaphthalene	µg/L	61.2	0.100 U	0.112				
<u>Inorganics</u>								
Cyanide, Total	mg/L	---	na	na	na	na	na	na
Cyanide, WAD	mg/L	0.2	0.0100 U					
Manganese, Total	mg/L	0.775	0.130	0.123	0.0673 J+	0.0875	0.0792	0.0713
<u>Natural Attenuation Parameters</u>								
Nitrates	mg/L	---	na	na	0.100 U	0.100 U	0.100 U	na
Nitrite	mg/L	---	na	na	0.100 U	0.100 U	0.100 U	na
Ammonia	mg/L	---	na	na	1.1	1.04	1.13	na
Manganese, Dissolved	mg/L	---	na	na	0.0821	0.0840	0.0764	na
Iron, Dissolved	mg/L	---	na	na	1.4	1.70	1.670	na
Sulfate	mg/L	---	na	na	66.9	67.4	60.5	na
Sulfide	mg/L	---	na	na	10 U	10 U	10.0 U	na
Methane	µg/L	---	na	na	11	10	9.84	na
Alkalinity, Total	mg/L	---	na	na	370	370	410	na
Total Kjeldahl Nitrogen	mg/L	---	na	na	1.33	1.22	1.11	na
Orthophosphate	mg/L	---	na	na	0.100 U	0.100 U	0.100 U	na
Total Organic Carbon	mg/L	---	na	na	na	na	na	na
Chloride	mg/L	---	na	na	na	na	na	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

	Performance Standard	MW57-GW-1011 24-Oct-2011	MW57-GW-0412 10-Apr-2012	MW57-GW-1012 09-Oct-2012	MW57-GW-0413 09-Apr-2013	MW57-GW-1013 22-Oct-2013
		DV	DV	DV	DV	
VOCs	Units					
Benzene	µg/L	5	1.00 U	1.00 U	1.00 U	0.500 U
Toluene	µg/L	1000	1.00 U	1.00 U	1.00 U	1.00 U
Ethylbenzene	µg/L	700	1.00 U	1.00 U	1.00 U	1.00 U
Xylenes, Total	µg/L	10000	3.00 U	3.00 U	3.00 U	3.00 U
PAHs						
Acenaphthene	µg/L	914	0.100 U	0.100 U	0.100 U	0.100 U
Acenaphthylene	µg/L	362	0.100 U	0.100 U	0.100 U	0.100 U
Anthracene	µg/L	---	0.100 U	0.100 U	0.100 U	0.100 U
Benzo(a)anthracene	µg/L	0.13	0.100 U	0.100 U	0.100 U	0.100 U
Benzo(a)pyrene	µg/L	0.2	0.100 U	0.100 U	0.100 U	0.100 U
Benzo(b)fluoranthene	µg/L	0.1	0.100 U	0.100 U	0.100 U	0.100 U
Benzo(ghi)perylene	µg/L	---	0.100 U	0.100 U	0.100 U	0.100 U
Benzo(k)fluoranthene	µg/L	0.14	0.100 U	0.100 U	0.100 U	0.100 U
Chrysene	µg/L	0.85	0.100 U	0.100 U	0.100 U	0.100 U
Dibenz(a,h)anthracene	µg/L	0.033	0.0170 U,MDL	0.0170 U,MDL	0.0130 U,MDL	0.0173 U
Fluoranthene	µg/L	---	0.100 U	0.100 U	0.100 U	0.100 U
Fluorene	µg/L	490	0.100 U	0.100 U	0.100 U	0.100 U
Indeno(1,2,3-cd)pyrene	µg/L	0.1	0.100 U	0.100 U	0.100 U	0.100 U
Naphthalene	µg/L	1.1	0.126	0.100 U	0.100 U	0.100 U
Phenanthrene	µg/L	294	0.100 U	0.100 U	0.100 U	0.100 U
Pyrene	µg/L	---	0.100 U	0.100 U	0.100 U	0.100 U
1-Methylnaphthalene	µg/L	---	0.100 U	0.100 U	0.100 U	0.100 U
2-Methylnaphthalene	µg/L	61.2	0.100 U	0.100 U	0.100 U	0.100 U
Inorganics						
Cyanide, Total	mg/L	---	na	na	na	na
Cyanide, WAD	mg/L	0.2	0.0100 U	0.0100 U	0.0100 U	0.0100 U
Manganese, Total	mg/L	0.775	0.317	0.18	0.246	0.216
Natural Attenuation Parameters						
Nitrate	mg/L	---	na	0.1 U	0.100 U	0.100 U
Nitrite	mg/L	---	na	0.1 U	0.100 U	0.100 U
Ammonia	mg/L	---	na	1.5	1.40	1.55
Manganese, Dissolved	mg/L	---	na	0.228	0.198	0.195
Iron, Dissolved	mg/L	---	na	1.28	1.37	1.520
Sulfate	mg/L	---	na	120	132	120
Sulfide	mg/L	---	na	10 U	10 U	28.3
Methane	µg/L	---	na	10	11	12.8
Alkalinity, Total	mg/L	---	na	355	360	376
Total Kjeldahl Nitrogen	mg/L	---	na	1.78	1.79	1.72
Orthophosphate	mg/L	---	na	0.1: U	0.100 U	0.100 U
Total Organic Carbon	mg/L	---	na	na	na	na
Chloride	mg/L	---	na	na	na	na

Iowa City, Iowa Former Manufactured Gas Plant Site
MidAmerican Energy Company

Groundwater Analytical Results

Notes:

na = not analyzed.
ns = not sampled, insufficient water.
nc = RPD not calculated.
RPD = Relative Percent Difference.
mg/L = milligrams per liter.
µg/L = microgram per liter.

Laboratory Qualifiers

* = Batch QC exceeds upper or lower control limits.
B = Analyte was detected in the associated Method Blank.
B1 = Analyte was detected in the associated Method Blank. Analyte concentration in the sample is greater than 10x the concentration found in the Method Blank.
C9 = Calibration Verification recovery was outside the method control limits for this analyte. The LCS for this analyte met CCV acceptance criteria, and was used to validate the batch.
CN5 = Sample found to contain Sulfide. The sulfide was treated and removed prior to distillation.
ET = Matrix interference in sample is causing an endpoint timeout.
H = Sample analysis performed past method-specified holding time.
H2 = Initial analysis within holding time. Reanalysis verification was past holding time.
J = Result is less than the RL but greater than or equal to the MDL and the concentration is an approximate value.
Ja = Result is less than the RL but greater than or equal to the MDL and the concentration is an approximate value.
L1 = Laboratory Control Sample and/or Laboratory Control Sample Duplicate recovery was outside control limits.
M1 = The MS and/or MSD were outside control limits.
MDL = Results calculated/entered to the method detection limit (MDL).
MHA = Due to high levels of analyte in the sample, the MS/MSD calculation does not provide useful spike recovery information.
P2 = Sample adjusted to method prescribed pH range prior to analysis.
R = Sample duplicate RPD exceeded the laboratory control limit.
RL1 = Reporting limit raised due to sample matrix effects.
S3 = Post digestion spike is out of acceptance limits for this analyte.
U = Indicates the analyte was analyzed for but not detected.
U* = Indicates the analyte was analyzed for but not detected. Batch QC exceeds the upper or lower control limits.
Ua = Analyte was not detected at or above the stated limit. Concentration is below the method reporting limit.
Z6 = Surrogate recovery was outside control-limits.
ZX = Due to sample matrix effects, the surrogate recovery was outside the control limits.

Data Validation (DV) Qualifiers

B = The analyte was found in an associated blank, as well as in the sample at a concentration greater than 5 times (or 10 times for common laboratory contaminants) that detected in an associated blank.
J = The analyte was positively identified; the quantitation is an estimation.
J+ = The analyte was positively identified; the quantitation is an estimation with a potential high bias.
J- = The analyte was positively identified; the quantitation is an estimation with a potential low bias.
UB = The analyte is considered not detected; the concentration in the sample was less than 5 times (or 10 times for common laboratory contaminants) that detected in an associated blank.
UJ = The analyte was analyzed for, but not detected. Due to a QC deficiency identified during data validation, the value reported may not accurately reflect the sample quantitation limit.
Data collected as part of the Remedial Action qualified in accordance with the January 2009 Quality Assurance Project Plan.

ATTACHMENT 3

Sediment Sampling Results

TABLE 4-1

**RALSTON CREEK - SEDIMENT ANALYTICAL RESULTS
MIDAMERICAN ENERGY COMPANY
FORMER MANUFACTURED GAS PLANT SITE – IOWA CITY, IOWA**

Units	Performance Standard	RC04	RC04	RC04	RC04	RC04	RC04
		RC04-RS 9/17/2002	RC-04-RS DUP 9/17/2002	RC04-SD-0410 4/8/2010	RC04-SD-1010 10/5/2010	DP01-SD-1010 10/5/2010	RC04-SD-1111 11/11/2011
Polynuclear Aromatic Hydrocarbons (PAHs)							
Acenaphthene	mg/kg	---	0.021	<0.2	U	<0.353	U,RL1
Acenaphthylene	mg/kg	---	<0.04	U	<0.39	U	<0.353
Anthracene	mg/kg	0.845	0.0071	<0.04	U	<0.353	U,RL1
Benzo(a)anthracene	mg/kg	1.050	0.013	J	0.052	J	<0.353
Benzo(a)pyrene	mg/kg	1.450	0.059	J	0.08	<0.353	U,RL1
Benzo(b)fluoranthene	mg/kg	---	0.068	0.087	<0.353	U,RL1	<0.117
Benzo(ghi)perylene	mg/kg	---	0.029	0.037	J	<0.353	U,RL1
Benzo(k)fluoranthene	mg/kg	---	0.011	J	0.029	J	<0.353
Chrysene	mg/kg	1.290	<0.0041	U	0.066	<0.353	U,RL1
Dibenzo(a,h)anthracene	mg/kg	---	0.017	<0.12	U	<0.353	U,RL1
Fluoranthene	mg/kg	2.230	0.041	J	0.21	<0.353	U,RL1
Fluorene	mg/kg	0.536	<0.018	U	<0.180	U	<0.353
Indeno(1,2,3-cd)pyrene	mg/kg	---	0.015	0.014	J	<0.353	U,RL1
Naphthalene	mg/kg	0.561	0.20	<0.59	U	11.3	RL1
Phenanthrene	mg/kg	1.170	0.056	0.14	<0.353	U,RL1	<0.117
Pyrene	mg/kg	1.520	0.059	0.14	<0.353	U,RL1	<0.117
2-Methylnaphthalene	mg/kg	---	na	na	0.363	RL1	0.363
Total PAHs	mg/kg	22.8	0.435	0.687	11.300	0.259	0.161
							0.518

TABLE 4-1

**RALSTON CREEK - SEDIMENT ANALYTICAL RESULTS
MIDAMERICAN ENERGY COMPANY
FORMER MANUFACTURED GAS PLANT SITE – IOWA CITY, IOWA**

Units	Performance Standard	RC04		RC04		RC04		RC05		RC05		RC05			
		DP01-SD-1111	11/11/2011 0-0.5 feet	RC04-SD-1112	11/8/2012 0-0.5 feet	RC04-SD-1013	10/24/2013 0-0.5 feet	DV	RC05-RS	9/17/2002 0-0.5 feet	RC05-SD-0410	4/8/2010 0-0.5 feet	DV	DP01-SD-0410	4/8/2010 0-0.5 feet
Polynuclear Aromatic Hydrocarbons (PAHs)															
Acenaphthene	mg/kg	---	<0.586	U,RL1	<0.516	U,RL1	<0.130	U	0.93		<0.128	U,RL1,M1		<0.135	U,RL1
Acenaphthylene	mg/kg	---	<0.586	U,RL1	<0.516	U,RL1	<0.130	U	<0.43	U	<0.128	U,RL1		<0.135	U,RL1
Anthracene	mg/kg	0.845	<0.586	U,RL1,M1	<0.516	U,RL1	<0.130	U	0.10		<0.128	U,RL1		<0.135	U,RL1
Benzo(a)anthracene	mg/kg	1.050	<0.586	U,RL1	<0.516	U,RL1	<0.130	U	0.18		<0.128	U,RL1		0.221	RL1
Benzo(a)pyrene	mg/kg	1.450	<0.586	U,RL1	<0.516	U,RL1	<0.130	U	0.19		<0.128	U,RL1		0.222	RL1
Benzo(b)fluoranthene	mg/kg	---	<0.586	U,RL1,M1	<0.516	U,RL1	<0.130	U	0.25		<0.128	U,RL1		0.271	RL1
Benzo(ghi)perylene	mg/kg	---	<0.586	U,RL1	<0.516	U,RL1	<0.130	U	0.055	J	<0.128	U,RL1		0.152	RL1
Benzo(k)fluoranthene	mg/kg	---	<0.586	U,RL1	<0.516	U,RL1	<0.130	U	0.088		<0.128	U,RL1		<0.135	U,RL1
Chrysene	mg/kg	1.290	<0.586	U,RL1	<0.516	U,RL1	<0.130	U	0.11		<0.128	U,RL1		0.196	RL1
Dibeno(a,h)anthracene	mg/kg	---	<0.586	U,RL1	<0.516	U,RL1	<0.130	U	<0.13	U	<0.128	U,RL1		<0.135	U,RL1
Fluoranthene	mg/kg	2.230	<0.586	U,RL1,M1	<0.516	U,RL1	<0.130	U	0.35		0.176	RL1,M1	J+	0.544	RL1
Fluorene	mg/kg	0.536	<0.586	U,RL1	<0.516	U,RL1	<0.130	U	0.20		<0.128	U,RL1		<0.135	U,RL1
Indeno(1,2,3-cd)pyrene	mg/kg	---	<0.586	U,RL1	<0.516	U,RL1	<0.130	U	0.10		<0.128	U,RL1		<0.135	U,RL1
Naphthalene	mg/kg	0.561	<0.586	U,RL1	<0.516	U,RL1	0.421	J,J+	0.74		0.403	RL1,L1, M1	J-	0.233	RL1,L1
Phenathrene	mg/kg	1.170	<0.586	U,RL1	<0.516	U,RL1	<0.130	U	0.40		<0.128	U,RL1		0.236	RL1
Pyrene	mg/kg	1.520	<0.586	U,RL1,M1	<0.516	U,RL1	<0.130	U	0.38		0.136	RL1		0.407	RL1
2-Methylnaphthalene	mg/kg	---	<0.586	U,RL1	<0.516	U,RL1	<0.130	U	na		<0.128	U,RL1		<0.135	U,RL1
Total PAHs	mg/kg	22.8	0.000		0.000		0.421		2.650		0.715			2.059	

TABLE 4-1

RALSTON CREEK - SEDIMENT ANALYTICAL RESULTS
MIDAMERICAN ENERGY COMPANY
FORMER MANUFACTURED GAS PLANT SITE – IOWA CITY, IOWA

Units	Performance Standard	RC05		RC05		RC05		RC05		RC05		RC05	
		RC05-SD-1010 10/5/2010 0-0.5 feet	RC05-SD-1111 11/11/2011 0-0.5 feet	DV	RC05-SD-1112 11/8/2012 0-0.5 feet	DP01-SD-1112 11/8/2012 0-0.5 feet	RC05-SD-1013 10/24/2013 0-0.5 feet	DP01-SD-1013 10/24/2013 0-0.5 feet	RC05-SD-1013 10/24/2013 0-0.5 feet	DP01-SD-1013 10/24/2013 0-0.5 feet			
Polynuclear Aromatic Hydrocarbons (PAHs)													
Acenaphthene	mg/kg	---	0.199	RL1,M1	<0.552	U,RL1	<0.580	U,RL1	0.663	RL1	<0.116	U	<0.116 U
Acenaphthylene	mg/kg	---	<0.117	U,RL1	<0.552	U,RL1	<0.580	U,RL1	<0.560	U,RL1	<0.116	U	<0.116 U
Anthracene	mg/kg	0.845	0.118	RL1,M1	0.593	RL1 J+	<0.580	U,RL1	<0.560	U,RL1	<0.116	U	<0.116 U
Benzo(a)anthracene	mg/kg	1.050	<0.117	U,RL1,M1	1.60	RL1 J+	<0.580	U,RL1	<0.560	U,RL1	<0.116	U	<0.116 U
Benzo(a)pyrene	mg/kg	1.450	<0.117	U,RL1,M1	1.20	RL1 J+	<0.580	U,RL1	<0.560	U,RL1	<0.116	U	<0.116 U
Benzo(b)fluoranthene	mg/kg	---	<0.117	U,RL1,M1	1.70	RL1 J+	<0.580	U,RL1	<0.560	U,RL1	<0.116	U	<0.116 U
Benzo(ghi)perylene	mg/kg	---	<0.117	U,RL1,M1	0.653	RL1 J+	<0.580	U,RL1	<0.560	U,RL1	<0.116	U	<0.116 U
Benzo(k)fluoranthene	mg/kg	---	<0.117	U,RL1	<0.552	U,RL1	<0.580	U,RL1	<0.560	U,RL1	<0.116	U	<0.116 U
Chrysene	mg/kg	1.290	<0.117	U,RL1	1.38	RL1 J+	<0.580	U,RL1	<0.560	U,RL1	<0.116	U	<0.116 U
Dibenzo(a,h)anthracene	mg/kg	---	<0.117	U,RL1	<0.552	U,RL1	<0.580	U,RL1	<0.560	U,RL1	<0.116	U	<0.116 U
Fluoranthene	mg/kg	2.230	0.125	RL1,M1	3.14	RL1 J+	<0.580	U,RL1	<0.560	U,RL1	<0.116	U	<0.116 U
Fluorene	mg/kg	0.536	<0.117	U,RL1,M1	<0.552	U,RL1	<0.580	U,RL1	<0.560	U,RL1	<0.116	U	<0.116 U
Indeno(1,2,3-cd)pyrene	mg/kg	---	<0.117	U,RL1,M1	0.572	RL1 J+	<0.580	U,RL1	<0.560	U,RL1	<0.116	U	<0.116 U
Naphthalene	mg/kg	0.561	0.894	RL1,M1	1.57	RL1 J+	3.94	RL1	4.47	RL1	0.204		0.277
Phenanthrene	mg/kg	1.170	0.39	RL1,M1	2.37	RL1 J+	<0.580	U,RL1	<0.560	U,RL1	<0.116	U	<0.116 U
Pyrene	mg/kg	1.520	<0.117	U,RL1	2.26	RL1 J+	<0.580	U,RL1	<0.560	U,RL1	<0.116	U	<0.116 U
2-Methylnaphthalene	mg/kg	---	<0.117	U,RL1,M1	<0.552	U,RL1	<0.580	U,RL1	<0.560	U,RL1	<0.116	U	<0.116 U
Total PAHs	mg/kg	22.8	1.527		14.113		3.94		4.47		0.204		0.277

TABLE 4-1

RALSTON CREEK - SEDIMENT ANALYTICAL RESULTS
MIDAMERICAN ENERGY COMPANY
FORMER MANUFACTURED GAS PLANT SITE - IOWA CITY, IOWA

Notes:

< = Less than.

mg/kg = Milligram(s) per kilogram.

na = Constituent not analyzed.

Concentrations above Performance Standard in bold font.

PAH = Polynuclear aromatic hydrocarbon.

Laboratory Qualifiers

U = Compound not detected above reporting limit.

J = Estimated value below reporting limit.

L1 = Laboratory Control Sample and/or Laboratory Control Sample Duplicate recovery was outside control limits.

M1 = The matrix spike (MS) and/or matrix spike duplicate (MSD) were outside control limits.

RL1 = Reporting limit raised due to sample matrix effects.

Data Validation (DV) Qualifiers

J = The analyte was positively identified; the quantitation is an estimation.

J+ = The analyte was positively identified; the quantitation is an estimation with a potential high bias.

J- = The analyte was positively identified; the quantitation is an estimation with a potential low bias.

UJ = The analyte was analyzed for, but not detected. Due to a quality control (QC) deficiency identified during data validation, the value reported may not accurately reflect the sample quantitation

Attachment 4

Groundwater Contaminants of Concern Trend Analysis Summary

TABLE 3-2
STATISTICAL SUMMARY
MIDAMERICAN ENERGY COMPANY
FORMER MANUFACTURED GAS PLANT SITE - IOWA CITY, IOWA

	VOCs					PAHs										Inorganics					
	Benzene	Toluene	Ethylbenzene	Xylenes, total		Acenaphthene	Acenaphthylene	Benzo(a)anthracene	Benz(a)pyrene	Benz(b)fluoranthene	Benzo(k)fluoranthene	Chrysene	Dibenz(a,h)anthracene	Fluorene	Indeno(1,2,3-cd)pyrene	Naphthalene	Phenanthrene	2-Methylnaphthalene	Manganese	Cyanide	
Performance Standard	5	1000	700	10000	914	362	0.13	0.2	0.1	0.14	0.85	0.033	490	0.1	1.1	294.0	61.2	775	0.200		
Compliance Wells																					
MW-7	UCL	<1	<1	<1	<3	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.017	<0.1	<0.1	<0.1	<0.1	8764	<0.01		
	Trend	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	D90	NT	
MW-29	UCL	<1	<1	<1	<3	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.017	<0.1	<0.1	<0.1	<0.1	134	<0.01		
	Trend	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	D90	NT	
MW-33	UCL	<1	<1	<1	<3	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.017	<0.1	<0.1	<0.1	<0.1	426	<0.01		
	Trend	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	D90	NT	
MW-35	UCL	<1	<1	<1	<3	0.149	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.017	0.077	<0.1	0.495	0.055	0.092	535	<0.01	
	Trend	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	I90	NT	NT	NT	I90	NT	
MW-41	UCL	<1	<1	<1	<3	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.017	<0.1	<0.1	<0.1	<0.1	181	<0.01		
	Trend	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	
MW-56	UCL	<1	<1	<1	<3	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.017	<0.1	<0.1	<0.1	<0.1	115	<0.01		
	Trend	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	D90	NT	
MW-57	UCL	<1	<1	<1	<3	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.017	<0.1	<0.1	<0.1	0.215	<0.1	427	<0.01	
	Trend	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	D90	NT	NT	NT	NT	NT	
TI Zone Wells																					
MW-3	Trend	D90	NT	I90	NT	D90	I90	NT	NT	NT	NT	NT	NT	NT	NT	D90	NT	D90	D90	I90	
MW-12	Trend	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT
MW-13	Trend	D90	D90	D90	D90	D90	D90	D90	D90	D90	D90	D90	D90	D90	D90	D90	D90	D90	D90	D90	NT
MW-16	Trend	NT	NT	NT	NT	NT	NT	NT	I90	I90	I90	I90	I90	I90	I90	I90	I90	I90	I90	I90	NT
MW-18	Trend	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	I90	I90	I90	I90	NT
MW-19	Trend	D90	NT	NT	NT	D90	D90	NT	NT	NT	NT	NT	NT	NT	D90	NT	D90	D90	D90	D90	NT
MW-20	Trend	I90	NT	NT	NT	D90	D90	D90	NT	NT	NT	NT	NT	NT	D90	NT	NT	NT	NT	D90	NT
MW-23	Trend	NT	NT	NT	D90	D90	D90	NT	NT	NT	NT	NT	NT	NT	D90	NT	D90	NT	NT	NT	NT
MW-25	Trend	I90	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	D90	NT	NT	NT	D90	D90	NT
MW-31	Trend	I90	I90	I90	I90	NT	NT	NT	D90	D90	D90	D90	D90	D90	D90	NT	NT	I90	D90	NT	
MW-36	Trend	I90	NT	NT	NT	I90	I90	D90	NT	D90	NT	D90	NT	NT	I90	NT	NT	D90	NT	NT	NT
MW-37	Trend	I90	NT	NT	NT	I90	I90	I90	NT	NT	NT	NT	NT	I90	NY	I90	NT	NT	NT	NT	NT
MW-55	Trend	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	D90	NT	

Notes:

NT = No statistically significant trend at greater than or equal to 90-percent confidence level.

D90 = Decreasing trend at greater than or equal to 90-percent confidence level.

I90 = Increasing trend at greater than or equal to 90-percent confidence level.

All concentration units in micrograms per liter except for cyanide, which is in milligrams per liter.

Statistical summary based on samples collected through October 2013.

UCL = 95 Percent Upper Confidence Limit.

Calculated UCLs that exceed the respective Performance Standard and increasing trends are shown in red text.

PAHs = Polynuclear aromatic hydrocarbons.

TI = Technical Impracticability.

VOCs = Volatile organic compounds.

ATTACHMENT 5

Five-Year Review Inspection Form

Attachment 5
FIVE-YEAR REVIEW INSPECTION FORM

I. SITE INFORMATION			
Site name: Iowa City FMGP	Date of inspection: July 7, 2014		
Location: Iowa City, Iowa	EPA ID: IAD984591172		
Agency, office, or company leading the five-year review: EPA-Region 7	Weather/temperature: Sunny and mid-80s		
Remedy Includes: (Check all that apply)			
<input type="checkbox"/> Landfill cover/containment <input checked="" type="checkbox"/> Monitored natural attenuation <input type="checkbox"/> Access controls <input type="checkbox"/> Groundwater containment <input checked="" type="checkbox"/> Institutional controls <input type="checkbox"/> Vertical barrier walls <input type="checkbox"/> Groundwater pump and treatment <input type="checkbox"/> Surface water collection and treatment <input checked="" type="checkbox"/> Other <u>LNAPL recovery and air monitoring</u>			
Attachments: <input type="checkbox"/> Inspection team roster attached <input type="checkbox"/> Site map attached			
II. INTERVIEWS (Check all that apply)			
1. O&M site manager <u>Kevin Armstrong</u> Name _____	Project Manager, MWH _____ Title _____	7-7-14 Date _____	
Interviewed <input checked="" type="checkbox"/> at site <input type="checkbox"/> at office <input type="checkbox"/> by phone Phone no. <u>515-251-1023</u>			
Problems, suggestions; <input type="checkbox"/> Report attached _____			
2. Other interviews (optional) <input type="checkbox"/> Report attached.			
Bryan Clark, Owner, Iowa-Illinois Square apartments-granted access to building crawlspace and discussed ongoing air monitoring in the building			
Jennifer McIvor, Environmental Manager, MidAmerican Energy Company-manages remedial action activities for all actions except air monitoring in Iowa-Illinois Square			
Ron Knoche, City Engineer, City of Iowa City-Engineering office oversees maintenance of Ralston Creek and directs Public Works to conduct needed maintenance.			
Ben Clark, Senior Civil Engineer, City of Iowa City			
III. DOCUMENTS & RECORDS VERIFIED (Check all that apply)			
1. O&M Documents			
<input checked="" type="checkbox"/> O&M manual	<input type="checkbox"/> Readily available	<input checked="" type="checkbox"/> Up to date	<input type="checkbox"/> N/A
<input type="checkbox"/> As-built drawings	<input type="checkbox"/> Readily available	<input type="checkbox"/> Up to date	<input checked="" type="checkbox"/> N/A
<input type="checkbox"/> Maintenance logs	<input type="checkbox"/> Readily available	<input type="checkbox"/> Up to date	<input checked="" type="checkbox"/> N/A
Remarks _____			

2.	Site-Specific Health and Safety Plan	<input checked="" type="checkbox"/> Readily available	<input checked="" type="checkbox"/> Up to date	<input type="checkbox"/> N/A
	□ Contingency plan/emergency response plan	<input type="checkbox"/> Readily available	<input type="checkbox"/> Up to date	<input type="checkbox"/> N/A
	Remarks _____			
3.	O&M and OSHA Training Records	<input checked="" type="checkbox"/> Readily available	<input checked="" type="checkbox"/> Up to date	<input type="checkbox"/> N/A
	Remarks _____			
4.	Permits and Service Agreements			
	□ Air discharge permit	<input type="checkbox"/> Readily available	<input type="checkbox"/> Up to date	<input checked="" type="checkbox"/> N/A
	□ Effluent discharge	<input type="checkbox"/> Readily available	<input type="checkbox"/> Up to date	<input checked="" type="checkbox"/> N/A
	□ Waste disposal, POTW	<input type="checkbox"/> Readily available	<input type="checkbox"/> Up to date	<input checked="" type="checkbox"/> N/A
	□ Other permits _____	<input type="checkbox"/> Readily available	<input type="checkbox"/> Up to date	<input checked="" type="checkbox"/> N/A
	Remarks _____			
5.	Groundwater Monitoring Records	<input checked="" type="checkbox"/> Readily available	<input checked="" type="checkbox"/> Up to date	<input type="checkbox"/> N/A
	Remarks _____			
IV. O&M COSTS				
1.	O&M Organization			
	□ State in-house	<input type="checkbox"/> Contractor for State		
	□ PRP in-house	<input checked="" type="checkbox"/> Contractor for PRP		
	□ Federal Facility in-house	<input type="checkbox"/> Contractor for Federal Facility		
	□ Other <u>MidAmerican contracts with MWH for O&M work. Building owner contracts with Stanley Consultants for O&M work.</u>			
2.	O&M Cost Records	<input checked="" type="checkbox"/> Readily available	<input checked="" type="checkbox"/> Up to date	
3.	Unanticipated or Unusually High O&M Costs During Review Period			
	Describe costs and reasons: <u>See description in FYR Report.</u>			
V. ACCESS AND INSTITUTIONAL CONTROLS <input checked="" type="checkbox"/> Applicable <input type="checkbox"/> N/A				
A. Fencing				
1.	Fencing damaged	<input type="checkbox"/> Location shown on site map	<input type="checkbox"/> Gates secured	<input checked="" type="checkbox"/> N/A
	Remarks _____			
B. Other Access Restrictions				
1.	Signs and other security measures	<input type="checkbox"/> Location shown on site map	<input checked="" type="checkbox"/> N/A	
	Remarks _____			

C. Institutional Controls (ICs)**1. Implementation and Enforcement**

Site conditions imply ICs not properly implemented Yes No N/A
Site conditions imply ICs not being fully enforced Yes No N/A

Type of monitoring (e.g., self-reporting, drive by) self-reported

Frequency annually

Responsible party/agency City and owner of Iowa-Illinois Square

Reporting is up-to-date Yes No N/A

Reports are verified by the lead agency Yes No N/A

Specific requirements in deed or decision documents have been met Yes No N/A

Violations have been reported Yes No N/A

2. Adequacy

ICs are adequate

ICs are inadequate

N/A

Remarks _____

D. General**1. Vandalism/trespassing** Location shown on site map No vandalism evident

Remarks _____

2. Land use changes on site N/A

Remarks _____

3. Land use changes off site N/A

Remarks One adjacent property and one near-by property have changed from commercial uses to multi-family dwellings.

VI. GENERAL SITE CONDITIONS**A. Roads** Applicable N/A**B. Other Site Conditions**

Remarks Apartment building and surroundings in good condition. Creek liner exhibiting some missing tiles and creek banks have significant woody growth that the city has agreed to remove.

VII. LANDFILL COVERS Applicable N/A**VIII. VERTICAL BARRIER WALLS** Applicable N/A**IX. GROUNDWATER/SURFACE WATER REMEDIES** Applicable N/A**A. Groundwater Extraction Wells, Pumps, and Pipelines** Applicable N/A**B. Surface Water Collection Structures, Pumps, and Pipelines** Applicable N/A**C. Treatment System** Applicable N/A**D. Monitored Natural Attenuation****1. Monitoring Wells (natural attenuation remedy)**

Properly secured/locked Functioning Routinely sampled Good condition

All required wells located Needs Maintenance

N/A

Remarks _____

X. OTHER REMEDIES

- A. LNAPL Recovery**-Recovery occurs in designated monitoring wells and removal and replacement of absorbent socks has been observed in the past but was not observed during this inspection. Monitoring wells were observed to be in good condition.
- B. Air Monitoring and Crawlspace Barrier and Passive Vent Inspection**-Air monitoring occurs in the apartment crawlspace. Crawlspace liner and gravel cover were observed to be in good condition. Vents were not obstructed.
- C. Creek Liner Inspection**-Creek liner condition was reviewed with City Engineering staff and MidAmerican Energy manager and consultant. City was requested to remove woody growth from eastern bank of creek adjacent to site and consider more aggressive maintenance of the tile liner. Liner is missing in some areas, most notably along freeze-thaw line.

XI. OVERALL OBSERVATIONS

A. Implementation of the Remedy

Describe issues and observations relating to whether the remedy is effective and functioning as designed. Begin with a brief statement of what the remedy is to accomplish (i.e., to contain contaminant plume, minimize infiltration and gas emission, etc.).

All aspects of the remedy appear to be functioning as intended and designed.

B. Adequacy of O&M

Describe issues and observations related to the implementation and scope of O&M procedures. In particular, discuss their relationship to the current and long-term protectiveness of the remedy.

O&M appears to be effective except for maintenance of vegetation removal on the banks of Ralston Creek. The city engineering office has committed to improving control of vegetation on the creek bank near the site. They committed to investigating improved maintenance of the tile liner in the creek near the site.

C. Early Indicators of Potential Remedy Problems

Describe issues and observations such as unexpected changes in the cost or scope of O&M or a high frequency of unscheduled repairs that suggest that the protectiveness of the remedy may be compromised in the future.

None