

# FEDERAL OPERATING PERMIT

A FEDERAL OPERATING PERMIT IS HEREBY ISSUED TO

Shell Chemical LP

AUTHORIZING THE OPERATION OF

Chemical Plant  
Petroleum Refining

LOCATED AT

Harris County, Texas

Latitude 29° 43' 18" Longitude 95° 7' 21"

Regulated Entity Number: RN100211879

This permit is issued in accordance with and subject to the Texas Clean Air Act (TCAA), Chapter 382 of the Texas Health and Safety Code and Title 30 Texas Administrative Code Chapter 122 (30 TAC Chapter 122), Federal Operating Permits. Under 30 TAC Chapter 122, this permit constitutes the permit holder's authority to operate the site and emission units listed in this permit. Operations of the site and emission units listed in this permit are subject to all additional rules or amended rules and orders of the Commission pursuant to the TCAA.

This permit does not relieve the permit holder from the responsibility of obtaining New Source Review authorization for new, modified, or existing facilities in accordance with 30 TAC Chapter 116, Control of Air Pollution by Permits for New Construction or Modification.

The site and emission units authorized by this permit shall be operated in accordance with 30 TAC Chapter 122, the general terms and conditions, special terms and conditions, and attachments contained herein.

This permit shall expire five years from the date of issuance. The renewal requirements specified in 30 TAC § 122.241 must be satisfied in order to renew the authorization to operate the site and emission units.

Permit No:     O1668     Issuance Date: April 1, 2014

---

For the Commission

## Table of Contents

<b>Section</b>	<b>Page</b>
General Terms and Conditions .....	1
Special Terms and Conditions .....	1
Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting .....	1
Additional Monitoring Requirements .....	19
New Source Review Authorization Requirements .....	20
Compliance Requirements .....	22
Risk Management Plan .....	24
Protection of Stratospheric Ozone .....	24
Permit Location .....	25
Permit Shield (30 TAC § 122.148) .....	25
Attachments .....	26
Applicable Requirements Summary .....	27
Additional Monitoring Requirements .....	452
Permit Shield .....	514
New Source Review Authorization References .....	554
Appendix A .....	588
Acronym List .....	589
Appendix B .....	590

## **General Terms and Conditions**

The permit holder shall comply with all terms and conditions contained in 30 TAC § 122.143 (General Terms and Conditions), 30 TAC § 122.144 (Recordkeeping Terms and Conditions), 30 TAC § 122.145 (Reporting Terms and Conditions), and 30 TAC § 122.146 (Compliance Certification Terms and Conditions).

In accordance with 30 TAC § 122.144(1), records of required monitoring data and support information required by this permit, or any applicable requirement codified in this permit, are required to be maintained for a period of five years from the date of the monitoring report, sample, or application unless a longer data retention period is specified in an applicable requirement. The five year record retention period supersedes any less stringent retention requirement that may be specified in a condition of a permit identified in the New Source Review Authorization attachment.

If the permit holder chooses to demonstrate that this permit is no longer required, a written request to void this permit shall be submitted to the Texas Commission on Environmental Quality (TCEQ) by the Responsible Official in accordance with 30 TAC § 122.161(e). The permit holder shall comply with the permit's requirements, including compliance certification and deviation reporting, until notified by the TCEQ that this permit is voided.

The permit holder shall comply with 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit.

All reports required by this permit must include in the submittal a cover letter which identifies the following information: company name, TCEQ regulated entity number, air account number (if assigned), site name, area name (if applicable), and Air Permits Division permit number(s).

## **Special Terms and Conditions: Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting**

1. Permit holder shall comply with the following requirements:
  - A. Emission units (including groups and processes) in the Applicable Requirements Summary attachment shall meet the limitations, standards, equipment specifications, monitoring, recordkeeping, reporting, testing, and other requirements listed in the Applicable Requirements Summary attachment to assure compliance with the permit.
  - B. The textual description in the column titled "Textual Description" in the Applicable Requirements Summary attachment is not enforceable and is not deemed as a substitute for the actual regulatory language. The Textual Description is provided for information purposes only.

- C. A citation listed on the Applicable Requirements Summary attachment, which has a notation [G] listed before it, shall include the referenced section and subsection for all commission rules, or paragraphs for all federal and state regulations and all subordinate paragraphs, subparagraphs and clauses, subclauses, and items contained within the referenced citation as applicable requirements.
- D. When a grouped citation, notated with a [G] in the Applicable Requirements Summary, contains multiple compliance options, the permit holder must keep records of when each compliance option was used.
- E. Emission units subject to 40 CFR Part 63, Subpart FFFF as identified in the attached Applicable Requirements Summary table are subject to 30 TAC Chapter 113, Subchapter C, § 113.890 which incorporates the 40 CFR Part 63 Subpart by reference.
- F. Emission units subject to 40 CFR Part 63, Subpart A as identified in the attached Applicable Requirements Summary table are subject to 30 TAC Chapter 113, Subchapter C, § 113.100 which incorporates the 40 CFR Part 63 Subpart by reference.
- G. Emission units subject to 40 CFR Part 63, Subpart F as identified in the attached Applicable Requirements Summary table are subject to 30 TAC Chapter 113, Subchapter C, § 113.110 which incorporates the 40 CFR Part 63 Subpart by reference.
- H. Emission units subject to 40 CFR Part 63, Subpart YY as identified in the attached Applicable Requirements Summary table are subject to 30 TAC Chapter 113, Subchapter C, § 113.560 which incorporates the 40 CFR Part 63 Subpart by reference.
- I. Emission units subject to 40 CFR Part 63, Subpart G as identified in the attached Applicable Requirements Summary table are subject to 30 TAC Chapter 113, Subchapter C, § 113.120 which incorporates the 40 CFR Part 63 Subpart by reference.
- J. Emission units subject to 40 CFR Part 63, Subpart H as identified in the attached Applicable Requirements Summary table are subject to 30 TAC Chapter 113, Subchapter C, § 113.130 which incorporates the 40 CFR Part 63 Subpart by reference.
- K. Emission units subject to 40 CFR Part 63, Subpart DDDDD as identified in the attached Applicable Requirements Summary table are subject to 30 TAC Chapter 113, Subchapter C, § 113.1130 which incorporates the 40 CFR Part 63 Subpart by reference.

- L. For the purpose of generating emission reduction credits through 30 TAC Chapter 101, Subchapter H, Division 1 (Emission Credit Banking and Trading), the permit holder shall comply with the following requirements:
- (i) Title 30 TAC § 101.302 (relating to General Provisions)
  - (ii) Title 30 TAC § 101.303 (relating to Emission Reduction Credit Generation Certification)
  - (iii) Title 30 TAC § 101.304 (relating to Mobile Emission Reduction Credit Generation and Certification)
  - (iv) Title 30 TAC § 101.305 (relating to Emission Reductions Achieved Outside the United States)
  - (v) Title 30 TAC § 101.309 (relating to Emission Credit Banking and Trading)
  - (vi) The terms and conditions by which the emission limits are established to generate the reduction credit are applicable requirements of this permit
- M. The permit holder shall comply with the following 30 TAC Chapter 101, Subchapter H, Division 3 (Mass Emission Cap and Trade Program) Requirements:
- (i) Title 30 TAC § 101.352 (relating to General Provisions)
  - (ii) Title 30 TAC § 101.353 (relating to Allocation of Allowances)
  - (iii) Title 30 TAC § 101.354 (relating to Allowance Deductions)
  - (iv) Title 30 TAC § 101.356 (relating to Allowance Banking and Trading)
  - (v) Title 30 TAC § 101.358 (relating to Emission Monitoring and Compliance Demonstration)
  - (vi) Title 30 TAC § 101.359 (relating to Reporting)
  - (vii) Title 30 TAC § 101.360 (relating to Level of Activity Certification)
  - (viii) The terms and conditions by which the emission limits are established to meet or exceed the cap are applicable requirements of this permit
- N. For the purpose of generating discrete emission reduction credits through 30 TAC Chapter 101, Subchapter H, Division 4 (Discrete Emission Credit

Banking and Trading), the permit holder shall comply with the following requirements:

- (i) Title 30 TAC § 101.372 (relating to General Provisions)
  - (ii) Title 30 TAC § 101.373 (relating to Discrete Emission Reduction Credit Generation and Certification)
  - (iii) Title 30 TAC § 101.374 (relating to Mobile Discrete Emission Reduction Credit Generation and Certification)
  - (iv) Title 30 TAC § 101.375 (relating to Emission Reductions Achieved Outside the United States)
  - (v) Title 30 TAC § 101.378 (relating to Discrete Emission Credit Banking and Trading)
  - (vi) The terms and conditions by which the emission limits are established to generate the discrete reduction credit are applicable requirements of this permit
- O. The permit holder shall comply with the following 30 TAC Chapter 101, Subchapter H, Division 6 (Highly Reactive Volatile Organic Compound Emissions Cap and Trade Program) requirements:
- (i) Title 30 TAC § 101.393 (relating to General Provisions)
  - (ii) Title 30 TAC § 101.394 (relating to Allocation of Allowances)
  - (iii) Title 30 TAC § 101.396 (relating to Allowance Deductions)
  - (iv) Title 30 TAC § 101.399 (relating to Allowance Banking and Trading)
  - (v) Title 30 TAC § 101.400 (relating to Reporting)
  - (vi) The terms and conditions by which the emission limits are established to meet or exceed the cap are applicable requirements of this permit
2. The permit holder shall comply with the following sections of 30 TAC Chapter 101 (General Air Quality Rules):
- A. Title 30 TAC § 101.1 (relating to Definitions), insofar as the terms defined in this section are used to define the terms used in other applicable requirements
  - B. Title 30 TAC § 101.3 (relating to Circumvention)

- C. Title 30 TAC § 101.8 (relating to Sampling), if such action has been requested by the TCEQ
  - D. Title 30 TAC § 101.9 (relating to Sampling Ports), if such action has been requested by the TCEQ
  - E. Title 30 TAC § 101.10 (relating to Emissions Inventory Requirements)
  - F. Title 30 TAC § 101.201 (relating to Emission Event Reporting and Recordkeeping Requirements)
  - G. Title 30 TAC § 101.211 (relating to Scheduled Maintenance, Start-up, and Shutdown Reporting and Recordkeeping Requirements)
  - H. Title 30 TAC § 101.221 (relating to Operational Requirements)
  - I. Title 30 TAC § 101.222 (relating to Demonstrations)
  - J. Title 30 TAC § 101.223 (relating to Actions to Reduce Excessive Emissions)
3. Permit holder shall comply with the following requirements of 30 TAC Chapter 111:
- A. Visible emissions from stationary vents with a flow rate of less than 100,000 actual cubic feet per minute and constructed after January 31, 1972 that are not listed in the Applicable Requirements Summary attachment for 30 TAC Chapter 111, Subchapter A, Division 1, shall not exceed 20% opacity averaged over a six-minute period. The permit holder shall comply with the following requirements for stationary vents at the site subject to this standard:
    - (i) Title 30 TAC § 111.111(a)(1)(B) (relating to Requirements for Specified Sources)
    - (ii) Title 30 TAC § 111.111(a)(1)(E)
    - (iii) Title 30 TAC § 111.111(a)(1)(F)(i), (ii), (iii), or (iv)
    - (iv) For emission units with vent emissions subject to 30 TAC § 111.111(a)(1)(B), complying with 30 TAC § 111.111(a)(1)(F)(ii), (iii), or (iv), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO<sub>x</sub>, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146. These periodic monitoring requirements do not apply to vents that are not capable of producing visible emissions such as vents that emit only colorless VOCs; vents from non-fuming liquids; vents that provide passive ventilation, such as

plumbing vents; or vent emissions from any other source that does not obstruct the transmission of light. Vents, as specified in the “Applicable Requirements Summary” attachment, that are subject to the emission limitation of 30 TAC § 111.111(a)(1)(B) and Compliance Assurance Monitoring (CAM), are not subject to the following periodic monitoring requirements and shall comply with the CAM requirements in the “Additional Monitoring Requirements” attachment:

- (1) An observation of stationary vents from emission units in operation shall be conducted at least once during each calendar quarter unless the emission unit is not operating for the entire quarter.
- (2) For stationary vents from a combustion source, if an alternative to the normally fired fuel is fired for a period greater than or equal to 24 consecutive hours, the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are present. If such period is greater than 3 months, observations shall be conducted once during each quarter. Supplementing the normally fired fuel with natural gas or fuel gas to increase the net heating value to the minimum required value does not constitute creation of an alternative fuel.
- (3) Records of all observations shall be maintained.
- (4) Visible emissions observations of emission units operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of emission units operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions observations shall be made during times when the activities described in 30 TAC § 111.111(a)(1)(E) are not taking place. Visible emissions shall be determined with each stationary vent in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each stationary vent during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer’s eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at



the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

(5) Compliance Certification:

(a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(1) and (a)(1)(B).

(b) However, if visible emissions are present during the observation, the permit holder shall either assume the visible emissions exceed the opacity limitations for the period observed and list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

(c) Some vents may be subject to multiple visible emission or monitoring requirements. All credible data must be considered when certifying compliance with this requirement even if the observation or monitoring was performed to demonstrate compliance with a different requirement.

B. For visible emissions from a building, enclosed facility, or other structure; the permit holder shall comply with the following requirements:

(i) Title 30 TAC § 111.111(a)(7)(A) (relating to Requirements for Specified Sources)

(ii) Title 30 TAC § 111.111(a)(7)(B)(i) or (ii)

(iii) For a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source subject to 30 TAC § 111.111(a)(7)(A), complying with

30 TAC § 111.111(a)(7)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO<sub>x</sub>, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:

- (1) An observation of visible emissions from a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source which is required to comply with 30 TAC § 111.111(a)(7)(A) shall be conducted at least once during each calendar quarter unless the air emission source or enclosed facility is not operating for the entire quarter.
- (2) Records of all observations shall be maintained.
- (3) Visible emissions observations of air emission sources or enclosed facilities operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of air emission sources or enclosed facilities operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each emissions outlet in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each emissions outlet during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.
- (4) Compliance Certification:
  - (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(7) and (a)(7)(A)
  - (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report

as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(7)(B) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

- C. For visible emissions from all other sources not specified in 30 TAC § 111.111(a)(1), (4), or (7); the permit holder shall comply with the following requirements:
- (i) Title 30 TAC § 111.111(a)(8)(A) (relating to Requirements for Specified Sources)
  - (ii) Title 30 TAC § 111.111(a)(8)(B)(i) or (ii)
  - (iii) For a source subject to 30 TAC § 111.111(a)(8)(A), complying with 30 TAC § 111.111(a)(8)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO<sub>x</sub>, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:
    - (1) An observation of visible emissions from a source which is required to comply with 30 TAC § 111.111(a)(8)(A) shall be conducted at least once during each calendar quarter unless the source is not operating for the entire quarter.
    - (2) Records of all observations shall be maintained.
    - (3) Visible emissions observations of sources operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of sources operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each source in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each source during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes.

When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

(4) Compliance Certification:

(a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(8) and (a)(8)(A)

(b) However, if visible emissions are present during the observation, the permit holder shall either assume the visible emissions exceed the opacity limitations for the period observed and list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(8)(B) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader

D. Certification of opacity readers determining opacities under Method 9 (as outlined in 40 CFR Part 60, Appendix A) to comply with opacity monitoring requirements shall be accomplished by completing the Visible Emissions Evaluators Course, or approved agency equivalent, no more than 180 days before the opacity reading.

E. Emission limits on nonagricultural processes, except for the steam generators specified in 30 TAC § 111.153, shall comply with the following requirements:

- (i) Emissions of PM from any source may not exceed the allowable rates as required in 30 TAC § 111.151(a) (relating to Allowable Emissions Limits)
  - (ii) Sources with an effective stack height ( $h_e$ ) less than the standard effective stack height ( $H_e$ ), must reduce the allowable emission level by multiplying it by  $[h_e/H_e]^2$  as required in 30 TAC § 111.151(b)
  - (iii) Effective stack height shall be calculated by the equation specified in 30 TAC § 111.151(c)
- F. Outdoor burning, as stated in 30 TAC § 111.201, shall not be authorized unless the following requirements are satisfied:
- (i) Title 30 TAC § 111.207 (relating to Exception for Recreation, Ceremony, Cooking, and Warmth)
  - (ii) Title 30 TAC § 111.219 (relating to General Requirements for Allowable Outdoor Burning)
  - (iii) Title 30 TAC § 111.221 (relating to Responsibility for Consequences of Outdoor Burning)
4. For storage vessels maintaining working pressure as specified in 30 TAC Chapter 115, Subchapter B, Division 1: “Storage of Volatile Organic Compounds,” the permit holder shall comply with the requirements of 30 TAC § 115.112(d)(1).
5. For industrial wastewater specified in 30 TAC Chapter 115, Subchapter B, the permit holder shall comply with the following requirements for wastewater drains, junction boxes, lift stations and weirs:
- A. Title 30 TAC § 115.142 (relating to Control Requirements)
  - B. Title 30 TAC § 115.142(1)(A) - (D) (relating to Control Requirements)
  - C. Title 30 TAC § 115.142(1)(E) and (F) (relating to Control Requirements)
  - D. Title 30 TAC § 115.145 (relating to Approved Test Methods)
  - E. Title 30 TAC § 115.146 (relating to Recordkeeping Requirements)
  - F. Title 30 TAC § 115.147(2) (relating to Exemptions), for streams with an annual VOC loading of 10 megagrams (11.03 tons) or less
  - G. Title 30 TAC § 115.148 (relating to Determination of Wastewater Characteristics)

6. Permit holder shall comply with the following 30 TAC Chapter 115, Subchapter C requirements:
  - A. The permit holder shall comply with the annual reporting requirements under 30 TAC § 115.247(2) for motor vehicle fuel dispensing facilities exempt from Stage II.
7. The permit holder shall comply with the following requirements of 30 TAC Chapter 115, Subchapter F, Division 3, Degassing of Storage Tanks, Transport Vessels and Marine Vessels:
  - A. For degassing of stationary VOC storage tanks, the permit holder shall comply with the following requirements:
    - (i) Title 30 TAC § 115.541(a) - (c) (relating to Emission Specifications)
    - (ii) Title 30 TAC § 115.541(f) (relating to Emission Specifications), for floating roof storage tanks
    - (iii) Title 30 TAC § 115.542(a) and (a)(1), (a)(2), (a)(3) or (a)(4) (relating to Control Requirements). Where the requirements of 30 TAC Chapter 115, Subchapter F contain multiple compliance options, the permit holder shall keep records of when each compliance option was used.
    - (iv) Title 30 TAC § 115.542(b) - (d), (relating to Control Requirements)
    - (v) Title 30 TAC § 115.543 (relating to Alternate Control Requirements)
    - (vi) Title 30 TAC § 115.544(a)(1) and (a)(2) (relating to Inspection, Monitoring, and Testing Requirements), for inspections
    - (vii) Title 30 TAC § 115.544(b) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring
    - (viii) Title 30 TAC § 115.544(b)(1) and (b)(2) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring of control devices
    - (ix) Title 30 TAC § 115.544(b)(2)(A) - (J) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring (as appropriate to the control device)
    - (x) Title 30 TAC § 115.544(b)(3), (b)(4) and (b)(6) (relating to Inspection, Monitoring, and Testing Requirements), for VOC concentration or lower explosive limit threshold monitoring

- (xi) Title 30 TAC § 115.544(c), and (c)(1) - (c)(3) (relating to Inspection, Monitoring, and Testing Requirements), for testing of control devices used to comply with 30 TAC § 115.542(a)(1)
  - (xii) Title 30 TAC § 115.545(1) - (7), (9) - (11) and (13) (relating to Approved Test Methods)
  - (xiii) Title 30 TAC § 115.546(a), (a)(1) and (a)(3) (relating to Recordkeeping and Notification Requirements), for recordkeeping
  - (xiv) Title 30 TAC § 115.546(a)(2) and (a)(2)(A) - (J) (relating to Recordkeeping and Notification Requirements), for recordkeeping (as appropriate to the control device)
  - (xv) Title 30 TAC § 115.546(a)(4) (relating to Recordkeeping and Notification Requirements), for recordkeeping of testing of control devices used to comply with 30 TAC § 115.542(a)(1)
  - (xvi) Title 30 TAC § 115.546(b) (relating to Recordkeeping and Notification Requirements), for notification
  - (xvii) Title 30 TAC § 115.547(4) (relating to Exemptions)
- B. For the degassing of all transport vessels with a nominal capacity of 8,000 gallons or more, the permit holder shall comply with the following requirements:
- (i) Title 30 TAC § 115.541(a) - (c) and (d) (relating to Emission Specifications)
  - (ii) Title 30 TAC § 115.542(a) and (a)(1), (a)(2), (a)(3) or (a)(4) (relating to Control Requirements). Where the requirements of 30 TAC Chapter 115, Subchapter F contain multiple compliance options, the permit holder shall keep records of when each compliance option was used.
  - (iii) Title 30 TAC § 115.542(b), (c) and (e) (relating to Control Requirements)
  - (iv) Title 30 TAC § 115.543 (relating to Alternate Control Requirements)
  - (v) Title 30 TAC § 115.544(a)(1) and (a)(2) (relating to Inspection, Monitoring, and Testing Requirements), for inspections
  - (vi) Title 30 TAC § 115.544(b) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring

- (vii) Title 30 TAC § 115.544(b)(1) and (b)(2) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring of control devices
- (viii) Title 30 TAC § 115.544(b)(2)(A) - (J) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring (as appropriate to the control device)
- (ix) Title 30 TAC § 115.544(b)(3), (b)(4) and (b)(6) (relating to Inspection, Monitoring, and Testing Requirements), for VOC concentration or lower explosive limit threshold monitoring
- (x) Title 30 TAC § 115.544(c), and (c)(1) - (c)(3) (relating to Inspection, Monitoring, and Testing Requirements), for testing of control devices used to comply with 30 TAC § 115.542(a)(1)
- (xi) Title 30 TAC § 115.545(1) - (11) and (13) (relating to Approved Test Methods)
- (xii) Title 30 TAC § 115.546(a), (a)(1) and (a)(3) (relating to Recordkeeping and Notification Requirements), for recordkeeping
- (xiii) Title 30 TAC § 115.546(a)(2) and (a)(2)(A) - (J) (relating to Recordkeeping and Notification Requirements), for recordkeeping (as appropriate to the control device)
- (xiv) Title 30 TAC § 115.546(a)(4) (relating to Recordkeeping and Notification Requirements), for recordkeeping of testing of control devices used to comply with 30 TAC § 115.542(a)(1)
- (xv) Title 30 TAC § 115.546(b) (relating to Recordkeeping and Notification Requirements), for notification

8. The permit holder shall comply with the following requirements of 30 TAC Chapter 117:

- A. For the manufacturing, distribution, sales, and installation of natural gas-fired water heaters, boilers, and process heaters subject to Subchapter E, Division 3 (30 TAC § 117.3200):
  - (i) Title 30 TAC § 117.3205 (relating to Emission Specifications)
  - (ii) Title 30 TAC § 117.3210 (relating to Certification Requirements)
  - (iii) Title 30 TAC § 117.3215 (relating to Notification and Labeling Requirements)



9. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 60, unless otherwise stated in the applicable subpart:
  - A. Title 40 CFR § 60.7 (relating to Notification and Recordkeeping)
  - B. Title 40 CFR § 60.8 (relating to Performance Tests)
  - C. Title 40 CFR § 60.11 (relating to Compliance with Standards and Maintenance Requirements)
  - D. Title 40 CFR § 60.12 (relating to Circumvention)
  - E. Title 40 CFR § 60.13 (relating to Monitoring Requirements)
  - F. Title 40 CFR § 60.14 (relating to Modification)
  - G. Title 40 CFR § 60.15 (relating to Reconstruction)
  - H. Title 40 CFR § 60.19 (relating to General Notification and Reporting Requirements)
10. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 61, unless otherwise stated in the applicable subpart:
  - A. Title 40 CFR § 61.05 (relating to Prohibited Activities)
  - B. Title 40 CFR § 61.07 (relating to Application for Approval of Construction or Modification)
  - C. Title 40 CFR § 61.09 (relating to Notification of Start-up)
  - D. Title 40 CFR § 61.10 (relating to Source Reporting and Request Waiver)
  - E. Title 40 CFR § 61.12 (relating to Compliance with Standards and Maintenance Requirements)
  - F. Title 40 CFR § 61.13 (relating to Emissions Tests and Waiver of Emission Tests)
  - G. Title 40 CFR § 61.14 (relating to Monitoring Requirements)
  - H. Title 40 CFR § 61.15 (relating to Modification)
  - I. Title 40 CFR § 61.19 (relating to Circumvention)
11. For facilities where total annual benzene quantity from waste is greater than or equal to 10 megagrams per year and subject to emission standards in

40 CFR Part 61, Subpart FF, the permit holder shall comply with the following requirements:

- A. Title 40 CFR § 61.342(c)(1)(i) - (iii) (relating to Standards: General)
  - B. Title 40 CFR § 61.342(e)(1) (relating to Standards: General)
  - C. Title 40 CFR § 61.342(e)(2)(i) - (ii) (relating to Standards: General)
  - D. Title 40 CFR § 61.342(f)(1), and (2) (relating to Standards: General)
  - E. Title 40 CFR § 61.342(g) (relating to Standards: General)
  - F. Title 40 CFR § 61.350(a) and (b) (relating to Standards: Delay of Repair)
  - G. Title 40 CFR § 61.355(a)(1)(iii), (a)(2), (a)(6), (b), and (c)(1) - (3) (relating to Test Methods, Procedures, and Compliance Provisions)
  - H. Title 40 CFR § 61.355(k)(1) - (6), and (7)(i) - (iv) (relating to Test Methods, Procedures, and Compliance Provisions), for calculation procedures
  - I. Title 40 CFR § 61.356(a) (relating to Recordkeeping Requirements)
  - J. Title 40 CFR § 61.356(b), and (b)(1) (relating to Recordkeeping Requirements)
  - K. Title 40 CFR § 61.356(b)(4) (relating to Recordkeeping Requirements)
  - L. Title 40 CFR § 61.356(b)(5) (relating to Recordkeeping Requirements)
  - M. Title 40 CFR § 61.356(c) (relating to Recordkeeping Requirements)
  - N. Title 40 CFR § 61.357(a), (d)(1), (d)(2) (d)(6) and (d)(8) (relating to Reporting Requirements)
  - O. Title 40 CFR § 61.357(d)(5) (relating to Reporting Requirements)
  - P. Waste generated by remediation activities at these facilities are subject to the requirements identified under 40 CFR § 61.342 for treatment and management of waste
12. For facilities with containers subject to emission standards in 40 CFR Part 61, Subpart FF, the permit holder shall comply with the following requirements:
- A. Title 40 CFR § 61.345(a)(1) - (3), (b), and (c) (relating to Standards: Containers)
  - B. Title 40 CFR § 61.355(h) (relating to Test Methods, Procedures and Compliance Provisions)

- C. Title 40 CFR § 61.356(g) (relating to Recordkeeping Requirements)
  - D. Title 40 CFR § 61.356(h) (relating to Recordkeeping Requirements)
13. The permit holder shall comply with the requirements of 30 TAC Chapter 113, Subchapter C, § 113.100 for units subject to any subpart of 40 CFR Part 63, unless otherwise stated in the applicable subpart.
  14. For the chemical manufacturing process specified in 40 CFR Part 63, Subpart F, the permit holder shall comply with 40 CFR § 63.103(a) (relating to General Compliance, Reporting, and Recordkeeping Provisions) (Title 30 TAC Chapter 113, Subchapter C, § 113.110 incorporated by reference).
  15. For the chemical manufacturing facilities with a 40 CFR Part 63, Subpart G Group 1 or Group 2 wastewater streams that are also subject to 40 CFR Part 61, Subpart FF, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.120 incorporated by reference):
    - A. Title 40 CFR § 63.110(e)(1)(i) and (e)(1)(ii) (relating to Applicability), for 40 CFR Part 63, Subpart G applicability to Group 1 or 2 Wastewater Streams
  16. For the chemical manufacturing facilities with a 40 CFR Part 63, Subpart G Group 2 wastewater stream, the permit holder shall comply with (Title 30 TAC Chapter 113, Subchapter C, § 113.120 incorporated by reference):
    - A. Title 40 CFR § 63.132(a), (a)(1), (a)(1)(i), and (a)(3) (relating to Process Wastewater Provisions - General)
    - B. Title 40 CFR § 63.132(b), (b)(1), (b)(1)(i), (b)(2), (b)(2)(i), and (b)(4) (relating to Process Wastewater Provisions - General)
  17. For the chemical manufacturing facilities subject to leak detection requirements in 40 CFR Part 63, Subpart G, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.120 incorporated by reference):
    - A. General Leak Detection Requirements:
      - (i) Title 40 CFR § 63.148(d)(1) - (3), and (e) (relating to Leak Inspection Provisions)
      - (ii) Title 40 CFR § 63.148(c), (g), (g)(2), (h), and (h)(2) (relating to Leak Inspection Provisions), for monitoring and testing requirements
      - (iii) Title 40 CFR §§ 63.148(g)(2), (h)(2), (i)(1) - (2), (i)(4)(i) - (viii), (i)(5), and 63.152(a)(1) - (5), for recordkeeping requirements

- (iv) Title 40 CFR §§ 63.148(j), 63.151(a)(6)(i) - (iii), (b)(1) - (2), (j)(1) - (3), 63.152(a)(1) - (5), (b), (b)(1)(i) - (ii), and (b)(4), for reporting requirements
  - B. For closed vent system or vapor collection systems constructed of hard piping:
    - (i) Title 40 CFR § 63.148(b)(1)(ii) (relating to Leak Inspection Provisions), for monitoring and testing requirements
    - (ii) Title 40 CFR § 63.148(i)(6) (relating to Leak Inspection Provisions), for recordkeeping requirements
  - C. For facilities operating flow indicators:
    - (i) Title 40 CFR § 63.148(f)(1) (relating to Leak Inspection Provisions), for monitoring and testing requirements
    - (ii) Title 40 CFR § 63.148(f)(1), (i)(3)(i) (relating to Leak Inspection Provisions), for recordkeeping requirements
    - (iii) Title 40 CFR § 63.148(j)(2) (relating to Leak Inspection Provisions), for reporting requirements
- 18. For the chemical manufacturing facilities subject to wastewater operations requirements in 40 CFR Part 63, Subpart G, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.120 incorporated by reference):
  - A. Title 40 CFR § 63.136(a) (relating to Process Wastewater Provisions - Individual Drain Systems)
- 19. The permit holder shall comply with certified registrations submitted to the TCEQ for purposes of establishing federally enforceable emission limits. A copy of the certified registration shall be maintained with the permit. Records sufficient to demonstrate compliance with the established limits shall be maintained. The certified registration and records demonstrating compliance shall be provided, on request, to representatives of the appropriate TCEQ regional office and any local air pollution control agency having jurisdiction over the site. The permit holder shall submit updated certified registrations when changes at the site require establishment of new emission limits. If changes result in emissions that do not remain below major source thresholds, the permit holder shall submit a revision application to codify the appropriate requirements in the permit.

## **Additional Monitoring Requirements**

20. Unless otherwise specified, the permit holder shall comply with the compliance assurance monitoring requirements as specified in the attached “CAM Summary” upon issuance of the permit. In addition, the permit holder shall comply with the following:
  - A. The permit holder shall comply with the terms and conditions contained in 30 TAC § 122.147 (General Terms and Conditions for Compliance Assurance Monitoring).
  - B. The permit holder shall report, consistent with the averaging time identified in the “CAM Summary,” deviations as defined by the deviation limit in the “CAM Summary.” Any monitoring data below a minimum limit or above a maximum limit, that is collected in accordance with the requirements specified in 40 CFR § 64.7(c), shall be reported as a deviation. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).
  - C. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time specified in the “CAM Summary,” for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances in order to avoid reporting deviations. All monitoring data shall be collected in accordance with the requirements specified in 40 CFR § 64.7(c).
  - D. The permit holder shall operate the monitoring, identified in the attached “CAM Summary,” in accordance with the provisions of 40 CFR § 64.7.
  - E. The permit holder shall comply with either of the following requirements for any particulate matter capture system associated with the control device subject to CAM. If the results of the following inspections indicate that the capture system is not working properly, the permit holder shall promptly take necessary corrective action:
    - (i) Once per year the permit holder shall inspect any fan for proper operation and inspect the capture system used in compliance of CAM for cracks, holes, tears, and other defects; or
    - (ii) Once per year, the permit holder shall inspect for fugitive emissions escaping from the capture system in compliance of CAM by performing a visible emissions observation for a period of at least six minutes in accordance with 40 CFR Part 60, Appendix A, Test Method 22.

- F. The permit holder shall comply with either of the following requirements for any capture system associated with the VOC control device subject to CAM. If the results of the following inspections indicate that the capture system is not working properly, the permit holder shall promptly take necessary corrective actions:
- (i) Once a year the permit holder shall inspect the capture system in compliance of CAM for leaks in accordance with 40 CFR Part 60, Appendix A, Test Method 21. Leaks shall be indicated by an instrument reading greater than or equal to 500 ppm above background or as defined by the underlying applicable requirement; or
  - (ii) Once a month, the permit holder shall conduct a visual, audible, and/or olfactory inspection of the capture system in compliance of CAM to detect leaking components.
- G. The permit holder shall comply with the requirements of 40 CFR § 70.6(a)(3)(ii)(A) and 30 TAC § 122.144(1)(A)-(F) for documentation of all required inspections.
21. The permit holder shall comply with the periodic monitoring requirements as specified in the attached “Periodic Monitoring Summary” upon issuance of the permit. Except for, as applicable, monitoring malfunctions, associated repairs, and required quality assurance or control activities (including, as applicable, calibration checks and required zero and span adjustments), the permit holder shall conduct all monitoring in continuous operation (or shall collect data at all required intervals) at all times that the pollutant-specific emissions unit is operating. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time specified in the “Periodic Monitoring Summary,” for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances to avoid reporting deviations. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).

### **New Source Review Authorization Requirements**

22. Permit holder shall comply with the requirements of New Source Review authorizations issued or claimed by the permit holder for the permitted area, including permits, permits by rule, standard permits, flexible permits, special permits, permits for existing facilities including Voluntary Emissions Reduction Permits and Electric Generating Facility Permits issued under 30 TAC Chapter 116, Subchapter I, or special exemptions referenced in the New Source Review Authorization References attachment. These requirements:
- A. Are incorporated by reference into this permit as applicable requirements

- B. Shall be located with this operating permit
  - C. Are not eligible for a permit shield
23. The permit holder shall comply with the general requirements of 30 TAC Chapter 106, Subchapter A or the general requirements, if any, in effect at the time of the claim of any PBR.
24. The permit holder shall maintain records to demonstrate compliance with any emission limitation or standard that is specified in a permit by rule (PBR) or Standard Permit listed in the New Source Review Authorizations attachment. The records shall yield reliable data from the relevant time period that are representative of the emission unit's compliance with the PBR or Standard Permit. These records may include, but are not limited to, production capacity and throughput, hours of operation, material safety data sheets (MSDS), chemical composition of raw materials, speciation of air contaminant data, engineering calculations, maintenance records, fugitive data, performance tests, capture/control device efficiencies, direct pollutant monitoring (CEMS, COMS, or PEMS), or control device parametric monitoring. These records shall be made readily accessible and available as required by 30 TAC § 122.144.
- A. If applicable, monitoring of control device performance or general work practice standards shall be made in accordance with the TCEQ Periodic Monitoring Guidance document.
  - B. Any monitoring or recordkeeping data indicating noncompliance with the PBR or Standard Permit shall be considered and reported as a deviation according to 30 TAC § 122.145 (Reporting Terms and Conditions).
25. The permit holder shall comply with the terms and conditions of the air addendum of the Industrial Hazardous Waste permits listed in the New Source Review Authorization Reference Attachment. Requirements other than those of the air addendum are not applicable to this operating permit.
26. The permit holder shall comply with the following requirements for Air Quality Standard Permits:
- A. Registration requirements listed in 30 TAC § 116.611, unless otherwise provided for in an Air Quality Standard Permit
  - B. General Conditions listed in 30 TAC § 116.615, unless otherwise provided for in an Air Quality Standard Permit
  - C. Applicable requirements of 30 TAC § 116.617 for Pollution Control Projects based on the information contained in the registration application.
27. The permit holder shall comply with the following requirements for flexible permits of 30 TAC Chapter 116:

- A. Title 30 TAC § 116.715 (relating to General and Special Conditions)
  - B. Title 30 TAC § 116.716 (relating to Emission Caps and Individual Emission Limitations)
  - C. Title 30 TAC § 116.717 (relating to Implementation Schedule for Additional Controls)
  - D. Title 30 TAC § 116.718 (relating to Significant Emission Increase)
  - E. Title 30 TAC § 116.720 (relating to Limitation on Physical and Operational Changes)
  - F. Title 30 TAC § 116.721(a) (relating to requirements for Amendments and Alterations)
28. The permit holder shall use a SIP approved permit amendment process to convert the Shell Oil Company flexible permit No. 21262 and Shell Chemical LP flexible permit No. 56496 into permits issued under a SIP approved permit program under 30 Tex. Admin. Code Chapter 116. The permit holder shall submit to TCEQ NSR SIP permit amendment applications in accordance with 30 TAC Chapter 116 Subchapter B no later than January 20, 2012.
29. Within sixty (60) days of the effective date of each Subchapter B permit amendment, the permit holder shall submit an application to TCEQ (and a copy to EPA) for a revision to its Title V permit to incorporate the NSR permit requirements, consistent with procedures in 30 TAC Chapter 122 (for Significant Revisions or Minor Revisions, as applicable). The TCEQ Executive Director may grant an extension of time, not to exceed thirty (30) days, within which to submit the revision application.

### **Compliance Requirements**

30. The permit holder shall certify compliance in accordance with 30 TAC § 122.146. The permit holder shall comply with 30 TAC § 122.146 using at a minimum, but not limited to, the continuous or intermittent compliance method data from monitoring, recordkeeping, reporting, or testing required by the permit and any other credible evidence or information. The certification period may not exceed 12 months and the certification must be submitted within 30 days after the end of the period being certified.
31. Permit holder shall comply with the following 30 TAC Chapter 117 requirements:
- A. The permit holder shall comply with the compliance schedules and submit written notification to the TCEQ Executive Director as required in 30 TAC Chapter 117, Subchapter H, Division 1:



- (i) For sources in the Houston-Galveston-Brazoria Nonattainment area, 30 TAC § 117.9020:
      - (1) Title 30 TAC § 117.9020(2)(A), (C), and (D)
  - B. The permit holder shall comply with the Initial Control Plan unit listing requirement in 30 TAC § 117.350(c) and (c)(1).
  - C. The permit holder shall comply with the requirements of 30 TAC § 117.354 for Final Control Plan Procedures for Attainment Demonstration Emission Specifications and 30 TAC § 117.356 for Revision of Final Control Plan.
- 32. Use of Emission Credits to comply with applicable requirements:
  - A. Unless otherwise prohibited, the permit holder may use emission credits to comply with the following applicable requirements listed elsewhere in this permit:
    - (i) Title 30 TAC Chapter 115
    - (ii) Title 30 TAC Chapter 117
    - (iii) Offsets for Title 30 TAC Chapter 116
  - B. The permit holder shall comply with the following requirements in order to use the emission credits to comply with the applicable requirements:
    - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.306(c)(2)
    - (ii) The emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 1
    - (iii) The executive director has approved the use of the credit according to 30 TAC § 101.306(c)(2)
    - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.302(g) and 30 TAC Chapter 122
- 33. Use of Discrete Emission Credits to comply with the applicable requirements:
  - A. Unless otherwise prohibited, the permit holder may use discrete emission credits to comply with the following applicable requirements listed elsewhere in this permit:
    - (i) Title 30 TAC Chapter 115

- (ii) Title 30 TAC Chapter 117
  - (iii) If applicable, offsets for Title 30 TAC Chapter 116
  - (iv) Temporarily exceed state NSR permit allowables
- B. The permit holder shall comply with the following requirements in order to use the credit to comply with the applicable requirements:
- (i) The permit holder must notify the TCEQ according to 30 TAC § 101.376(d)
  - (ii) The discrete emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 4
  - (iii) The executive director has approved the use of the discrete emission credits according to 30 TAC § 101.376(d)(1)(A)
  - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.372(h) and 30 TAC Chapter 122

### **Risk Management Plan**

34. For processes subject to 40 CFR Part 68 and specified in 40 CFR § 68.10, the permit holder shall comply with the requirements of the Accidental Release Prevention Provisions in 40 CFR Part 68. The permit holder shall submit to the appropriate agency either a compliance schedule for meeting the requirements of 40 CFR Part 68 by the date provided in 40 CFR § 68.10(a), or as part of the compliance certification submitted under this permit, a certification statement that the source is in compliance with all requirements of 40 CFR Part 68, including the registration and submission of a risk management plan.

### **Protection of Stratospheric Ozone**

35. Permit holders at a site subject to Title VI of the FCAA Amendments shall meet the following requirements for protection of stratospheric ozone.
- A. Any on site servicing, maintenance, and repair on refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants or non-exempt substitutes shall be conducted in accordance with 40 CFR Part 82, Subpart F. Permit holders shall ensure that repairs on or refrigerant removal from refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants are performed only by properly certified technicians using certified

equipment. Records shall be maintained as required by 40 CFR Part 82, Subpart F.

### **Permit Location**

36. The permit holder shall maintain a copy of this permit and records related to requirements listed in this permit on site.

### **Permit Shield (30 TAC § 122.148)**

37. A permit shield is granted for the emission units, groups, or processes specified in the attached "Permit Shield." Compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements listed in the attachment "Permit Shield." Permit shield provisions shall not be modified by the executive director until notification is provided to the permit holder. No later than 90 days after notification of a change in a determination made by the executive director, the permit holder shall apply for the appropriate permit revision to reflect the new determination. Provisional terms are not eligible for this permit shield. Any term or condition, under a permit shield, shall not be protected by the permit shield if it is replaced by a provisional term or condition or the basis of the term and condition changes.

## **Attachments**

**Applicable Requirements Summary**

**Additional Monitoring Requirements**

**Permit Shield**

**New Source Review Authorization References**

## **Applicable Requirements Summary**

**Unit Summary ..... 28**

**Applicable Requirements Summary ..... 81**

Note: A “none” entry may be noted for some emission sources in this permit’s “Applicable Requirements Summary” under the heading of “Monitoring and Testing Requirements” and/or “Recordkeeping Requirements” and/or “Reporting Requirements.” Such a notation indicates that there are no requirements for the indicated emission source as identified under the respective column heading(s) for the stated portion of the regulation when the emission source is operating under the conditions of the specified SOP Index Number. However, other relevant requirements pursuant to 30 TAC Chapter 122 including Recordkeeping Terms and Conditions (30 TAC § 122.144), Reporting Terms and Conditions (30 TAC § 122.145), and Compliance Certification Terms and Conditions (30 TAC § 122.146) continue to apply.

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
H87920	Boilers/Steam Generators/Steam Generating Units	N/A	REG2-1	30 TAC Chapter 112, Sulfur Compounds	No changing attributes.
H87920	Boilers/Steam Generators/Steam Generating Units	N/A	R7201-1	30 TAC Chapter 117, Subchapter B	No changing attributes.
H87920	Boilers/Steam Generators/Steam Generating Units	N/A	60-Db-1	40 CFR Part 60, Subpart Db	No changing attributes.
PROAROM	Chemical Manufacturing Process	N/A	63F-1	40 CFR Part 63, Subpart F	No changing attributes.
PROBD3	Chemical Manufacturing Process	N/A	63F-1	40 CFR Part 63, Subpart F	No changing attributes.
PRODIST	Chemical Manufacturing Process	N/A	63F-1	40 CFR Part 63, Subpart F	No changing attributes.
PROOXY	Chemical Manufacturing Process	N/A	63F-1	40 CFR Part 63, Subpart F	No changing attributes.
PROPAU	Chemical Manufacturing Process	N/A	63F-1	40 CFR Part 63, Subpart F	No changing attributes.
OP2ELFLA	Closed Vent System And Control Device	N/A	61FF-1	40 CFR Part 61, Subpart FF	No changing attributes.
OP3ELFLA	Closed Vent System And Control Device	N/A	61FF-1	40 CFR Part 61, Subpart FF	No changing attributes.
OP3GRFLA	Closed Vent System And Control Device	N/A	61FF-1	40 CFR Part 61, Subpart FF	No changing attributes.

## Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
IRUFLR	Distillation Operations	N/A	60NNN-1	40 CFR Part 60, Subpart NNN	No changing attributes.
IRUFLR	Distillation Operations	N/A	60NNN-2	40 CFR Part 60, Subpart NNN	No changing attributes.
IRUFLR	Distillation Operations	N/A	60NNN-3	40 CFR Part 60, Subpart NNN	No changing attributes.
IRUFLRG	Distillation Operations	N/A	60NNN-1	40 CFR Part 60, Subpart NNN	No changing attributes.
IRUFLRG	Distillation Operations	N/A	60NNN-2	40 CFR Part 60, Subpart NNN	No changing attributes.
IRUFLRG	Distillation Operations	N/A	60NNN-3	40 CFR Part 60, Subpart NNN	No changing attributes.
OP2DIST	Distillation Operations	N/A	60NNN-1	40 CFR Part 60, Subpart NNN	No changing attributes.
BD3FLR	Emission Points/Stationary Vents/Process Vents	N/A	R5720-1	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
BD3FLR	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
BD3FLR	Emission Points/Stationary Vents/Process Vents	N/A	R5121-2	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
BD3FLR	Emission Points/Stationary	N/A	R5121-3	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.

## Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	Vents/Process Vents				
BD3FLR	Emission Points/Stationary Vents/Process Vents	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
BD3FLR	Emission Points/Stationary Vents/Process Vents	N/A	63G-2	40 CFR Part 63, Subpart G	No changing attributes.
BD3FLR	Emission Points/Stationary Vents/Process Vents	N/A	63G-3	40 CFR Part 63, Subpart G	No changing attributes.
BD3FLRG	Emission Points/Stationary Vents/Process Vents	N/A	R5720-1	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
BD3FLRG	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
BD3FLRG	Emission Points/Stationary Vents/Process Vents	N/A	R5121-2	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
BD3FLRG	Emission Points/Stationary Vents/Process Vents	N/A	R5121-3	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
BD3FLRG	Emission Points/Stationary Vents/Process Vents	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
BD3FLRG	Emission	N/A	63G-2	40 CFR Part 63, Subpart G	No changing attributes.



## Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	Points/Stationary Vents/Process Vents				
BD3FLRG	Emission Points/Stationary Vents/Process Vents	N/A	63G-3	40 CFR Part 63, Subpart G	No changing attributes.
CIPXFLR	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
CIPXFLR	Emission Points/Stationary Vents/Process Vents	N/A	R5121-2	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
CIPXFLR	Emission Points/Stationary Vents/Process Vents	N/A	R5121-3	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
CIPXFLR	Emission Points/Stationary Vents/Process Vents	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.
CIPXFLRG	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
CIPXFLRG	Emission Points/Stationary Vents/Process Vents	N/A	R5121-2	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
CIPXFLRG	Emission Points/Stationary Vents/Process Vents	N/A	R5121-3	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.

## Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
E-87100	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
E-87100	Emission Points/Stationary Vents/Process Vents	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
E-87109	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
E-87109	Emission Points/Stationary Vents/Process Vents	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
FLACU	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
FLACU	Emission Points/Stationary Vents/Process Vents	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
FLBEU	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
FLBEU	Emission Points/Stationary Vents/Process Vents	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
FLOXU	Emission Points/Stationary	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.

## Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	Vents/Process Vents				
FLOXU	Emission Points/Stationary Vents/Process Vents	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
FLPAP	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
FLPAP	Emission Points/Stationary Vents/Process Vents	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
FOL100	Emission Points/Stationary Vents/Process Vents	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FOL110	Emission Points/Stationary Vents/Process Vents	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FOL120	Emission Points/Stationary Vents/Process Vents	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FOL130	Emission Points/Stationary Vents/Process Vents	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FOL140	Emission Points/Stationary Vents/Process Vents	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FOL150	Emission	N/A	R1111-01	30 TAC Chapter 111, Visible	No changing attributes.

## Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	Points/Stationary Vents/Process Vents			Emissions	
FOL160	Emission Points/Stationary Vents/Process Vents	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FOL170	Emission Points/Stationary Vents/Process Vents	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FOL180	Emission Points/Stationary Vents/Process Vents	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FOL190	Emission Points/Stationary Vents/Process Vents	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FOL601	Emission Points/Stationary Vents/Process Vents	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FOL602	Emission Points/Stationary Vents/Process Vents	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FOL603	Emission Points/Stationary Vents/Process Vents	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FOL604	Emission Points/Stationary Vents/Process Vents	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.

## Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
FOL700	Emission Points/Stationary Vents/Process Vents	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FOL710	Emission Points/Stationary Vents/Process Vents	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
GRPACMAP2	Emission Points/Stationary Vents/Process Vents	VOL411, VOL412	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRPACMAP3	Emission Points/Stationary Vents/Process Vents	VF34003, VF34004, VF34005, VF34009, VF34010, VF34011	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRPACMAP3	Emission Points/Stationary Vents/Process Vents	VF34003, VF34004, VF34005, VF34009, VF34010, VF34011	R5121-2	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRPPAUPV2	Emission Points/Stationary Vents/Process Vents	V8231, V8305, V8306, V8307, V8309	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRPPAUPV2	Emission Points/Stationary Vents/Process Vents	V8231, V8305, V8306, V8307, V8309	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
GRPPAUPV3	Emission Points/Stationary	V8207, V8208, V8209, V8212,	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.

## Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	Vents/Process Vents	V8213, V8219, V8222, V8223, V8224, V8228, V8270, V8319, V8333, V8362			
GRPPAUPV3	Emission Points/Stationary Vents/Process Vents	V8207, V8208, V8209, V8212, V8213, V8219, V8222, V8223, V8224, V8228, V8270, V8319, V8333, V8362	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
GRPPAUPV4	Emission Points/Stationary Vents/Process Vents	V8200, V8201, V8202, V8203	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRPPAUPV4	Emission Points/Stationary Vents/Process Vents	V8200, V8201, V8202, V8203	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
GRPVNT	Emission Points/Stationary Vents/Process Vents	FLRPURGE, LO2FLR, OP2FLR, PY3FLR	R5720-1	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
GRPVNT	Emission Points/Stationary Vents/Process Vents	FLRPURGE, LO2FLR, OP2FLR, PY3FLR	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRPVNT	Emission Points/Stationary Vents/Process Vents	FLRPURGE, LO2FLR, OP2FLR, PY3FLR	R5121-2	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRPVNT	Emission Points/Stationary Vents/Process Vents	FLRPURGE, LO2FLR, OP2FLR, PY3FLR	R5121-3	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRPVNT2	Emission Points/Stationary Vents/Process Vents	FLRPURGG, LO2FLRG, OP2FLRG, PY3FLRG	R5720-1	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
GRPVNT2	Emission Points/Stationary Vents/Process Vents	FLRPURGG, LO2FLRG, OP2FLRG, PY3FLRG	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRPVNT2	Emission Points/Stationary Vents/Process Vents	FLRPURGG, LO2FLRG, OP2FLRG, PY3FLRG	R5121-2	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRPVNT2	Emission Points/Stationary Vents/Process Vents	FLRPURGG, LO2FLRG, OP2FLRG, PY3FLRG	R5121-3	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
H1300	Emission Points/Stationary Vents/Process Vents	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
HT2FLR	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
HT2FLR	Emission Points/Stationary	N/A	R5121-2	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.

## Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	Vents/Process Vents				
HT2FLR	Emission Points/Stationary Vents/Process Vents	N/A	R5121-3	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
HT2FLR	Emission Points/Stationary Vents/Process Vents	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.
HT2FLRG	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
HT2FLRG	Emission Points/Stationary Vents/Process Vents	N/A	R5121-2	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
HT2FLRG	Emission Points/Stationary Vents/Process Vents	N/A	R5121-3	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
HT3FLR	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
HT3FLR	Emission Points/Stationary Vents/Process Vents	N/A	R5121-2	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
HT3FLR	Emission Points/Stationary Vents/Process Vents	N/A	R5121-3	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
HT3FLRG	Emission	N/A	R5121-1	30 TAC Chapter 115, Vent	No changing attributes.



## Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	Points/Stationary Vents/Process Vents			Gas Controls	
HT3FLRG	Emission Points/Stationary Vents/Process Vents	N/A	R5121-2	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
HT3FLRG	Emission Points/Stationary Vents/Process Vents	N/A	R5121-3	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
IRUFLR	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
IRUFLR	Emission Points/Stationary Vents/Process Vents	N/A	R5121-2	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
IRUFLR	Emission Points/Stationary Vents/Process Vents	N/A	R5121-3	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
IRUFLR	Emission Points/Stationary Vents/Process Vents	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.
IRUFLRG	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
IRUFLRG	Emission Points/Stationary Vents/Process Vents	N/A	R5121-2	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
IRUFLRG	Emission Points/Stationary Vents/Process Vents	N/A	R5121-3	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
LPGFL	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
NTFFLR	Emission Points/Stationary Vents/Process Vents	N/A	R5720-1	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
NTFFLR	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
NTFFLR	Emission Points/Stationary Vents/Process Vents	N/A	R5121-2	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
NTFFLR	Emission Points/Stationary Vents/Process Vents	N/A	R5121-3	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
NTFFLR	Emission Points/Stationary Vents/Process Vents	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.
NTFFLRG	Emission Points/Stationary Vents/Process Vents	N/A	R5720-1	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
NTFFLRG	Emission Points/Stationary	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	VENT TYPE = Title 30 TAC Chapter 115, Subchapter B, Vent

## Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	Vents/Process Vents				Gas Control rules are applicable and the vent is not specifically classified under the rule.
NTFFLRG	Emission Points/Stationary Vents/Process Vents	N/A	R5121-2	30 TAC Chapter 115, Vent Gas Controls	VENT TYPE = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.
NTFFLRG	Emission Points/Stationary Vents/Process Vents	N/A	R5121-3	30 TAC Chapter 115, Vent Gas Controls	VENT TYPE = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
OP2ACMAP	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
OP2ACMAP	Emission Points/Stationary Vents/Process Vents	N/A	R5121-2	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
OP2DECOK	Emission Points/Stationary Vents/Process Vents	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
OP2DECOK	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
OP2DECOK2	Emission	N/A	R5121-1	30 TAC Chapter 115, Vent	No changing attributes.

## Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	Points/Stationary Vents/Process Vents			Gas Controls	
OP2DIST	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
OP2DIST	Emission Points/Stationary Vents/Process Vents	N/A	R5121-2	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
OP2DIST	Emission Points/Stationary Vents/Process Vents	N/A	R5121-3	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
SITE3FL	Emission Points/Stationary Vents/Process Vents	N/A	R5720-1	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
SITE3FL	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
V337	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
V337	Emission Points/Stationary Vents/Process Vents	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
V392	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
V392	Emission Points/Stationary Vents/Process Vents	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
V8204	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
V8204	Emission Points/Stationary Vents/Process Vents	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
V8217	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
V8321	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
V8321	Emission Points/Stationary Vents/Process Vents	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
V8360	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	CONTROL DEVICE TYPE = Chiller or catalytic incinerator.
V8360	Emission Points/Stationary Vents/Process Vents	N/A	R5121-2	30 TAC Chapter 115, Vent Gas Controls	CONTROL DEVICE TYPE = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					incinerator, carbon adsorption system, chiller, flare or vapor combustor.
V8360	Emission Points/Stationary Vents/Process Vents	N/A	63G-1	40 CFR Part 63, Subpart G	CONTROL DEVICE = Catalytic incinerator., BY-PASS LINES = The vent system contains by-pass lines that can divert the vent stream from the control device., FLOW INDICATOR = A flow indicator is installed and operated at the entrance of the by-pass line., PERFORMANCE TEST = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.
V8360	Emission Points/Stationary Vents/Process Vents	N/A	63G-2	40 CFR Part 63, Subpart G	CONTROL DEVICE = Boiler or process heater with a design heat input capacity of greater than 44 MW, BY-PASS LINES = The vent system does not contain by-pass lines that can divert the vent stream from the control device., PERFORMANCE TEST = No previous performance test was

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					conducted.
V87923	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
V87923	Emission Points/Stationary Vents/Process Vents	N/A	63G-1	40 CFR Part 63, Subpart G	OVERLAP = Title 40 CFR Part 60, Subpart RRR
V87923	Emission Points/Stationary Vents/Process Vents	N/A	63G-2	40 CFR Part 63, Subpart G	OVERLAP = Title 40 CFR Part 60, Subpart NNN
VP31142	Emission Points/Stationary Vents/Process Vents	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
VP31142	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
VUT109	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	CONTROL DEVICE TYPE = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.
VUT109	Emission Points/Stationary	N/A	R5121-2	30 TAC Chapter 115, Vent Gas Controls	CONTROL DEVICE TYPE = Smokeless flare

## Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	Vents/Process Vents				
VUT109	Emission Points/Stationary Vents/Process Vents	N/A	R5121-3	30 TAC Chapter 115, Vent Gas Controls	CONTROL DEVICE TYPE = Smokeless flare
VUT109	Emission Points/Stationary Vents/Process Vents	N/A	R5121-4	30 TAC Chapter 115, Vent Gas Controls	CONTROL DEVICE TYPE = Smokeless flare
X8529A	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
X8529A	Emission Points/Stationary Vents/Process Vents	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
X8529B	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
X8529B	Emission Points/Stationary Vents/Process Vents	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
A1301	Flares	N/A	R1111-1	30 TAC Chapter 111, Visible Emissions	No changing attributes.
A1301	Flares	N/A	R5720-1	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
A1301	Flares	N/A	60A-1	40 CFR Part 60, Subpart A	No changing attributes.
A1301	Flares	N/A	63A-1	40 CFR Part 63, Subpart A	No changing attributes.



## Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
A1333	Flares	N/A	R1111-1	30 TAC Chapter 111, Visible Emissions	No changing attributes.
A1333	Flares	N/A	R5720-1	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
A1333	Flares	N/A	60A-1	40 CFR Part 60, Subpart A	No changing attributes.
A1333	Flares	N/A	63A-1	40 CFR Part 63, Subpart A	No changing attributes.
OP2ELFLA	Flares	N/A	R1111-1	30 TAC Chapter 111, Visible Emissions	No changing attributes.
OP2ELFLA	Flares	N/A	R5720-1	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
OP2ELFLA	Flares	N/A	60A-1	40 CFR Part 60, Subpart A	No changing attributes.
OP2ELFLA	Flares	N/A	63A-1	40 CFR Part 63, Subpart A	No changing attributes.
OP3ELFLA	Flares	N/A	R1111-1	30 TAC Chapter 111, Visible Emissions	No changing attributes.
OP3ELFLA	Flares	N/A	R5720-1	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
OP3ELFLA	Flares	N/A	60A-1	40 CFR Part 60, Subpart A	No changing attributes.
OP3ELFLA	Flares	N/A	63A-1	40 CFR Part 63, Subpart A	No changing attributes.
OP3GRFLA	Flares	N/A	R1111-1	30 TAC Chapter 111, Visible Emissions	No changing attributes.
OP3GRFLA	Flares	N/A	R5720-1	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
OP3GRFLA	Flares	N/A	60A-1	40 CFR Part 60, Subpart A	No changing attributes.

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
OP3GRFLA	Flares	N/A	63A-1	40 CFR Part 63, Subpart A	No changing attributes.
BD3FUG	Fugitive Emission Units	N/A	R5352ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
BD3FUG	Fugitive Emission Units	N/A	63HALL	40 CFR Part 63, Subpart H	No changing attributes.
CIPXFUG	Fugitive Emission Units	N/A	R5352ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
CIPXFUG	Fugitive Emission Units	N/A	61JALL	40 CFR Part 61, Subpart J	No changing attributes.
CIPXFUG	Fugitive Emission Units	N/A	61VALL	40 CFR Part 61, Subpart V	No changing attributes.
CIPXFUG	Fugitive Emission Units	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.
ENVSOFRLR	Fugitive Emission Units	N/A	R5352ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
FUGACU	Fugitive Emission Units	N/A	R5352ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
FUGACU	Fugitive Emission Units	N/A	61JALL	40 CFR Part 61, Subpart J	No changing attributes.
FUGACU	Fugitive Emission Units	N/A	61VALL	40 CFR Part 61, Subpart V	No changing attributes.
FUGACU	Fugitive Emission Units	N/A	63HALL	40 CFR Part 63, Subpart H	No changing attributes.
FUGBEU	Fugitive Emission Units	N/A	R5352ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
FUGBEU	Fugitive Emission Units	N/A	61JALL	40 CFR Part 61, Subpart J	No changing attributes.
FUGBEU	Fugitive Emission Units	N/A	61VALL	40 CFR Part 61, Subpart V	No changing attributes.
FUGBEU	Fugitive Emission Units	N/A	63HALL	40 CFR Part 63, Subpart H	No changing attributes.

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
FUGBIFBOIL	Fugitive Emission Units	N/A	R5352ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
FUGBIFBOIL	Fugitive Emission Units	N/A	63HALL	40 CFR Part 63, Subpart H	No changing attributes.
FUGOXU	Fugitive Emission Units	N/A	R5352ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
FUGOXU	Fugitive Emission Units	N/A	61JALL	40 CFR Part 61, Subpart J	No changing attributes.
FUGOXU	Fugitive Emission Units	N/A	61VALL	40 CFR Part 61, Subpart V	No changing attributes.
FUGOXU	Fugitive Emission Units	N/A	63HALL	40 CFR Part 63, Subpart H	No changing attributes.
FUGPAU3	Fugitive Emission Units	N/A	R5352ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
FUGPAU3	Fugitive Emission Units	N/A	63HALL	40 CFR Part 63, Subpart H	No changing attributes.
HT2FUG	Fugitive Emission Units	N/A	R5352ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
HT2FUG	Fugitive Emission Units	N/A	61JALL	40 CFR Part 61, Subpart J	No changing attributes.
HT2FUG	Fugitive Emission Units	N/A	61VALL	40 CFR Part 61, Subpart V	No changing attributes.
HT2FUG	Fugitive Emission Units	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.
HT3FUG	Fugitive Emission Units	N/A	R5352ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
IRUFUG	Fugitive Emission Units	N/A	R5352ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
IRUFUG	Fugitive Emission Units	N/A	60VVALL	40 CFR Part 60, Subpart VV	No changing attributes.

## Unit Summary

<b>Unit/Group/ Process ID No.</b>	<b>Unit Type</b>	<b>Group/Inclusive Units</b>	<b>SOP Index No.</b>	<b>Regulation</b>	<b>Requirement Driver</b>
IRUFUG	Fugitive Emission Units	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.
LPGFE	Fugitive Emission Units	N/A	R5352ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
OL3FUG	Fugitive Emission Units	N/A	R5352ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
OL3FUG	Fugitive Emission Units	N/A	61JALL	40 CFR Part 61, Subpart J	No changing attributes.
OL3FUG	Fugitive Emission Units	N/A	61VALL	40 CFR Part 61, Subpart V	No changing attributes.
OL3FUG	Fugitive Emission Units	N/A	63YY	40 CFR Part 63, Subpart YY	No changing attributes.
OP2FUG	Fugitive Emission Units	N/A	R5352ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
OP2FUG	Fugitive Emission Units	N/A	61JALL	40 CFR Part 61, Subpart J	No changing attributes.
OP2FUG	Fugitive Emission Units	N/A	61VALL	40 CFR Part 61, Subpart V	No changing attributes.
OP2FUG	Fugitive Emission Units	N/A	63YY	40 CFR Part 63, Subpart YY	No changing attributes.
PAUFE	Fugitive Emission Units	N/A	R5352ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
PAUFE	Fugitive Emission Units	N/A	60VVALL	40 CFR Part 60, Subpart VV	No changing attributes.
PAUFE	Fugitive Emission Units	N/A	63HALL	40 CFR Part 63, Subpart H	No changing attributes.
PY3FUG	Fugitive Emission Units	N/A	R5352ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
PY3FUG	Fugitive Emission Units	N/A	61JALL	40 CFR Part 61, Subpart J	No changing attributes.
PY3FUG	Fugitive Emission Units	N/A	61VALL	40 CFR Part 61, Subpart V	No changing attributes.

## Unit Summary

<b>Unit/Group/ Process ID No.</b>	<b>Unit Type</b>	<b>Group/Inclusive Units</b>	<b>SOP Index No.</b>	<b>Regulation</b>	<b>Requirement Driver</b>
SITE3FE	Fugitive Emission Units	N/A	R5352ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
SITE3FE	Fugitive Emission Units	N/A	63HALL	40 CFR Part 63, Subpart H	No changing attributes.
WRACKFE	Fugitive Emission Units	N/A	R5352ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
WRACKFE	Fugitive Emission Units	N/A	63HALL	40 CFR Part 63, Subpart H	No changing attributes.
CWT13	Industrial Process Cooling Towers	N/A	R5720-1	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
CWT18	Industrial Process Cooling Towers	N/A	R5767	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
CWT1D	Industrial Process Cooling Towers	N/A	R5760-1	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
CWT3C	Industrial Process Cooling Towers	N/A	R5720-1	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
CWT9	Industrial Process Cooling Towers	N/A	R5767	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
OP2	Industrial Process Cooling Towers	N/A	R5760-1	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
OP2	Industrial Process Cooling Towers	N/A	63YY	40 CFR Part 63, Subpart YY	No changing attributes.
OP3CWT	Industrial Process Cooling Towers	N/A	R5760-1	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
OP3CWT	Industrial Process Cooling Towers	N/A	63YY	40 CFR Part 63, Subpart YY	No changing attributes.

## Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
ACNLOAD	Loading/Unloading Operations	N/A	R5211-1	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
ACNLOAD	Loading/Unloading Operations	N/A	R5211-2	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
ACNLOAD	Loading/Unloading Operations	N/A	R5211-3	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
RCLOAD	Loading/Unloading Operations	N/A	R5211-1	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
RCLOAD	Loading/Unloading Operations	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
SCRWRTC	Loading/Unloading Operations	N/A	R5211-1	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
SCRWRTC	Loading/Unloading Operations	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
SITE3TC	Loading/Unloading Operations	N/A	R5211-1	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
SITE3TT	Loading/Unloading Operations	N/A	R5211-1	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
TTLOAD	Loading/Unloading	N/A	R5211-1	30 TAC Chapter 115,	No changing attributes.

## Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	Operations			Loading and Unloading of VOC	
TTLOAD	Loading/Unloading Operations	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
WRTC	Loading/Unloading Operations	N/A	R5211-1	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
WRTCECH	Loading/Unloading Operations	N/A	R5211-1	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
WRTCMEK	Loading/Unloading Operations	N/A	R5211-1	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
WRTT	Loading/Unloading Operations	N/A	R5211-1	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
WRTTECH	Loading/Unloading Operations	N/A	R5211-1	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
WRTTMEK	Loading/Unloading Operations	N/A	R5211-1	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
F8300	Process Heaters/Furnaces	N/A	R7201-1	30 TAC Chapter 117, Subchapter B	No changing attributes.
F8300	Process Heaters/Furnaces	N/A	63DDDDD	40 CFR Part 63, Subpart DDDDD	No changing attributes.

## Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
F8301	Process Heaters/Furnaces	N/A	R7201-1	30 TAC Chapter 117, Subchapter B	No changing attributes.
F8301	Process Heaters/Furnaces	N/A	63DDDDD	40 CFR Part 63, Subpart DDDDD	No changing attributes.
FH3601	Process Heaters/Furnaces	N/A	R7ICI-01	30 TAC Chapter 117, Subchapter B	No changing attributes.
FH3601	Process Heaters/Furnaces	N/A	63DDDDD	40 CFR Part 63, Subpart DDDDD	No changing attributes.
FOL601	Process Heaters/Furnaces	N/A	R7ICI-01	30 TAC Chapter 117, Subchapter B	No changing attributes.
FOL601	Process Heaters/Furnaces	N/A	63DDDDD	40 CFR Part 63, Subpart DDDDD	No changing attributes.
FOL602	Process Heaters/Furnaces	N/A	R7ICI-01	30 TAC Chapter 117, Subchapter B	No changing attributes.
FOL602	Process Heaters/Furnaces	N/A	63DDDDD	40 CFR Part 63, Subpart DDDDD	No changing attributes.
FOL603	Process Heaters/Furnaces	N/A	R7ICI-01	30 TAC Chapter 117, Subchapter B	No changing attributes.
FOL603	Process Heaters/Furnaces	N/A	63DDDDD	40 CFR Part 63, Subpart DDDDD	No changing attributes.
FOL604	Process Heaters/Furnaces	N/A	R7ICI-01	30 TAC Chapter 117, Subchapter B	No changing attributes.
FOL604	Process Heaters/Furnaces	N/A	63DDDDD	40 CFR Part 63, Subpart DDDDD	No changing attributes.



### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
FP31180	Process Heaters/Furnaces	N/A	R7ICI-1	30 TAC Chapter 117, Subchapter B	No changing attributes.
GRPFURN1	Process Heaters/Furnaces	FOL700, FOL710	R7ICI-1	30 TAC Chapter 117, Subchapter B	No changing attributes.
GRPFURN2	Process Heaters/Furnaces	FP31010, FP31020, FP31030, FP31040, FP31050, FP31060, FP31070, FP31080, FP31120, FP31140	REG2-1	30 TAC Chapter 112, Sulfur Compounds	No changing attributes.
GRPFURN2	Process Heaters/Furnaces	FP31010, FP31020, FP31030, FP31040, FP31050, FP31060, FP31070, FP31080, FP31120, FP31140	R7ICI-1	30 TAC Chapter 117, Subchapter B	No changing attributes.
GRPFURN3	Process Heaters/Furnaces	FP31090, FP31100	R7ICI-1	30 TAC Chapter 117, Subchapter B	No changing attributes.
GRPFURN4	Process Heaters/Furnaces	FP31110, FP31130	REG2-1	30 TAC Chapter 112, Sulfur Compounds	No changing attributes.
GRPFURN4	Process Heaters/Furnaces	FP31110, FP31130	R7ICI-1	30 TAC Chapter 117, Subchapter B	No changing attributes.

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRPFURN5	Process Heaters/Furnaces	FOL100, FOL110, FOL120, FOL130, FOL140, FOL150, FOL160, FOL170, FOL180, FOL190	R7ICI-1	30 TAC Chapter 117, Subchapter B	No changing attributes.
H1300	Process Heaters/Furnaces	N/A	R7ICI-1	30 TAC Chapter 117, Subchapter B	No changing attributes.
H1300	Process Heaters/Furnaces	N/A	63DDDDD	40 CFR Part 63, Subpart DDDDD	No changing attributes.
H902	Process Heaters/Furnaces	N/A	R7ICI-1	30 TAC Chapter 117, Subchapter B	No changing attributes.
H902	Process Heaters/Furnaces	N/A	63DDDDD	40 CFR Part 63, Subpart DDDDD	No changing attributes.
OP2ACMAP	Reactor	N/A	60RRR-1	40 CFR Part 60, Subpart RRR	No changing attributes.
OP2ACMAP	Reactor	N/A	60RRR-2	40 CFR Part 60, Subpart RRR	No changing attributes.
P87921	SRIC Engines	N/A	R7ICI-1	30 TAC Chapter 117, Subchapter B	No changing attributes.
A327	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
A327	Storage Tanks/Vessels	N/A	60K-1	40 CFR Part 60, Subpart K	NSPS K PRODUCT STORED = Petroleum (other than crude oil) or condensate
A327	Storage Tanks/Vessels	N/A	60K-2	40 CFR Part 60, Subpart K	NSPS K PRODUCT STORED =

## Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					Petroleum liquid (other than petroleum or condensate)
A328	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	PRIMARY SEAL = Vapor mounted
A328	Storage Tanks/Vessels	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	PRIMARY SEAL = Mechanical shoe, SECONDARY SEAL = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized
A328	Storage Tanks/Vessels	N/A	60K-1	40 CFR Part 60, Subpart K	NSPS K PRODUCT STORED = Petroleum (other than crude oil) or condensate
A328	Storage Tanks/Vessels	N/A	60K-2	40 CFR Part 60, Subpart K	NSPS K PRODUCT STORED = Petroleum liquid (other than petroleum or condensate)
AP18	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
AP18	Storage Tanks/Vessels	N/A	63FFFF-1	40 CFR Part 63, Subpart FFFF	No changing attributes.
AP19	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
AP19	Storage Tanks/Vessels	N/A	63YY	40 CFR Part 63, Subpart YY	No changing attributes.
AP3	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

## Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
D303	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D303	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
D306	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D306	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
D307	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D307	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
D308	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D308	Storage Tanks/Vessels	N/A	63G-01	40 CFR Part 63, Subpart G	No changing attributes.
D313	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D334	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D341	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D342	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D342	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
D342	Storage Tanks/Vessels	N/A	63G-2	40 CFR Part 63, Subpart G	No changing attributes.
D350	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115,	No changing attributes.

## Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
				Storage of VOCs	
D350	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
D351	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D351	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
D352	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D352	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
D353	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D353	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
D364	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D365	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D366	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D367	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D369	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D370	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
D370	Storage Tanks/Vessels	N/A	60K-1	40 CFR Part 60, Subpart K	No changing attributes.
D370	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
D371	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D371	Storage Tanks/Vessels	N/A	60K-1	40 CFR Part 60, Subpart K	No changing attributes.
D371	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
D377	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D377	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
D379	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D379	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	SEAL TYPE = Liquid-mounted seal (as defined in 40 CFR § 63.111)
D379	Storage Tanks/Vessels	N/A	63G-2	40 CFR Part 63, Subpart G	SEAL TYPE = Metallic shoe seal (as defined in 40 CFR § 63.111)
D380	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D380	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
D381	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D381	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
D393	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115,	No changing attributes.

## Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
				Storage of VOCs	
D393	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
D394	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D394	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
D395	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D395	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
D398	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D398	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
D399	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D399	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
D400	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D400	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
D401	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D401	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
D402	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

## Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
D402	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
D403	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D403	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
D8100	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
D8100	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
DIESEL TANK	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
EX63	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
EX63	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
EX64	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
EX64	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
EX65	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
EX65	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
EX66	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
EX66	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
EX67	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.



## Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
EX68	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
EX68	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
EX69	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
EX69	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
EX70	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
EX70	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
EX76	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
EX76	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
EX77	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
EX77	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
EX80	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
EX80	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
F310	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
F310	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
F336	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
F337	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
F347	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
F347	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
F349	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
F349	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
F350	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
F350	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
F351	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
F355	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
F356	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
F357	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
F357	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
F358	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
F358	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.

## Unit Summary

<b>Unit/Group/ Process ID No.</b>	<b>Unit Type</b>	<b>Group/Inclusive Units</b>	<b>SOP Index No.</b>	<b>Regulation</b>	<b>Requirement Driver</b>
F359	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
F359	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
F360	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
F360	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
F361	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
F361	Storage Tanks/Vessels	N/A	60K-1	40 CFR Part 60, Subpart K	No changing attributes.
F361	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
G330	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
G330	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
G331	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
G331	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
G343	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
G343	Storage Tanks/Vessels	N/A	60K-1	40 CFR Part 60, Subpart K	No changing attributes.
G343	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
G344	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
G344	Storage Tanks/Vessels	N/A	60K-1	40 CFR Part 60, Subpart K	No changing attributes.
G344	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
G353	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
G353	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
GRPVESHO	Storage Tanks/Vessels	VBD901, VBD902, VBD903, VBD920, VBD921, VBD934, VBD991, VIP950	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPVESHO	Storage Tanks/Vessels	VBD901, VBD902, VBD903, VBD920, VBD921, VBD934, VBD991, VIP950	R5112-2	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPVESHO	Storage Tanks/Vessels	VBD901, VBD902, VBD903, VBD920, VBD921, VBD934, VBD991, VIP950	R5112-3	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
J313	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
J313	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
J314	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
J314	Storage Tanks/Vessels	N/A	63FFFF-1	40 CFR Part 63, Subpart FFFF	No changing attributes.

## Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
J320	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
K306	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
K307	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
L306	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
L306	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
L308	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
L308	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
L332	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
L332	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
L333	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
L333	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
L334	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
L335	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
L336	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115,	No changing attributes.

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
				Storage of VOCs	
S332	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
S332	Storage Tanks/Vessels	N/A	61FF-1	40 CFR Part 61, Subpart FF	No changing attributes.
S390	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
S391	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
S392	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
S400	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T1302	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T1310	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T13146	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T1318	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T1318	Storage Tanks/Vessels	N/A	60Kb-1	40 CFR Part 60, Subpart Kb	No changing attributes.
T1319	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

### Unit Summary

<b>Unit/Group/ Process ID No.</b>	<b>Unit Type</b>	<b>Group/Inclusive Units</b>	<b>SOP Index No.</b>	<b>Regulation</b>	<b>Requirement Driver</b>
T1331	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T1332	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T1333	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T1334	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T182	Storage Tanks/Vessels	N/A	60Kb-1	40 CFR Part 60, Subpart Kb	No changing attributes.
T2800	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T317	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T331	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T658	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T74B	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T74B	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
T87000	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T87000	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T87001	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T87003	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T87004	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T87005	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T87005	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
T87007	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T87007	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
T87100	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T87100	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
T87300	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T87300	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
T87400	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T87400	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
T87401	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.



### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T87401	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
T87500	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T87500	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
TB3-301-R1	Storage Tanks/Vessels	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TB3-301-R1	Storage Tanks/Vessels	N/A	63G-2	40 CFR Part 63, Subpart G	No changing attributes.
TBD301	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TBD301	Storage Tanks/Vessels	N/A	63FFFF-1	40 CFR Part 63, Subpart FFFF	No changing attributes.
TBD910	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TBD910	Storage Tanks/Vessels	N/A	63FFFF-1	40 CFR Part 63, Subpart FFFF	No changing attributes.
TBD911	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TBD911	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
TBD912	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	Seal Type = Two seals mounted one above the other so that each forms a continuous closure that completely covers the space between the wall of the storage vessel and the edge of the

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					floating roof
TBD912	Storage Tanks/Vessels	N/A	63G-2	40 CFR Part 63, Subpart G	Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)
TBD913	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TBD913	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
TC33001	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TC33002	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TF34001	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TOL301	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TOL302	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TOL303	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TOL304	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TOL305	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TOL3070	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
TOL400	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TOL401	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TOL901	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, PRODUCT STORED = VOC other than crude oil or condensate
TOL901	Storage Tanks/Vessels	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, PRODUCT STORED = Crude oil and/or condensate
TOL901	Storage Tanks/Vessels	N/A	63YY	40 CFR Part 63, Subpart YY	No changing attributes.
TOL902	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TOL902	Storage Tanks/Vessels	N/A	63YY	40 CFR Part 63, Subpart YY	No changing attributes.
TOL903	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TOL903	Storage Tanks/Vessels	N/A	63YY	40 CFR Part 63, Subpart YY	No changing attributes.
TOL904	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TOL904	Storage Tanks/Vessels	N/A	61FF-1	40 CFR Part 61, Subpart FF	No changing attributes.
TOL904	Storage Tanks/Vessels	N/A	63YY	40 CFR Part 63, Subpart YY	No changing attributes.

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
TOL905	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TOL905	Storage Tanks/Vessels	N/A	63FFFF-1	40 CFR Part 63, Subpart FFFF	No changing attributes.
TOL908	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TOL909	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TOL910	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TOL911	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, PRODUCT STORED = VOC other than crude oil or condensate
TOL911	Storage Tanks/Vessels	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, PRODUCT STORED = Crude oil and/or condensate
TOL911	Storage Tanks/Vessels	N/A	60K-1	40 CFR Part 60, Subpart K	NSPS K PRODUCT STORED = Petroleum (other than crude oil) or condensate
TOL911	Storage Tanks/Vessels	N/A	60K-2	40 CFR Part 60, Subpart K	NSPS K PRODUCT STORED = Petroleum liquid (other than petroleum or condensate)
TOL911	Storage Tanks/Vessels	N/A	63YY	40 CFR Part 63, Subpart YY	No changing attributes.

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
TOL912	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, PRODUCT STORED = VOC other than crude oil or condensate
TOL912	Storage Tanks/Vessels	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, PRODUCT STORED = Crude oil and/or condensate
TOL912	Storage Tanks/Vessels	N/A	63YY	40 CFR Part 63, Subpart YY	No changing attributes.
TOL913	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TOL913	Storage Tanks/Vessels	N/A	63FFFF-1	40 CFR Part 63, Subpart FFFF	No changing attributes.
TOL914	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TOL920	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TOL920	Storage Tanks/Vessels	N/A	60Ka-1	40 CFR Part 60, Subpart Ka	No changing attributes.
TOL920	Storage Tanks/Vessels	N/A	63YY	40 CFR Part 63, Subpart YY	No changing attributes.
TR35020	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TU30911	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

### Unit Summary

<b>Unit/Group/ Process ID No.</b>	<b>Unit Type</b>	<b>Group/Inclusive Units</b>	<b>SOP Index No.</b>	<b>Regulation</b>	<b>Requirement Driver</b>
TU30913	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TUT604	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TUT918	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
VBD933	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
VBD933	Storage Tanks/Vessels	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
VBD933	Storage Tanks/Vessels	N/A	R5112-3	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
VBD933	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
VBD933	Storage Tanks/Vessels	N/A	63G-2	40 CFR Part 63, Subpart G	No changing attributes.
VBD933	Storage Tanks/Vessels	N/A	63G-3	40 CFR Part 63, Subpart G	No changing attributes.
VBD990	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
VBD990	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
VBD993	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
VBD993	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
VBD994	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

### Unit Summary

<b>Unit/Group/ Process ID No.</b>	<b>Unit Type</b>	<b>Group/Inclusive Units</b>	<b>SOP Index No.</b>	<b>Regulation</b>	<b>Requirement Driver</b>
VBD994	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
VC3303	Storage Tanks/Vessels	N/A	63YY	40 CFR Part 63, Subpart YY	No changing attributes.
VIP901	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
VIP902	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
VIP904	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
VIP905	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
VOL200	Storage Tanks/Vessels	N/A	63YY	40 CFR Part 63, Subpart YY	No changing attributes.
VOL201	Storage Tanks/Vessels	N/A	63YY	40 CFR Part 63, Subpart YY	No changing attributes.
VOL250	Storage Tanks/Vessels	N/A	63YY	40 CFR Part 63, Subpart YY	No changing attributes.
VOL251	Storage Tanks/Vessels	N/A	63YY	40 CFR Part 63, Subpart YY	No changing attributes.
VOL300	Storage Tanks/Vessels	N/A	63YY	40 CFR Part 63, Subpart YY	No changing attributes.
VOL350	Storage Tanks/Vessels	N/A	63YY	40 CFR Part 63, Subpart YY	No changing attributes.
VP31143	Storage Tanks/Vessels	N/A	63YY	40 CFR Part 63, Subpart YY	No changing attributes.
VP31144	Storage Tanks/Vessels	N/A	63YY	40 CFR Part 63, Subpart YY	No changing attributes.
VP31158	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
X303	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

## Unit Summary

<b>Unit/Group/ Process ID No.</b>	<b>Unit Type</b>	<b>Group/Inclusive Units</b>	<b>SOP Index No.</b>	<b>Regulation</b>	<b>Requirement Driver</b>
X303	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
X304	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
X304	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
X308	Storage Tanks/Vessels	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
X308	Storage Tanks/Vessels	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
PROAERAT	Treatment Process	N/A	61FF-1	40 CFR Part 61, Subpart FF	No changing attributes.
AU602	Volatile Organic Compound Water Separators	N/A	R7ICI-01	30 TAC Chapter 115, Water Separation	No changing attributes.
CPI	Volatile Organic Compound Water Separators	N/A	R5131-1	30 TAC Chapter 115, Water Separation	No changing attributes.
GRPAPI	Volatile Organic Compound Water Separators	NAPI, SAPI	R5131-1	30 TAC Chapter 115, Water Separation	No changing attributes.
LO3CPI	Volatile Organic Compound Water Separators	N/A	R5131-1	30 TAC Chapter 115, Water Separation	No changing attributes.
A1304	Wastewater Units	N/A	R5147	30 TAC Chapter 115, Industrial Wastewater	No changing attributes.
A13113	Wastewater Units	N/A	R5147	30 TAC Chapter 115, Industrial Wastewater	No changing attributes.



### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
A1315	Wastewater Units	N/A	R5147	30 TAC Chapter 115, Industrial Wastewater	No changing attributes.
DISTRBOX	Wastewater Units	N/A	R5147	30 TAC Chapter 115, Industrial Wastewater	No changing attributes.
GRPWW	Wastewater Units	EAERAT, MAERAT, WAERAT	R5140-1	30 TAC Chapter 115, Industrial Wastewater	No changing attributes.
NEUT1	Wastewater Units	N/A	R5147	30 TAC Chapter 115, Industrial Wastewater	No changing attributes.
NEUT2	Wastewater Units	N/A	R5147	30 TAC Chapter 115, Industrial Wastewater	No changing attributes.
NEUT3	Wastewater Units	N/A	R5147	30 TAC Chapter 115, Industrial Wastewater	No changing attributes.
NEUT4	Wastewater Units	N/A	R5147	30 TAC Chapter 115, Industrial Wastewater	No changing attributes.
P1309S	Wastewater Units	N/A	R5147	30 TAC Chapter 115, Industrial Wastewater	No changing attributes.
S13141	Wastewater Units	N/A	R5147	30 TAC Chapter 115, Industrial Wastewater	No changing attributes.
S13142	Wastewater Units	N/A	R5147	30 TAC Chapter 115, Industrial Wastewater	No changing attributes.
S13143	Wastewater Units	N/A	R5147	30 TAC Chapter 115, Industrial Wastewater	No changing attributes.
SETENT	Wastewater Units	N/A	R5147	30 TAC Chapter 115,	No changing attributes.

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
				Industrial Wastewater	
T1301	Wastewater Units	N/A	R5147	30 TAC Chapter 115, Industrial Wastewater	No changing attributes.
T13145	Wastewater Units	N/A	R5147	30 TAC Chapter 115, Industrial Wastewater	No changing attributes.
T1320	Wastewater Units	N/A	R5147	30 TAC Chapter 115, Industrial Wastewater	No changing attributes.
T19054	Wastewater Units	N/A	R5147	30 TAC Chapter 115, Industrial Wastewater	No changing attributes.
T3272	Wastewater Units	N/A	R5147	30 TAC Chapter 115, Industrial Wastewater	No changing attributes.

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
H87920	EU	REG2-1	SO <sub>2</sub>	30 TAC Chapter 112, Sulfur Compounds	§ 112.9(c)	No person shall use liquid fuel with a sulfur content greater than 0.3% by weight, or allow emissions of SO <sub>2</sub> to exceed 150 ppmv, based on 20% excess air, averaged over a 3-hour period.	§ 112.2(a) ** See Periodic Monitoring Summary	§ 112.2(c)	§ 112.2(b)
H87920	EU	R7201-1	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O <sub>2</sub> , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(e) [G]§ 117.340(f)(2)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5)
H87920	EU	60-Db-1	SO <sub>2</sub>	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
H87920	EU	60-Db-1	PM	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						unit > 29 MW (100 MMBtu/hr).			
H87920	EU	60-Db-1	PM (OPACITY)	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
H87920	EU	60-Db-1	NO <sub>x</sub>	40 CFR Part 60, Subpart Db	§ 60.44b(l)(2) § 60.44b(h) § 60.44b(i) § 60.46b(a)	Affected facilities with a low heat release rate and combusting natural gas or distillate oil in excess of 30% of the heat input from the combustion of all fuels, a limit determined by use of the specified formula.	§ 60.46b(c) § 60.46b(e) § 60.46b(e)(1) § 60.46b(e)(3) [G]§ 60.48b(b) § 60.48b(c) § 60.48b(d) § 60.48b(e) [G]§ 60.48b(e)(2) § 60.48b(e)(3) § 60.48b(f)	[G]§ 60.48b(b) § 60.48b(c) [G]§ 60.49b(d) [G]§ 60.49b(g) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3) § 60.49b(b) § 60.49b(h) § 60.49b(i) § 60.49b(v) § 60.49b(w)
PROAROM	PRO	63F-1	112(B) HAPS	40 CFR Part 63, Subpart F	§ 63.100(b) [G]§ 63.102(a) [G]§ 63.102(c) § 63.104(a) [G]§ 63.104(d) § 63.104(e) § 63.104(e)(1) [G]§ 63.104(e)(2) § 63.105(d)	Except as provided in paragraphs (b)(4) and (c) of this section, the provisions of subparts F, G, and H apply to chemical manufacturing process units that meet the criteria.	§ 63.103(b)(1) § 63.103(b)(3) § 63.103(b)(4) [G]§ 63.103(b)(5) § 63.103(b)(6) [G]§ 63.104(b)	[G]§ 63.103(c) [G]§ 63.104(e)(2) [G]§ 63.104(f)(1) [G]§ 63.105(b) § 63.105(c) § 63.105(e)	§ 63.103(b)(2) [G]§ 63.103(b)(5) [G]§ 63.103(d) [G]§ 63.104(f)(2)
PROBD3	PRO	63F-1	112(B) HAPS	40 CFR Part 63, Subpart F	§ 63.100(b) [G]§ 63.102(a) [G]§ 63.102(c) § 63.104(a)	Except as provided in paragraphs (b)(4) and (c) of this section, the provisions of subparts F,	§ 63.103(b)(1) § 63.103(b)(3) § 63.103(b)(4) [G]§ 63.103(b)(5)	[G]§ 63.103(c) [G]§ 63.104(e)(2) [G]§ 63.104(f)(1) [G]§ 63.105(b)	§ 63.103(b)(2) [G]§ 63.103(b)(5) [G]§ 63.103(d) [G]§ 63.104(f)(2)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
					[G]§ 63.104(d) § 63.104(e) § 63.104(e)(1) [G]§ 63.104(e)(2) § 63.105(d)	G, and H apply to chemical manufacturing process units that meet the criteria.	§ 63.103(b)(6) [G]§ 63.104(b)	§ 63.105(c) § 63.105(e)	
PRODIST	PRO	63F-1	112(B) HAPS	40 CFR Part 63, Subpart F	§ 63.100(b) [G]§ 63.102(a) [G]§ 63.102(c) § 63.105(d)	Except as provided in paragraphs (b)(4) and (c) of this section, the provisions of subparts F, G, and H apply to chemical manufacturing process units that meet the criteria.	§ 63.103(b)(1) § 63.103(b)(3) § 63.103(b)(4) [G]§ 63.103(b)(5) § 63.103(b)(6)	[G]§ 63.103(c) [G]§ 63.105(b) § 63.105(c) § 63.105(e)	§ 63.103(b)(2) [G]§ 63.103(b)(5) [G]§ 63.103(d)
PROOXY	PRO	63F-1	112(B) HAPS	40 CFR Part 63, Subpart F	§ 63.100(b) [G]§ 63.102(a) [G]§ 63.102(c) § 63.104(a) [G]§ 63.104(d) § 63.104(e) § 63.104(e)(1) [G]§ 63.104(e)(2) § 63.105(d)	Except as provided in paragraphs (b)(4) and (c) of this section, the provisions of subparts F, G, and H apply to chemical manufacturing process units that meet the criteria.	§ 63.103(b)(1) § 63.103(b)(3) § 63.103(b)(4) [G]§ 63.103(b)(5) § 63.103(b)(6) [G]§ 63.104(b)	[G]§ 63.103(c) [G]§ 63.104(e)(2) [G]§ 63.104(f)(1) [G]§ 63.105(b) § 63.105(c) § 63.105(e)	§ 63.103(b)(2) [G]§ 63.103(b)(5) [G]§ 63.103(d) [G]§ 63.104(f)(2)
PROPAU	PRO	63F-1	112(B) HAPS	40 CFR Part 63, Subpart F	§ 63.100(b) [G]§ 63.102(a) [G]§ 63.102(c) § 63.104(a) [G]§ 63.104(d) § 63.104(e) § 63.104(e)(1) [G]§ 63.104(e)(2) § 63.105(d)	Except as provided in paragraphs (b)(4) and (c) of this section, the provisions of subparts F, G, and H apply to chemical manufacturing process units that meet the criteria.	§ 63.103(b)(1) § 63.103(b)(3) § 63.103(b)(4) [G]§ 63.103(b)(5) § 63.103(b)(6) [G]§ 63.104(b)	[G]§ 63.103(c) [G]§ 63.104(e)(2) [G]§ 63.104(f)(1) [G]§ 63.105(b) § 63.105(c) § 63.105(e)	§ 63.103(b)(2) [G]§ 63.103(b)(5) [G]§ 63.103(d) [G]§ 63.104(f)(2)
OP2ELFLA	CD	61FF-1	BENZENE	40 CFR Part 61, Subpart FF	§ 61.349(a) § 60.18 § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install,	§ 60.18(f)(2) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(c)	§ 61.354(c) § 61.354(c)(3) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2)(i)(D)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(F)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g) § 61.354(c)	operate, and maintain the closed-vent system and control device.	§ 61.354(c)(3) [G]§ 61.355(h)	§ 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(7)	
OP3ELFLA	CD	61FF-1	BENZENE	40 CFR Part 61, Subpart FF	§ 61.349(a) § 60.18 § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g) § 61.354(c)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 60.18(f)(2) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(3) [G]§ 61.355(h)	§ 61.354(c) § 61.354(c)(3) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2)(i)(D) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(7)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(F)
OP3GRFLA	CD	61FF-1	BENZENE	40 CFR Part 61, Subpart FF	§ 61.349(a) § 60.18 § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g) § 61.354(c)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 60.18(f)(2) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(3) [G]§ 61.355(h)	§ 61.354(c) § 61.354(c)(3) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2)(i)(D) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(7)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(F)
IRUFLR	EP	60NNN-1	VOC/TOC	40 CFR Part 60, Subpart NNN	§ 60.662(b) § 60.18	Each affected facility shall combust the emissions in a flare that meets the requirements of § 60.18.	§ 60.663(b) § 60.663(b)(1) § 60.663(b)(2) § 60.664(a) § 60.664(d) [G]§ 60.664(e)	§ 60.663(b)(2) § 60.665(b) § 60.665(b)(3) § 60.665(d) § 60.665(f)	§ 60.665(a) § 60.665(b) § 60.665(b)(3) § 60.665(k) § 60.665(l) § 60.665(l)(2) § 60.665(l)(4)
IRUFLR	EP	60NNN-2	VOC/TOC	40 CFR Part 60,	§ 60.662(b)	Each affected facility	§ 60.663(b)	§ 60.663(b)(2)	§ 60.665(a)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart NNN	§ 60.18	shall combust the emissions in a flare that meets the requirements of § 60.18.	§ 60.663(b)(1) § 60.663(b)(2) § 60.664(a) § 60.664(d) [G]§ 60.664(e)	§ 60.665(b) § 60.665(b)(3) § 60.665(d) § 60.665(f)	§ 60.665(b) § 60.665(b)(3) § 60.665(k) § 60.665(l) § 60.665(l)(2) § 60.665(l)(4)
IRUFLR	EP	60NNN-3	VOC/TOC	40 CFR Part 60, Subpart NNN	§ 60.662(b) § 60.18	Each affected facility shall combust the emissions in a flare that meets the requirements of § 60.18.	§ 60.663(b) § 60.663(b)(1) § 60.663(b)(2) § 60.664(a) § 60.664(d) [G]§ 60.664(e)	§ 60.663(b)(2) § 60.665(b) § 60.665(b)(3) § 60.665(d) § 60.665(f)	§ 60.665(a) § 60.665(b) § 60.665(b)(3) § 60.665(k) § 60.665(l) § 60.665(l)(2) § 60.665(l)(4)
IRUFLRG	EP	60NNN-1	VOC/TOC	40 CFR Part 60, Subpart NNN	§ 60.662(b) § 60.18	Each affected facility shall combust the emissions in a flare that meets the requirements of § 60.18.	§ 60.663(b) § 60.663(b)(1) § 60.663(b)(2) § 60.664(a) § 60.664(d) [G]§ 60.664(e)	§ 60.663(b)(2) § 60.665(b) § 60.665(b)(3) § 60.665(d) § 60.665(f)	§ 60.665(a) § 60.665(b) § 60.665(b)(3) § 60.665(k) § 60.665(l) § 60.665(l)(2) § 60.665(l)(4)
IRUFLRG	EP	60NNN-2	VOC/TOC	40 CFR Part 60, Subpart NNN	§ 60.662(b) § 60.18	Each affected facility shall combust the emissions in a flare that meets the requirements of § 60.18.	§ 60.663(b) § 60.663(b)(1) § 60.663(b)(2) § 60.664(a) § 60.664(d) [G]§ 60.664(e)	§ 60.663(b)(2) § 60.665(b) § 60.665(b)(3) § 60.665(d) § 60.665(f)	§ 60.665(a) § 60.665(b) § 60.665(b)(3) § 60.665(k) § 60.665(l) § 60.665(l)(2) § 60.665(l)(4)
IRUFLRG	EP	60NNN-3	VOC/TOC	40 CFR Part 60, Subpart NNN	§ 60.662(b) § 60.18	Each affected facility shall combust the emissions in a flare that meets the requirements of § 60.18.	§ 60.663(b) § 60.663(b)(1) § 60.663(b)(2) § 60.664(a) § 60.664(d) [G]§ 60.664(e)	§ 60.663(b)(2) § 60.665(b) § 60.665(b)(3) § 60.665(d) § 60.665(f)	§ 60.665(a) § 60.665(b) § 60.665(b)(3) § 60.665(k) § 60.665(l) § 60.665(l)(2) § 60.665(l)(4)
OP2DIST	EP	60NNN-1	VOC/TOC	40 CFR Part 60,	§ 60.662(a)	Affected facilities shall	§ 60.663(c)	§ 60.663(c)(1)	§ 60.665(a)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart NNN		reduce TOC emissions by 98 weight-percent or to a concentration of 20ppmv, whichever is less stringent. Introduce the stream into the flame zone of a boiler/process heater.	§ 60.663(c)(1) § 60.663(d) § 60.664(c)	§ 60.663(d) § 60.665(b) § 60.665(b)(2) § 60.665(b)(2)(i) § 60.665(c) § 60.665(c)(4) § 60.665(d) § 60.665(e)	§ 60.665(b) § 60.665(b)(2) § 60.665(b)(2)(i) § 60.665(c) § 60.665(c)(4) § 60.665(k) § 60.665(l) § 60.665(l)(1) § 60.665(l)(2) § 60.665(l)(3)
BD3FLR	EP	R5720-1	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.727(c)(2)	A vent gas stream that has the potential to emit HRVOCs, but has a concentration less than 100 ppmv at all times or has a maximum potential flow rate equal to or less than 100 dry standard cubic feet per hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this title. The maximum potential HRVOC emissions for the sum of all vent gas streams claimed under this exemption, must be less for the account specified in § 115.722(a) or (b) of this title than 0.5 tpy.	None	§ 115.726(e)(3)(A) § 115.726(j)(2)	None
BD3FLR	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						properly in accordance with §115.122(a)(2).			
BD3FLR	EP	R5121-2	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
BD3FLR	EP	R5121-3	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
BD3FLR	EP	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(1) § 63.11 § 63.113(h) [G]§ 63.115(f)	Reduce emissions of organic HAP using a flare. §63.113(a)(1)(i)-(ii)	§ 63.114(a) § 63.114(a)(2) [G]§ 63.115(f) [G]§ 63.116(a)	[G]§ 63.117(a)(5) § 63.118(a)(1) § 63.118(a)(2) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.114(e) [G]§ 63.117(a)(5) § 63.117(f) § 63.118(f)(2) § 63.118(f)(5) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
									§ 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
BD3FLR	EP	63G-2	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(1) § 63.11 § 63.113(h) [G]§ 63.115(f)	Reduce emissions of organic HAP using a flare.§63.113(a)(1)(i)-(ii)	§ 63.114(a) § 63.114(a)(2) [G]§ 63.115(f) [G]§ 63.116(a)	[G]§ 63.117(a)(5) § 63.118(a)(1) § 63.118(a)(2) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.114(e) [G]§ 63.117(a)(5) § 63.117(f) § 63.118(f)(2) § 63.118(f)(5) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
BD3FLR	EP	63G-3	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(1) § 63.11 § 63.113(h) [G]§ 63.115(f)	Reduce emissions of organic HAP using a flare.§63.113(a)(1)(i)-(ii)	§ 63.114(a) § 63.114(a)(2) [G]§ 63.115(f) [G]§ 63.116(a)	[G]§ 63.117(a)(5) § 63.118(a)(1) § 63.118(a)(2) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.114(e) [G]§ 63.117(a)(5) § 63.117(f) § 63.118(f)(2) § 63.118(f)(5) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
									[G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
BD3FLRG	EP	R5720-1	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.727(c)(2)	A vent gas stream that has the potential to emit HRVOCs, but has a concentration less than 100 ppmv at all times or has a maximum potential flow rate equal to or less than 100 dry standard cubic feet per hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this title. The maximum potential HRVOC emissions for the sum of all vent gas streams claimed under this exemption, must be less for the account specified in § 115.722(a) or (b) of this title than 0.5 tpy.	None	§ 115.726(e)(3)(A) § 115.726(j)(2)	None
BD3FLRG	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						stream is controlled properly in accordance with §115.122(a)(2).			
BD3FLRG	EP	R5121-2	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
BD3FLRG	EP	R5121-3	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
BD3FLRG	EP	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(1) § 63.11 § 63.113(h) [G]§ 63.115(f)	Reduce emissions of organic HAP using a flare. §63.113(a)(1)(i)-(ii)	§ 63.114(a) § 63.114(a)(2) [G]§ 63.115(f) [G]§ 63.116(a)	[G]§ 63.117(a)(5) § 63.118(a)(1) § 63.118(a)(2) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.114(e) [G]§ 63.117(a)(5) § 63.117(f) § 63.118(f)(2) § 63.118(f)(5) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
									§ 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
BD3FLRG	EP	63G-2	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(1) § 63.11 § 63.113(h) [G]§ 63.115(f)	Reduce emissions of organic HAP using a flare. §63.113(a)(1)(i)-(ii)	§ 63.114(a) § 63.114(a)(2) [G]§ 63.115(f) [G]§ 63.116(a)	[G]§ 63.117(a)(5) § 63.118(a)(1) § 63.118(a)(2) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.114(e) [G]§ 63.117(a)(5) § 63.117(f) § 63.118(f)(2) § 63.118(f)(5) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
BD3FLRG	EP	63G-3	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(1) § 63.11 § 63.113(h) [G]§ 63.115(f)	Reduce emissions of organic HAP using a flare. §63.113(a)(1)(i)-(ii)	§ 63.114(a) § 63.114(a)(2) [G]§ 63.115(f) [G]§ 63.116(a)	[G]§ 63.117(a)(5) § 63.118(a)(1) § 63.118(a)(2) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.114(e) [G]§ 63.117(a)(5) § 63.117(f) § 63.118(f)(2) § 63.118(f)(5) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3)

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
									[G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
CIPXFLR	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
CIPXFLR	EP	R5121-2	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
CIPXFLR	EP	R5121-3	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						with §115.122(a)(1) of this title.			
CIPXFLR	EP	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2455(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart FFFF
CIPXFLRG	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
CIPXFLRG	EP	R5121-2	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
CIPXFLRG	EP	R5121-3	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						title.			
E-87100	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(B)	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(i) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(i) § 115.126(2)	None
E-87100	EP	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(2) § 63.113(h) [G]§ 63.115(f) § 63.116(b)	Reduce emissions of total organic HAPs by 98 wt.% or to a concentration of 20 ppm by volume; whichever is less stringent or as specified. §63.113(a)(2)(i)-(ii)	§ 63.114(a) § 63.114(a)(1)(i) § 63.114(e) [G]§ 63.115(f)	§ 63.114(a)(1) § 63.118(a)(1) § 63.118(a)(2) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.114(e) § 63.117(f) § 63.118(f)(1) § 63.118(f)(2) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
E-87109	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(B)	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas	[G]§ 115.125 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(i) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(i) § 115.126(2)	None



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						stream is controlled properly in accordance with §115.122(a)(2).			
E-87109	EP	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(2) § 63.113(h) [G]§ 63.115(f) § 63.116(b)	Reduce emissions of total organic HAPs by 98 wt.% or to a concentration of 20 ppm by volume; whichever is less stringent or as specified. §63.113(a)(2)(i)-(ii)	§ 63.114(a) § 63.114(a)(1)(i) § 63.114(d)(1) § 63.114(e) [G]§ 63.115(f)	§ 63.114(a)(1) § 63.114(d)(1) § 63.118(a)(1) § 63.118(a)(2) § 63.118(a)(3) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.114(e) § 63.117(f) § 63.118(f)(1) § 63.118(f)(2) § 63.118(f)(3) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FLACU	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
FLACU	EP	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(1) § 63.11 § 63.113(h)	Reduce emissions of organic HAP using a flare. §63.113(a)(1)(i)-(ii)	§ 63.114(a) § 63.114(a)(2) § 63.114(d)(2)	[G]§ 63.117(a)(5) § 63.118(a)(1) § 63.118(a)(2)	§ 63.114(e) [G]§ 63.117(a)(5) § 63.117(f)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
					[G]§ 63.115(f)		[G]§ 63.115(f) [G]§ 63.116(a)	§ 63.118(a)(4) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.118(f)(2) § 63.118(f)(4) § 63.118(f)(5) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FLBEU	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
FLBEU	EP	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(1) § 63.11 § 63.113(h) [G]§ 63.115(f)	Reduce emissions of organic HAP using a flare. §63.113(a)(1)(i)-(ii)	§ 63.114(a) § 63.114(a)(2) § 63.114(d)(2) [G]§ 63.115(f) [G]§ 63.116(a)	[G]§ 63.117(a)(5) § 63.118(a)(1) § 63.118(a)(2) § 63.118(a)(4) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.114(e) [G]§ 63.117(a)(5) § 63.117(f) § 63.118(f)(2) § 63.118(f)(4) § 63.118(f)(5) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FLOXU	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
FLOXU	EP	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(1) § 63.11 § 63.113(h) [G]§ 63.115(f)	Reduce emissions of organic HAP using a flare. §63.113(a)(1)(i)-(ii)	§ 63.114(a) § 63.114(a)(2) § 63.114(d)(2) [G]§ 63.115(f) [G]§ 63.116(a)	[G]§ 63.117(a)(5) § 63.118(a)(1) § 63.118(a)(2) § 63.118(a)(4) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.114(e) [G]§ 63.117(a)(5) § 63.117(f) § 63.118(f)(2) § 63.118(f)(4) § 63.118(f)(5) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
									[G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FLPAP	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
FLPAP	EP	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(1) § 63.11 § 63.113(h) [G]§ 63.115(f)	Reduce emissions of organic HAP using a flare. §63.113(a)(1)(i)-(ii)	§ 63.114(a) § 63.114(a)(2) [G]§ 63.115(f) [G]§ 63.116(a)	[G]§ 63.117(a)(5) § 63.118(a)(1) § 63.118(a)(2) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.114(e) [G]§ 63.117(a)(5) § 63.117(f) § 63.118(f)(2) § 63.118(f)(5) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(ii)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									[G]§ 63.152(c)(6)
FOL100	EP	R1111-01	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(A) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 30% averaged over a six minute period.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
FOL110	EP	R1111-01	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(A) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 30% averaged over a six minute period.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
FOL120	EP	R1111-01	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(A) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 30% averaged over a six minute period.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
FOL130	EP	R1111-01	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(A) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 30% averaged over a six minute period.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
FOL140	EP	R1111-01	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(A) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 30% averaged over a six minute period.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
FOL150	EP	R1111-01	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(A) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 30% averaged over a six minute period.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
FOL160	EP	R1111-01	OPACITY	30 TAC Chapter 111, Visible	§ 111.111(a)(1)(A) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall	[G]§ 111.111(a)(1)(F) ** See Periodic	None	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Emissions		not exceed an opacity of 30% averaged over a six minute period.	Monitoring Summary		
FOL170	EP	R1111-01	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(A) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 30% averaged over a six minute period.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
FOL180	EP	R1111-01	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(A) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 30% averaged over a six minute period.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
FOL190	EP	R1111-01	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(A) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 30% averaged over a six minute period.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
FOL601	EP	R1111-01	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(A) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 30% averaged over a six minute period.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
FOL602	EP	R1111-01	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(A) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 30% averaged over a six minute period.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
FOL603	EP	R1111-01	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(A) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 30% averaged over a six minute period.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FOL604	EP	R1111-01	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(A) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 30% averaged over a six minute period.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
FOL700	EP	R1111-01	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(A) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 30% averaged over a six minute period.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
FOL710	EP	R1111-01	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(A) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 30% averaged over a six minute period.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
GRPACMAP2	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
GRPACMAP3	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
GRPACMAP3	EP	R5121-2	VOC	30 TAC Chapter 115, Vent Gas	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4)	A vent gas stream having a combined weight of	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
				Controls	§ 115.127(a)(2)	volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).		§ 115.126(4)	
GRPPAUPV2	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(B)	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(ii) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(ii) § 115.126(2)	None
GRPPAUPV2	EP	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(2) § 63.113(h) [G]§ 63.115(f) § 63.116(b)	Reduce emissions of total organic HAPs by 98 wt.% or to a concentration of 20 ppm by volume; whichever is less stringent or as specified. §63.113(a)(2)(i)-(ii)	§ 63.114(a) § 63.114(a)(1)(ii) § 63.114(d)(1) § 63.114(e) [G]§ 63.115(f)	§ 63.114(a)(1) § 63.114(d)(1) § 63.118(a)(1) § 63.118(a)(2) § 63.118(a)(3) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.114(e) § 63.117(f) § 63.118(f)(1) § 63.118(f)(2) § 63.118(f)(3) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
GRPPAUPV3	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(B)	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(ii) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(ii) § 115.126(2)	None
GRPPAUPV3	EP	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(2) § 63.113(h) [G]§ 63.115(f) § 63.116(b)	Reduce emissions of total organic HAPs by 98 wt.% or to a concentration of 20 ppm by volume; whichever is less stringent or as specified. §63.113(a)(2)(i)-(ii)	§ 63.114(a) § 63.114(a)(1)(ii) § 63.114(d)(1) § 63.114(e) [G]§ 63.115(f)	§ 63.114(a)(1) § 63.114(d)(1) § 63.118(a)(1) § 63.118(a)(2) § 63.118(a)(3) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.114(e) § 63.117(f) § 63.118(f)(1) § 63.118(f)(2) § 63.118(f)(3) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
GRPPAUPV4	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(C)	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance	[G]§ 115.125 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(ii) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(ii) § 115.126(2)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
						with §115.122(a)(1) of this title.			
GRPPAUPV4	EP	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(2) § 63.113(h) [G]§ 63.115(f) § 63.116(b)	Reduce emissions of total organic HAPs by 98 wt.% or to a concentration of 20 ppm by volume; whichever is less stringent or as specified. §63.113(a)(2)(i)-(ii)	§ 63.114(a) § 63.114(a)(1)(ii) § 63.114(d)(1) § 63.114(e) [G]§ 63.115(f)	§ 63.114(a)(1) § 63.114(d)(1) § 63.118(a)(1) § 63.118(a)(2) § 63.118(a)(3) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.114(e) § 63.117(f) § 63.118(f)(1) § 63.118(f)(2) § 63.118(f)(3) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
GRPVNT	EP	R5720-1	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.727(c)(2)	A vent gas stream that has the potential to emit HRVOCs, but has a concentration less than 100 ppmv at all times or has a maximum potential flow rate equal to or less than 100 dry standard cubic feet per hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this title. The maximum potential HRVOC	None	§ 115.726(e)(3)(A) § 115.726(j)(2)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						emissions for the sum of all vent gas streams claimed under this exemption, must be less for the account specified in § 115.722(a) or (b) of this title than 0.5 tpy.			
GRPVNT	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7) ** See CAM Summary	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
GRPVNT	EP	R5121-2	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7) ** See CAM Summary	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
GRPVNT	EP	R5121-3	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7) ** See CAM Summary	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
GRPVNT2	EP	R5720-1	HIGHLY REACTIVE	30 TAC Chapter 115, HRVOC Vent	§ 115.727(c)(2)	A vent gas stream that has the potential to emit	None	§ 115.726(e)(3)(A) § 115.726(j)(2)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
			VOC	Gas		HRVOCs, but has a concentration less than 100 ppmv at all times or has a maximum potential flow rate equal to or less than 100 dry standard cubic feet per hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this title. The maximum potential HRVOC emissions for the sum of all vent gas streams claimed under this exemption, must be less for the account specified in § 115.722(a) or (b) of this title than 0.5 tpy.			
GRPVNT2	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7) ** See CAM Summary	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
GRPVNT2	EP	R5121-2	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7) ** See CAM Summary	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPVNT2	EP	R5121-3	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7) ** See CAM Summary	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
H1300	EP	R1111-01	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(A) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 30% averaged over a six minute period.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
HT2FLR	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
HT2FLR	EP	R5121-2	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
HT2FLR	EP	R5121-3	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.			
HT2FLR	EP	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2455(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart FFFF
HT2FLRG	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
HT2FLRG	EP	R5121-2	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
HT2FLRG	EP	R5121-3	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						stream is burned properly in accordance with §115.122(a)(1) of this title.			
HT3FLR	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
HT3FLR	EP	R5121-2	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
HT3FLR	EP	R5121-3	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
HT3FLRG	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						stream is burned properly in accordance with §115.122(a)(1) of this title.			
HT3FLRG	EP	R5121-2	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
HT3FLRG	EP	R5121-3	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
IRUFLR	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
IRUFLR	EP	R5121-2	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E),	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).			
IRUFLR	EP	R5121-3	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
IRUFLR	EP	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2455(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart FFFF
IRUFLRG	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
IRUFLRG	EP	R5121-2	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
						stream is controlled properly in accordance with §115.122(a)(2).			
IRUFLRG	EP	R5121-3	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
LPGFL	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
NTFFLR	EP	R5720-1	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.727(c)(2)	A vent gas stream that has the potential to emit HRVOCs, but has a concentration less than 100 ppmv at all times or has a maximum potential flow rate equal to or less than 100 dry standard cubic feet per hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this title. The maximum potential HRVOC emissions for the sum of all vent gas streams	None	§ 115.726(e)(3)(A) § 115.726(j)(2)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						claimed under this exemption, must be less for the account specified in § 115.722(a) or (b) of this title than 0.5 tpy.			
NTFFLR	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
NTFFLR	EP	R5121-2	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
NTFFLR	EP	R5121-3	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
NTFFLR	EP	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2455(a) The permit holder shall comply with the applicable limitation,	The permit holder shall comply with the applicable requirements of 40 CFR Part 63,	The permit holder shall comply with the applicable monitoring and testing requirements	The permit holder shall comply with the applicable recordkeeping	The permit holder shall comply with the applicable reporting requirements of 40 CFR

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					standard and/or equipment specification requirements of 40 CFR Part 63, Subpart FFFF	Subpart FFFF	of 40 CFR Part 63, Subpart FFFF	requirements of 40 CFR Part 63, Subpart FFFF	Part 63, Subpart FFFF
NTFFLRG	EP	R5720-1	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.727(c)(2)	A vent gas stream that has the potential to emit HRVOCs, but has a concentration less than 100 ppmv at all times or has a maximum potential flow rate equal to or less than 100 dry standard cubic feet per hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this title. The maximum potential HRVOC emissions for the sum of all vent gas streams claimed under this exemption, must be less for the account specified in § 115.722(a) or (b) of this title than 0.5 tpy.	None	§ 115.726(e)(3)(A) § 115.726(j)(2)	None
NTFFLRG	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
NTFFLRG	EP	R5121-2	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A)	No person may allow a vent gas stream to be emitted from the	[G]§ 115.125 § 115.126(1) § 115.126(1)(B)	§ 115.126 § 115.126(1) § 115.126(1)(B)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.18	processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	§ 115.126(2) § 115.126(7)	§ 115.126(2)	
NTFFLRG	EP	R5121-3	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
OP2ACMAP	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(C)	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(C) § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(1) § 115.126(1)(C) § 115.126(2)	None
OP2ACMAP	EP	R5121-2	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(C)	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(C) § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(1) § 115.126(1)(C) § 115.126(2)	None
OP2DECOK	EP	R1111-01	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(A) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						30% averaged over a six minute period.			
OP2DECOK	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
OP2DECOK2	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
OP2DIST	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7) ** See CAM Summary	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
OP2DIST	EP	R5121-2	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7) ** See CAM Summary	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						properly in accordance with §115.122(a)(2).			
OP2DIST	EP	R5121-3	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7) ** See CAM Summary	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
SITE3FL	EP	R5720-1	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.727(c)(2)	A vent gas stream that has the potential to emit HRVOCs, but has a concentration less than 100 ppmv at all times or has a maximum potential flow rate equal to or less than 100 dry standard cubic feet per hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this title. The maximum potential HRVOC emissions for the sum of all vent gas streams claimed under this exemption, must be less for the account specified in § 115.722(a) or (b) of this title than 0.5 tpy.	None	§ 115.726(e)(3)(A) § 115.726(j)(2)	None
SITE3FL	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						stream is burned properly in accordance with §115.122(a)(1) of this title.			
V337	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
V337	EP	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(1) § 63.11 § 63.113(h) [G]§ 63.115(f)	Reduce emissions of organic HAP using a flare. §63.113(a)(1)(i)-(ii)	§ 63.114(a) § 63.114(a)(2) § 63.114(d)(2) [G]§ 63.115(f) [G]§ 63.116(a)	[G]§ 63.117(a)(5) § 63.118(a)(1) § 63.118(a)(2) § 63.118(a)(4) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.114(e) [G]§ 63.117(a)(5) § 63.117(f) § 63.118(f)(2) § 63.118(f)(4) § 63.118(f)(5) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
V392	EP	R5121-1	VOC	30 TAC Chapter	§ 115.127(a)(2)(A)	A vent gas stream having	[G]§ 115.125	§ 115.126	None



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Vent Gas Controls	[G]§ 115.122(a)(4) § 115.127(a)(2)	a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	§ 115.126(2) § 115.126(3)(B)	§ 115.126(2) § 115.126(3) § 115.126(3)(B)	
V392	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2) § 115.126(3)(C)	§ 115.126 § 115.126(2) § 115.126(3) § 115.126(3)(C)	None
V392	EP	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.113(e) [G]§ 63.115(f)	The owner or operator of a Group 2 process vent with a TRE index > 4.0 shall maintain a TRE index value > 4.0, comply with the sections as specified.	[G]§ 63.115(a) [G]§ 63.115(b) [G]§ 63.115(c) [G]§ 63.115(d) § 63.115(e) § 63.115(e)(1) [G]§ 63.115(f)	§ 63.117(b) [G]§ 63.118(c) [G]§ 63.152(a)	§ 63.115(e)(2) [G]§ 63.118(g) [G]§ 63.118(h) [G]§ 63.118(k) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(i) § 63.152(c)(4)(ii) § 63.152(c)(4)(iii)
V8204	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4)	A vent gas stream having a combined weight of	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
				Controls	§ 115.127(a)(2)	volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	§ 115.126(3)(B)	§ 115.126(3) § 115.126(3)(B)	
V8204	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2) § 115.126(3)(C)	§ 115.126 § 115.126(2) § 115.126(3) § 115.126(3)(C)	None
V8204	EP	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.113(e) [G]§ 63.115(f)	The owner or operator of a Group 2 process vent with a TRE index > 4.0 shall maintain a TRE index value > 4.0, comply with the sections as specified.	[G]§ 63.115(a) [G]§ 63.115(b) [G]§ 63.115(c) [G]§ 63.115(d) § 63.115(e) § 63.115(e)(1) [G]§ 63.115(f)	§ 63.117(b) [G]§ 63.118(c) [G]§ 63.152(a)	§ 63.115(e)(2) [G]§ 63.118(g) [G]§ 63.118(h) [G]§ 63.118(k) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(i) § 63.152(c)(4)(ii) § 63.152(c)(4)(iii)
V8217	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).			
V8217	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
V8321	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
V8321	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
V8321	EP	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.113(f) [G]§ 63.115(f)	The owner or operator of a Group 2 process vent with a flow rate < than 0.005 standard m3/min shall maintain a flow rate less than 0.005 standard m3/min and comply with	[G]§ 63.115(a) [G]§ 63.115(b) § 63.115(e) § 63.115(e)(1) [G]§ 63.115(f)	[G]§ 63.118(d) [G]§ 63.152(a)	§ 63.115(e)(2) § 63.117(c) [G]§ 63.118(g) [G]§ 63.118(i) [G]§ 63.118(k) [G]§ 63.151(b) § 63.151(e)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
						the sections as specified.			[G]§ 63.151(e)(1) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(i) § 63.152(c)(4)(ii) § 63.152(c)(4)(iii) [G]§ 63.152(c)(6)
V8360	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(B)	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(ii) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(ii) § 115.126(2)	None
V8360	EP	R5121-2	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(B)	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(C) § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(1) § 115.126(1)(C) § 115.126(2)	None
V8360	EP	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.110(d)(5)(ii) § 60.662(c) § 63.110(d)(5)(ii)(D) [G]§ 63.115(f)	If the Group 2 process vent has a TRE value greater than or equal to 1 as determined by the	[G]§ 60.664(e) § 60.664(f) § 60.664(g) § 60.664(g)(1)	[G]§ 60.665(h)	§ 60.664(g)(1) § 60.665(l) § 60.665(l)(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						procedures in 40 CFR part 60 subpart NNN, the process vent is required to comply only with §63.110(d)(5)(ii)(A)-(D).	§ 60.664(g)(2) [G]§ 63.115(a) § 63.115(e) § 63.115(e)(1) [G]§ 63.115(f)		
V8360	EP	63G-2	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.110(d)(5)(ii) § 60.662(c) § 63.110(d)(5)(ii)(D) [G]§ 63.115(f)	If the Group 2 process vent has a TRE value greater than or equal to 1 as determined by the procedures in 40 CFR part 60 subpart NNN, the process vent is required to comply only with §63.110(d)(5)(ii)(A)-(D).	[G]§ 60.664(e) § 60.664(f) § 60.664(g) § 60.664(g)(1) § 60.664(g)(2) [G]§ 63.115(a) § 63.115(e) § 63.115(e)(1) [G]§ 63.115(f)	[G]§ 60.665(h)	§ 60.664(g)(1) § 60.665(l) § 60.665(l)(7)
V87923	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
V87923	EP	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(1) § 63.11 § 63.113(h) [G]§ 63.115(f)	Reduce emissions of organic HAP using a flare. §63.113(a)(1)(i)-(ii)	§ 63.114(a) § 63.114(a)(2) [G]§ 63.115(f) [G]§ 63.116(a)	[G]§ 63.117(a)(5) § 63.118(a)(1) § 63.118(a)(2) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.114(e) [G]§ 63.117(a)(5) § 63.117(f) § 63.118(f)(2) § 63.118(f)(5) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									[G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
V87923	EP	63G-2	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(1) § 63.11 § 63.113(h) [G]§ 63.115(f)	Reduce emissions of organic HAP using a flare.§63.113(a)(1)(i)-(ii)	§ 63.114(a) § 63.114(a)(2) [G]§ 63.115(f) [G]§ 63.116(a)	[G]§ 63.117(a)(5) § 63.118(a)(1) § 63.118(a)(2) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.114(e) [G]§ 63.117(a)(5) § 63.117(f) § 63.118(f)(2) § 63.118(f)(5) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
VP31142	EP	R1111-01	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(A) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 30% averaged over a six minute period.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
VP31142	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4)	A vent gas stream having a combined weight of	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Controls	§ 115.127(a)(2)	volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).		§ 115.126(4)	
VUT109	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(B)	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(C) § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(1) § 115.126(1)(C) § 115.126(2)	None
VUT109	EP	R5121-2	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
VUT109	EP	R5121-3	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
VUT109	EP	R5121-4	VOC	30 TAC Chapter 115, Vent Gas	§ 115.121(a)(2) § 115.122(a)(2)	No person may allow a vent gas stream to be	[G]§ 115.125 § 115.126(1)	§ 115.126 § 115.126(1)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Controls	§ 115.122(a)(2)(A) § 60.18	emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	§ 115.126(1)(B) § 115.126(2) § 115.126(7)	§ 115.126(1)(B) § 115.126(2)	
X8529A	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
X8529A	EP	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(1) § 63.11 § 63.113(h) [G]§ 63.115(f)	Reduce emissions of organic HAP using a flare. §63.113(a)(1)(i)-(ii)	§ 63.114(a) § 63.114(a)(2) § 63.114(d)(2) [G]§ 63.115(f) [G]§ 63.116(a)	[G]§ 63.117(a)(5) § 63.118(a)(1) § 63.118(a)(2) § 63.118(a)(4) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.114(e) [G]§ 63.117(a)(5) § 63.117(f) § 63.118(f)(2) § 63.118(f)(4) § 63.118(f)(5) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(ii)



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									[G]§ 63.152(c)(6)
X8529B	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
X8529B	EP	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(1) § 63.11 § 63.113(h) [G]§ 63.115(f)	Reduce emissions of organic HAP using a flare. §63.113(a)(1)(i)-(ii)	§ 63.114(a) § 63.114(a)(2) § 63.114(d)(2) [G]§ 63.115(f) [G]§ 63.116(a)	[G]§ 63.117(a)(5) § 63.118(a)(1) § 63.118(a)(2) § 63.118(a)(4) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.114(e) [G]§ 63.117(a)(5) § 63.117(f) § 63.118(f)(2) § 63.118(f)(4) § 63.118(f)(5) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
A1301	EU	R1111-1	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						two-hour period, except for emission event emissions as provided in §101.222(b).			
A1301	EP	R5720-1	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.722(d) § 115.722(d)(1) § 115.722(d)(2) [G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) [G]§ 115.725(l) § 115.725(m)(2)(A) § 115.725(m)(2)(B) [G]§ 115.726(a)(2)	All flares must continuously meet the requirements of 40 CFR § 60.18(c)(2)-(6) and (d) as amended through October 17, 2000 (65 FR 61744) when vent gas containing HRVOC is being routed to the flare.	[G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) § 115.725(d)(3) § 115.725(d)(4) § 115.725(d)(5) § 115.725(d)(6) § 115.725(d)(7) § 115.725(k)(1) [G]§ 115.725(l) § 115.725(m)(1) § 115.725(m)(2)(A) § 115.725(m)(2)(B) § 115.725(n)	§ 115.726(a)(1) § 115.726(a)(1)(A) § 115.726(d)(1) § 115.726(d)(10) § 115.726(d)(2) § 115.726(d)(3) § 115.726(d)(4) § 115.726(i) § 115.726(j)(1) § 115.726(j)(2)	§ 115.725(n) § 115.726(a)(1)(B) [G]§ 115.726(a)(2)
A1301	CD	60A-1	OPACITY	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None
A1301	CD	63A-1	OPACITY	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.			
A1333	EU	R1111-1	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for emission event emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
A1333	EP	R5720-1	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.722(d) § 115.722(d)(1) § 115.722(d)(2) [G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) [G]§ 115.725(l) § 115.725(m)(2)(A) § 115.725(m)(2)(B) [G]§ 115.726(a)(2)	All flares must continuously meet the requirements of 40 CFR § 60.18(c)(2)-(6) and (d) as amended through October 17, 2000 (65 FR 61744) when vent gas containing HRVOC is being routed to the flare.	[G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) § 115.725(d)(3) § 115.725(d)(4) § 115.725(d)(5) § 115.725(d)(6) § 115.725(d)(7) § 115.725(k)(1) [G]§ 115.725(l) § 115.725(m)(1) § 115.725(m)(2)(A) § 115.725(m)(2)(B) § 115.725(n)	§ 115.726(a)(1) § 115.726(a)(1)(A) § 115.726(d)(1) § 115.726(d)(10) § 115.726(d)(2) § 115.726(d)(3) § 115.726(d)(4) § 115.726(i) § 115.726(j)(1) § 115.726(j)(2)	§ 115.725(n) § 115.726(a)(1)(B) [G]§ 115.726(a)(2)
A1333	CD	60A-1	OPACITY	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1)	Flares shall comply with paragraphs (c)-(f) of §	§ 60.18(d) § 60.18(f)(1)	None	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	60.18.	§ 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)		
A1333	CD	63A-1	OPACITY	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
OP2ELFLA	EU	R1111-1	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for emission event emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
OP2ELFLA	EP	R5720-1	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.722(d) § 115.722(d)(1) § 115.722(d)(2) [G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) [G]§ 115.725(l)	All flares must continuously meet the requirements of 40 CFR § 60.18(c)(2)-(6) and (d) as amended through October 17, 2000 (65 FR 61744) when vent gas containing HRVOC is being routed to the flare.	[G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) § 115.725(d)(3) § 115.725(d)(4) § 115.725(d)(5) § 115.725(d)(6)	§ 115.726(a)(1) § 115.726(a)(1)(A) § 115.726(d)(1) § 115.726(d)(10) § 115.726(d)(2) § 115.726(d)(3) § 115.726(d)(4) § 115.726(i) § 115.726(j)(1) § 115.726(j)(2)	§ 115.725(n) § 115.726(a)(1)(B) [G]§ 115.726(a)(2)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.725(m)(2)(A) § 115.725(m)(2)(B) [G]§ 115.726(a)(2)		§ 115.725(d)(7) § 115.725(k)(1) [G]§ 115.725(l) § 115.725(m)(1) § 115.725(m)(2)(A) § 115.725(m)(2)(B) § 115.725(n)		
OP2ELFLA	CD	60A-1	OPACITY	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None
OP2ELFLA	CD	63A-1	OPACITY	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
OP3ELFLA	EU	R1111-1	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for emission event emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
OP3ELFLA	EP	R5720-1	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.722(d) § 115.722(d)(1) § 115.722(d)(2) [G]§ 115.725(d)(1) § 115.725(d)(2)	All flares must continuously meet the requirements of 40 CFR § 60.18(c)(2)-(6) and (d) as amended through	[G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii)	§ 115.726(a)(1) § 115.726(a)(1)(A) § 115.726(d)(1) § 115.726(d)(10) § 115.726(d)(2)	§ 115.725(n) § 115.726(a)(1)(B) [G]§ 115.726(a)(2)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) [G]§ 115.725(l) § 115.725(m)(2)(A) § 115.725(m)(2)(B) [G]§ 115.726(a)(2)	October 17, 2000 (65 FR 61744) when vent gas containing HRVOC is being routed to the flare.	§ 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) § 115.725(d)(3) § 115.725(d)(4) § 115.725(d)(5) § 115.725(d)(6) § 115.725(d)(7) § 115.725(k)(1) [G]§ 115.725(l) § 115.725(m)(1) § 115.725(m)(2)(A) § 115.725(m)(2)(B) § 115.725(n)	§ 115.726(d)(3) § 115.726(d)(4) § 115.726(i) § 115.726(j)(1) § 115.726(j)(2)	
OP3ELFLA	CD	60A-1	OPACITY	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None
OP3ELFLA	CD	63A-1	OPACITY	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
OP3GRFLA	EU	R1111-1	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
						two-hour period, except for emission event emissions as provided in §101.222(b).			
OP3GRFLA	EP	R5720-1	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.722(d) § 115.722(d)(1) § 115.722(d)(2) [G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) [G]§ 115.725(l) § 115.725(m)(2)(A) § 115.725(m)(2)(B) [G]§ 115.726(a)(2)	All flares must continuously meet the requirements of 40 CFR § 60.18(c)(2)-(6) and (d) as amended through October 17, 2000 (65 FR 61744) when vent gas containing HRVOC is being routed to the flare.	[G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) § 115.725(d)(3) § 115.725(d)(4) § 115.725(d)(5) § 115.725(d)(6) § 115.725(d)(7) § 115.725(k)(1) [G]§ 115.725(l) § 115.725(m)(1) § 115.725(m)(2)(A) § 115.725(m)(2)(B) § 115.725(n)	§ 115.726(a)(1) § 115.726(a)(1)(A) § 115.726(d)(1) § 115.726(d)(10) § 115.726(d)(2) § 115.726(d)(3) § 115.726(d)(4) § 115.726(i) § 115.726(j)(1) § 115.726(j)(2)	§ 115.725(n) § 115.726(a)(1)(B) [G]§ 115.726(a)(2)
OP3GRFLA	CD	60A-1	OPACITY	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(iii) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4) § 60.18(f)(5)	None	None
OP3GRFLA	CD	63A-1	OPACITY	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(iii)	minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.			
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains, contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(12)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter	§ 115.352(1)(A)	No pressure relief valves	§ 115.354(1)	§ 115.352(7)	[G]§ 115.354(7)



### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Pet. Refinery & Petrochemicals	§ 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8)	(gaseous service), contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP < 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(7) § 115.357(12) § 115.357(8)	other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.356(4)	
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated > 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No flanges, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(12)		§ 115.357(1)	§ 115.356(4)	
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No flanges, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No compressor seal, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No compressor seal, in hydrogen service or equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No compressor seals, contacting a process fluid with a TVP >0.044 psia, not in hydrogen service or not equipped with a shaft seal, shall be allowed to have a VOC leak, for more than 15	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(8)	days after discovery, exceeding the specified VOC concentration.		§ 115.356(4)	
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No pump seals, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No pump seal, equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No pump seals, contacting a process fluid with a TVP >0.044 psia and not equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process,	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
						that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.			
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§115.356(3)(C) of this title.			
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
BD3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
BD3FUG	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.162(e) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h)	Equipment that is in organic HAP service less than 300 hours per year is excluded from the requirements of §§63.163 - 63.174 and §63.178 if it is identified as required in §63.181(j).	[G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.181(j)	[G]§ 63.182(a) [G]§ 63.182(b)
BD3FUG	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.164 § 63.162(a) § 63.162(c)	Standards: Compressors. §63.164(a)-(i)	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c)



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
					[G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171		[G]§ 63.180(d)	[G]§ 63.181(d) [G]§ 63.181(f)	[G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
BD3FUG	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.165 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief device in gas/vapor service. §63.165(a)-(d)	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
BD3FUG	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.166 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Sampling connection systems. §63.166(a)-(c)	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
BD3FUG	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pumps in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
BD3FUG	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Valves in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
BD3FUG	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
					§ 63.162(h) [G]§ 63.171				[G]§ 63.182(d)
BD3FUG	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Agitators in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
BD3FUG	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Instrumentation systems. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
BD3FUG	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief devices in liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
BD3FUG	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.170 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Surge control vessels and bottom receivers.	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
BD3FUG	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.173 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h)	Standards: Agitators gas/vapor service and in light liquid service. §63.173(a)-(j).	[G]§ 63.173 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.171				
BD3FUG	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.174 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in gas/vapor service and in light liquid service. §63.174(a)-(j)	[G]§ 63.174 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
BD3FUG	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.163 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.176	Standards: Pumps in light liquid service. §63.163(a)-(j)	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
BD3FUG	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.167 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Open-ended valves or lines. §63.167(a)-(e).	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
BD3FUG	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.168 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h)	Standards: Valves in gas/vapor service and in light liquid service. §63.168(a)-(j)	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.171 [G]§ 63.175			[G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7)	
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains, contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(12)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter	§ 115.352(1)(A)	No pressure relief valves	§ 115.354(1)	§ 115.352(7)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Pet. Refinery & Petrochemicals	§ 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8)	(gaseous service), contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP < 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(7) § 115.357(12) § 115.357(8)	other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.356(4)	
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated > 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No flanges, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B)	None



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(12)		§ 115.357(1)	§ 115.356(4)	
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No flanges, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No compressor seal, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No compressor seal, in hydrogen service or equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No compressor seals, contacting a process fluid with a TVP >0.044 psia, not in hydrogen service or not equipped with a shaft seal, shall be allowed to have a VOC leak, for more than 15	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(8)	days after discovery, exceeding the specified VOC concentration.		§ 115.356(4)	
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No pump seals, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No pump seal, equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No pump seals, contacting a process fluid with a TVP >0.044 psia and not equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process,	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
						that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.			
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§115.356(3)(C) of this title.			
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
CIPXFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
CIPXFUG	EU	61JALL	BENZENE	40 CFR Part 61, Subpart J	§ 61.112(a) § 61.112(b)	Each owner or operator subject to this subpart shall comply with the requirements of 40 CFR 61, Subpart V - National Emission Standard for Equipment Leaks (Fugitive Emission Sources).	None	None	None
CIPXFUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	§ 61.242-1(e)	Equipment that is in vacuum service is	None	[G]§ 61.246(e)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
						excluded from the requirements of §61.242-2 to §61.242-11, if it is identified as required in §61.246(e)(5).			
CIPXFUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-2 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for pumps. §61.242-2(a)-(g)	[G]§ 61.242-2 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(h) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
CIPXFUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-3 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for compressors. §61.242-3(a)-(i)	[G]§ 61.242-3 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(h) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
CIPXFUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-4 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for pressure relief devices in gas/vapor service. §61.242-4(a)-(c)	[G]§ 61.242-4 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
CIPXFUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-5 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for sampling connection systems. §61.242-5(a)-(c)	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
CIPXFUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-6 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for open-ended valves or lines. §61.242-6(a)-(c)	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
CIPXFUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-7 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10 [G]§ 61.243-1 [G]§ 61.243-2	Comply with standards for valves. §61.242-7(a)-(h)	[G]§ 61.242-7 [G]§ 61.243-1 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(f) [G]§ 61.246(g) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) § 61.247(d) [G]§ 61.247(e)
CIPXFUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-8 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for pressure relief devices in liquid service. § 61.242-8(a)-(d)	[G]§ 61.242-8 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
CIPXFUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	§ 61.242-9 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d)	Each product accumulator vessel shall be equipped with a closed-vent system to capture and transport any leakage from the vessel to a control device as in §61.242-11, except in §61.242-1(c).	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
CIPXFUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-8 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for flanges and other connectors. § 61.242-8(a)-(d)	[G]§ 61.242-8 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
CIPXFUG	EU	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2480(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart FFFF

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					Part 63, Subpart FFFF				
ENVSOFRLR	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains, contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
ENVSOFRLR	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
ENVSOFRLR	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(12)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
ENVSOFRLR	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP greater than 0.044 psia, shall be	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8)	allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
ENVSOFLR	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP < 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
ENVSOFLR	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.			
ENVSOFRLR	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated > 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
ENVSOFRLR	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
ENVSOFRLR	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	days after discovery, exceeding the specified VOC concentration.	§ 115.357(1)		
ENVSOFRLR	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
ENVSOFRLR	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
ENVSOFRLR	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(8)				
ENVSOFRLR	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
ENVSOFRLR	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
ENVSOFRLR	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(12)	No flanges, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
ENVSOFRLR	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery	§ 115.352(1)(A) § 115.352(1)	No flanges, contacting a process fluid with a TVP	§ 115.354(1) § 115.354(10)	§ 115.352(7) § 115.354(10)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				& Petrochemicals	§ 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	>0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
ENVSOFRLR	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No compressor seal, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
ENVSOFRLR	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No compressor seal, in hydrogen service or equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
ENVSOFRLR	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No compressor seals, contacting a process fluid with a TVP >0.044 psia, not in hydrogen service or not equipped with a shaft seal, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ENVSOFRLR	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No pump seals, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
ENVSOFRLR	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No pump seal, equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
ENVSOFRLR	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No pump seals, contacting a process fluid with a TVP >0.044 psia and not equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
ENVSOFRLR	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.			
ENVSOFRLR	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
ENVSOFRLR	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
ENVSOFRLR	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
ENVSOFRLR	EU	R5352ALL	VOC	30 TAC Chapter	§ 115.357(11)	Sampling connection	None	§ 115.356	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Pet. Refinery & Petrochemicals		systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.		§ 115.356(3) [G]§ 115.356(3)(C)	
ENVSOFLR	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains, contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery,	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						exceeding the specified VOC concentration.		§ 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(12)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(1)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(12)	a double block and bleed system, and contacting a process fluid with a TVP < 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.			
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1)	No open-ended valves or lines, rated > 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(12)				
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2)	No valves, rated less than or equal to 10,000 psig and contacting a process	§ 115.354(1) § 115.354(10) § 115.354(2)	§ 115.352(7) § 115.354(10) § 115.356	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(12)	No flanges, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No flanges, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No compressor seal, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No compressor seal, in hydrogen service or equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No compressor seals, contacting a process fluid with a TVP >0.044 psia, not in hydrogen service or not equipped with a shaft seal, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No pump seals, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No pump seal, equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No pump seals, contacting a process fluid with a TVP >0.044 psia and not equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§115.356(3)(C) of this title.			
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
FUGACU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						requirements of this division except §115.356(3)(C) of this title.			
FUGACU	EU	61JALL	BENZENE	40 CFR Part 61, Subpart J	§ 61.112(a) § 61.112(b)	Each owner or operator subject to this subpart shall comply with the requirements of 40 CFR 61, Subpart V - National Emission Standard for Equipment Leaks (Fugitive Emission Sources).	None	None	None
FUGACU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	§ 61.242-1(e)	Equipment that is in vacuum service is excluded from the requirements of §61.242-2 to §61.242-11, if it is identified as required in §61.246(e)(5).	None	[G]§ 61.246(e)	None
FUGACU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-2 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for pumps. §61.242-2(a)-(g)	[G]§ 61.242-2 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(h) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUGACU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-3 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for compressors. §61.242-3(a)-(i)	[G]§ 61.242-3 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(h) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUGACU	EU	61VALL	VHAP	40 CFR Part 61,	[G]§ 61.242-4	Comply with standards	[G]§ 61.242-4	[G]§ 61.246(a)	[G]§ 61.247(a)



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
				Subpart V	§ 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	for pressure relief devices in gas/vapor service. §61.242-4(a)-(c)	[G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUGACU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-5 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for sampling connection systems. §61.242-5(a)-(c)	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUGACU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-6 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for open-ended valves or lines. §61.242-6(a)-(c)	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUGACU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-7 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10 [G]§ 61.243-1 [G]§ 61.243-2	Comply with standards for valves. §61.242-7(a)-(h)	[G]§ 61.242-7 [G]§ 61.243-1 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(f) [G]§ 61.246(g) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) § 61.247(d) [G]§ 61.247(e)
FUGACU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-8 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for pressure relief devices in liquid service. § 61.242-8(a)-(d)	[G]§ 61.242-8 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUGACU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	§ 61.242-9 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d)	Each product accumulator vessel shall be equipped with a closed-vent system to capture and transport any leakage from the vessel to a control device	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
						as in §61.242-11, except in §61.242-1(c).			
FUGACU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-8 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for flanges and other connectors. § 61.242-8(a)-(d)	[G]§ 61.242-8 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUGACU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.162(e) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h)	Equipment that is in organic HAP service less than 300 hours per year is excluded from the requirements of §§63.163 - 63.174 and §63.178 if it is identified as required in §63.181(j).	[G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.181(j)	[G]§ 63.182(a) [G]§ 63.182(b)
FUGACU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.164 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Compressors. §63.164(a)-(i)	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGACU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.165 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief device in gas/vapor service. §63.165(a)-(d)	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGACU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.166 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Sampling connection systems. §63.166(a)-(c)	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
FUGACU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pumps in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGACU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Valves in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGACU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGACU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Agitators in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGACU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Instrumentation systems. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
FUGACU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief devices in liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGACU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.170 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Surge control vessels and bottom receivers.	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGACU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.173 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Agitators gas/vapor service and in light liquid service. §63.173(a)-(j).	[G]§ 63.173 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGACU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.174 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in gas/vapor service and in light liquid service. §63.174(a)-(j)	[G]§ 63.174 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGACU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.163 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.176	Standards: Pumps in light liquid service. §63.163(a)-(j)	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
								§ 63.181(h)(7) § 63.181(h)(8)	
FUGACU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.167 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Open-ended valves or lines. §63.167(a)-(e).	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGACU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.168 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Valves in gas/vapor service and in light liquid service. §63.168(a)-(j)	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains, contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2)	No process drains, contacting a process fluid with a TVP >0.044 psia,	§ 115.354(1) § 115.354(10) § 115.354(5)	§ 115.352(7) § 115.354(10) § 115.356	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(A) § 115.352(3) § 115.352(7)	shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(6) § 115.354(9) [G]§ 115.355	[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(12)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion,	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP < 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355 § 115.357(1)	§ 115.356(4)	
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5)	No open-ended valves or lines, rated > 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355 § 115.357(1)	§ 115.356(4)	
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(7)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(12) § 115.357(8)	VOC concentration.			
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(12)	No flanges, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No flanges, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5)	No compressor seal, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(7) § 115.357(1)	specified VOC concentration.		§ 115.356(4)	
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No compressor seal, in hydrogen service or equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No compressor seals, contacting a process fluid with a TVP >0.044 psia, not in hydrogen service or not equipped with a shaft seal, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No pump seals, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No pump seal, equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery,	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(3) § 115.352(5) § 115.352(7)	exceeding the specified VOC concentration.		§ 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No pump seals, contacting a process fluid with a TVP >0.044 psia and not equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.			
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
FUGBEU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.			
FUGBEU	EU	61JALL	BENZENE	40 CFR Part 61, Subpart J	§ 61.112(a) § 61.112(b)	Each owner or operator subject to this subpart shall comply with the requirements of 40 CFR 61, Subpart V - National Emission Standard for Equipment Leaks (Fugitive Emission Sources).	None	None	None
FUGBEU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	§ 61.242-1(e)	Equipment that is in vacuum service is excluded from the requirements of §61.242-2 to §61.242-11, if it is identified as required in §61.246(e)(5).	None	[G]§ 61.246(e)	None
FUGBEU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-2 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for pumps. §61.242-2(a)-(g)	[G]§ 61.242-2 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(h) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUGBEU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-3 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for compressors. §61.242-3(a)-(i)	[G]§ 61.242-3 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(h)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
								[G]§ 61.246(i) § 61.246(j)	
FUGBEU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-4 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for pressure relief devices in gas/vapor service. §61.242-4(a)-(c)	[G]§ 61.242-4 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUGBEU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-5 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for sampling connection systems. §61.242-5(a)-(c)	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUGBEU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-6 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for open-ended valves or lines. §61.242-6(a)-(c)	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUGBEU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-7 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10 [G]§ 61.243-1 [G]§ 61.243-2	Comply with standards for valves. §61.242-7(a)-(h)	[G]§ 61.242-7 [G]§ 61.243-1 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(f) [G]§ 61.246(g) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) § 61.247(d) [G]§ 61.247(e)
FUGBEU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-8 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for pressure relief devices in liquid service. § 61.242-8(a)-(d)	[G]§ 61.242-8 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUGBEU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	§ 61.242-9 § 61.242-1(a) § 61.242-1(b)	Each product accumulator vessel shall be equipped with a	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.242-1(d)	closed-vent system to capture and transport any leakage from the vessel to a control device as in §61.242-11, except in §61.242-1(c).		§ 61.246(j)	[G]§ 61.247(e)
FUGBEU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-8 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for flanges and other connectors. § 61.242-8(a)-(d)	[G]§ 61.242-8 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUGBEU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.162(e) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h)	Equipment that is in organic HAP service less than 300 hours per year is excluded from the requirements of §§63.163 - 63.174 and §63.178 if it is identified as required in §63.181(j).	[G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.181(j)	[G]§ 63.182(a) [G]§ 63.182(b)
FUGBEU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.164 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Compressors. §63.164(a)-(i)	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGBEU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.165 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief device in gas/vapor service. §63.165(a)-(d)	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGBEU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.166 § 63.162(a)	Standards: Sampling connection systems.	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b)	[G]§ 63.182(a) [G]§ 63.182(b)



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
					§ 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	§63.166(a)-(c)		§ 63.181(c) [G]§ 63.181(i)	§ 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGBEU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pumps in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGBEU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Valves in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGBEU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGBEU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Agitators in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGBEU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c)	Standards: Instrumentation systems. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
					[G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171			[G]§ 63.181(d)	[G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGBEU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief devices in liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGBEU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.170 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Surge control vessels and bottom receivers.	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGBEU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.173 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Agitators gas/vapor service and in light liquid service. §63.173(a)-(j).	[G]§ 63.173 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGBEU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.174 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in gas/vapor service and in light liquid service. §63.174(a)-(j)	[G]§ 63.174 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGBEU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.163 § 63.162(a) § 63.162(c) [G]§ 63.162(f)	Standards: Pumps in light liquid service. §63.163(a)-(j)	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
					[G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.176			§ 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8)	§ 63.182(c)(4) [G]§ 63.182(d)
FUGBEU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.167 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Open-ended valves or lines. §63.167(a)-(e).	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGBEU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.168 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Valves in gas/vapor service and in light liquid service. §63.168(a)-(j)	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains, contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						VOC concentration.			
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(12)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery	§ 115.352(1)(A) § 115.352(1)	No open-ended valves or lines, in an emergency	§ 115.354(1) § 115.354(2)	§ 115.352(7) § 115.356	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				& Petrochemicals	§ 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP < 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery	§ 115.352(1)(A) § 115.352(1)	No open-ended valves or lines, rated > 10,000 psig	§ 115.354(1) § 115.354(2)	§ 115.352(7) § 115.356	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				& Petrochemicals	§ 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery,	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	exceeding the specified VOC concentration.	§ 115.357(1)		
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(12)	No flanges, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No flanges, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery	§ 115.352(1)(B) § 115.352(1)	No compressor seal, contacting a process fluid	§ 115.354(1) § 115.354(2)	§ 115.352(7) § 115.356	None



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				& Petrochemicals	§ 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No compressor seal, in hydrogen service or equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No compressor seals, contacting a process fluid with a TVP >0.044 psia, not in hydrogen service or not equipped with a shaft seal, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No pump seals, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No pump seal, equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No pump seals, contacting a process fluid with a TVP >0.044 psia and not equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FUGBIFBOIL	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
FUGBIFBOIL	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.162(e) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h)	Equipment that is in organic HAP service less than 300 hours per year is excluded from the requirements of §§63.163 - 63.174 and §63.178 if it is identified as required in §63.181(j).	[G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.181(j)	[G]§ 63.182(a) [G]§ 63.182(b)
FUGBIFBOIL	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.164 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Compressors. §63.164(a)-(i)	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGBIFBOIL	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.165 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief device in gas/vapor service. §63.165(a)-(d)	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGBIFBOIL	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.166 § 63.162(a) § 63.162(c)	Standards: Sampling connection systems. §63.166(a)-(c)	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.162(g) § 63.162(h) [G]§ 63.171			[G]§ 63.181(i)	[G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGBIFBOIL	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pumps in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGBIFBOIL	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Valves in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGBIFBOIL	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGBIFBOIL	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Agitators in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGBIFBOIL	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f)	Standards: Instrumentation systems. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
					[G]§ 63.162(g) § 63.162(h) [G]§ 63.171				§ 63.182(c)(4) [G]§ 63.182(d)
FUGBIFBOIL	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief devices in liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGBIFBOIL	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.170 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Surge control vessels and bottom receivers.	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGBIFBOIL	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.173 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Agitators gas/vapor service and in light liquid service. §63.173(a)-(j).	[G]§ 63.173 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGBIFBOIL	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.174 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in gas/vapor service and in light liquid service. §63.174(a)-(j)	[G]§ 63.174 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGBIFBOIL	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.163 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g)	Standards: Pumps in light liquid service. §63.163(a)-(j)	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.162(h) [G]§ 63.171 [G]§ 63.176			[G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8)	[G]§ 63.182(d)
FUGBIFBOIL	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.167 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Open-ended valves or lines. §63.167(a)-(e).	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGBIFBOIL	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.168 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Valves in gas/vapor service and in light liquid service. §63.168(a)-(j)	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains, contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(12)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A)	No open-ended valves or lines, in an emergency shutdown system or containing materials that	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2)	[G]§ 115.354(7)



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP < 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A)	No open-ended valves or lines, rated > 10,000 psig and contacting a process fluid with a TVP less than	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) [G]§ 115.354(9) [G]§ 115.355 § 115.354(8)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(9) [G]§ 115.355	§ 115.356(3)(B) § 115.356(4)	
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(1) § 115.357(12)				
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(12)	No flanges, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No flanges, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A)	No compressor seal, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No compressor seal, in hydrogen service or equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No compressor seals, contacting a process fluid with a TVP >0.044 psia, not in hydrogen service or not equipped with a shaft seal, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No pump seals, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery	§ 115.352(1)(B) § 115.352(1)	No pump seal, equipped with a shaft seal system,	[G]§ 115.355	§ 115.352(7) § 115.356	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				& Petrochemicals	§ 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.		[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No pump seals, contacting a process fluid with a TVP >0.044 psia and not equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter	§ 115.357(5)	Reciprocating	None	§ 115.356	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Pet. Refinery & Petrochemicals		compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.		§ 115.356(3) [G]§ 115.356(3)(C)	
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
FUGOXU	EU	R5352ALL	VOC	30 TAC Chapter	§ 115.357(13)	Components/systems	None	§ 115.356	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Pet. Refinery & Petrochemicals		that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.		§ 115.356(3) [G]§ 115.356(3)(C)	
FUGOXU	EU	61JALL	BENZENE	40 CFR Part 61, Subpart J	§ 61.112(a) § 61.112(b)	Each owner or operator subject to this subpart shall comply with the requirements of 40 CFR 61, Subpart V - National Emission Standard for Equipment Leaks (Fugitive Emission Sources).	None	None	None
FUGOXU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	§ 61.242-1(e)	Equipment that is in vacuum service is excluded from the requirements of §61.242-2 to §61.242-11, if it is identified as required in §61.246(e)(5).	None	[G]§ 61.246(e)	None
FUGOXU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-2 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for pumps. §61.242-2(a)-(g)	[G]§ 61.242-2 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(h) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUGOXU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-3 § 61.242-1(a)	Comply with standards for compressors.	[G]§ 61.242-3 [G]§ 61.245(b)	[G]§ 61.246(a) [G]§ 61.246(b)	[G]§ 61.247(a) [G]§ 61.247(b)



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
					§ 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	§61.242-3(a)-(i)	[G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(h) [G]§ 61.246(i) § 61.246(j)	§ 61.247(c) [G]§ 61.247(e)
FUGOXU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-4 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for pressure relief devices in gas/vapor service. §61.242-4(a)-(c)	[G]§ 61.242-4 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUGOXU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-5 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for sampling connection systems. §61.242-5(a)-(c)	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUGOXU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-6 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for open-ended valves or lines. §61.242-6(a)-(c)	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUGOXU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-7 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10 [G]§ 61.243-1 [G]§ 61.243-2	Comply with standards for valves. §61.242-7(a)-(h)	[G]§ 61.242-7 [G]§ 61.243-1 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(f) [G]§ 61.246(g) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) § 61.247(d) [G]§ 61.247(e)
FUGOXU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-8 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for pressure relief devices in liquid service. § 61.242-8(a)-(d)	[G]§ 61.242-8 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FUGOXU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	§ 61.242-9 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d)	Each product accumulator vessel shall be equipped with a closed-vent system to capture and transport any leakage from the vessel to a control device as in §61.242-11, except in §61.242-1(c).	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUGOXU	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-8 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for flanges and other connectors. § 61.242-8(a)-(d)	[G]§ 61.242-8 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUGOXU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.162(e) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h)	Equipment that is in organic HAP service less than 300 hours per year is excluded from the requirements of §§63.163 - 63.174 and §63.178 if it is identified as required in §63.181(j).	[G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.181(j)	[G]§ 63.182(a) [G]§ 63.182(b)
FUGOXU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.164 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Compressors. §63.164(a)-(i)	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGOXU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.165 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief device in gas/vapor service. §63.165(a)-(d)	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
FUGOXU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.166 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Sampling connection systems. §63.166(a)-(c)	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGOXU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pumps in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGOXU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Valves in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGOXU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGOXU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Agitators in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGOXU	EU	63HALL	112(B)	40 CFR Part 63,	[G]§ 63.169	Standards:	[G]§ 63.169	§ 63.181(a)	[G]§ 63.182(a)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
			HAPS	Subpart H	§ 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Instrumentation systems. §63.169(a)-(d)	[G]§ 63.180(b) [G]§ 63.180(d)	[G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGOXU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief devices in liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGOXU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.170 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Surge control vessels and bottom receivers.	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGOXU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.173 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Agitators gas/vapor service and in light liquid service. §63.173(a)-(j).	[G]§ 63.173 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGOXU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.174 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in gas/vapor service and in light liquid service. §63.174(a)-(j)	[G]§ 63.174 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGOXU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.163 § 63.162(a)	Standards: Pumps in light liquid service.	[G]§ 63.163 [G]§ 63.176	§ 63.181(a) [G]§ 63.181(b)	[G]§ 63.182(a) [G]§ 63.182(b)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
					§ 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.176	§63.163(a)-(j)	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8)	§ 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGOXU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.167 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Open-ended valves or lines. §63.167(a)-(e).	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGOXU	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.168 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Valves in gas/vapor service and in light liquid service. §63.168(a)-(j)	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains, contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(1)	days after discovery, exceeding the specified VOC concentration.		§ 115.356(3)(B) § 115.356(4)	
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(12)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP < 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated > 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2)	No open-ended valves or lines, rated less than or equal to 10,000 psig and	§ 115.354(1) § 115.354(10) § 115.354(2)	§ 115.352(7) § 115.354(10) § 115.356	[G]§ 115.354(7)



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356(3)(B) § 115.356(4)	
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(12)	No flanges, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No flanges, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No compressor seal, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No compressor seal, in hydrogen service or equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No compressor seals, contacting a process fluid with a TVP >0.044 psia, not in hydrogen service or not equipped with a shaft seal, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8)	No pump seals, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(1)	concentration.			
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No pump seal, equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No pump seals, contacting a process fluid with a TVP >0.044 psia and not equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§115.356(3)(C) of this title.			
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§115.356(3)(C) of this title.			
FUGPAU3	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
FUGPAU3	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.162(e) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h)	Equipment that is in organic HAP service less than 300 hours per year is excluded from the requirements of §§63.163 - 63.174 and §63.178 if it is identified as required in §63.181(j).	[G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.181(j)	[G]§ 63.182(a) [G]§ 63.182(b)
FUGPAU3	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.164 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Compressors. §63.164(a)-(i)	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGPAU3	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.165 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief device in gas/vapor service. §63.165(a)-(d)	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
FUGPAU3	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.166 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Sampling connection systems. §63.166(a)-(c)	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGPAU3	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pumps in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGPAU3	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Valves in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGPAU3	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGPAU3	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Agitators in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGPAU3	EU	63HALL	112(B)	40 CFR Part 63,	[G]§ 63.169	Standards:	[G]§ 63.169	§ 63.181(a)	[G]§ 63.182(a)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
			HAPS	Subpart H	§ 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Instrumentation systems. §63.169(a)-(d)	[G]§ 63.180(b) [G]§ 63.180(d)	[G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGPAU3	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief devices in liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGPAU3	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.170 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Surge control vessels and bottom receivers.	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGPAU3	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.173 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Agitators gas/vapor service and in light liquid service. §63.173(a)-(j).	[G]§ 63.173 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGPAU3	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.174 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in gas/vapor service and in light liquid service. §63.174(a)-(j)	[G]§ 63.174 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGPAU3	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.163 § 63.162(a)	Standards: Pumps in light liquid service.	[G]§ 63.163 [G]§ 63.176	§ 63.181(a) [G]§ 63.181(b)	[G]§ 63.182(a) [G]§ 63.182(b)



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.176	§63.163(a)-(j)	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8)	§ 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGPAU3	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.167 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Open-ended valves or lines. §63.167(a)-(e).	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
FUGPAU3	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.168 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Valves in gas/vapor service and in light liquid service. §63.168(a)-(j)	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains, contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(1)	days after discovery, exceeding the specified VOC concentration.		§ 115.356(3)(B) § 115.356(4)	
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(12)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP < 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated > 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2)	No open-ended valves or lines, rated less than or equal to 10,000 psig and	§ 115.354(1) § 115.354(10) § 115.354(2)	§ 115.352(7) § 115.354(10) § 115.356	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356(3)(B) § 115.356(4)	
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(12)	No flanges, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No flanges, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No compressor seal, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No compressor seal, in hydrogen service or equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No compressor seals, contacting a process fluid with a TVP >0.044 psia, not in hydrogen service or not equipped with a shaft seal, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8)	No pump seals, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(1)	concentration.			
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No pump seal, equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No pump seals, contacting a process fluid with a TVP >0.044 psia and not equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§115.356(3)(C) of this title.			
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§115.356(3)(C) of this title.			
HT2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
HT2FUG	EU	61JALL	BENZENE	40 CFR Part 61, Subpart J	§ 61.112(a) § 61.112(b)	Each owner or operator subject to this subpart shall comply with the requirements of 40 CFR 61, Subpart V - National Emission Standard for Equipment Leaks (Fugitive Emission Sources).	None	None	None
HT2FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	§ 61.242-1(e)	Equipment that is in vacuum service is excluded from the requirements of §61.242-2 to §61.242-11, if it is identified as required in §61.246(e)(5).	None	[G]§ 61.246(e)	None
HT2FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-2 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for pumps. §61.242-2(a)-(g)	[G]§ 61.242-2 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(h) [G]§ 61.246(i)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
								§ 61.246(j)	
HT2FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-3 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for compressors. §61.242-3(a)-(i)	[G]§ 61.242-3 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(h) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
HT2FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-4 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for pressure relief devices in gas/vapor service. §61.242-4(a)-(c)	[G]§ 61.242-4 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
HT2FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-5 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for sampling connection systems. §61.242-5(a)-(c)	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
HT2FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-6 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for open-ended valves or lines. §61.242-6(a)-(c)	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
HT2FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-7 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10 [G]§ 61.243-1 [G]§ 61.243-2	Comply with standards for valves. §61.242-7(a)-(h)	[G]§ 61.242-7 [G]§ 61.243-1 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(f) [G]§ 61.246(g) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) § 61.247(d) [G]§ 61.247(e)
HT2FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-8 § 61.242-1(a) § 61.242-1(b)	Comply with standards for pressure relief devices in liquid service. §	[G]§ 61.242-8 [G]§ 61.245(b) [G]§ 61.245(c)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.242-1(d) [G]§ 61.242-10	61.242-8(a)-(d)	[G]§ 61.245(d)	[G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(e)
HT2FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	§ 61.242-9 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d)	Each product accumulator vessel shall be equipped with a closed-vent system to capture and transport any leakage from the vessel to a control device as in §61.242-11, except in §61.242-1(c).	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
HT2FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-8 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for flanges and other connectors. § 61.242-8(a)-(d)	[G]§ 61.242-8 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
HT2FUG	EU	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2480(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart FFFF
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains, contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(12)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A)	No open-ended valves or lines, in an emergency shutdown system or containing materials that	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2)	[G]§ 115.354(7)

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP < 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A)	No open-ended valves or lines, rated > 10,000 psig and contacting a process fluid with a TVP less than	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) [G]§ 115.354(9) [G]§ 115.355 § 115.354(8)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(9) [G]§ 115.355	§ 115.356(3)(B) § 115.356(4)	
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)



### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(1) § 115.357(12)				
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(12)	No flanges, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No flanges, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A)	No compressor seal, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No compressor seal, in hydrogen service or equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No compressor seals, contacting a process fluid with a TVP >0.044 psia, not in hydrogen service or not equipped with a shaft seal, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No pump seals, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery	§ 115.352(1)(B) § 115.352(1)	No pump seal, equipped with a shaft seal system,	[G]§ 115.355	§ 115.352(7) § 115.356	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				& Petrochemicals	§ 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.		[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No pump seals, contacting a process fluid with a TVP >0.044 psia and not equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter	§ 115.357(5)	Reciprocating	None	§ 115.356	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Pet. Refinery & Petrochemicals		compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.		§ 115.356(3) [G]§ 115.356(3)(C)	
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
HT3FUG	EU	R5352ALL	VOC	30 TAC Chapter	§ 115.357(13)	Components/systems	None	§ 115.356	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Pet. Refinery & Petrochemicals		that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.		§ 115.356(3) [G]§ 115.356(3)(C)	
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains, contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(7) § 115.352(9) § 115.357(1) § 115.357(12)	the specified VOC concentration.	[G]§ 115.355 § 115.357(1)		
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP < 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery	§ 115.352(1)(A) § 115.352(1)	No open-ended valves or lines, in an emergency	§ 115.354(1) § 115.354(10)	§ 115.352(7) § 115.354(10)	[G]§ 115.354(7)

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				& Petrochemicals	§ 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated > 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12)	No open-ended valves or lines, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(8)				
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery	§ 115.352(1)(A) § 115.352(1)	No flanges, contacting a process fluid with a TVP	§ 115.354(1) § 115.354(10)	§ 115.352(7) § 115.354(10)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				& Petrochemicals	§ 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(12)	of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No flanges, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No compressor seal, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No compressor seal, in hydrogen service or equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery	§ 115.352(1)(B) § 115.352(1)	No compressor seals, contacting a process fluid	§ 115.354(1) § 115.354(10)	§ 115.352(7) § 115.354(10)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				& Petrochemicals	§ 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	with a TVP >0.044 psia, not in hydrogen service or not equipped with a shaft seal, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No pump seals, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No pump seal, equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No pump seals, contacting a process fluid with a TVP >0.044 psia and not equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR	None	§ 115.356 § 115.356(3)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				& Petrochemicals		§63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.		[G]§ 115.356(3)(C)	
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
IRUFUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
IRUFUG	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-1(d)	Equipment that is in vacuum service is excluded from the requirements of §60.482-2 to §60.482-10, if it is identified as required in	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§60.486(e)(5).			
IRUFUG	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-2 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9	Pumps in light liquid service shall comply with the requirements outlined in § 60.482-2(a)-(f).	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
IRUFUG	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-3 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9	Compressors shall comply with the requirements outlined in § 60.482-3(a)-(j).	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
IRUFUG	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-6 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9	Open-ended valves or lines shall comply with the requirements outlined in § 60.482-6(a)-(c).	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
IRUFUG	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-7 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2	Valves in gas/vapor service and in light liquid service shall comply with the requirements outlined in § 60.482-7(a)-(h).	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e)
IRUFUG	EU	60VVALL	VOC	40 CFR Part 60,	§ 60.482-4(a)	Except during pressure	§ 60.482-4(b)(1)	[G]§ 60.486(a)	§ 60.487(a)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart VV	§ 60.482-1(a) § 60.482-1(b) § 60.482-4(b)(1) § 60.482-4(b)(2) § 60.482-4(d)(1) § 60.482-4(d)(2) [G]§ 60.482-9	releases, each pressure relief device in gas/vapor service shall be operated with no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background.	§ 60.482-4(b)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j)	[G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
IRUFUG	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-8 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9	Pumps in heavy liquid service shall comply with the requirements of §60.482-8(a)-(d).	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
IRUFUG	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-8 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9	Pressure relief devices in light-liquid service shall comply with the requirements of §60.482-8(a)-(d).	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
IRUFUG	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-8 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9	Pressure relief devices in heavy liquid service shall comply with the requirements of §60.482-8(a)-(d).	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
IRUFUG	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-8 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9	Flanges and other connectors shall comply with the requirements of §60.482-8(a)-(d).	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
IRUFUG	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-8 § 60.482-1(a) § 60.482-1(b)	Valves in heavy liquid service shall comply with the requirements of	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-9	§60.482-8(a)-(d).	[G]§ 60.485(d) § 60.485(f)	§ 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(e)
IRUFUG	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-5 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9	Sampling connection systems shall be in compliance with the requirements outlined in § 60.482-5(a)-(c).	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
IRUFUG	EU	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2480(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart FFFF
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains, contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter	§ 115.352(1)(A)	No pressure relief valves	§ 115.354(1)	§ 115.352(7)	[G]§ 115.354(7)



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Pet. Refinery & Petrochemicals	§ 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(12)	(gaseous service), contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP < 0.044 psia, shall be allowed to have a VOC	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						leak, for more than 15 days after discovery, exceeding the specified VOC concentration.			
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated > 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2)	No open-ended valves or lines, rated 10,000 psig or greater and contacting	§ 115.354(1) § 115.354(10) § 115.354(2)	§ 115.352(7) § 115.354(10) § 115.356	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.354(9)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(3)(B)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.356(4)	
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(12)	No flanges, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No flanges, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No compressor seal, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C)	No compressor seal, in hydrogen service or equipped with a shaft seal system, shall be allowed to have a VOC leak, for	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(3) § 115.352(5) § 115.352(7)	more than 15 days after discovery, exceeding the specified VOC concentration.		§ 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No compressor seals, contacting a process fluid with a TVP >0.044 psia, not in hydrogen service or not equipped with a shaft seal, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No pump seals, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No pump seal, equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No pump seals, contacting a process fluid with a TVP >0.044 psia and not equipped with a	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1)	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(6) § 115.354(9) [G]§ 115.355	[G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter	§ 115.357(2)	Each pressure relief valve	None	§ 115.356	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Pet. Refinery & Petrochemicals	§ 115.352(9)	equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).		§ 115.356(3) [G]§ 115.356(3)(C)	
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
LPGFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains, contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(12)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(6) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8)	after discovery, exceeding the specified VOC concentration.	§ 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.356(3)(B) § 115.356(4)	
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP < 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP greater than 0.044 psia,	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.			
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated > 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(1) § 115.357(12)	VOC concentration.			
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(12)	No flanges, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A)	No flanges, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	[G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No compressor seal, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No compressor seal, in hydrogen service or equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No compressor seals, contacting a process fluid with a TVP >0.044 psia, not in hydrogen service or not equipped with a shaft seal, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery	§ 115.352(1)(B) § 115.352(1)	No pump seals, contacting a process fluid	§ 115.354(1) § 115.354(2)	§ 115.352(7) § 115.356	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				& Petrochemicals	§ 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No pump seal, equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No pump seals, contacting a process fluid with a TVP >0.044 psia and not equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.			
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17,	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.			
OL3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
OL3FUG	EU	61JALL	BENZENE	40 CFR Part 61, Subpart J	§ 61.112(a) § 61.112(b)	Each owner or operator subject to this subpart shall comply with the requirements of 40 CFR 61, Subpart V - National Emission Standard for Equipment Leaks (Fugitive Emission Sources).	None	None	None
OL3FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	§ 61.242-1(e)	Equipment that is in vacuum service is excluded from the requirements of §61.242-2 to §61.242-11, if it is identified as required in §61.246(e)(5).	None	[G]§ 61.246(e)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
OL3FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-2 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for pumps. §61.242-2(a)-(g)	[G]§ 61.242-2 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(h) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
OL3FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-3 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for compressors. §61.242-3(a)-(i)	[G]§ 61.242-3 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(h) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
OL3FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-4 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for pressure relief devices in gas/vapor service. §61.242-4(a)-(c)	[G]§ 61.242-4 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
OL3FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-5 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for sampling connection systems. §61.242-5(a)-(c)	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
OL3FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-6 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for open-ended valves or lines. §61.242-6(a)-(c)	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
OL3FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-7 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10 [G]§ 61.243-1	Comply with standards for valves. §61.242-7(a)-(h)	[G]§ 61.242-7 [G]§ 61.243-1 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(f) [G]§ 61.246(g)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) § 61.247(d) [G]§ 61.247(e)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
					[G]§ 61.243-2			[G]§ 61.246(i) § 61.246(j)	
OL3FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-8 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for pressure relief devices in liquid service. § 61.242-8(a)-(d)	[G]§ 61.242-8 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
OL3FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	§ 61.242-9 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d)	Each product accumulator vessel shall be equipped with a closed-vent system to capture and transport any leakage from the vessel to a control device as in §61.242-11, except in §61.242-1(c).	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
OL3FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-8 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for flanges and other connectors. § 61.242-8(a)-(d)	[G]§ 61.242-8 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
OL3FUG	EU	63YY	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart YY
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A)	No process drains, contacting a process fluid with a TVP less than or equal to 0.044 psia, shall	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(3) § 115.352(7) § 115.357(1)	be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355 § 115.357(1)	§ 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(12)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(12)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(8)				
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP < 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						VOC concentration.			
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated > 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter	§ 115.352(1)(A)	No open-ended valves or	§ 115.354(1)	§ 115.352(7)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
				115, Pet. Refinery & Petrochemicals	§ 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) [G]§ 115.356(2)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(12)	No flanges, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12)	No flanges, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B)	None



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(8)			§ 115.356(4)	
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No compressor seal, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No compressor seal, in hydrogen service or equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No compressor seals, contacting a process fluid with a TVP >0.044 psia, not in hydrogen service or not equipped with a shaft seal, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3)	No pump seals, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(5) § 115.352(7) § 115.357(1)	discovery, exceeding the specified VOC concentration.	§ 115.357(1)	§ 115.356(3)(B) § 115.356(4)	
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No pump seal, equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No pump seals, contacting a process fluid with a TVP >0.044 psia and not equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
						requirements of this division except §115.356(3)(C) of this title.			
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						from the requirements of this division except §115.356(3)(C) of this title.			
OP2FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
OP2FUG	EU	61JALL	BENZENE	40 CFR Part 61, Subpart J	§ 61.112(a) § 61.112(b)	Each owner or operator subject to this subpart shall comply with the requirements of 40 CFR 61, Subpart V - National Emission Standard for Equipment Leaks (Fugitive Emission Sources).	None	None	None
OP2FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	§ 61.242-1(e)	Equipment that is in vacuum service is excluded from the requirements of §61.242-2 to §61.242-11, if it is identified as required in §61.246(e)(5).	None	[G]§ 61.246(e)	None
OP2FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-2 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d)	Comply with standards for pumps. §61.242-2(a)-(g)	[G]§ 61.242-2 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
					[G]§ 61.242-10			[G]§ 61.246(h) [G]§ 61.246(i) § 61.246(j)	
OP2FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-3 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for compressors. §61.242-3(a)-(i)	[G]§ 61.242-3 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(h) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
OP2FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-4 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for pressure relief devices in gas/vapor service. §61.242-4(a)-(c)	[G]§ 61.242-4 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
OP2FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-5 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for sampling connection systems. §61.242-5(a)-(c)	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
OP2FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-6 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for open-ended valves or lines. §61.242-6(a)-(c)	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
OP2FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-7 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10 [G]§ 61.243-1 [G]§ 61.243-2	Comply with standards for valves. §61.242-7(a)-(h)	[G]§ 61.242-7 [G]§ 61.243-1 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(f) [G]§ 61.246(g) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) § 61.247(d) [G]§ 61.247(e)
OP2FUG	EU	61VALL	VHAP	40 CFR Part 61,	[G]§ 61.242-8	Comply with standards	[G]§ 61.242-8	[G]§ 61.246(a)	[G]§ 61.247(a)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
				Subpart V	§ 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	for pressure relief devices in liquid service. § 61.242-8(a)-(d)	[G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
OP2FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	§ 61.242-9 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d)	Each product accumulator vessel shall be equipped with a closed-vent system to capture and transport any leakage from the vessel to a control device as in §61.242-11, except in §61.242-1(c).	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
OP2FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-8 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for flanges and other connectors. § 61.242-8(a)-(d)	[G]§ 61.242-8 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
OP2FUG	EU	63YY	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart YY
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains, contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						VOC concentration.			
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(12)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery	§ 115.352(1)(A) § 115.352(1)	No open-ended valves or lines, in an emergency	§ 115.354(1) § 115.354(2)	§ 115.352(7) § 115.356	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				& Petrochemicals	§ 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP < 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery	§ 115.352(1)(A) § 115.352(1)	No open-ended valves or lines, rated > 10,000 psig	§ 115.354(1) § 115.354(2)	§ 115.352(7) § 115.356	[G]§ 115.354(7)



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				& Petrochemicals	§ 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery,	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	exceeding the specified VOC concentration.	§ 115.357(1)		
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(12)	No flanges, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No flanges, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery	§ 115.352(1)(B) § 115.352(1)	No compressor seal, contacting a process fluid	§ 115.354(1) § 115.354(2)	§ 115.352(7) § 115.356	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				& Petrochemicals	§ 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No compressor seal, in hydrogen service or equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No compressor seals, contacting a process fluid with a TVP >0.044 psia, not in hydrogen service or not equipped with a shaft seal, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No pump seals, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No pump seal, equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No pump seals, contacting a process fluid with a TVP >0.044 psia and not equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PAUFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
PAUFE	EU	6oVVALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-1(d)	Equipment that is in vacuum service is excluded from the requirements of §60.482-2 to §60.482-10, if it is identified as required in §60.486(e)(5).	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
PAUFE	EU	6oVVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-2 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9	Pumps in light liquid service shall comply with the requirements outlined in § 60.482-2(a)-(f).	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
PAUFE	EU	6oVVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-3 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9	Compressors shall comply with the requirements outlined in § 60.482-3(a)-(j).	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
PAUFE	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-6 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9	Open-ended valves or lines shall comply with the requirements outlined in § 60.482-6(a)-(c).	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
PAUFE	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-7 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2	Valves in gas/vapor service and in light liquid service shall comply with the requirements outlined in § 60.482-7(a)-(h).	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e)
PAUFE	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-4(a) § 60.482-1(a) § 60.482-1(b) § 60.482-4(b)(1) § 60.482-4(b)(2) § 60.482-4(d)(1) § 60.482-4(d)(2) [G]§ 60.482-9	Except during pressure releases, each pressure relief device in gas/vapor service shall be operated with no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background.	§ 60.482-4(b)(1) § 60.482-4(b)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
PAUFE	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-8 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9	Pumps in heavy liquid service shall comply with the requirements of §60.482-8(a)-(d).	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
PAUFE	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-8 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9	Pressure relief devices in light-liquid service shall comply with the requirements of §60.482-8(a)-(d).	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
PAUFE	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-8 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9	Pressure relief devices in heavy liquid service shall comply with the requirements of §60.482-8(a)-(d).	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
PAUFE	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-8 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9	Flanges and other connectors shall comply with the requirements of §60.482-8(a)-(d).	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
PAUFE	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-8 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9	Valves in heavy liquid service shall comply with the requirements of §60.482-8(a)-(d).	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
PAUFE	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-5 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9	Sampling connection systems shall be in compliance with the requirements outlined in § 60.482-5(a)-(c).	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
PAUFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.162(e) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h)	Equipment that is in organic HAP service less than 300 hours per year is excluded from the requirements of §§63.163 - 63.174 and §63.178 if it is identified as required in §63.181(j).	[G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.181(j)	[G]§ 63.182(a) [G]§ 63.182(b)
PAUFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.164 § 63.162(a) § 63.162(c) [G]§ 63.162(f)	Standards: Compressors. §63.164(a)-(i)	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
					[G]§ 63.162(g) § 63.162(h) [G]§ 63.171			[G]§ 63.181(f)	§ 63.182(c)(4) [G]§ 63.182(d)
PAUFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.165 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief device in gas/vapor service. §63.165(a)-(d)	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
PAUFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.166 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Sampling connection systems. §63.166(a)-(c)	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
PAUFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pumps in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
PAUFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Valves in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
PAUFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.171				
PAUFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Agitators in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
PAUFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Instrumentation systems. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
PAUFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief devices in liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
PAUFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.170 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Surge control vessels and bottom receivers.	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
PAUFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.173 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Agitators gas/vapor service and in light liquid service. §63.173(a)-(j).	[G]§ 63.173 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
PAUFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.174 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in gas/vapor service and in light liquid service. §63.174(a)-(j)	[G]§ 63.174 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
PAUFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.163 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.176	Standards: Pumps in light liquid service. §63.163(a)-(j)	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
PAUFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.167 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Open-ended valves or lines. §63.167(a)-(e).	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
PAUFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.168 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Valves in gas/vapor service and in light liquid service. §63.168(a)-(j)	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								[G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7)	
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains, contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(12)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2)	No pressure relief valves (gaseous service), contacting a process fluid	§ 115.354(1) § 115.354(10) § 115.354(2)	§ 115.352(7) § 115.354(10) § 115.356	[G]§ 115.354(7)

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8)	with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP < 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(8)	a double block and bleed system, and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.			
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated > 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356(3)(B) § 115.356(4)	
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.354(9)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(3)(B)	[G]§ 115.354(7)



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(7) § 115.357(12) § 115.357(8)	exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.356(4)	
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(12)	No flanges, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No flanges, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No compressor seal, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No compressor seal, in hydrogen service or equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No compressor seals, contacting a process fluid with a TVP >0.044 psia, not in hydrogen service or not equipped with a shaft seal, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						VOC concentration.			
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No pump seals, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No pump seal, equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No pump seals, contacting a process fluid with a TVP >0.044 psia and not equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.			
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
PY3FUG	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
PY3FUG	EU	61JALL	BENZENE	40 CFR Part 61, Subpart J	§ 61.112(a) § 61.112(b)	Each owner or operator subject to this subpart shall comply with the requirements of 40 CFR 61, Subpart V - National Emission Standard for Equipment Leaks (Fugitive Emission Sources).	None	None	None
PY3FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	§ 61.242-1(e)	Equipment that is in vacuum service is excluded from the requirements of §61.242-2 to §61.242-11, if it is	None	[G]§ 61.246(e)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
						identified as required in §61.246(e)(5).			
PY3FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-2 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for pumps. §61.242-2(a)-(g)	[G]§ 61.242-2 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(h) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
PY3FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-3 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for compressors. §61.242-3(a)-(i)	[G]§ 61.242-3 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(h) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
PY3FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-4 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for pressure relief devices in gas/vapor service. §61.242-4(a)-(c)	[G]§ 61.242-4 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
PY3FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-5 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for sampling connection systems. §61.242-5(a)-(c)	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
PY3FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-6 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for open-ended valves or lines. §61.242-6(a)-(c)	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
PY3FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-7 § 61.242-1(a) § 61.242-1(b)	Comply with standards for valves. §61.242-7(a)-(h)	[G]§ 61.242-7 [G]§ 61.243-1 [G]§ 61.245(b)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.242-1(d) [G]§ 61.242-10 [G]§ 61.243-1 [G]§ 61.243-2		[G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(e) [G]§ 61.246(f) [G]§ 61.246(g) [G]§ 61.246(i) § 61.246(j)	§ 61.247(d) [G]§ 61.247(e)
PY3FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-8 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for pressure relief devices in liquid service. § 61.242-8(a)-(d)	[G]§ 61.242-8 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
PY3FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	§ 61.242-9 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d)	Each product accumulator vessel shall be equipped with a closed-vent system to capture and transport any leakage from the vessel to a control device as in §61.242-11, except in §61.242-1(c).	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
PY3FUG	EU	61VALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-8 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for flanges and other connectors. § 61.242-8(a)-(d)	[G]§ 61.242-8 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains, contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(12)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A)	No open-ended valves or lines, in an emergency shutdown system or containing materials that	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2)	[G]§ 115.354(7)



### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP < 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A)	No open-ended valves or lines, rated > 10,000 psig and contacting a process fluid with a TVP less than	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(9) [G]§ 115.355	§ 115.356(3)(B) § 115.356(4)	
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(1) § 115.357(12)				
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(12)	No flanges, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No flanges, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A)	No compressor seal, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No compressor seal, in hydrogen service or equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No compressor seals, contacting a process fluid with a TVP >0.044 psia, not in hydrogen service or not equipped with a shaft seal, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No pump seals, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery	§ 115.352(1)(B) § 115.352(1)	No pump seal, equipped with a shaft seal system,	[G]§ 115.355	§ 115.352(7) § 115.356	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				& Petrochemicals	§ 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.		[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No pump seals, contacting a process fluid with a TVP >0.044 psia and not equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter	§ 115.357(5)	Reciprocating	None	§ 115.356	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Pet. Refinery & Petrochemicals		compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.		§ 115.356(3) [G]§ 115.356(3)(C)	
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
SITE3FE	EU	R5352ALL	VOC	30 TAC Chapter	§ 115.357(13)	Components/systems	None	§ 115.356	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Pet. Refinery & Petrochemicals		that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.		§ 115.356(3) [G]§ 115.356(3)(C)	
SITE3FE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.162(e) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h)	Equipment that is in organic HAP service less than 300 hours per year is excluded from the requirements of §§63.163 - 63.174 and §63.178 if it is identified as required in §63.181(j).	[G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.181(j)	[G]§ 63.182(a) [G]§ 63.182(b)
SITE3FE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.164 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Compressors. §63.164(a)-(i)	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
SITE3FE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.165 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief device in gas/vapor service. §63.165(a)-(d)	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
SITE3FE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.166 § 63.162(a) § 63.162(c) [G]§ 63.162(g)	Standards: Sampling connection systems. §63.166(a)-(c)	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1)



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
					§ 63.162(h) [G]§ 63.171				§ 63.182(c)(4) [G]§ 63.182(d)
SITE3FE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pumps in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
SITE3FE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Valves in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
SITE3FE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
SITE3FE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Agitators in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
SITE3FE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g)	Standards: Instrumentation systems. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.162(h) [G]§ 63.171				[G]§ 63.182(d)
SITE3FE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief devices in liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
SITE3FE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.170 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Surge control vessels and bottom receivers.	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
SITE3FE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.172(d) § 63.11(b) § 63.172(e) [G]§ 63.172(h) § 63.172(m)	Flares used to comply with this subpart shall comply with the requirements of § 63.11(b) of 40 CFR 63, Subpart A.	§ 63.172(e) [G]§ 63.172(h) [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.180(e)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) § 63.181(g)(1)(iii) § 63.181(g)(1)(iv) [G]§ 63.181(g)(2)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
SITE3FE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.173 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Agitators gas/vapor service and in light liquid service. §63.173(a)-(j).	[G]§ 63.173 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
SITE3FE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.174 § 63.162(a) § 63.162(c)	Standards: Connectors in gas/vapor service and in light liquid service.	[G]§ 63.174 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
					[G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	§63.174(a)-(j)		[G]§ 63.181(d)	[G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
SITE3FE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.163 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.176	Standards: Pumps in light liquid service. §63.163(a)-(j)	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
SITE3FE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.167 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Open-ended valves or lines. §63.167(a)-(e).	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
SITE3FE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.168 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Valves in gas/vapor service and in light liquid service. §63.168(a)-(j)	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains, contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(12)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(6) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8)	after discovery, exceeding the specified VOC concentration.	§ 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.356(3)(B) § 115.356(4)	
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP < 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP greater than 0.044 psia,	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.			
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated > 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(1) § 115.357(12)	VOC concentration.			
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(12)	No flanges, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A)	No flanges, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1)	None



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	[G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No compressor seal, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No compressor seal, in hydrogen service or equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No compressor seals, contacting a process fluid with a TVP >0.044 psia, not in hydrogen service or not equipped with a shaft seal, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery	§ 115.352(1)(B) § 115.352(1)	No pump seals, contacting a process fluid	§ 115.354(1) § 115.354(2)	§ 115.352(7) § 115.356	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				& Petrochemicals	§ 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No pump seal, equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No pump seals, contacting a process fluid with a TVP >0.044 psia and not equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.			
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17,	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.			
WRACKFE	EU	R5352ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
WRACKFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.162(e) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h)	Equipment that is in organic HAP service less than 300 hours per year is excluded from the requirements of §§63.163 - 63.174 and §63.178 if it is identified as required in §63.181(j).	[G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.181(j)	[G]§ 63.182(a) [G]§ 63.182(b)
WRACKFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.164 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Compressors. §63.164(a)-(i)	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
WRACKFE	EU	63HALL	112(B)	40 CFR Part 63,	[G]§ 63.165	Standards: Pressure relief	[G]§ 63.165	§ 63.181(a)	[G]§ 63.182(a)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
			HAPS	Subpart H	§ 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	device in gas/vapor service. §63.165(a)-(d)	[G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	[G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f)	[G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
WRACKFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.166 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Sampling connection systems. §63.166(a)-(c)	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
WRACKFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pumps in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
WRACKFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Valves in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
WRACKFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
WRACKFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Agitators in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
					[G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171			[G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
WRACKFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Instrumentation systems. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
WRACKFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief devices in liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
WRACKFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.170 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Surge control vessels and bottom receivers.	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
WRACKFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.172(d) § 63.11(b) § 63.172(e) [G]§ 63.172(h) § 63.172(m)	Flares used to comply with this subpart shall comply with the requirements of § 63.11(b) of 40 CFR 63, Subpart A.	§ 63.172(e) [G]§ 63.172(h) [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.180(e)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) § 63.181(g)(1)(iii) § 63.181(g)(1)(iv) [G]§ 63.181(g)(2)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
WRACKFE	EU	63HALL	112(B)	40 CFR Part 63,	[G]§ 63.173	Standards: Agitators	[G]§ 63.173	§ 63.181(a)	[G]§ 63.182(a)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
			HAPS	Subpart H	§ 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	gas/vapor service and in light liquid service. §63.173(a)-(j).	[G]§ 63.180(b) [G]§ 63.180(d)	[G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
WRACKFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.174 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in gas/vapor service and in light liquid service. §63.174(a)-(j)	[G]§ 63.174 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
WRACKFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.163 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.176	Standards: Pumps in light liquid service. §63.163(a)-(j)	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
WRACKFE	EU	63HALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.167 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Open-ended valves or lines. §63.167(a)-(e).	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
WRACKFE	EU	63HALL	112(B)	40 CFR Part 63,	[G]§ 63.168	Standards: Valves in	[G]§ 63.168	§ 63.181(a)	[G]§ 63.182(a)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
			HAPS	Subpart H	§ 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	gas/vapor service and in light liquid service. §63.168(a)-(j)	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	[G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7)	[G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
CWT13	EU	R5720-1	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.767(3) § 115.764(a)(1) § 115.766(i)	Any site for which no stream directed to a cooling tower heat exchange system contains 5.0% or greater by weight HRVOC is exempt from the requirements of § 115.761 of this title (relating to Site-wide Cap).	§ 115.764(a)(1) § 115.764(a)(3) § 115.764(c) § 115.764(d) [G]§ 115.764(g)(1)	§ 115.766(a)(4) § 115.766(c) § 115.766(d) § 115.766(i)(1)	§ 115.766(i)(2)
CWT18	EU	R5767	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.767(2)	Any cooling tower heat exchange system in which no individual heat exchanger has greater than 100 ppmw HRVOCs in the process side fluid is exempt from the requirements of this division, with the exception of the recordkeeping requirements of §115.766(b) and (c) of this title.	None	§ 115.766(b) § 115.766(b)(2) § 115.766(c)	None
CWT1D	EU	R5760-1	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.761(c)(1) § 115.761(c)(3) § 115.766(i)	HRVOC emissions at each site located in Harris County that is	§ 115.764(c) § 115.764(f)	§ 115.766(a)(1) § 115.766(a)(2) § 115.766(a)(3)	§ 115.766(i)(2)



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						subject to this division or Division 1 of this subchapter must not exceed 1,200 pounds of HRVOCs per one-hour block period from any flare, vent, pressure relief valve, cooling tower, or any combination.		§ 115.766(a)(5) § 115.766(a)(6) § 115.766(c) [G]§ 115.766(g) [G]§ 115.766(h) § 115.766(i)(1)	
CWT3C	EU	R5720-1	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.767(3) § 115.764(a)(1) § 115.766(i)	Any site for which no stream directed to a cooling tower heat exchange system contains 5.0% or greater by weight HRVOC is exempt from the requirements of § 115.761 of this title (relating to Site-wide Cap).	§ 115.764(a)(1) § 115.764(a)(3) § 115.764(c) § 115.764(d) [G]§ 115.764(g)(1)	§ 115.766(a)(4) § 115.766(c) § 115.766(d) § 115.766(i)(1)	§ 115.766(i)(2)
CWT9	EU	R5767	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.767(2)	Any cooling tower heat exchange system in which no individual heat exchanger has greater than 100 ppmw HRVOCs in the process side fluid is exempt from the requirements of this division, with the exception of the recordkeeping requirements of §115.766(b) and (c) of this title.	None	§ 115.766(b) § 115.766(b)(2) § 115.766(c)	None
OP2	EU	R5760-1	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.761(c)(1) § 115.761(c)(3) § 115.766(i)	HRVOC emissions at each site located in Harris County that is subject to this division or	§ 115.764(c) § 115.764(f)	§ 115.766(a)(1) § 115.766(a)(2) § 115.766(a)(3) § 115.766(a)(5)	§ 115.766(i)(2)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						Division 1 of this subchapter must not exceed 1,200 pounds of HRVOCs per one-hour block period from any flare, vent, pressure relief valve, cooling tower, or any combination.		§ 115.766(a)(6) § 115.766(c) [G]§ 115.766(g) [G]§ 115.766(h) § 115.766(i)(1)	
OP2	EU	63YY	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart YY
OP3CWT	EU	R5760-1	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.761(c)(1) § 115.761(c)(3) § 115.766(i)	HRVOC emissions at each site located in Harris County that is subject to this division or Division 1 of this subchapter must not exceed 1,200 pounds of HRVOCs per one-hour block period from any flare, vent, pressure relief valve, cooling tower, or any combination.	§ 115.764(c) § 115.764(f)	§ 115.766(a)(1) § 115.766(a)(2) § 115.766(a)(3) § 115.766(a)(5) § 115.766(a)(6) § 115.766(c) [G]§ 115.766(g) [G]§ 115.766(h) § 115.766(i)(1)	§ 115.766(i)(2)
OP3CWT	EU	63YY	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart YY

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ACNLOAD	EU	R5211-1	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.213(b) § 115.212(a)(2) § 115.212(a)(3)(B) § 115.212(a)(3)(D) § 115.212(a)(3)(E) § 115.213(b)(1) § 115.213(b)(4) [G]§ 115.213(b)(6) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(ii) § 60.18	General loading - 90% overall control option in the covered non-attainment counties. As an alternative operations may elect to achieve a 90% overall control of emissions at the account.	§ 115.212(a)(3)(B) § 115.213(b) § 115.213(b)(1) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) [G]§ 115.215(3) § 115.215(4) § 115.215(9)	§ 115.213(b)(1) § 115.216 § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B)	§ 115.213(b)(1) § 115.213(b)(2) § 115.213(b)(3) § 115.213(b)(4)
ACNLOAD	EU	R5211-2	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.213(b) § 115.212(a)(2) § 115.212(a)(3)(B) § 115.212(a)(3)(D) § 115.212(a)(3)(E) § 115.213(b)(1) § 115.213(b)(4) [G]§ 115.213(b)(6) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(ii) § 60.18	General loading - 90% overall control option in the covered non-attainment counties. As an alternative operations may elect to achieve a 90% overall control of emissions at the account.	§ 115.212(a)(3)(B) § 115.213(b) § 115.213(b)(1) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) [G]§ 115.215(3) § 115.215(4) § 115.215(9)	§ 115.213(b)(1) § 115.216 § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B)	§ 115.213(b)(1) § 115.213(b)(2) § 115.213(b)(3) § 115.213(b)(4)
ACNLOAD	EU	R5211-3	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.213(b) § 115.212(a)(2) § 115.212(a)(3)(B) § 115.212(a)(3)(D) § 115.212(a)(3)(E) § 115.213(b)(1) § 115.213(b)(4) [G]§ 115.213(b)(6) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(ii) § 60.18	General loading - 90% overall control option in the covered non-attainment counties. As an alternative operations may elect to achieve a 90% overall control of emissions at the account.	§ 115.212(a)(3)(B) § 115.213(b) § 115.213(b)(1) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) [G]§ 115.215(3) § 115.215(4) § 115.215(9)	§ 115.213(b)(1) § 115.216 § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B)	§ 115.213(b)(1) § 115.213(b)(2) § 115.213(b)(3) § 115.213(b)(4)
RCLOAD	EU	R5211-1	VOC	30 TAC Chapter	§ 115.217(a)(1)	Vapor pressure (at land-	§ 115.214(a)(1)(A)	§ 115.216	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Loading and Unloading of VOC	§ 115.212(a)(2) [G]§ 115.212(a)(7) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216(2) § 115.216(3)(B)	
RCLOAD	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.126(c)	For each Group 2 transfer rack, maintain records as required in § 63.130(f). No other provisions for transfer racks apply to the Group 2 transfer rack.	None	§ 63.130(f) § 63.130(f)(1) § 63.130(f)(2) § 63.130(f)(3) § 63.130(f)(3)(i) § 63.130(f)(3)(ii)	§ 63.152(c)(4)(iii)
SCRWRTC	EU	R5211-1	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(1) § 115.212(a)(1)(A) § 115.212(a)(3)(A) § 115.212(a)(3)(A)(ii) § 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) § 115.212(a)(3)(E) § 115.214(a)(1)(B) § 115.214(a)(1)(C)	At operations other than gasoline terminals, gasoline bulk plants, and marine terminals, vapors of VOC with a true vapor pressure of 0.5 psia or greater, must be controlled by one of the following methods.	§ 115.212(a)(3)(B) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.214(a)(1)(A)(ii) § 115.214(a)(1)(A)(iii) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(9)	§ 115.216 § 115.216(1) § 115.216(1)(C) § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B)	None
SCRWRTC	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.126(c)	For each Group 2 transfer rack, maintain records as required in § 63.130(f). No other provisions for transfer racks apply to the Group 2 transfer rack.	None	§ 63.130(f) § 63.130(f)(1) § 63.130(f)(2) § 63.130(f)(3) § 63.130(f)(3)(i) § 63.130(f)(3)(ii)	§ 63.152(c)(4)(iii)
SITE3TC	EU	R5211-1	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.213(b) § 115.212(a)(2) § 115.212(a)(3)(B) § 115.212(a)(3)(D) § 115.212(a)(3)(E)	General loading - 90% overall control option in the covered non-attainment counties. As an alternative operations	§ 115.212(a)(3)(B) § 115.213(b) § 115.213(b)(1) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i)	§ 115.213(b)(1) § 115.216 § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(i)	§ 115.213(b)(1) § 115.213(b)(2) § 115.213(b)(3) § 115.213(b)(4)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
					§ 115.213(b)(1) § 115.213(b)(4) [G]§ 115.213(b)(6) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(ii)	may elect to achieve a 90% overall control of emissions at the account.	§ 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(9)	§ 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B)	
SITE3TT	EU	R5211-1	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.213(b) § 115.212(a)(2) § 115.212(a)(3)(B) § 115.212(a)(3)(D) § 115.212(a)(3)(E) § 115.213(b)(1) § 115.213(b)(4) [G]§ 115.213(b)(6) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(ii)	General loading - 90% overall control option in the covered non-attainment counties. As an alternative operations may elect to achieve a 90% overall control of emissions at the account.	§ 115.212(a)(3)(B) § 115.213(b) § 115.213(b)(1) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(9)	§ 115.213(b)(1) § 115.216 § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B)	§ 115.213(b)(1) § 115.213(b)(2) § 115.213(b)(3) § 115.213(b)(4)
TTLOAD	EU	R5211-1	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.212(a)(2) [G]§ 115.212(a)(7) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None
TTLOAD	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.126(c)	For each Group 2 transfer rack, maintain records as required in § 63.130(f). No other provisions for transfer racks apply to the Group 2 transfer rack.	None	§ 63.130(f) § 63.130(f)(1) § 63.130(f)(2) § 63.130(f)(3) § 63.130(f)(3)(i) § 63.130(f)(3)(ii)	§ 63.152(c)(4)(iii)
WRTC	EU	R5211-1	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.212(a)(2) [G]§ 115.212(a)(7) § 115.214(a)(1)(B)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.			
WRTCECH	EU	R5211-1	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.212(a)(2) [G]§ 115.212(a)(7) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None
WRTCMEK	EU	R5211-1	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.213(b) § 115.212(a)(2) § 115.212(a)(3)(B) § 115.212(a)(3)(D) § 115.212(a)(3)(E) § 115.213(b)(1) § 115.213(b)(4) [G]§ 115.213(b)(6) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(ii)	General loading - 90% overall control option in the covered non-attainment counties. As an alternative operations may elect to achieve a 90% overall control of emissions at the account.	§ 115.212(a)(3)(B) § 115.213(b) § 115.213(b)(1) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(9)	§ 115.213(b)(1) § 115.216 § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B)	§ 115.213(b)(1) § 115.213(b)(2) § 115.213(b)(3) § 115.213(b)(4)
WRTT	EU	R5211-1	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.212(a)(2) [G]§ 115.212(a)(7) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None
WRTTECH	EU	R5211-1	VOC	30 TAC Chapter 115, Loading and	§ 115.217(a)(1) § 115.212(a)(2)	Vapor pressure (at land-based operations). All	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i)	§ 115.216 § 115.216(2)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Unloading of VOC	[G]§ 115.212(a)(7) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.215 § 115.215(4)	§ 115.216(3)(B)	
WRITMEK	EU	R5211-1	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.213(b) § 115.212(a)(2) § 115.212(a)(3)(B) § 115.212(a)(3)(D) § 115.212(a)(3)(E) § 115.213(b)(1) § 115.213(b)(4) [G]§ 115.213(b)(6) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(ii)	General loading - 90% overall control option in the covered non-attainment counties. As an alternative operations may elect to achieve a 90% overall control of emissions at the account.	§ 115.212(a)(3)(B) § 115.213(b) § 115.213(b)(1) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(9)	§ 115.213(b)(1) § 115.216 § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B)	§ 115.213(b)(1) § 115.213(b)(2) § 115.213(b)(3) § 115.213(b)(4)
F8300	EU	R7201-1	NOX	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NOx emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
						comply with § 117.320.			
F8300	EU	R7201-1	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g)	§ 117.345(a) § 117.345(f) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c)
F8300	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7506(b)(1)	The affected boilers and process heaters listed in paragraphs (b)(1) through (3) of this section are subject to only the initial notification requirements in §63.9(b) ( i.e. , they are not subject to the emission limits, work practice standards, performance testing, monitoring, SSMP, site-specific monitoring plans, recordkeeping and reporting requirements of this subpart or any other requirements in subpart A of this part).	None	None	None
F8301	EU	R7201-1	NOX	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NOx emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c)



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.340(p)(2)(C)		
F8301	EU	R7201-1	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O <sub>2</sub> , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g)	§ 117.345(a) § 117.345(f) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c)
F8301	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7506(c)(3)	Existing small gaseous fuel boilers and process heaters are not subject to the initial notification requirements in §63.9(b) and are not subject to any requirements in this subpart or in subpart A of this part.	None	None	None
FH3601	EU	R7ICI-01	NOX	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO <sub>x</sub> emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
						also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.			
FH3601	EU	R7ICI-01	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O <sub>2</sub> , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g)	§ 117.345(a) § 117.345(f) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c)
FH3601	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7506(b)(1)	The affected boilers and process heaters listed in paragraphs (b)(1) through (3) of this section are subject to only the initial notification requirements in §63.9(b) (i.e., they are not subject to the emission limits, work practice standards, performance testing, monitoring, SSMP, site-specific monitoring plans, recordkeeping and reporting requirements of this subpart or any other requirements in subpart A of this part).	None	None	None
FOL601	EU	R7ICI-01	NOX	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
					§ 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	comply with the NOx emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C)		
FOL601	EU	R7ICI-01	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O <sub>2</sub> , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g)	§ 117.345(a) § 117.345(f) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c)
FOL601	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7506(b)(1)	The affected boilers and process heaters listed in paragraphs (b)(1) through (3) of this section are subject to only the initial notification requirements in §63.9(b) (i.e., they are not subject to the emission limits, work practice standards, performance testing, monitoring, SSMP, site-specific monitoring plans, recordkeeping and reporting requirements of this subpart or any	None	None	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
						other requirements in subpart A of this part).			
FOL602	EU	R7ICI-01	NOX	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NOx emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c)
FOL602	EU	R7ICI-01	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O <sub>2</sub> , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g)	§ 117.345(a) § 117.345(f) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c)
FOL602	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7506(b)(1)	The affected boilers and process heaters listed in paragraphs (b)(1) through (3) of this section are subject to only the initial notification requirements in §63.9(b) (i.e. , they are not subject	None	None	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
						to the emission limits, work practice standards, performance testing, monitoring, SSMP, site-specific monitoring plans, recordkeeping and reporting requirements of this subpart or any other requirements in subpart A of this part).			
FOL603	EU	R7ICI-01	NOX	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NOx emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c)
FOL603	EU	R7ICI-01	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O <sub>2</sub> , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g)	§ 117.345(a) § 117.345(f) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
FOL603	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7506(b)(1)	The affected boilers and process heaters listed in paragraphs (b)(1) through (3) of this section are subject to only the initial notification requirements in §63.9(b) ( i.e. , they are not subject to the emission limits, work practice standards, performance testing, monitoring, SSMP, site-specific monitoring plans, recordkeeping and reporting requirements of this subpart or any other requirements in subpart A of this part).	None	None	None
FOL604	EU	R7ICI-01	NOX	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NOx emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FOL604	EU	R7ICI-01	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O <sub>2</sub> , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g)	§ 117.345(a) § 117.345(f) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c)
FOL604	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7506(b)(1)	The affected boilers and process heaters listed in paragraphs (b)(1) through (3) of this section are subject to only the initial notification requirements in §63.9(b) (i.e., they are not subject to the emission limits, work practice standards, performance testing, monitoring, SSMP, site-specific monitoring plans, recordkeeping and reporting requirements of this subpart or any other requirements in subpart A of this part).	None	None	None
FP31180	EU	R7ICI-1	NO <sub>x</sub>	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO <sub>x</sub> emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
						daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.340(o)(1) § 117.340(p)(1)		
FP31180	EU	R7ICI-1	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O <sub>2</sub> , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(e) [G]§ 117.340(f)(2)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5)
GRPFURN1	EU	R7ICI-1	NO <sub>x</sub>	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO <sub>x</sub> emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3)



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
GRPFURN1	EU	R7ICI-1	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(e) [G]§ 117.340(f)(2)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5)
GRPFURN2	EU	REG2-1	SO2	30 TAC Chapter 112, Sulfur Compounds	§ 112.9(c)	No person shall use liquid fuel with a sulfur content greater than 0.3% by weight, or allow emissions of SO2 to exceed 150 ppmv, based on 20% excess air, averaged over a 3-hour period.	§ 112.2(a) ** See Periodic Monitoring Summary	§ 112.2(c)	§ 112.2(b)
GRPFURN2	EU	R7ICI-1	NOx	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO <sub>x</sub> emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						specified in § 117.9800 to comply with § 117.320.			
GRPFURN2	EU	R7ICI-1	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(e) [G]§ 117.340(f)(2)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5)
GRPFURN3	EU	R7ICI-1	NO <sub>x</sub>	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO <sub>x</sub> emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3)
GRPFURN3	EU	R7ICI-1	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(2) § 117.345(f)(7)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(e) [G]§ 117.340(f)(2)	§ 117.345(f)(8) § 117.345(f)(9)	§ 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5)
GRPFURN4	EU	REG2-1	SO2	30 TAC Chapter 112, Sulfur Compounds	§ 112.9(c)	No person shall use liquid fuel with a sulfur content greater than 0.3% by weight, or allow emissions of SO2 to exceed 150 ppmv, based on 20% excess air, averaged over a 3-hour period.	§ 112.2(a) ** See Periodic Monitoring Summary	§ 112.2(c)	§ 112.2(b)
GRPFURN4	EU	R7ICI-1	NOx	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO <sub>x</sub> emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3)
GRPFURN4	EU	R7ICI-1	CO	30 TAC Chapter	§ 117.310(c)(1)	CO emissions must not	[G]§ 117.335(a)(1)	§ 117.345(a)	§ 117.335(b)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				117, Subchapter B	§ 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	exceed 400 ppmv at 3.0% O <sub>2</sub> , dry basis.	§ 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(e) [G]§ 117.340(f)(2)	§ 117.345(f) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9)	§ 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5)
GRPFURN5	EU	R7ICI-1	NO <sub>x</sub>	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO <sub>x</sub> emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3)
GRPFURN5	EU	R7ICI-1	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O <sub>2</sub> , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.340(e) [G]§ 117.340(f)(2)		§ 117.345(d)(5)
GRPFURN5	EU	R7ICI-1	NH <sub>3</sub>	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(2) § 117.310(c)(2)(A)	For process heaters that inject urea or ammonia into the exhaust stream for NO <sub>x</sub> control, ammonia emissions must not exceed 10 ppmv at 3.0% O <sub>2</sub> , dry.	§ 117.335(a)(2) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(11) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c)
H1300	EU	R7ICI-1	NO <sub>x</sub>	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO <sub>x</sub> emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c)
H1300	EU	R7ICI-1	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O <sub>2</sub> , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g)	§ 117.345(a) § 117.345(f) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
H1300	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
H902	EU	R7ICI-1	NO <sub>x</sub>	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO <sub>x</sub> emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3)
H902	EU	R7ICI-1	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O <sub>2</sub> , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
							§ 117.340(e) [G]§ 117.340(f)(2)		§ 117.345(d)(5)
H902	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
OP2ACMAP	EP	60RRR-1	VOC/TOC	40 CFR Part 60, Subpart RRR	§ 60.702(a) [G]§ 60.704(b)(5)	For each vent stream, reduce TOC by 98%w or to a TOC concentration of 20 ppmv, on a dry basis corrected to 3% oxygen, whichever is less stringent. If a boiler or process heater is used, introduce vent stream as specified.	§ 60.703(c) § 60.703(c)(1) § 60.703(c)(1)(i) § 60.704(a) § 60.704(b) § 60.704(b)(1) § 60.704(b)(2) § 60.704(b)(3) [G]§ 60.704(b)(4)	§ 60.703(c)(1) § 60.705(b) § 60.705(b)(2)(i) § 60.705(c) § 60.705(c)(4) § 60.705(d)(1) § 60.705(s)	§ 60.705(a) § 60.705(b) § 60.705(b)(2)(i) § 60.705(c) § 60.705(c)(4) § 60.705(k) § 60.705(l) § 60.705(l)(1) § 60.705(l)(2) § 60.705(s)
P87921	EU	R7ICI-1	EXEMPT	30 TAC Chapter 117, Subchapter B	§ 117.303(a)(6)(D) [G]§ 117.310(f)	Units exempted from the provisions of this division, except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1), and 117.354(a)(5), include stationary gas turbines and stationary internal combustion engines that are used exclusively in emergency situations, except that operation for testing or maintenance purposes is allowed for up to 52	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						hours per year, based on a rolling 12-month average.			
A327	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
A327	EU	60K-1	VOC	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a true vapor pressure of 78 mm Hg (1.5 psia) or greater but not greater than 570 mm Hg (11.1 psia) shall have a floating roof, a vapor recovery system, or their equivalents.	§ 60.113(a) § 60.113(b) ** See Periodic Monitoring Summary	§ 60.113(a)	None
A327	EU	60K-2	VOC	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a true vapor pressure of 78 mm Hg (1.5 psia) or greater but not greater than 570 mm Hg (11.1 psia) shall have a floating roof, a vapor recovery system, or their equivalents.	§ 60.113(a) § 60.113(b) ** See Periodic Monitoring Summary	§ 60.113(a)	None
A328	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation,	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115,	The permit holder shall comply with the applicable monitoring and testing requirements	The permit holder shall comply with the applicable recordkeeping	The permit holder shall comply with the applicable reporting requirements of 30 TAC



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	Storage of VOCs	of 30 TAC Chapter 115, Storage of VOCs	requirements of 30 TAC Chapter 115, Storage of VOCs	Chapter 115, Storage of VOCs
A328	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
A328	EU	60K-1	VOC	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a true vapor pressure of 78 mm Hg (1.5 psia) or greater but not greater than 570 mm Hg (11.1 psia) shall have a floating roof, a vapor recovery system, or their equivalents.	§ 60.113(a) § 60.113(b) ** See Periodic Monitoring Summary	§ 60.113(a)	None
A328	EU	60K-2	VOC	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a true vapor pressure of 78 mm Hg (1.5 psia) or greater but not greater than 570 mm Hg (11.1 psia) shall have a floating roof, a vapor recovery system, or their equivalents.	§ 60.113(a) § 60.113(b) ** See Periodic Monitoring Summary	§ 60.113(a)	None
AP18	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of	§ 115.112 The permit holder shall	The permit holder shall comply with the	The permit holder shall comply with the	The permit holder shall comply with the	The permit holder shall comply with the

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				VOCs	comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	applicable requirements of 30 TAC Chapter 115, Storage of VOCs	applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
AP18	EU	63FFFF-1	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2470(a)-Table 4.1.b.i § 63.1062(a)(1) § 63.1063(a)(1)(i) [G]§ 63.1063(a)(2) [G]§ 63.1063(b) § 63.1063(e)(1) § 63.1063(e)(2) § 63.2470(a)	For each Group 1 storage tank for which the maximum true vapor pressure of total HAP at the storage temperature is < 76.6 kilopascals, you must comply with the requirements of Subpart WW of this part, except as specified in § 63.2470.	§ 63.1063(c)(1) [G]§ 63.1063(c)(1)(i) § 63.1063(d) [G]§ 63.1063(d)(1) § 63.1063(d)(2) § 63.1066(b)(1)	§ 63.1063(e)(2) § 63.1065 § 63.1065(a) [G]§ 63.1065(b)(1) § 63.1065(c) § 63.1065(d) § 63.1066(b)(2)	§ 63.1066(b) § 63.1066(b)(1) § 63.1066(b)(2) § 63.1066(b)(4) § 63.2450(q)
AP19	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
AP19	EU	63YY	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart YY
AP3	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of	§ 115.112 The permit holder shall	The permit holder shall comply with the	The permit holder shall comply with the	The permit holder shall comply with the	The permit holder shall comply with the

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				VOCs	comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	applicable requirements of 30 TAC Chapter 115, Storage of VOCs	applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D303	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D303	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
D306	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D306	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						methods in §63.123(a). Not required to comply with §63.119 to §63.123.			
D307	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D307	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
D308	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D308	EU	63G-01	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

## Applicable Requirements Summary

<b>Unit Group Process ID No.</b>	<b>Unit Group Process Type</b>	<b>SOP Index No.</b>	<b>Pollutant</b>	<b>State Rule or Federal Regulation Name</b>	<b>Emission Limitation, Standard or Equipment Specification Citation</b>	<b>Textual Description (See Special Term and Condition 1.B.)</b>	<b>Monitoring And Testing Requirements</b>	<b>Recordkeeping Requirements (30 TAC § 122.144)</b>	<b>Reporting Requirements (30 TAC § 122.145)</b>
D313	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D334	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D341	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D342	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
D342	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
D342	EU	63G-2	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
D350	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D350	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)				§ 63.152(c)(2) § 63.152(c)(4)(ii)
D351	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D351	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
D352	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					VOCs				
D352	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
D353	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D353	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a)



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)				§ 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
D364	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D365	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D366	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D367	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of	§ 115.112 The permit holder shall	The permit holder shall comply with the	The permit holder shall comply with the	The permit holder shall comply with the	The permit holder shall comply with the

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				VOCs	comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	applicable requirements of 30 TAC Chapter 115, Storage of VOCs	applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D369	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D370	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D370	EU	60K-1	VOC	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a true vapor pressure of 78 mm Hg (1.5 psia) or greater but not greater than 570 mm Hg (11.1 psia) shall have a floating roof, a vapor recovery system, or their equivalents.	§ 60.113(a) § 60.113(b) ** See Periodic Monitoring Summary	§ 60.113(a)	None
D370	EU	63G-1	112(B)	40 CFR Part 63,	§ 63.119(b)	Tanks using a fixed roof	§ 63.120(a)(2)(i)	§ 63.120(a)(4)	§ 63.120(a)(5)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
			HAPS	Subpart G	§ 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)	and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(2)(ii)	§ 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
D371	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D371	EU	60K-1	VOC	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a true vapor pressure of 78 mm Hg (1.5 psia) or greater but not greater than 570 mm Hg (11.1 psia) shall have a floating roof, a vapor recovery system, or their equivalents.	§ 60.113(a) § 60.113(b) ** See Periodic Monitoring Summary	§ 60.113(a)	None
D371	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1)	Tanks using a fixed roof and an internal floating	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a)	§ 63.120(a)(5) § 63.120(a)(6)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)	roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).		§ 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
D377	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D377	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)				§ 63.152(c)(2) § 63.152(c)(4)(ii)
D379	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D379	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(i) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
D379	EU	63G-2	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
					§ 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)				[G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
D380	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D380	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
D381	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of	§ 115.112 The permit holder shall	The permit holder shall comply with the	The permit holder shall comply with the	The permit holder shall comply with the	The permit holder shall comply with the

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				VOCs	comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	applicable requirements of 30 TAC Chapter 115, Storage of VOCs	applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D381	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
D393	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D393	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.119(b)(3)(ii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)	§63.119(a)(1) must comply with: §63.119(b)(1)-(6).		[G]§ 63.152(a)	§ 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
D394	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D394	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
D395	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					VOCs				
D395	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
D398	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D398	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
D399	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D399	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.			
D400	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D400	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
D401	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D401	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						with §63.119 to §63.123.			
D402	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D402	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
D403	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D403	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
D8100	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of	§ 115.112 The permit holder shall	The permit holder shall comply with the	The permit holder shall comply with the	The permit holder shall comply with the	The permit holder shall comply with the

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				VOCs	comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	applicable requirements of 30 TAC Chapter 115, Storage of VOCs	applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
D8100	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
DIESEL TANK	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
EX63	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation,	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115,	The permit holder shall comply with the applicable monitoring and testing requirements	The permit holder shall comply with the applicable recordkeeping	The permit holder shall comply with the applicable reporting requirements of 30 TAC

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	Storage of VOCs	of 30 TAC Chapter 115, Storage of VOCs	requirements of 30 TAC Chapter 115, Storage of VOCs	Chapter 115, Storage of VOCs
EX63	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
EX64	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
EX64	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
EX65	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					VOCs				
EX65	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
EX66	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
EX66	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
EX67	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
EX68	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of	§ 115.112 The permit holder shall	The permit holder shall comply with the	The permit holder shall comply with the	The permit holder shall comply with the	The permit holder shall comply with the

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				VOCs	comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	applicable requirements of 30 TAC Chapter 115, Storage of VOCs	applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
EX68	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
EX69	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
EX69	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
EX70	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115,	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					requirements of 30 TAC Chapter 115, Storage of VOCs			Storage of VOCs	
EX70	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
EX76	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
EX76	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
EX77	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
EX77	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
EX80	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
EX80	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
F310	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
F310	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						methods in §63.123(a). Not required to comply with §63.119 to §63.123.			
F336	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
F337	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
F347	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
F347	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						with §63.119 to §63.123.			
F349	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
F349	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
F350	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
F350	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
F351	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of	§ 115.112 The permit holder shall	The permit holder shall comply with the	The permit holder shall comply with the	The permit holder shall comply with the	The permit holder shall comply with the

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				VOCs	comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	applicable requirements of 30 TAC Chapter 115, Storage of VOCs	applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
F355	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
F356	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
F357	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
F357	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.			
F358	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
F358	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
F359	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
F359	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with:	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
					§ 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)	§63.119(b)(1)-(6).			§ 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
F360	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
F360	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
F361	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
F361	EU	60K-1	VOC	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a true vapor pressure of 78 mm Hg (1.5 psia) or greater but not greater than 570 mm Hg (11.1 psia) shall have a floating roof, a vapor recovery system, or their equivalents.	§ 60.113(a) § 60.113(b) ** See Periodic Monitoring Summary	§ 60.113(a)	None
F361	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
G330	EU	R5112-4	VOC	30 TAC Chapter	§ 115.112	The permit holder shall	The permit holder shall	The permit holder shall	The permit holder shall

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Storage of VOCs	The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
G330	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
G331	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
G331	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
G343	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115,	The permit holder shall comply with the applicable recordkeeping requirements of 30	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs		Storage of VOCs	TAC Chapter 115, Storage of VOCs	VOCs
G343	EU	60K-1	VOC	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a true vapor pressure of 78 mm Hg (1.5 psia) or greater but not greater than 570 mm Hg (11.1 psia) shall have a floating roof, a vapor recovery system, or their equivalents.	§ 60.113(a) § 60.113(b) ** See Periodic Monitoring Summary	§ 60.113(a)	None
G343	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
G344	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
G344	EU	60K-1	VOC	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a true vapor pressure of 78 mm Hg (1.5 psia) or greater but not greater than 570 mm Hg (11.1	§ 60.113(a) § 60.113(b) ** See Periodic Monitoring Summary	§ 60.113(a)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
						psia) shall have a floating roof, a vapor recovery system, or their equivalents.			
G344	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
G353	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
G353	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPVESHO	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	** See CAM Summary	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRPVESHO	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	** See CAM Summary	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRPVESHO	EU	R5112-3	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	** See CAM Summary	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
J313	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
J313	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
J314	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
J314	EU	63FFFF-1	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2470(a)-Table 4.1.b.i § 63.1062(a)(1) § 63.1063(a)(1)(i) [G]§ 63.1063(a)(2) [G]§ 63.1063(b) § 63.1063(e)(1) § 63.1063(e)(2) § 63.2470(a)	For each Group 1 storage tank for which the maximum true vapor pressure of total HAP at the storage temperature is < 76.6 kilopascals, you must comply with the requirements of Subpart WW of this part, except as specified in §63.2470.	§ 63.1063(c)(1) § 63.1063(c)(1)(ii) § 63.1063(d) [G]§ 63.1063(d)(1) § 63.1063(d)(2) § 63.1066(b)(1)	§ 63.1063(e)(2) § 63.1065 § 63.1065(a) [G]§ 63.1065(b)(1) § 63.1065(c) § 63.1065(d) § 63.1066(b)(2)	§ 63.1066(b) § 63.1066(b)(1) § 63.1066(b)(2) § 63.1066(b)(4) § 63.2450(q)
J320	EU	R5112-1	VOC	30 TAC Chapter	§ 115.112	The permit holder shall	The permit holder shall	The permit holder shall	The permit holder shall

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Storage of VOCs	The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
K306	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
K307	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
L306	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
L306	EU	63G-1	112(B)	40 CFR Part 63,	§ 63.119(a)(3)	Group 2 tanks not using	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
			HAPS	Subpart G		emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.			
L308	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
L308	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
L332	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
L332	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a).	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						Not required to comply with §63.119 to §63.123.			
L333	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
L333	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(e)(4)(iii)
L334	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
L335	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
L336	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
S332	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
S332	EU	61FF-1	BENZENE	40 CFR Part 61, Subpart FF	§ 61.351(a) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 61.351(a)(1) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5)	§ 60.115b § 60.115b(a)(2) § 61.356(k)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 61.357(e) § 61.357(f)
S390	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					requirements of 30 TAC Chapter 115, Storage of VOCs			Storage of VOCs	
S391	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
S392	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
S400	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
T1302	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115,	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					requirements of 30 TAC Chapter 115, Storage of VOCs			Storage of VOCs	
T1310	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
T13146	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
T1318	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
T1318	EU	60Kb-1	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs	§ 60.116b(a) § 60.116b(b) § 60.116b(d) § 60.116b(f)(2)	§ 60.116b(a) § 60.116b(b)	§ 60.116b(d)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
						for which construction/reconstruction/modification began after 7/23/84.			
T1319	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
T1331	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
T1332	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
T1333	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115,	The permit holder shall comply with the applicable recordkeeping requirements of 30	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
					equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs		Storage of VOCs	TAC Chapter 115, Storage of VOCs	VOCs
T1334	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
T182	EU	60Kb-1	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction/modification began after 7/23/84.	§ 60.116b(a) § 60.116b(b) § 60.116b(d) § 60.116b(f)(2)	§ 60.116b(a) § 60.116b(b)	§ 60.116b(d)
T2800	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
T317	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation,	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115,	The permit holder shall comply with the applicable monitoring and testing requirements	The permit holder shall comply with the applicable recordkeeping	The permit holder shall comply with the applicable reporting requirements of 30 TAC

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	Storage of VOCs	of 30 TAC Chapter 115, Storage of VOCs	requirements of 30 TAC Chapter 115, Storage of VOCs	Chapter 115, Storage of VOCs
T331	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
T658	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
T74B	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
T74B	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with	§ 63.120(a)(3)(i) § 63.120(a)(3)(ii) § 63.120(a)(3)(iii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.119(b)(3)(iii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)	§63.119(a)(1) must comply with: §63.119(b)(1)-(6).		[G]§ 63.152(a)	§ 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
T87000	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
T87000	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T87001	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
					VOCs				
T87003	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
T87004	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
T87005	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
T87005	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(e) § 63.119(a)(1) § 63.119(e)(1) § 63.119(e)(3) § 63.119(e)(4) § 63.119(e)(5) § 63.172(a) [G]§ 63.172(h)	The owner or operator who elects to use a closed vent system and control device (defined in § 63.111) to comply with §63.119(a)(1) or (a)(2) shall comply with §63.119(e)(1)-(5).	§ 63.120(d)(1) § 63.120(d)(5) [G]§ 63.172(f)(1) [G]§ 63.172(f)(2) § 63.172(g) [G]§ 63.172(h) [G]§ 63.172(k) [G]§ 63.172(l)	§ 63.120(d)(1)(i) § 63.120(d)(1)(i)(A) § 63.120(d)(1)(i)(C) § 63.123(a) § 63.123(f)(1) [G]§ 63.123(f)(2) [G]§ 63.152(a) [G]§ 63.172(k)	§ 63.120(d)(1) § 63.120(d)(2) § 63.120(d)(2)(i) § 63.120(d)(2)(ii) § 63.120(d)(3) § 63.120(d)(3)(i) § 63.120(d)(4) § 63.122(b)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.172(i) § 63.172(m)		[G]§ 63.180(b) [G]§ 63.180(d)	[G]§ 63.172(l) § 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) [G]§ 63.181(g)(2) [G]§ 63.181(g)(3)	§ 63.122(c)(1) [G]§ 63.122(g)(1) [G]§ 63.122(g)(2) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6) [G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
T87007	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
T87007	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(e) § 63.119(a)(1) § 63.119(e)(1) § 63.119(e)(3)	The owner or operator who elects to use a closed vent system and control device (defined in §	§ 63.120(d)(1) § 63.120(d)(5) [G]§ 63.172(f)(1) [G]§ 63.172(f)(2)	§ 63.120(d)(1)(i) § 63.120(d)(1)(i)(A) § 63.120(d)(1)(i)(C) § 63.123(a)	§ 63.120(d)(1) § 63.120(d)(2) § 63.120(d)(2)(i) § 63.120(d)(2)(ii)



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
					§ 63.119(e)(4) § 63.119(e)(5) § 63.172(a) [G]§ 63.172(h) § 63.172(i) § 63.172(m)	63.111) to comply with §63.119(a)(1) or (a)(2) shall comply with §63.119(e)(1)-(5).	§ 63.172(g) [G]§ 63.172(h) [G]§ 63.172(k) [G]§ 63.172(l) [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.123(f)(1) [G]§ 63.123(f)(2) [G]§ 63.152(a) [G]§ 63.172(k) [G]§ 63.172(l) § 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) [G]§ 63.181(g)(2) [G]§ 63.181(g)(3)	§ 63.120(d)(3) § 63.120(d)(3)(i) § 63.120(d)(4) § 63.122(b) § 63.122(c)(1) [G]§ 63.122(g)(1) [G]§ 63.122(g)(2) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6) [G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
T87100	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
T87100	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(e) § 63.119(a)(1) § 63.119(e)(1) § 63.119(e)(3) § 63.119(e)(4) § 63.119(e)(5) § 63.172(a) [G]§ 63.172(h) § 63.172(i) § 63.172(m)	The owner or operator who elects to use a closed vent system and control device (defined in § 63.111) to comply with §63.119(a)(1) or (a)(2) shall comply with §63.119(e)(1)-(5).	§ 63.120(d)(1) § 63.120(d)(5) [G]§ 63.172(f)(1) [G]§ 63.172(f)(2) § 63.172(g) [G]§ 63.172(h) [G]§ 63.172(k) [G]§ 63.172(l) [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.120(d)(1)(i) § 63.120(d)(1)(i)(A) § 63.120(d)(1)(i)(C) § 63.123(a) § 63.123(f)(1) [G]§ 63.123(f)(2) [G]§ 63.152(a) [G]§ 63.172(k) [G]§ 63.172(l) [G]§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) [G]§ 63.181(g)(2) [G]§ 63.181(g)(3)	§ 63.120(d)(1) § 63.120(d)(2) § 63.120(d)(2)(i) § 63.120(d)(2)(ii) § 63.120(d)(3) § 63.120(d)(3)(i) § 63.120(d)(4) § 63.122(b) § 63.122(c)(1) [G]§ 63.122(g)(1) [G]§ 63.122(g)(2) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6) [G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
T87300	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115,	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					requirements of 30 TAC Chapter 115, Storage of VOCs			Storage of VOCs	
T87300	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T87400	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
T87400	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T87401	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T87401	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T87500	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
T87500	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(e) § 63.119(a)(1) § 63.119(e)(1) § 63.119(e)(3) § 63.119(e)(4) § 63.119(e)(5) § 63.172(a) [G]§ 63.172(h) § 63.172(i) § 63.172(m)	The owner or operator who elects to use a closed vent system and control device (defined in § 63.111) to comply with §63.119(a)(1) or (a)(2) shall comply with §63.119(e)(1)-(5).	§ 63.120(d)(1) § 63.120(d)(5) [G]§ 63.172(f)(1) [G]§ 63.172(f)(2) § 63.172(g) [G]§ 63.172(h) [G]§ 63.172(k) [G]§ 63.172(l) [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.120(d)(1)(i) § 63.120(d)(1)(i)(A) § 63.120(d)(1)(i)(C) § 63.123(a) § 63.123(f)(1) [G]§ 63.123(f)(2) [G]§ 63.152(a) [G]§ 63.172(k) [G]§ 63.172(l) § 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) [G]§ 63.181(g)(2) [G]§ 63.181(g)(3)	§ 63.120(d)(1) § 63.120(d)(2) § 63.120(d)(2)(i) § 63.120(d)(2)(ii) § 63.120(d)(3) § 63.120(d)(3)(i) § 63.120(d)(4) § 63.122(b) § 63.122(c)(1) [G]§ 63.122(g)(1) [G]§ 63.122(g)(2) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
									§ 63.152(c)(2)(iii) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6) [G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
TB3-301-R1	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TB3-301-R1	EU	63G-2	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
TBD301	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TBD301	EU	63FFFF-1	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2470(a)-Table4.1.b.i § 63.1062(a)(1) § 63.1063(a)(1)(i) [G]§ 63.1063(a)(2) [G]§ 63.1063(b) § 63.1063(e)(1) § 63.1063(e)(2) § 63.2470(a)	For each Group 1 storage tank for which the maximum true vapor pressure of total HAP at the storage temperature is < 76.6 kilopascals, you must comply with the requirements of Subpart WW of this part, except as specified in §63.2470.	§ 63.1063(c)(1) § 63.1063(c)(1)(ii) § 63.1063(d) [G]§ 63.1063(d)(1) § 63.1063(d)(2) § 63.1066(b)(1)	§ 63.1063(e)(2) § 63.1065 § 63.1065(a) [G]§ 63.1065(b)(1) § 63.1065(c) § 63.1065(d) § 63.1066(b)(2)	§ 63.1066(b) § 63.1066(b)(1) § 63.1066(b)(2) § 63.1066(b)(4) § 63.2450(q)
TBD910	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TBD910	EU	63FFFF-1	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2470(a)-Table4.1.b.i § 63.1062(a)(1) § 63.1063(a)(1)(i) [G]§ 63.1063(a)(2) [G]§ 63.1063(b) § 63.1063(e)(1) § 63.1063(e)(2) § 63.2470(a)	For each Group 1 storage tank for which the maximum true vapor pressure of total HAP at the storage temperature is < 76.6 kilopascals, you must comply with the requirements of Subpart WW of this part, except	§ 63.1063(c)(1) § 63.1063(c)(1)(ii) § 63.1063(d) [G]§ 63.1063(d)(1) § 63.1063(d)(2) § 63.1066(b)(1)	§ 63.1063(e)(2) § 63.1065 § 63.1065(a) [G]§ 63.1065(b)(1) § 63.1065(c) § 63.1065(d) § 63.1066(b)(2)	§ 63.1066(b) § 63.1066(b)(1) § 63.1066(b)(2) § 63.1066(b)(4) § 63.2450(q)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						as specified in §63.2470.			
TBD911	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TBD911	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
TBD912	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(iii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(3)(i) § 63.120(a)(3)(ii) § 63.120(a)(3)(iii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
					§ 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)				§ 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
TBD912	EU	63G-2	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
TBD913	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TBD913	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii)



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.119(b)(3)(ii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)	§63.119(a)(1) must comply with: §63.119(b)(1)-(6).		[G]§ 63.152(a)	§ 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
TC33001	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TC33002	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TF34001	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115,	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					requirements of 30 TAC Chapter 115, Storage of VOCs			Storage of VOCs	
TOL301	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TOL302	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TOL303	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TOL304	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
					requirements of 30 TAC Chapter 115, Storage of VOCs			Storage of VOCs	
TOL305	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TOL3070	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TOL400	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TOL401	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115,	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					requirements of 30 TAC Chapter 115, Storage of VOCs			Storage of VOCs	
TOL901	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TOL901	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TOL901	EU	63YY	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart YY
TOL902	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
					Chapter 115, Storage of VOCs				
TOL902	EU	63YY	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart YY
TOL903	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TOL903	EU	63YY	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart YY
TOL904	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
TOL904	EU	61FF-1	BENZENE	40 CFR Part 61, Subpart FF	§ 61.351(a) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 61.351(a)(1) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5)	§ 60.115b § 60.115b(a)(2) § 61.356(k)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 61.357(e) § 61.357(f)
TOL904	EU	63YY	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart YY
TOL905	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TOL905	EU	63FFFF-1	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2470(a)-Table 4.1.b.i § 63.1062(a)(2) § 63.1063(a)(1)(ii)(B) [G]§ 63.1063(a)(2) [G]§ 63.1063(b) § 63.1063(c)(2)(iv)(B)	For each Group 1 storage tank for which the maximum true vapor pressure of total HAP at the storage temperature is < 76.6 kilopascals, you must comply with the	§ 63.1063(c)(2)(i) § 63.1063(c)(2)(ii) § 63.1063(c)(2)(iii) § 63.1063(c)(2)(iv) § 63.1063(c)(2)(iv)(A) § 63.1063(d) [G]§ 63.1063(d)(1)	§ 63.1063(c)(2)(iv)(B) § 63.1063(e)(2) § 63.1065 § 63.1065(a) [G]§ 63.1065(b)(1) § 63.1065(b)(2) § 63.1065(c)	§ 63.1066(b) § 63.1066(b)(1) § 63.1066(b)(2) § 63.1066(b)(4) § 63.2450(q)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.1063(e)(1) § 63.1063(e)(2) § 63.2470(a)	requirements of Subpart WW of this part, except as specified in §63.2470.	[G]§ 63.1063(d)(3) § 63.1066(b)(1)	§ 63.1065(d) § 63.1066(b)(2)	
TOL908	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TOL909	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TOL910	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TOL911	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115,	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					requirements of 30 TAC Chapter 115, Storage of VOCs			Storage of VOCs	
TOL911	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TOL911	EU	60K-1	VOC	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a true vapor pressure of 78 mm Hg (1.5 psia) or greater but not greater than 570 mm Hg (11.1 psia) shall have a floating roof, a vapor recovery system, or their equivalents.	§ 60.113(a) § 60.113(b) ** See Periodic Monitoring Summary	§ 60.113(a)	None
TOL911	EU	60K-2	VOC	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a true vapor pressure of 78 mm Hg (1.5 psia) or greater but not greater than 570 mm Hg (11.1 psia) shall have a floating roof, a vapor recovery system, or their equivalents.	§ 60.113(a) § 60.113(b) ** See Periodic Monitoring Summary	§ 60.113(a)	None
TOL911	EU	63YY	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103 The permit holder shall comply with the applicable limitation,	The permit holder shall comply with the applicable requirements of 40 CFR Part 63,	The permit holder shall comply with the applicable monitoring and testing requirements	The permit holder shall comply with the applicable recordkeeping	The permit holder shall comply with the applicable reporting requirements of 40 CFR



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					standard and/or equipment specification requirements of 40 CFR Part 63, Subpart YY	Subpart YY	of 40 CFR Part 63, Subpart YY	requirements of 40 CFR Part 63, Subpart YY	Part 63, Subpart YY
TOL912	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TOL912	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TOL912	EU	63YY	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart YY
TOL913	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115,	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					requirements of 30 TAC Chapter 115, Storage of VOCs			Storage of VOCs	
TOL913	EU	63FFFF-1	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2470(a)-Table 4.1.b.i § 63.1062(a)(1) § 63.1063(a)(1)(i) [G]§ 63.1063(a)(2) [G]§ 63.1063(b) § 63.1063(e)(1) § 63.1063(e)(2) § 63.2470(a)	For each Group 1 storage tank for which the maximum true vapor pressure of total HAP at the storage temperature is < 76.6 kilopascals, you must comply with the requirements of Subpart WW of this part, except as specified in § 63.2470.	§ 63.1063(c)(1) [G]§ 63.1063(c)(1)(i) § 63.1063(d) [G]§ 63.1063(d)(1) § 63.1063(d)(2) § 63.1066(b)(1)	§ 63.1063(e)(2) § 63.1065 § 63.1065(a) [G]§ 63.1065(b)(1) § 63.1065(c) § 63.1065(d) § 63.1066(b)(2)	§ 63.1066(b) § 63.1066(b)(1) § 63.1066(b)(2) § 63.1066(b)(4) § 63.2450(q)
TOL914	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TOL920	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TOL920	EU	60Ka-1	VOC	40 CFR Part 60, Subpart Ka	§ 60.110a(a)	The affected facility is each storage vessel for petroleum liquids that has a storage capacity > 151,416 L (40,000 gal)	§ 60.115a(a) § 60.115a(b)	§ 60.115a(a)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
						and for which construction commenced after 5/18/78 and prior to 7/23/84.			
TOL920	EU	63YY	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart YY
TR35020	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TU30911	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TU30913	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115,	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					requirements of 30 TAC Chapter 115, Storage of VOCs			Storage of VOCs	
TUT604	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TUT918	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
VBD933	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	** See CAM Summary	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
VBD933	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	** See CAM Summary	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115,	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					requirements of 30 TAC Chapter 115, Storage of VOCs			Storage of VOCs	
VBD933	EU	R5112-3	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	** See CAM Summary	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
VBD933	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(e) § 63.11 § 63.119(a)(2) § 63.119(e)(1) § 63.119(e)(3) § 63.119(e)(4) § 63.119(e)(5) § 63.172(a) [G]§ 63.172(h) § 63.172(i) § 63.172(m)	The owner or operator who elects to use a closed vent system and control device (defined in § 63.111) to comply with §63.119(a)(1) or (a)(2) shall comply with §63.119(e)(1)-(5).	§ 63.120(e)(1) § 63.120(e)(4) [G]§ 63.172(f)(1) [G]§ 63.172(f)(2) § 63.172(g) [G]§ 63.172(h) [G]§ 63.172(k) [G]§ 63.172(l) [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.123(a) [G]§ 63.123(f)(2) [G]§ 63.152(a) [G]§ 63.172(k) [G]§ 63.172(l) § 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) [G]§ 63.181(g)(2) [G]§ 63.181(g)(3)	[G]§ 63.120(e)(2) § 63.122(c)(2) [G]§ 63.122(g)(1) [G]§ 63.122(g)(3) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6) [G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
VBD933	EU	63G-2	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(e) § 63.11 § 63.119(a)(2) § 63.119(e)(1) § 63.119(e)(3) § 63.119(e)(4) § 63.119(e)(5) § 63.172(a) [G]§ 63.172(h) § 63.172(i) § 63.172(m)	The owner or operator who elects to use a closed vent system and control device (defined in § 63.111) to comply with §63.119(a)(1) or (a)(2) shall comply with §63.119(e)(1)-(5).	§ 63.120(e)(1) § 63.120(e)(4) [G]§ 63.172(f)(1) [G]§ 63.172(f)(2) § 63.172(g) [G]§ 63.172(h) [G]§ 63.172(k) [G]§ 63.172(l) [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.123(a) [G]§ 63.123(f)(2) [G]§ 63.152(a) [G]§ 63.172(k) [G]§ 63.172(l) § 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) [G]§ 63.181(g)(2) [G]§ 63.181(g)(3)	[G]§ 63.120(e)(2) § 63.122(c)(2) [G]§ 63.122(g)(1) [G]§ 63.122(g)(3) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6) [G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
VBD933	EU	63G-3	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(e) § 63.11 § 63.119(a)(2) § 63.119(e)(1) § 63.119(e)(3) § 63.119(e)(4) § 63.119(e)(5) § 63.172(a) [G]§ 63.172(h) § 63.172(i) § 63.172(m)	The owner or operator who elects to use a closed vent system and control device (defined in § 63.111) to comply with §63.119(a)(1) or (a)(2) shall comply with §63.119(e)(1)-(5).	§ 63.120(e)(1) § 63.120(e)(4) [G]§ 63.172(f)(1) [G]§ 63.172(f)(2) § 63.172(g) [G]§ 63.172(h) [G]§ 63.172(k) [G]§ 63.172(l) [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.123(a) [G]§ 63.123(f)(2) [G]§ 63.152(a) [G]§ 63.172(k) [G]§ 63.172(l) § 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) [G]§ 63.181(g)(2)	[G]§ 63.120(e)(2) § 63.122(c)(2) [G]§ 63.122(g)(1) [G]§ 63.122(g)(3) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
								[G]§ 63.181(g)(3)	§ 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6) [G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
VBD990	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	** See Periodic Monitoring Summary	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
VBD990	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(e) § 63.11 § 63.119(a)(2) § 63.119(e)(1) § 63.119(e)(3) § 63.119(e)(4) § 63.119(e)(5) § 63.172(a) [G]§ 63.172(h) § 63.172(i) § 63.172(m)	The owner or operator who elects to use a closed vent system and control device (defined in § 63.111) to comply with §63.119(a)(1) or (a)(2) shall comply with §63.119(e)(1)-(5).	§ 63.120(e)(1) § 63.120(e)(4) [G]§ 63.172(f)(1) [G]§ 63.172(f)(2) § 63.172(g) [G]§ 63.172(h) [G]§ 63.172(k) [G]§ 63.172(l) [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.123(a) [G]§ 63.123(f)(2) [G]§ 63.152(a) [G]§ 63.172(k) [G]§ 63.172(l) § 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) [G]§ 63.181(g)(2) [G]§ 63.181(g)(3)	[G]§ 63.120(e)(2) § 63.122(c)(2) [G]§ 63.122(g)(1) [G]§ 63.122(g)(3) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
									§ 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6) [G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
VBD993	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	** See Periodic Monitoring Summary	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
VBD993	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(e) § 63.11 § 63.119(a)(2) § 63.119(e)(1) § 63.119(e)(3) § 63.119(e)(4) § 63.119(e)(5) § 63.172(a) [G]§ 63.172(h) § 63.172(i) § 63.172(m)	The owner or operator who elects to use a closed vent system and control device (defined in § 63.111) to comply with §63.119(a)(1) or (a)(2) shall comply with §63.119(e)(1)-(5).	§ 63.120(e)(1) § 63.120(e)(4) [G]§ 63.172(f)(1) [G]§ 63.172(f)(2) § 63.172(g) [G]§ 63.172(h) [G]§ 63.172(k) [G]§ 63.172(l) [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.123(a) [G]§ 63.123(f)(2) [G]§ 63.152(a) [G]§ 63.172(k) [G]§ 63.172(l) § 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) [G]§ 63.181(g)(2) [G]§ 63.181(g)(3)	[G]§ 63.120(e)(2) § 63.122(c)(2) [G]§ 63.122(g)(1) [G]§ 63.122(g)(3) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(4)(ii)



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
									[G]§ 63.152(c)(6) [G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
VBD994	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	** See Periodic Monitoring Summary	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
VBD994	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(e) § 63.11 § 63.119(a)(2) § 63.119(e)(1) § 63.119(e)(3) § 63.119(e)(4) § 63.119(e)(5) § 63.172(a) [G]§ 63.172(h) § 63.172(i) § 63.172(m)	The owner or operator who elects to use a closed vent system and control device (defined in § 63.111) to comply with § 63.119(a)(1) or (a)(2) shall comply with § 63.119(e)(1)-(5).	§ 63.120(e)(1) § 63.120(e)(4) [G]§ 63.172(f)(1) [G]§ 63.172(f)(2) § 63.172(g) [G]§ 63.172(h) [G]§ 63.172(k) [G]§ 63.172(l) [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.123(a) [G]§ 63.123(f)(2) [G]§ 63.152(a) [G]§ 63.172(k) [G]§ 63.172(l) § 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) [G]§ 63.181(g)(2) [G]§ 63.181(g)(3)	[G]§ 63.120(e)(2) § 63.122(c)(2) [G]§ 63.122(g)(1) [G]§ 63.122(g)(3) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6) [G]§ 63.182(a) [G]§ 63.182(b)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
									§ 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
VC3303	EU	63YY	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart YY
VIP901	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	** See Periodic Monitoring Summary	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
VIP902	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	** See Periodic Monitoring Summary	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
VIP904	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	** See Periodic Monitoring Summary	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115,	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
					requirements of 30 TAC Chapter 115, Storage of VOCs			Storage of VOCs	
VIP905	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	** See Periodic Monitoring Summary	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
VOL200	EU	63YY	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart YY
VOL201	EU	63YY	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart YY
VOL250	EU	63YY	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart YY

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
VOL251	EU	63YY	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart YY
VOL300	EU	63YY	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart YY
VOL350	EU	63YY	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart YY
VP31143	EU	63YY	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart YY	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart YY
VP31144	EU	63YY	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103 The permit holder shall comply with the applicable limitation,	The permit holder shall comply with the applicable requirements of 40 CFR Part 63,	The permit holder shall comply with the applicable monitoring and testing requirements	The permit holder shall comply with the applicable recordkeeping	The permit holder shall comply with the applicable reporting requirements of 40 CFR

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					standard and/or equipment specification requirements of 40 CFR Part 63, Subpart YY	Subpart YY	of 40 CFR Part 63, Subpart YY	requirements of 40 CFR Part 63, Subpart YY	Part 63, Subpart YY
VP31158	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
X303	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
X303	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
X304	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					Chapter 115, Storage of VOCs				
X304	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
X308	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
X308	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
PROAERAT	PRO	61FF-1	BENZENE	40 CFR Part 61, Subpart FF	§ 61.348(a)(1) § 61.348(a)(1)(ii) § 61.348(a)(2) § 61.348(a)(4) § 61.348(f)	The owner or operator shall design, install, operate and maintain a treatment process that removes or destroys benzene as specified.	§ 61.348(f) § 61.354(a)(2)	§ 61.354(a)(2) § 61.356(e) § 61.356(e)(1) § 61.356(e)(2) [G]§ 61.356(i)	§ 61.357(d)(7) § 61.357(d)(7)(ii)
AU602	EU	R7ICI-01	VOC	30 TAC Chapter 115, Water Separation	§ 115.137(a)(2) [G]§ 115.132(a)(4)	Any single or multiple compartment VOC water separator which separates materials	[G]§ 115.135(a) § 115.136(a)(1) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(1) § 115.136(a)(3) § 115.136(a)(4)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						having a true vapor pressure of VOC < .5 psia obtained from any equipment is exempt from §115.132(a).			
CPI	EU	R5131-1	VOC	30 TAC Chapter 115, Water Separation	§ 115.137(a)(2) [G]§ 115.132(a)(4)	Any single or multiple compartment VOC water separator which separates materials having a true vapor pressure of VOC < .5 psia obtained from any equipment is exempt from §115.132(a).	[G]§ 115.135(a) § 115.136(a)(1) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(1) § 115.136(a)(3) § 115.136(a)(4)	None
GRPAPI	EU	R5131-1	VOC	30 TAC Chapter 115, Water Separation	§ 115.137(a)(2) [G]§ 115.132(a)(4)	Any single or multiple compartment VOC water separator which separates materials having a true vapor pressure of VOC < .5 psia obtained from any equipment is exempt from §115.132(a).	[G]§ 115.135(a) § 115.136(a)(1) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(1) § 115.136(a)(3) § 115.136(a)(4)	None
LO3CPI	EU	R5131-1	VOC	30 TAC Chapter 115, Water Separation	§ 115.137(a)(2) [G]§ 115.132(a)(4)	Any single or multiple compartment VOC water separator which separates materials having a true vapor pressure of VOC < .5 psia obtained from any equipment is exempt from §115.132(a).	[G]§ 115.135(a) § 115.136(a)(1) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(1) § 115.136(a)(3) § 115.136(a)(4)	None
A1304	EU	R5147	VOC	30 TAC Chapter 115, Industrial Wastewater	§ 115.147(2) [G]§ 115.142(4) [G]§ 115.148	An owner or operator may exempt from control requirements of §115.142 one or more affected VOC	§ 115.145 § 115.145(1) § 115.145(10) [G]§ 115.145(2)	§ 115.146(1) § 115.146(3) § 115.146(4)	[G]§ 115.142(4)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						wastewater streams for which the total annual VOC loading is less than or equal to 10 Mg (11.03 tons).	[G]§ 115.145(3) § 115.145(4) § 115.145(5) § 115.145(6) § 115.145(7) § 115.145(9) [G]§ 115.148		
A13113	EU	R5147	VOC	30 TAC Chapter 115, Industrial Wastewater	§ 115.147(2) [G]§ 115.142(4) [G]§ 115.148	An owner or operator may exempt from control requirements of §115.142 one or more affected VOC wastewater streams for which the total annual VOC loading is less than or equal to 10 Mg (11.03 tons).	§ 115.145 § 115.145(1) § 115.145(10) [G]§ 115.145(2) [G]§ 115.145(3) § 115.145(4) § 115.145(5) § 115.145(6) § 115.145(7) § 115.145(9) [G]§ 115.148	§ 115.146(1) § 115.146(3) § 115.146(4)	[G]§ 115.142(4)
A1315	EU	R5147	VOC	30 TAC Chapter 115, Industrial Wastewater	§ 115.147(2) [G]§ 115.142(4) [G]§ 115.148	An owner or operator may exempt from control requirements of §115.142 one or more affected VOC wastewater streams for which the total annual VOC loading is less than or equal to 10 Mg (11.03 tons).	§ 115.145 § 115.145(1) § 115.145(10) [G]§ 115.145(2) [G]§ 115.145(3) § 115.145(4) § 115.145(5) § 115.145(6) § 115.145(7) § 115.145(9) [G]§ 115.148	§ 115.146(1) § 115.146(3) § 115.146(4)	[G]§ 115.142(4)
DISTRBOX	EU	R5147	VOC	30 TAC Chapter 115, Industrial Wastewater	§ 115.147(2) [G]§ 115.142(4) [G]§ 115.148	An owner or operator may exempt from control requirements of §115.142 one or more affected VOC wastewater streams for which the total annual VOC loading is less than or equal to 10 Mg (11.03	§ 115.145 § 115.145(1) § 115.145(10) [G]§ 115.145(2) [G]§ 115.145(3) § 115.145(4) § 115.145(5) § 115.145(6)	§ 115.146(1) § 115.146(3) § 115.146(4)	[G]§ 115.142(4)



## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						tons).	§ 115.145(7) § 115.145(9) [G]§ 115.148		
GRPWW	EU	R5140-1	VOC	30 TAC Chapter 115, Industrial Wastewater	[G]§ 115.142(3) § 115.142 [G]§ 115.148	In the Beaumont/Port Arthur area, and after December 31, 2002 in the Houston/Galveston area, each properly operated biotreatment unit shall meet the specified requirements. §§115.142(3)(A)-(B)	§ 115.144(4) § 115.144(4)(A) § 115.144(4)(B) § 115.145 § 115.145(1) § 115.145(10) [G]§ 115.145(2) [G]§ 115.145(3) § 115.145(4) § 115.145(5) § 115.145(6) § 115.145(7) § 115.145(9) [G]§ 115.148	§ 115.146(1) § 115.146(2) § 115.146(3) § 115.146(4)	None
NEUT1	EU	R5147	VOC	30 TAC Chapter 115, Industrial Wastewater	§ 115.147(2) [G]§ 115.142(4) [G]§ 115.148	An owner or operator may exempt from control requirements of §115.142 one or more affected VOC wastewater streams for which the total annual VOC loading is less than or equal to 10 Mg (11.03 tons).	§ 115.145 § 115.145(1) § 115.145(10) [G]§ 115.145(2) [G]§ 115.145(3) § 115.145(4) § 115.145(5) § 115.145(6) § 115.145(7) § 115.145(9) [G]§ 115.148	§ 115.146(1) § 115.146(3) § 115.146(4)	[G]§ 115.142(4)
NEUT2	EU	R5147	VOC	30 TAC Chapter 115, Industrial Wastewater	§ 115.147(2) [G]§ 115.142(4) [G]§ 115.148	An owner or operator may exempt from control requirements of §115.142 one or more affected VOC wastewater streams for which the total annual VOC loading is less than or equal to 10 Mg (11.03 tons).	§ 115.145 § 115.145(1) § 115.145(10) [G]§ 115.145(2) [G]§ 115.145(3) § 115.145(4) § 115.145(5) § 115.145(6) § 115.145(7)	§ 115.146(1) § 115.146(3) § 115.146(4)	[G]§ 115.142(4)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 115.145(9) [G]§ 115.148		
NEUT3	EU	R5147	VOC	30 TAC Chapter 115, Industrial Wastewater	§ 115.147(2) [G]§ 115.142(4) [G]§ 115.148	An owner or operator may exempt from control requirements of §115.142 one or more affected VOC wastewater streams for which the total annual VOC loading is less than or equal to 10 Mg (11.03 tons).	§ 115.145 § 115.145(1) § 115.145(10) [G]§ 115.145(2) [G]§ 115.145(3) § 115.145(4) § 115.145(5) § 115.145(6) § 115.145(7) § 115.145(9) [G]§ 115.148	§ 115.146(1) § 115.146(3) § 115.146(4)	[G]§ 115.142(4)
NEUT4	EU	R5147	VOC	30 TAC Chapter 115, Industrial Wastewater	§ 115.147(2) [G]§ 115.142(4) [G]§ 115.148	An owner or operator may exempt from control requirements of §115.142 one or more affected VOC wastewater streams for which the total annual VOC loading is less than or equal to 10 Mg (11.03 tons).	§ 115.145 § 115.145(1) § 115.145(10) [G]§ 115.145(2) [G]§ 115.145(3) § 115.145(4) § 115.145(5) § 115.145(6) § 115.145(7) § 115.145(9) [G]§ 115.148	§ 115.146(1) § 115.146(3) § 115.146(4)	[G]§ 115.142(4)
P1309S	EU	R5147	VOC	30 TAC Chapter 115, Industrial Wastewater	§ 115.147(2) [G]§ 115.142(4) [G]§ 115.148	An owner or operator may exempt from control requirements of §115.142 one or more affected VOC wastewater streams for which the total annual VOC loading is less than or equal to 10 Mg (11.03 tons).	§ 115.145 § 115.145(1) § 115.145(10) [G]§ 115.145(2) [G]§ 115.145(3) § 115.145(4) § 115.145(5) § 115.145(6) § 115.145(7) § 115.145(9) [G]§ 115.148	§ 115.146(1) § 115.146(3) § 115.146(4)	[G]§ 115.142(4)
S13141	EU	R5147	VOC	30 TAC Chapter	§ 115.147(2)	An owner or operator	§ 115.145	§ 115.146(1)	[G]§ 115.142(4)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Industrial Wastewater	[G]§ 115.142(4) [G]§ 115.148	may exempt from control requirements of §115.142 one or more affected VOC wastewater streams for which the total annual VOC loading is less than or equal to 10 Mg (11.03 tons).	§ 115.145(1) § 115.145(10) [G]§ 115.145(2) [G]§ 115.145(3) § 115.145(4) § 115.145(5) § 115.145(6) § 115.145(7) § 115.145(9) [G]§ 115.148	§ 115.146(3) § 115.146(4)	
S13142	EU	R5147	VOC	30 TAC Chapter 115, Industrial Wastewater	§ 115.147(2) [G]§ 115.142(4) [G]§ 115.148	An owner or operator may exempt from control requirements of §115.142 one or more affected VOC wastewater streams for which the total annual VOC loading is less than or equal to 10 Mg (11.03 tons).	§ 115.145 § 115.145(1) § 115.145(10) [G]§ 115.145(2) [G]§ 115.145(3) § 115.145(4) § 115.145(5) § 115.145(6) § 115.145(7) § 115.145(9) [G]§ 115.148	§ 115.146(1) § 115.146(3) § 115.146(4)	[G]§ 115.142(4)
S13143	EU	R5147	VOC	30 TAC Chapter 115, Industrial Wastewater	§ 115.147(2) [G]§ 115.142(4) [G]§ 115.148	An owner or operator may exempt from control requirements of §115.142 one or more affected VOC wastewater streams for which the total annual VOC loading is less than or equal to 10 Mg (11.03 tons).	§ 115.145 § 115.145(1) § 115.145(10) [G]§ 115.145(2) [G]§ 115.145(3) § 115.145(4) § 115.145(5) § 115.145(6) § 115.145(7) § 115.145(9) [G]§ 115.148	§ 115.146(1) § 115.146(3) § 115.146(4)	[G]§ 115.142(4)
SETENT	EU	R5147	VOC	30 TAC Chapter 115, Industrial Wastewater	§ 115.147(2) [G]§ 115.142(4) [G]§ 115.148	An owner or operator may exempt from control requirements of §115.142 one or more affected VOC wastewater streams for	§ 115.145 § 115.145(1) § 115.145(10) [G]§ 115.145(2) [G]§ 115.145(3)	§ 115.146(1) § 115.146(3) § 115.146(4)	[G]§ 115.142(4)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						which the total annual VOC loading is less than or equal to 10 Mg (11.03 tons).	§ 115.145(4) § 115.145(5) § 115.145(6) § 115.145(7) § 115.145(9) [G]§ 115.148		
T1301	EU	R5147	VOC	30 TAC Chapter 115, Industrial Wastewater	§ 115.147(2) [G]§ 115.142(4) [G]§ 115.148	An owner or operator may exempt from control requirements of §115.142 one or more affected VOC wastewater streams for which the total annual VOC loading is less than or equal to 10 Mg (11.03 tons).	§ 115.145 § 115.145(1) § 115.145(10) [G]§ 115.145(2) [G]§ 115.145(3) § 115.145(4) § 115.145(5) § 115.145(6) § 115.145(7) § 115.145(9) [G]§ 115.148	§ 115.146(1) § 115.146(3) § 115.146(4)	[G]§ 115.142(4)
T13145	EU	R5147	VOC	30 TAC Chapter 115, Industrial Wastewater	§ 115.147(2) [G]§ 115.142(4) [G]§ 115.148	An owner or operator may exempt from control requirements of §115.142 one or more affected VOC wastewater streams for which the total annual VOC loading is less than or equal to 10 Mg (11.03 tons).	§ 115.145 § 115.145(1) § 115.145(10) [G]§ 115.145(2) [G]§ 115.145(3) § 115.145(4) § 115.145(5) § 115.145(6) § 115.145(7) § 115.145(9) [G]§ 115.148	§ 115.146(1) § 115.146(3) § 115.146(4)	[G]§ 115.142(4)
T1320	EU	R5147	VOC	30 TAC Chapter 115, Industrial Wastewater	§ 115.147(2) [G]§ 115.142(4) [G]§ 115.148	An owner or operator may exempt from control requirements of §115.142 one or more affected VOC wastewater streams for which the total annual VOC loading is less than or equal to 10 Mg (11.03 tons).	§ 115.145 § 115.145(1) § 115.145(10) [G]§ 115.145(2) [G]§ 115.145(3) § 115.145(4) § 115.145(5) § 115.145(6) § 115.145(7)	§ 115.146(1) § 115.146(3) § 115.146(4)	[G]§ 115.142(4)

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements  (30 TAC § 122.144)	Reporting Requirements  (30 TAC § 122.145)
							§ 115.145(9) [G]§ 115.148		
T19054	EU	R5147	VOC	30 TAC Chapter 115, Industrial Wastewater	§ 115.147(2) [G]§ 115.142(4) [G]§ 115.148	An owner or operator may exempt from control requirements of §115.142 one or more affected VOC wastewater streams for which the total annual VOC loading is less than or equal to 10 Mg (11.03 tons).	§ 115.145 § 115.145(1) § 115.145(10) [G]§ 115.145(2) [G]§ 115.145(3) § 115.145(4) § 115.145(5) § 115.145(6) § 115.145(7) § 115.145(9) [G]§ 115.148	§ 115.146(1) § 115.146(3) § 115.146(4)	[G]§ 115.142(4)
T3272	EU	R5147	VOC	30 TAC Chapter 115, Industrial Wastewater	§ 115.147(2) [G]§ 115.142(4) [G]§ 115.148	An owner or operator may exempt from control requirements of §115.142 one or more affected VOC wastewater streams for which the total annual VOC loading is less than or equal to 10 Mg (11.03 tons).	§ 115.145 § 115.145(1) § 115.145(10) [G]§ 115.145(2) [G]§ 115.145(3) § 115.145(4) § 115.145(5) § 115.145(6) § 115.145(7) § 115.145(9) [G]§ 115.148	§ 115.146(1) § 115.146(3) § 115.146(4)	[G]§ 115.142(4)

**Additional Monitoring Requirements**

**Compliance Assurance Monitoring Summary ..... 453**

**Periodic Monitoring Summary..... 470**

## CAM Summary

<b>Unit/Group/Process Information</b>	
ID No.: GRPVESSHO	
Control Device ID No.: OP3ELFLA	Control Device Type: Flare
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1
Pollutant: VOC	Main Standard: 115.112
<b>Monitoring Information</b>	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: No pilot flame	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

## CAM Summary

<b>Unit/Group/Process Information</b>	
ID No.: GRPVESSHO	
Control Device ID No.: OP3GRFLA	Control Device Type: Flare
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: 115.112
<b>Monitoring Information</b>	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: No pilot flame	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	



## CAM Summary

<b>Unit/Group/Process Information</b>	
ID No.: GRPVESHO	
Control Device ID No.: OP2ELFLA	Control Device Type: Flare
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-3
Pollutant: VOC	Main Standard: 115.112
<b>Monitoring Information</b>	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: No pilot flame	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

## CAM Summary

<b>Unit/Group/Process Information</b>	
ID No.: GRPVNT	
Control Device ID No.: OP3ELFLA	Control Device Type: Flare
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-1
Pollutant: VOC	Main Standard: § 115.121(a)(2)
<b>Monitoring Information</b>	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: No pilot flame	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

## CAM Summary

<b>Unit/Group/Process Information</b>	
ID No.: GRPVNT	
Control Device ID No.: OP3GRFLA	Control Device Type: Flare
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-2
Pollutant: VOC	Main Standard: § 115.121(a)(2)
<b>Monitoring Information</b>	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: No pilot flame	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

## CAM Summary

<b>Unit/Group/Process Information</b>	
ID No.: GRPVNT	
Control Device ID No.: OP2ELFLA	Control Device Type: Flare
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-3
Pollutant: VOC	Main Standard: § 115.121(a)(2)
<b>Monitoring Information</b>	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: No pilot flame	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

## CAM Summary

<b>Unit/Group/Process Information</b>	
ID No.: GRPVNT2	
Control Device ID No.: OP3ELFLA	Control Device Type: Flare
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-1
Pollutant: VOC	Main Standard: § 115.121(a)(2)
<b>Monitoring Information</b>	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: No pilot flame	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

## CAM Summary

<b>Unit/Group/Process Information</b>	
ID No.: GRPVNT2	
Control Device ID No.: OP3GRFLA	Control Device Type: Flare
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-2
Pollutant: VOC	Main Standard: § 115.121(a)(2)
<b>Monitoring Information</b>	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: No pilot flame	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

## CAM Summary

<b>Unit/Group/Process Information</b>	
ID No.: GRPVNT2	
Control Device ID No.: OP2ELFLA	Control Device Type: Flare
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-3
Pollutant: VOC	Main Standard: § 115.121(a)(2)
<b>Monitoring Information</b>	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: No pilot flame	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

## CAM Summary

<b>Unit/Group/Process Information</b>	
ID No.: LPGFL	
Control Device ID No.: A1301	Control Device Type: Flare
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-1
Pollutant: VOC	Main Standard: § 115.121(a)(1)
<b>Monitoring Information</b>	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: No pilot flame	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	



## CAM Summary

<b>Unit/Group/Process Information</b>	
ID No.: OP2DIST	
Control Device ID No.: OP3ELFLA	Control Device Type: Flare
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-1
Pollutant: VOC	Main Standard: § 115.121(a)(2)
<b>Monitoring Information</b>	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: No pilot flame	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

## CAM Summary

<b>Unit/Group/Process Information</b>	
ID No.: OP2DIST	
Control Device ID No.: OP2ELFLA	Control Device Type: Flare
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-2
Pollutant: VOC	Main Standard: § 115.121(a)(2)
<b>Monitoring Information</b>	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: No pilot flame	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

## CAM Summary

<b>Unit/Group/Process Information</b>	
ID No.: OP2DIST	
Control Device ID No.: OP3GRFLA	Control Device Type: Flare
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-3
Pollutant: VOC	Main Standard: § 115.121(a)(2)
<b>Monitoring Information</b>	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: No pilot flame	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

## CAM Summary

<b>Unit/Group/Process Information</b>	
ID No.: SITE3FL	
Control Device ID No.: A1301	Control Device Type: Flare
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-1
Pollutant: VOC	Main Standard: § 115.121(a)(1)
<b>Monitoring Information</b>	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: No pilot flame	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

## CAM Summary

<b>Unit/Group/Process Information</b>	
ID No.: VBD933	
Control Device ID No.: OP3ELFLA	Control Device Type: Flare
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1
Pollutant: VOC	Main Standard: 115.112
<b>Monitoring Information</b>	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: No pilot flame	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

## CAM Summary

<b>Unit/Group/Process Information</b>	
ID No.: VBD933	
Control Device ID No.: OP3GRFLA	Control Device Type: Flare
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: 115.112
<b>Monitoring Information</b>	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: No pilot flame	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

## CAM Summary

<b>Unit/Group/Process Information</b>	
ID No.: VBD933	
Control Device ID No.: OP2ELFLA	Control Device Type: Flare
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-3
Pollutant: VOC	Main Standard: 115.112
<b>Monitoring Information</b>	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: No pilot flame	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: A327	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-1
Pollutant: VOC	Main Standard: § 60.112(a)(1)
<b>Monitoring Information</b>	
Indicator: External floating roof	
Minimum Frequency: Annually	
Averaging Period: n/a	
<p>Deviation Limit: If a failure cannot be repaired within 60 days and if the storage tank cannot be emptied within 60 days, the owner or operator may submit written requests for up to two extensions of up to 30 additional days each to the appropriate regional office.</p>	
<p>Periodic Monitoring Text: Visually inspect and record the inspection of the external floating roof to ensure: the roof is floating on the surface of the VOC and not on the leg supports, liquid has not accumulated on the external floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. If any monitoring data indicates the roof is not floating on the surface of the VOC, if liquid has accumulated on the external floating roof, the seals are detached, or if there are holes or tears in the seal fabric, and the failure cannot be repaired within 60 days and if the storage tank cannot be emptied within 60 days, the owner or operator may submit written requests for up to two extensions of up to 30 additional days each to the appropriate regional office after which it will be considered and reported as a deviation.</p>	



## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: A327	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-2
Pollutant: VOC	Main Standard: § 60.112(a)(1)
<b>Monitoring Information</b>	
Indicator: External floating roof	
Minimum Frequency: Annually	
Averaging Period: n/a	
<p>Deviation Limit: If a failure cannot be repaired within 60 days and if the storage tank cannot be emptied within 60 days, the owner or operator may submit written requests for up to two extensions of up to 30 additional days each to the appropriate regional office.</p>	
<p>Periodic Monitoring Text: Visually inspect and record the inspection of the external floating roof to ensure: the roof is floating on the surface of the VOC and not on the leg supports, liquid has not accumulated on the external floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. If any monitoring data indicates the roof is not floating on the surface of the VOC, if liquid has accumulated on the external floating roof, the seals are detached, or if there are holes or tears in the seal fabric, and the failure cannot be repaired within 60 days and if the storage tank cannot be emptied within 60 days, the owner or operator may submit written requests for up to two extensions of up to 30 additional days each to the appropriate regional office after which it will be considered and reported as a deviation.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: A328	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-1
Pollutant: VOC	Main Standard: § 60.112(a)(1)
<b>Monitoring Information</b>	
Indicator: External Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
<p>Deviation Limit: If a failure cannot be repaired within 60 days and if the storage tank cannot be emptied within 60 days, the owner or operator may submit written requests for up to two extensions of up to 30 additional days each to the appropriate regional office.</p>	
<p>Periodic Monitoring Text: Visually inspect and record the inspection of the external floating roof to ensure: the roof is floating on the surface of the VOC and not on the leg supports, liquid has not accumulated on the external floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. If any monitoring data indicates the roof is not floating on the surface of the VOC, if liquid has accumulated on the external floating roof, the seals are detached, or if there are holes or tears in the seal fabric, and the failure cannot be repaired within 60 days and if the storage tank cannot be emptied within 60 days, the owner or operator may submit written requests for up to two extensions of up to 30 additional days each to the appropriate regional office after which it will be considered and reported as a deviation.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: A328	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-2
Pollutant: VOC	Main Standard: § 60.112(a)(1)
<b>Monitoring Information</b>	
Indicator: External Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
<p>Deviation Limit: If a failure cannot be repaired within 60 days and if the storage tank cannot be emptied within 60 days, the owner or operator may submit written requests for up to two extensions of up to 30 additional days each to the appropriate regional office.</p>	
<p>Periodic Monitoring Text: Visually inspect and record the inspection of the external floating roof to ensure: the roof is floating on the surface of the VOC and not on the leg supports, liquid has not accumulated on the external floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. If any monitoring data indicates the roof is not floating on the surface of the VOC, if liquid has accumulated on the external floating roof, the seals are detached, or if there are holes or tears in the seal fabric, and the failure cannot be repaired within 60 days and if the storage tank cannot be emptied within 60 days, the owner or operator may submit written requests for up to two extensions of up to 30 additional days each to the appropriate regional office after which it will be considered and reported as a deviation.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: D370	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-1
Pollutant: VOC	Main Standard: § 60.112(a)(1)
<b>Monitoring Information</b>	
Indicator: External Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
<p>Deviation Limit: If a failure cannot be repaired within 60 days and if the storage tank cannot be emptied within 60 days, the owner or operator may submit written requests for up to two extensions of up to 30 additional days each to the appropriate regional office.</p>	
<p>Periodic Monitoring Text: Visually inspect and record the inspection of the external floating roof to ensure: the roof is floating on the surface of the VOC and not on the leg supports, liquid has not accumulated on the external floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. If any monitoring data indicates the roof is not floating on the surface of the VOC, if liquid has accumulated on the external floating roof, the seals are detached, or if there are holes or tears in the seal fabric, and the failure cannot be repaired within 60 days and if the storage tank cannot be emptied within 60 days, the owner or operator may submit written requests for up to two extensions of up to 30 additional days each to the appropriate regional office after which it will be considered and reported as a deviation.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: D371	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-1
Pollutant: VOC	Main Standard: § 60.112(a)(1)
<b>Monitoring Information</b>	
Indicator: External Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
<p>Deviation Limit: If a failure cannot be repaired within 60 days and if the storage tank cannot be emptied within 60 days, the owner or operator may submit written requests for up to two extensions of up to 30 additional days each to the appropriate regional office.</p>	
<p>Periodic Monitoring Text: Visually inspect and record the inspection of the external floating roof to ensure: the roof is floating on the surface of the VOC and not on the leg supports, liquid has not accumulated on the external floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. If any monitoring data indicates the roof is not floating on the surface of the VOC, if liquid has accumulated on the external floating roof, the seals are detached, or if there are holes or tears in the seal fabric, and the failure cannot be repaired within 60 days and if the storage tank cannot be emptied within 60 days, the owner or operator may submit written requests for up to two extensions of up to 30 additional days each to the appropriate regional office after which it will be considered and reported as a deviation.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: F361	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-1
Pollutant: VOC	Main Standard: § 60.112(a)(1)
<b>Monitoring Information</b>	
Indicator: External Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
<p>Deviation Limit: If a failure cannot be repaired within 60 days and if the storage tank cannot be emptied within 60 days, the owner or operator may submit written requests for up to two extensions of up to 30 additional days each to the appropriate regional office.</p>	
<p>Periodic Monitoring Text: Visually inspect and record the inspection of the external floating roof to ensure: the roof is floating on the surface of the VOC and not on the leg supports, liquid has not accumulated on the external floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. If any monitoring data indicates the roof is not floating on the surface of the VOC, if liquid has accumulated on the external floating roof, the seals are detached, or if there are holes or tears in the seal fabric, and the failure cannot be repaired within 60 days and if the storage tank cannot be emptied within 60 days, the owner or operator may submit written requests for up to two extensions of up to 30 additional days each to the appropriate regional office after which it will be considered and reported as a deviation.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: FOL100	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
<b>Monitoring Information</b>	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>However, if visible emissions are present during the observation, the permit holder shall either assume the visible emissions exceed the opacity limitations for the period observed and list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: FOL110	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
<b>Monitoring Information</b>	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>However, if visible emissions are present during the observation, the permit holder shall either assume the visible emissions exceed the opacity limitations for the period observed and list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.</p>	



## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: FOL120	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
<b>Monitoring Information</b>	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>However, if visible emissions are present during the observation, the permit holder shall either assume the visible emissions exceed the opacity limitations for the period observed and list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: FOL130	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
<b>Monitoring Information</b>	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>However, if visible emissions are present during the observation, the permit holder shall either assume the visible emissions exceed the opacity limitations for the period observed and list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: FOL140	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
<b>Monitoring Information</b>	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>However, if visible emissions are present during the observation, the permit holder shall either assume the visible emissions exceed the opacity limitations for the period observed and list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: FOL150	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
<b>Monitoring Information</b>	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>However, if visible emissions are present during the observation, the permit holder shall either assume the visible emissions exceed the opacity limitations for the period observed and list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: FOL160	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
<b>Monitoring Information</b>	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>However, if visible emissions are present during the observation, the permit holder shall either assume the visible emissions exceed the opacity limitations for the period observed and list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: FOL170	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
<b>Monitoring Information</b>	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>However, if visible emissions are present during the observation, the permit holder shall either assume the visible emissions exceed the opacity limitations for the period observed and list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: FOL180	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
<b>Monitoring Information</b>	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>However, if visible emissions are present during the observation, the permit holder shall either assume the visible emissions exceed the opacity limitations for the period observed and list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: FOL190	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
<b>Monitoring Information</b>	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>However, if visible emissions are present during the observation, the permit holder shall either assume the visible emissions exceed the opacity limitations for the period observed and list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.</p>	



## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: FOL601	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
<b>Monitoring Information</b>	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>However, if visible emissions are present during the observation, the permit holder shall either assume the visible emissions exceed the opacity limitations for the period observed and list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: FOL602	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
<b>Monitoring Information</b>	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>However, if visible emissions are present during the observation, the permit holder shall either assume the visible emissions exceed the opacity limitations for the period observed and list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: FOL603	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
<b>Monitoring Information</b>	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>However, if visible emissions are present during the observation, the permit holder shall either assume the visible emissions exceed the opacity limitations for the period observed and list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: FOL604	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
<b>Monitoring Information</b>	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>However, if visible emissions are present during the observation, the permit holder shall either assume the visible emissions exceed the opacity limitations for the period observed and list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: FOL700	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
<b>Monitoring Information</b>	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>However, if visible emissions are present during the observation, the permit holder shall either assume the visible emissions exceed the opacity limitations for the period observed and list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: FOL710	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
<b>Monitoring Information</b>	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>However, if visible emissions are present during the observation, the permit holder shall either assume the visible emissions exceed the opacity limitations for the period observed and list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: G343	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-1
Pollutant: VOC	Main Standard: § 60.112(a)(1)
<b>Monitoring Information</b>	
Indicator: External Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
<p>Deviation Limit: If a failure cannot be repaired within 60 days and if the storage tank cannot be emptied within 60 days, the owner or operator may submit written requests for up to two extensions of up to 30 additional days each to the appropriate regional office.</p>	
<p>Periodic Monitoring Text: Visually inspect and record the inspection of the external floating roof to ensure: the roof is floating on the surface of the VOC and not on the leg supports, liquid has not accumulated on the external floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. If any monitoring data indicates the roof is not floating on the surface of the VOC, if liquid has accumulated on the external floating roof, the seals are detached, or if there are holes or tears in the seal fabric, and the failure cannot be repaired within 60 days and if the storage tank cannot be emptied within 60 days, the owner or operator may submit written requests for up to two extensions of up to 30 additional days each to the appropriate regional office after which it will be considered and reported as a deviation.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: G344	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-1
Pollutant: VOC	Main Standard: § 60.112(a)(1)
<b>Monitoring Information</b>	
Indicator: External Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
<p>Deviation Limit: If a failure cannot be repaired within 60 days and if the storage tank cannot be emptied within 60 days, the owner or operator may submit written requests for up to two extensions of up to 30 additional days each to the appropriate regional office.</p>	
<p>Periodic Monitoring Text: Visually inspect and record the inspection of the external floating roof to ensure: the roof is floating on the surface of the VOC and not on the leg supports, liquid has not accumulated on the external floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. If any monitoring data indicates the roof is not floating on the surface of the VOC, if liquid has accumulated on the external floating roof, the seals are detached, or if there are holes or tears in the seal fabric, and the failure cannot be repaired within 60 days and if the storage tank cannot be emptied within 60 days, the owner or operator may submit written requests for up to two extensions of up to 30 additional days each to the appropriate regional office after which it will be considered and reported as a deviation.</p>	



## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: GRPFURN2	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 112, Sulfur Compounds	SOP Index No.: REG2-1
Pollutant: SO <sub>2</sub>	Main Standard: § 112.9(c)
<b>Monitoring Information</b>	
Indicator: Sulfur content of fuel	
Minimum Frequency: Once per quarter and within 24 hours of any fuel change	
Averaging Period: Every three hours	
Deviation Limit: Sulfur content of liquid fuel exceeds 0.3 weight percent, averaged over 3 hours. Any data above 0.3 weight percent, averaged over 3 hours shall be considered and reported as a deviation.	
Periodic Monitoring Text: Measure and record the sulfur content of the liquid fuel when in use. Any monitoring data above the deviation limit shall be considered and reported as a deviation.	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: GRPFURN4	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 112, Sulfur Compounds	SOP Index No.: REG2-1
Pollutant: SO <sub>2</sub>	Main Standard: § 112.9(c)
<b>Monitoring Information</b>	
Indicator: Sulfur content of the fuel.	
Minimum Frequency: Once per quarter and within 24 hours of any fuel change	
Averaging Period: Every three hours	
Deviation Limit: Sulfur content of liquid fuel exceeds 0.3 weight percent, averaged over 3 hours. Any data above 0.3 weight percent, averaged over 3 hours shall be considered and reported as a deviation	
Periodic Monitoring Text: Measure and record the sulfur content of the liquid fuel when in use. Any monitoring data above the deviation limit shall be considered and reported as a deviation.	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: H1300	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
<b>Monitoring Information</b>	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>However, if visible emissions are present during the observation, the permit holder shall either assume the visible emissions exceed the opacity limitations for the period observed and list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: H87920	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 112, Sulfur Compounds	SOP Index No.: REG2-1
Pollutant: SO <sub>2</sub>	Main Standard: § 112.9(c)
<b>Monitoring Information</b>	
Indicator: Sulfur content of fuel	
Minimum Frequency: Quarterly and within 24 hours of any fuel change	
Averaging Period: Every three hours	
Deviation Limit: Sulfur content of liquid fuel exceeds 0.3 weight percent averaged over 3 hours. Any data above 0.3 weight percent, averaged over 3 hours, shall be considered and reported as a deviation.	
Periodic Monitoring Text: Measure and record the sulfur content of the fuel when in use. Any monitoring data above the deviation limit shall be considered and reported as a deviation.	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: OP2ACMAP	
Control Device ID No.: FOL140	Control Device Type: Process Heater (Design heat input is greater than or equal to 44MW)
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-1
Pollutant: VOC	Main Standard: § 115.121(a)(1)
<b>Monitoring Information</b>	
Indicator: Period of Operation	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Failure to monitor and record during periods of operation	
Periodic Monitoring Text: Monitor and record the periods of operation of the process heater. All periods that are not recorded shall be considered and reported as a deviation. The records must be readily available for inspection.	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: OP2ACMAP	
Control Device ID No.: FOL150	Control Device Type: Process Heater (Design heat input is greater than or equal to 44MW)
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-2
Pollutant: VOC	Main Standard: § 115.121(a)(1)
<b>Monitoring Information</b>	
Indicator: Period of Operation	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Failure to monitor and record during periods of operation	
Periodic Monitoring Text: Monitor and record the periods of operation of the process heater. All periods that are not recorded shall be considered and reported as a deviation. The records must be readily available for inspection.	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: OP2DECOK	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
<b>Monitoring Information</b>	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>However, if visible emissions are present during the observation, the permit holder shall either assume the visible emissions exceed the opacity limitations for the period observed and list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: TOL911	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-1
Pollutant: VOC	Main Standard: § 60.112(a)(1)
<b>Monitoring Information</b>	
Indicator: External Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
<p>Deviation Limit: If a failure cannot be repaired within 60 days and if the storage tank cannot be emptied within 60 days, the owner or operator may submit written requests for up to two extensions of up to 30 additional days each to the appropriate regional office.</p>	
<p>Periodic Monitoring Text: Visually inspect and record the inspection of the external floating roof to ensure: the roof is floating on the surface of the VOC and not on the leg supports, liquid has not accumulated on the external floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. If any monitoring data indicates the roof is not floating on the surface of the VOC, if liquid has accumulated on the external floating roof, the seals are detached, or if there are holes or tears in the seal fabric, and the failure cannot be repaired within 60 days and if the storage tank cannot be emptied within 60 days, the owner or operator may submit written requests for up to two extensions of up to 30 additional days each to the appropriate regional office after which it will be considered and reported as a deviation.</p>	



## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: TOL911	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-2
Pollutant: VOC	Main Standard: § 60.112(a)(1)
<b>Monitoring Information</b>	
Indicator: External Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
<p>Deviation Limit: If a failure cannot be repaired within 60 days and if the storage tank cannot be emptied within 60 days, the owner or operator may submit written requests for up to two extensions of up to 30 additional days each to the appropriate regional office.</p>	
<p>Periodic Monitoring Text: Visually inspect and record the inspection of the external floating roof to ensure: the roof is floating on the surface of the VOC and not on the leg supports, liquid has not accumulated on the external floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. If any monitoring data indicates the roof is not floating on the surface of the VOC, if liquid has accumulated on the external floating roof, the seals are detached, or if there are holes or tears in the seal fabric, and the failure cannot be repaired within 60 days and if the storage tank cannot be emptied within 60 days, the owner or operator may submit written requests for up to two extensions of up to 30 additional days each to the appropriate regional office after which it will be considered and reported as a deviation.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: V8360	
Control Device ID No.: F8300	Control Device Type: Process Heater (Design heat input is greater than or equal to 44MW)
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-2
Pollutant: VOC	Main Standard: § 115.121(a)(2)
<b>Monitoring Information</b>	
Indicator: Period of Operation	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Failure to monitor and record during periods of operation.	
Periodic Monitoring Text: Monitor and record the periods of operation of the process heater. All periods that are not recorded shall be considered and reported as a deviation. The records must be readily available for inspection.	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: VBD990	
Control Device ID No.: A1301	Control Device Type: Flare
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1
Pollutant: VOC	Main Standard: 115.112
<b>Monitoring Information</b>	
Indicator: Visible Emissions	
Minimum Frequency: Once per day	
Averaging Period: n/a	
Deviation Limit: Observation of visible emissions exceeding 5 minutes in any two hour period during daily observations.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. If visible emissions greater than the Deviation Limit are observed the permit holder shall either report a deviation or determine visible emissions consistent with Test Method 22 or Test Method 9.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: VBD993	
Control Device ID No.: A1301	Control Device Type: Flare
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1
Pollutant: VOC	Main Standard: 115.112
<b>Monitoring Information</b>	
Indicator: Visible Emissions	
Minimum Frequency: Once per day	
Averaging Period: n/a	
Deviation Limit: Observation of visible emissions exceeding 5 minutes in any two hour period during daily observations	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. If visible emissions greater than the Deviation Limit are observed the permit holder shall either report a deviation or determine visible emissions consistent with Test Method 22 or Test Method 9.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: VBD994	
Control Device ID No.: A1301	Control Device Type: Flare
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1
Pollutant: VOC	Main Standard: 115.112
<b>Monitoring Information</b>	
Indicator: Visible emissions	
Minimum Frequency: Once per day	
Averaging Period: n/a	
Deviation Limit: Observation of visible emissions exceeding 5 minutes in any two hour period during daily observations.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. If visible emissions greater than the Deviation Limit are observed the permit holder shall either report a deviation or determine visible emissions consistent with Test Method 22 or Test Method 9.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: VIP901	
Control Device ID No.: A1301	Control Device Type: Flare
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1
Pollutant: VOC	Main Standard: 115.112
<b>Monitoring Information</b>	
Indicator: Visible emissions	
Minimum Frequency: Once per day	
Averaging Period: n/a	
Deviation Limit: Observation of visible emissions exceeding 5 minutes in any two hour period during daily observations.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. If visible emissions greater than the Deviation Limit are observed the permit holder shall either report a deviation or determine visible emissions consistent with Test Method 22 or Test Method 9</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: VIP902	
Control Device ID No.: A1301	Control Device Type: Flare
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1
Pollutant: VOC	Main Standard: 115.112
<b>Monitoring Information</b>	
Indicator: Visible emissions	
Minimum Frequency: Once per day	
Averaging Period: n/a	
Deviation Limit: Observation of visible emissions exceeding 5 minutes in any two hour period during daily observations.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. If visible emissions greater than the Deviation Limit are observed the permit holder shall either report a deviation or determine visible emissions consistent with Test Method 22 or Test Method 9.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: VIP904	
Control Device ID No.: A1301	Control Device Type: Flare
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1
Pollutant: VOC	Main Standard: 115.112
<b>Monitoring Information</b>	
Indicator: Visible emissions	
Minimum Frequency: once per day	
Averaging Period: n/a	
Deviation Limit: Observation of visible emissions exceeding 5 minutes in any two hour period during daily observations.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. If visible emissions greater than the Deviation Limit are observed the permit holder shall either report a deviation or determine visible emissions consistent with Test Method 22 or Test Method 9.</p>	



## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: VIP905	
Control Device ID No.: A1301	Control Device Type: Flare
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1
Pollutant: VOC	Main Standard: 115.112
<b>Monitoring Information</b>	
Indicator: Visible emissions	
Minimum Frequency: Once per day	
Averaging Period: n/a	
Deviation Limit: Observation of visible emissions exceeding 5 minutes in any two hour period during daily observations.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. If visible emissions greater than the Deviation Limit are observed the permit holder shall either report a deviation or determine visible emissions consistent with Test Method 22 or Test Method 9.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: VP31142	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
<b>Monitoring Information</b>	
Indicator: Visible emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Visible emissions shall not exceed 30% opacity averaged over a six-minute period.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>However, if visible emissions are present during the observation, the permit holder shall either assume the visible emissions exceed the opacity limitations for the period observed and list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: VUT109	
Control Device ID No.: GRPFURN2	Control Device Type: Process Heater (Design heat input is greater than or equal to 44MW)
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-1
Pollutant: VOC	Main Standard: § 115.121(a)(2)
<b>Monitoring Information</b>	
Indicator: Period of Operation	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Failure to monitor and record during periods of operation.	
Periodic Monitoring Text: Monitor and record the periods of operation of the process heater. All periods that are not recorded shall be considered and reported as a deviation. The records must be readily available for inspection.	

**Permit Shield**

**Permit Shield .....515**

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
H87920	N/A	40 CFR Part 63, Subpart DDDDD	Boiler is an affected source under 40 CFR Part 63 Subpart EEE. Therefore, it is not subject to Subpart DDDDD.
BD3FLR	N/A	40 CFR Part 60, Subpart NNN	Vent is not from a facility that produces any chemicals as a product, co-product, by-product, or intermediate from a SOCOMI distillation operation.
BD3FLRG	N/A	40 CFR Part 60, Subpart NNN	Vent is not from a facility that produces any chemicals as a product, co-product, by-product, or intermediate from a SOCOMI distillation operation.
CIPXFLR	N/A	40 CFR Part 63, Subpart F	Vent is not part of a CMPU.
CIPXFLRG	N/A	40 CFR Part 60, Subpart N	Vent is not from a facility that produces any chemicals as a product, co-product, by-product, or intermediate from a SOCOMI distillation operation.
CIPXFLRG	N/A	40 CFR Part 63, Subpart F	Vent is not part of a CMPU.
E-87100	N/A	40 CFR Part 60, Subpart NNN	Compliance with MACT G is deemed to constitute compliance with NSPS NNN. The owner or operator may elect to apply this subpart to all such equipment in the chemical manufacturing process unit.
E-87109	N/A	40 CFR Part 60, Subpart III	Compliance with MACT G is deemed to constitute compliance with NSPS III. The owner or operator may elect to apply this subpart to all such equipment in the chemical manufacturing process unit.

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
FLACU	N/A	40 CFR Part 60, Subpart A	Emission unit was not constructed or modified after the date of publication for any standard of this subpart.
FLBEU	N/A	40 CFR Part 60, Subpart A	Emission unit was not constructed or modified after the date of publication for any standard of this subpart.
FLOXU	N/A	40 CFR Part 60, Subpart A	Emission unit was not constructed or modified after the date of publication for any standard of this subpart.
GRPACMAP2	VOL411, VOL412	40 CFR Part 60, Subpart RRR	Construction, modification, reconstruction commenced on or before June 29, 1990
GRPACMAP3	VF34003, VF34004, VF34005, VF34009, VF34010, VF34011	40 CFR Part 60, Subpart RRR	Construction, modification, reconstruction was not commenced after 6/29/1990
GRPPAUPV3	V8207, V8208, V8209, V8212, V8213, V8219, V8222, V8223, V8224, V8228, V8270, V8319, V8333, V8362	40 CFR Part 60, Subpart A	Emission unit was not constructed or modified after the date of publication for any standard of 40 CFR Part 60
GRPPAUPV4	V8200, V8201, V8202, V8203	40 CFR Part 60, Subpart III	Compliance with MACT G is deemed to constitute compliance with NSPS III. The owner or operator may elect to apply this subpart to all such equipment in the chemical manufacturing process unit.
GRPVNT	FLRPURGE, LO2FLR,	40 CFR Part 60, Subpart A	Emission unit was not constructed or modified after

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
	OP2FLR, PY3FLR		the date of publication for any standard of this part.
GRPVENT2	FLRPURGG, LO2FLRG, OP2FLRG, PY3FLRG	40 CFR Part 60, Subpart A	Emission unit was not constructed or modified after the date of publication for any standard of this part.
HT2FLR	N/A	40 CFR Part 60, Subpart NNN	Vent is not from a facility that produces any chemicals as a product, co-product, by-product, or intermediate from a SOCOMI distillation operation.
HT2FLR	N/A	40 CFR Part 63, Subpart F	Vent is not part of a CMPU.
HT2FLRG	N/A	40 CFR Part 60, Subpart NNN	Vent is not from a facility that produces any chemicals as a product, co-product, by-product, or intermediate from a SOCOMI distillation operation.
HT2FLRG	N/A	40 CFR Part 63, Subpart F	Vent is not part of a CMPU.
HT3FLR	N/A	40 CFR Part 60, Subpart NNN	Vent is not from a facility that produces any chemicals as a product, co-product, by-product, or intermediate from a SOCOMI distillation operation.
HT3FLR	N/A	40 CFR Part 63, Subpart F	Vent is not part of a CMPU.
HT3FLRG	N/A	40 CFR Part 60, Subpart NNN	Vent is not from a facility that produces any chemicals as a product, co-product, by-product, or intermediate from a SOCOMI distillation operation.
HT3FLRG	N/A	40 CFR Part 63, Subpart F	Vent is not part of a CMPU.
IRUFLR	N/A	40 CFR Part 63, Subpart F	Vent is not part of a CMPU.

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
IRUFLRG	N/A	40 CFR Part 63, Subpart F	Vent is not part of a CPMU.
NTFFLR	N/A	40 CFR Part 60, Subpart NNN	Vent is not from a facility that produces any chemicals as a product, co-product, by-product, or intermediate from a SOCFI distillation operation.
NTFFLR	N/A	40 CFR Part 63, Subpart F	Vent is not part of a CPMU.
NTFFLRG	N/A	40 CFR Part 60, Subpart NNN	Vent is not from a facility that produces any chemicals as a product, co-product, by-product, or intermediate from a SOCFI distillation operation.
NTFFLRG	N/A	40 CFR Part 63, Subpart F	Vent is not part of a CPMU.
OP2DECOK	N/A	40 CFR Part 60, Subpart A	Emission unit was not constructed or modified after the date of publication for any standard of this part.
V337	N/A	40 CFR Part 60, Subpart A	Emission unit was not constructed or modified after the date of publication for any standard of this subpart.
V392	N/A	40 CFR Part 60, Subpart NNN	Construction or modification of the storage vessel was not commenced after 12/30/1983.
V8204	N/A	40 CFR Part 60, Subpart NN	Construction, modification, or reconstruction was not commenced after December 30, 1983
V8217	N/A	40 CFR Part 63, Subpart F	Doesn't meet definition of storage vessel b/c Acetone is not a HAP



## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
V8321	N/A	40 CFR Part 60, Subpart NNN	Construction, modification, or reconstruction was not commenced after December 30, 1983
V87923	N/A	40 CFR Part 60, Subpart RRR	Compliance with MACT G is deemed to constitute compliance with NSPS RRR. The owner or operator may elect to apply this subpart to all such equipment in the chemical manufacturing process unit.
VP31142	N/A	40 CFR Part 60, Subpart A	Emission unit was not constructed or modified after the date of publication for any standard of this part.
VUT109	N/A	40 CFR Part 60, Subpart A	Emission unit was not constructed or modified after the date of publication for any standard of this part.
X8529A	N/A	40 CFR Part 60, Subpart A	Emission unit was not constructed or modified after the date of publication for any standard of this subpart.
X8529B	N/A	40 CFR Part 60, Subpart A	Emission unit was not constructed or modified after the date of publication for any standard of this subpart.
A1301	N/A	30 TAC Chapter 117, Commercial	Unit is a flare and is exempt from this division.
A1333	N/A	30 TAC Chapter 117, Commercial	Unit is a flare and is exempt from this division.
OP2ELFLA	N/A	30 TAC Chapter 117, Commercial	Flares are exempted from the provisions of this division
OP2ELFLA	N/A	40 CFR Part 60, Subpart J	Flare not located at a petroleum refinery

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
OP3ELFLA	N/A	30 TAC Chapter 112, Sulfur Compounds	Flare does not combust liquid fuel
OP3ELFLA	N/A	40 CFR Part 60, Subpart J	Flare not located at a petroleum refinery
OP3GRFLA	N/A	30 TAC Chapter 112, Sulfur Compounds	Flare does not combust liquid fuel
OP3GRFLA	N/A	40 CFR Part 60, Subpart J	Flare not located at a petroleum refinery
BD3FUG	N/A	40 CFR Part 60, Subpart V	Fugitive emissions that are also subject to the provisions of 40 CFR part 63, subpart H are required only to comply with the provisions of 40 CFR part 63, subpart H.
BD3FUG	N/A	40 CFR Part 60, Subpart VV	The facility is not an affected facility.
CIPXFUG	N/A	40 CFR Part 60, Subpart VV	The facility is not an affected facility.
CIPXFUG	N/A	40 CFR Part 63, Subpart F	Fugitives are not part of a CMPU.
FUGACU	N/A	40 CFR Part 60, Subpart VV	The facility is not an affected facility.
FUGBEU	N/A	40 CFR Part 60, Subpart VV	The facility is not an affected facility.
FUGOXU	N/A	40 CFR Part 60, Subpart VV	The facility is not an affected facility.
HT2FUG	N/A	40 CFR Part 60, Subpart VV	The facility is not an affected facility.
HT2FUG	N/A	40 CFR Part 63, Subpart F	Fugitives are not part of a CMPU.

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
HT3FUG	N/A	40 CFR Part 60, Subpart VV	The facility is not an affected facility.
HT3FUG	N/A	40 CFR Part 61, Subpart V	Source is not intended to operate in VHAP service.
HT3FUG	N/A	40 CFR Part 63, Subpart F	Fugitives are not part of a CPMU.
IRUFUG	N/A	40 CFR Part 61, Subpart V	Source is not intended to operate in VHAP service.
IRUFUG	N/A	40 CFR Part 63, Subpart F	Fugitives are not part of a CPMU.
OL3FUG	N/A	40 CFR Part 60, Subpart VV	The facility is not an affected facility.
OP2FUG	N/A	40 CFR Part 60, Subpart VV	Fugitives subject to 40 CFR Part 61, Subpart V and 40 CFR Part 60, Subpart VV are only required to comply with 40 CFR Part 61, Subpart V.
PY3FUG	N/A	40 CFR Part 60, Subpart VV	The facility is not an affected facility
SITE3FE	N/A	40 CFR Part 60, Subpart VV	The facility does not produce as an intermediate or final product, one or more of the SOCOMI chemicals.
SITE3FE	N/A	40 CFR Part 61, Subpart V	Equipment is not intended to operate in VHAP service.
SITE3FE	N/A	40 CFR Part 63, Subpart CC	Fugitive emissions are not from petroleum refining process units, or bulk gasoline terminals or pipeline breakout stations classified under SIC code 2911 that emit or have equipment containing or contacting one or more HAPs.
WRACKFE	N/A	40 CFR Part 60, Subpart VV	The facility does not produce as an intermediate or

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			final product, one or more of the SOCMCI chemicals.
WRACKFE	N/A	40 CFR Part 61, Subpart V	Equipment is not intended to operate in VHAP service.
WRACKFE	N/A	40 CFR Part 63, Subpart CC	Fugitive emissions are not from petroleum refining process units, or bulk gasoline terminals or pipeline breakout stations classified under SIC code 2911 that emit or have equipment containing or contacting one or more HAPs.
H9200	N/A	30 TAC Chapter 111, Incineration	Incinerator does not burn solid, medical or hazardous waste
CWT13	N/A	40 CFR Part 63, Subpart Q	No chromium based cooling tower chemical used after 9/8/94
CWT18	N/A	40 CFR Part 63, Subpart Q	No chromium based cooling tower chemical used after 9/8/94
CWT1D	N/A	40 CFR Part 63, Subpart Q	No chromium based cooling tower chemical used after 9/8/94
CWT3C	N/A	40 CFR Part 63, Subpart Q	No chromium based cooling tower chemical used after 9/8/94
CWT9	N/A	40 CFR Part 63, Subpart Q	No chromium based cooling tower chemical used after September 8, 1994
OP2	N/A	40 CFR Part 63, Subpart FFFF	OP2 Cooling Water Tower is a heat exchange system

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			that is subject to 40 CFR part 63, subparts G and YY. Therefore, it is not subject to Subpart FFFF.
OP2	N/A	40 CFR Part 63, Subpart Q	No chromium based cooling tower chemical used after September 8, 1994
OP3CWT	N/A	40 CFR Part 63, Subpart Q	No chromium based cooling tower chemical used after September 8, 1994
RCLOAD	N/A	40 CFR Part 61, Subpart BB	Loading rack does not load benzene into tank trucks, railcars, or marine vessels.
SCRWRTC	N/A	40 CFR Part 61, Subpart BB	The rack is not a production facility or bulk terminal which uses a loading rack to load benzene into tank trucks, railcars, or marine vessels.
SCRWRTC	N/A	40 CFR Part 63, Subpart CC	Not a gasoline loading rack classified under SIC Code 2911 that emits or has equipment containing or contacting one or more HAPs.
TTLOAD	N/A	40 CFR Part 61, Subpart BB	Loading rack does not load benzene into tank trucks, railcars, or marine vessels.
WRTCECH	N/A	40 CFR Part 61, Subpart BB	Loading rack does not load benzene into tank trucks, railcars, or marine vessels.
WRTCECH	N/A	40 CFR Part 63, Subpart CC	Not a gasoline loading rack classified under SIC code 2911 that emits or has equipment containing or contacting one or more HAPs.

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
WRTCECH	N/A	40 CFR Part 63, Subpart F	Does not meet the definition of transfer rack because material is not part of a HON CMPU.
WRTTECH	N/A	40 CFR Part 61, Subpart BB	The rack is not a production facility or bulk terminal which uses a loading rack to load benzene into tank trucks, railcars or marine vessels.
WRTTECH	N/A	40 CFR Part 63, Subpart CC	Not a gasoline loading rack classified under SIC code 2911 that emits or has equipment containing or contacting one or more HAPs.
WRTTECH	N/A	40 CFR Part 63, Subpart F	Does not meet the definition of transfer rack because material is not part of a HON CMPU.
D345	N/A	30 TAC Chapter 115, Storage of VOCs	Acetone is not considered a VOC
D345	N/A	40 CFR Part 60, Subpart Kb	Acetone is not considered a VOC
D345	N/A	40 CFR Part 63, Subpart F	Tank does not meet the definition of storage vessel because stored material is not a HAP
D390	N/A	30 TAC Chapter 115, Storage of VOCs	Acetone is not considered a VOC
D390	N/A	40 CFR Part 60, Subpart K	Tank does not store petroleum liquids
D390	N/A	40 CFR Part 63, Subpart F	Doesn't meet definition of storage vessel b/c Acetone is not a HAP
D391	N/A	30 TAC Chapter 115, Storage of VOCs	Acetone is not considered a VOC
D391	N/A	40 CFR Part 60, Subpart K	Tank does not store petroleum liquids

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
D391	N/A	40 CFR Part 63, Subpart F	Tank does not meet the definition of storage vessel because stored material is not a HAP
D392	N/A	30 TAC Chapter 115, Storage of VOCs	Acetone is not considered a VOC
D392	N/A	40 CFR Part 60, Subpart K	Tank does not store petroleum liquids
D392	N/A	40 CFR Part 63, Subpart F	Tank does not meet the definition of storage vessel because stored material is not a HAP
F335	N/A	30 TAC Chapter 115, Storage of VOCs	Acetone is not considered a VOC
F335	N/A	40 CFR Part 60, Subpart K	Tank does not store petroleum liquids
F335	N/A	40 CFR Part 63, Subpart F	Tank does not meet definition of storage vessel material stored is not a HAP
F353	N/A	30 TAC Chapter 115, Storage of VOCs	Acetone is not considered a VOC
F353	N/A	40 CFR Part 60, Subpart K	Construction or modification of the storage vessel was not commenced after 6/11/1973.
F353	N/A	40 CFR Part 63, Subpart F	Does not meet the definition of storage vessel because material is not a HAP.
F354	N/A	30 TAC Chapter 115, Storage of VOCs	Acetone is not considered a VOC
F354	N/A	40 CFR Part 60, Subpart Ka	Tank does not store petroleum liquids
F354	N/A	40 CFR Part 63, Subpart F	Tank does not meet definition of storage vessel because material stored is not a HAP

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
GASOLINE TANK	N/A	30 TAC Chapter 115, Storage of VOCs	Capacity less than 25,000 gallons located at motor vehicle fuel dispensing facility.
GASOLINE TANK	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973
LDLSDMK	N/A	30 TAC Chapter 115, Loading and Unloading of VOC	Loading and unloading of acetone, which is not a VOC.
SCRWRTT	N/A	30 TAC Chapter 115, Loading and Unloading of VOC	Loading and unloading of acetone, which is not a VOC.
SCRWRTT	N/A	40 CFR Part 61, Subpart BB	The rack is not a production facility or bulk terminal which uses a loading rack to load benzene into tank trucks, railcars, or marine vessels.
SCRWRTT	N/A	40 CFR Part 63, Subpart CC	Not a gasoline loading rack classified under SIC Code 2911 that emits or has equipment containing or contacting one or more HAPs.
SCRWRTT	N/A	40 CFR Part 63, Subpart F	Does not meet the definition of transfer rack because material is not part of a HON Chemical Manufacturing Process Unit.
T665A	N/A	30 TAC Chapter 115, Storage of VOCs	Acetone is not considered a VOC
T665A	N/A	40 CFR Part 60, Subpart Kb	Acetone is not a VOL
T665A	N/A	40 CFR Part 63, Subpart F	Tank does not meet the definition of a storage vessel because material stored is not a HAP.



## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
T87301	N/A	30 TAC Chapter 115, Storage of VOCs	Acetone is not considered a VOC
T87301	N/A	40 CFR Part 60, Subpart Kb	Acetone is not considered a VOC
T87301	N/A	40 CFR Part 63, Subpart F	Does not meet definition of storage vessel because acetone is not a HAP
T87302	N/A	30 TAC Chapter 115, Storage of VOCs	Acetone is not considered a VOC
T87302	N/A	40 CFR Part 60, Subpart Kb	Acetone is not considered a VOC
T87302	N/A	40 CFR Part 63, Subpart F	Does not meet definition of storage vessel because acetone is not a HAP
TC33003	N/A	30 TAC Chapter 115, Storage of VOCs	Stores non-contaminated water; Listed in Permit 3214.
TC33003	N/A	40 CFR Part 60, Subpart K	Tank does not store petroleum liquids.
TC33003	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TC33007	N/A	30 TAC Chapter 115, Storage of VOCs	Stores non-VOC material; Listed in emissions inventory.
TC33007	N/A	40 CFR Part 60, Subpart K	Tank does not store petroleum liquids.
TC33007	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TOL30900	N/A	30 TAC Chapter 115, Storage of VOCs	Stores non-VOC material; Listed in Permit 3214.
TOL30900	N/A	40 CFR Part 60, Subpart K	Tank constructed before June 11, 1973.

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
TOL30900	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene.
TU30900	N/A	30 TAC Chapter 115, Storage of VOCs	Stores non-VOC material; Listed in Permit 3214.
TU30900	N/A	40 CFR Part 60, Subpart K	Tank constructed before June 11, 1973
TU30900	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TU30901	N/A	30 TAC Chapter 115, Storage of VOCs	Stores non-VOC material; Listed in Permit 3214.
TU30901	N/A	40 CFR Part 60, Subpart K	Tank constructed before June 11, 1973
TU30901	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TUT605	N/A	40 CFR Part 60, Subpart K	Reid vapor pressure and true vapor pressure less than 1.0 psia.
TUT605	N/A	40 CFR Part 63, Subpart F	Storage tank is not part of a CMPU.
V8302	N/A	30 TAC Chapter 115, Storage of VOCs	Acetone is not considered a VOC
V8302	N/A	40 CFR Part 60, Subpart NNN	Distillation unit does not produce VOC
V8303	N/A	40 CFR Part 60, Subpart NNN	Distillation Unit does not produce VOC
V8303	N/A	40 CFR Part 63, Subpart F	Tank does not meet definition of storage vessel because material stored is not a HAP
V8310	N/A	30 TAC Chapter 115, Storage of VOCs	Acetone is not considered a VOC
V8310	N/A	40 CFR Part 60, Subpart NNN	Distillation unit does not produce VOC

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
V8310	N/A	40 CFR Part 63, Subpart F	Tank does not meet definition of storage vessel because material stored is not a HAP
WRTCDMK	N/A	30 TAC Chapter 115, Loading and Unloading of VOC	Loading and unloading of acetone, which is not a VOC.
WRTCDMK	N/A	40 CFR Part 61, Subpart BB	The rack is not a production facility or bulk terminal which uses a loading rack to load benzene into tank trucks, railcars, or marine vessels.
WRTCDMK	N/A	40 CFR Part 63, Subpart CC	Not a gasoline loading rack classified under SIC Code 2911 that emits or has equipment containing or contacting one or more HAPs.
WRTCDMK	N/A	40 CFR Part 63, Subpart F	Does not meet the definition of transfer rack because material is not part of a HON Chemical Manufacturing Process Unit.
WRTTDMK	N/A	30 TAC Chapter 115, Loading and Unloading of VOC	Loading and unloading of acetone, which is not a VOC.
WRTTDMK	N/A	40 CFR Part 61, Subpart BB	The rack is not a production facility or bulk terminal which uses a loading rack to load benzene into tank trucks, railcars, or marine vessels.
WRTTDMK	N/A	40 CFR Part 63, Subpart CC	Not a gasoline loading rack classified under SIC Code 2911 that emits or has equipment containing or contacting one ore more HAPs.
WRTTDMK	N/A	40 CFR Part 63, Subpart F	Does not meet the definition of transfer rack because

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			material is not part of a HON Chemical Manufacturing Process Unit.
F8300	N/A	30 TAC Chapter 112, Sulfur Compounds	Furnace is not fired by liquid fuel
FP31180	N/A	40 CFR Part 63, Subpart DDDDD	Heater is an ethylene cracking furnace covered by 40 CFR Part 63.1103(e)(1)(G). Therefore, it is not subject to Subpart DDDDD.
GRPFURN1	FOL700, FOL710	30 TAC Chapter 112, Sulfur Compounds	Furnace does not combust liquid fuel
GRPFURN1	FOL700, FOL710	40 CFR Part 60, Subpart J	Not located at a petroleum refinery
GRPFURN1	FOL700, FOL710	40 CFR Part 63, Subpart DDDDD	Heater is an ethylene cracking furnace covered by 40 CFR Part 63.1103(e)(1)(G). Therefore, it is not subject to Subpart DDDDD.
GRPFURN2	FP31010, FP31020, FP31030, FP31040, FP31050, FP31060, FP31070, FP31080, FP31120, FP31140	40 CFR Part 60, Subpart J	Not located at a petroleum refinery
GRPFURN2	FP31010, FP31020, FP31030, FP31040, FP31050, FP31060, FP31070, FP31080, FP31120, FP31140	40 CFR Part 63, Subpart DDDDD	Heater is an ethylene cracking furnace covered by 40 CFR Part 63, Subpart YY. Therefore, it is not subject to Subpart DDDDD.
GRPFURN3	FP31090, FP31100	30 TAC Chapter 112, Sulfur	Furnace does not combust liquid fuel

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
		Compounds	
GRPFURN3	FP31090, FP31100	40 CFR Part 60, Subpart J	Not located at a petroleum refinery
GRPFURN3	FP31090, FP31100	40 CFR Part 63, Subpart DDDDD	Heater is an ethylene cracking furnace covered by 40 CFR Part 63.1103(e)(1)(G). Therefore, it is not subject to Subpart DDDDD.
GRPFURN4	FP31110, FP31130	40 CFR Part 60, Subpart J	Not located at a petroleum refinery
GRPFURN4	FP31110, FP31130	40 CFR Part 63, Subpart DDDDD	Heater is an ethylene cracking furnace covered by 40 CFR Part 63.1103(e)(1)(G). Therefore, it is not subject to Subpart DDDDD.
GRPFURN5	FOL100, FOL110, FOL120, FOL130, FOL140, FOL150, FOL160, FOL170, FOL180, FOL190	30 TAC Chapter 112, Sulfur Compounds	Furnace does not combust liquid fuel.
GRPFURN5	FOL100, FOL110, FOL120, FOL130, FOL140, FOL150, FOL160, FOL170, FOL180, FOL190	40 CFR Part 60, Subpart J	Not located at a petroleum refinery
GRPFURN5	FOL100, FOL110, FOL120, FOL130, FOL140, FOL150, FOL160, FOL170, FOL180, FOL190	40 CFR Part 63, Subpart DDDDD	Heater is an ethylene cracking furnace covered by 40 CFR Part 63.1103(e)(1)(G). Therefore, it is not subject to Subpart DDDDD.
H1300	N/A	30 TAC Chapter 112, Sulfur	Unit is not a liquid fuel-fired steam generator,

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
		Compounds	furnace or heater.
H1300	N/A	40 CFR Part 60, Subpart J	Not located at a petroleum refinery
H87002	N/A	30 TAC Chapter 111, Incineration	Incinerator does not burn solid, medical or hazardous waste
H902	N/A	30 TAC Chapter 112, Sulfur Compounds	Unit is not a liquid fuel-fired steam generator, furnace or heater.
H902	N/A	40 CFR Part 60, Subpart J	Not located at a petroleum refinery
A327	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
A328	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
AP18	N/A	40 CFR Part 60, Subpart K	Tank constructed before June 11, 1973
AP18	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
AP19	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
AP3	N/A	40 CFR Part 60, Subpart K	Reid vapor pressure and true vapor pressure less than 1.0 psia
AP3	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
D303	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973
D303	N/A	40 CFR Part 61, Subpart Y	Vessel does not store product benzene.

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
D303	N/A	40 CFR Part 63, Subpart CC	Storage tank is not associated with a petroleum refining process.
D306	N/A	40 CFR Part 60, Subpart K	Tank does not store petroleum liquids
D307	N/A	40 CFR Part 60, Subpart K	Tank does not store petroleum liquids
D308	N/A	40 CFR Part 60, Subpart Kb	A group I or II storage vessel that is also subject to the provisions of 40 CFR Part 60, Subpart Kb, is required to comply only with the provisions of 40 CFR Part 63, Subpart G.
D313	N/A	40 CFR Part 60, Subpart K	Tank capacity <40,000 gallons
D313	N/A	40 CFR Part 63, Subpart F	Does not meet the definition of a storage vessels because the capacity of the tank is less than 10,000 gallons
D334	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
D334	N/A	40 CFR Part 61, Subpart Y	Vessel does not store product benzene.
D334	N/A	40 CFR Part 63, Subpart F	Tank does not meet the definition of storage vessel because stored material is not a HAP.
D341	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
D341	N/A	40 CFR Part 63, Subpart F	Does not meet the definition of a storage vessel

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			because material is not a HAP.
D342	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
D350	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
D350	N/A	40 CFR Part 61, Subpart Y	A Group 1 or II storage vessel that is subject to the provisions of 40 CFR Part 61, Subpart Y and 40 CFR Part 63, Subpart G is required only to comply with the provisions of 40 CFR part 63, subpart G.
D351	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
D351	N/A	40 CFR Part 61, Subpart Y	A Group 1 or II storage vessel that is subject to the provisions of 40 CFR Part 61, Subpart Y and 40 CFR Part 63, Subpart G is required only to comply with the provisions of 40 CFR part 63, subpart G.
D352	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
D352	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene.
D353	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene.
D353	N/A	40 CFR Part 63, Subpart F	Tank is not part of a HON CMPU



## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
D365	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
D365	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
D365	N/A	40 CFR Part 63, Subpart F	Does not meet the definition of a storage vessel because material is not a HAP.
D369	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
D369	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene.
D369	N/A	40 CFR Part 63, Subpart F	Tank does not meet the definition of storage vessel because stored material is not a HAP.
D370	N/A	40 CFR Part 61, Subpart Y	A Group 1 or II storage vessel that is subject to the provisions of both 40 CFR Part 61, Subpart Y and 40 CFR Part 63, Subpart G is required only to comply with the provisions of 40 CFR part 63, subpart G.
D371	N/A	40 CFR Part 61, Subpart Y	A Group 1 or II storage vessel that is subject to the provisions of both 40 CFR Part 61, Subpart Y and 40 CFR Part 63, Subpart G is required only to comply with the provisions of 40 CFR part 63, subpart G.
D377	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
D377	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
D377	N/A	40 CFR Part 63, Subpart CC	Storage tank is not associated with a petroleum refining process.
D379	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
D379	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene.
D379	N/A	40 CFR Part 63, Subpart CC	Storage tank is not associated with a petroleum refining process.
D380	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
D380	N/A	40 CFR Part 61, Subpart Y	A Group 1 or II storage vessel that is subject to the provisions of both 40 CFR Part 61, Subpart Y and 40 CFR Part 63, Subpart G is required only to comply with the provisions of 40 CFR part 63, subpart G.
D381	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
D381	N/A	40 CFR Part 61, Subpart Y	A Group 1 or II storage vessel that is subject to the provisions of both 40 CFR Part 61, Subpart Y and 40 CFR Part 63, Subpart G is required only to comply with the provisions of 40 CFR part 63, subpart G.
D393	N/A	40 CFR Part 60, Subpart K	Storage capacity less than 40,000 gallons
D393	N/A	40 CFR Part 61, Subpart Y	A Group I or II storage vessel that is also subject to

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			the provisions of 40 CFR Part 61, Subpart Y is required only to comply with the provisions of 40 CFR Part 63, Subpart G
D394	N/A	40 CFR Part 60, Subpart K	Tank does not store petroleum liquids
D395	N/A	40 CFR Part 60, Subpart K	Tank does not store petroleum liquids
D398	N/A	40 CFR Part 60, Subpart K	Tank does not store petroleum liquids
D399	N/A	40 CFR Part 60, Subpart K	Tank does not store petroleum liquids
D400	N/A	40 CFR Part 60, Subpart K	Tank does not store petroleum liquids
D401	N/A	40 CFR Part 60, Subpart K	Tank does not store petroleum liquids
D402	N/A	40 CFR Part 60, Subpart Kb	Group I or II storage vessel that is also subject to the provisions of 40 CFR Part 60, Subpart Kb is required only to comply with the provisions of 40 CFR Part 63, Subpart G
D403	N/A	40 CFR Part 60, Subpart Kb	Group I or II storage vessel that is also subject to the provisions of 40 CFR Part 60, Subpart Kb is required only to comply with the provisions of 40 CFR Part 63, Subpart G
D8100	N/A	40 CFR Part 60, Subpart Kb	Group I or II storage vessel that is also subject to the provisions of 40 CFR Part 60, Subpart Kb is required only to comply with the provisions of 40 CFR Part 63, Subpart G

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
D8100	N/A	40 CFR Part 61, Subpart FF	Group I or II wastewater stream that is also subject to the provisions of 40 CFR Part 61, Subpart FF may comply with the requirements of 63.110(e)(1)(i) or 63.110(e)(1)(ii).
DIESEL TANK	N/A	40 CFR Part 60, Subpart K	Tank constructed before June 11, 1973
EX63	N/A	40 CFR Part 60, Subpart K	Tank does not store petroleum liquids
EX64	N/A	40 CFR Part 60, Subpart K	Tank does not store petroleum liquids
EX65	N/A	40 CFR Part 60, Subpart K	Tank does not store petroleum liquids
EX66	N/A	40 CFR Part 60, Subpart K	Tank capacity < 40,000 gallons
EX67	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is greater than or equal to 19,800 gallons but less than 39,900 gallons with true vapor pressure less than 2.2 psia
EX67	N/A	40 CFR Part 63, Subpart F	Does not meet the definition of a storage vessel because tank does not store a HAP.
EX68	N/A	40 CFR Part 60, Subpart K	Tank capacity less than 40,000 gallons
EX69	N/A	40 CFR Part 60, Subpart K	Tank does not store petroleum liquids
EX70	N/A	40 CFR Part 60, Subpart K	Tank does not store petroleum liquids
EX70	N/A	40 CFR Part 61, Subpart FF	Tank is not a waste treatment tank.
EX76	N/A	40 CFR Part 60, Subpart Ka	Tank does not store petroleum liquids

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
EX77	N/A	40 CFR Part 60, Subpart Ka	Tank does not store petroleum liquids
EX80	N/A	40 CFR Part 60, Subpart Kb	Group I or II storage vessel that is also subject to the provisions of 40 CFR Part 60, Subpart Kb is required only to comply with the provisions of 40 CFR Part 63, Subpart G
F310	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
F310	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene.
F337	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
F337	N/A	40 CFR Part 63, Subpart F	Tank does not meet the definition of storage vessel because stored material is not a HAP.
F347	N/A	40 CFR Part 60, Subpart K	Construction or modification of the storage vessel was not commenced after 6/11/1973.
F349	N/A	40 CFR Part 60, Subpart K	Construction or modification of the storage vessel was not commenced after 6/11/1973.
F350	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene.
F355	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
F355	N/A	40 CFR Part 63, Subpart F	Tank does not meet the definition of storage vessel

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			because stored material is not a HAP.
F356	N/A	40 CFR Part 63, Subpart F	Tank does not meet the definition of storage vessel because stored material is not a HAP.
F357	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
F357	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene.
F358	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
F358	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene.
F359	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
F359	N/A	40 CFR Part 61, Subpart Y	A Group 1 or II storage vessel that is subject to the provisions of both 40 CFR Part 61, Subpart Y and 40 CFR Part 63, Subpart G is required only to comply with the provisions of 40 CFR part 63, subpart G.
F359	N/A	40 CFR Part 63, Subpart CC	Storage tank is not associated with a petroleum refining process
F360	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
F360	N/A	40 CFR Part 61, Subpart Y	A Group 1 or II storage vessel that is subject to the

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			provisions of both 40 CFR Part 61, Subpart Y and 40 CFR Part 63, Subpart G is required only to comply with the provisions of 40 CFR part 63, subpart G.
F360	N/A	40 CFR Part 63, Subpart CC	Storage tank is not associated with a petroleum refining process
F361	N/A	40 CFR Part 61, Subpart Y	A Group 1 or II storage vessel that is subject to the provisions of both 40 CFR Part 61, Subpart Y and 40 CFR Part 63, Subpart G is required only to comply with the provisions of 40 CFR part 63, subpart G.
F361	N/A	40 CFR Part 63, Subpart CC	Storage tank is not associated with a petroleum refining process
G330	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973
G331	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973
G343	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene.
G344	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene.
G353	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene.
GRPVESHO	VBD901, VBD902, VBD903, VBD920, VBD921, VBD934, VBD991, VIP950	40 CFR Part 60, Subpart Kb	Pressure vessels designed to operate in excess of 204.9 kPa and without emissions to the atmosphere

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
GRPVESSHO	VBD901, VBD902, VBD903, VBD920, VBD921, VBD934, VBD991, VIP950	40 CFR Part 63, Subpart F	Storage tank is not part of a CMPU.
J313	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
J313	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene.
J314	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
J314	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene.
J314	N/A	40 CFR Part 63, Subpart F	Tank is not part of a HON CMPU
K306	N/A	40 CFR Part 60, Subpart K	Tank constructed before June 11, 1973
K306	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
K307	N/A	40 CFR Part 60, Subpart K	Tank constructed before June 11, 1973
K307	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
L306	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
L306	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene.
L308	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.



## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
L308	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene.
L332	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
L332	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene.
L333	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
L333	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene.
L335	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
L335	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene.
L335	N/A	40 CFR Part 63, Subpart F	Tank does not meet the definition of storage vessel because stored material is not a HAP.
L336	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
L336	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene.
L336	N/A	40 CFR Part 63, Subpart F	Tank does not meet the definition of storage vessel because stored material is not a HAP.
S332	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
S332	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene.
S332	N/A	40 CFR Part 63, Subpart F	Tank does not meet the definition of storage vessel because stored material is not a HAP.
S390	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene.
S390	N/A	40 CFR Part 63, Subpart F	Tank does not meet the definition of storage vessel because stored material is not a HAP.
S391	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
S391	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene.
S391	N/A	40 CFR Part 63, Subpart F	Tank does not meet the definition of storage vessel because stored material is not a HAP.
S392	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
S392	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene.
S392	N/A	40 CFR Part 63, Subpart F	Tank does not meet the definition of storage vessel because stored material is not a HAP.
S400	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
S400	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene.

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
S400	N/A	40 CFR Part 63, Subpart F	Tank does not meet the definition of storage vessel because stored material is not a HAP.
T1302	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
T1310	N/A	40 CFR Part 60, Subpart K	Does not store petroleum liquids
T13146	N/A	40 CFR Part 60, Subpart K	True vapor pressure and reid vapor pressure is less than 1.0 psia.
T1319	N/A	40 CFR Part 60, Subpart K	Does not store petroleum liquids
T1331	N/A	40 CFR Part 60, Subpart Kb	Tank volume less than 19,800 gallons.
T1332	N/A	40 CFR Part 60, Subpart Kb	Tank volume less than 19,800 gallons.
T1333	N/A	40 CFR Part 60, Subpart Kb	Tank volume less than 19,800 gallons.
T1334	N/A	40 CFR Part 60, Subpart Kb	Tank volume less than 19,800 gallons.
T182	N/A	30 TAC Chapter 115, Storage of VOCs	Tanks stores acetone which is not a VOC
T182	N/A	40 CFR Part 60, Subpart K	Tank stores acetone which is not a petroleum liquid.
T317	N/A	40 CFR Part 60, Subpart Kb	Storage capacity less than 10,600 gallons
T317	N/A	40 CFR Part 63, Subpart F	Does not meet the definition of a storage vessels because the capacity of the tank is less than 10,000 gallons

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
T658	N/A	40 CFR Part 60, Subpart K	Tank does not store petroleum liquids.
T658	N/A	40 CFR Part 63, Subpart F	Tank does not meet the definition of storage vessel because stored material is not a HAP.
T74B	N/A	40 CFR Part 60, Subpart Kb	A Group I or Group II storage vessel that is also subject to the provisions of 40 CFR Part 60 Subpart Kb is required only to comply with the provisions of 40 CFR Part 63 Subpart G.
T87000	N/A	40 CFR Part 60, Subpart Kb	Group I or II storage vessel that is also subject to the provisions of 40 CFR Part 60, Subpart Kb is required only to comply with the provisions of 40 CFR Part 63, Subpart G
T87001	N/A	40 CFR Part 60, Subpart Kb	Storage capacity less than 10,600 gallons
T87003	N/A	40 CFR Part 60, Subpart Kb	Storage capacity less than 10,600 gallons
T87003	N/A	40 CFR Part 63, Subpart F	Does not meet the definition of a storage vessel because the capacity of the tank is less than 10,000 gallons
T87004	N/A	40 CFR Part 60, Subpart Kb	Storage capacity less than 10,600 gallons
T87004	N/A	40 CFR Part 63, Subpart F	Tank does not meet the definition of a storage vessel because the capacity of the tank is less than 10,000 gallons.
T87005	N/A	40 CFR Part 60, Subpart Kb	Group I or II storage vessel that is also subject to the

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			provisions of 40 CFR Part 60, Subpart Kb is required only to comply with the provisions of 40 CFR Part 63, Subpart G
T87007	N/A	40 CFR Part 60, Subpart Kb	Group I or II storage vessel that is also subject to the provisions of 40 CFR Part 60, Subpart Kb is required only to comply with the provisions of 40 CFR Part 63, Subpart G
T87100	N/A	40 CFR Part 60, Subpart Kb	Group I or II storage vessel that is also subject to the provisions of 40 CFR Part 60, Subpart Kb is required only to comply with the provisions of 40 CFR Part 63, Subpart G
T87300	N/A	40 CFR Part 60, Subpart Kb	Group I or II storage vessel that is also subject to the provisions of 40 CFR Part 60, Subpart Kb is required only to comply with the provisions of 40 CFR Part 63, Subpart G
T87400	N/A	40 CFR Part 60, Subpart Kb	Group I or II storage vessel that is also subject to the provisions of 40 CFR Part 60, Subpart Kb is required only to comply with the provisions of 40 CFR Part 63, Subpart G
T87401	N/A	40 CFR Part 60, Subpart Kb	Group I or II storage vessel that is also subject to the provisions of 40 CFR Part 60, Subpart Kb is required only to comply with the provisions of 40 CFR Part 63, Subpart G

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
T87500	N/A	40 CFR Part 60, Subpart Kb	Group I or II storage vessel that is also subject to the provisions of 40 CFR Part 60, Subpart Kb is required only to comply with the provisions of 40 CFR Part 63, Subpart G
TB3-301-R1	N/A	40 CFR Part 60, Subpart Kb	A Group I or Group II storage vessel that is also subject to the provisions of 40 CFR Part 60, Subpart Kb is required only to comply with the provisions of 40 CFR Part 63, Subpart G.
TBD301	N/A	40 CFR Part 60, Subpart K	Tank capacity less than 40,000 gallons.
TBD301	N/A	40 CFR Part 63, Subpart F	Storage tank is not part of a CMPU.
TBD910	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
TBD910	N/A	40 CFR Part 63, Subpart G	Storage vessel is shared among CMPUs and a non-HON process unit has the predominant use.
TBD911	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
TBD912	N/A	40 CFR Part 60, Subpart K	Reid vapor pressure and true vapor pressure less than 1.0 psia.
TBD913	N/A	40 CFR Part 60, Subpart K	Tank Capacity less than 40,000 gallons
TC33001	N/A	40 CFR Part 60, Subpart K	Tank does not store petroleum liquids.

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
TC33001	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TC33002	N/A	40 CFR Part 60, Subpart K	Tank does not store petroleum liquids.
TC33002	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TF34001	N/A	40 CFR Part 60, Subpart K	Storage capacity of tank is less than 40,000 gals.
TF34001	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TOL301	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
TOL301	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TOL302	N/A	40 CFR Part 60, Subpart K	Tank constructed before June 11, 1973
TOL302	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TOL303	N/A	40 CFR Part 60, Subpart K	Tank constructed before June 11, 1973
TOL303	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TOL304	N/A	40 CFR Part 60, Subpart K	Tank constructed before June 11, 1973
TOL304	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TOL305	N/A	40 CFR Part 60, Subpart K	Tank constructed before June 11, 1973
TOL305	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TOL3070	N/A	40 CFR Part 60, Subpart K	Tank constructed before June 11, 1973

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
TOL3070	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TOL400	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
TOL400	N/A	40 CFR Part 63, Subpart F	Storage tank is not part of a CMPU.
TOL401	N/A	40 CFR Part 60, Subpart K	Tank constructed before June 11, 1973.
TOL401	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TOL901	N/A	40 CFR Part 60, Subpart K	Tank constructed before June 11, 1973
TOL901	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TOL902	N/A	40 CFR Part 60, Subpart K	Reid vapor pressure and true vapor pressure less than 1.0 psia
TOL902	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TOL903	N/A	40 CFR Part 60, Subpart K	Tank constructed before June 11, 1973.
TOL903	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TOL904	N/A	40 CFR Part 60, Subpart K	Tank constructed before June 11, 1973
TOL904	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TOL905	N/A	40 CFR Part 60, Subpart K	Tank constructed before June 11, 1973
TOL905	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene



## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
TOL908	N/A	40 CFR Part 60, Subpart K	Tank constructed before June 11, 1973.
TOL908	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TOL909	N/A	40 CFR Part 60, Subpart K	Tank constructed before June 11, 1973.
TOL909	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TOL910	N/A	40 CFR Part 60, Subpart K	Tank constructed before June 11, 1973.
TOL910	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TOL911	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TOL912	N/A	40 CFR Part 60, Subpart K	Tank constructed before June 11, 1973
TOL912	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TOL913	N/A	40 CFR Part 60, Subpart K	Tank constructed before June 11, 1973
TOL913	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TOL914	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TOL920	N/A	40 CFR Part 61, Subpart FF	Tank does not meet the definition of waste management unit.
TOL920	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TR35020	N/A	40 CFR Part 60, Subpart K	Tank constructed before June 11, 1973.
TR35020	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
TU30911	N/A	40 CFR Part 60, Subpart K	Reid vapor pressure and true vapor pressure less than 1.0 psia.
TU30911	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TU30913	N/A	40 CFR Part 60, Subpart K	Reid vapor pressure and true vapor pressure less than 1.0 psia.
TU30913	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
TUT604	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
TUT604	N/A	40 CFR Part 63, Subpart F	Storage tank is not part of a CMPU.
TUT918	N/A	40 CFR Part 60, Subpart K	Reid vapor pressure and true vapor pressure less than 1.0 psia.
TUT918	N/A	40 CFR Part 61, Subpart FF	Tank does not meet the definition of waste management unit.
TUT918	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
VBD990	N/A	40 CFR Part 60, Subpart K	Construction/modification of the storage vessel was commenced prior to 6/11/73.
VIP901	N/A	40 CFR Part 63, Subpart F	Storage tank is not associated with a HON CMPU.
VIP902	N/A	40 CFR Part 63, Subpart F	Storage tank is not associated with a HON CMPU.
VIP904	N/A	40 CFR Part 63, Subpart F	Storage tank is not associated with a HON CMPU.

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
VIP905	N/A	40 CFR Part 63, Subpart F	Storage tank is not associated with a HON CMPU.
VP31158	N/A	40 CFR Part 60, Subpart K	Tank constructed before June 11, 1973
VP31158	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene
X303	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
X303	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene.
X304	N/A	40 CFR Part 60, Subpart K	Construction/modification of storage vessel commenced on or before June 11, 1973.
X304	N/A	40 CFR Part 61, Subpart Y	Tank does not store product benzene.
X308	N/A	40 CFR Part 60, Subpart K	Tank does not store petroleum liquids
CPI	N/A	40 CFR Part 60, Subpart VV	Facility does not control air emissions from oil-water and organic-water separator for which another subpart of 40 CFR Parts 60, 61, or 63 references.
GRPAPI	NAPI, SAPI	40 CFR Part 63, Subpart DD	Facility does not meet the definition of an offsite waste and recovery operation.

**New Source Review Authorization References**

**New Source Review Authorization References ..... 555**

**New Source Review Authorization References by Emission Unit..... 558**

## New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

<b>Prevention of Significant Deterioration (PSD) Permits</b>	
PSD Permit No.: PSDTX896	Issuance Date: 02/12/2016
PSD Permit No.: PSDTX928	Issuance Date: 12/17/2014
PSD Permit No.: PSDTX974	Issuance Date: 09/30/2013
<b>Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.</b>	
Authorization No.: 1119	Issuance Date: 03/30/2006
Authorization No.: 1120	Issuance Date: 04/05/2006
Authorization No.: 18576	Issuance Date: 04/15/2014
Authorization No.: 1968	Issuance Date: 03/07/2011
Authorization No.: 19849	Issuance Date: 10/09/2013
Authorization No.: 21262	Issuance Date: 12/17/2014
Authorization No.: 2597	Issuance Date: 06/17/2011
Authorization No.: 3173	Issuance Date: 03/07/2011
Authorization No.: 3178	Issuance Date: 01/27/2016
Authorization No.: 3179	Issuance Date: 07/21/2011
Authorization No.: 3214	Issuance Date: 06/30/2008
Authorization No.: 3215	Issuance Date: 10/20/2015
Authorization No.: 3216	Issuance Date: 10/27/2015
Authorization No.: 3217	Issuance Date: 11/03/2008
Authorization No.: 3218	Issuance Date: 06/06/2011
Authorization No.: 3219	Issuance Date: 09/30/2013
Authorization No.: 37206	Issuance Date: 02/12/2016
Authorization No.: 3985A	Issuance Date: 01/21/2016
Authorization No.: 48912	Issuance Date: 02/05/2016
Authorization No.: 56476	Issuance Date: 08/08/2014
Authorization No.: 56496	Issuance Date: 05/12/2015
Authorization No.: 80525	Issuance Date: 04/19/2007

## New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Authorization No.: 9334	Issuance Date: 11/26/2013
<b>Permits By Rule (30 TAC Chapter 106) for the Application Area</b>	
Number: 106.261	Version No./Date: 03/14/1997
Number: 106.261*	Version No./Date: 12/24/1998
Number: 106.261	Version No./Date: 09/04/2000
Number: 106.261	Version No./Date: 10/01/2003
Number: 106.261	Version No./Date: 11/01/2003
Number: 106.262	Version No./Date: 03/14/1997
Number: 106.262	Version No./Date: 12/24/1998
Number: 106.262	Version No./Date: 09/04/2000
Number: 106.262	Version No./Date: 11/01/2003
Number: 106.262	Version No./Date: 03/14/2016
Number: 106.263*	Version No./Date: 09/04/2000
Number: 106.263	Version No./Date: 11/01/2001
Number: 106.264*	Version No./Date: 03/14/1997
Number: 106.264*	Version No./Date: 09/04/2000
Number: 106.355*	Version No./Date: 11/01/2001
Number: 106.371	Version No./Date: 09/04/2000
Number: 106.472	Version No./Date: 03/14/1997
Number: 106.472	Version No./Date: 09/04/2000
Number: 106.473	Version No./Date: 09/04/2000
Number: 106.475*	Version No./Date: 03/14/1997
Number: 106.475	Version No./Date: 09/04/2000
Number: 106.476	Version No./Date: 09/04/2000
Number: 106.478*	Version No./Date: 03/14/1997
Number: 106.478	Version No./Date: 09/04/2000
Number: 106.492	Version No./Date: 09/04/2000
Number: 106.532	Version No./Date: 09/04/2000

## New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Number: 51*	Version No./Date: 09/12/1989
Number: 51	Version No./Date: 06/07/1996
Number: 53	Version No./Date: 06/07/1996
Number: 80	Version No./Date: 09/20/1993
Number: 80	Version No./Date: 10/04/1995
Number: 86	Version No./Date: 09/12/1989
Number: 86	Version No./Date: 09/13/1993
Number: 106	Version No./Date: 09/20/1993
Number: 118	Version No./Date: 09/12/1989
Number: 118	Version No./Date: 09/13/1993
Number: 118	Version No./Date: 09/20/1993
Number: 118	Version No./Date: 06/07/1996
<b>Municipal Solid Waste and Industrial Hazardous Waste Permits With an Air Addendum</b>	
Permit No.: HW50099001	

\* Site-wide (see Statement of Basis - Special Terms and Conditions)

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
A1301	FLARE	21262, 3179, 106.261[79604]09/04/2000, 106.262[79604]09/04/2000, 106.492[79604]09/04/2000, PSDTX928
A1304	PRIMARY CLARIFIERS	48912
A13113	PRIMARY CLARIFIERS	48912
A1315	BIOSOLIDS TANK	48912
A1333	FLARE	3179, 106.261[113881]09/04/2000, 106.262[113881]09/04/2000, 106.492/09/04/2000
A327	STORAGE TANK	1119, 086/09/12/1989, 118/09/12/1989, 106.261[109247]09/04/2000, 106.478[109247]09/04/2000, 106.261[132997]09/04/2000, 106.478[132997]09/04/2000
A328	STORAGE TANK	1120, 086/09/12/1989, 118/09/12/1989, 106.261[109247]09/04/2000, 106.478[109247]09/04/2000, 106.261[132997]09/04/2000, 106.478[132997]09/04/2000
ACNLOAD	LOADING RACK	106.261[50423]12/24/1998, 106.262[50423]12/24/1998
ACUDCN	ACU UNIT DECONTAMINATION	9334
ACUMSSFUG	ACU MSS STREAM FUGITIVE	9334



## New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
ACUPMPDCN	ACU PUMP DECONTAMINATION	9334
ACUSAMPL	ACU SAMPLE LOADING EMISSIONS	9334
AP18	STORAGE TANK	3214
AP19	STORAGE TANK	3214, 106.261[115088]09/04/2000, 106.478[115088]09/04/2000
AP3	STORAGE TANK	3219, PSDTX974
AU602	WATER SEPARATOR	3218, 106.532[80503]09/04/2000
BD3DCN	BD3 UNIT DECONTAMINATION	3218
BD3FLRG	VENTS	3219, PSDTX974
BD3FLR	VENTS	3219, PSDTX974
BD3FUG	FUGITIVES	3217
BD3MSSFUG	BD3 MSS STREAM FUGITIVE EMISSIONS	3218
BD3PMPDCN	BD3 PUMP DECONTAMINATION	3218
BD3SAMPL	BD3 EMISSIONS FROM LOADING SAMPLE	3218
BEUDCN	BEU UNIT DECONTAMINATION	9334
BEUMSSFUG	BEU MSS STREAM FUGITIVE	9334
BEUPMPDCN	BEU PUMP DECONTAMINATION	9334
BEUSAMPL	BEU SAMPLE LOADING EMISSIONS	9334

## New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
CIPXDCN	CIPX UNIT DECONTAMINATION	3218
CIPXFLRG	VENTS	3219, PSDTX974
CIPXFLR	VENTS	3219, PSDTX974
CIPXFUG	FUGITIVES	3218
CIPXMSSFUG	CIPX MSS STREAM FUGITIVE EMISSIONS	3218
CIPXPMPDCN	CIPX PUMP DECONTAMINATION	3218
CIPXSAMPL	CIPX EMISSIONS FROM LOADING SAMPLE	3218
CPI	WATER SEPARATOR	3179
CUMSD	CUMENE UNIT SHUTDOWN/DECONTAMINATION	3179
CWT13	COOLING TOWER	3179
CWT18	COOLING TOWER	3179
CWT1D	COOLING TOWER	106.371/09/04/2000
CWT3C	COOLING TOWER	1968
CWT9	COOLING TOWER	21262, PSDTX928
D303	STORAGE TANK	9334
D306	STORAGE TANK	3179
D307	STORAGE TANK	3179
D308	STORAGE TANK	3179

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
D313	STORAGE TANK	3179
D334	STORAGE TANK	9334
D341	STORAGE TANK	1968
D342	STORAGE TANK	3179, 106.262[80503]09/04/2000, 106.478[80503]0904/2000
D345	STORAGE TANK	3179, 106.262[77284]09/04/2000, 106.261[77284]09/04/2000, 106.262[80503]09/04/2000, 106.478[80503]09/04/2000
D350	STORAGE TANK	9334, 106.262[102096]09/04/2000, 106.478[102096]09/04/2000
D351	STORAGE TANK	9334
D352	STORAGE TANK	9334
D353	STORAGE TANK	9334
D364	STORAGE TANK	9334
D365	STORAGE TANK	3178, 051/06/07/1996
D366	STORAGE TANK	9334
D367	STORAGE TANK	9334
D369	STORAGE TANK	3178, 051/06/07/1996
D370	STORAGE TANK	9334

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
D371	STORAGE TANK	9334
D377	STORAGE TANK	9334
D379	STORAGE TANK	9334
D380	STORAGE TANK	9334
D381	STORAGE TANK	9334
D390	STORAGE TANK	3179, 106.261[87871]11/01/2003
D391	STORAGE TANK	3179, 106.261[87871]11/01/2003
D392	STORAGE TANK	3179, 106.261[87871]11/01/2003, 106.262[85596]11/01/2001, 106.263[85596]11/01/2001
D393	STORAGE TANK	3179, 106.262[80503]09/04/2000, 106.478[80503]09/04/2000
D394	STORAGE TANK	3179, 106.472/09/04/2000, 106.262[77284]09/04/2000, 106.261[77284]09/04/2000
D395	STORAGE TANK	3179
D398	STORAGE TANK	3179, 106.478/09/04/2000
D399	STORAGE TANK	3179
D400	STORAGE TANK	3179
D401	STORAGE TANK	3179

## New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
D402	STORAGE TANK	3179
D403	STORAGE TANK	3179
D8100	STORAGE TANK	3179
DIESEL TANK	STORAGE TANK	106.472/09/04/2000, 106.473/09/04/2000
DISTRBOX	DISTRIBUTION BOX	48912
DSTDCN	VESSEL SHUTDOWN AND DEGASSING	3179
DSTMSSFUG	DISTRIBUTION MSS STREAM FUGITIVE	3179
DSTPMPDCN	DISTRIBUTION PUMP DECONTAMINATION	3179
DSTSAMPL	DISTRIBUTION SAMPLE EMISSIONS	3179
E8256	E8256	3179, 106.262[77284]09/04/2000, 106.261[77284]09/04/2000
E-87100	PROCESS VENT	3179
E-87109	PROCESS VENT	3179
EAERAT	AERATION BASIN	48912
ENVSOFLR	FUGITIVES	48912
EX63	STORAGE TANK	3179
EX64	STORAGE TANK	3179
EX65	STORAGE TANK	3179

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
EX66	STORAGE TANK	3179
EX67	STORAGE TANK	3179
EX68	STORAGE TANK	3179
EX69	STORAGE TANK	3179
EX70	PROCESS WATER STORAGE TANK	3179
EX76	STORAGE TANK	3179
EX77	STORAGE TANK	3179
EX80	PROCESS WATER STORAGE TANK	3179
F310	STORAGE TANK	9334
F335	STORAGE TANK	3179
F336	STORAGE TANK	086/09/13/1993, 118/09/13/1993
F337	STORAGE TANK	3173
F347	STORAGE TANK	9334, 19849, 106.478/09/04/2000
F349	STORAGE TANK	1968, 19849, 106.472/09/04/2000, 106.478/09/04/2000
F350	STORAGE TANK	9334
F351	STORAGE TANK	3985A
F353	STORAGE TANK	3173, 106.263/11/01/2001,

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
		106.478/09/04/2000
F354	STORAGE TANK	3179, 106.262[80503]09/04/2000, 106.478[80503]09/04/2000
F355	STORAGE TANK	9334
F356	STORAGE TANK	3178, 051/06/07/1996
F357	STORAGE TANK	9334
F358	STORAGE TANK	9334
F359	STORAGE TANK	9334
F360	STORAGE TANK	9334
F361	STORAGE TANK	9334
F8300	FURNACE	3179, 106.262[77284]09/04/2000, 106.261[77284]09/04/2000, 106.261[87871]11/01/2003
F8301	FURNACE	3179
FH3601	PROCESS HEATER	3215
FLACU	PROCESS VENT	9334, 080/10/04/1995
FLBEU	PROCESS VENT	3178
FLOXU	PROCESS VENT	9334
FLPAP	PROCESS VENT	3179

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
FLRPURGE	PROCESS VENTS	3219, PSDTX974
FLRPURGG	PROCESS VENTS	3219, PSDTX974
FOL100	PYROLYSIS FURNACE	3219, 106.261[87871]11/01/2003, PSDTX974
FOL110	PYROLYSIS FURNACE	3219, 106.261[87871]11/01/2003, PSDTX974
FOL120	PYROLYSIS FURNACE	3219, 106.261[87871]11/01/2003, PSDTX974
FOL130	PYROLYSIS FURNACE	3219, 106.261[87871]11/01/2003, PSDTX974
FOL140	PYROLYSIS FURNACE	3219, 106.261[87871]11/01/2003, PSDTX974
FOL150	PYROLYSIS FURNACE	3219, 106.261[87871]11/01/2003, PSDTX974
FOL160	PYROLYSIS FURNACE	3219, 106.261[87871]11/01/2003, PSDTX974
FOL170	PYROLYSIS FURNACE	3219, 106.261[87871]11/01/2003, PSDTX974
FOL180	PYROLYSIS FURNACE	3219, 106.261[87871]11/01/2003, PSDTX974
FOL190	PYROLYSIS FURNACE	3219, 106.261[87871]11/01/2003, PSDTX974
FOL601	GAS OIL STABILIZER REBOILER	3216, 106.261[113881]09/04/2000, 106.262[113881]09/04/2000 106.492/09/04/2000
FOL602	STAGE 3 PREHEATER FURNACE	3216, 106.261[113881]09/04/2000, 106.262[113881]09/04/2000, 106.492/09/04/2000



## New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
FOL603	HYDROGEN PREHEAT FURNACE	3216, 106.261[113881]09/04/2000, 106.262[113881]09/04/2000, 106.492/09/04/2000
FOL604	GASOLINE STABILIZER REBOILER	3216, 106.261[113881]09/04/2000, 106.262[113881]09/04/2000, 106.492/09/04/2000
FOL700	PYROLYSIS FURNACE	56496
FOL710	PYROLYSIS FURNACE	56496
FP31010	PROCESS HEATER	3214
FP31020	PROCESS HEATER	3214
FP31030	PROCESS HEATER	3214
FP31040	PROCESS HEATER	3214
FP31050	PROCESS HEATER	3214
FP31060	PROCESS HEATER	3214
FP31070	PROCESS HEATER	3214
FP31080	PROCESS HEATER	3214
FP31090	PROCESS HEATER	3214
FP31100	PROCESS HEATER	3214
FP31110	PROCESS HEATER	3214

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
FP31120	PROCESS HEATER	3214
FP31130	PROCESS HEATER	3214
FP31140	PROCESS HEATER	3214
FP31180	PROCESS HEATER	3214
FUGACU	FUGITIVES	9334
FUGBEU	FUGITIVES	9334
FUGBIFBOIL	FUGITIVES	37206, PSDTX896
FUGOXU	FUGITIVES	9334, 106.262[98473]09/04/2000
FUGPAU3	FUGITIVES	3179, 106.262[52089]09/04/2000
G330	STORAGE TANK	3179
G331	STORAGE TANK	3179
G343	STORAGE TANK	9334
G344	STORAGE TANK	9334
G353	STORAGE TANK	9334, 106.261[96915]09/04/2000, 106.262[96915]09/04/2000
G354	STORAGE TANK	21262, 106.261[113881]09/04/2000, 106.262[113881]09/04/2000, 106.492/09/04/2000, PSDTX928
GASOLINE TANK	STORAGE TANK	106.472/09/04/2000, 106.473/09/04/2000

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
H1300	OXU FURNACE	9334
H87002	THERMAL OXIDIZER	3179, 106.261[101891]09/04/2000
H87920	BOILER	37206, PSDTX896
H902	PROCESS HEATER	9334
H9200	INCINERATOR	3179, 106.261[100328]09/04/2000, 106.262[100328]09/04/2000, 106.261[123359]09/04/2000, 106.262[123359]09/04/2000, 106.262[77284]09/04/2000, 106.261[77284]09/04/2000
HT2DCN	HT2 UNIT DECONTAMINATION	3218
HT2FLRG	VENTS	3219, PSDTX974
HT2FLR	VENTS	3219, PSDTX974
HT2FUG	FUGITIVES	3216, 106.261[76699]03/14/1997, 106.262[76699]03/14/1997
HT2MSSFUG	HT2 MSS STREAM FUGITIVE EMISSIONS	3218
HT2PMPDCN	HT2 PUMP DECONTAMINATION	3218
HT2SAMPL	HT2 EMISSIONS FROM LOADING SAMPLE	3218
HT3DCN	HT3 UNIT DECONTAMINATION	3218
HT3FLRG	VENTS	3219, PSDTX974

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
HT3FLR	VENTS	3219, PSDTX974
HT3FUG	FUGITIVES	3215, 106.261[115088]09/04/2000, 106.478[115088]09/04/2000
HT3MSSFUG	HT3 MSS STREAM FUGITIVE EMISSIONS	3218
HT3PMPDCN	HT3 PUMP DECONTAMINATION	3218
HT3SAMPL	HT3 EMISSIONS FROM LOADING SAMPLE	3218
IRUDCN	IRU UNIT DECONTAMINATION	3218
IRUFLRG	VENTS	3219, PSDTX974
IRUFLR	VENTS	3219, PSDTX974
IRUFUG	FUGITIVES	18576, 106.261[113881]09/04/2000, 106.262[113881]09/04/2000, 106.492/09/04/2000
IRUMSSFUG	IRU MSS STREAM FUGITIVE EMISSIONS	3218
IRUPMPDCN	IRU PUMP DECONTAMINATION	3218
IRUSAMPL	IRU EMISSIONS FROM LOADING SAMPLE	3218
J313	STORAGE TANK	9334
J314	STORAGE TANK	9334
J320	STORAGE TANK	21262, PSDTX928
K306	STORAGE TANK	3219, PSDTX974

## New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
K307	STORAGE TANK	3219, 106.262[87173]09/04/2000, 106.261[87173]09/04/2000, PSDTX974
L306	STORAGE TANK	9334
L308	STORAGE TANK	9334
L332	STORAGE TANK	9334
L333	STORAGE TANK	9334
L334	STORAGE TANK	9334
L335	STORAGE TANK	9334
L336	STORAGE TANK	9334
LDLSDMK	ACETONE LAND LOADING LOSSES	3179
LO2FLRG	PROCESS VENTS	3219, PSDTX974
LO2FLR	PROCESS VENTS	3219, PSDTX974
LO3CPI	WATER SEPARATOR	106.478/09/04/2000
LPGFE	FUGITIVE EMISSION	1968
LPGFL	PROCESS VENT	1968
MAERAT	AERATION BASIN	48912
MSSTNKLAND	DPCP FLOATING ROOF TANK LANDINGS	2597
NAPI	OIL-WATER SEPARATOR	48912

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
NEUT1	NEUTRALIZATION	48912
NEUT2	NEUTRALIZATION	48912
NEUT3	NEUTRALIZATION	48912
NEUT4	NEUTRALIZATION	48912
NTFFLRG	VENTS	3219, PSDTX974
NTFFLR	VENTS	3219, PSDTX974
NTFFUG	NTFFUG	18576, 106.261[79604]09/04/2000, 106.262[79604]09/04/2000, 106.492[79604]09/04/2000
OL3FUG	INCLUDES FUG EMISSIONS A327FUG, A328FUG & FTOL911	3214, 106.261[101891]09/04/2000, 106.261[115088]09/04/2000, 106.478[115088]09/04/2000, 106.261[133287]09/04/2000, 106.261[92219]09/04/2000, 106.478/09/04/2000
OP2ACMAP	AC/MAP CONVERTER	3219, PSDTX974
OP2	COOLING WATER TOWER	3219, PSDTX974
OP2DCN	OP2 UNIT DECONTAMINATION	3219, PSDTX974
OP2DECOK2	FURNACE DECOKE VENT	3219, PSDTX974
OP2DECOK	FURNACE DECOKE VENT	3219, PSDTX974

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
OP2DIST	PROCESS VENTS	3219, PSDTX974
OP2ELFLA	FLARE STACK	3219, 106.261[79604]09/04/2000, 106.262[79604]09/04/2000, 106.492[79604]09/04/2000, PSDTX974
OP2FLRG	PROCESS VENTS	3219, PSDTX974
OP2FLR	PROCESS VENTS	3219, PSDTX974
OP2FUG	FUGITIVE EMISSIONS	3219, 106.478/09/04/2000, 106.261[127854]09/04/2000, PSDTX974
OP2MSSFUG	OP2 MSS STREAM FUGITIVE	3219, PSDTX974
OP2PMPDCN	OP2 PUMP DECONTAMINATION	3219, PSDTX974
OP2SAMPL	OP2 SAMPLE LOADING EMISSIONS	3219, PSDTX974
OP3CWT	COOLING WATER TOWER	3214
OP3DCN	OPE UNIT DECONTAMINATION	3219, PSDTX974
OP3ELFLA	FLARE STACK	3219, 106.261[79604]09/04/2000, 106.262[79604]09/04/2000, 106.492[79604]09/04/2000, PSDTX974
OP3GRFLA	FLARE STACK	3219, 106.476/09/04/2000, 106.492/09/04/2000, 106.261[79604]09/04/2000, 106.262[79604]09/04/2000, 106.492[79604]09/04/2000, PSDTX974

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
OP3MSSFUG	OP3MSS STREAM FUGITIVE	3219, PSDTX974
OP3PMPDCN	OP3 PUMP DECONTAMINATION	3219, PSDTX974
OP3SAMPL	OPE SAMPLE LOADING EMISSIONS	3219, PSDTX974
P1309S	SUMP PUMP	48912
P87921	ENGINE	3179
PAU2SD	PHENOL-2 UNIT SHUTDOWN/DECONTAMINATION	3179
PAU3SD	PHENOL-3 UNIT SHUTDOWN/DECONTAMINATION	3179
PAUFE	FUGITIVES	3179, 106.262[77284]09/04/2000, 106.261[77284]09/04/2000, 106.262[100328]09/04/2000, 106.261[100328]09/04/2000, 106.262[108593]09/04/2000, 106.261[108593]09/04/2000, 106.478/09/04/2000
PAUMSSFUG	PAU MSS STREAM FUGITIVE EMISSIONS	3179
PAUPMPDCN	PAU PUMP DECONTAMINATION	3179
PAUSAMPL	PAU EMISSIONS FROM LOADING SAMPLE	3179
PROAERAT	TREATMENT PROCESS	48912
PROAROM	AROMATICS PROCESS UNIT	9334
PROBD3	BDIII PROCESS UNIT	3219, PSDTX974



### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
PRODIST	PROCESS	3985A
PROOXY	OXY PROCESS UNIT	19849, 3173
PROPAU	PAU PROCESS UNIT	3179
PY3FLRG	PROCESS VENTS	3219, PSDTX974
PY3FLR	PROCESS VENTS	3219, PSDTX974
PY3FUG	FUGITIVE EMISSIONS	3214
RCLOAD	LOADING RACK	3179
S13141	BELT FILTER PRESSES	48912
S13142	BELT FILTER PRESSES	48912
S13143	BELT FILTER PRESSES	48912
S332	STORAGE TANK	106.472/09/04/2000
S390	STORAGE TANK	9334, 106.261[109247]09/04/2000, 106.478[109247]09/04/2000
S391	STORAGE TANK	9334, 106.261[109247]09/04/2000, 106.478[109247]09/04/2000
S392	STORAGE TANK	9334, 106.261[109247]09/04/2000, 106.478[109247]09/04/2000
S400	STORAGE TANK	9334, 106.261[109247]09/04/2000, 106.478[109247]09/04/2000

## New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
SAPI	OIL WATER SEPARATOR	48912
SCRWRTC	RAIL CAR LOADING SCRUBBER	3179, 3985A, 106.262[84642]11/01/2003, 106.262[92386]09/04/2000, 106.478[92386]09/04/2000, 106.261[108593]09/04/2000, 106.262[108593]09/04/2000
SCRWRTT	TANK TRUCK LOADING SCRUBBER	3179, 3985A
SETENT	SET WASTEWATER TREATMENT ENTRANCE	48912
SETMSSFUG	STE MSS STREAM FUGITIVE EMISSIONS	48912
SETPMPDCN	SET PUMP DECONTAMINATION	48912
SETSAMPL	SET EMISSIONS FROM LOADING SAMPLE	48912
SITE <sub>3</sub> FE	LOADING FUGITIVES	18576, 080/09/20/1993, 106.261[113881]09/04/2000, 106.262[113881]09/04/2000, 106.261[79604]09/04/2000, 106.262[79604]09/04/2000, 106.492[79604]09/04/2000, 106.492/09/04/2000
SITE <sub>3</sub> FL	PROCESS VENT	3179
SITE <sub>3</sub> TC	DISTRIBUTION LOADING	18576
SITE <sub>3</sub> TT	DISTRIBUTION LOADING	18576
T1301	STORAGE TANK	48912

## New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
T1302	STORAGE TANK	48912
T1310	STORAGE TANK	48912
T13145	BIOSOLIDS TANK	48912
T13146	STORAGE TANK	106.472/09/04/2000
T1318	STORAGE TANK	48912
T1319	STORAGE TANK	48912
T1320	75% PHOSPHORIC ACID TANK	48912
T1331	STORAGE TANK	48912
T1332	STORAGE TANK	48912
T1333	STORAGE TANK	48912
T1334	STORAGE TANK	48912
T182	STORAGE TANK	3179
T19054	98% SULFURIC ACID TANK	48912
T2800	STORAGE TANK	48912
T317	STORAGE TANK	3179
T3272	LIME TANK	48912
T331	STORAGE TANK	3219, 106.262[87173]09/04/2000, 106.261[87173]09/04/2000, PSDTX974

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
T658	STORAGE TANK	3985A
T665A	STORAGE TANK	3179, 106.261[87871]11/01/2003
T74B	STORAGE TANK	3985A, 106.262[92386]09/04/2000, 106.478[92386]09/04/2000, 106.261[108593]09/04/2000, 106.262[108593]09/04/2000
T87000	STORAGE TANK	3179
T87001	STORAGE TANK	106.472/03/14/1997
T87003	STORAGE TANK	3179
T87004	STORAGE TANK	106.472/03/14/1997
T87005	STORAGE TANK	106.472/03/14/1997
T87007	STORAGE TANK	3179
T87100	STORAGE TANK	3179
T87300	STORAGE TANK	3179
T87301	STORAGE TANK	3179, 106.261[87871]11/01/2003
T87302	STORAGE TANK	3179, 106.261[87871]11/01/2003
T87400	STORAGE TANK	3179
T87401	STORAGE TANK	3179
T87500	STORAGE TANK	3179

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
TB3-301-R1	TANK	3217, 106.262[92675]11/01/2003, 106.478[92675]09/04/2000
TBD301	TANK	18576, 106.261[113881]09/04/2000, 106.262[113881]09/04/2000, 106.492/09/04/2000
TBD910	TANK	18576, 106.261[113881]09/04/2000, 106.262[113881]09/04/2000, 106.492/09/04/2000
TBD911	TANK	3217, 106.261[113881]09/04/2000, 106.262[113881]09/04/2000, 106.492/09/04/2000
TBD912	TANK	3217, 106.261[113881]09/04/2000, 106.262[113881]09/04/2000, 106.492/09/04/2000
TBD913	TANK	3217
TC33001	STORAGE TANK	3214
TC33002	STORAGE TANK	3214, 106.472/09/04/2000
TC33003	STORAGE TANK	3214
TC33007	STORAGE TANK	3214
TF34001	STORAGE TANK	3214, 106.261[101891]09/04/2000
TOL301	STORAGE TANK	56496

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
TOL302	STORAGE TANK	56496
TOL303	STORAGE TANK	56496
TOL304	STORAGE TANK	56496
TOL305	STORAGE TANK	56496
TOL3070	STORAGE TANK	106.472/09/04/2000
TOL30900	STORAGE TANK	56496
TOL400	STORAGE TANK	3219, 106.261[102948]09/04/2000, 106.261[129997]09/04/2000, PSDTX974
TOL401	STORAGE TANK	3219, 106.262[87173]09/04/2000, 106.261[87173]09/04/2000, PSDTX974
TOL901	STORAGE TANK	3219, 106.262[130755]09/04/2000, 106.478[130755]09/04/2000, PSDTX974
TOL902	STORAGE TANK	3219, PSDTX974
TOL903	STORAGE TANK	3219, 106.262[87173]09/04/2000, 106.261[87173]09/04/2000, PSDTX974
TOL904	STORAGE TANK	3219, 106.262[87173]09/04/2000, 106.261[87173]09/04/2000, PSDTX974
TOL905	STORAGE TANK	3216, 106.261[113881]09/04/2000, 106.262[113881]09/04/2000, 106.492/09/04/2000, 106.261[76699]03/14/1997,

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
		106.262[76699]03/14/1997
TOL908	STORAGE TANK	3219, PSDTX974
TOL909	STORAGE TANK	3219, 106.261[102948]09/04/2000, 106.262[87173]09/04/2000, 106.261[87173]09/04/2000, PSDTX974
TOL910	STORAGE TANK	3219, 106.261[102948]09/04/2000, 106.262[87173]09/04/2000, 106.261[87173]09/04/2000, PSDTX974
TOL911	STORAGE TANK	2597, 086/09/13/1993, 106.262[130755]09/04/2000, 106.478[130755]09/04/2000
TOL912	STORAGE TANK	3214, 106.472/09/04/2000
TOL913	STORAGE TANK	3214
TOL914	STORAGE TANK	3219, PSDTX974
TOL920	STORAGE TANK	3214106.262[87173]09/04/2000, 106.261[87173]09/04/2000
TR35020	STORAGE TANK	56496
TTLOAD	LOADING RACK	3179
TU30900	STORAGE TANK	56496, 106.261[87871]11/01/2003
TU30901	STORAGE TANK	56496, 106.261[87871]11/01/2003

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
TU30911	STORAGE TANK	3214
TU30913	STORAGE TANK	3214
TUT604	STORAGE TANK	3218, 106.261[78624]09/04/2000
TUT605	TANK	3218, 106.261[78624]09/04/2000
TUT918	STORAGE TANK	3218
V118	PROCESS VENT	3173, 106.261[76265]03/14/1997, 106.262[76265]03/14/1997
V337	PROCESS VENT	9334
V392	PROCESS VENT	3173, 106.261[112344]09/04/2000, 106.262[112344]09/04/2000
V8200	PROCESS VENT	3179
V8201	PROCESS VENT	3179
V8202	PROCESS VENT	3179
V8203	PROCESS VENT	3179
V8204	PROCESS VENT	3179
V8207	PROCESS VENT	3179
V8208	PROCESS VENT	3179
V8209	PROCESS VENT	3179



### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
V8212	PROCESS VENT	3179
V8213	PROCESS VENT	3179
V8217	PROCESS VENT	3179
V8219	PROCESS VENT	3179
V8222	PROCESS VENT	3179
V8223	PROCESS VENT	3179
V8224	PROCESS VENT	3179
V8228	PROCESS VENT	3179
V8231	PROCESS VENT	3179
V8270	PROCESS VENT	3179
V8302	PROCESS VENT	3179
V8303	PROCESS VENT	3179
V8305	PROCESS VENT	3179
V8306	PROCESS VENT	3179
V8307	PROCESS VENT	3179
V8309	PROCESS VENT	3179
V8310	PROCESS VENT	3179
V8319	PROCESS VENT	3179

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
V8321	PROCESS VENT	3179
V8333	PROCESS VENT	3179
V8360	PROCESS VENT	3179
V8362	PROCESS VENT	3179
V87923	PROCESS VENT	3179
VBD901	STORAGE VESSEL	3217
VBD902	STORAGE VESSEL	3217
VBD903	STORAGE VESSEL	3217
VBD920	STORAGE VESSEL	3217
VBD921	STORAGE VESSEL	3217
VBD933	STORAGE VESSEL	3217
VBD934	STORAGE VESSEL	18576, 3217, 106.261[79604]09/04/2000, 106.262[79604]09/04/2000, 106.492[79604]09/04/2000
VBD990	STORAGE VESSEL	3179
VBD991	STORAGE VESSEL	3217
VBD993	STORAGE VESSEL	3179
VBD994	STORAGE VESSEL	3179

## New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
VC33003	OP3 1ST STAGE PGC SUCTION DRUM	3214
VF34003	AC/MAP CONVERTER	3219, PSDTX974
VF34004	AC/MAP CONVERTER	3219, PSDTX974
VF34005	AC/MAP CONVERTER	56496
VF34009	AC/MAP CONVERTER	3219, PSDTX974
VF34010	AC/MAP CONVERTER	3219, PSDTX974
VF34011	AC/MAP CONVERTER	3219, PSDTX974
VIP901	STORAGE VESSEL	18576
VIP902	STORAGE VESSEL	3218
VIP904	STORAGE VESSEL	18576
VIP905	STORAGE VESSEL	18576
VIP950	STORAGE VESSEL	18576
VOL200	OP2 PYROFRACTIONATOR REFLUX DRUM	3219, PSDTX974
VOL201	OP2 QUENCH OIL SURGE DRUM	3219, PSDTX974
VOL250	OP2 PYROFRACTIONATOR REFLUX DRUM	3219, PSDTX974
VOL251	OP2 QUENCH OIL SURGE DRUM	3219, PSDTX974
VOL300	OP2 1ST STAGE PGC (KOL-300) SUCTION DRUM	3219, PSDTX974
VOL350	OP2 1ST STAGE PGC (KOL-350) SUCTION DRUM	3219, PSDTX974

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
VOL411	AC/MAP CONVERTER	3219, PSDTX974
VOL412	AC/MAP CONVERTER	3219, PSDTX974
VP31142	FURNACE DECOKE VENT	3214, 56496
VP31143	OP3 PYROFRACTIONATOR REFLUX DRUM	3214
VP31144	OP3 QUENCH OIL SURGE DRUM	3214
VP31158	STORAGE TANK	56496
VUT109	OLEFINS FUEL GAS	3214
WAERAT	AERATION BASIN	48912
WRACKFE	LOADING FUGITIVES	3179, 3985A
WRTC	DISTRIBUTION LOADING	1968, 19849, 3173
WRTCDMK	ACETONE RAIL CAR LOADING	3179
WRTCECH	DISTRIBUTION LOADING	3985A
WRTCMEK	DISTRIBUTION LOADING	3985A
WRTT	DISTRIBUTION LOADING	1968, 19849, 053/06/07/1996, 118/06/07/1996
WRTTDMK	ACETONE TANK TRUCK LOADING	3179
WRTTECH	DISTRIBUTION LOADING	3985A
WRTTMEK	DISTRIBUTION LOADING	3985A

### **New Source Review Authorization References by Emissions Unit**

The following is a list of New Source Review (NSR) authorizations for this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

<b>Unit/Group/Process ID No.</b>	<b>Emission Unit Name/Description</b>	<b>New Source Review Authorization**</b>
X303	STORAGE TANK	9334
X304	STORAGE TANK	9334
X308	STORAGE TANK	3179
X8529A	PROCESS VENT	3178
X8529B	PROCESS VENT	3178

\*\*This column may include Permit by Rule (PBR) numbers and version dates, PBR or Standard Permit Registration numbers in brackets, Minor NSR permit numbers, and Major NSR permit numbers.

**Appendix A**

**Acronym List ..... 589**

## Acronym List

The following abbreviations or acronyms may be used in this permit:

ACFM	.....	actual cubic feet per minute
AMOC	.....	alternate means of control
ARP	.....	Acid Rain Program
ASTM	.....	American Society of Testing and Materials
B/PA	.....	Beaumont/Port Arthur (nonattainment area)
CAM	.....	Compliance Assurance Monitoring
CD	.....	control device
COMS	.....	continuous opacity monitoring system
CVS	.....	closed-vent system
D/FW	.....	Dallas/Fort Worth (nonattainment area)
DR	.....	Designated Representative
EIP	.....	El Paso (nonattainment area)
EP	.....	emission point
EPA	.....	U.S. Environmental Protection Agency
EU	.....	emission unit
FCAA Amendments	.....	Federal Clean Air Act Amendments
FOP	.....	federal operating permit
GF	.....	grandfathered
gr/100 scf	.....	grains per 100 standard cubic feet
HAP	.....	hazardous air pollutant
H/G/B	.....	Houston/Galveston/Brazoria (nonattainment area)
H <sub>2</sub> S	.....	hydrogen sulfide
ID No.	.....	identification number
lb/hr	.....	pound(s) per hour
MMBtu/hr	.....	Million British thermal units per hour
MRRT	.....	monitoring, recordkeeping, reporting, and testing
NA	.....	nonattainment
N/A	.....	not applicable
NADB	.....	National Allowance Data Base
NO <sub>x</sub>	.....	nitrogen oxides
NSPS	.....	New Source Performance Standard (40 CFR Part 60)
NSR	.....	New Source Review
ORIS	.....	Office of Regulatory Information Systems
Pb	.....	lead
PBR	.....	Permit By Rule
PM	.....	particulate matter
ppmv	.....	parts per million by volume
PSD	.....	prevention of significant deterioration
RO	.....	Responsible Official
SO <sub>2</sub>	.....	sulfur dioxide
TCEQ	.....	Texas Commission on Environmental Quality
TSP	.....	total suspended particulate
TVP	.....	true vapor pressure
U.S.C.	.....	United States Code
VOC	.....	volatile organic compound

**Appendix B**

**Major NSR Summary Table.....591**



## Major NSR Summary Table

Permit Number: 37206 and PSDTX896 (Version Date: 02/09/2010)							
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
H87920	Phenol / Acetone Plant Boiler	NO <sub>x</sub>	37.00	150.90	6,8,13,14,15	5,14,15,21,22	14,15
H87920	Phenol / Acetone Plant Boiler	SO <sub>2</sub>	7.60	33.00	6,8,13,14,18	5,14,21,22	14,18
H87920	Phenol / Acetone Plant Boiler	CO	32.30	127.90	6,8,13,14,16,17,19	5,14,16,21,22	14
H87920	Phenol / Acetone Plant Boiler	VOC	1.30	5.40	6,8,13,14	5,14,21,22	14
H87920	Phenol / Acetone Plant Boiler	PM/PM <sub>10</sub>	12.30 (4) 65.00 (5)	48.50	2,6,8,13,14	2,5,14,21,22	14
FUGBIFBOIL	Piping Fugitives (6)	VOC	0.10	0.41	20	20	

(1) Emission point identification – either specific equipment designation or emission point number from plot plan.  
 (2) Specific point source name. For fugitive sources use area name or fugitive source name.  
 (3) CO - carbon monoxide  
     PM - particulate matter suspended in the atmosphere, including PM<sub>10</sub>  
     PM<sub>10</sub> – particulate matter equal to or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no particulate matter greater than 10 microns is emitted.  
 (4) Pound per hour emission rate without soot blowing.  
 (5) Pound per hour emission rate during soot blowing.  
 (6) Fugitive emissions are an estimate only.

\* Emission rates are based on and the facilities are limited by the following maximum operating schedule:  
     Hrs/day 24    Days/week 7    Weeks/year 52

\*\* Compliance with annual emission limits is based on a rolling 12-month period.

## Major NSR Summary Table

Permit Number: 3219 and PSDTX974 (Version Date: 06/06/2011)							
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
AP3	Gas Oil Storage Tank	VOC	0.70	2.10			
FOL100	Pyrolysis Furnace	CO (5)	12.60	50.80	16,17	16,17	16,17
FOL100	Pyrolysis Furnace	NH <sub>3</sub>	1.80	3.90			
FOL100	Pyrolysis Furnace	NO <sub>x</sub> ***	25.20	381.00	16,17	16,17	16,17
FOL100	Pyrolysis Furnace	PM <sub>10</sub> (5)	3.30	13.20			
FOL100	Pyrolysis Furnace	SO <sub>2</sub>	1.20	5.00			
FOL100	Pyrolysis Furnace	VOC	0.10	0.20			
FOL110	Pyrolysis Furnace	CO (5)	12.60	50.80	16,17	16,17	16,17
FOL110	Pyrolysis Furnace	NH <sub>3</sub>	1.80	3.90			
FOL110	Pyrolysis Furnace	NO <sub>x</sub> ***	25.20	381.00	16,17	16,17	16,17
FOL110	Pyrolysis Furnace	PM <sub>10</sub> (5)	3.30	13.20			
FOL110	Pyrolysis Furnace	SO <sub>2</sub>	1.20	5.00			
FOL110	Pyrolysis Furnace	VOC	0.10	0.20			
FOL120	Pyrolysis Furnace	CO (5)	12.60	50.80	16,17	16,17	16,17
FOL120	Pyrolysis Furnace	NH <sub>3</sub>	1.80	3.90			
FOL120	Pyrolysis Furnace	NO <sub>x</sub> ***	25.20	381.00	16,17	16,17	16,17
FOL120	Pyrolysis Furnace	PM <sub>10</sub> (5)	3.30	13.20			
FOL120	Pyrolysis Furnace	SO <sub>2</sub>	1.20	5.00			
FOL120	Pyrolysis Furnace	VOC	0.10	0.20			
FOL130	Pyrolysis Furnace	CO (5)	12.60	50.80	16,17	16,17	16,17
FOL130	Pyrolysis Furnace	NH <sub>3</sub>	1.80	3.90			
FOL130	Pyrolysis Furnace	NO <sub>x</sub> ***	25.20	381.00	16,17	16,17	16,17

## Major NSR Summary Table

Permit Number: 3219 and PSDTX974 (Version Date: 06/06/2011)							
Emission Point No. (1)	Source Name (2)	Air Contaminant	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
		Name (3)					
FOL130	Pyrolysis Furnace	PM <sub>10</sub> (5)	3.30	13.20			
FOL130	Pyrolysis Furnace	SO <sub>2</sub>	1.20	5.00			
FOL130	Pyrolysis Furnace	VOC	0.10	0.20			
FOL140	Pyrolysis Furnace	CO (5)	12.60	50.80	16,17	16,17	16,17
FOL140	Pyrolysis Furnace	NH <sub>3</sub>	1.80	3.90			
FOL140	Pyrolysis Furnace	NO <sub>x</sub> ***	25.20	381.00	16,17	16,17	16,17
FOL140	Pyrolysis Furnace	PM <sub>10</sub> (5)	3.30	13.20			
FOL140	Pyrolysis Furnace	SO <sub>2</sub>	1.20	5.00			
FOL140	Pyrolysis Furnace	VOC	0.10	0.20			
FOL150	Pyrolysis Furnace	CO (5)	12.60	50.80	16,17	16,17	16,17
FOL150	Pyrolysis Furnace	NH <sub>3</sub>	1.80	3.90			
FOL150	Pyrolysis Furnace	NO <sub>x</sub> ***	25.20	381.00	16,17	16,17	16,17
FOL150	Pyrolysis Furnace	PM <sub>10</sub> (5)	3.30	13.20			
FOL150	Pyrolysis Furnace	SO <sub>2</sub>	1.20	5.00			
FOL150	Pyrolysis Furnace	VOC	0.10	0.20			
FOL160	Pyrolysis Furnace	CO (5)	12.60	50.80	16,17	16,17	16,17
FOL160	Pyrolysis Furnace	NH <sub>3</sub>	1.80	3.90			
FOL160	Pyrolysis Furnace	NO <sub>x</sub> ***	25.20	381.00	16,17	16,17	16,17
FOL160	Pyrolysis Furnace	PM <sub>10</sub> (5)	3.30	13.20			
FOL160	Pyrolysis Furnace	SO <sub>2</sub>	1.20	5.00			
FOL160	Pyrolysis Furnace	VOC	0.10	0.20			
FOL170	Pyrolysis Furnace	CO (5)	12.60	50.80	16,17	16,17	16,17

## Major NSR Summary Table

Permit Number: 3219 and PSDTX974 (Version Date: 06/06/2011)							
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
FOL170	Pyrolysis Furnace	NH <sub>3</sub>	1.80	3.90			
FOL170	Pyrolysis Furnace	NO <sub>x</sub> ***	25.20	381.00	16,17	16,17	16,17
FOL170	Pyrolysis Furnace	PM <sub>10</sub> (5)	3.30	13.20			
FOL170	Pyrolysis Furnace	SO <sub>2</sub>	1.20	5.00			
FOL170	Pyrolysis Furnace	VOC	0.10	0.20			
FOL180	Pyrolysis Furnace	CO (5)	12.60	50.80	16,17	16,17	16,17
FOL180	Pyrolysis Furnace	NH <sub>3</sub>	1.80	3.90			
FOL180	Pyrolysis Furnace	NO <sub>x</sub> ***	25.20	381.00	16,17	16,17	16,17
FOL180	Pyrolysis Furnace	PM <sub>10</sub> (5)	3.30	13.20			
FOL180	Pyrolysis Furnace	SO <sub>2</sub>	1.20	5.00			
FOL180	Pyrolysis Furnace	VOC	0.10	0.20			
FOL190	Pyrolysis Furnace	CO (5)	12.60	50.80	16,17	16,17	16,17
FOL190	Pyrolysis Furnace	NH <sub>3</sub>	1.80	3.90			
FOL190	Pyrolysis Furnace	NO <sub>x</sub> ***	25.20	381.00	16,17	16,17	16,17
FOL190	Pyrolysis Furnace	PM <sub>10</sub> (5)	3.30	13.20			
FOL190	Pyrolysis Furnace	SO <sub>2</sub>	1.20	5.00			
FOL190	Pyrolysis Furnace	VOC	0.10	0.20			
OP2FUR10	Ten Pyrolysis Furnaces	NO <sub>x</sub> ***		381.00	16,17	16,17	16,17
K306	Pitch Storage Tank	VOC	10.80	4.60			
K307	Pitch Storage Tank	VOC	10.80	4.60			
OP2	Cooling Water Tower (4)	VOC	5.44	24.30	6	6	
OP2DECOK	OP-2 Furnace Decoking Vent	CO (5)	60.42	108.75			

## Major NSR Summary Table

Permit Number: 3219 and PSDTX974 (Version Date: 06/06/2011)							
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
OP2DECOK	OP-2 Furnace Decoking Vent	NO <sub>x</sub>	0.25	0.50			
OP2DECOK	OP-2 Furnace Decoking Vent	PM <sub>10</sub> (5)	1.21	2.18			
OP2DECOK	OP-2 Furnace Decoking Vent	VOC	0.08	0.15			
OP2ELFLA, OP3ELFLA, and OP3GRFLA	OP-2 Elevated Flare, OP-3 Elevated Flare, and OP-3 Ground Flare	CO (5)	287.00 (6) 4075.22 (7)	235.05 (6)(7)	8,12,19	4,8,10,11,14,19	
OP2ELFLA, OP3ELFLA, and OP3GRFLA	OP-2 Elevated Flare, OP-3 Elevated Flare, and OP-3 Ground Flare	H <sub>2</sub> S	5.13	7.80 (6)(7)	8,12,19	4,8,10,11,14,19	
OP2ELFLA, OP3ELFLA, and OP3GRFLA	OP-2 Elevated Flare, OP-3 Elevated Flare, and OP-3 Ground Flare	NO <sub>x</sub>	56.00 (6) 791.08 (7)	46.56 (6)(7)	8,12,19	4,8,10,11,14,19	
OP2ELFLA, OP3ELFLA, and OP3GRFLA	OP-2 Elevated Flare, OP-3 Elevated Flare, and OP-3 Ground Flare	SO <sub>2</sub>	483.00	736.00 (6)(7)	8,12,19	4,8,10,11,14,19	
OP2ELFLA, OP3ELFLA, and OP3GRFLA	OP-2 Elevated Flare, OP-3 Elevated Flare, and OP-3 Ground Flare	VOC	464.00 (6) 3740.10 (7)	344.15 (6)(7)	8,12,19	4,8,10,11,14,19	
T331	Blended Pitch Tank	VOC	10.80	4.60		18	
TOL400	Flush oil Storage	VOC	0.20	0.20		18	
TOL401	Alcohol Storage Tank	VOC	14.50	0.10		18	
TOL901	Algerian Condensate	VOC	2.70	5.70		18	

## Major NSR Summary Table

Permit Number: 3219 and PSDTX974 (Version Date: 06/06/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
TOL902	Gas Oil Storage Tank	VOC	74.80	25.10		18	
TOL903	Gas Oil Storage Tank	VOC	74.80	7.80		18	
TOL904	Recovered Oil Storage Tank	VOC	0.30	0.64		18	
TOL908	Pitch Storage Tank	VOC	2.45	3.40		18	
TOL909	Gas Oil Storage Tank	VOC	0.24	0.20		18	
TOL910	Gas Oil Storage Tank	VOC	0.14	0.10		18	
TOL914	Pitch Storage Tank	VOC	6.40	32.25		18	
VOL411/412	OP-2 AC/MAP Converter Regeneration Vent	CO (5)	2.60	2.90			
OP2FUG	Op-2 Process Fugitives (4)	NH <sub>3</sub>	0.34	1.49	2,3,13	2,3,13	
OP2FUG	Op-2 Process Fugitives (4)	VOC	9.70	42.50	2,3,13	2,3,13	
OP2DCN	OP-2 Unit Decontamination (7)	H <sub>2</sub> S	0.50	0.01	12	10,11,14	
OP2DCN	OP-2 Unit Decontamination (7)	VOC (8)	27.31	0.05	12	10,11,14	
OP2DCN	OP-2 Unit Decontamination (7)	Benzene	0.95	0.01	12	10,11,14	
OP2MSSFUG	OP-2 Maintenance, Startup, and Shutdown (MSS) Stream Fugitive (7)(4)	VOC (8)	5.18	0.62	12	10,11,14	
OP2MSSFUG	OP-2 Maintenance, Startup, and Shutdown (MSS) Stream Fugitive (7)(4)	Benzene	0.18	0.02	12	10,11,14	

## Major NSR Summary Table

Permit Number: 3219 and PSDTX974 (Version Date: 06/06/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
OP2PMPDC N	OP-2 Equipment/Vessel Decontamination (7)	VOC (8)	15.00	0.08	12	10,11,14	
OP2PMPDC N	OP-2 Equipment/Vessel Decontamination (7)	Benzene	0.52	0.01	12	10,11,14	
OP2SAMPL	OP-2 Sample Loading Emissions (7)	VOC	0.09	0.02	12	10,11,14	
OP2SAMPL	OP-2 Sample Loading Emissions (7)	Benzene	0.01	0.01	12	10,11,14	
OP3DCN	OP-3 Unit Decontamination (7)	H2S	0.70	0.01	12	10,11,14	
OP3DCN	OP-3 Unit Decontamination (7)	VOC (8)	38.31	0.08	12	10,11,14	
OP3DCN	OP-3 Unit Decontamination (7)	Benzene	1.33	0.01	12	10,11,14	
OP3MSSFUG	OP-3 MSS Stream Fugitives (7)(4)	VOC (8)	5.18	0.62	12	10,11,14	
OP3MSSFUG	OP-3 MSS Stream Fugitives (7)(4)	Benzene	0.18	0.02	12	10,11,14	
OP3PMPDC N	OP-3 Equipment/Vessel Decontamination (7)	VOC (8)	15.00	0.08	12	10,11,14	
OP3PMPDC N	OP-3 Equipment/Vessel Decontamination (7)	Benzene	0.52	0.01	12	10,11,14	
OP3SAMPL	OP-3 Sample Loading Emissions (7)	VOC (8)	0.09	0.02	12	10,11,14	
OP3SAMPL	OP-3 Sample Loading Emissions (7)	Benzene	0.01	0.01	12	10,11,14	

## Major NSR Summary Table

Permit Number: 3219 and PSDTX974 (Version Date: 06/06/2011)						
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
<p>(1) Emission point identification – either specific equipment designation or emission point number from plot plan.</p> <p>(2) Specific point source name. For fugitive sources use area name or fugitive source name.</p> <p>(3) CO - carbon monoxide  H<sub>2</sub>S - hydrogen sulfide  NH<sub>3</sub> - ammonia  NO<sub>x</sub> - total oxides of nitrogen  PM - particulate matter, suspended in the atmosphere, including PM<sub>10</sub>  PM<sub>10</sub> - particulate matter equal to or less than 10 microns in diameter  SO<sub>2</sub> - sulfur oxides  VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code §101.1</p> <p>(4) Emission Point Nos. (EPNs) OP2, OP2MSSFUG, and OP3MSSFUG are subject to the following mandate: Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.</p> <p>(5) PSDTX974</p> <p>(6) Emissions from the combined EPNs OP2ELFLA, OP3ELFLA, and OP3GRFLA include routine emissions as well as maintenance, start-up, and shutdown (MSS) emissions authorized on December 21, 2007.</p> <p>(7) MSS emissions are authorized in the amendment application, Form PI-1, dated January 3, 2008.</p> <p>(8) The VOC rates include the benzene rates which follow</p> <p style="margin-left: 40px;">* Emission rates are based on and the facilities are limited by the following maximum operating schedule:  Hrs/day 24    Days/week 7    Weeks/year 52</p> <p style="margin-left: 40px;">** Compliance with annual emission limits is based on a rolling 12-month period.</p> <p style="margin-left: 40px;">*** Ten furnaces are limited to the combined annual emission rate of 381.00 tpy and listed under EPN OP2FUR10</p>						



## Major NSR Summary Table

Permit Number: 37206 and PSDTX896 (Version Date: 02/09/2010)							
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
H87920	Phenol / Acetone Plant Boiler	NO <sub>x</sub>	37.00	150.90	6,8,13,14,15	5,14,15,21,22	14,15
H87920	Phenol / Acetone Plant Boiler	SO <sub>2</sub>	7.60	33.00	6,8,13,14,18	5,14,21,22	14,18
H87920	Phenol / Acetone Plant Boiler	CO	32.30	127.90	6,8,13,14,16,17,19	5,14,16,21,22	14
H87920	Phenol / Acetone Plant Boiler	VOC	1.30	5.40	6,8,13,14	5,14,21,22	14
H87920	Phenol / Acetone Plant Boiler	PM/PM <sub>10</sub>	12.30 (4) 65.00 (5)	48.50	2,6,8,13,14	2,5,14,21,22	14
FUGBIFBOIL	Piping Fugitives (6)	VOC	0.10	0.41	20	20	

(1) Emission point identification – either specific equipment designation or emission point number from plot plan.  
 (2) Specific point source name. For fugitive sources use area name or fugitive source name.  
 (3) CO - carbon monoxide  
     PM - particulate matter suspended in the atmosphere, including PM<sub>10</sub>  
     PM<sub>10</sub> – particulate matter equal to or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no particulate matter greater than 10 microns is emitted.  
 (4) Pound per hour emission rate without soot blowing.  
 (5) Pound per hour emission rate during soot blowing.  
 (6) Fugitive emissions are an estimate only.

\* Emission rates are based on and the facilities are limited by the following maximum operating schedule:  
     Hrs/day 24    Days/week 7    Weeks/year 52

\*\* Compliance with annual emission limits is based on a rolling 12-month period.

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
A1006	H <sub>2</sub> S Point Analyzer	CO (5)	777.95	2688.22		30	30
A1006	H <sub>2</sub> S Point Analyzer	VOC	1877.69	2846.90		30	30
A102	Analyzer	VOC	1877.69	2846.90		30	30
A10823	CCU CO Analyzer	NO <sub>x</sub>	495.45	1825.00		30	30
A10823	CCU CO Analyzer	CO (5)	777.95	2688.22		30	30
A10823	CCU CO Analyzer	PM	77.13	272.80		30	30
A10823	CCU CO Analyzer	SO <sub>2</sub>	2050.72	5259.84		30	30
A10823	CCU CO Analyzer	VOC	1877.69	2846.90		30	30
A10824	CO Analyzer	NO <sub>x</sub>	495.45	1825.00		30	30
A10824	CO Analyzer	CO (5)	777.95	2688.22		30	30
A10824	CO Analyzer	PM	77.13	272.80		30	30
A10824	CO Analyzer	SO <sub>2</sub>	2050.72	5259.84		30	30
A10824	CO Analyzer	VOC	1877.69	2846.90		30	30
A10825	O <sub>2</sub> Analyzer	NO <sub>x</sub>	495.45	1825.00		30	30
A10825	O <sub>2</sub> Analyzer	PM	77.13	272.80		30	30
A10825	O <sub>2</sub> Analyzer	CO (5)	777.95	2688.22		30	30
A10825	O <sub>2</sub> Analyzer	SO <sub>2</sub>	2050.72	5259.84		30	30
A10825	O <sub>2</sub> Analyzer	VOC	1877.69	2846.90		30	30
A10502	CCU SNCR NO <sub>x</sub> /SO <sub>2</sub> /O <sub>2</sub> Analyzer	NO <sub>x</sub>	495.45	1825.00		30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
A10502	CCU SNCR NO <sub>x</sub> /SO <sub>2</sub> /O <sub>2</sub> Analyzer	CO (5)	777.95	2688.22		30	30
A10502	CCU SNCR NO <sub>x</sub> /SO <sub>2</sub> /O <sub>2</sub> Analyzer	PM	77.13	272.80		30	30
A10502	CCU SNCR NO <sub>x</sub> /SO <sub>2</sub> /O <sub>2</sub> Analyzer	SO <sub>2</sub>	2050.72	5259.84		30	30
A10502	CCU SNCR NO <sub>x</sub> /SO <sub>2</sub> /O <sub>2</sub> Analyzer	VOC	1877.69	2846.90		30	30
A1284	Debut. Tops Analyzer	VOC	1877.69	2846.90		30	30
A1284	Debut. Tops Analyzer	H <sub>2</sub> S	29.61	85.77		30	30
A1301	PSA Product H <sub>2</sub> Analyzer	VOC	1877.69	2846.90	4	4,30	4,30
A162	H5301 O <sub>2</sub> Analyzer	NO <sub>x</sub>	495.45	1825.00		30	30
A162	H5301 O <sub>2</sub> Analyzer	CO (5)	777.95	2688.22		30	30
A162	H5301 O <sub>2</sub> Analyzer	PM	77.13	272.80		30	30
A162	H5301 O <sub>2</sub> Analyzer	SO <sub>2</sub>	2050.72	5259.84		30	30
A162	H5301 O <sub>2</sub> Analyzer	VOC	1877.69	2846.90		30	30
A1745	SR-3/4 SO <sub>2</sub> CEMS Analyzer	SO <sub>2</sub>	2050.72	5259.84		30	30
A1745	SR-3/4 SO <sub>2</sub> CEMS Analyzer	VOC	1877.69	2846.90		30	30
A1760	H <sub>2</sub> S Analyzer	VOC	1877.69	2846.90		30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
A1760	H <sub>2</sub> S Analyzer	H <sub>2</sub> S	29.61	85.77		30	30
A180	H5302 O <sub>2</sub> Analyzer	NO <sub>x</sub>	495.45	1825.00		30	30
A180	H5302 O <sub>2</sub> Analyzer	CO (5)	777.95	2688.22		30	30
A180	H5302 O <sub>2</sub> Analyzer	PM	77.13	272.80		30	30
A180	H5302 O <sub>2</sub> Analyzer	SO <sub>2</sub>	2050.72	5259.84		30	30
A180	H5302 O <sub>2</sub> Analyzer	VOC	1877.69	2846.90		30	30
A1905/6	A1905/6 Analyzer	VOC	1877.69	2846.90		30	30
A213	CR3 Recycle Gas SG Analyzer	VOC	1877.69	2846.90		30	30
A213	CR3 Recycle Gas SG Analyzer	Benzene	10.96	30.36		30	30
A214	CR3 Recycle Gas Moisture	VOC	1877.69	2846.90		30	30
A214	CR3 Recycle Gas Moisture	Benzene	10.96	30.36		30	30
A236	H5305 O <sub>2</sub> Analyzer	NO <sub>x</sub>	495.45	1825.00		30	30
A236	H5305 O <sub>2</sub> Analyzer	CO (5)	777.95	2688.22		30	30
A236	H5305 O <sub>2</sub> Analyzer	PM	77.13	272.80		30	30
A236	H5305 O <sub>2</sub> Analyzer	SO <sub>2</sub>	2050.72	5259.84		30	30
A236	H5305 O <sub>2</sub> Analyzer	VOC	1877.69	2846.90		30	30
A298	CR3 Regen Gas O <sub>2</sub> Analyzer	VOC	1877.69	2846.90		30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
A298	CR3 Regen Gas O <sub>2</sub> Analyzer	Benzene	10.96	30.36		30	30
A300	CR3 Regen Gas Comb. Analyzer	VOC	1877.69	2846.90		30	30
A300	CR3 Regen Gas Comb. Analyzer	Benzene	10.96	30.36		30	30
A329	CR3 Reactor Inlet O <sub>2</sub> Analyzer	VOC	1877.69	2846.90		30	30
A34160	CR-3 Furnaces CEMS Analyzer	NO <sub>x</sub>	495.45	1825.00		30	30
A34160	CR-3 Furnaces CEMS Analyzer	CO (5)	777.95	2688.22		30	30
A34160	CR-3 Furnaces CEMS Analyzer	PM	77.13	272.80		30	30
A34160	CR-3 Furnaces CEMS Analyzer	SO <sub>2</sub>	2050.72	5259.84		30	30
A34160	CR-3 Furnaces CEMS Analyzer	VOC	1877.69	2846.90		30	30
A553	PLAT2 Rec. Gas Gravity Analyzer	VOC	1877.69	2846.90		30	30
A554	PLAT2 Rec. Gas Gravity Analyzer	VOC	1877.69	2846.90		30	30
A785	H5303 O <sub>2</sub> Analyzer	NO <sub>x</sub>	495.45	1825.00		30	30
A785	H5303 O <sub>2</sub> Analyzer	CO (5)	777.95	2688.22		30	30
A785	H5303 O <sub>2</sub> Analyzer	PM	77.13	272.80		30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
A785	H5303 O <sub>2</sub> Analyzer	SO <sub>2</sub>	2050.72	5259.84		30	30
A785	H5303 O <sub>2</sub> Analyzer	VOC	1877.69	2846.90		30	30
A786	H5304 O <sub>2</sub> Analyzer	NO <sub>x</sub>	495.45	1825.00		30	30
A786	H5304 O <sub>2</sub> Analyzer	CO (5)	777.95	2688.22		30	30
A786	H5304 O <sub>2</sub> Analyzer	PM	77.13	272.80		30	30
A786	H5304 O <sub>2</sub> Analyzer	SO <sub>2</sub>	2050.72	5259.84		30	30
A786	H5304 O <sub>2</sub> Analyzer	VOC	1877.69	2846.90		30	30
A842	Tank SS307 Blanket O <sub>2</sub> Analyzer	VOC	1877.69	2846.90		30	30
A89128	Tank SS314 Blanket O <sub>2</sub> Analyzer	VOC	1877.69	2846.90		30	30
AE2340	Octane Testing Engine	NO <sub>x</sub>	495.45	1825.00		30	30
AE2340	Octane Testing Engine	CO (5)	777.95	2688.22		30	30
AE2340	Octane Testing Engine	PM	77.13	272.80		30	30
AE2340	Octane Testing Engine	SO <sub>2</sub>	2050.72	5259.84		30	30
AE2340	Octane Testing Engine	VOC	1877.69	2846.90		30	30
AE2636	Octane Testing Engine	NO <sub>x</sub>	495.45	1825.00		30	30
AE2636	Octane Testing Engine	CO (5)	777.95	2688.22		30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
AE2636	Octane Testing Engine	PM	77.13	272.80		30	30
AE2636	Octane Testing Engine	SO <sub>2</sub>	2050.72	5259.84		30	30
AE2636	Octane Testing Engine	VOC	1877.69	2846.90		30	30
AE2650	Octane Testing Engine	NO <sub>x</sub>	495.45	1825.00		30	30
AE2650	Octane Testing Engine	CO (5)	777.95	2688.22		30	30
AE2650	Octane Testing Engine	PM	77.13	272.80		30	30
AE2650	Octane Testing Engine	SO <sub>2</sub>	2050.72	5259.84		30	30
AE2650	Octane Testing Engine	VOC	1877.69	2846.90		30	30
AE348	On-line Knock Engine	NO <sub>x</sub>	495.45	1825.00		30	30
AE348	On-line Knock Engine	CO (5)	777.95	2688.22		30	30
AE348	On-line Knock Engine	PM	77.13	272.80		30	30
AE348	On-line Knock Engine	SO <sub>2</sub>	2050.72	5259.84		30	30
AE348	On-line Knock Engine	VOC	1877.69	2846.90		30	30
AE349	On-line Knock Engine	NO <sub>x</sub>	495.45	1825.00		30	30
AE349	On-line Knock Engine	CO (5)	777.95	2688.22		30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
AE349	On-line Knock Engine	PM	77.13	272.80		30	30
AE349	On-line Knock Engine	SO <sub>2</sub>	2050.72	5259.84		30	30
AE349	On-line Knock Engine	VOC	1877.69	2846.90		30	30
AE388	On-line Knock Engine	NO <sub>x</sub>	495.45	1825.00		30	30
AE388	On-line Knock Engine	CO (5)	777.95	2688.22		30	30
AE388	On-line Knock Engine	PM	77.13	272.80		30	30
AE388	On-line Knock Engine	SO <sub>2</sub>	2050.72	5259.84		30	30
AE388	On-line Knock Engine	VOC	1877.69	2846.90		30	30
AE389	On-line Knock Engine	NO <sub>x</sub>	495.45	1825.00		30	30
AE389	On-line Knock Engine	CO (5)	777.95	2688.22		30	30
AE389	On-line Knock Engine	PM	77.13	272.80		30	30
AE389	On-line Knock Engine	SO <sub>2</sub>	2050.72	5259.84		30	30
AE389	On-line Knock Engine	VOC	1877.69	2846.90		30	30
AE700	Octane Testing Engine	NO <sub>x</sub>	495.45	1825.00		30	30
AE700	Octane Testing Engine	CO (5)	777.95	2688.22		30	30



Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
AE700	Octane Testing Engine	PM	77.13	272.80		30	30
AE700	Octane Testing Engine	SO <sub>2</sub>	2050.72	5259.84		30	30
AE700	Octane Testing Engine	VOC	1877.69	2846.90		30	30
AE768	Octane Testing Engine	NO <sub>x</sub>	495.45	1825.00		30	30
AE768	Octane Testing Engine	CO (5)	777.95	2688.22		30	30
AE768	Octane Testing Engine	VOC	1877.69	2846.90		30	30
AP1	AP1 Storage Tank	VOC	1877.69	2846.90		30	30
AP16	AP16 Storage Tank	VOC	1877.69	2846.90		30	30
AP16	AP16 Storage Tank	Benzene	10.96	30.36		30	30
AP16	AP16 Storage Tank	H <sub>2</sub> S	29.61	85.77		30	30
AP17	AP17 Storage Tank	VOC	1877.69	2846.90		30	30
AP17	AP17 Storage Tank	Benzene	10.96	30.36		30	30
AP17	AP17 Storage Tank	H <sub>2</sub> S	29.61	85.77		30	30
AP2	AP2 Storage Tank	VOC	1877.69	2846.90		30	30
AP4	AP4 Storage Tank	VOC	1877.69	2846.90		30	30
AP5	AP5 Storage Tank	VOC	1877.69	2846.90	4	4,30	4,30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
AP6	AP6 Storage Tank	VOC	1877.69	2846.90	4	4,30	4,30
AP6	AP6 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
AP7	AP7 Storage Tank	VOC	1877.69	2846.90	4	4,30	4,30
AP8	AP7 Storage Tank	VOC	1877.69	2846.90	4	4,30	4,30
AP8	AP8 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	30
AYARDOWS	WW – Sewer A Yard Oily Water	VOC	1877.69	2846.90		30	30
AYARDOWS	WW – Sewer A Yard Oily Water	Benzene	10.96	30.36	3,4	3,4,30	3,4,30
AYARDOWS	WW – Sewer A Yard Oily Water	NH <sub>3</sub>	5.44	23.74		30	30
BARGE	Marine Loading – Barge Docks	VOC	1877.69	2846.90	4	4,30	4,30
BARGE	Marine Loading – Barge Docks	Benzene	10.96	30.36	4	4,30	4,30
BARGE	Marine Loading – Barge Docks	H <sub>2</sub> S	29.61	85.77		30	30
BENZENE1	Marine Loading – Benzene Dock 1	VOC	1877.69	2846.90	4	4,30	4,30
BENZENE1	Marine Loading – Benzene Dock 1	Benzene	10.96	30.36	4	4,30	4,30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
BENZENE1	Marine Loading – Benzene Dock 1	H <sub>2</sub> S	29.61	85.77		30	30
BENZENE2	Marine Loading – Benzene Dock 2	VOC	1877.69	2846.90	4	4,30	4,30
BENZENE2	Marine Loading – Benzene Dock 2	Benzene	10.96	30.36	4	4,30	4,30
BENZENE2	Marine Loading – Benzene Dock 2	H <sub>2</sub> S	29.61	85.77		30	30
BENZENE4	Marine Loading – Benzene Dock 4	VOC	1877.69	2846.90	4	4,30	4,30
BENZENE4	Marine Loading – Benzene Dock 4	Benzene	10.96	30.36	4	4,30	4,30
BENZENE4	Marine Loading – Benzene Dock 4	H <sub>2</sub> S	29.61	85.77		30	30
BYARDOWS	WW – Sewer B Yard Oily Water	VOC	1877.69	2846.90		30	30
BYARDOWS	WW – Sewer B Yard Oily Water	Benzene	10.96	30.36	3,4	3,4,30	3,4,30
BYARDOWS	WW – Sewer B Yard Oily Water	H <sub>2</sub> S	29.61	85.77		30	30
BYARDOWS	WW – Sewer B Yard Oily Water	NH <sub>3</sub>	5.44	23.74		30	30
C9150/51	C9150/51 Vent	VOC	1877.69	2846.90		30	30
C9150/51	C9150/51 Vent	H <sub>2</sub> S	29.61	85.77		30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
C9152/53	C9152/53 Vent	VOC	1877.69	2846.90		30	30
C9152/53	C9152/53 Vent	H <sub>2</sub> S	29.61	85.77		30	30
CCLP	WW – Cat Cracker Lube Plant	VOC	1877.69	2846.90		30	30
CCLP	WW – Cat Cracker Lube Plant	Benzene	10.96	30.36	3,4	3,4,30	3,4,30
CCLP	WW – Cat Cracker Lube Plant	NH <sub>3</sub>	5.44	23.74		30	30
CPI1	WW – CP1 Oil Water Separator	VOC	1877.69	2846.90		30	30
CPI1	WW – CP1 Oil Water Separator	Benzene	10.96	30.36	3,4	3,4,30	3,4,30
CPI1	WW – CP1 Oil Water Separator	NH <sub>3</sub>	5.44	23.74		30	30
CPI2	WW – CP1 Oil Water Separator	VOC	1877.69	2846.90		30	30
CPI2	WW – CP1 Oil Water Separator	Benzene	10.96	30.36	3,4	3,4,30	3,4,30
CPI2	WW – CP1 Oil Water Separator	NH <sub>3</sub>	5.44	23.74		30	30
CRUDE	Marine Loading – Crude Docks	VOC	1877.69	2846.90	4	4,30	4,30
CRUDE	Marine Loading – Crude Docks	Benzene	10.96	30.36	4	4,30	4,30
CRUDE	Marine Loading – Crude Docks	H <sub>2</sub> S	29.61	85.77		30	30
CYARDOWS	Wastewater Fugitives (4)	VOC	1877.69	2846.90	9,14	9,15,30	15,30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
CYARDOWS	Wastewater Fugitives (4)	Benzene	10.96	30.36	9,14	9,15,30	15,30
CYARDOWS	Wastewater Fugitives (4)	NH <sub>3</sub>	5.44	23.74	9,14	9,15,30	15,30
CWT10	Cooling Tower No.10 (4)	PM	77.13	272.80	9,14	9,30	30
CWT10	Cooling Tower No.10 (4)	VOC	1877.69	2846.90	9,14,23	9,23,30	30
CWT11	Cooling Tower No.11 (4)	PM	77.13	272.80	9,14	9,30	30
CWT11	Cooling Tower No.11 (4)	VOC	1877.69	2846.90	9,14,23	9,23,30	30
CWT12	Cooling Tower No.12 (4)	PM	77.13	272.80	9,14	9,30	30
CWT12	Cooling Tower No.12 (4)	VOC	1877.69	2846.90	9,14,23	9,23,30	30
CWT14	Cooling Tower No.14 (4)	PM	77.13	272.80	9,14	9,30	30
CWT14	Cooling Tower No.14 (4)	VOC	1877.69	2846.90	9,14,23	9,23,30	30
CWT15	Cooling Tower No.15 (4)	PM	77.13	272.80	9,14	9,30	30
CWT15	Cooling Tower No.15 (4)	VOC	1877.69	2846.90	9,14,23	9,23,30	30
CWT16/16A	Cooling Tower No.16/16A (4)	PM	77.13	272.80	9,14	9,30	30
CWT16/16A	Cooling Tower No.16/16A (4)	VOC	1877.69	2846.90	9,14,23	9,23,30	30
CWT17	Cooling Tower No.17 (4)	PM	77.13	272.80	9,14	9,30	30
CWT17	Cooling Tower No.17 (4)	VOC	1877.69	2846.90	9,14,23	9,23,30	30
CWT6	Cooling Tower No.6 (4)	PM	77.13	272.80	9,14	9,30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
CWT6	Cooling Tower No.6 (4)	VOC	1877.69	2846.90	9,14,23	9,23,30	30
CWT7	Cooling Tower No.7 (4)	PM	77.13	272.80	9,14	9,30	30
CWT7	Cooling Tower No.7 (4)	VOC	1877.69	2846.90	9,14,23	9,23,30	30
CWT8	Cooling Tower No.8 (4)	PM	77.13	272.80	9,14	9,30	30
CWT8	Cooling Tower No.8 (4)	VOC	1877.69	2846.90	9,14,23	9,23,30	30
CWT9	Cooling Tower No.9 (4)	PM	77.13	272.80	9,14	9,30	30
CWT9	Cooling Tower No.9 (4)	VOC	1877.69	2846.90	9,14,23	9,23,30	30
D363	FTXNK2/ ANTIICA NT Storage Tank	VOC	1877.69	2846.90		30	30
DAOWS	WW – Sewer DA Oily Water	VOC	1877.69	2846.90		30	30
DAOWS	WW – Sewer DA Oily Water	Benzene	10.96	30.36	3,4	3,4,30	3,4,30
DAOWS	WW – Sewer DA Oily Water	NH <sub>3</sub>	5.44	23.74		30	30
DD2	WW – Dispatching Distilling 2	VOC	1877.69	2846.90		30	30
DD2	WW – Dispatching Distilling 2	Benzene	10.96	30.36	3,4	3,4,30	3,4,30
DD2	WW – Dispatching Distilling 2	NH <sub>3</sub>	5.44	23.74		30	30
DOCK1	Marine Loading – Dock 1	VOC	1877.69	2846.90	4	4,30	4,30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
DOCK1	Marine Loading – Dock 1	Benzene	10.96	30.36	4	4,30	4,30
DOCK1	Marine Loading – Dock 1	H <sub>2</sub> S	29.61	85.77		30	30
DOCK2	Marine Loading – Dock 2	VOC	1877.69	2846.90	4	4,30	4,30
DOCK2	Marine Loading – Dock 2	Benzene	10.96	30.36	4	4,30	4,30
DOCK2	Marine Loading – Dock 2	H <sub>2</sub> S	29.61	85.77		30	30
DOCK4	Marine Loading – Dock 4	VOC	1877.69	2846.90	4	4,30	4,30
DOCK4	Marine Loading – Dock 4	Benzene	10.96	30.36	4	4,30	4,30
DOCK4	Marine Loading – Dock 4	H <sub>2</sub> S	29.61	85.77		30	30
DOCKS	Dock Wastewater Collection	VOC	1877.69	2846.90		30	30
DOCKS	Dock Wastewater Collection	Benzene	10.96	30.36	3,4	3,4,30	3,4,30
DOCKS	Dock Wastewater Collection	NH <sub>3</sub>	5.44	23.74		30	30
DW103	DW103 Storage Tank	VOC	1877.69	2846.90		30	30
DW104	DW104 Storage Tank	VOC	1877.69	2846.90		30	30
DYARDOWS	WW – Sewer D Yard Oily Water	VOC	1877.69	2846.90		30	30
DYARDOWS	WW – Sewer D Yard Oily Water	Benzene	10.96	30.36	3,4	3,4,30	3,4,30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
DYARDOWS	WW – Sewer D Yard Oily Water	NH <sub>3</sub>	5.44	23.74		30	30
F314	F314 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
F314	F314 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
F315	F315 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
F315	F315 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
F316	F316 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
F316	F316 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
F317	F317 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
F317	F317 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
F325	F325 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
F326	F326 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
F338	F338 Storage Tank	VOC	1877.69	2846.90	17	17,30	30
F338	F338 Storage Tank	Benzene	10.96	30.36	17	17,30	30
F338	F338 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30
F364	F364 Storage Tank	VOC	1877.69	2846.90	2,4,17	2,4,17,30	2,4,30



Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
F365	F365 Storage Tank	VOC	1877.69	2846.90	2,4,17	2,4,17,30	2,4,30
F366	F366 Storage Tank	VOC	1877.69	2846.90	2,4,17	2,4,17,30	2,4,30
F367	F367 Storage Tank	VOC	1877.69	2846.90	2,4,17	2,4,17,30	2,4,30
FLARECCU	CCU Flare	NO <sub>x</sub>	495.45	1825.00	24	30	30
FLARECCU	CCU Flare	CO (5)	777.95	2688.22	24	30	30
FLARECCU	CCU Flare	VOC	1877.69	2846.90	2,4,24	2,4,30	2,4,30
FLARECCU	CCU Flare	H <sub>2</sub> S	5.44	23.74	24	30	30
FLARECOKE	Coker Flare	NO <sub>x</sub>	495.45	1825.00	24	30	30
FLARECOKE	Coker Flare	CO (5)	777.95	2688.22	24	30	30
FLARECOKE	Coker Flare	SO <sub>2</sub>	2050.72	5259.84	24	30	30
FLARECOKE	Coker Flare	VOC	1877.69	2846.90	2,24	2,30	2,30
FLARECOKE	Coker Flare	H <sub>2</sub> S	29.61	85.77	2,24	2,30	2,30
FLAREEP	East Property Flare	NO <sub>x</sub>	495.45	1825.00	24	30	30
FLAREEP	East Property Flare	CO (5)	777.95	2688.22	24	30	30
FLAREEP	East Property Flare	SO <sub>2</sub>	2050.72	5259.84	24	30	30
FLAREEP	East Property Flare	VOC	1877.69	2846.90	2,3,4,24	2,3,4,30	2,3,4,30
FLAREEP	East Property Flare	H <sub>2</sub> S	29.61	85.77	2,24	2,30	2,30
FLAREGIRB	EP (Girbitol) Flare	NO <sub>x</sub>	495.45	1825.00	24	30	30
FLAREGIRB	EP (Girbitol) Flare	CO (5)	777.95	2688.22	24	30	30
FLAREGIRB	EP (Girbitol) Flare	SO <sub>2</sub>	2050.72	5259.84	24	30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
FLAREGIRB	EP (Girbitol) Flare	VOC	1877.69	2846.90	2,4,24	2,4,30	2,4,30
FLAREGIRB	EP (Girbitol) Flare	H <sub>2</sub> S	29.61	85.77	2,24	2,30	30
FLARELHT	LHT Flare	NO <sub>x</sub>	495.45	1825.00	24	30	30
FLARELHT	LHT Flare	CO (5)	777.95	2688.22	24	30	30
FLARELHT	LHT Flare	SO <sub>2</sub>	2050.72	5259.84	24	30	30
FLARELHT	LHT Flare	VOC	1877.69	2846.90	24	30	30
FLARELHT	LHT Flare	H <sub>2</sub> S	29.61	85.77	24	30	30
FLARENPP	North property Flare	NO <sub>x</sub>	495.45	1825.00	24	30	30
FLARENPP	North property Flare	CO (5)	777.95	2688.22	24	30	30
FLARENPP	North property Flare	SO <sub>2</sub>	2050.72	5259.84	24	30	30
FLARENPP	North property Flare	VOC	1877.69	2846.90	2,4,24	2,4,30	2,4,30
FLARENPP	North property Flare	H <sub>2</sub> S	29.61	85.77	2,24	2,30	2,30
FLARESOUTH	South Property Flare	NO <sub>x</sub>	495.45	1825.00	24	30	30
FLARESOUTH	South Property Flare	CO (5)	777.95	2688.22	24	30	30
FLARESOUTH	South Property Flare	SO <sub>2</sub>	2050.72	5259.84	24	30	30
FLARESOUTH	South Property Flare	VOC	1877.69	2846.90	2,4,24	2,4,30	2,4,30
FLARESOUTH	South Property Flare	H <sub>2</sub> S	29.61	85.77	24	30	30
FLAREWP	West Property Flare	NO <sub>x</sub>	495.45	1825.00	24	30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
FLAREWP	West Property Flare	CO (5)	777.95	2688.22	24	30	30
FLAREWP	West Property Flare	SO <sub>2</sub>	2050.72	5259.84	24	30	30
FLAREWP	West Property Flare	VOC	1877.69	2846.90	2,3,4,24	2,3,4,30	2,3,4,30
FLAREWP	West Property Flare	H <sub>2</sub> S	29.61	85.77	2,24	2,30	2,30
FP182	FP182 Storage Tank	VOC	1877.69	2846.90		30	30
FP190	FP190 Storage Tank	VOC	1877.69	2846.90		30	30
FP194	FP194 Storage Tank	VOC	1877.69	2846.90		30	30
FP195	FP195 Storage Tank	VOC	1877.69	2846.90		30	30
FP200	FP200 Storage Tank	VOC	1877.69	2846.90		30	30
FUGALKY	Alky Fugitives (4)	VOC	1877.69	2846.90	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGALKY	Alky Fugitives (4)	H <sub>2</sub> S	29.61	85.77	9,11,14	9,11,15,30	15,30
FUGAYARD	Fugitives (4)	VOC	1877.69	2846.90	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGAYARD	Fugitives (4)	H <sub>2</sub> S	29.61	85.77	9,11,14	9,11,15,30	15,30
FUGCCU	FCCU Fugitives (4)	VOC	1877.69	2846.90	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGCCU	FCCU Fugitives (4)	Benzene	10.96	30.36	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGCCU	FCCU Fugitives (4)	H <sub>2</sub> S	29.61	85.77	11,14	11,15,30	15,30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
FUGCCU	FCCU Fugitives (4)	NH <sub>3</sub>	5.44	23.74	14	11,15,30	15,30
FUGCFH	CFH Fugitives (4)	VOC	1877.69	2846.90	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGCFH	CFH Fugitives (4)	H <sub>2</sub> S	29.61	85.77	11,14	11,15,30	15,30
FUGCCUSCR	FCCU SCR Fugitives (4)	Benzene	10.96	30.36	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGCCUSCR	FCCU SCR Fugitives (4)	NH <sub>3</sub>	5.44	23.74	14	15,30	15,30
FUGCGHT	CGHT Fugitives (4)	VOC	1877.69	2846.90	2,4,10,14	2,4,10,15,30	2,4,15,30
FUGCOKER	Coke Handling Fugitives (4)	VOC	1877.69	2846.90	2,4,10,14	2,4,15,10,30	2,4,15,30
FUGCOKER	Coke Handling Fugitives (4)	Benzene	10.96	30.36	2,3,4,10,14	2,3,4,10,30	2,3,4,30
FUGCOKER	Coke Handling Fugitives (4)	H <sub>2</sub> S	29.61	85.77	11,14	11,30	30
FUGCOKER	Coke Handling Fugitives (4)	NH <sub>3</sub>	5.44	23.74	14	30	30
FUGCOKEPM1	Coke Pile Wind Erosion Fugitives (4)	PM	77.13	272.80	19	19,30	30
FUGCOKEPM1A	Coke Pile 2 Fugitives (4)	PM	77.13	272.80	19	19,30	30
FUGCOKEPM2	Coke Pile Crane Fugitives (4)	PM	77.13	272.80		30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
FUGCOKEPM3	Coke Crusher Fugitives (4)	PM	77.13	272.80		30	30
FUGCOKEPM4	Coke Crusher Discharge Fugitives (4)	PM	77.13	272.80		30	30
FUGCOKEPM5	Coke Transfer Conveyor Fugitives (4)	PM	77.13	272.80		30	30
FUGCOKEPM6	Coke Conveyor Discharge Fugitives (4)	PM	77.13	272.80		30	30
FUGCOKEPM7	Coke Barge Loading Fugitives (4)	PM	77.13	272.80		30	30
FUGCPU	CPU Fugitives (4)	VOC	1877.69	2846.90	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGCPU	CPU Fugitives (4)	H <sub>2</sub> S	29.61	85.77	11,14	11,15,30	15,30
FUGCR3	CR3 Fugitives (4)	VOC	1877.69	2846.90	2,4,10,14	2,4,10,15,30	2,4,15,30
FUGCR3	CR3 Fugitives (4)	Benzene	10.96	30.36	2,4,10,14	2,4,10,15,30	2,4,15,30
FUGCR3	CR3 Fugitives (4)	H <sub>2</sub> S	29.61	85.77	11,14	11,15,30	15,30
FUGCR3SCR	CR3 SCR Fugitives (4)	NH <sub>3</sub>	5.44	23.74	14	15,30	15,30
FUGCR3TF	Hydroprocessing Tank Farm (4)	VOC	1877.69	2846.90	2,4,14	2,4,15,30	2,4,15,30
FUGCR3TF	Hydroprocessing Tank Farm (4)	Benzene	10.96	30.36	2,3,4,14	2,3,4,15,30	2,3,4,15,30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
FUGCR3TF	Hydroprocessing Tank Farm (4)	H <sub>2</sub> S	29.61	85.77	11,14	11,15,30	15,30
FUGDHT	DHT Fugitives (4)	VOC	1877.69	2846.90	2,4,10,14	2,4,10,15,30	2,4,15,30
FUGDHT	DHT Fugitives (4)	Benzene	10.96	30.36	2,4,10,14	2,4,10,15,30	2,4,15,30
FUGDHT	DHT Fugitives (4)	H <sub>2</sub> S	29.61	85.77	11,14	11,15,30	15,30
FUGDHT	DHT Fugitives (4)	NH <sub>3</sub>	5.44	23.74	14	15,30	15,30
FUGDISP	DISP Fugitives (4)	VOC	1877.69	2846.90	2,4,14	2,4,15,30	2,4,15,30
FUGDISP	DISP Fugitives (4)	Benzene	10.96	30.36	2,4,14	2,4,15,30	2,4,15,30
FUGDISP	DISP Fugitives (4)	H <sub>2</sub> S	29.61	85.77	11,14	11,15,30	15,30
FUGDISP	DISP Fugitives (4)	NH <sub>3</sub>	5.44	23.74	14	15,30	15,30
FUGDOCK	Dock Fugitives (4)	VOC	1877.69	2846.90	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGDOCK	Dock Fugitives (4)	Benzene	10.96	30.36	2,3,4,9,14	2,3,4,9,15,30	2,3,4,15,30
FUGDOCK	Dock Fugitives (4)	NH <sub>3</sub>	5.44	23.74	14	15,30	15,30
FUGDU1	DU1 Fugitives (4)	VOC	1877.69	2846.90	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGDU1	DU1 Fugitives (4)	Benzene	10.96	30.36	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGDU1	DU1 Fugitives (4)	H <sub>2</sub> S	29.61	85.77	11,14	11,15,30	15,30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
FUGDU2	DU2 Fugitives (4)	VOC	1877.69	2846.90	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGDU2	DU2 Fugitives (4)	Benzene	10.96	30.36	2,3,4,9,14	2,3,4,9,15,30	2,3,4,15,30
FUGDU2	DU2 Fugitives (4)	H <sub>2</sub> S	29.61	85.77	11,14	11,15,30	15,30
FUGDU2	DU2 Fugitives (4)	NH <sub>3</sub>	5.44	23.74	14	15,30	15,30
FUGDU2B	DU3 Fugitives (4)	VOC	1877.69	2846.90	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGDU2B	DU3 Fugitives (4)	Benzene	10.96	30.36	2,3,4,9,14	2,3,4,9,15,30	2,3,4,15,30
FUGENVN	Environmental North Fugitives (4)	VOC	1877.69	2846.90	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGENVN	Environmental North Fugitives (4)	Benzene	10.96	30.36	2,3,4,9,14	2,3,4,9,15,30	2,3,4,15,30
FUGGASTR	GASTR Fugitives (4)	VOC	1877.69	2846.90	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGGFRAC	GFRAC Fugitives (4)	VOC	1877.69	2846.90	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGGFRAC	GFRAC Fugitives (4)	Benzene	10.96	30.36	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGGFRAC	GFRAC Fugitives (4)	H <sub>2</sub> S	29.61	85.77	11,14	11,15,30	15,30
FUGGIRBIT	Girbitol Fugitives (4)	VOC	1877.69	2846.90	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGGIRBIT	Girbitol Fugitives (4)	H <sub>2</sub> S	29.61	85.77	11,14	11,15,30	15,30
FUGGOHT	GOHT Fugitives (4)	VOC	1877.69	2846.90	2,4,10,14	2,4,10,15,30	2,4,15,30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
FUGGOHT	GOHT Fugitives (4)	Benzene	10.96	30.36	2,4,10,14	2,4,10,15,30	2,4,15,30
FUGGOHT	GOHT Fugitives (4)	H <sub>2</sub> S	29.61	85.77	11,14	11,15,30	15,30
FUGGR	GR Fugitives (4)	VOC	1877.69	2846.90	2,4,14	2,4,15,30	2,4,15,30
FUGGR	GR Fugitives (4)	Benzene	10.96	30.36	2,4,14	2,4,15,30	2,4,15,30
FUGGR	GR Fugitives (4)	H <sub>2</sub> S	29.61	85.77	11,14	11,15,30	15,30
FUGGR200	GR200 Fugitives (4)	VOC	1877.69	2846.90	4,14	4,15,30	4,15,30
FUGHDU1	HDU1 Fugitives (4)	VOC	1877.69	2846.90	2,4,10,14	2,4,10,15,30	2,4,15,30
FUGHDU1	HDU1 Fugitives (4)	Benzene	10.96	30.36	2,4,10,14	2,4,10,15,30	2,4,15,30
FUGHDU1	HDU1 Fugitives (4)	H <sub>2</sub> S	29.61	85.77	11,14	11,15,30	15,30
FUGHDU1	HDU1 Fugitives (4)	NH <sub>3</sub>	5.44	23.74	14	15,30	15,30
FUGHP1	HP1 Fugitives (4)	VOC	1877.69	2846.90	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGHP1	HP1 Fugitives (4)	Benzene	10.96	30.36	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGHP1	HP1 Fugitives (4)	H <sub>2</sub> S	29.61	85.77	11,14	11,15,30	15,30
FUGLHT2	LHT2 Fugitives (4)	VOC	1877.69	2846.90	2,4,10,14	2,4,10,15,30	2,4,15,30
FUGLHT2	LHT2 Fugitives (4)	Benzene	10.96	30.36	2,4,10,14	2,4,10,15,30	2,4,15,30



Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
FUGLHT2	LHT2 Fugitives (4)	H <sub>2</sub> S	29.61	85.77	11,14	11,15,30	15,30
FUGMTBE	MTBE Fugitives (4)	VOC	1877.69	2846.90	4,9,14	4,9,15,30	4,15,30
FUGPLAT2	PLAT2 Fugitives (4)	VOC	1877.69	2846.90	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGPLAT2	PLAT2 Fugitives (4)	Benzene	10.96	30.36	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGPLAT2	PLAT2 Fugitives (4)	H <sub>2</sub> S	29.61	85.77	11,14	11,15,30	15,30
FUGPOSTFRAC	POSTCFR AC Fugitives (4)	VOC	1877.69	2846.90	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGPSA	PSA Fugitives (4)	VOC	1877.69	2846.90	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGPSA	PSA Fugitives (4)	Benzene	10.96	30.36	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGSGP	SGP Fugitives (4)	VOC	1877.69	2846.90	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGSGP	SGP Fugitives (4)	Benzene	10.96	30.36	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGSGP	SGP Fugitives (4)	H <sub>2</sub> S	29.61	85.77	11,14	11,15,30	15,30
FUGSHCU	SHCU Fugitives (4)	VOC	1877.69	2846.90	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGSHCU	SHCU Fugitives (4)	Benzene	10.96	30.36	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGSHCU	SHCU Fugitives (4)	H <sub>2</sub> S	29.61	85.77	11,14	11,15,30	15,30
FUGSR3/4	SR3/4 Fugitives (4)	VOC	1877.69	2846.90	2,10,14	2,10,15,30	2,15,30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
FUGSR5	SR5 Fugitives (4)	VOC	1877.69	2846.90	2,10,14	2,10,15,30	2,15,30
FUGSR5	SR5 Fugitives (4)	H <sub>2</sub> S	29.61	85.77	11,14	11,15,30	15,30
FUGSR6	SR6 Fugitives (4)	VOC	1877.69	2846.90	2,10,14	2,10,15,30	2,15,30
FUGSR6	SR6 Fugitives (4)	H <sub>2</sub> S	29.61	85.77	11,14	11,15,30	15,30
FUGSR6	SR6 Fugitives (4)	NH <sub>3</sub>	5.44	23.74	14	15,30	15,30
FUGSR7	SR7 Fugitives (4)	VOC	1877.69	2846.90	2,10,14	2,10,15,30	2,15,30
FUGSR7	SR7 Fugitives (4)	H <sub>2</sub> S	29.61	85.77	11,14	11,15,30	15,30
FUGSR7	SR7 Fugitives (4)	NH <sub>3</sub>	5.44	23.74	14	15,30	15,30
FUGSR8	SR8 Fugitives (4)	VOC	1877.69	2846.90	2,10,14	2,10,15,30	2,15,30
FUGSR8	SR8 Fugitives (4)	H <sub>2</sub> S	29.61	85.77	11,14	11,15,30	15,30
FUGSR8	SR8 Fugitives (4)	NH <sub>3</sub>	5.44	23.74	14	15,30	15,30
FUGTHCR	Thermal Cracking Fugitives (4)	VOC	1877.69	2846.90	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGTHCR	Thermal Cracking Fugitives (4)	Benzene	10.96	30.36	2,4,9,14	2,4,9,15,30	2,4,15,30
FUGTHCR	Thermal Cracking Fugitives (4)	H <sub>2</sub> S	29.61	85.77	11,14	11,15,30	15,30
FUGWBT	West Blend Tank Fugitives (4)	VOC	1877.69	2846.90	2,4,9,14	2,4,9,15,30	2,4,15,30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
G308	G308 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
G308	G308 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
G309	G309 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
G309	G309 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
G310	G310 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
G310	G310 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
G311	G311 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
G311	G311 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
G313	G313 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
G313	G313 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
G314	G314 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
G315	G315 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
G315	G315 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
G316	G316 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
G316	G316 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
G317	G317 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
G319	G319 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
G320	G320 Storage Tank	VOC	1877.69	2846.90	4	4,30	4,30
G320	G320 Storage Tank	Benzene	10.96	30.36	4	4,30	4,30
G322	G322 Storage Tank	VOC	1877.69	2846.90	4	4,30	4,30
G322	G322 Storage Tank	Benzene	10.96	30.36	4	4,30	4,30
G323	G323 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
G323	G323 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
G326	G326 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
G326	G326 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
G327	G327 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
G327	G327 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
G328	G328 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
G328	G328 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
G329	G329 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
G329	G329 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
G332	G332 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
G332	G332 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
G332	G332 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30
G342	G342 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
G342	G342 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
G345	G345 Storage Tank	VOC	1877.69	2846.90	2,17	2,17,30	2,30
G346	G346 Storage Tank	VOC	1877.69	2846.90	2,17	2,17,30	2,30
G346	G346 Storage Tank	Benzene	10.96	30.36	2,17	2,17,30	2,30
G347	G347 Storage Tank	VOC	1877.69	2846.90	4	4,30	4,30
G348	G347 Storage Tank	VOC	1877.69	2846.90	4	4,30	4,30
G348	G348 Storage Tank	Benzene	10.96	30.36	4	4,30	4,30
G352	G352 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
G354	G354 Storage Tank	VOC	1877.69	2846.90	17	17,30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
G355	G355 Storage Tank	VOC	1877.69	2846.90	17	17,30	30
G355	G355 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
G356	G356 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
G356	G356 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
G357	G357 Storage Tank	VOC	1877.69	2846.90	17	17,30	30
G357	G357 Storage Tank	Benzene	10.96	30.36	17	17,30	30
G358	G358 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
G358	G358 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
G360	G360 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
G360	G360 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
G361	G361 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
GIRBOTWW	WW Collection in Girbitol	VOC	1877.69	2846.90		30	30
GIRBOTWW	WW Collection in Girbitol	Benzene	10.96	30.36	3,4	3,4,30	3,4,30
GIRBOTWW	WW Collection in Girbitol	NH <sub>3</sub>	5.44	23.74		30	30
H1000	PLAT2 Heater	NO <sub>x</sub>	495.45	1825.00	8	8,30	8,30
H1000	PLAT2 Heater	CO (5)	777.95	2688.22	8	8,30	8,30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
H1000	PLAT2 Heater	PM	77.13	272.80		30	30
H1000	PLAT2 Heater	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30
H1000	Guard Bed Start-up Heater	VOC	1877.69	2846.90		30	30
H1001	Guard Bed Start-up Heater	NO <sub>x</sub>	495.45	1825.00		30	30
H1001	Guard Bed Start-up Heater	CO (5)	777.95	2688.22		30	30
H1001	Guard Bed Start-up Heater	PM	77.13	272.80		30	30
H1001	Guard Bed Start-up Heater	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30
H1001	HDU-1 Charge Heater	VOC	1877.69	2846.90		30	30
H1010	HDU-1 Charge Heater	NO <sub>x</sub>	495.45	1825.00		30	30
H1010	HDU-1 Charge Heater	CO (5)	777.95	2688.22		30	30
H1010	HDU-1 Charge Heater	PM	77.13	272.80		30	30
H1010	HDU-1 Charge Heater	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30
H1010	HDU-1 Reboiler Heater	VOC	1877.69	2846.90		30	30
H1011	HDU-1 Reboiler Heater	NO <sub>x</sub>	495.45	1825.00		30	30
H1011	HDU-1 Reboiler Heater	CO (5)	777.95	2688.22		30	30
H1011	HDU-1 Reboiler Heater	PM	77.13	272.80		30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
H1011	HDU-1 Reboiler Heater	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30
H1011	HDU-1 Reboiler Heater	VOC	1877.69	2846.90		30	30
H1100	DHT Heater	NO <sub>x</sub>	495.45	1825.00		30	30
H1100	DHT Heater	CO (5)	777.95	2688.22		30	30
H1100	DHT Heater	PM	77.13	272.80		30	30
H1100	DHT Heater	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30
H1100	DHT Heater	VOC	1877.69	2846.90		30	30
H1170	CFH Heater	NO <sub>x</sub>	495.45	1825.00		30,33	30
H1170	CFH Heater	CO (5)	777.95	2688.22		30	30
H1170	CFH Heater	PM	77.13	272.80		30	30
H1170	CFH Heater	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	30
H1170	CFH Heater	VOC	1877.69	2846.90		30	30
H31001/2	Coker heater No. 1 and 2	NO <sub>x</sub>	495.45	1825.00	8	8,30	8,30
H31001/2	Coker heater No. 1 and 2	CO (5)	777.95	2688.22	8	8,30	8,30
H31001/2	Coker heater No. 1 and 2	PM	77.13	272.80		30	30
H31001/2	Coker heater No. 1 and 2	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30
H31001/2	Coker heater No. 1 and 2	VOC	1877.69	2846.90		30	30
H31003	Coker Heater #3	NO <sub>x</sub>	495.45	1,825.00	7,8	7,8,30	7,8,30



Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
H31003	Coker Heater #3	CO (5)	777.95	2688.22	7,8	7,8,30	7,8,30
H31003	Coker Heater #3	PM	77.13	272.80		30	30
H31003	Coker Heater #3	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30
H31003	Coker Heater #3	VOC	1877.69	2846.90		30	30
H3300	DHT H <sub>2</sub> Heater	NO <sub>x</sub>	495.45	1825.00	7	7,30	7,30
H3300	DHT H <sub>2</sub> Heater	CO (5)	777.95	2688.22	7	7,30	7,30
H3300	DHT H <sub>2</sub> Heater	PM	77.13	272.80		30	30
H3300	DHT H <sub>2</sub> Heater	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30
H3300	DHT H <sub>2</sub> Heater	VOC	1877.69	2846.90		30	30
H36100	CGHT Heater	NO <sub>x</sub>	495.45	1825.00		30	30
H36100	CGHT Heater	CO (5)	777.95	2688.22		30	30
H36100	CGHT Heater	PM	77.13	272.80		30	30
H36100	CGHT Heater	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30
H36100	CGHT Heater	VOC	1877.69	2846.90		30	30
H5100	DU-2 South Crude Heater	NO <sub>x</sub>	495.45	1825.00	7,8	7,8,30,35	7,8,30
H5100	DU-2 South Crude Heater	CO (5)	777.95	2688.22	7,8	7,8,30	7,8,30
H5100	DU-2 South Crude Heater	PM	77.13	272.80		30	30
H5100	DU-2 South Crude Heater	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
H5100	DU-2 South Crude Heater	VOC	1877.69	2846.90		30	30
H5101	DU-2 North Crude Heater	NO <sub>x</sub>	495.45	1825.00	7,8	7,8,30,36	7,8,30
H5101	DU-2 North Crude Heater	CO (5)	777.95	2688.22	7,8	7,8,30	7,8,30
H5101	DU-2 North Crude Heater	PM	77.13	272.80		30	30
H5101	DU-2 North Crude Heater	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30
H5101	DU-2 North Crude Heater	VOC	1877.69	2846.90		30	30
H5102	DU-2 South Flasher Charge Heater	NO <sub>x</sub>	495.45	1825.00	8	8,30	8,30
H5102	DU-2 South Flasher Charge Heater	CO (5)	777.95	2688.22	8	8,30	8,30
H5102	DU-2 South Flasher Charge Heater	PM	77.13	272.80		30	30
H5102	DU-2 South Flasher Charge Heater	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30
H5102	DU-2 South Flasher Charge Heater	VOC	1877.69	2846.90		30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
H5103	DU-2 North Flasher Charge Heater	NO <sub>x</sub>	495.45	1825.00	8	8,30	8,30
H5103	DU-2 North Flasher Charge Heater	CO (5)	777.95	2688.22	8	8,30	8,30
H5103	DU-2 North Flasher Charge Heater	PM	77.13	272.80		30	30
H5103	DU-2 North Flasher Charge Heater	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30
H5103	DU-2 North Flasher Charge Heater	VOC	1877.69	2846.90		30	30
H5104	DU-2 Preflash Heater	NO <sub>x</sub>	495.45	1,825.00	7,8	7,8,30	7,8,30
H5104	DU-2 Preflash Heater	CO (5)	777.95	2688.22	7,8	7,8,30	7,8,30
H5104	DU-2 Preflash Heater	PM	77.13	272.80		30	30
H5104	DU-2 Preflash Heater	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30
H5104	DU-2 Preflash Heater	VOC	1877.69	2846.90		30	30
H5105	DU-2 Preflash2 Heater	NO <sub>x</sub>	495.45	1,825.00	7	7,30	7,30
H5105	DU-2 Preflash2 Heater	CO (5)	777.95	2688.22	7	7,30	7,30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
H5105	DU-2 Preflash2 Heater	PM	77.13	272.80		30	30
H5105	DU-2 Preflash2 Heater	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30
H5105	DU-2 Preflash2 Heater	VOC	1877.69	2846.90		30	30
H5200	HDU-2 Charge Heater	NO <sub>x</sub>	495.45	1825.00		30	30
H5200	HDU-2 Charge Heater	CO (5)	777.95	2688.22		30	30
H5200	HDU-2 Charge Heater	PM	77.13	272.80		30	30
H5200	HDU-2 Charge Heater	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30
H5200	HDU-2 Charge Heater	VOC	1877.69	2846.90		30	30
H53NN	Catalytic Reformer SCR	NO <sub>x</sub>	495.45	1825.00	4,7,8	4,7,8,30,34	4,7,8,30
H53NN	Catalytic Reformer SCR	CO (5)	777.95	2688.22	4,7,8	4,8,7,30	4,7,8,30
H53NN	Catalytic Reformer SCR	PM	77.13	272.80	4	4,30	4,30
H53NN	Catalytic Reformer SCR	SO <sub>2</sub>	2050.72	5259.84	2,4	2,4,30	2,4,30
H53NN	Catalytic Reformer SCR	VOC	1877.69	2846.90	4	4,30	4,30
H53NN	Catalytic Reformer SCR	NH <sub>3</sub>	5.44	23.74	4	4,30	4,30
H5400	SHCU South Charge Heater	NO <sub>x</sub>	495.45	1825.00		30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
H5400	SHCU South Charge Heater	CO (5)	777.95	2688.22		30	30
H5400	SHCU South Charge Heater	PM	77.13	272.80		30	30
H5400	SHCU South Charge Heater	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30
H5400	SHCU South Charge Heater	VOC	1877.69	2846.90		30	30
H5402	SHCU Reboiler Heater	NO <sub>x</sub>	495.45	1825.00	8	8,30	8,30
H5402	SHCU Reboiler Heater	CO (5)	777.95	2688.22	8	8,30	8,30
H5402	SHCU Reboiler Heater	PM	77.13	272.80		30	30
H5402	SHCU Reboiler Heater	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30
H5402	SHCU Reboiler Heater	VOC	1877.69	2846.90		30	30
H5403	SHCU North Charge Heater	NO <sub>x</sub>	495.45	1825.00		30	30
H5403	SHCU North Charge Heater	CO (5)	777.95	2688.22		30	30
H5403	SHCU North Charge Heater	PM	77.13	272.80		30	30
H5403	SHCU North Charge Heater	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
H5403	SHCU North Charge Heater	VOC	1877.69	2846.90		30	30
H5404	SHCU Post-Frac Heater	NO <sub>x</sub>	495.45	1,825.00	7,8	7,8,30	7,8,30
H5404	SHCU Post-Frac Heater	CO	777.95	2,688.22	7,8	7,8,30	7,8,30
H5404	SHCU Post-Frac Heater	PM	77.13	272.80		30	30
H5404	SHCU Post-Frac Heater	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30
H5404	SHCU Post-Frac Heater	VOC	1877.69	2846.90		30	30
H5500A	SMR Heater A	NO <sub>x</sub>	495.45	1825.00	8	8,30	8,30
H5500A	SMR Heater A	CO (5)	777.95	2688.22	8	8,30	8,30
H5500A	SMR Heater A	PM	77.13	272.80		30	30
H5500A	SMR Heater A	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30
H5500A	SMR Heater A	VOC	1877.69	2846.90		30	30
H5500B	SMR Heater B	NO <sub>x</sub>	495.45	1825.00	8	8,30	8,30
H5500B	SMR Heater B	CO (5)	777.95	2688.22	8	8,30	8,30
H5500B	SMR Heater B	PM	77.13	272.80		30	30
H5500B	SMR Heater B	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30
H5500B	SMR Heater B	VOC	1877.69	2846.90		30	30
H5500C	SMR Heater C	NO <sub>x</sub>	495.45	1825.00	8	8,30	8,30
H5500C	SMR Heater C	CO (5)	777.95	2688.22	8	8,30	8,30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
H5500C	SMR Heater C	PM	77.13	272.80		30	30
H5500C	SMR Heater C	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30
H5500C	SMR Heater C	VOC	1877.69	2846.90		30	30
H5600	SGP Heat Medium Heater	NO <sub>x</sub>	495.45	1825.00	8	8,30	8,30
H5600	SGP Heat Medium Heater	CO (5)	777.95	2688.22	8	8,30	8,30
H5600	SGP Heat Medium Heater	PM	77.13	272.80		30	30
H5600	SGP Heat Medium Heater	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30
H5600	SGP Heat Medium Heater	VOC	1877.69	2846.90		30	30
H600	CCU CO Boiler	NO <sub>x</sub>	56.88	124.56	7,8	7,8,32	7,8
H600	CCU CO Boiler	CO	346.32	1402.62	2,4,7,8	2,4,7,8,32	2,4,7,8
H600	CCU CO Boiler	PM	66.00	289.08	2,4	2,4	2,4
H600	CCU CO Boiler	SO <sub>2</sub>	593.48	216.62	2,25	2,25	2
H600	CCU CO Boiler	VOC	3.20	14.02			
H600	CCU CO Boiler	NH <sub>3</sub>	5.25	23.02			
H613	DU-1 Secondary Pre-heater	NO <sub>x</sub>	495.45	1825.00	7	7,30,37	7,30
H613	DU-1 Secondary Pre-heater	CO (5)	777.95	2688.22	7	7,30	7,30
H613	DU-1 Secondary Pre-heater	PM	77.13	272.80		30	30
H613	DU-1 Secondary Pre-heater	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
H613	DU-1 Secondary Pre-heater	VOC	1877.69	2846.90		30	30
H63000	HVI Column Charge Heater	NO <sub>x</sub>	495.45	1825.00		30	30
H63000	HVI Column Charge Heater	CO (5)	777.95	2688.22		30	30
H63000	HVI Column Charge Heater	PM	77.13	272.80		30	30
H63000	HVI Column Charge Heater	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30
H63000	HVI Column Charge Heater	VOC	1877.69	2846.90		30	30
H70001/2	GOHT Recycle Gas and Frac. Reboiler Heaters	NO <sub>x</sub>	495.45	1825.00		30	30
H70001/2	GOHT Recycle Gas and Frac. Reboiler Heaters	CO (5)	777.95	2688.22		30	30
H70001/2	GOHT Recycle Gas and Frac. Reboiler Heaters	PM	77.13	272.80		30	30
H70001/2	GOHT Recycle Gas and Frac. Reboiler Heaters	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30



Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
H70001/2	GOHT Recycle Gas and Frac. Reboiler Heaters	VOC	1877.69	2846.90		30	30
H850S1	PERC Heater – North Stack	NO <sub>x</sub>	495.45	1825.00		30	30
H850S1	PERC Heater – North Stack	CO (5)	777.95	2688.22		30	30
H850S1	PERC Heater – North Stack	PM	77.13	272.80		30	30
H850S1	PERC Heater – North Stack	SO <sub>2</sub>	2050.72	5259.84	25	25,30	30
H850S1	PERC Heater – North Stack	VOC	1877.69	2846.90		30	30
H850S2	PERC Heater – South Stack	NO <sub>x</sub>	495.45	1825.00		30	30
H850S2	PERC Heater – South Stack	CO (5)	777.95	2688.22		30	30
H850S2	PERC Heater – South Stack	PM	77.13	272.80		30	30
H850S2	PERC Heater – South Stack	SO <sub>2</sub>	2050.72	5259.84	25	25,30	30
H850S2	PERC Heater – South Stack	VOC	1877.69	2846.90		30	30
H9150R1	Heater	NO <sub>x</sub>	495.45	1825.00		30	30
H9150R1	Heater	CO (5)	777.95	2688.22		30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
H9150R1	Heater	PM	77.13	272.80		30	30
H9150R1	Heater	SO <sub>2</sub>	2050.72	5259.84	2,25	2,25,30	2,30
H9150R1	Heater	VOC	1877.69	2846.90		30	30
HVIOWS	WW – Sewer HVI Oily Water	VOC	1877.69	2846.90		30	30
HVIOWS	WW – Sewer HVI Oily Water	Benzene	10.96	30.36	3,4	3,4,30	3,4,30
J301B	J301B Storage Tank	VOC	1877.69	2846.90		30	30
J302B	J302B Storage Tank	VOC	1877.69	2846.90		30	30
J303B	J303B Storage Tank	VOC	1877.69	2846.90		30	30
J303B	J303B Storage Tank	Benzene	10.96	30.36		30	30
J304	J304 Storage Tank	VOC	1877.69	2846.90	4	4,30	4,30
J304	J304 Storage Tank	Benzene	10.96	30.36	4	4,30	4,30
J305B	J305 Storage Tank	VOC	1877.69	2846.90		30	30
J306	J303B Storage Tank	VOC	1877.69	2846.90		30	30
J308	J308 Storage Tank	VOC	1877.69	2846.90		30	30
J308	J308 Storage Tank	Benzene	10.96	30.36		30	30
J309	J309 Storage Tank	VOC	1877.69	2846.90		30	30
J309	J309 Storage Tank	Benzene	10.96	30.36		30	30
J311	J311 Storage Tank	VOC	1877.69	2846.90		30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
J311	J311 Storage Tank	Benzene	10.96	30.36		30	30
J312	J312 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
J312	J312 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
J315	J315 Storage Tank	VOC	1877.69	2846.90	4	4,30	4,30
J315	J315 Storage Tank	Benzene	10.96	30.36	4	4,30	4,30
J316	J316 Storage Tank	VOC	1877.69	2846.90	4	4,30	4,30
J316	J316 Storage Tank	Benzene	10.96	30.36	4	4,30	4,30
J317	J317 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
J317	J317 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
J317	J317 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30
J318B	S318B Storage Tank	VOC	1877.69	2846.90	2,4,17	2,4,17,30	2,4,30
J318B	S318B Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30
J318B	S318B Storage Tank	NH <sub>3</sub>	5.44	23.74	17	17,30	30
J320	J320 Storage Tank	VOC	1877.69	2846.90	17	17,30	30
J320	J320 Storage Tank	Benzene	10.96	30.36	17	17,30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
J322	J322 Storage Tank	VOC	1877.69	2846.90	4	4,30	4,30
J322	J322 Storage Tank	Benzene	10.96	30.36	4	4,30	4,30
J323	J323 Storage Tank	VOC	1877.69	2846.90	4	4,30	4,30
J323	J323 Storage Tank	Benzene	10.96	30.36	4	4,30	4,30
J324	J324 Storage Tank	VOC	1877.69	2846.90	4	4,30	4,30
J324	J324 Storage Tank	Benzene	10.96	30.36	4	4,30	4,30
J324	J324 Storage Tank	H <sub>2</sub> S	29.61	85.77		30	30
J325	J325 Storage Tank	VOC	1877.69	2846.90		30	30
J325	J325 Storage Tank	H <sub>2</sub> S	29.61	85.77		30	30
J326	J326 Storage Tank	VOC	1877.69	2846.90		30	30
J326	J326 Storage Tank	Benzene	10.96	30.36		30	30
J326	J326 Storage Tank	H <sub>2</sub> S	29.61	85.77		30	30
J327	J327 Storage Tank	VOC	1877.69	2846.90		30	30
J327	J327 Storage Tank	Benzene	10.96	30.36		30	30
J327	J327 Storage Tank	H <sub>2</sub> S	29.61	85.77		30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
J328	J328 Storage Tank	VOC	1877.69	2846.90		30	30
J328	J328 Storage Tank	Benzene	10.96	30.36		30	30
J328	J328 Storage Tank	H <sub>2</sub> S	29.61	85.77		30	30
J329	J329 Storage Tank	VOC	1877.69	2846.90		30	30
J330	J330 Storage Tank	VOC	1877.69	2846.90		30	30
J331	J331 Storage Tank	VOC	1877.69	2846.90		30	30
J331	J331 Storage Tank	H <sub>2</sub> S	29.61	85.77		30	30
J332	J332 Storage Tank	VOC	1877.69	2846.90		30	30
J332	J332 Storage Tank	H <sub>2</sub> S	29.61	85.77		30	30
J336	J336 Storage Tank	VOC	1877.69	2846.90	4	4,30	4,30
J336	J336 Storage Tank	Benzene	10.96	30.36	4	4,30	4,30
J337	J337 Storage Tank	VOC	1877.69	2846.90	4	4,30	4,30
J337	J337 Storage Tank	Benzene	10.96	30.36	4	4,30	4,30
J338	J338 Storage Tank	VOC	1877.69	2846.90	4	4,30	4,30
J338	J338 Storage Tank	Benzene	10.96	30.36	4	4,30	4,30
J340	J340 Storage Tank	VOC	1877.69	2846.90		30	30
J348	J348 Storage Tank	VOC	1877.69	2846.90		30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
J348	J348 Storage Tank	Benzene	10.96	30.36		30	30
J348	J348 Storage Tank	H <sub>2</sub> S	29.61	85.77		30	30
J349	J349 Storage Tank	VOC	1877.69	2846.90		30	30
J349	J349 Storage Tank	Benzene	10.96	30.36		30	30
J349	J349 Storage Tank	H <sub>2</sub> S	29.61	85.77		30	30
K301	K301 Storage Tank	VOC	1877.69	2846.90		30	30
K302	K302 Storage Tank	VOC	1877.69	2846.90		30	30
K303	K303 Storage Tank	VOC	1877.69	2846.90	4	4,30	4,30
K303	K303 Storage Tank	Benzene	10.96	30.36	4	4,30	4,30
K304	K304 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
K304	K304 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
K306	K306 Storage Tank	VOC	1877.69	2846.90		30	30
K310	K310 Storage Tank	VOC	1877.69	2846.90		30	30
K311	K311 Storage Tank	VOC	1877.69	2846.90		30	30
L2COMPVT	L2COMPV T Vent	VOC	1877.69	2846.90		30	30
L2COMPVT	L2COMPV T Vent	H <sub>2</sub> S	29.61	85.77		30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
LDSULF67	SR6 and SR7 Loading Rack	H <sub>2</sub> S	29.61	85.77		30	30
LEUOWS	WW – Sewer LEU Oily Water	VOC	1877.69	2846.90		30	30
LEUOWS	WW – Sewer LEU Oily Water	Benzene	10.96	30.36	3,4	3,4,30	3,4,30
LEUOWS	WW – Sewer LEU Oily Water	NH <sub>3</sub>	5.44	23.74		30	30
LHT1OWS	WW – Sewer LHT1 Oily Water	VOC	1877.69	2846.90		30	30
LHT1OWS	WW – Sewer LHT1 Oily Water	Benzene	10.96	30.36	3,4	3,4,30	3,4,30
LHT1OWS	WW – Sewer LHT1 Oily Water	H <sub>2</sub> S	29.61	85.77		30	30
LHT1OWS	WW – Sewer LHT1 Oily Water	NH <sub>3</sub>	5.44	23.74		30	30
LHT2OWS	WW – Sewer LHT2 Oily Water	VOC	1877.69	2846.90		30	30
LHT2OWS	WW – Sewer LHT2 Oily Water	Benzene	10.96	30.36	3,4	3,4,30	3,4,30
LHT2OWS	WW – Sewer LHT2 Oily Water	H <sub>2</sub> S	29.61	85.77		30	30
LHT2OWS	WW – Sewer LHT2 Oily Water	NH <sub>3</sub>	5.44	23.74		30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
LOADOWS	WW – Sewer Loading Racks	VOC	1877.69	2846.90		30	30
LOADOWS	WW – Sewer Loading Racks	Benzene	10.96	30.36	3,4	3,4,30	3,4,30
LOADOWS	WW – Sewer Loading Racks	NH <sub>3</sub>	5.44	23.74		30	30
M301	Marine Fuel Oil Storage Tank	VOC	1877.69	2846.90		30	30
M302	Marine Diesel Storage Tank	VOC	1877.69	2846.90		30	30
MANHOLE4	WW – Manhole 4	VOC	1877.69	2846.90		30	30
MANHOLE4	WW – Manhole 4	Benzene	10.96	30.36	3,4	3,4,30	3,4,30
MANHOLE4	WW – Manhole 4	NH <sub>3</sub>	5.44	23.74		30	30
MVIDEEASS	WW – Sewer DEA	VOC	1877.69	2846.90		30	30
MVIDEEASS	WW – Sewer DEA	Benzene	10.96	30.36	3,4	3,4,30	3,4,30
MVIDEEASS	WW – Sewer DEA	H <sub>2</sub> S	29.61	85.77		30	30
MVIDEEASS	WW – Sewer DEA	NH <sub>3</sub>	5.44	23.74		30	30
MVIOWS	WW – Sewer MVI Oily Water	VOC	1877.69	2846.90		30	30
MVIOWS	WW – Sewer MVI Oily Water	Benzene	10.96	30.36	3,4	3,4,30	3,4,30
MVIOWS	WW – Sewer MVI Oily Water	NH <sub>3</sub>	5.44	23.74		30	30



Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
N92252	X4HDU1 Storage Tank	VOC	1877.69	2846.90		30	30
NAB	North Aeration Basin	VOC	1877.69	2846.90		30	30
NAB	North Aeration Basin	Benzene	10.96	30.36	3	3,30	3,30
NAB	North Aeration Basin	NH <sub>3</sub>	5.44	23.74		30	30
NDAF	WW – North DAF Unit	VOC	1877.69	2846.90		30	30
NDAF	WW – North DAF Unit	Benzene	10.96	30.36	3	3,30	3,30
NDAF	WW – North DAF Unit	NH <sub>3</sub>	5.44	23.74		30	30
NONE2	FXTNK2/ Amine Neutralizer Storage Tank	VOC	1877.69	2846.90		30	30
NONE3	FXTNK2/Filmer Storage tank	VOC	1877.69	2846.90		30	30
OWATCTF	WW – Alky Tank Farm Oily Water	VOC	1877.69	2846.90		30	30
OWATCTF	WW – Alky Tank Farm Oily Water	Benzene	10.96	30.36	3,4	3,4,30	3,4,30
OWDU1	WW – Sewer Oily Water HUB	VOC	1877.69	2846.90		30	30
OWDU1	WW – Sewer Oily Water HUB	Benzene	10.96	30.36	3,4	3,4,30	3,4,30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
OWDU1	WW – Sewer Oily Water HUB	NH <sub>3</sub>	5.44	23.74		30	30
PAINTFE	Miscellaneous Painting Fugitives	VOC	1877.69	2846.90		30	30
PAINTFE	Miscellaneous Painting Fugitives	PM	77.13	272.80		30	30
RKLBLEND	Load	VOC	1877.69	2846.90		30	30
RKLDIALA	Load	VOC	1877.69	2846.90		30	30
RKLTC	Load	VOC	1877.69	2846.90		30	30
RKLTC/TT	Load	VOC	1877.69	2846.90		30	30
RKLTC/TT	Load	H <sub>2</sub> S	29.61	85.77		30	30
RKLCTTU	Load	VOC	1877.69	2846.90		30	30
S302	S302 Storage Tank	VOC	1877.69	2846.90		30	30
S305	S305 Storage Tank	VOC	1877.69	2846.90	4	4,30	4,30
S306	S306 Storage Tank	VOC	1877.69	2846.90	4	4,30	4,30
S307	S307 Storage Tank	VOC	1877.69	2846.90		30	30
S310	S310 Storage Tank	VOC	1877.69	2846.90		30	30
S312	S312 Storage Tank	VOC	1877.69	2846.90		30	30
S313	S313 Storage Tank	VOC	1877.69	2846.90		30	30
S318	S318 Storage Tank	VOC	1877.69	2846.90		30	30
S325	S325 Storage Tank	VOC	1877.69	2846.90		30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
S326	S326 Storage Tank	VOC	1877.69	2846.90		30	30
S339	S339 Storage Tank	VOC	1877.69	2846.90	3,17	3,17,30	3,30
S348	S348 Storage Tank	VOC	1877.69	2846.90		30	30
S359	S359 Storage Tank	VOC	1877.69	2846.90		30	30
S360	S360 Storage Tank	VOC	1877.69	2846.90		30	30
S395	S395 Storage Tank	VOC	1877.69	2846.90		30	30
S401	S401 Storage Tank	VOC	1877.69	2846.90		30	30
S402	S402 Storage Tank	VOC	1877.69	2846.90		30	30
S412	S412 Storage Tank	VOC	1877.69	2846.90		30	30
S412	S412 Storage Tank	Benzene	10.96	30.36		30	30
S429	S429 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
S429	S429 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30
S429	S429 Storage Tank	NH <sub>3</sub>	5.44	23.74	17	17,30	30
S430	S430 Storage Tank	VOC	1877.69	2846.90		30	30
SAB	South Aeration Basin	VOC	1877.69	2846.90		30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
SAB	South Aeration Basin	Benzene	10.96	30.36	3	3,30	3,30
SAB	South Aeration Basin	NH <sub>3</sub>	5.44	23.74		30	30
SDAF	WW – South DAF Unit	VOC	1877.69	2846.90		30	30
SDAF	WW – South DAF Unit	Benzene	10.96	30.36	3	3,30	3,30
SDAF	WW – South DAF Unit	NH <sub>3</sub>	5.44	23.74		30	30
SR3/4PIT	SR3/4 Sulfur Pit	VOC	1877.69	2846.90	4	4,30	4,30
SR3/4PIT	SR3/4 Sulfur Pit	H <sub>2</sub> S	29.61	85.77	4	4,30	4,30
SR3/4STACK	SR-3/4 Incinerator	NO <sub>x</sub>	495.45	1825.00	7	7,30	7,30
SR3/4STACK	SR-3/4 Incinerator	CO (5)	777.95	2688.22	7	7,30	7,30
SR3/4STACK	SR-3/4 Incinerator	PM	77.13	272.80		30	30
SR3/4STACK	SR-3/4 Incinerator	SO <sub>2</sub>	2050.72	5259.84	2,4,7,21	2,4,7,21,30	2,4,7,30
SR3/4STACK	SR-3/4 Incinerator	VOC	1877.69	2846.90		30	30
SR3/4STACK	SR-3/4 Incinerator	H <sub>2</sub> S	29.61	85.77		30	30
SR3/4WW	SR3/4 Wastewater Collection	VOC	1877.69	2846.90		30	30
SR3/4WW	SR3/4 Wastewater Collection	Benzene	10.96	30.36	3,4	3,4,30	3,4,30
SR3/4WW	SR3/4 Wastewater Collection	NH <sub>3</sub>	5.44	23.74		30	30
SR5L01	SR5 Loading Rack	VOC	1877.69	2846.90		30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
SR5L01	SR5 Loading Rack	H <sub>2</sub> S	29.61	85.77		30	30
SR5L02	SR5 Loading Rack	VOC	1877.69	2846.90		30	30
SR5L02	SR5 Loading Rack	H <sub>2</sub> S	29.61	85.77		30	30
SR5STACK	SR5 Tail Gas Incinerator	NO <sub>x</sub>	495.45	1825.00		30	30
SR5STACK	SR5 Tail Gas Incinerator	CO (5)	777.95	2688.22		30	30
SR5STACK	SR5 Tail Gas Incinerator	PM	77.13	272.80		30	30
SR5STACK	SR5 Tail Gas Incinerator	SO <sub>2</sub>	2050.72	5259.84	2,4,21	2,4,21,30	2,4,30
SR5STACK	SR5 Tail Gas Incinerator	VOC	1877.69	2846.90		30	30
SR5STACK	SR5 Tail Gas Incinerator	H <sub>2</sub> S	29.61	85.77		30	30
SR6STACK	SR6 Tail Gas Incinerator	NO <sub>x</sub>	495.45	1825.00		30	30
SR6STACK	SR6 Tail Gas Incinerator	CO (5)	777.95	2688.22		30	30
SR6STACK	SR6 Tail Gas Incinerator	PM	77.13	272.80		30	30
SR6STACK	SR6 Tail Gas Incinerator	SO <sub>2</sub>	2050.72	5259.84	2,4,21	2,4,21,30	2,4,30
SR6STACK	SR6 Tail Gas Incinerator	VOC	1877.69	2846.90		30	30
SR6STACK	SR6 Tail Gas Incinerator	H <sub>2</sub> S	29.61	85.77		30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
SR7STACK	SR7 Tail Gas Incinerator	NO <sub>x</sub>	495.45	1825.00		30	30
SR7STACK	SR7 Tail Gas Incinerator	CO (5)	777.95	2688.22		30	30
SR7STACK	SR7 Tail Gas Incinerator	PM	77.13	272.80		30	30
SR7STACK	SR7 Tail Gas Incinerator	SO <sub>2</sub>	2050.72	5259.84	2,4,21	2,4,21,30	2,4,30
SR7STACK	SR7 Tail Gas Incinerator	VOC	1877.69	2846.90		30	30
SR7STACK	SR7 Tail Gas Incinerator	H <sub>2</sub> S	29.61	85.77		30	30
SR8STACK	SR8 Tail Gas Incinerator	NO <sub>x</sub>	495.45	1,825.00	7	7,30	7,30
SR8STACK	SR8 Tail Gas Incinerator	CO (5)	777.95	2688.22	7	7,30	7,30
SR8STACK	SR8 Tail Gas Incinerator	PM	77.13	272.80		30	30
SR8STACK	SR8 Tail Gas Incinerator	SO <sub>2</sub>	2050.72	5259.84	2,4,7,21	2,4,7,21,30	2,4,7,30
SR8STACK	SR8 Tail Gas Incinerator	VOC	1877.69	2846.90		30	30
SR8STACK	SR8 Tail Gas Incinerator	H <sub>2</sub> S	29.61	85.77		30	30
SRTT	SR3/4 Loading Rack	VOC	1877.69	2846.90		30	30
SRTT	SR3/4 Loading Rack	H <sub>2</sub> S	29.61	85.77		30	30
SS306	SS306 Storage Tank	VOC	1877.69	2846.90		30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
SS307	SS307 Storage Tank	VOC	1877.69	2846.90		30	30
SS308	SS308 Storage Tank	VOC	1877.69	2846.90		30	30
SS312	SS312 Storage Tank	VOC	1877.69	2846.90		30	30
SS314	SS314 Storage Tank	VOC	1877.69	2846.90		30	30
SS316	SS316 Storage Tank	VOC	1877.69	2846.90		30	30
SS324	SS324 Storage Tank	VOC	1877.69	2846.90		30	30
SS325	SS325 Storage Tank	VOC	1877.69	2846.90		30	30
SS335	SS335 Storage Tank	VOC	1877.69	2846.90		30	30
SS339	SS339 Storage Tank	VOC	1877.69	2846.90		30	30
SS341	SS341 Storage Tank	VOC	1877.69	2846.90		30	30
SS343	SS343 Storage Tank	VOC	1877.69	2846.90		30	30
SS343	SS343 Storage Tank	H <sub>2</sub> S	29.61	85.77		30	30
SS344	SS344 Storage Tank	VOC	1877.69	2846.90		30	30
SS348	SS348 Storage Tank	VOC	1877.69	2846.90		30	30
SS364	SS364 Storage Tank	VOC	1877.69	2846.90		30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
SS375	SS375 Storage Tank	VOC	1877.69	2846.90	4	4,30	4,30
SS376	SS376 Storage Tank	VOC	1877.69	2846.90	2,4,17	2,4,17,30	2,4,30
SS376	SS376 Storage Tank	Benzene	10.96	30.36	2,4,17	2,4,17,30	2,4,30
SS377	SS377 Storage Tank	VOC	1877.69	2846.90	2,4,17	2,4,17,30	2,4,30
SS377	SS377 Storage Tank	Benzene	10.96	30.36	2,4,17	2,4,17,30	2,4,30
SS378	SS378 Storage Tank	VOC	1877.69	2846.90	2,4,17	2,4,17,30	2,4,30
SS378	SS378 Storage Tank	Benzene	10.96	30.36	2,4,17	2,4,17,30	2,4,30
SS379	SS379 Storage Tank	VOC	1877.69	2846.90	2,4,17	2,4,17,30	2,4,30
SS379	SS379 Storage Tank	Benzene	10.96	30.36	2,4,17	2,4,17,30	2,4,30
SS388	SS388 Storage Tank	VOC	1877.69	2846.90		30	30
SS396	SS396 Storage Tank	VOC	1877.69	2846.90		30	30
SS403	SS403 Storage Tank	VOC	1877.69	2846.90		30	30
SS403	SS403 Storage Tank	Benzene	10.96	30.36		30	30
SS425	SS425 Storage Tank	VOC	1877.69	2846.90	2,4,17	2,4,17,30	2,4,30
ST1400	X2HDU1 Storage Tank	VOC	1877.69	2846.90		30	30



Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
SULFUR	SR5 Sulfur Pit	VOC	1877.69	2846.90	4	4,30	4,30
SULFUR	SR5 Sulfur Pit	H <sub>2</sub> S	29.61	85.77	4	4,30	4,30
T1211	T1211 Storage Tank	VOC	1877.69	2846.90	4	4,30	4,30
T1212	T1212 Storage Tank	VOC	1877.69	2846.90		30	30
T1710	T1710 Storage Tank	VOC	1877.69	2846.90		30	30
T1F323	T1F323 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
T1F323	T1F323 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
T1F324	T1F324 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
T1F324	T1F324 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
T1F329	T1F329 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
T1F329	T1F329 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
T1F330	T1F330 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
T1F330	T1F330 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
T1F348	T1F348 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
T301	T301 Storage Tank	Benzene	10.96	30.36	2,3,4,17	2,3,4,17,30	2,3,4,30
T301	T301 Storage Tank	VOC	1877.69	2846.90	2,3,4,17	2,3,4,17,30	2,3,4,30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
T301	T301 Storage Tank	NH <sub>3</sub>	5.44	23.74	17	17,30	30
T302	T302 EXTFLT Refinery WW Storage Tank	VOC	1877.69	2846.90	2,3,4,17	2,3,4,17,30	2,3,4,30
T302	T302 EXTFLT Refinery WW Storage Tank	Benzene	10.96	30.36	2,3,4,17	2,3,4,17,30	2,3,4,30
T302	T302 EXTFLT Refinery WW Storage Tank	NH <sub>3</sub>	5.44	23.74	17	17,30	30
T315	T315 Storage Tank	VOC	1877.69	2846.90		30	30
T316	T316 Storage Tank	VOC	1877.69	2846.90	4	4,30	4,30
T59	T59 Storage Tank	VOC	1877.69	2846.90		30	30
T93002	T93002 Storage Tank	VOC	1877.69	2846.90	2	2,30	2,30
T93402	T93402 Storage Tank	VOC	1877.69	2846.90		30	30
TA301	TA301 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
TA301	TA301 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
TA301	TA301 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30
TA305	TA305 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
TA305	TA305 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
TA305	TA305 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30
TA306	TA306 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
TA306	TA306 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
TA306	TA306 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30
TA307	TA307 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
TA307	TA307 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
TA307	TA307 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30
TA308	TA308 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
TA308	TA308 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
TA309	TA309 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
TA309	TA309 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
TA310	TA310 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
TA310	TA310 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
TA310	TA310 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
TA312	TA312 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
TA312	TA312 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
TA312	TA312 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30
TA313	TA313 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
TA313	TA313 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
TA313	TA313 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30
TA315	TA315 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
TA315	TA315 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
TA315	TA315 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30
TA316	TA316 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
TA316	TA316 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
TA316	TA316 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30
TA317	TA317 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
TA317	TA317 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
TA317	TA317 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
TA318	TA318 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
TA318	TA318 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
TA318	TA318 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30
TA319	TA319 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
TA319	TA319 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
TA319	TA319 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30
TA320	TA320 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
TA320	TA320 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
TA320	TA320 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30
TA321	TA321 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
TA321	TA321 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
TA321	TA321 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30
TA322	TA322 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
TA322	TA322 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
TA322	TA322 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
TA324	TA324 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
TA324	TA324 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
TA324	TA324 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30
TA325	TA325 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
TA325	TA325 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
TA325	TA325 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30
TA326	TA326 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
TA326	TA326 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
TA326	TA326 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30
TA329	TA329 Storage Tank	VOC	1877.69	2846.90	2,17	2,17,30	2,30
TA329	TA329 Storage Tank	Benzene	10.96	30.36	2,17	2,17,30	2,30
TA329	TA329 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30
TA330	TA330 Storage Tank	Benzene	10.96	30.36	2,17	2,17,30	2,30
TA330	TA330 Storage Tank	VOC	1877.69	2846.90	2,17	2,17,30	2,30
TA330	TA330 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
TA331	TA331 Storage Tank	VOC	1877.69	2846.90	2,4,17	2,4,17,30	2,4,30
TA331	TA331 Storage Tank	Benzene	10.96	30.36	2,4,17	2,4,17,30	2,4,30
TA331	TA331 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30
TA332	TA332 Storage Tank	VOC	1877.69	2846.90	2,4,17	2,4,17,30	2,4,30
TA332	TA332 Storage Tank	Benzene	10.96	30.36	2,4,17	2,4,17,30	2,4,30
TA332	TA332 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30
TA334	TA334 Storage Tank	VOC	1877.69	2846.90	2,4,17	2,4,17,30	2,4,30
TA334	TA334 Storage Tank	Benzene	10.96	30.36	2,4,17	2,4,17,30	2,4,30
TA334	TA334 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30
TC and G	WW – Thermal Cracking and Gas Treating	VOC	1877.69	2846.90		30	30
TC and G	WW – Thermal Cracking and Gas Treating	Benzene	10.96	30.36	3,4	3,4,30	3,4,30
TC and G	WW – Thermal Cracking and Gas Treating	NH <sub>3</sub>	5.44	23.74		30	30
TCACIDLOAD	Acid tank Car Loading	VOC	1877.69	2846.90	2	2,30	2,30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
TG324	TG324 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
TG324	TG324 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
TG324	TG324 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30
TG362	TG362 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
TG362	TG362 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
TG362	TG362 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30
TJ333	TJ333 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
TJ333	TJ333 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
TJ334	TJ334 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
TJ334	TJ334 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
TJ335	TJ335 Storage Tank	VOC	1877.69	2846.90	4,17	4,17,30	4,30
TJ335	TJ335 Storage Tank	Benzene	10.96	30.36	4,17	4,17,30	4,30
TJ339R1	TJ339R1 Storage Tank	VOC	1877.69	2846.90	17	17,30	30
TJ339R1	TJ339R1 Storage Tank	Benzene	10.96	30.36	17	17,30	30
TJ339R1	TJ339R1 Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30



Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
TK305	TK305 Storage Tank	VOC	1877.69	2846.90		30	30
TK305	TK305 Storage Tank	Benzene	10.96	30.36		30	30
TRKLFIL	WW – Trickle Filter	VOC	1877.69	2846.90		30	30
TRKLFIL	WW – Trickle Filter	Benzene	10.96	30.36	3	3,30	3,30
TRKLFIL	WW – Trickle Filter	NH <sub>3</sub>	5.44	23.74		30	30
TRKLSMP	WW – Trickle Sump	VOC	1877.69	2846.90		30	30
TRKLSMP	WW – Trickle Sump	Benzene	10.96	30.36	3	3,30	3,30
TRKLSMP	WW – Trickle Sump	NH <sub>3</sub>	5.44	23.74		30	30
TSR67	Molten Sulfur Tank	H <sub>2</sub> S	29.61	85.77		30	30
U301	U301 Storage Tank	VOC	1877.69	2846.90		30	30
U302	U302 Storage Tank	VOC	1877.69	2846.90		30	30
V1111	V1111 Storage Tank	VOC	1877.69	2846.90	4	4,30	4,30
V54	Vessel/Regen Gas KO Pot	VOC	1877.69	2846.90		30	30
V5518	Hydrogen Plant Vent	CO (5)	22.14	96.98			
V5518	Hydrogen Plant Vent	VOC	14.79	53.98			
V5527	Column in HP1	VOC	1877.69	2846.90		30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
V9160	Vent V9160	VOC	1877.69	2846.90		30	30
VA03	VA03 Storage Tank	VOC	1877.69	2846.90		30	30
VA03	VA03 Storage Tank	H <sub>2</sub> S	29.61	85.77		30	30
VA04	VA04 Storage Tank	VOC	1877.69	2846.90		30	30
VA04	VA04 Storage Tank	H <sub>2</sub> S	29.61	85.77		30	30
WAXPTOWS	WW – Sewer Wax Plant Oily Water	VOC	1877.69	2846.90		30	30
WAXPTOWS	WW – Sewer Wax Plant Oily Water	Benzene	10.96	30.36	3,4	3,4,30	3,4,30
WAXPTOWS	WW – Sewer Wax Plant Oily Water	NH <sub>3</sub>	5.44	23.74		30	30
WAXPTWAX	WW – Sewer Wax Plant Wax	VOC	1877.69	2846.90		30	30
WAXPTWAX	WW – Sewer Wax Plant Wax	Benzene	10.96	30.36	3,4	3,4,30	3,4,30
WAXPTWAX	WW – Sewer Wax Plant Wax	NH <sub>3</sub>	5.44	23.74		30	30
WX285	WX285 Storage Tank	VOC	1877.69	2846.90		30	30
X2HDU1	FXTNK2/ X2HDU1 Storage Tank	VOC	1877.69	2846.90		30	30
X311	INTFLT/A mine Solutions Storage Tank	VOC	1877.69	2846.90	17	17,30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
X311	INTFLT/A mine Solutions Storage Tank	Benzene	10.96	30.36	17	17,30	30
X311	INTFLT/A mine Solutions Storage Tank	NH <sub>3</sub>	5.44	23.74	17	17,30	30
X312	INTFLT/A mine Solutions Storage Tank	VOC	1877.69	2846.90	17	17,30	30
X312	INTFLT/A mine Solutions Storage Tank	Benzene	10.96	30.36	17	17,30	30
X312	INTFLT/A mine Solutions Storage Tank	NH <sub>3</sub>	5.44	23.74	17	17,30	30
X313	INTFLT/SI op Oil Storage Tank	VOC	1877.69	2846.90	17	17,30	30
X313	INTFLT/SI op Oil Storage Tank	Benzene	10.96	30.36	17	17,30	30
X313	INTFLT/SI op Oil Storage Tank	H <sub>2</sub> S	29.61	85.77	17	17,30	30
X315	Ballast Water Storage Tank	VOC	1877.69	2846.90	3,4,17	3,4,17,30	3,4,30
X315	Ballast Water Storage Tank	Benzene	10.96	30.36	3,4,17	3,4,17,30	3,4,30
X316	WW – DAF Float	VOC	1877.69	2846.90	3	3,30	3,30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
X316	WW – DAF Float	Benzene	10.96	30.36	3	3,30	3,30
X316	WW – DAF Float	NH <sub>3</sub>	5.44	23.74		30	30
X320	Ballast Water O/S Storage Tank	VOC	1877.69	2846.90	3,4,17	3,4,17,30	3,4,30
X320	Ballast Water O/S Storage Tank	Benzene	10.96	30.36	3,4,17	3,4,17,30	3,4,30
X321	Slop Oil Storage Tank	VOC	1877.69	2846.90	3,4,17	3,4,17,30	3,4,30
X321	Slop Oil Storage Tank	Benzene	10.96	30.36	3,4,17	3,4,17,30	3,4,30
X322	X322 Storage Tank	VOC	1877.69	2846.90	3,4,17	3,4,17,30	3,4,30
X322	X322 Storage Tank	Benzene	10.96	30.36	3,4,17	3,4,17,30	3,4,30
X323	X323 Storage Tank	VOC	1877.69	2846.90	3,4,17	3,4,17,30	3,4,30
X323	X323 Storage Tank	Benzene	10.96	30.36	3,4,17	3,4,17,30	3,4,30
X324	FXTNK2/ Misc Organic Storage Tank	VOC	1877.69	2846.90		30	30
X324	FXTNK2/ Misc Organic Storage Tank	Benzene	10.96	30.36		30	30
X325	FXTNK2/ Misc Organic Storage Tank	VOC	1877.69	2846.90		30	30

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
X325	FXTNK2/ Misc Organic Storage Tank	Benzene	10.96	30.36		30	30
X326	FXTNK2/ DAF Float Storage Tank	VOC	1877.69	2846.90		30	30
X326	FXTNK2/ DAF Float Storage Tank	Benzene	10.96	30.36		30	30
X327	FXTNK2/ DAF Float Storage Tank	VOC	1877.69	2846.90		30	30
X327	FXTNK2/ DAF Float Storage Tank	Benzene	10.96	30.36		30	30
X328	FXTNK2/ Misc Organic Storage Tank	VOC	1877.69	2846.90		30	30
X328	FXTNK2/ Misc Organic Storage Tank	Benzene	10.96	30.36		30	30
X330	WW – Equalization tank	VOC	1877.69	2846.90	2,3	2,3,30	2,3,30
X330	WW – Equalization tank	Benzene	10.96	30.36	2,3	2,3,30	2,3,30
X330	WW – Equalization tank	NH <sub>3</sub>	5.44	23.74		30	30
X330SM	WW - Sump	VOC	1877.69	2846.90		30	30
X330SM	WW - Sump	Benzene	10.96	30.36	3,4	3,4,30	3,4,30
X330SM	WW - Sump	NH <sub>3</sub>	5.44	23.74		30	30

Planned Maintenance, Startup and Shutdown (MSS) Emission rate Limits

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
CRUDES	Shutdown of DU-2,VF-3,VF-4,HDU-2	NO <sub>x</sub>	14.77	0.70	41	40,41	
CRUDES	Shutdown of DU-2,VF-3,VF-4,HDU-2	CO	199.70	11.46	41	40,41	
CRUDES	Shutdown of DU-2,VF-3,VF-4,HDU-2	PM	18.31	12.43	41	40,41	
CRUDES	Shutdown of DU-2,VF-3,VF-4,HDU-2	SO <sub>2</sub>	1560.81	46.29	41	40,41	
CRUDES	Shutdown of DU-2,VF-3,VF-4,HDU-2	VOC	2588.61	61.08	41	40,41	
RUDES	Shutdown of DU-2,VF-3,VF-4,HDU-2	Benzene	19.80	0.78	41	40,41	
CRUDES	Shutdown of DU-2,VF-3,VF-4,HDU-2	H <sub>2</sub> S	59.86	2.43	41	40,41	
COKERS	Shutdown of Cokers,GO HT	NO <sub>x</sub>	14.77	0.70	41	40,41	
COKERS	Shutdown of Cokers,GO HT	CO	199.70	11.46	41	40,41	
COKERS	Shutdown of Cokers,GO HT	PM	18.31	12.43	41	40,41	
COKERS	Shutdown of Cokers,GO HT	SO <sub>2</sub>	1560.81	46.29	41	40,41	
COKERS	Shutdown of Cokers,GO HT	VOC	2588.61	61.08	41	40,41	

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
COKERSD	Shutdown of Cokers,GO HT	Benzene	19.80	0.78	41	40,41	
COKERSD	Shutdown of Cokers,GO HT	H <sub>2</sub> S	59.86	2.43	41	40,41	
SGPSD	Shutdown of SGP	NO <sub>x</sub>	14.77	0.70	41	40,41	
SGPSD	Shutdown of SGP	CO	199.70	11.46	41	40,41	
SGPSD	Shutdown of SGP	PM	18.31	12.43	41	40,41	
SGPSD	Shutdown of SGP	SO <sub>2</sub>	1560.81	46.29	41	40,41	
SGPSD	Shutdown of SGP	VOC	2588.61	61.08	41	40,41	
SGPSD	Shutdown of SGP	Benzene	19.80	0.78	41	40,41	
SGPSD	Shutdown of SGP	H <sub>2</sub> S	59.86	2.43	41	40,41	
SULFURSD	Shutdown of Sulfur Block	NO <sub>x</sub>	14.77	0.70	41	40,41	
SULFURSD	Shutdown of Sulfur Block	CO	199.70	11.46	41	40,41	
SULFURSD	Shutdown of Sulfur Block	PM	18.31	12.43	41	40,41	
SULFURSD	Shutdown of Sulfur Block	SO <sub>2</sub>	1560.81	46.29	41	40,41	
SULFURSD	Shutdown of Sulfur Block	VOC	2588.61	61.08	41	40,41	
SULFURSD	Shutdown of Sulfur Block	Benzene	19.80	0.78	41	40,41	
SULFURSD	Shutdown of Sulfur Block	H <sub>2</sub> S	59.86	2.43	41	40,41	
SHCUSD	Shutdown of SHCU	NO <sub>x</sub>	14.77	0.70	41	40,41	

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
SHCUSD	Shutdown of SHCU	CO	199.70	11.46	41	40,41	
SHCUSD	Shutdown of SHCU	PM	18.31	12.43	41	40,41	
SHCUSD	Shutdown of SHCU	SO <sub>2</sub>	1560.81	46.29	41	40,41	
SHCUSD	Shutdown of SHCU	VOC	2588.61	61.08	41	40,41	
SHCUSD	Shutdown of SHCU	Benzene	19.80	0.78	41	40,41	
SHCUSD	Shutdown of SHCU	H <sub>2</sub> S	59.86	2.43	41	40,41	
HP1SDSU	Shutdown/Startup of HP-1	NO <sub>x</sub>	14.77	0.70	41	40,41	
HP1SDSU	Shutdown/Startup of HP-1	CO	199.70	11.46	41	40,41	
HP1SDSU	Shutdown/Startup of HP-1	PM	18.31	12.43	41	40,41	
HP1SDSU	Shutdown/Startup of HP-1	SO <sub>2</sub>	1560.81	46.29	41	40,41	
HP1SDSU	Shutdown/Startup of HP-1	VOC	2588.61	61.08	41	40,41	
HP1SDSU	Shutdown/Startup of HP-1	Benzene	19.80	0.78	41	40,41	
HP1SDSU	Shutdown/Startup of HP-1	H <sub>2</sub> S	59.86	2.43	41	40,41	
DPREFSDSU	Shutdown/Startup of Other Units	NO <sub>x</sub>	14.77	0.70	41	40,41	
DPREFSDSU	Shutdown/Startup of Other Units	CO	199.70	11.46	41	40,41	
DPREFSDSU	Shutdown/Startup of Other Units	PM	18.31	12.43	41	40,41	
DPREFSDSU	Shutdown/Startup of Other Units	SO <sub>2</sub>	1560.81	46.29	41	40,41	



Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
DPREFSDSU	Shutdown/ Startup of Other Units	VOC	2588.61	61.08	41	40,41	
DPREFSDSU	Shutdown/ Startup of Other Units	Benzene	19.80	0.78	41	40,41	
DPREFSDSU	Shutdown/ Startup of Other Units	H <sub>2</sub> S	59.86	2.43	41	40,41	
FLNFLARE	North Property Flare	NO <sub>x</sub>	14.77	0.70	41,49,50	40,41,49,50	
FLNFLARE	North Property Flare	CO	199.70	11.46	41,49,50	40,41,49,50	
FLNFLARE	North Property Flare	PM	18.31	12.43	41,49,50	40,41,49,50	
FLNFLARE	North Property Flare	SO <sub>2</sub>	1560.81	46.29	41,49,50	40,41,49,50	
FLNFLARE	North Property Flare	VOC	2588.61	61.08	41,49,50	40,41,49,50	
FLNFLARE	North Property Flare	Benzene	19.80	0.78	41,49,50	40,41,49,50	
FLNFLARE	North Property Flare	H <sub>2</sub> S	59.86	2.43	41,49,50	40,41,49,50	
COKE FLARE	Coker Flare	NO <sub>x</sub>	14.77	0.70	41,49,50	40,41,49,50	
COKE FLARE	Coker Flare	CO	199.70	11.46	41,49,50	40,41,49,50	
COKE FLARE	Coker Flare	PM	18.31	12.43	41,49,50	40,41,49,50	
COKE FLARE	Coker Flare	SO <sub>2</sub>	1560.81	46.29	41,49,50	40,41,49,50	
COKE FLARE	Coker Flare	VOC	2588.61	61.08	41,49,50	40,41,49,50	
COKE FLARE	Coker Flare	Benzene	19.80	0.78	41,49,50	40,41,49,50	
COKE FLARE	Coker Flare	H <sub>2</sub> S	59.86	2.43	41,49,50	40,41,49,50	
WP FLARE	West Property Flare	NO <sub>x</sub>	14.77	0.70	41,49,50	40,41,49,50	
WP FLARE	West Property Flare	CO	199.70	11.46	41,49,50	40,41,49,50	

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
WP FLARE	West Property Flare	PM	18.31	12.43	41,49,50	40,41,49,50	
WP FLARE	West Property Flare	SO <sub>2</sub>	1560.81	46.29	41,49,50	40,41,49,50	
WP FLARE	West Property Flare	VOC	2588.61	61.08	41,49,50	40,41,49,50	
WP FLARE	West Property Flare	Benzene	19.80	0.78	41,49,50	40,41,49,50	
WP FLARE	West Property Flare	H <sub>2</sub> S	59.86	2.43	41,49,50	40,41,49,50	
EP FLARE	East Property Flare	NO <sub>x</sub>	14.77	0.70	41,49,50	40,41,49,50	
EP FLARE	East Property Flare	CO	199.70	11.46	41,49,50	40,41,49,50	
EP FLARE	East Property Flare	PM	18.31	12.43	41,49,50	40,41,49,50	
EP FLARE	East Property Flare	SO <sub>2</sub>	1560.81	46.29	41,49,50	40,41,49,50	
EP FLARE	East Property Flare	VOC	2588.61	61.08	41,49,50	40,41,49,50	
EP FLARE	East Property Flare	Benzene	19.80	0.78	41,49,50	40,41,49,50	
EP FLARE	East Property Flare	H <sub>2</sub> S	59.86	2.43	41,49,50	40,41,49,50	
TA324	MAYA Crude	NO <sub>x</sub>	14.77	0.70	44,49	40,44,49	
TA324	MAYA Crude	CO	199.70	11.46	44,49	40,44,49	
TA324	MAYA Crude	PM	18.31	12.43	44	40,44	
TA324	MAYA Crude	SO <sub>2</sub>	1560.81	46.29	44	40,44	

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
TA324	MAYA Crude	VOC	2588.61	61.08	44	40,44	
TA324	MAYA Crude	Benzene	19.80	0.78	44	40,44	
TA324	MAYA Crude	H <sub>2</sub> S	59.86	2.43	44	40,44	
TA325	DUI Crude	NO <sub>x</sub>	14.77	0.70	44,49	40,44,49	
TA325	DUI Crude	CO	199.70	11.46	44,49	40,44,49	
TA325	DUI Crude	PM	18.31	12.43	44	40,44	
TA325	DUI Crude	SO <sub>2</sub>	1560.81	46.29	44	40,44	
TA325	DUI Crude	VOC	2588.61	61.08	44	40,44	
TA325	DUI Crude	Benzene	19.80	0.78	44	40,44	
TA325	DUI Crude	H <sub>2</sub> S	59.86	2.43	44	40,44	
TA326	DUI Crude	NO <sub>x</sub>	14.77	0.70	44,49	40,44,49	
TA326	DUI Crude	CO	199.70	11.46	44,49	40,44,49	
TA326	DUI Crude	PM	18.31	12.43	44	40,44	
TA326	DUI Crude	SO <sub>2</sub>	1560.81	46.29	44	40,44	
TA326	DUI Crude	VOC	2588.61	61.08	44	40,44	
TA326	DUI Crude	Benzene	19.80	0.78	44	40,44	
TA326	DUI Crude	H <sub>2</sub> S	59.86	2.43	44	40,44	
F364	MAYA Crude	NO <sub>x</sub>	14.77	0.70	44,49	40,44,49	
F364	MAYA Crude	CO	199.70	11.46	44,49	40,44,49	
F364	MAYA Crude	PM	18.31	12.43	44	40,44	
F364	MAYA Crude	SO <sub>2</sub>	1560.81	46.29	44	40,44	
F364	MAYA Crude	VOC	2588.61	61.08	44	40,44	
F364	MAYA Crude	Benzene	19.80	0.78	44	40,44	
F364	MAYA Crude	H <sub>2</sub> S	59.86	2.43	44	40,44	
TG362	MAYA Crude	NO <sub>x</sub>	14.77	0.70	44,49	40,44,49	
TG362	MAYA Crude	CO	199.70	11.46	44,49	40,44,49	

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
TG362	MAYA Crude	PM	18.31	12.43	44	40,44	
TG362	MAYA Crude	SO <sub>2</sub>	1560.81	46.29	44	40,44	
TG362	MAYA Crude	VOC	2588.61	61.08	44	40,44	
TG362	MAYA Crude	Benzene	19.80	0.78	44	40,44	
TG362	MAYA Crude	H <sub>2</sub> S	59.86	2.43	44	40,44	
TA329	MAYA Crude	NO <sub>x</sub>	14.77	0.70	44,49	40,44,49	
TA329	MAYA Crude	CO	199.70	11.46	44,49	40,44,49	
TA329	MAYA Crude	PM	18.31	12.43	44	40,44	
TA329	MAYA Crude	SO <sub>2</sub>	1560.81	46.29	44	40,44	
TA329	MAYA Crude	VOC	2588.61	61.08	44	40,44	
TA329	MAYA Crude	Benzene	19.80	0.78	44	40,44	
TA329	MAYA Crude	H <sub>2</sub> S	59.86	2.43	44	40,44	
TA330	MAYA Crude	NO <sub>x</sub>	14.77	0.70	44,49	40,44,49	
TA330	MAYA Crude	CO	199.70	11.46	44,49	40,44,49	
TA330	MAYA Crude	PM	18.31	12.43	44	40,44	
TA330	MAYA Crude	SO <sub>2</sub>	1560.81	46.29	44	40,44	
TA330	MAYA Crude	VOC	2588.61	61.08	44	40,44	
TA330	MAYA Crude	Benzene	19.80	0.78	44	40,44	
TA330	MAYA Crude	H <sub>2</sub> S	59.86	2.43	44	40,44	
TA331	MAYA Crude	NO <sub>x</sub>	14.77	0.70	44,49	40,44,49	
TA331	MAYA Crude	CO	199.70	11.46	44,49	40,44,49	

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
TA331	MAYA Crude	PM	18.31	12.43	44	40,44	
TA331	MAYA Crude	SO <sub>2</sub>	1560.81	46.29	44	40,44	
TA331	MAYA Crude	VOC	2588.61	61.08	44	40,44	
TA331	MAYA Crude	Benzene	19.80	0.78	44	40,44	
TA331	MAYA Crude	H <sub>2</sub> S	59.86	2.43	44	40,44	
TA332	MAYA Crude	NO <sub>x</sub>	14.77	0.70	44,49	40,44,49	
TA332	MAYA Crude	CO	199.70	11.46	44,49	40,44,49	
TA332	MAYA Crude	PM	18.31	12.43	44	40,44	
TA332	MAYA Crude	SO <sub>2</sub>	1560.81	46.29	44	40,44	
TA332	MAYA Crude	VOC	2588.61	61.08	44	40,44	
TA332	MAYA Crude	Benzene	19.80	0.78	44	40,44	
TA332	MAYA Crude	H <sub>2</sub> S	59.86	2.43	44	40,44	
TA334	MAYA Crude	NO <sub>x</sub>	14.77	0.70	44,49	40,44,49	
TA334	MAYA Crude	CO	199.70	11.46	44,49	40,44,49	
TA334	MAYA Crude	PM	18.31	12.43	44	40,44	
TA334	MAYA Crude	SO <sub>2</sub>	1560.81	46.29	44	40,44	
TA334	MAYA Crude	VOC	2588.61	61.08	44	40,44	
TA334	MAYA Crude	Benzene	19.80	0.78	44	40,44	
TA334	MAYA Crude	H <sub>2</sub> S	59.86	2.43	44	40,44	
G313	Gasoline (RU2000)	NO <sub>x</sub>	14.77	0.70	44,49	40,44,49	
G313	Gasoline (RU2000)	CO	199.70	11.46	44,49	40,44,49	

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
G313	Gasoline (RU2000)	PM	18.31	12.43	44	40,44	
G313	Gasoline (RU2000)	SO <sub>2</sub>	1560.81	46.29	44	40,44	
G313	Gasoline (RU2000)	VOC	2588.61	61.08	44	40,44	
G313	Gasoline (RU2000)	Benzene	19.80	0.78	44	40,44	
G313	Gasoline (RU2000)	H <sub>2</sub> S	59.86	2.43	44	40,44	
G315	Gasoline (RU2000)	NO <sub>x</sub>	14.77	0.70	44,49	40,44,49	
G315	Gasoline (RU2000)	CO	199.70	11.46	44,49	40,44,49	
G315	Gasoline (RU2000)	PM	18.31	12.43	44	40,44	
G315	Gasoline (RU2000)	SO <sub>2</sub>	1560.81	46.29	44	40,44	
G315	Gasoline (RU2000)	VOC	2588.61	61.08	44	40,44	
G315	Gasoline (RU2000)	Benzene	19.80	0.78	44	40,44	
G315	Gasoline (RU2000)	H <sub>2</sub> S	59.86	2.43	44	40,44	
G323	Gasoline (RU2000)	NO <sub>x</sub>	14.77	0.70	44,49	40,44,49	
G323	Gasoline (RU2000)	CO	199.70	11.46	44,49	40,44,49	
G323	Gasoline (RU2000)	PM	18.31	12.43	44	40,44	
G323	Gasoline (RU2000)	SO <sub>2</sub>	1560.81	46.29	44	40,44	
G323	Gasoline (RU2000)	VOC	2588.61	61.08	44	40,44	
G323	Gasoline (RU2000)	Benzene	19.80	0.78	44	40,44	
G323	Gasoline (RU2000)	H <sub>2</sub> S	59.86	2.43	44	40,44	
G326	Gasoline (RU2000)	NO <sub>x</sub>	14.77	0.70	44,49	40,44,49	
G326	Gasoline (RU2000)	CO	199.70	11.46	44,49	40,44,49	
G326	Gasoline (RU2000)	PM	18.31	12.43	44	40,44	
G326	Gasoline (RU2000)	SO <sub>2</sub>	1560.81	46.29	44	40,44	
G326	Gasoline (RU2000)	VOC	2588.61	61.08	44	40,44	
G326	Gasoline (RU2000)	Benzene	19.80	0.78	44	40,44	
G326	Gasoline (RU2000)	H <sub>2</sub> S	59.86	2.43	44	40,44	

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
G327	Gasoline (RU2000)	NO <sub>x</sub>	14.77	0.70	44,49	40,44,49	
G327	Gasoline (RU2000)	CO	199.70	11.46	44,49	40,44,49	
G327	Gasoline (RU2000)	PM	18.31	12.43	44	40,44	
G327	Gasoline (RU2000)	SO <sub>2</sub>	1560.81	46.29	44	40,44	
G327	Gasoline (RU2000)	VOC	2588.61	61.08	44	40,44	
G327	Gasoline (RU2000)	Benzene	19.80	0.78	44	40,44	
G327	Gasoline (RU2000)	H <sub>2</sub> S	59.86	2.43	44	40,44	
FUGABRBLST	Abrasive Blasting: Sitewide	NO <sub>x</sub>	14.77	0.70	43	40,43,52,53	
FUGABRBLST	Abrasive Blasting: Sitewide	CO	199.70	11.46	43	40,43,52,53	
FUGABRBLST	Abrasive Blasting: Sitewide	PM	18.31	12.43	43	40,43,52,53	
FUGABRBLST	Abrasive Blasting: Sitewide	SO <sub>2</sub>	1560.81	46.29	43	40,43,52,53	
FUGABRBLST	Abrasive Blasting: Sitewide	VOC	2588.61	61.08	43	40,43,52,53	
FUGABRBLST	Abrasive Blasting: Sitewide	Benzene	19.80	0.78	43	40,43,52,53	
FUGABRBLST	Abrasive Blasting: Sitewide	H <sub>2</sub> S	59.86	2.43	43	40,43,52,53	
AEROSDISP	Aerosol Can Crushing and Disposal	NO <sub>x</sub>	14.77	0.70		40	
AEROSDISP	Aerosol Can Crushing and Disposal	CO	199.70	11.46		40	

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
AEROSDISP	Aerosol Can Crushing and Disposal	PM	18.31	12.43		40	
AEROSDISP	Aerosol Can Crushing and Disposal	SO <sub>2</sub>	1560.81	46.29		40	
AEROSDISP	Aerosol Can Crushing and Disposal	VOC	2588.61	61.08		40	
AEROSDISP	Aerosol Can Crushing and Disposal	Benzene	19.80	0.78		40	
AEROSDISP	Aerosol Can Crushing and Disposal	H <sub>2</sub> S	59.86	2.43		40	
AEROSAPPL	Aerosol Can Application : Paint and Solvents	NO <sub>x</sub>	14.77	0.70		40	
AEROSAPPL	Aerosol Can Application : Paint and Solvents	CO	199.70	11.46		40	
AEROSAPPL	Aerosol Can Application : Paint and Solvents	PM	18.31	12.43		40	
AEROSAPPL	Aerosol Can Application : Paint and Solvents	SO <sub>2</sub>	1560.81	46.29		40	
AEROSAPPL	Aerosol Can Application : Paint and Solvents	VOC	2588.61	61.08		40	



Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
AEROSAPPL	Aerosol Can Application : Paint and Solvents	Benzene	19.80	0.78		40	
AEROSAPPL	Aerosol Can Application : Paint and Solvents	H <sub>2</sub> S	59.86	2.43		40	
DEGREAS01	Chemical Cleaning – Degreaser Units	NO <sub>x</sub>	14.77	0.70		40	
DEGREAS01	Chemical Cleaning – Degreaser Units	CO	199.70	11.46		40	
DEGREAS01	Chemical Cleaning – Degreaser Units	PM	18.31	12.43		40	
DEGREAS01	Chemical Cleaning – Degreaser Units	SO <sub>2</sub>	1560.81	46.29		40	
DEGREAS01	Chemical Cleaning – Degreaser Units	VOC	2588.61	61.08		40	
DEGREAS01	Chemical Cleaning – Degreaser Units	Benzene	19.80	0.78		40	
DEGREAS01	Chemical Cleaning – Degreaser Units	H <sub>2</sub> S	59.86	2.43		40	
FUGSMPDPR	Process Sampling	NO <sub>x</sub>	14.77	0.70	43	40,43	
FUGSMPDPR	Process Sampling	CO	199.70	11.46	43	40,43	
FUGSMPDPR	Process Sampling	PM	18.31	12.43	43	40,43	
FUGSMPDPR	Process Sampling	SO <sub>2</sub>	1560.81	46.29	43	40,43	

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
FUGSMPDPR	Process Sampling	VOC	2588.61	61.08	43	40,43	
FUGSMPDPR	Process Sampling	Benzene	19.80	0.78	43	40,43	
FUGSMPDPR	Process Sampling	H <sub>2</sub> S	59.86	2.43	43	40,43	
FUGMSSDPR	Fugitive Components Associated with Maintenance	NO <sub>x</sub>	14.77	0.70	41,43	40,41,43	
FUGMSSDPR	Fugitive Components Associated with Maintenance	CO	199.70	11.46	41,43	40,41,43	
FUGMSSDPR	Fugitive Components Associated with Maintenance	PM	18.31	12.43	41,43	40,41,43	
FUGMSSDPR	Fugitive Components Associated with Maintenance	SO <sub>2</sub>	1560.81	46.29	41,43	40,41,43	
FUGMSSDPR	Fugitive Components Associated with Maintenance	VOC	2588.61	61.08	41,43	40,41,43	
FUGMSSDPR	Fugitive Components Associated with Maintenance	Benzene	19.80	0.78	41,43	40,41,43	

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
FUGMSSDPR	Fugitive Components Associated with Maintenance	H <sub>2</sub> S	59.86	2.43	41,43	40,41,43	
FUGVACDPR	Vacuum Truck Loading & Unloading	NO <sub>x</sub>	14.77	0.70	43,46	40,43,46	
FUGVACDPR	Vacuum Truck Loading & Unloading	CO	199.70	11.46	43,46	40,43,46	
FUGVACDPR	Vacuum Truck Loading & Unloading	PM	18.31	12.43	43,46	40,43,46	
FUGVACDPR	Vacuum Truck Loading & Unloading	SO <sub>2</sub>	1560.81	46.29	43,46	40,43,46	
FUGVACDPR	Vacuum Truck Loading & Unloading	VOC	2588.61	61.08	43,46	40,43,46	
FUGVACDPR	Vacuum Truck Loading & Unloading	Benzene	19.80	0.78	43,46	40,43,46	
FUGVACDPR	Vacuum Truck Loading & Unloading	H <sub>2</sub> S	59.86	2.43	43,46	40,43,46	
PAINTFE	Painting Emissions Sitewide	NO <sub>x</sub>	14.77	0.70		40,51	
PAINTFE	Painting Emissions Sitewide	CO	199.70	11.46		40,51	
PAINTFE	Painting Emissions Sitewide	PM	18.31	12.43		40,51	
PAINTFE	Painting Emissions Sitewide	SO <sub>2</sub>	1560.81	46.29		40,51	
PAINTFE	Painting Emissions Sitewide	VOC	2588.61	61.08		40,51	

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
PAINTFE	Painting Emissions Sitewide	Benzene	19.80	0.78		40,51	
PAINTFE	Painting Emissions Sitewide	H <sub>2</sub> S	59.86	2.43		40,51	
MSSDECNDPR	Combustion Device Decoking Pump and Minor Process Decontamination	NO <sub>x</sub>	14.77	0.70	41	40,41,48	
MSSDECNDPR	Combustion Device Decoking Pump and Minor Process Decontamination	CO	199.70	11.46	41	40,41,48	
MSSDECNDPR	Combustion Device Decoking Pump and Minor Process Decontamination	PM	18.31	12.43	41	40,41,48	
MSSDECNDPR	Combustion Device Decoking Pump and Minor Process Decontamination	SO <sub>2</sub>	1560.81	46.29	41	40,41,48	
MSSDECNDPR	Combustion Device Decoking Pump and Minor Process Decontamination	VOC	2588.61	61.08	41	40,41,48	

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.
MSSDECNDPR	Combustion Device Decoking Pump and Minor Process Decontamination	Benzene	19.80	0.78	41	40,41,48	
MSSDECNDPR	Combustion Device Decoking Pump and Minor Process Decontamination	H <sub>2</sub> S	59.86	2.43	41	40,41,48	
TNKVENT	Forced Ventilation of Tank w/ Residual	NO <sub>x</sub>	14.77	0.70	45	40	
TNKVENT	Forced Ventilation of Tank w/ Residual	CO	199.70	11.46	45	40	
TNKVENT	Forced Ventilation of Tank w/ Residual	PM	18.31	12.43	45	40	
TNKVENT	Forced Ventilation of Tank w/ Residual	SO <sub>2</sub>	1560.81	46.29	45	40	
TNKVENT	Forced Ventilation of Tank w/ Residual	VOC	2588.61	61.08	45	40	
TNKVENT	Forced Ventilation of Tank w/ Residual	Benzene	19.80	0.78	45	40	
TNKVENT	Forced Ventilation of Tank w/ Residual	H <sub>2</sub> S	59.86	2.43	45	40	

Permit Number: 21262 and PSDTX928 (Version Date: 01/27/2011)

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY**	Spec. Cond.	Spec. Cond.	Spec. Cond.

- (1) Emission point identification – either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources use area name or fugitive source name.
- (3) CO - carbon monoxide  
 H<sub>2</sub>S - hydrogen sulfide  
 NH<sub>3</sub> - ammonia  
 NO<sub>x</sub> - nitrogen oxides  
 PM - particulate matter suspended in the atmosphere,including PM<sub>10</sub>  
 PM<sub>10</sub> - particulate matter equal to or less than 10 microns in diameter. Where PM is not listed,it shall be assumed that no particulate matter greater than 10 microns is emitted.  
 SO<sub>2</sub> - sulfur oxide  
 VOC - volatile organic compounds as defined in Table 30 Texas Administrative Code § 101.1
- (4) Fugitive emissions are an estimate only and should not be considered as a maximum allowable emission rate.
- (5) In the Amendment submitted June 23,2009,existing CO emissions from EPN V5518 were permitted and offset by a decrease in the EPN H600 long-term CO cap contribution. For normal operational requirements,the short-term cap was left unchanged. The remainder of the CO limit from H600 was removed from the cap and added as an individual limit.

\* Emission rates are based on and the facilities are limited by the following maximum operating schedule:  
 Hrs/day      Days/week      Weeks/year      or Hrs/year 8,760

\*\* Compliance with annual emission limits is based on a rolling 12-month period.

Note - Emission rates represent flexible permit cap limits,not individual source limits.

## Emission Sources - Maximum Allowable Emission Rates

Permit Number 37206 and PSDTX896

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
H87920	Phenol/Acetone Plant Boiler	NO <sub>x</sub>	37.00	132.77
		CO	32.00	93.82
		VOC	1.60	6.25
		SO <sub>2</sub>	12.65	34.69
		PM (5)	12.28	48.00
		PM <sub>10</sub> (5)	12.28	48.00
		PM <sub>2.5</sub> (5)	12.28	48.00
		PM (6)	65.00	---
		PM <sub>10</sub> (6)	65.00	---
		PM <sub>2.5</sub> (6)	65.00	---
FUGBIFBOIL	Piping Fugitives (7)	VOC	0.14	0.58

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
- NO<sub>x</sub> - total oxides of nitrogen
- SO<sub>2</sub> - sulfur dioxide
- PM - total particulate matter, suspended in the atmosphere, including PM<sub>10</sub> and PM<sub>2.5</sub>, as represented
- PM<sub>10</sub> - total particulate matter equal to or less than 10 microns in diameter, including PM<sub>2.5</sub>, as represented
- PM<sub>2.5</sub> - particulate matter equal to or less than 2.5 microns in diameter
- CO - carbon monoxide
- HAP - hazardous air pollutant as listed in § 112(b) of the Federal Clean Air Act or Title 40 Code of Federal Regulations Part 63, Subpart C
- (4) Compliance with annual emission limits (tons per year) is based on a 12 month rolling period.
- (5) Pounds per hour emission rate without soot blowing, annual emission rate includes soot blowing.

Emission Sources - Maximum Allowable Emission Rates

- (6) Pound per hour emission rate during soot blowing.
- (7) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.

Date: October 31, 2013



## SPECIAL CONDITIONS

Permit Numbers 37206 and PSDTX896

### EMISSION LIMITATIONS AND OPERATING CONDITIONS

1. This permit covers only those sources of emissions listed in the attached table entitled "Emission Sources - Maximum Allowable Emission Rates," table (MAERT) and those sources are limited to the emission limits and other conditions specified in that attached table.
2. Visible emissions from Emission Point No. (EPN) H87920 shall not exceed an average of 10 percent opacity over a six-minute period, except for those periods described in 30 Texas Administrative Code § 111.111 (a)(1)(E) [30 TAC § 111.111 (a)(1)(E)].

This determination shall be made by first making an observation for visible emissions while the facility is operating. Observations shall be made at least 15 feet and no more than 0.25 mile from the emission point. Contributions from uncombined water shall not be included in determining compliance with this condition. Observations shall be performed and recorded on a quarterly basis. If visible emissions are present during the observation, the permit holder shall either record this as a violation of the opacity limit in this condition or a Method 9 opacity test shall be conducted to determine if this is a violation of the 10 percent opacity limit.

3. The Phenol/Acetone Boiler shall be limited to firing the following fuels:
  - A. Pipeline-quality, sweet natural gas containing no more than 5.0 grains total sulfur and 0.25 grain of hydrogen sulfide per 100 dry standard cubic feet.
  - B. Vent gas from the liquid fuel surge drum.
  - C. Liquid waste-derived fuel streams identified in this permit. Liquid streams shall have a sulfur content that does not exceed 0.04 weight percent.
  - D. Mixtures of vent gas from the surge drum, natural gas, and liquid waste-derived fuel streams.
  - E. Firing of any other fuel will require authorization from the permitting authority.
4. The permittee may not feed liquid waste-derived fuel to the Phenol/Acetone Boiler during start-up or shutdown of the boiler.
5. The permittee shall devise waste feed cutoff procedures to safely stop and/or reduce the flow of liquid waste-derived fuel streams to the Phenol/Acetone Boiler in the event of an upset. Written waste feed cutoff procedures and upset conditions which would initiate waste feed cutoff procedures shall be maintained with the boiler operator at all times. Liquid

## SPECIAL CONDITIONS

Permit Numbers 37206 and PSDTX896

Page 2

waste-derived fuel streams shall not be fed to the Phenol/Acetone Boiler until the upset conditions that initiated the waste feed cutoff procedures no longer exist.

6. The holder of this permit shall continuously monitor the boiler firebox temperature. The minimum firebox temperature shall be maintained above 1,600° F while burning liquid waste-derived fuel. If the minimum firebox temperature falls below 1,600° F while burning liquid waste-derived fuel, waste feed cutoff procedures shall be initiated to discontinue fuel to the boiler.
7. The combustion gas concentration of carbon monoxide (CO) measured by the CO continuous emission monitoring systems (CEMS) shall not exceed 78 parts per million by dry volume (ppmv) on a 60-minute rolling average when corrected to 7 percent oxygen (O<sub>2</sub>), dry basis, in the flue gas.
8. The hourly liquid waste-derived fuel feed rate to the Phenol/Acetone Boiler shall be measured with a flow recording meter. The maximum liquid waste-derived fuel feed rate to the boiler shall be 9,260 pounds per hour.

### LIMITATIONS ON WASTES FIRED IN PHENOL/ACETONE BOILER

9. No combination of liquid waste-derived fuel and/or natural gas as fed to the boiler shall exceed 400 million British thermal capacity units per hour (MMBtu/hr) and the annual firing rate shall not exceed an average of 357 MMBtu/hr.
10. Operation above the limitations found in Special Condition Nos. 6, 8, 9 and 11 during testing of the Phenol/Acetone Boiler, as required by 40 CFR Part 266 and 40 CFR Part 63, is allowed. Compliance with the MAERT emission limits will be maintained during such testing. **(02/10)**
11. The total ash content of liquid waste-derived fuel fed to the boiler shall not exceed 5.5 pounds per hour. Operation at higher ash feed rates is permissible during initial demonstration of compliance stack testing or during subsequent stack testing authorized under 40 CFR Part 266. If test results indicate that the emissions listed in the attached MAERT are met at higher ash feed rates, the permit holder may request a permit alteration to establish that ash feed rate as the new ash feed rate limitation in this permit special condition.
12. The only two authorized liquid waste-derived fuel streams that may be fired in the boiler are phenol heavy ends and Bisphenol A heavy ends. Firing of other liquid waste-derived fuel streams is prohibited unless prior approval is obtained from the Texas Commission on Environmental Quality (TCEQ).

## SPECIAL CONDITIONS

Permit Numbers 37206 and PSDTX896

Page 3

13. At the request of the permitting authority, the holder of this permit shall provide a representative analysis and/or sample of the liquid waste-derived fuel as fired. The analysis shall list the organic compounds and show the concentrations of each compound in percent by weight.

### INITIAL DEMONSTRATION OF COMPLIANCE

14. Upon request of the TCEQ Executive Director or delegated representative, the holder of this permit shall perform stack sampling tests to establish the actual pattern and quantities of air contaminants being emitted into the atmosphere from the Phenol/Acetone Plant Boiler Stack. The holder of this permit is responsible for providing sampling and testing facilities and conducting the sampling and testing operations at his expense.
  - A. The appropriate TCEQ Regional Office in the region where the source is located shall be contacted as soon as testing is scheduled but not less than 45 days prior to sampling to schedule a pretest meeting.

The notice shall include:

- (1) Date for pretest meeting.
- (2) Date sampling will occur.
- (3) Name of firm conducting sampling.
- (4) Type of sampling equipment to be used.
- (5) Method or procedure to be used in sampling.

The purpose of the pretest meeting is to review the necessary sampling and testing procedures, to provide the proper data forms for recording pertinent data, and to review the format procedures for submitting the test report.

A written proposed description of any deviation from sampling procedures specified in permit conditions or TCEQ or Environmental Protection Agency (EPA) sampling procedures shall be made available to the TCEQ prior to the pretest meeting. The TCEQ Regional Director shall approve or disapprove of any deviation from specified sampling procedures.

Requests to waive testing for any pollutant specified in B of this condition shall be submitted to the TCEQ Office of Permitting and Registration, Air Permits Division. Test waivers and alternate/equivalent procedure proposals for New Source Performance Standards (NSPS) testing which must have EPA approval shall be submitted to the TCEQ Regional Office.

## SPECIAL CONDITIONS

Permit Numbers 37206 and PSDTX896

Page 4

- B. Air contaminants emitted from the Phenol/Acetone Plant Boiler to be tested for are nitrogen oxides (NO<sub>x</sub>), CO, particulate matter, sulfur dioxide, and total unburned hydrocarbons (excluding methane and ethane).
- C. Sampling shall occur within 60 days after the Phenol/Acetone Plant Boiler achieves maximum production but not later than 180 days after start-up of the boiler and at such other times as may be required by the Executive Director of the TCEQ. Requests for additional time to perform sampling shall be submitted to the TCEQ Regional Office.
- D. The sources specified for testing shall operate at maximum heat input during stack emission testing. Primary operating parameters that enable determination of production rate shall be monitored and recorded during the stack test. These parameters are to be determined at the pretest meeting. If the Phenol/Acetone Plant Boiler is unable to operate at maximum rates during testing, then additional stack testing may be required when production rates are increased more than 10 percent above the rate at which testing was performed.
- E. Two copies of the final sampling report shall be forwarded to the TCEQ within 120 days after sampling is completed. Sampling reports shall comply with the attached provisions of Chapter 14 of the TCEQ Sampling Procedures Manual. The reports shall be distributed as follows:

One copy to the TCEQ Houston Regional Office

One copy to the TCEQ Field Operations Support Division in Austin

Initial compliance testing was completed in July, 2000.

## CONTINUOUS DEMONSTRATION OF COMPLIANCE

- 15. The holder of this permit shall install, calibrate, maintain, and operate a CEMS to measure and store the concentrations of NO<sub>x</sub> in the Phenol/Acetone Plant Boiler stack. The CEMS used to measure and store the in-stack concentration of NO<sub>x</sub> from the Phenol/Acetone Plant Boiler shall be installed, calibrated, and maintained in accordance with the requirements of 40 CFR Part 60.13 and 40 CFR Part 60.48b. In addition, the holder of this permit shall comply with the following:
  - A. The CEMS shall meet the design and performance specifications, pass the field tests, and meet the installation requirements and data analysis and reporting requirements specified in the applicable Performance Specifications in 40 CFR Part 60, Appendix B. The performance specification tests (PSTs) shall be conducted prior to or during the sampling required by Special Condition No. 14, and written copies of the results shall

## SPECIAL CONDITIONS

Permit Numbers 37206 and PSDTX896

Page 5

- be submitted within 120 days of completion of the tests to the TCEQ Houston Regional Office.
- B. The system shall be zeroed and spanned daily and corrective action taken when the 24-hour span drift exceeds two times the amounts specified in 40 CFR Part 60, Appendix B. Each gaseous monitor shall be quality-assured at least quarterly using cylinder gas audits (CGAs). The CGA method to be used is contained in 40 CFR Part 60, Appendix F, Procedure 1.
  - C. The gaseous monitoring data shall be reduced to hourly average concentrations at least once everyday, using a minimum of four equally-spaced data points from each one-hour period. At least 23 hourly averages shall be generated per day.
  - D. All CGA exceedances greater than 15 percent shall be reported to the TCEQ Houston Regional Office within 24 hours of detection, and necessary corrective action shall be taken. Supplemental stack concentration measurements may be required at the discretion of the TCEQ Regional Director.
16. The holder of this permit shall install, calibrate, maintain, and operate a CEMS to measure and store the concentrations of CO in the Phenol/Acetone Plant Boiler stack. Oxygen and CO concentrations shall be measured using CEMS which sample from essentially the same location in the exhaust gas stream. The CO and O<sub>2</sub> CEMS shall be certified for use by meeting the design and performance specifications and passing the field tests in 40 CFR Part 266, Appendix IX, Section 2.0. The O<sub>2</sub> concentrations shall be quantified, stored, and reported as percent by volume on a dry basis. Carbon monoxide concentrations shall be quantified, stored, and reported as parts per million by volume (ppmv), corrected to 7 percent by volume O<sub>2</sub>, on a dry basis.
17. The CEMS for CO and O<sub>2</sub> shall be zeroed and spanned daily for each monitoring range on those days when the boiler is in service. Corrective action shall be taken when the 24-hour span drift exceeds two times the amount specified in 40 CFR Part 266, Appendix IX. Each calendar quarter, monitor accuracy shall be certified using a calibration error test as described in 40 CFR Part 266, Section 2.1.6.3. Reference method testing can be substituted for CGAs if preferred by the permittee as allowed by 40 CFR Part 266, Appendix IX, §2.1.10.3. Corrective action shall be taken when the CGA or reference method testing exceeds ±5 percent of span as defined in 40 CFR Part 266, Appendix IX, §2.1.4.7. The CO and O<sub>2</sub> CEMS shall operate at a minimum of 90 percent uptime, based on a 24-hour period, while burning liquid waste-derived fuel.
18. At least quarterly, the holder of this permit shall test the total sulfur in the liquid waste derived stream, as identified in Special Condition No. 2, fired in the Phenol/Acetone Boiler. The tests shall be conducted on at least one representative sample. If any of the

## SPECIAL CONDITIONS

Permit Numbers 37206 and PSDTX896

Page 6

quarterly tests demonstrate that the sulfur content exceeds 0.04 percent weight, this shall be reported as a violation.

19. At least once annually, a relative accuracy test, a calibration error test, a response time test, and a calibration drift test shall be conducted concurrently during a PST period. This constitutes a PST as specified in 40 CFR Part 266, Appendix IX, §2.1.10.4. These tests shall be conducted using all applicable sections of 40 CFR 266, Appendix IX, §2.1.6 and all applicable test methods found in 40 CFR Part 60, Appendix A.

## FUGITIVE MONITORING

20. Piping, Valves, Connectors, Pumps, and Compressors in Volatile Organic Compound (VOC) Service - 28VHP

Except as may be provided for in the special conditions of this permit, the following requirements apply to the above-referenced equipment.

- A. These conditions shall not apply (1) where the VOC has an aggregate partial pressure or vapor pressure of less than 0.044 psia at 68 F or (2) operating pressure is at least 5 kilopascals (0.725 psi) below ambient pressure. Equipment excluded from this condition shall be identified in a list to be made available upon request.
- B. Construction of new and reworked piping, valves, pump systems, and compressor systems shall conform to applicable ANSI, API, ASME, or equivalent codes.
- C. New and reworked underground process pipelines shall contain no buried valves such that fugitive emission monitoring is rendered impractical.
- D. To the extent that good engineering practice will permit, new and reworked valves and piping connections shall be so located to be reasonably accessible for leak-checking during plant operation. Non-accessible valves, as defined by 30 TAC Chapter 115, shall be identified in a list to be made available upon request.
- E. New and reworked piping connections shall be welded or flanged. Screwed connections are permissible only on piping smaller than two-inch diameter. No later than the next scheduled quarterly monitoring after initial installation or replacement, all new or reworked connections shall be gas-tested or hydraulically-tested at no less than normal operating pressure and adjustments made as necessary to obtain leak-free performance. Flanges shall be inspected by visual, audible, and/or olfactory means at least weekly by operating personnel walk-through.

## SPECIAL CONDITIONS

Permit Numbers 37206 and PSDTX896

Page 7

Each open-ended valve or line shall be equipped with a cap, blind flange, plug, or a second valve. Except during sampling, the second valve shall be closed.

- F. Accessible valves shall be monitored by leak-checking for fugitive emissions at least quarterly using an approved gas analyzer. Sealless/leakless valves (including, but not limited to, welded bonnet bellows and diaphragm valves) and relief valves equipped with a rupture disc upstream or venting to a control device are not required to be monitored.

For valves equipped with rupture discs, a pressure-sensing device shall be installed between the relief valve and rupture disc to monitor disc integrity. All leaking discs shall be replaced at the earliest opportunity but no later than the next process shutdown.

An approved gas analyzer shall conform to requirements listed in 40 CFR 60.485(a) - (b).

Replaced components shall be re-monitored within 15 days of being placed back into VOC service.

- G. Except as may be provided for in the special conditions of this permit, all pump and compressor seals shall be monitored with an approved gas analyzer at least quarterly or be equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal. Seal systems designed and operated to prevent emissions or seals equipped with an automatic seal failure detection and alarm system need not be monitored. These seal systems may include (but are not limited to) dual pump seals with barrier fluid at higher pressure than process pressure, seals degassing to vent control systems kept in good working order, or seals equipped with an automatic seal failure detection and alarm system. Submerged pumps or sealless pumps (including, but not limited to, diaphragm, canned, or magnetic-driven pumps) may be used to satisfy the requirements of this condition and need not be monitored.
- H. Damaged or leaking valves or connectors found to be emitting VOC in excess of 500 ppmv or found by visual inspection to be leaking (e.g., dripping process fluids) shall be tagged and replaced or repaired. Damaged or leaking pump and compressor seals found to be emitting VOC in excess of 2,000 ppmv or found by visual inspection to be leaking (e.g., dripping process fluids) shall be tagged and replaced or repaired.
- I. Every reasonable effort shall be made to repair a leaking component, as specified in this paragraph, within 15 days after the leak is found. If the repair of a component would require a unit shutdown, the repair may be delayed until the next scheduled shutdown. All leaking components which cannot be repaired until a scheduled shutdown shall be identified for such repair by tagging. The TCEQ Executive Director, at his discretion,

## SPECIAL CONDITIONS

Permit Numbers 37206 and PSDTX896

Page 8

may require early unit shutdown or other appropriate action based on the number and severity of tagged leaks awaiting shutdown.

- J. The results of the required fugitive monitoring and maintenance program shall be made available to the TCEQ Executive Director or his designated representative upon request. Records shall indicate appropriate dates, test methods, instrument readings, repair results, and corrective actions taken for all components. Records of connector inspections are not required unless a leak is detected.
- K. Alternative monitoring frequency schedules of 30 TAC §§ 115.352-115.359 or National Emission Standards for Organic Hazardous Air Pollutants, 40 CFR Part 63, Subpart H, may be used in lieu of Items F through G of this condition.

Compliance with the requirements of this condition does not assure compliance with requirements of 30 TAC Chapter 115, an applicable NSPS, or an applicable National Emission Standards for Hazardous Air Pollutants and does not constitute approval of alternative standards for these regulations.

## RECORDKEEPING REQUIREMENTS

- 21. The following records shall be kept at the plant for the life of the permit. All records required in this permit shall be made available at the request of personnel from the TCEQ, EPA, or any air pollution control agency with jurisdiction.
  - A. A copy of this permit.
  - B. Permit application dated December 1997 and February 1999.
  - C. A complete copy of the testing report and records of the initial performance testing completed pursuant to Special Condition No. 14 to demonstrate initial compliance.
  - D. Stack sampling results or other testing that may be conducted on units authorized under this permit after the date of issuance of this permit.
  - E. Written waste feed cutoff procedures and upset conditions which would initiate waste feed cutoff procedures pursuant to Special Condition No. 5.
- 22. The following information shall be collected and maintained by the holder of this permit in a form suitable for inspection for a period of five years after the data is obtained and shall be made immediately available upon request to representatives of the TCEQ, EPA, or any local air pollution control program having jurisdiction:



SPECIAL CONDITIONS

Permit Numbers 37206 and PSDTX896

Page 9

- A. Records of the CEMS data required by Special Condition Nos. 15, 16, and 17 which includes raw data files of all CEMS data, calibration checks and adjustments, and maintenance performed on these systems of devices in a permanent form suitable for inspection.
- B. Records required by Special Condition No. 19 regarding fugitive emission monitoring shall be kept and maintained.
- C. Records of hourly average temperature of the Phenol/Acetone Boiler while burning liquid waste-derived fuel to demonstrate compliance with Special Condition No. 6.
- D. Records of the hourly feed rate of liquid waste-derived fuel to the Phenol/Acetone Boiler to demonstrate compliance with Special Condition No.8.
- E. Applicable records required by the Resource Conservation and Recovery Act may be used to satisfy recordkeeping required by this permit.
- F. Records of visible emissions observations and any opacity monitoring conducted as required under Special Condition No. 2.

Dated February 9, 2010



TEXAS COMMISSION ON ENVIRONMENTAL QUALITY  
AIR QUALITY PERMIT



A Permit Is Hereby Issued To  
**Shell Chemical LP**  
Authorizing the Construction and Operation of  
**Deer Park Chemical Plant**  
Located at **Deer Park, Harris County, Texas**  
Latitude 29° 43' 18" Longitude 095° 07' 21"

Permit: 3219 and PSDTX974

Revision Date : September 30, 2013

Renewal Date: December 21, 2017

  
For the Commission

1. **Facilities** covered by this permit shall be constructed and operated as specified in the application for the permit. All representations regarding construction plans and operation procedures contained in the permit application shall be conditions upon which the permit is issued. Variations from these representations shall be unlawful unless the permit holder first makes application to the Texas Commission on Environmental Quality (commission) Executive Director to amend this permit in that regard and such amendment is approved. [Title 30 Texas Administrative Code 116.116 (30 TAC 116.116)]
2. **Voiding of Permit.** A permit or permit amendment is automatically void if the holder fails to begin construction within 18 months of the date of issuance, discontinues construction for more than 18 months prior to completion, or fails to complete construction within a reasonable time. Upon request, the executive director may grant an 18-month extension. Before the extension is granted the permit may be subject to revision based on best available control technology, lowest achievable emission rate, and netting or offsets as applicable. One additional extension of up to 18 months may be granted if the permit holder demonstrates that emissions from the facility will comply with all rules and regulations of the commission, the intent of the Texas Clean Air Act (TCAA), including protection of the public's health and physical property; and (b)(1)the permit holder is a party to litigation not of the permit holder's initiation regarding the issuance of the permit; or (b)(2) the permit holder has spent, or committed to spend, at least 10 percent of the estimated total cost of the project up to a maximum of \$5 million. A permit holder granted an extension under subsection (b)(1) of this section may receive one subsequent extension if the permit holder meets the conditions of subsection (b)(2) of this section. [30 TAC 116.120(a), (b) and (c)]
3. **Construction Progress.** Start of construction, construction interruptions exceeding 45 days, and completion of construction shall be reported to the appropriate regional office of the commission not later than 15 working days after occurrence of the event. [30 TAC 116.115(b)(2)(A)]
4. **Start-up Notification.** The appropriate air program regional office shall be notified prior to the commencement of operations of the facilities authorized by the permit in such a manner that a representative of the commission may be present. The permit holder shall provide a separate notification for the commencement of operations for each unit of phased construction, which may involve a series of units commencing operations at different times. Prior to operation of the facilities authorized by the permit, the permit holder shall identify the source or sources of allowances to be utilized for compliance with Chapter 101, Subchapter H, Division 3 of this title (relating to Mass Emissions Cap and Trade Program). [30 TAC 116.115(b)(2)(B)(iii)]
5. **Sampling Requirements.** If sampling is required, the permit holder shall contact the commission's Office of Compliance and Enforcement prior to sampling to obtain the proper data forms and procedures. All sampling and testing procedures must be approved by the executive director and coordinated with the regional representatives of the commission. The permit holder is also responsible for providing sampling facilities and conducting the sampling operations or contracting with an independent sampling consultant. [30 TAC 116.115(b)(2)(C)]

6. **Equivalency of Methods.** The permit holder must demonstrate or otherwise justify the equivalency of emission control methods, sampling or other emission testing methods, and monitoring methods proposed as alternatives to methods indicated in the conditions of the permit. Alternative methods shall be applied for in writing and must be reviewed and approved by the executive director prior to their use in fulfilling any requirements of the permit. [30 TAC 116.115(b)(2)(D)]
7. **Recordkeeping.** The permit holder shall maintain a copy of the permit along with records containing the information and data sufficient to demonstrate compliance with the permit, including production records and operating hours; keep all required records in a file at the plant site. If, however, the facility normally operates unattended, records shall be maintained at the nearest staffed location within Texas specified in the application; make the records available at the request of personnel from the commission or any air pollution control program having jurisdiction; comply with any additional recordkeeping requirements specified in special conditions attached to the permit; and retain information in the file for at least two years following the date that the information or data is obtained. [30 TAC 116.115(b)(2)(E)]
8. **Maximum Allowable Emission Rates.** The total emissions of air contaminants from any of the sources of emissions must not exceed the values stated on the table attached to the permit entitled "Emission Sources--Maximum Allowable Emission Rates." [30 TAC 116.115(b)(2)(F)]
9. **Maintenance of Emission Control.** The permitted facilities shall not be operated unless all air pollution emission capture and abatement equipment is maintained in good working order and operating properly during normal facility operations. The permit holder shall provide notification for upsets and maintenance in accordance with 30 TAC 101.201, 101.211, and 101.221 of this title (relating to Emissions Event Reporting and Recordkeeping Requirements; Scheduled Maintenance, Startup, and Shutdown Reporting and Recordkeeping Requirements; and Operational Requirements). [30 TAC 116.115(b)(2)(G)]
10. **Compliance with Rules.** Acceptance of a permit by an applicant constitutes an acknowledgment and agreement that the permit holder will comply with all rules, regulations, and orders of the commission issued in conformity with the TCAA and the conditions precedent to the granting of the permit. If more than one state or federal rule or regulation or permit condition is applicable, the most stringent limit or condition shall govern and be the standard by which compliance shall be demonstrated. Acceptance includes consent to the entrance of commission employees and agents into the permitted premises at reasonable times to investigate conditions relating to the emission or concentration of air contaminants, including compliance with the permit. [30 TAC 116.115(b)(2)(H)]
11. **This** permit may not be transferred, assigned, or conveyed by the holder except as provided by rule. [30 TAC 116.110(e)]
12. **There** may be additional special conditions attached to a permit upon issuance or modification of the permit. Such conditions in a permit may be more restrictive than the requirements of Title 30 of the Texas Administrative Code. [30 TAC 116.115(c)]
13. **Emissions** from this facility must not cause or contribute to a condition of "air pollution" as defined in Texas Health and Safety Code (THSC) 382.003(3) or violate THSC 382.085. If the executive director determines that such a condition or violation occurs, the holder shall implement additional abatement measures as necessary to control or prevent the condition or violation.
14. **The** permit holder shall comply with all the requirements of this permit. Emissions that exceed the limits of this permit are not authorized and are violations of this permit.

## Special Conditions

Permit Numbers 3219 and PSDTX974

### Emission Standards

1. This permit authorizes emissions only from those points listed in the attached table entitled "Emission Sources - Maximum Allowable Emission Rates" and the facilities covered by this permit are authorized to emit subject to the emission rate limits on that table and other operating requirements specified in the special conditions. **(02/09)**

### Fugitive Emissions

2. Piping, Valves, Connectors, Pumps and Compressors in Volatile Organic Compounds (VOC) Service - 28VHP
  - A. These conditions shall not apply (1) where the VOC has an aggregate partial pressure or vapor pressure of less than 0.044 psia at 68°F or (2) operating pressure is at least 5 kilopascals (0.725 psi) below ambient pressure. Equipment excluded from this condition shall be identified in a list to be made available upon request.
  - B. Construction of new and reworked piping, valves, pump systems, and compressor systems shall conform to applicable ANSI, API, ASME, or equivalent codes.
  - C. New and reworked underground process pipelines shall contain no buried valves such that fugitive emission monitoring is rendered impractical.
  - D. To the extent that good engineering practice will permit, new and reworked valves and piping connections shall be so located to be reasonably accessible for leak-checking during plant operation. Non-accessible valves, as defined by Title 30 Texas Administrative Code Chapter 115 (30 TAC Chapter 115), shall be identified in a list to be made available upon request.
  - E. New and reworked piping connections shall be welded or flanged. Screwed connections are permissible only on piping smaller than two-inch diameter. No later than the next scheduled quarterly monitoring after initial installation or replacement, all new or reworked connections shall be gas-tested or hydraulically tested at no less than normal operating pressure and adjustments made as necessary to obtain leak-free performance. Connectors shall be inspected by visual, audible, and/or olfactory means at least weekly by operating personnel walk through.

Each open-ended valve or line shall be equipped with a cap, blind flange, plug, or a second valve. Except during sampling, the second valve shall be closed.
  - F. Accessible valves shall be monitored by leak checking for fugitive emissions at least quarterly using an approved gas analyzer. Sealless/leakless valves (including, but not limited to, welded bonnet bellows and diaphragm valves) and relief valves equipped with a rupture disc upstream or venting to a control device are not required to be monitored. For valves equipped with rupture discs, a pressure-sensing device shall be installed between the relief valve and rupture disc to monitor disc integrity. All leaking discs shall be replaced at the earliest opportunity but no later than the next process shutdown.

An approved gas analyzer shall conform to requirements listed in Title 40 Code of Federal Regulations § 60.485(a) (b) [40 CFR § 60.485(a) (b)].

Replaced components shall be re-monitored within 15 days of being placed back into VOC service.

- G. Except as may be provided for in the special conditions of this permit, all pump and compressor seals shall be monitored with an approved gas analyzer at least quarterly or be equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal. Seal systems designed and operated to prevent emissions or seals equipped with an automatic seal failure detection and alarm system need not be monitored. These seal systems may include (but are not limited to) dual pump seals with barrier fluid at higher pressure than process pressure, seals degassing to vent control systems kept in good working order, or seals equipped with an automatic seal failure detection and alarm system. Submerged pumps or sealless pumps (including, but not limited to, diaphragm, canned, or magnetic-driven pumps) may be used to satisfy the requirements of this condition and need not be monitored.
- H. Damaged or leaking valves or connectors found to be emitting VOC in excess of 500 ppmv or found by visual inspection to be leaking (e.g., dripping process fluids) shall be tagged and replaced or repaired. Damaged or leaking pump and compressor seals found to be emitting VOC in excess of 2,000 ppmv or found by visual inspection to be leaking (e.g., dripping process fluids) shall be tagged and replaced or repaired.
- I. Every reasonable effort shall be made to repair a leaking component, as specified in this paragraph, within 15 days after the leak is found. If the repair of a component would require a unit shutdown, the repair may be delayed until the next scheduled shutdown. All leaking components which cannot be repaired until a scheduled shutdown shall be identified for such repair by tagging. At the discretion of the Texas Commission on Environmental Quality (TCEQ) Executive Director or his designated representative, early unit shutdown or other appropriate action may be required based on the number and severity of tagged leaks awaiting shutdown.
- J. The results of the required fugitive instrument monitoring and maintenance program shall be made available to the TCEQ Executive Director or his designated representative upon request. Records shall indicate appropriate dates, test methods, instrument readings, repair results, justification for delay of repairs, and corrective actions taken for all components. Records of physical inspections are not required unless a leak is detected.
- K. Alternative monitoring frequency schedules of 30 TAC §§ 115.352-115.359 or National Emission Standards for Organic Hazardous Air Pollutants, 40 CFR Part 63, Subpart H, may be used in lieu of Items F through G of this condition.
- L. Compliance with the requirements of this condition does not assure compliance with requirements of 30 TAC Chapter 115, an applicable New Source Performance Standards (NSPS), or an applicable National Emission Standards for Hazardous Air Pollutants Standards (NESHAPS) and does not constitute approval of alternative standards for these regulations

3. Quarterly Instrument Connector Monitoring - 28CNTQ

A. In addition to the weekly physical inspection required by Item E of Special Condition (SC) No. 2, all accessible connectors in benzene gas and vapor and benzene light liquid service shall be monitored quarterly with an approved gas analyzer in accordance with Items F through J of SC No. 2. This requirement is limited to those components in the following sections of OP-2: pyrolysis fractionation, process gas feed to the olefins plant and debutanizer bottoms.

B. In lieu of the monitoring frequency specified in paragraph A, connectors may be monitored on a semiannual basis if the percent of connectors leaking for two consecutive quarterly monitoring periods is less than 0.5 percent.

Connectors may be monitored on an annual basis if the percent of connectors leaking for two consecutive semiannual monitoring periods is less than 0.5 percent.

If the percent of connectors leaking for any semiannual or annual monitoring period is 0.5 percent or greater, the facility shall revert to quarterly monitoring until the facility again qualifies for the alternative monitoring schedules previously outlined in this paragraph.

C. The percent of connectors leaking used in paragraph B shall be determined using the following formula:

$$(Cl + Cs) \times 100 / Ct = Cp$$

Where:

Cl = the number of connectors found leaking by the end of the monitoring period, either by Method 21 or sight, sound, and smell.

Cs = the number of connectors for which repair has been delayed and are listed on the facility shutdown log.

Ct = the total number of connectors in the facility subject to the monitoring requirements, as of the last day of the monitoring period, not including nonaccessible and unsafe to-monitor connectors.

Cp = the percentage of leaking connectors for the monitoring period.

**Emission Standards**

4. Emission limits are based upon feed rates represented in the permit applications dated November 1993 and December 1999. Feed rates shall not exceed these representations without prior approval from the permitting authority. Records shall be kept at the plant site of the quantity of feed stream to the flares and copies of the permit application dated November 1993 and December 1999 to demonstrate compliance with this special condition. Records shall be made readily available to TCEQ personnel upon request or any local pollution control program with jurisdiction. **(06/11)**

5. The AC/MAP Converter regenerations emissions shall be directed to one of the ethylene furnaces designated as Facility Identification Number (FIN) FP31090 and/or FP31100 and Emission Point Number (EPN) OL3FURN15 authorized in Permit Number 3214 or to the atmosphere designated as EPN VOL411/412.

This permit authorizes emissions from the AC/MAP Converter Regenerations designated as EPN VOL411/412 only for the following maintenance, start-up, and shutdown activities as shown in the Confidential Section, Page 6, Section 9, dated February 2004.

These emissions are subject to the maximum allowable emission rates indicated on the MAERT. Any maintenance, start-up, and shutdown activities not in the above referenced Confidential Section are not authorized by this permit. Records shall be kept at the plant demonstrating compliance with this representation for the last two years. **(09/13)**

6. The highly reactive VOC (HRVOC) emissions associated with cooling tower water shall be monitored continuously and records maintained as specified in 30 TAC Chapter 115, Subchapter H, Division 2, regarding cooling tower heat exchange systems effective December 23, 2004.
7. Furnaces FOL150, 160, 170, 180, and 190 shall operate with Lo NO<sub>x</sub> burners and/or other technology so that each furnace emits no more than 0.08 pound (lb) nitrogen oxide (NO<sub>x</sub>)/Million British thermal units (MMBtu) averaged hourly and 0.06 lb NO<sub>x</sub>/MMBtu (high heating value [HHV]) averaged annually. The combined annual average of all ten furnaces shall be no more than 0.03 lb NO<sub>x</sub>/MMBtu (NHV). **(09/13)**

As a condition of issuance of TCEQ Permit Numbers 3219 and PSDTX974, NO<sub>x</sub> reductions equal to or greater than 381 tpy shall be affected no later than start-up of the OP 2 Hotside Restart project furnaces. These reductions shall be generated at one or more of the EPNs FUT100, FUT110, FUT120, and FUT130 included in Permit Numbers 920 and 9856 (EPNs FUT100, FUT110, and FUT120 are located in Permit Number 9856 and EPN FUT130 is located in Permit Number 920). A pollution control standard permit registration must be submitted to authorize burner replacements with PI-1S.

This permit is conditioned on the completion of the following emission reduction projects represented in the permit amendment application OP-2 start-up, PI-1 dated December 1999, as follows in the Table 2N dated May 1998. This reduction of VOC emissions shall occur not later than the commencement of operation of the OP-2 Start up project. The permit holder shall maintain records of these emission reductions and provide access and/or copies upon request to TCEQ personnel or any local air pollution control program having jurisdiction.

This permit authorizes, during planned start-ups and shutdowns, CO and NO<sub>x</sub> emissions in excess of the ppm limits or lbs/MMBTU limits for the furnaces listed in the confidential attachment to the letter from the applicant dated July 29, 2009, provided that the MAERT rates are not exceeded.

## Flares

8. Each flare shall be designed and operated in accordance with the following requirements. **(06/11)**
  - A. The flare systems shall be designed such that the combined assist natural gas and waste stream to each flare meets the 40 CFR § 60.18 specifications of minimum heating value and maximum tip velocity under normal, upset, startup, shutdown, and maintenance flow conditions.

The heating value and velocity requirements shall be satisfied during operations authorized by this permit. Flare testing per 40 CFR § 60.18(f) may be requested by the appropriate regional office (or is required per NSPS Subpart) to demonstrate compliance with these requirements.
  - B. The flare shall be operated with a flame present at all times and/or have a constant pilot flame. The pilot flame shall be continuously monitored by a thermocouple, an infrared monitor, or an approved equivalent device. The time, date, and duration of any loss of pilot flame shall be recorded. Each monitoring device shall be accurate to, and shall be calibrated at a frequency in accordance with, the manufacturer's specifications.
  - C. The flare shall be operated with no visible emissions except periods not to exceed a total of five minutes during any two consecutive hours. This shall be ensured by the use of steam or air assist to the flare when warranted by waste gas requirements.
  - D. Monitoring shall be used to maintain waste gas above the minimum heating value.
  - E. The combined assist natural gas and waste stream to each flares shall meet the 40 CFR § 60.18 specifications of minimum heating value and maximum tip velocity. These flares shall have a continuous flow monitor that provides a record of the vent stream flow to the flare.
9. The permit holder shall notify the appropriate TCEQ Regional Office and the appropriate local air pollution control agencies of any violations of the visible emission requirements of 30 TAC § 111.111(a)(4)(A). Line plugging, purging of refrigerant exchangers and AC or MAP converter swaps are part of the normal operating process. **(06/11)**

## Planned Maintenance, Start-Up, and Shutdown (MSS)

10. This permit authorizes the emissions from the planned MSS activities summarized in the MSS Activity Summary (Attachment C) attached to this permit. In addition, emission events are not authorized by this permit. **(06/11)**

Attachment A identifies the inherently low emitting MSS activities that may be performed at the plant. Emissions from activities identified in Attachment A shall be considered to be equal to the potential to emit represented in the permit application. The estimated emissions from the activities listed in Attachment A must be revalidated annually. This



revalidation shall consist of the estimated emissions for each type of activity and the basis for that emission estimate.

Routine maintenance activities, as identified in Attachment B may be tracked through the work orders or equivalent. Emissions from activities identified in Attachment B shall be calculated using the number of work orders or equivalent that month and the emissions associated with that activity identified in the permit application.

The performance of each planned MSS activity not identified in Attachments A or B and the emissions associated with it shall be recorded and include at least the following information:

- A. The process unit at which emissions from the MSS activity occurred, including the emission point number and common name of the process unit;
- B. The type of planned MSS activity and the reason for the planned activity;
- C. The common name and the facility identification number, if applicable, of the facilities at which the MSS activity and emissions occurred;
- D. The date on which the MSS activity occurred;
- E. The estimated quantity of each air contaminant, or mixture of air contaminants, emitted with the data and methods used to determine it. The emissions shall be estimated using the methods identified in the permit application, consistent with good engineering practice.

Emissions from all completed planned MSS activities shall be summed monthly and the rolling 12-month emissions shall be updated by the end of the month following the activity.

11. Process units and facilities, with the exception of those identified in Attachment A, shall be depressurized, emptied, degassed, and placed in service in accordance with the following requirements: **(06/11)**
  - A. The process equipment shall be depressurized to a control device or a controlled recovery system prior to venting to atmosphere, degassing, or draining liquid. Equipment that only contains material that is liquid with VOC partial pressure less than 0.50 psi at the normal process temperature may be opened to atmosphere and drained in accordance with paragraph C of this special condition.
  - B. If mixed phase materials must be removed from process equipment, the cleared material shall be routed to a knockout drum or equivalent to allow for managed initial phase separation. If the VOC partial pressure is greater than 0.50 psi at either the normal process temperature, any vents in the system must be routed to a control device or a controlled recovery system. Control must remain in place until degassing has been completed or the system is no longer vented to atmosphere.
  - C. All liquids from process equipment or storage vessels must be removed to the maximum extent practical prior to opening equipment to commence degassing

and/or maintenance. Liquids with a VOC partial pressure greater than or equal to 0.044 psia at 68°F shall be drained into a closed vessel unless prevented by the physical configuration of the equipment. If it is necessary to drain liquid into an open pan or sump, the liquid must be covered or transferred to a covered vessel within one hour of being drained. After draining is complete, empty open pans may remain in use for housekeeping reasons to collect incidental drips.

- D. If the VOC partial pressure is greater than 0.50 psi at the normal process temperature or 95°F, facilities shall be degassed using good engineering practice to ensure air contaminants are removed from the system through the control device or controlled recovery system to the extent allowed by process equipment or storage vessel design. The vapor pressure at 95°F may be used if the actual temperature of the liquid is verified to be less than 95°F and the temperature is recorded. The facilities to be degassed shall not be vented directly to atmosphere, except as necessary to establish isolation of the work area or to monitor VOC concentration following controlled depressurization. The venting shall be minimized to the maximum extent practicable and actions taken recorded. The control device or recovery system utilized shall be recorded with the estimated emissions from controlled and uncontrolled degassing calculated using the methods that were used to determine allowable emissions for the permit application.
- (1) For MSS activities identified in Attachment B, the following option may be used in lieu of (2) below. The facilities being prepared for maintenance shall not be vented directly to atmosphere, except as necessary to verify an acceptable VOC concentration and establish isolation of the work area, until the VOC concentration has been verified to be less than 10 percent of the lower explosive limit (LEL) per the site safety procedures.
  - (2) The locations and/or identifiers where the purge gas or steam enters the process equipment or storage vessel and the exit points for the exhaust gases shall be recorded. If the process equipment is purged with a gas, two system volumes of purge gas must have passed through the control device or controlled recovery system before the vent stream may be sampled to verify acceptable VOC concentration prior to uncontrolled venting. The VOC sampling and analysis shall be performed using an instrument meeting the requirements of SC No. 12. The sampling point shall be upstream of the inlet to the control device or controlled recovery system. The sample ports and the collection system must be designed and operated such that there is no air leakage into the sample probe or the collection system downstream of the process equipment or vessel being purged. The facilities shall be degassed to a control device or controlled recovery system until the VOC concentration is less than 10,000 ppmv or 10 percent of the LEL.
- E. Gases and vapors (including vapors from residual liquids) with VOC partial pressure greater than 0.50 psi may be vented directly to atmosphere if all the following criteria are met:
- (1) It is not technically practicable to depressurize or degas, as applicable, into the process.

- (2) There is not an available connection to a plant control system (flare).
- (3) There is no more than 50 lb of air contaminant to be vented to atmosphere during shutdown or start-up, as applicable

Except when identified for an activity on Attachment A, all instances of venting directly to the atmosphere per E of this special condition must be documented when occurring as part of any MSS activity. The emissions associated with venting without control must be included in the work order or equivalent, or in the form of a procedure, a report, or database entry for those planned MSS activities identified in Attachment B.

12. Air contaminant concentration shall be measured using an instrument/detector meeting one set of requirements specified below: **(06/11)**
  - A. The VOC concentration shall be measured using an instrument meeting all the requirements specified in EPA Method 21 (40 CFR Part 60, Appendix A) with the following exceptions:
    - (1) The instrument shall be calibrated within 24 hours of use with a calibration gas such that the response factor of the VOC (or mixture of VOCs) to be monitored shall be less than 2.0. The calibration gas and the gas to be measured, and its approximate response factor shall be recorded.
    - (2) Sampling shall be performed as directed by this permit in lieu of section 8.3 of Method 21. During sampling, data recording shall not begin until after two times the instrument response time. The date and time shall be recorded, and VOC concentration shall be monitored for at least 5 minutes, recording VOC concentration each minute. The highest measured VOC concentration shall not exceed the specified VOC concentration limit prior to uncontrolled venting.
  - B. Colorimetric gas detector tubes may be used to determine air contaminant concentrations if they are used in accordance with the following requirements:
    - (1) The air contaminant concentration measured is less than 80 percent of the range of the tube. If the maximum range of the tube is greater than the release concentration defined in (3), the concentration measured is at least 20 percent of the maximum range of the tube.
    - (2) The tube is used in accordance with the manufacturer's guidelines.
    - (3) At least two samples taken at least five minutes apart must satisfy the following prior to uncontrolled venting:

Measured contaminant concentration (ppmv) < release concentration

Where the release concentration is: 10,000\* mole fraction of the total air contaminants present that can be detected by the tube. The mole fraction may be estimated based on process knowledge. The release concentration and basis for its determination shall be recorded.

Records shall be maintained of the tube type, range, measured concentrations, and time the samples were taken.

- C. Lower explosive limit measured with a lower explosive limit detector:
- (1) The detector shall be calibrated monthly with a certified pentane gas standard at 25% of the lower explosive limit (LEL) for pentane. Records of the calibration date/time and calibration result (pass/fail) shall be maintained.
  - (2) A daily functionality test shall be performed on each detector using the same certified gas standard used for calibration. The LEL monitor shall read no lower than 90% of the calibration gas certified value. Records, including the date/time and test results, shall be maintained.
  - (3) A certified methane or isobutylene gas standard equivalent to 25% of the LEL for pentane may be used for calibration and functionality tests provided that the LEL response is within 95% of that for pentane.
13. This condition applies only to piping and components subject to leak detection and repair monitoring requirements identified in other NSR permits. Each open-ended valve or line shall be equipped with an appropriately sized cap, blind flange, plug, or a second valve to seal the line. Except during sampling, both valves shall be closed. If the isolation of equipment for hot work or the removal of a component for repair or replacement results in an open ended line or valve, it is exempt from the requirement to install a cap, blind flange, plug, or second valve for 72 hours. If the repair or replacement is not completed within 72 hours, the permit holder must complete either of the following actions within that time period. **(06/11)**
- A. a cap, blind flange, plug, or second valve must be installed on the line or valve; or
  - B. the open-ended valve or line shall be monitored once for leaks above background for a plant or unit turnaround lasting up to 45 days with an approved gas analyzer and the results recorded. For all other situations, the open-ended valve or line shall be monitored once by the end of the 72 hours period following the creation of the open ended line and monthly thereafter with an approved gas analyzer and the results recorded. For turnarounds and all other situations, leaks are indicated by readings of 500 ppmv and must be repaired within 24 hours or a cap, blind flange, plug, or second valve must be installed on the line or valve.
14. With the exception of the MAERT emission limits, these permit conditions become effective 180 days after this permit has been issued, but no earlier than December 1, 2011. In addition, the functionality test requirement in SC No. 12.C.(2) becomes effective 180 days after this permit has been issued, but no earlier than February 1, 2012. During this period, monitoring and recordkeeping shall satisfy the requirements of SC Nos. 10.A through 10.D. Emissions shall be estimated using good engineering practice and methods to provide reasonably accurate representations for emissions. The basis used for determining the quantity of air contaminants to be emitted shall be recorded. The permit holder may maintain abbreviated records of emissions from Attachment A and B activities

as allowed in SC No. 10 rather than documenting all the information required by SC Nos. 10. parts A through D. **(06/11)**

15. Planned maintenance activities must be conducted in a manner consistent with good practice for minimizing emissions, including the use of air pollution control equipment, practices and processes. All reasonable and practical efforts to comply with SC Nos. 10 through 13 must be used when conducting the planned maintenance activity, until the commission determines that the efforts are unreasonable or impractical, or that the activity is an unplanned maintenance activity. **(06/11)**

### **Initial Determination Of Compliance**

16. The holder of this permit shall perform stack sampling and other testing as required to establish the actual pattern and quantities of air contaminants being emitted into the atmosphere from Furnaces FOL150, 160, 170, 180, and 190. The holder of this permit is responsible for providing sampling and testing facilities and conducting the sampling and testing operations at his expense. The sampling was completed in August 2004. **(09/13)**

- A. The appropriate TCEQ Regional Office in the region where the source is located shall be contacted as soon as testing is scheduled, but not less than 45 days prior to sampling to schedule a pretest meeting.

The notice shall include:

- (1) Date for pretest meeting.
- (2) Date sampling will occur.
- (3) Name of firm conducting sampling.
- (4) Type of sampling equipment to be used.
- (5) Method or procedure to be used in sampling.

The purpose of the pretest meeting is to review the necessary sampling and testing procedures, to provide the proper data forms for recording pertinent data, and to review the format procedures for submitting the test reports.

A written proposed description of any deviation from sampling procedures specified in permit provisions or TCEQ or EPA Sampling Procedures Manual shall be made available to the TCEQ prior to the pretest meeting. The TCEQ Regional Director shall approve or disapprove of any deviation from specified sampling procedures.

Requests to waive testing for any pollutant specified in this condition shall be submitted to the TCEQ Office of Permitting and Registration, Air Permits Division. Test waivers and alternate or equivalent procedure proposals for NSPS testing which must have the EPA approval shall be submitted to the TCEQ Office of Air, Air Permits Division.

- B. Air contaminants emitted from the Cracking Furnaces FOL150, 160, 170, 180, and 190 to be tested for include (but are not limited to) NO<sub>x</sub> and carbon monoxide (CO).

- C. Sampling shall occur within 180 days after initial start-up of the facilities and at such other times as may be required by the Executive Director of the TCEQ. Requests for additional time to perform sampling shall be submitted to the TCEQ Regional Office. Additional time to comply with the applicable requirements of 40 CFR Part 60 and 40 CFR Part 61 requires the EPA approval, and requests shall be submitted to the TCEQ Regional Office.
- D. Each furnace tested shall operate at maximum firing rate while it is being tested. Primary operating parameters that enable determination of production rate shall be monitored and recorded during the stack test. These parameters are to be determined at the pretest meeting. If the plant is unable to operate at maximum rates during testing, then future production rates may be limited to the rates established during testing. Additional stack testing may be required when higher production rates are achieved.
- E. Copies of the final sampling report shall be forwarded to the TCEQ within 60 days after sampling is completed. Sampling reports shall comply with the attached provisions of Chapter 14 of the TCEQ Sampling Procedures Manual. The reports shall be distributed as follows:
  - One copy to the TCEQ Houston Regional Office.
  - One copy to the Harris County Air Pollution Control Program in Pasadena.

### **Continuous Demonstration Of Compliance**

- 17. The holder of this permit shall install, calibrate, maintain and operate a continuous emissions monitoring system (CEMS) to measure and record the in-stack concentration of NO<sub>x</sub> and CO from Cracking Furnaces FOL150, 160, 170, 180, and 190. Any monitoring systems not in operation when this permit is issued shall be operational upon start up of the associated furnace. **(09/13)**
  - A. The CEMS shall meet the design and performance specifications, pass the field tests, and meet the installation requirements and the data analysis and reporting requirements specified in the applicable Performance Specification Nos. 1 through 7, 40 CFR Part 60, Appendix B. If there are no applicable performance specifications in 40 CFR Part 60, Appendix B, contact the TCEQ Office of Air, Air Permits Division for requirements to be met.
  - B. The system shall be zeroed and spanned daily and corrective action taken when the 24 hour span drift exceeds two times the amounts specified in 40 CFR Part 60, Appendix B or as specified by the TCEQ if not specified in Appendix B.

Zero and span is not required on weekends and plant holidays if instrument technicians are not normally scheduled on those days, unless the monitor is required by a subpart of NSPS or NESHAPS, in which case zero and span shall be done daily without exception.

Each monitor shall be quality-assured at least quarterly in accordance with 40 CFR Part 60, Appendix F, Procedure 1, § 5.1.2. Cylinder gas audit (CGA) conducted in all

four calendar quarters may be used in lieu of relative accuracy test audits (RATA) for non NSPS sources and for NSPS sources not subject to 40 CFR Part 60, Appendix F.

- C. The monitoring data shall be reduced to hourly average concentrations at least once weekly, using a minimum of four equally-spaced data points from each one-hour period. The individual average concentrations shall be reduced to units of the permit allowable emission rate in pounds per hour at least once every week and cumulative ton per year (TPY) on a 12 month rolling average at least once every month.
- D. All monitoring data and quality-assurance data shall be maintained by the source for a period of two years and shall be made available to the TCEQ Executive Director or designated representative upon request. The data from the CEMS may, at the discretion of the TCEQ, be used to determine compliance with the conditions of this permit.
- E. All CGA exceedances of 15 percent accuracy and any CEMS downtime associated with emissions from Cracking Furnaces FOL150, 160, 170, 180, and 190 shall be reported to the appropriate TCEQ Regional Director and necessary corrective action shall be taken. The CEMS downtime and excess emissions at these emission points shall be reported quarterly. Supplemental stack concentration measurements may be required at the discretion of the appropriate TCEQ Regional Director.
- F. For NSPS sources subject to Appendix F, the appropriate TCEQ Regional Office shall be notified at least 30 days prior to each annual RATA in order to provide them the opportunity to observe the testing.
- G. Quality-assured (or valid) data must be generated when Cracking Furnaces FOL150, 160, 170, 180, and 190 are operating except during the performance of a daily zero and span check. Loss of valid data due to periods of monitor break down, out-of-control operation (producing inaccurate data), repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time (in minutes) that the Cracking Furnaces FOL150, 160, 170, 180, and 190 are operated over the previous rolling 12-month period. The measurements missed shall be estimated using engineering judgment and the methods used recorded.

### **Storage And Loading Of VOC**

- 18. The following requirements pertain to storage and loading devices
  - A. The control requirements specified in paragraphs B through E of this condition shall not apply (1) where the VOC has an aggregate partial pressure of less than 0.5 psia at the maximum expected operating temperature or (2) to storage tanks smaller than 25,000 gallons.
  - B. An internal floating deck or “roof” or equivalent control shall be installed in all tanks. The floating roof shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the internal floating roof: (1) a liquid-mounted seal, (2) two continuous seals mounted one above the other, or (3) a mechanical shoe seal.

- C. An open-top tank containing a floating roof (external floating roof tank) which uses double seal or secondary seal technology shall be an approved control alternative to an internal floating roof tank provided the primary seal consists of either a mechanical shoe seal or a liquid-mounted seal, and the secondary seal is rim mounted.  
  
A weather shield is not approvable as a secondary seal unless specifically reviewed and determined to be vapor-tight.
- D. For any tank equipped with a floating roof, the permit holder shall perform the visual inspections and seal gap measurements as specified in 40 CFR § 60.113b, Testing and Procedures (as amended at 54 FR 32973, Aug. 11, 1989), to verify seal integrity. Fitting integrity verification is only required during internal tank inspections when the tank is out of service. Records shall be maintained of the dates seals were inspected and seal gap measurements made, results of inspections and measurements made (including raw data), and actions taken to correct any deficiencies noted.
- E. The floating roof design shall incorporate sufficient flotation to conform to the requirements of API Code 650 dated November 1, 1998, except that an internal floating cover need not be designed to meet rainfall support requirements and the materials of construction may be steel or other materials.
- F. Uninsulated tank exterior surfaces exposed to the sun shall be white or aluminum. Storage tanks must be equipped with permanent submerged fill pipes.
- G. For purposes of assuring compliance with VOC emission limitations for storage vessels, the holder of this permit shall maintain an annual record of tank identification number, name of the material stored or loaded, VOC annual average temperature in degrees Fahrenheit, VOC vapor pressure at the annual average material temperature in psia and VOC throughput on a rolling 12-month basis. Records of VOC annual average temperature is not required to be kept for unheated tanks which receive liquids that are at or below ambient temperatures.
- H. Storage tanks on this permit are limited to the annual throughputs listed in the confidential application dated December 1999; and this information shall be maintained by the permit holder for a period of two years and shall be made available upon request to TCEQ personnel or any local air pollution control agency having jurisdiction.

### **Compliance Assurance Monitoring (CAM)**

- 19. The following requirements apply to the capture systems for the OP-2 Elevated Flare, the OP 3 Elevated Flare, and the OP-3 Ground Flare, identified as EPNs OP2ELFLA, OP3ELFLA, and OP3GRFLA, respectively. **(06/11)**
  - A. The holder of this permit shall perform one of the following:



- (1) During each calendar month, conduct a visual, audible, and/or olfactory inspection of the capture system to verify there are no leaking components in the capture system; or
  - (2) During each calendar year, verify the capture system is leak free by inspecting in accordance with 40 CFR Part 60, Appendix A, Test Method 21. Leaks shall be indicated by an instrument reading greater than or equal to 500 ppmv above background.
- B. The control devices identified as EPNs OP2ELFLA, OP3ELFLA, and OP3GRFLA shall each comply with either of the following requirements:
- (1) Install a flow indicator that records and verifies zero flow at least once every fifteen minutes immediately downstream of each valve that if opened would allow a vent stream to bypass the control device and be emitted, either directly or indirectly, to the atmosphere; or
  - (2) Once a month, inspect the valves, verifying the position of the valves and the condition of the car seals prevent flow out the bypass.

### **Recordkeeping**

20. The recordkeeping requirement of SC No. 18 shall not apply to storage tanks less than 100 gallons in capacity and storing a chemical with a true vapor pressure at or less than 0.01 psia. **(9/13)**

Storage Tanks (EPNs AP-3, TOL400, TOL401, TOL908, TOL909, TOL910, and TOL914) are exempt from the submerged fill pipe requirements of SC No. 18F.

Dated: September 30, 2013

**ATTACHMENT A**

Permit Number 3219 and PSDTX974

**INHERENTLY LOW EMITTING ACTIVITIES**

Activity	Emissions				
	VOC	NO <sub>x</sub>	CO	PM	H <sub>2</sub> S/SO <sub>2</sub>
Catalyst activation/deactivation	x				
Management of sludge from pits, ponds, sumps, and water conveyances	x				
Aerosol cans	x			x	
Calibration of analytical equipment	x	x	x		x
Carbon can replacement	x				
Catalyst charging/handling				x	
Instrumentation/analyzer maintenance	x				
Meter proving	x				
Replacement of analyzer filters and screens	x				
Maintenance on water treatment systems (cooling, boiler, potable)	x				
Soap and other aqueous based cleaners	x				
Cleaning sight glasses	x				

Dated: June 6, 2011

**ATTACHMENT B**

Permit Number 3219 and PSDTX974

**ROUTINE MAINTENANCE ACTIVITIES**

Pump repair/replacement

Fugitive component (valve, pipe, flange) repair/replacement

Compressor repair/replacement

Heat exchanger repair/replacement

Vessel repair/replacement

Furnace repair/replacement

Dated: June 6, 2011

**ATTACHMENT C**  
 Permit Number 3219 and PSDTX974  
 MSS ACTIVITY SUMMARY

<b>Facilities</b>	<b>Emissions Activity</b>	<b>EPN</b>
OP-2 and OP-3 Units	AC Converter Swap	Flares
OP-2 and OP-3 Units	Amine Bypass	Flares
OP-2 and OP-3 Units	Bed Swap	Flares
OP-2 and OP-3 Units	Core Wash	Flares
OP-2 and OP-3 Units	Drier Swap	Flares
All process units	Filter Swap	Flares
All process units	Instrumentation Testing	Flares
All process units	Lube Oil Set Maintenance and Testing	Flares
All process units	Driver Equipment (Pumps, Turbines, Etc.) Lubrication	Flares
OP-2 and OP-3 Units	MAP Converter Swap	Flares
PSA Unit	PSA S/U and S/D	Flares
All process units	Reboiler Swap	Flares
All process units	Steam, Curtailment	Flares
CIPX Unit	CIPX Unit Start-Up/ Shutdown	Flares
HT-2 Unit	HT-2 Train 2 Start-Up/ Shutdown	Flares, Furnaces
IRU	IRU Unit Start-Up/ Shutdown	Flares

<b>Facilities</b>	<b>Emissions Activity</b>	<b>EPN</b>
HT-3 Unit	HT-3 Unit Start-Up/ Shutdown	Flares, Furnaces
BBHT Unit	BBHT Unit Start-Up/ Shutdown	Flares
BD-3 Unit	BD-3 Unit Start-Up/ Shutdown	Flares
OP-2 Unit	OP-2 Unit Start-Up/ Shutdown	Flares, Furnaces
OP-3 Unit	OP-3 Unit Start-Up/ Shutdown	Flares, Furnaces
CIPX, HT-2, HT-3, IRU, BBHT, BD-3 Units	Heavy Olefin SD/M/SU	Flares, Furnaces
All process units	Steam Loss	Flares
All process units	Maintenance	Flares
All process units	Pump Switching	Flares
OP-2 Unit	Unit decontamination	OP2DCN
OP-2 Unit	Piping fugitives	OP2MSSFUG
OP-2 Unit	Equipment/Vessel decontamination	OP2PMPDCN
OP-2 Unit	Sample loading	OP2SAMPL
OP-3 Unit	Unit decontamination	OP3DCN
OP-3 Unit	Piping fugitives	OP3MSSFUG
OP-3 Unit	Equipment/Vessel decontamination	OP3PMPDCN
OP-3 Unit	Sample loading	OP3SAMPL
Furnaces	Planned startup and shutdowns. Decoking.	Furnaces

Notes:

1. Flares refers to EPNs OP2ELFLA, OP3ELFLA, and OP3GRFLA.
2. Furnaces refers to EPNs FOL150, FOL160, FOL170, FOL180, FOL190, [FOL700, FOL710 (Permit No. 56496)], [FP3-1010, FP3-1020, FP3-1030, FP3-1040, FP3-1050, FP3-1060, FP3-1070, FP3-1080, FP3-1110, FP3-1120, FP3-1130, FP3-1140, FP3-1090, FP3-1100, and FP3-1180 (Permit No. 3214)].

Date: September 30, 2013

Emission Sources - Maximum Allowable Emission Rates

Permit Number 3219 and PSDTX974

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
AP3	Gas Oil Storage Tank	VOC	0.70	2.10
FOL150	Pyrolysis Furnace	CO (6)	12.60	50.80
		NH <sub>3</sub>	1.80	3.90
		NO <sub>x</sub>	25.20	(10)
		PM <sub>10</sub> (6)	3.30	13.20
		SO <sub>2</sub>	1.20	5.00
		VOC	0.10	0.20
FOL160	Pyrolysis Furnace	CO (6)	12.60	50.80
		NH <sub>3</sub>	1.80	3.90
		NO <sub>x</sub>	25.20	(10)
		PM <sub>10</sub> (6)	3.30	13.20
		SO <sub>2</sub>	1.20	5.00
		VOC	0.10	0.20
FOL170	Pyrolysis Furnace	CO (6)	12.60	50.80
		NH <sub>3</sub>	1.80	3.90
		NO <sub>x</sub>	25.20	(10)
		PM <sub>10</sub> (6)	3.30	13.20
		SO <sub>2</sub>	1.20	5.00
		VOC	0.10	0.20

## Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
FOL180	Pyrolysis Furnace	CO (6)	12.60	50.80
		NH <sub>3</sub>	1.80	3.90
		NO <sub>x</sub>	25.20	(10)
		PM <sub>10</sub> (6)	3.30	13.20
		SO <sub>2</sub>	1.20	5.00
		VOC	0.10	0.20
FOL190	Pyrolysis Furnace	CO (6)	12.60	50.80
		NH <sub>3</sub>	1.80	3.90
		NO <sub>x</sub>	25.20	(10)
		PM <sub>10</sub> (6)	3.30	13.20
		SO <sub>2</sub>	1.20	5.00
		VOC	0.10	0.20
OP2FUR10	Five Pyrolysis Furnaces	NO <sub>x</sub>	-	190.50
K306	Pitch Storage Tank	VOC	10.80	4.60
K307	Pitch Storage Tank	VOC	10.80	4.60
OP2	Cooling Water Tower (5)	VOC	5.44	24.30
OP2DECOK	OP-2 Furnace Decoking Vent	CO (6)	60.42	108.75
		NO <sub>x</sub>	0.25	0.50
		PM <sub>10</sub> (6)	1.21	2.18
		VOC	0.08	0.15

## Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
OP2ELFLA, OP3ELFLA, and OP3GRFLA	OP-2 Elevated Flare, OP-3 Elevated Flare, and OP-3 Ground Flare (7)	CO (6)	287.00	--
		H <sub>2</sub> S	5.13	--
		NO <sub>x</sub>	56.00	--
		SO <sub>2</sub>	483.00	--
		VOC	464.00	--
OP2ELFLA, OP3ELFLA, and OP3GRFLA	OP-2 Elevated Flare, OP-3 Elevated Flare, and OP-3 Ground Flare (8)	CO	4075.22	--
		NO <sub>x</sub>	791.08	--
		VOC	3740.10	--
OP2ELFLA, OP3ELFLA, and OP3GRFLA	OP-2 Elevated Flare, OP-3 Elevated Flare, and OP-3 Ground Flare (7) (8)	CO (6)	--	235.05
		H <sub>2</sub> S	--	7.80
		NO <sub>x</sub>	--	46.56
		SO <sub>2</sub>	--	736.00
		VOC	--	344.15
T331	Blended Pitch Tank	VOC	10.80	4.60
TOL400	Flush Oil Storage Tank	VOC	0.20	0.20
TOL401	Alcohol Storage Tank	VOC	14.50	0.10
TOL901	Algerian Condensate	VOC	2.70	5.70
TOL902	Gas Oil Storage Tank	VOC	74.80	25.10
TOL903	Gas Oil Storage Tank	VOC	74.80	7.80
TOL904	Recovered Oil Storage Tank	VOC	0.30	0.64
TOL908	Pitch Storage Tank	VOC	2.45	3.40
TOL909	Gas Oil Storage Tank	VOC	0.24	0.20
TOL910	Gas Oil Storage Tank	VOC	0.14	0.10



## Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
TOL914	Pitch Storage Tank	VOC	6.40	32.25
VOL411/412	OP-2 AC/MAP Converter Regeneration Vent	CO	2.60	2.90
OP2FUG	OP-2 Process Fugitives (5)	NH <sub>3</sub>	0.34	1.49
		VOC	9.70	42.50
OP2DCN	OP-2 Unit Decontamination (8)	H <sub>2</sub> S	0.50	0.01
		VOC (9)	27.31	0.05
		Benzene	0.95	0.01
OP2MSSFUG	OP-2 Maintenance, Startup, and Shutdown (MSS) Stream Fugitive (5) (8)	VOC (9)	5.18	0.62
		Benzene	0.18	0.02
OP2PMPDCN	OP-2 Equipment/Vessel Decontamination (8)	VOC (9)	15.00	0.08
		Benzene	0.52	0.01
OP2SAMPL	OP-2 Sample Loading Emissions (8)	VOC (9)	0.09	0.02
		Benzene	0.01	0.01
OP3DCN	OP-3 Unit Decontamination (8)	H <sub>2</sub> S	0.70	0.01
		VOC (9)	38.31	0.08
		Benzene	1.33	0.01
OP3MSSFUG	OP-3 MSS Stream Fugitive (5) (8)	VOC (9)	5.18	0.62
		Benzene	0.18	0.02
OP3PMPDCN	OP-3 Equipment/Vessel Decontamination (8)	VOC (9)	15.00	0.08
		Benzene	0.52	0.01
OP3SAMPL	OP-3 Sample Loading Emissions (8)	VOC (9)	0.09	0.02
		Benzene	0.01	0.01

Emission Sources - Maximum Allowable Emission Rates

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3) CO - carbon monoxide  
H<sub>2</sub>S - hydrogen sulfide  
NH<sub>3</sub> - ammonia  
NO<sub>x</sub> - total oxides of nitrogen  
PM - total particulate matter, suspended in the atmosphere, including PM<sub>10</sub> and PM<sub>2.5</sub>, as represented  
PM<sub>10</sub> - total particulate matter equal to or less than 10 microns in diameter, including PM<sub>2.5</sub>, as represented  
SO<sub>2</sub> - sulfur oxides  
VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
- (4) Compliance with annual emission limits (tons per year) is based on a 12 month rolling period.
- (5) Emission Point Nos. (EPNs) OP<sub>2</sub>, OP<sub>2</sub>MSSFUG, and OP<sub>3</sub>MSSFUG are subject to the following mandate:  
Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.  
EPN No. OP<sub>2</sub>FUG is subject to the following mandate: Fugitive emissions are an estimate only and should not be considered as a maximum allowable emission rate.
- (6) PSDTX974 pollutant.
- (7) Emissions from the combined EPNs OP<sub>2</sub>ELFLA, OP<sub>3</sub>ELFLA, and OP<sub>3</sub>GRFLA include routine emissions as well as maintenance, start-up, and shutdown (MSS) emissions authorized on December 21, 2007.
- (8) MSS emissions authorized in the amendment application, Form PI-1, dated January 3, 2008.
- (9) The VOC rates include the benzene emission rates which follow.
- (10) Five furnaces are limited to the combined annual emission rate listed under EPN OP<sub>2</sub>FUR10

Date: September 30, 2013

## SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

### EMISSION CAPS AND INDIVIDUAL EMISSION LIMITATIONS

1. This permit authorizes emissions only from those points listed in the attached table entitled "Emission Sources - Maximum Allowable Emission Rates," and the facilities covered by this permit are authorized to emit subject to the emission rate limits on that table and other operating conditions specified in this permit. **(9/07)**

### FEDERAL APPLICABILITY

2. These facilities shall comply with all applicable requirements of the U.S. Environmental Protection Agency (EPA) regulations on Standards of Performance for New Stationary Sources Leaks of Volatile Organic Compounds (VOC) in the Synthetic Organic Chemical Manufacturing Industry (SOCMI); Equipment Leaks of VOC in Petroleum Refineries; VOC Emissions from SOCMI Distillation Operations; VOC Emissions from Petroleum Refinery Wastewater Systems; and VOC Emissions from SOCMI Reactor Processes in Title 40 Code of Federal Regulations Part 60 (40 CFR Part 60), Subparts A, J, K, Ka, Kb, VV, GGG, NNN, QQQ, and RRR.
3. These facilities shall comply with all applicable requirements of EPA regulations on National Emission Standards for Hazardous Air Pollutants (NESHAPS) promulgated in 40 CFR Part 61, as applicable, for:
  - A. Equipment Leaks (Fugitive Emission Sources) of Benzene, Subparts A and J.
  - B. Equipment Leaks (Fugitive Emission Sources), Subpart A and V.
  - C. Benzene Waste Operations, Subparts A and FF. **(9/07)**
4. These facilities shall comply with all applicable requirements of EPA regulations on NESHAPS in 40 CFR Part 63, Subpart A and:
  - A. Organic Hazardous Air Pollutants from the Synthetic Organic Chemical Manufacturing Industry (SOCMI), Subpart F;
  - B. SOCMI for Process Vents, Storage Vessels, Transfer Operations, and Wastewater, Subpart G;
  - C. Organic Hazardous Air Pollutants for Equipment Leaks, Subpart H;

SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 2

- D. Petroleum Refineries, Subparts CC;
- E. Marine Vessel Loading Operations, Subpart Y; and
- F. Petroleum Refineries: Catalytic Cracking Units, Catalytic Reforming Units, and Sulfur Recover Units, Subpart UUU. **(9/07)**

EMISSION STANDARDS **(9/07)**

5. The following five Process Heaters shall achieve a British thermal units (Btu) weighted average of 0.04 lb (pound) NO<sub>x</sub>/MMBtu with the installation of Low-Nitrogen Oxides (NO<sub>x</sub>) burners:

H5100, H5101, H5302, H5303, and H304

The following three Process Heaters shall operate at 0.06 lb NO<sub>x</sub>/MMBtu with the installation of Low-NO<sub>x</sub> burners:

HCOKER2, HPREFLASH2, and HPREFLASH.

The Process Heater HPOSTFRAC shall operate at 0.03 lb NO<sub>x</sub>/MMBtu with the installation of Low-NO<sub>x</sub> burners.

The SR-8 Incinerator (Emission Point No. [EPN] SR8STACK) shall operate at 0.08 lb NO<sub>x</sub>/MMBtu with the installation of Low-NO<sub>x</sub> burners.

Heaters (H3300 and H9150R1) shall operate at 0.035 lb NO<sub>x</sub>/MMBtu with the installation of Low-NO<sub>x</sub> burners.

After completion of the burner upgrades, emissions of NO<sub>x</sub>, carbon monoxide (CO), sulfur dioxide (SO<sub>2</sub>), particulate matter (PM), and VOC from the heaters associated with this permit shall be determined in accordance with the represented emission factors unless a CEMS or process control computer is required to be installed and operated under Special Condition No. 8. After the installation and calibration of the CEMS or process control computer, data collected therein shall be used instead of or in combination with these emission factors at an individual heater. **(3/99)**

## SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 3

6. The FCCU CO Boiler (EPN H600) is an affected facility subject to 40 CFR Part 60, Subparts A and J, and the following emissions limits:

50 ppmvd SO<sub>2</sub> at 0 percent oxygen (O<sub>2</sub>) on a 7-day rolling average  
25 ppmvd SO<sub>2</sub> at 0 percent O<sub>2</sub> on a 365-day rolling average  
500 ppmvd CO at 0 percent O<sub>2</sub> on a 1-hour average  
1 lb of PM per 1,000 lb of coke burn-off (front-half only) **(7/04)**

## INITIAL STACK TESTING

7. The holder of this permit shall perform stack testing as referenced below:

- A. Stack sampling for Process Heaters (H-5100, H-5101, H-5302, H-5303, and H-5304) that will receive Low-NO<sub>x</sub> burners per Special Condition No. 5 shall be performed after installation of the new burners and no later than July 1, 2000. (This requirement for Process Heater H-5100 and H-5101 was completed in July 1999) **(9/07)**

Stack sampling for Process Heaters (HCOKER2, HPREFLASH2, HPREFLASH, and HPOSTFRAC) shall be performed no later than 180 days following start-up of the process heaters or no later than 60 days after achieving maximum rates, whichever is sooner.

Stack sampling for the SR8 Incinerator (EPN SR8STACK) shall be performed no later than 180 days following start-up of the incinerator or no later than 60 days after achieving maximum rates, whichever is sooner. (This requirement was completed in January 2001) **(9/07)**

Stack sampling for Process Heater H-613 that will receive Low-NO<sub>x</sub> burners per Special Condition No. 5 shall be performed after installation of the new burners and no later than July 1, 2001. (This requirement was completed in September 2000) **(9/07)**

The CCU CO Boiler: the need for additional stack testing at the CCU shall be negotiated following the submittal to Texas Commission on Environmental Quality (TCEQ) of the additional information required per Special Condition No. 28.

Stack sampling for the DHT H<sub>2</sub> Heater (EPN H3300) shall be performed no later than 180 days following start-up of the DHT H<sub>2</sub> Heater. **(7/04)**

SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 4

Stack sampling for the SR-3/4 Incinerator (EPN 1660B) shall be performed no later than 180 days following start-up of the modified SR-3/4 Incinerator. **(7/04)**

- B. The appropriate TCEQ Regional Office in the region where the source is located shall be contacted as soon as testing is scheduled but not less than 45 days prior to sampling to schedule a pretest meeting.

The notice shall include:

- (1) Date for pretest meeting.
- (2) Date sampling will occur.
- (3) Name of firm conducting sampling.
- (4) Type of sampling equipment to be used.
- (5) Method or procedure to be used in sampling.

The purpose of the pretest meeting is to review the necessary sampling and testing procedures, to provide the proper data forms for recording pertinent data, and to review the format procedures for submitting the test reports.

A written proposed description of any deviation from sampling procedures specified in permit conditions or TCEQ or EPA sampling procedures shall be made available to the TCEQ prior to the pretest meeting. The TCEQ Regional Director or the Director of the TCEQ Austin Compliance Support Division of any deviation from specified sampling procedures.

Requests to waive testing for any pollutant specified in C of this condition shall be submitted to the TCEQ Office of Permitting, Remediation, and Registration, Air Permits Division in Austin.

- C. Air contaminants emitted from the process heaters to be tested for include (but are not limited to) CO and NO<sub>x</sub>. Specific pollutants to be tested shall be negotiated at pre-test meetings with the TCEQ. Should CCU stack testing be required, air contaminants to be tested for from the CCU shall be determined following submittal of the engineering data as required in Special Condition No. 28.

Air contaminants emitted from the SR-3/4 incinerator to be tested for include (but are not limited to) SO<sub>2</sub>, CO, and NO<sub>x</sub>. **(7/04)**

- D. Requests for additional time to perform sampling shall be submitted to the TCEQ Regional Office.

## SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 5

- E. The facility shall operate at maximum operating rates during stack emission testing. Primary operating parameters that enable determination of production rate shall be monitored and recorded during the stack test. These parameters are to be determined at the pretest meeting. If the facility is unable to operate at maximum rates during testing, then future production rates may be limited to the rates established during testing. Additional stack testing may be required when higher production rates are achieved.
- F. Three copies of the final sampling report shall be forwarded to the TCEQ within 60 days after sampling is completed. The reports shall be distributed as follows:

One copy to the TCEQ Houston Regional Office.

One copy to the Harris County Pollution Control Department, Pasadena.

One copy to the TCEQ Austin Compliance Support Division.

## CONTINUOUS DEMONSTRATION OF COMPLIANCE

- 8. The holder of this permit shall install, calibrate, and maintain a CEMS to determine the in-stack concentration of NO<sub>x</sub>, CO, and O<sub>2</sub> from Process Heaters: H5500, H1000, H5301, H5302, H5303, H5304, HCOKER2, HPREFLASH2, and HPOSTFRAC.

The holder of this permit shall install, calibrate, and maintain a CEMS or process control computer to determine the in-stack concentration of NO<sub>x</sub>, CO, and O<sub>2</sub> from Process Heaters: H5402, H5600, H31001, H31002, H5100, H5101, H5102, and H5103.

- A. The CEMS shall meet the design and performance specifications, pass the field tests, and meet the installation requirements and the data analysis and reporting requirements specified in the applicable Performance Specification Nos. 1 through 9, 40 CFR Part 60, Appendix B. If there are no applicable performance specifications in 40 CFR Part 60, Appendix B, contact the TCEQ Office of Permitting, Remediation, and Registration, Air Permits Division in Austin for requirements to be met. Performance testing of the CEMS shall be completed within 180 days of the date of installation of the CEMS or within 180 days after initial start-up for new process heaters.
- B. The system shall be zeroed and spanned daily and corrective action taken when the 24-hour span drift exceeds two times the amounts specified in 40 CFR Part 60, Appendix B, or as specified by the TCEQ if not specified in Appendix B. Zero and span is not required on weekends and plant holidays if instrument technicians are not normally scheduled on those days, unless the monitor is required by a

## SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 6

subpart of New Source Performance Standards (NSPS) or NESHAPS, in which case zero and span shall be done daily without exception.

Each monitor shall be quality-assured at least quarterly in accordance with 40 CFR Part 60, Appendix F, Procedure 1, § 5.1.2. A Cylinder Gas Audit (CGA) conducted in all four calendar quarters may be used in lieu of Relative Accuracy Test Audit (RATA) for non-NSPS sources and for NSPS sources not subject to 40 CFR Part 60, Appendix F.

- C. The monitoring data shall be reduced to hourly average concentrations at least once everyday, using a minimum of four data points representative of each one-hour period. The individual average concentrations shall be reduced to units of the permit allowable emission rate in pounds per hour (lbs/hr) and tons per year (TPY) at least once every month.
- D. All CEMS monitoring data and quality-assurance data shall be maintained by the source for a period of two years and all process computer data shall be maintained by the source for a period of 18 months. Data shall be made available to the TCEQ Executive Director or his designated representative upon request. The data from the CEMS or process computer may, at the discretion of the TCEQ, be used to determine compliance with the conditions of this permit.
- E. All CGA exceedances of 15 percent accuracy and any CEMS downtime greater than 24 hours shall be reported to the appropriate TCEQ Regional Director, and necessary corrective action shall be taken. Supplemental stack concentration measurements may be required at the discretion of the appropriate TCEQ Regional Director.
- F. For NSPS sources subject to Appendix F, the appropriate TCEQ Regional Office shall be notified at least 30 days prior to each annual RATA in order to provide them the opportunity to observe the testing.
- G. The holder of this permit shall conduct performance testing within 180 days after the installation of the first process control computer for purposes of comparing process control computer data with stack testing results. Prior to conducting the performance testing, the holder of this permit shall submit a written proposed description of the testing to be performed to the TCEQ Office of Permitting, Remediation, and Registration, Air Permits Division. Copies of the proposal shall be sent to the TCEQ Houston Regional Office and the Harris County Pollution Control Department in Pasadena. Additionally, a final report comparing the process control computer data with stack testing results shall be submitted to the



## SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 7

above-referenced authorities within 60 days of completion of the performance testing. (3/99)

### FUGITIVE MONITORING

#### 9. Piping, Valves, Flanges, Pumps, and Compressors in VOC Service - 28VHP

Except as may be provided for in the special conditions of this permit, the following requirements apply to all the equipment covered under this permit except the equipment specified in Special Condition No. 10.

- A. These conditions shall not apply (1) where the VOC has an aggregate partial pressure or vapor pressure of less than 0.044 pound per square inch, absolute (psia) at 68°F or (2) operating pressure is at least 5 kilopascals (0.725 pound square inch [psi]) below ambient pressure. Equipment excluded from this condition shall be identified in a list to be made available upon request.
- B. Construction of new and reworked piping, valves, pump systems, and compressor systems shall conform to applicable American National Standards Institute (ANSI), American Petroleum Institute (API), American Society of Mechanical Engineers (ASME), or equivalent codes.
- C. New and reworked underground process pipelines shall contain no buried valves such that fugitive emission monitoring is rendered impractical.
- D. To the extent that good engineering practice will permit, new and reworked valves and piping connections shall be so located to be reasonably accessible for leak checking during plant operation. Non-accessible valves, as defined by Title 30 Texas Administrative Code Chapter 115 (30 TAC Chapter 115), shall be identified in a list to be made available upon request.
- E. New and reworked piping connections shall be welded or flanged. Screwed connections are permissible only on piping smaller than two-inch diameter. No later than the next scheduled quarterly monitoring after initial installation or replacement, all new or reworked connections shall be gas-tested or hydraulically-tested at no less than normal operating pressure and adjustments made as necessary to obtain leak-free performance. Connectors shall be inspected by visual, audible, and/or olfactory means at least weekly by operating personnel walk-through.

## SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 8

Each open-ended valve or line shall be equipped with a cap, blind flange, plug, or a second valve. Except during sampling, the second valve shall be closed.

- F. Accessible valves shall be monitored by leak-checking for fugitive emissions at least quarterly using an approved gas analyzer. Sealless/leakless valves (including, but not limited to, welded bonnet bellows and diaphragm valves) and relief valves equipped with a rupture disc upstream or venting to a control device are not required to be monitored. For valves equipped with rupture discs, a pressure-sensing device shall be installed between the relief valve and rupture disc to monitor disc integrity. All leaking discs shall be replaced at the earliest opportunity but no later than the next process shutdown.

An approved gas analyzer shall conform to requirements listed in 40 CFR § 60.485(a)-(b).

Replaced components shall be re-monitored within 15 days of being placed back into VOC service.

- G. Except as may be provided for in the special conditions of this permit, all pump and compressor seals shall be monitored with an approved gas analyzer at least quarterly or be equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal. Seal systems designed and operated to prevent emissions or seals equipped with an automatic seal failure detection and alarm system need not be monitored. These seal systems may include (but are not limited to) dual pump seals with barrier fluid at higher pressure than process pressure, seals degassing to vent control systems kept in good working order, or seals equipped with an automatic seal failure detection and alarm system. Submerged pumps or sealless pumps (including, but not limited to, diaphragm, canned, or magnetic-driven pumps) may be used to satisfy the requirements of this condition and need not be monitored.
- H. Damaged or leaking valves or connectors found to be emitting VOC in excess of 500 parts per million by volume (ppmv) or found by visual inspection to be leaking (e.g., dripping process fluids) shall be tagged and replaced or repaired. Damaged or leaking pump and compressor seals found to be emitting VOC in excess of 2,000 ppmv or found by visual inspection to be leaking (e.g., dripping process fluids) shall be tagged and replaced or repaired.
- I. Every reasonable effort shall be made to repair a leaking component, as specified in this paragraph, within 15 days after the leak is found. If the repair of a component would require a unit shutdown, the repair may be delayed until the

## SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 9

next scheduled shutdown. All leaking components which cannot be repaired until a scheduled shutdown shall be identified for such repair by tagging. At the discretion of the TCEQ Executive Director or his designated representative, early unit shutdown or other appropriate action may be required based on the number and severity of tagged leaks awaiting shutdown.

- J. The results of the required fugitive instrument monitoring and maintenance program shall be made available to the TCEQ Executive Director or his designated representative upon request. Records shall indicate appropriate dates, test methods, instrument readings, repair results, justification for delay of repairs, and corrective actions taken for all components. Records of physical inspections are not required unless a leak is detected.
- K. Alternative monitoring frequency schedules of 30 TAC §§ 115.352 through 115.359 or National Emission Standards for Organic Hazardous Air Pollutants, 40 CFR Part 63, Subpart H, may be used in lieu of Items F through G of this condition.

Compliance with the requirements of this condition does not assure compliance with requirements of 30 TAC Chapter 115, an applicable NSPS, or an applicable NESHAPS and does not constitute approval of alternative standards for these regulations.

Connectors in benzene service in the following areas shall be monitored in accordance with the program requirements of Special Condition No. 9 for the Valves: DOCKF, FUGCR3, and FEFUGDIS. **(4/01)**

### 10. Piping, Valves, Flanges, Pumps, and Compressors in VOC Service - Intensive Directed Maintenance - 28MID

The following requirements apply to the coker, Sulfur Recovery Units (SRUs) 6, 7, and 8, the HVI Unit, and gas oil hydro-treater.

Except as may be provided for in the special conditions of this permit, the following requirements apply to the above-referenced equipment.

- A. These conditions shall not apply (1) where the concentration in the stream is less than 10 percent by weight or (2) where the VOC has an aggregate partial pressure or vapor pressure of less than 0.044 psia at 68°F or (3) operating pressure is at least 5 kilopascals (0.725 psi) below ambient pressure. Equipment excluded from this condition shall be identified in a list to be made available upon request.

## SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 10

- B. Construction of new and reworked piping, valves, pump systems, and compressor systems shall conform to applicable ANSI, API, ASME, or equivalent codes.
- C. New and reworked underground process pipelines shall contain no buried valves such that fugitive emission monitoring is rendered impractical.
- D. To the extent that good engineering practice will permit, new and reworked valves and piping connections shall be so located to be reasonably accessible for leak-checking during plant operation. Non-accessible valves, as defined by 30 TAC Chapter 115, shall be identified in a list to be made available upon request.
- E. New and reworked piping connections shall be welded or flanged. Screwed connections are permissible only on piping smaller than two-inch diameter. No later than the next scheduled quarterly monitoring after initial installation or replacement, all new or reworked connections shall be gas-tested or hydraulically-tested at no less than normal operating pressure and adjustments made as necessary to obtain leak-free performance. Connectors shall be inspected by visual, audible, and/or olfactory means at least weekly by operating personnel walk-through.

Each open-ended valve or line shall be equipped with a cap, blind flange, plug, or a second valve. Except during sampling, the second valve shall be closed.

- F. Accessible valves shall be monitored by leak-checking for fugitive emissions at least quarterly using an approved gas analyzer with a directed maintenance program. Sealless/leakless valves (including, but not limited to, welded bonnet bellows and diaphragm valves) and relief valves equipped with a rupture disc upstream or venting to a control device are not required to be monitored. For valves equipped with rupture discs, a pressure-sensing device shall be installed between the relief valve and rupture disc to monitor disc integrity. All leaking discs shall be replaced at the earliest opportunity but no later than the next process shutdown.

An approved gas analyzer shall conform to requirements listed in 40 CFR § 60.485(a)-(b).

A directed maintenance program shall consist of the repair and maintenance of components assisted simultaneously by the use of an approved gas analyzer such that a minimum concentration of leaking VOC is obtained for each component

## SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 11

being maintained. Replaced components shall be re-monitored within 15 days of being placed back into VOC service.

- G. All new and replacement pumps and compressors shall be equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal. These seal systems need not be monitored and may include (but are not limited to) dual pump seals with barrier fluid at higher pressure than process pressure, seals degassing to vent control systems kept in good working order, or seals equipped with an automatic seal failure detection and alarm system. Submerged pumps or sealless pumps (including, but not limited to, diaphragm, canned, or magnetic-driven pumps) may be used to satisfy the requirements of this condition and need not be monitored.

All other pump and compressor seals emitting VOC shall be monitored with an approved gas analyzer at least quarterly.

- H. Damaged or leaking valves, connectors, compressor seals, and pump seals found to be emitting VOC in excess of 500 ppmv or found by visual inspection to be leaking (e.g., dripping process fluids) shall be tagged and replaced or repaired. Every reasonable effort shall be made to repair a leaking component, as specified in this paragraph, within 15 days after the leak is found. If the repair of a component would require a unit shutdown, the repair may be delayed until the next scheduled shutdown. All leaking components which cannot be repaired until a scheduled shutdown shall be identified for such repair by tagging. At the discretion of the TCEQ Executive Director or his designated representative, early unit shutdown or other appropriate action may be required based on the number and severity of tagged leaks awaiting shutdown.

- I. In lieu of the monitoring frequency specified in paragraph F, valves in gas and light liquid service may be monitored on a semiannual basis if the percent of valves leaking for two consecutive quarterly monitoring periods is less than 0.5 percent.

Valves in gas and light liquid service may be monitored on an annual basis if the percent of valves leaking for two consecutive semiannual monitoring periods is less than 0.5 percent.

If the percent of valves leaking for any semiannual or annual monitoring period is 0.5 percent or greater, the facility shall revert to quarterly monitoring until the facility again qualifies for the alternative monitoring schedules previously outlined in this paragraph.

SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 12

- J. The percent of valves leaking used in paragraph I shall be determined using the following formula:

$$(Vl + Vs) \times 100/Vt = Vp$$

Where:

- Vl = the number of valves found leaking by the end of the monitoring period, either by Method 21 or sight, sound, and smell.
- Vs = the number of valves for which repair has been delayed and are listed on the facility shutdown log.
- Vt = the total number of valves in the facility subject to the monitoring requirements, as of the last day of the monitoring period, not including nonaccessible and unsafe-to-monitor valves.
- Vp = the percentage of leaking valves for the monitoring period.
- K. The results of the required fugitive instrument monitoring and maintenance program shall be made available to the TCEQ Executive Director or his designated representative upon request. Records shall indicate appropriate dates, test methods, instrument readings, repair results, justification for delay of repairs, and corrective actions taken for all components. Records of physical inspections are not required unless a leak is detected.
- L. Compliance with the requirements of this condition does not assure compliance with requirements of 30 TAC Chapter 115, an applicable NSPS, or an applicable NESHAPS and does not constitute approval of alternative standards for these regulations. **(3/99)**

11. Piping, Valves, Pumps, and Compressors in Hydrogen Sulfide (H<sub>2</sub>S) Service

- A. Audio, olfactory, and visual checks for H<sub>2</sub>S leaks within the operating area shall be made once per shift.
- B. Immediately, but no later than one hour upon detection of an H<sub>2</sub>S leak, plant personnel shall take the following actions:
- (1) Stop the leak by taking the equipment out of service or bypass the equipment so that it is no longer in service;

## SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 13

- (2) Isolate the leak;
- (3) Commence repair or replacement of the leaking component; or,
- (4) If the leak cannot be repaired within six hours, the holder of this permit shall use a leak collection and containment system to prevent the leak until repair or replacement can be made if immediate repair is not possible.

Date and time of each inspection shall be noted in the operators log or equivalent. Records shall be maintained at the plant site of the time leaks were detected and all repairs and replacements made due to leaks. These records shall be maintained for a period of two years and made available to representatives of the TCEQ upon request.

### CARBON COMPOUND WASTE GAS STREAMS

12. Non-fugitive emissions from relief valves, safety valves, or rupture discs of gases containing VOC at a concentration of greater than 1 percent are not authorized by this permit unless authorized on the maximum allowable emission rates table (MAERT). Any releases directly to atmosphere from relief valves, safety valves, or rupture discs of gases containing VOC at a concentration greater than 1 weight percent are not consistent with good practice for minimizing emissions.

Storage tank vents, cooling tower exhaust, process fugitive emissions, and Vents (A1905, A1906, AG1137, A330, A9267, A9268, A1745, A553, AR329, C9150/51, C9152/53, AT529, AT665, V731, A1006, V1138, V9160, V1047, and L2COMPVT) are excluded from this requirement. Any other exception to this condition requires prior review and approval by the TCEQ Executive Director, and such exceptions may be subject to strict monitoring requirements. **(7/04)**

13. The relief valves listed on Attachment B of this permit are exempt from the control requirements of Special Condition No. 12.
14. The relief valves listed on Attachment C of this permit shall be equipped with a rupture disc no later than the next process shutdown. A pressure-sensing device shall be installed between the relief valve and the rupture disc to monitor disc integrity.

All leaking rupture discs shall be replaced at the earliest opportunity but no later than the next process shutdown.

## SPECIAL CONDITIONS

Permit Numbers 21262 and PSD-TX-928

Page 14

15. The holder of this permit shall maintain records documenting all incidents which involve the opening of a relief valve that relieves to the atmosphere. In the event that any single relief valve relieves to the atmosphere two or more times within a 12-month period, the holder of this permit shall submit a report to the TCEQ within 45 days of the second relief incident which proposes a plan to prevent multiple reliefs for that valve.

### STORAGE AND LOADING OF VOC

16. New seals shall be installed on the following storage tanks:

Liquid-mounted or shoe-mounted primary seal and a rim-mounted secondary seal shall be installed on the following External Floating Roof (EFR) Tanks: G316, G355, G357, G360, TA318, TA319, TA320, G332, G329, G342, S429, A301, A307, G362, A326, and F323.

Liquid-mounted or shoe-mounted primary seals on the following Internal Floating Roof (IFR) Tanks: A310, A312, G324, X-313, L-303, and L-304. **(3/99)**

17. A. The control requirements specified in paragraphs B through E of this condition shall not apply (1) where the VOC has an aggregate partial pressure of less than 0.5 psia at the maximum expected operating temperature or (2) to storage tanks smaller than 25,000 gallons or (3) to IFR tanks that store material where the VOC has an aggregate partial pressure of less than 0.5 psia. When storing material in IFR tanks, where the VOC has an aggregate partial pressure of less than 0.5 psia, the following shall apply to those specific tanks:
  - (1) General Condition No. 9 of this permit relating to maintenance of emission control is superseded by this special condition.
  - (2) Change of service of IFR tanks, for which seal and roof inspections have not been required per this special condition, to storage of material where the VOC has an aggregate partial pressure of greater than 0.5 psia, must be preceded by a seal inspection and any necessary seal repairs. The type of inspection shall conform to all applicable requirements of 40 CFR § 60.113b(a). For purposes of determining the type of inspection referenced in this paragraph, the inspection intervals defined in 40 CFR § 60.113b(a)(4) will be measured in calendar years and will include periods of time in which the material being stored has an aggregate partial pressure of less than 0.5 psia.



## SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 15

- (3) Emissions from IFRs for which this exemption is claimed shall be calculated using the equations from EPA AP-42 for fixed-roof tanks.
  - (4) Increase in emissions resulting from calculation as a fixed-roof tank shall be absorbed under the existing VOC cap in this flexible permit.
  - (5) The holder of this permit may elect to inspect and maintain the floating roof seals and, thereby, take credit for the resulting emission reduction.
  - (6) This exemption from inspection and maintenance shall not supersede any applicable requirements of NSPS or NESHAPS.
- B. For any tank for which controls are required in order to meet the flexible permit cap, the floating roof shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the IFR: (1) a liquid-mounted seal, (2) two continuous seals mounted one above the other, or (3) a mechanical shoe seal. Installation of equivalent control requires prior review and approval by the TCEQ Executive Director.
- C. An open-top tank containing a floating roof (EFR tank) which uses double seal or secondary seal technology shall be an approved control alternative to an IFR tank provided the primary seal consists of either a mechanical shoe seal, or a liquid-mounted seal, and the secondary seal is rim-mounted. A weather shield is not approvable as a secondary seal unless specifically reviewed and determined to be vapor-tight.
- D. For any tank equipped with a floating roof, the holder of this permit shall follow 40 CFR § 60.113b, Testing and Procedures, to verify seal integrity. Additionally, the permit holder shall follow 40 CFR § 60.115b, Reporting and Recordkeeping Requirements, to provide records of the dates seals were inspected, seal integrity, and corrective actions taken.
- E. The floating roof design shall incorporate sufficient flotation to conform to the requirements of API Code 650, or an equivalent degree of flotation, except that an internal floating cover need not be designed to meet rainfall support requirements; and the materials of construction may be steel or other materials.
- F. Uninsulated tank exterior surfaces exposed to the sun shall be white or aluminum with the exception of those tanks dedicated to pitch or heavy oil service, in which case the surfaces are painted black to absorb sunlight to assist in warming the tank contents.

SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 16

- G. Emissions from all tanks and loading operations associated with this permit shall be calculated using the methods described in Appendix A to the flexible permit application submitted on August 15, 1995, February 10, 1997, and December 23, 1998. (3/99)

COKE HANDLING

18. Coke stockpiles shall be sprinkled with water and/or chemicals as necessary to control coke dust emissions to the minimum level possible under existing conditions.
19. The moisture content of all coke stockpiles shall be maintained at no less than 7 percent moisture at all times in order to minimize fugitive dust emissions. Coke shall be tested for moisture content three times per week. Records shall be maintained for a period of two years.
20. All conveyors shall be covered and water sprays shall be installed and operated as necessary at all coke product transfer points in order to control coke dust emissions to the minimum level possible under existing conditions.

SULFUR UNITS

21. The minimum sulfur recovery efficiency for these permitted units (taken as a whole) shall be 99.8 percent. In addition, the minimum sulfur recover efficiency for SRU-8 alone shall be 99.8 percent. The sulfur recovery efficiency shall be determined by calculation as follows:

$$\text{Efficiency} = 100 (1 - S \text{ stack}/S \text{ feed})$$

Where: Efficiency = sulfur recovery efficiency, percent  
S feed = total sulfur in SRU feed, lbs/hr  
S stack = sulfur in incinerator stack, lbs/hr

The average sulfur emission reduction efficiency (sulfur recovery efficiency) shall be demonstrated for each calendar day by a mass balance calculation using data obtained from the incinerator stack SO<sub>2</sub> monitor, feed sulfur and composition data, and other process flow data. Periods of upset or maintenance emissions shall not be included in determining recovery efficiency. The maximum duration of any shell claus off-gas treating unit maintenance outage that may be excluded from recovery efficiency calculations is 12 hours. Records and copies of the compliance calculations shall be maintained on-site for a period of two years and made readily available to TCEQ personnel upon request. (3/99)

## SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 17

22. In the event that an entire sulfur recovery train must be shut down for emergency reasons, the acid gas feed stream may be routed to the plant flare for a period not to exceed eight hours. Within two hours of diverting the acid gas feed to the emergency flare, the permit holder shall begin operational changes to reduce the amount of SRU feed. These items include (but are not limited to) storing of sour water and process unit curtailment or shutdown. **(3/99)**

## OPERATING PARAMETERS AND CONDITIONS

23. The VOC associated with cooling tower water shall be monitored monthly with a portable organic vapor analyzer, laboratory analysis of cooling water for total organic carbon, and/or approved air stripping system or equivalent. The appropriate equipment shall be maintained so as to minimize fugitive VOC emissions from the cooling tower. Faulty equipment shall be repaired at the earliest opportunity but no later than the next scheduled shutdown of the process unit in which the leak occurs. Records shall be kept of monitoring and repair data for a period of two years.
24. Flares shall be designed and operated in accordance with 40 CFR § 60.18 including specifications of minimum heating value of the waste gas, maximum tip velocity, and pilot flame monitoring. If necessary to insure adequate combustion, sufficient fuel gas shall be added to make the gases combustible. An infrared monitor is considered equivalent to a thermocouple for flame monitoring purposes.
25. Fuel used in the process heaters shall be limited to either natural gas, plant gas, or a combination of natural gas and plant gas. The H<sub>2</sub>S concentration of the fuel gas shall not exceed 162 ppmv on an hourly basis. The H<sub>2</sub>S concentration shall be monitored and recorded in accordance with NSPS, Subpart J.

## CONTROL TECHNOLOGY IMPLEMENTATION

26. Storage tanks required to have new seals per Special Condition No. 16 shall be upgraded at a rate of at least two per year beginning January 1, 1996. Upgraded seals shall be installed on all of the tanks by December 31, 2005. **(3/99)**
27. The CEMS or process computers required per Special Condition No. 8 for process heaters not requiring burner upgrades shall be installed prior to or during the next scheduled process heater turnaround, with all installations to be completed by December 31, 2004. Prior to installation of the CEMS or process computer, these sources shall be monitored using applicable process parameter data stored in either process instrumentation or the Manual Data Capture system. **(3/99)**

SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 18

28. The holder of this permit shall submit additional engineering details which outline control options for the CCU to the TCEQ Air Permits Division no later than December 31, 2003. The following control requirements (equivalent to 1995 best available control technology):

Pollutant	Emission Limit	CEMS
PM	1.0 lb/1,000 lb of coke burn-off	No
Opacity	15 - 20 percent	Yes
CO	500 ppmv	Yes
SO <sub>2</sub>	200 - 300 ppmv	Yes
NO <sub>x</sub>	200 ppmv	Yes
VOC	< 10 ppmv	No

The selected control plan shall be implemented no later than December 31, 2005.

29. The control techniques implemented per Special Condition Nos. 26 through 28 shall be installed according to the schedule listed in Attachment D of this permit.

RECORDKEEPING

30. The holder of this permit shall keep records to demonstrate compliance with the hourly (lb/hr) and annual TPY emission limits specified by the flexible permit for the following compounds: NO<sub>x</sub>, CO, PM, SO<sub>2</sub>, VOC, H<sub>2</sub>S, and benzene. Compliance with the emission limits for each source shall be demonstrated according to the "Source Specific Compliance Guidelines" outlined in the document entitled, Flexible Permit Compliance Document, submitted with the flexible permit applications on August 15, 1995, February 10, 1997, and December 23, 1998. An annual summary of emissions for each criteria pollutant for which an emissions cap has been established in this permit shall be submitted on or before the date the annual air emissions inventory is due for the prior calendar year. This summary will include a table listing the criteria pollutant, actual total annual emissions for that pollutant, and the emissions cap for that pollutant. (3/99)
31. All records required by the conditions of this permit shall be maintained at the plant site for a minimum of two years, unless otherwise specifically stated in these conditions. These records shall be made available to representatives of the TCEQ or any air pollution control program having jurisdiction upon request.

## SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 19

### ADDITIONAL PERMIT ACTION

32. The holder of this permit shall establish NO<sub>x</sub> concentration limits of 20 ppmvd on a 365-day rolling average and 40 ppmvd on a three-hour rolling average, each at 0 percent O<sub>2</sub> for the FCCU CO Boiler (EPN H600) SCR outlet to satisfy the specific Consent Decree terms and conditions as required by the EPA. The holder of this permit shall keep records at the plant site to demonstrate compliance with this condition. The emission limits shall not apply during periods of required SCR bypass, provided that such bypass is necessary, meets the definition of start-up, shutdown, or malfunction, and that DPRLP implements good air pollution control practices to minimize emissions during such events. **(9/07)**
33. The holder of this permit shall establish a maximum NO<sub>x</sub> emission rate of 9.96 tons per year for the Catalytic Cracker Feed Hydrotreater (CFH) Furnace (EPN H1170), based upon the maximum annual average firing rate of 65 MMBtu/hr heat input and maximum annual average NO<sub>x</sub> emission rate of 0.035 lb/MMBtu, to satisfy the specific Consent Decree terms and conditions as required by the EPA. The holder of this permit shall keep records at the plant site to demonstrate compliance with this condition. **(9/07)**
34. The holder of this permit shall establish a maximum NO<sub>x</sub> emission rate of 77.5 tons per year for the Catalytic Reformer SCR (EPN H53NN), based upon the maximum annual average firing rate of 885 MMBtu/hr heat input and maximum annual average NO<sub>x</sub> emission rate of 0.02 lb/MMBtu, to satisfy the specific Consent Decree terms and conditions as required by the EPA. The holder of this permit shall keep records at the plant site to demonstrate compliance with this condition. **(9/07)**
35. The holder of this permit shall establish a maximum NO<sub>x</sub> emission rate of 56.76 tons per year for the Distilling Unit No. 2 Furnace (EPN H5100) based upon the maximum annual average firing rate of 324 MMBtu/hr heat input and maximum annual average NO<sub>x</sub> emission rate of 0.040 lb/MMBtu, to satisfy the specific Consent Decree terms and conditions as required by the EPA. The holder of this permit shall keep records at the plant site to demonstrate compliance with this condition. **(9/07)**
36. The holder of this permit shall establish a maximum NO<sub>x</sub> emission rate of 56.76 tons per year for the Distilling Unit No. 2 Furnace (EPN H5101) based upon the maximum annual average firing rate of 324 MMBtu/hr heat input and maximum annual average NO<sub>x</sub> emission rate of 0.040 lb/MMBtu, to satisfy the specific Consent Decree terms and conditions as required by the EPA. The holder of this permit shall keep records at the plant site to demonstrate compliance with this condition. **(9/07)**

## SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 20

37. The holder of this permit shall establish a maximum NO<sub>x</sub> emission rate of 24.18 tons per year for the Distilling Unit No. 1 Furnace (EPN H613) based upon the maximum annual average firing rate of 138 MMBtu/hr heat input and maximum annual average NO<sub>x</sub> emission rate of 0.040 lb/MMBtu, to satisfy the specific Consent Decree terms and conditions as required by the EPA. The holder of this permit shall keep records at the plant site to demonstrate compliance with this condition. **(9/07)**
  
38. A copy of this permit shall be kept at the plant site and made immediately available at the request of personnel from the TCEQ or any air pollution control agency having jurisdiction.

### PLANNED MAINTENANCE, START-UP, AND SHUTDOWN (MSS) ACTIVITIES

39. This permit authorizes emissions from those points listed in the attached table entitled “Emission Sources - Maximum Allowable Emission Rates” (MAERT) and the facilities covered by this permit are authorized to emit subject to the emission rate limits on the MAERT table and other requirements specified in the special conditions.

Planned startup and shutdown emissions due to the activities identified in Special Condition 2 are authorized from facilities and emission points identified in Attachment D in other construction permits at the site provided the facility and emissions are compliant with the respective MAERT and special conditions, or Special Condition 12 of this permit. **(08/10)**

40. This permit authorizes the emissions from the facilities identified in Attachment D for the planned maintenance, startup, and shutdown (MSS) activities summarized in the MSS Activity Summary (Attachment C) attached to this permit.

Attachment A identifies the inherently low emitting MSS activities that may be performed at Regulated Entity Identification Number (RN) 100211879. Emissions from activities identified in Attachment A shall be considered to be equal to the potential to emit represented in the permit application. The estimated emissions from the activities listed in Attachment A must be revalidated annually. This revalidation shall consist of the estimated emissions for each type of activity and the basis for that emission estimate.

Routine maintenance activities, as identified in Attachment B may be tracked through the work orders or equivalent. Emissions from activities identified in Attachment B shall be estimated using the number of work orders or equivalent each month and the emissions associated with that activity identified in the permit application.

## SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 21

Unless otherwise prescribed in this permit, the performance of each planned MSS activity not identified in Attachments A or B and the emissions associated with it shall be recorded and include at least the following information:

- A. the physical location at which emissions from the MSS activity occurred, including the emission point number and common name for the point at which the emissions were released into the atmosphere;
- B. the type of planned MSS activity and the reason for the planned activity;
- C. the common name and the facility identification number, if applicable, of the facilities at which the MSS activity and emissions occurred;
- D. the date on which the MSS activity occurred;
- E. the estimated quantity of each air contaminant, or mixture of air contaminants, emitted with the data and methods used to determine it. The emissions shall be estimated using the methods identified in the permit application, consistent with good engineering practice.

Emissions from all completed planned MSS activities shall be summed monthly and the rolling 12-month emissions shall be updated by the end of the month following the activity. **(08/10)**

- 41. Process units and facilities, with the exception of those identified in Special Conditions 44 and 45, and Attachment A shall be depressurized, emptied, degassed, and placed in service in accordance with the following requirements.
  - A. The process equipment shall be depressurized to a control device or a controlled recovery system prior to venting to atmosphere, degassing, or draining liquid. Equipment that only contains material that is liquid with VOC partial pressure less than 0.50 psi at the normal process temperature may be opened to atmosphere and drained in accordance with paragraph C of this special condition.
  - B. If mixed phase materials must be removed from process equipment, the cleared material shall be routed to a knockout drum or equivalent to allow for managed initial phase separation. If the VOC partial pressure is greater than 0.50 psi at either the normal process temperature, any vents in the system must be routed to a control device or a controlled recovery system. Control must remain in place until degassing has been completed or the system is no longer vented to atmosphere.

## SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 22

- C. All liquids from process equipment or storage vessels must be removed to the maximum extent practical prior to opening equipment to commence degassing and/or maintenance. Liquids with a VOC partial pressure greater than or equal to 0.044 psia at 68°F shall be drained into a closed vessel unless prevented by the physical configuration of the equipment. If it is necessary to drain liquid into an open pan or sump, the liquid must be covered or transferred to a covered vessel within one hour of being drained. After draining is complete, empty open pans may remain in use for housekeeping reasons to collect incidental drips.
  
- D. If the VOC partial pressure is greater than 0.50 psi at the normal process temperature, facilities shall be degassed using good engineering practice to ensure air contaminants are removed from the system through the control device or controlled recovery system to the extent allowed by process equipment design. The control device or recovery system utilized shall be recorded with the estimated emissions from controlled and uncontrolled degassing calculated using the methods that were used to determine allowable emissions for the permit application.
  - i. For MSS activities identified in Attachment B, the following option may be used in lieu of ii below. The facilities being prepared for maintenance shall not be vented directly to atmosphere, except as necessary to verify an acceptable VOC concentration and establish isolation of the work area, until the VOC concentration has been verified to be less than 10 percent of the lower explosive limit (LEL) per the site safety procedures.
  
  - ii. The locations and/or identifiers where the purge gas or steam enters the process equipment or storage vessel and the exit points for the exhaust gases shall be recorded. If the process equipment is purged with a gas, two system volumes of purge gas must have passed through the control device or controlled recovery system before the vent stream may be sampled to verify acceptable-VOC concentration prior to uncontrolled venting. The VOC sampling and analysis shall be performed using an instrument meeting the requirements of Special Condition 4 42. The sampling point shall be upstream of the inlet to the control device or controlled recovery system. The sample ports and the collection system must be designed and operated such that there is no air leakage into the sample probe or the collection system downstream of the process equipment or vessel being purged. The facilities shall be degassed to a control device or controlled recovery system until the VOC concentration is less than 10,000 ppmv or 10 percent of the LEL.



## SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 23

- E. Gases and vapors (including vapors from residual liquids) with VOC partial pressure greater than 0.50 psi may be vented directly to atmosphere if all the following criteria are met:
  - i. It is not technically practicable to depressurize or degas, as applicable, into the process.
  - ii. There is not an available connection to a plant control system (flare).
  - iii. There is no more than 50 lb of air contaminant to be vented to atmosphere during shutdown or startup, as applicable.

Except when identified for an activity on Attachment A, all instances of venting directly to atmosphere per Special Condition 41.E must be documented when occurring as part of any MSS activity. The emissions associated with venting without control must be included in the work order or equivalent, or in the form of a procedure, a report, or database entry for those planned MSS activities identified in Attachment B. **(08/10)**

- 42. Air contaminant concentration shall be measured using an instrument/detector meeting one set of requirements specified below.
  - A. VOC concentration shall be measured using an instrument meeting all the requirements specified in EPA Method 21 (40 CFR 60, Appendix A) with the following exceptions:
    - i. The instrument shall be calibrated within 24 hours of use with a calibration gas such that the response factor of the VOC (or mixture of VOCs) to be monitored shall be less than 2.0. The calibration gas and the gas to be measured, and its approximate response factor shall be recorded.
    - ii. Sampling shall be performed as directed by this permit in lieu of section 8.3 of Method 21. During sampling, data recording shall not begin until after two times the instrument response time. The date and time shall be recorded, and VOC concentration shall be monitored for at least 5 minutes, recording VOC concentration each minute. The highest measured VOC concentration shall not exceed the specified VOC concentration limit prior to uncontrolled venting.

SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 24

B. Colorimetric gas detector tubes may be used to determine air contaminant concentrations if they are used in accordance with the following requirements.

- i. The air contaminant concentration measured is less than 80 percent of the range of the tube. If the maximum range of the tube is greater than the release concentration defined in iii., the concentration measured is at least 20 percent of the maximum range of the tube.
- ii. The tube is used in accordance with the manufacturer's guidelines.
- iii. At least 2 samples taken at least 5 minutes apart must satisfy the following prior to uncontrolled venting:

measured contaminant concentration (ppmv) < release concentration.

Where the release concentration is:

10,000\*mole fraction of the total air contaminants present that can be detected by the tube.

The mole fraction may be estimated based on process knowledge. The release concentration and basis for its determination shall be recorded.

Records shall be maintained of the tube type, range, measured concentrations, and time the samples were taken.

C. Lower explosive limit measured with a lower explosive limit detector.

- i. The detector shall be calibrated monthly with a certified pentane gas standard at 25% of the lower explosive limit (LEL) for pentane. Records of the calibration date/time and calibration result (pass/fail) shall be maintained.
- ii. A daily functionality test shall be performed on each detector using the same certified gas standard used for calibration. The LEL monitor shall read no lower than 90% of the calibration gas certified value. Records, including the date/time and test results, shall be maintained.
- iii. A certified methane or isobutylene gas standard equivalent to 25% of the LEL for pentane may be used for calibration and functionality tests provided that the LEL response is within 95% of that for pentane. **(08/10)**

## SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 25

43. If the removal of a component for repair or replacement results in an open ended line or valve, the open ended line is exempt from any NSR permit condition requirement to install a cap, blind flange, plug, or second valve for 72 hours. If the repair or replacement is not completed within 72 hours, the permit holder must complete either of the following actions within that time period;
  - A. a cap, blind flange, plug, or second valve must be installed on the line or valve; or
  - B. the permit holder shall verify that there is no leakage from the open-ended line or valve. The open-ended line or valve shall be monitored on a weekly basis in accordance with the applicable NSR permit condition for fugitive emission monitoring except that a leak is defined as any VOC reading greater than background. Leaks must be repaired within 24 hours or a cap, blind flange, plug, or second valve must be installed on the line or valve. The results of this weekly check and any corrective actions taken shall be recorded. **(08/10)**
  
44. This permit authorizes emissions from EPN TNKLNDR1 and TNKLNDR2, for the storage tanks identified in the attached facility list during planned floating roof landings. Tank roofs may only be landed for changes of tank service or tank inspection/maintenance as identified in the permit application, except when the VOC vapors below the floating roof are routed to a control device or a controlled recovery system from the time the floating roof is landed until the floating roof is being refloated. Emissions from change of service tank landings shall not exceed 10 tons of VOC in any rolling 12 month period. Tank roof landings include all operations when the tank floating roof is on its supporting legs. These emissions are subject to the maximum allowable emission rates indicated on the MAERT. The following requirements apply to tank roof landings.
  - A. The tank liquid level shall be continuously lowered after the tank floating roof initially lands on its supporting legs until the tank has been drained to the maximum extent practicable without entering the tank. Liquid level may be maintained steady for a period of up to two hours if necessary to allow for valve lineups and pump changes necessary to drain the tank. This requirement does not apply where the vapor under a floating roof is routed to control or a controlled recovery system during this process.
  - B. If the VOC partial pressure of the liquid previously stored in the tank is greater than 0.50 psi at 95°F, tank refilling or degassing of the vapor space under the landed floating roof must begin within 24 hours after the tank has been drained

## SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 26

unless the vapor under the floating roof is routed to control or a controlled recovery system during this period. Floating roof tanks with liquid capacities less than 100,000 gallons may be degassed without control if the VOC partial pressure of the standing liquid in the tank has been reduced to less than 0.02 psia prior to ventilating the tank. Controlled degassing of the vapor space under landed roofs shall be completed as follows:

- i. Any gas or vapor removed from the vapor space under the floating roof must be routed to a control device or a controlled recovery system and controlled degassing must be maintained until the VOC concentration is less than 10,000 ppmv or 10 percent of the LEL. The locations and identifiers of vents other than permanent roof fittings and seals, control device or controlled recovery system, and controlled exhaust stream shall be recorded. There shall be no other gas/vapor flow out of the vapor space under the floating roof when degassing to the control device or controlled recovery system.
- ii. The vapor space under the floating roof shall be vented using good engineering practice to ensure air contaminants are flushed out of the tank through the control device or controlled recovery system to the extent allowed by the storage tank design.
- iii. A volume of purge gas equivalent to twice the volume of the vapor space under the floating roof must have passed through the control device or into a controlled recovery system, before the vent stream may be sampled to verify acceptable VOC concentration. The measurement of purge gas volume shall not include any make-up air introduced into the control device or recovery system. The VOC sampling and analysis shall be performed as specified in Special Condition 42.
- iv. The sampling point shall be upstream of the inlet to the control device or controlled recovery system. The sample ports and the collection system must be designed and operated such that there is no air leakage into the sample probe or the collection system downstream of the process equipment or vessel being purged.
- v. If ventilation is to be maintained with emission control, the VOC concentration shall be recorded once an hour.

## SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 27

- vi. Degassing must be performed every 24 hours unless there is no standing liquid in the tank or the VOC partial pressure of the remaining liquid in the tank is less than 0.15 psia.
- C. The tank shall not be opened except as necessary to set up for degassing and cleaning, or ventilated without control, until either all standing liquid has been removed from the tank or the liquid in the tank has a VOC partial pressure less than 0.02 psia. These criteria may be demonstrated in any one of the following ways.
- i. Low VOC partial pressure liquid that is soluble with the liquid previously stored may be added to the tank to lower the VOC partial pressure of the liquid mixture remaining in the tank to less than 0.02 psia. This liquid shall be added during tank degassing if practicable. The estimated volume of liquid remaining in the drained tank and the volume and type of liquid added shall be recorded. The liquid VOC partial pressure may be estimated based on this information and engineering calculations.
  - ii. If water is added or sprayed into the tank to remove standing VOC, one of the following must be demonstrated:
    - a. Take a representative sample of the liquid remaining in the tank and verify no visible sheen using the static sheen test from 40 CFR 435 Subpart A Appendix 1.
    - b. Take a representative sample of the liquid remaining in the tank and verify hexane soluble VOC concentration is less than 1000 ppmw using EPA method 1664 (may also use 8260B or 5030 with 8015 from SW-846).
    - c. Stop ventilation and close the tank for at least 24 hours. When the tank manway is opened after this period, verify VOC concentration is less than 1000 ppmv through the procedure in Special Condition 42.
  - iii. No standing liquid verified through visual inspection.

The permit holder shall maintain records to document the method used to release the tank.

## SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 28

- D. Following a planned MSS-related floating roof landing, tanks shall be refilled as rapidly as practicable until the roof is off its legs with the following exceptions:
- i. Only two gasoline tanks may be filled at any time at a rate not to exceed 22,400 Bbl/hour total. Only two crude tanks may be filled at any time at a rate not to exceed 10,254 bbl/hour total.
  - ii. The vapor space below the tank roof is directed to a control device when the tank is refilled until the roof is floating on the liquid. The control device used and the method and locations used to connect the control device shall be recorded. All vents from the tank being filled must exit through the control device.
- E. The occurrence of each roof landing and the associated emissions shall be recorded and the rolling 12-month tank roof landing emissions shall be updated on a monthly basis. These records shall include at least the following information:
- i. the identification of the tank and emission point number, and any control devices or recovery systems used to reduce emissions;
  - ii. the reason for the tank roof landing;
  - iii. for the purpose of estimating emissions, the date, time, and other information specified for each of the following events:
    - a. the roof was initially landed,
    - b. all liquid was pumped from the tank to the extent practical,
    - c. start and completion of controlled degassing, and total volumetric flow,
    - d. all standing liquid was removed from the tank or any transfers of low VOC partial pressure liquid to or from the tank including volumes and vapor pressures to reduce tank liquid VOC partial pressure to <0.02 psi,

SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 29

- e. if there is liquid in the tank, VOC partial pressure of liquid, start and completion of uncontrolled degassing, and total volumetric flow,
  - f. refilling commenced, liquid filling the tank, and the volume necessary to float the roof; and
  - g. tank roof off supporting legs, floating on liquid;
- iv. the estimated quantity of each air contaminant, or mixture of air contaminants, emitted between events c and g with the data and methods used to determine it. The emissions associated with roof landing activities shall be calculated using the methods described in Section 7.1.3.2 of AP-42 "Compilation of Air Pollution Emission Factors, Chapter 7-Storage of Organic Liquids" dated November 2006 and the permit application.  
**(08/10)**
45. Fixed roof tanks shall not be ventilated without control, until either all standing liquid has been removed from the tank or the liquid in the tank has a VOC partial pressure less than 0.02 psia. This shall be verified and documented through one of the criteria identified in Special Condition 44.C. Fixed roof tanks manways may be opened without emission controls when there is standing liquid with a VOC partial pressure greater than 0.02 psi vapor as necessary to set up for degassing and cleaning. One manway may be opened to allow access to the tank to remove or de-volatilize the remaining liquid. The emission control system shall meet the requirements of Special Condition 44.B.i through 44.B.v and records maintained per Special Condition 44.E.iii.c through 44.E.iii.e, and 44.E.iv. Low vapor pressure liquid may be added to and removed from the tank as necessary to lower the vapor pressure of the liquid mixture remaining in the tank to less than 0.02 psia.  
**(08/10)**
46. The following requirements apply to vacuum and air mover truck operations to support planned MSS at this site:
- A. Vacuum pumps and blowers shall not be operated on trucks except as allowed in Part C of this condition.
  - B. The permit holder shall determine the vacuum truck emissions each month using the daily vacuum truck records and the calculation methods utilized in the permit application. If records of the volume of liquid transferred for each pick-up are not maintained, the emissions shall be determined using the physical properties of the

SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 30

liquid vacuumed with the greatest potential emissions. Rolling 12 month vacuum truck emissions shall also be determined on a monthly basis.

- C. Vacuum pump or blower may be operated consistent with the requirements in Shell operating procedure M-144, formerly EC-3 submitted with the application. Ensure that these emissions shall stay below the permitted cap. **(08/10)**
47. MSS activities represented in the permit application may be authorized under permit by rule only if the procedures, emission controls, monitoring, and recordkeeping are the same as those required by this permit. **(08/10)**
48. All permanent facilities must comply with all operating requirements, limits, and representations in the permits identified in Attachment D during planned startup and shutdown unless alternate requirements and limits are identified in this permit. Alternate requirements for emissions from routine emission points are identified below.
- A. Combustion units, with the exception of flares, at this site are exempt from NO<sub>x</sub> and CO operating requirements identified in special conditions in other NSR permits during planned startup and shutdown if the following criteria are satisfied.
- i. The maximum allowable emission rates in the permit authorizing the facility are not exceeded.
  - ii. The startup period does not exceed the duration in specified in Attachment E and the firing rate does not exceed 75 percent of the design firing rate. The time it takes to complete the shutdown does not exceed the periods specified in Attachment E.
  - iii. Control devices are started and operating properly when venting a waste gas stream.
- B. A record shall be maintained indicating that the start and end times each of the activities identified above occur and documentation that the requirements for each have been satisfied. **(08/10)**
49. Control devices required by this permit for emissions from planned MSS activities are limited to those types identified in this condition. Control devices shall be operated with no visible emissions except periods not to exceed a total of five minutes during any two consecutive hours. Each device used must meet all the requirements identified for that type of control device.



## SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 31

Controlled recovery systems identified in this permit shall be directed to an operating refinery process or to a collection system that is vented through a control device meeting the requirements of this permit condition.

- A. Carbon Adsorption System (CAS).
- i. The CAS shall consist of 2 carbon canisters in series with adequate carbon supply for the emission control operation.
  - ii. The CAS shall be sampled down stream on the first can and the concentration recorded at least once every hour of CAS run time to determine breakthrough of the VOC. The sampling frequency may be extended using either of the following methods:
    - a. It may be extended to up to 30 percent of the minimum potential saturation time for a new can of carbon. The permit holder shall maintain records including the calculations performed to determine the minimum saturation time.
    - b. The carbon sampling frequency may be extended to longer periods based on previous experience with carbon control of a MSS waste gas stream. The past experience must be with the same VOC, type of facility, and MSS activity. The basis for the sampling frequency shall be recorded. If breakthrough is monitored on the initial sample of the upstream can when the polishing can is put in place, a permit deviation shall be recorded.
  - iii. The method of VOC sampling and analysis shall be by detector meeting the requirements of Special Condition 42.
  - iv. Breakthrough is defined as the highest measured VOC concentration at or exceeding 100 ppmv above background. When the condition of breakthrough of VOC from the initial saturation canister occurs, the waste gas flow shall be switched to the second canister and a fresh canister shall be placed as the new final polishing canister within four hours. Sufficient new activated carbon canisters shall be maintained at the site to replace spent carbon canisters such that replacements can be done in the above specified time frame.

## SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 32

- v. Records of CAS monitoring shall include the following:
  - a. Sample time and date.
  - b. Monitoring results (ppmv).
  - c. Canister replacement log.
- vi. Single canister systems are allowed if the time the carbon canister is in service is limited to no more than 30% of the minimum potential saturation time. The permit holder shall maintain records for these systems, including the calculations performed to determine the saturation time. The time limit on carbon canister service shall be recorded and the expiration date attached to the carbon can.

### B. Thermal Oxidizer.

- i. The thermal oxidizer firebox exit temperature shall be maintained at not less than 1400°F and waste gas flows shall be limited to assure at least a 0.5 second residence time in the fire box while waste gas is being fed into the oxidizer.
- ii. The thermal oxidizer exhaust temperature shall be continuously monitored and recorded when waste gas is directed to the oxidizer. The temperature measurements shall be made at intervals of six minutes or less and recorded at that frequency.

The temperature measurement device shall be installed, calibrated, and maintained according to accepted practice and the manufacturer's specifications. The device shall have an accuracy of the greater of  $\pm 0.75$  percent of the temperature being measured expressed in degrees Celsius or  $\pm 2.5^\circ\text{C}$ .

### C. Internal Combustion Engine.

- i. The internal combustion engine shall have a VOC destruction efficiency of at least 99 percent.
- ii. The engine must have been stack tested with butane to confirm the required destruction efficiency within the past 12 months. VOC shall be measured in accordance with the applicable United States Environmental Protection Agency (EPA) Reference Method during the stack test and the exhaust flow rate may be determined from measured fuel flow rate and measured oxygen concentration. A copy of the stack test report shall be

## SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 33

maintained with the engine. There shall also be documentation of acceptable VOC emissions following each occurrence of engine maintenance which may reasonably be expected to increase emissions including oxygen sensor replacement and catalyst cleaning or replacement. Stain tube indicators specifically designed to measure VOC concentration shall be acceptable for this documentation, provided a hot air probe or equivalent device is used to prevent error due to high stack temperature, and three sets of concentration measurements are made and averaged. Portable VOC analyzers meeting the requirements of Special Condition 4 are also acceptable for this documentation

- iii. The engine shall be operated with an oxygen sensor-based air-to-fuel ratio (AFR) controller. Documentation for each AFR controller that the manufacturer's, or supplier's recommended maintenance has been performed, including replacement of the oxygen sensor as necessary for oxygen sensor-based controllers shall be maintained with the engine. The oxygen sensor shall be replaced at least quarterly in the absence of a specific written recommendation.

### D. The plant flare system

- i. The heating value and velocity requirements in 40 CFR 60.18 shall be satisfied during operations authorized by this permit.
- ii. The flare shall be operated with a flame present at all times and/or have a constant pilot flame. The pilot flame shall be continuously monitored by a thermal couple or an infrared monitor. The time, date, and duration of any loss of pilot flame shall be recorded. Each monitoring device shall be accurate to, and shall be calibrated at a frequency in accordance with, the manufacturer's specifications or equivalent.
- iii. Flares systems shall have a continuous flow monitor that provides a record of the vent stream flow to the flare. The monitoring shall be used to maintain waste gas above the minimum heating value.
- iv. The combined assist natural gas and waste stream to each flares shall meet the Title 40 Code of Federal Regulations (40 CFR) § 60.18 specifications

SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 34

of minimum heating value and maximum tip velocity. These flares shall have a continuous flow monitor that provides a record of the vent stream flow to the flare. Measurement, good engineering practice, or process knowledge shall also be used to monitor the waste gas stream for compliance with the minimum heating value. **(08/10)**

50. The following requirements apply to capture systems for the plant flare system.

- A. Either conduct a once a month visual, audible, and/or olfactory inspection of the capture system to verify there are no leaking components in the capture system; or verify the capture system is leak-free by inspecting in accordance with 40 CFR Part 60, Appendix A, Test Method 21 once a year. Leaks shall be indicated by an instrument reading greater than or equal to 500 ppmv above background.
- B. The control device shall not have a bypass.

or

If there is a bypass for the control device, comply with either of the following requirements:

- i. Install a flow indicator that records and verifies zero flow at least once every fifteen minutes immediately downstream of each valve that if opened would allow a vent stream to bypass the control device and be emitted, either directly or indirectly, to the atmosphere; or
- ii. Once a month, inspect the valves, verifying the position of the valves and the condition of the car seals that prevent flow out the bypass.

These requirements do not apply to high point vent and low point drain valves. A deviation shall be reported if the monitoring or inspections indicate bypass of the control device when required to be in service per this permit.

- C. If any of the above inspections is not satisfactory, the permit holder shall promptly take necessary corrective action. Records shall be maintained documenting the performance and results of the inspections required above. **(08/10)**

SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 35

51. This permit authorizes emissions from the Miscellaneous Painting Fugitives (EPN PAINTFE) for the following planned MSS activities:

<u>Source</u>	<u>Location</u>	<u>Activity</u>
PAINTFE	Refinery Paint Yard	Paint coatings are applied primarily by air atomization or airless sprayers. A limited amount of brushing and rolling is also used. The painting activity emissions will be minimized through good housekeeping practices.

The performance of each maintenance activity and the emissions associated with it shall be recorded, and the rolling 12-month emissions shall be updated on a monthly basis. These records shall include at least the following information:

- A. The physical location at which emissions from the MSS activity occurred, including the emission point number, common name, and any other identifier for the point at which the emissions were released into the atmosphere;
  - B. The type of planned MSS activity and the reason for the planned activity;
  - C. The common name and the facility identification number of the facilities at which the MSS activity and emissions occurred;
  - D. The dates of the MSS activity and its duration;
  - E. The estimated quantity of each air contaminant, or mixture of air contaminants, emitted with the data and methods used to determine it. The emissions shall be estimated using the methods identified in the amendment application, PI-1 dated May 22, 2006, consistent with good engineering practice. **(9/07)**
52. No visible emissions shall leave the property due to painting or abrasive blasting. **(08/10)**
53. Black Beauty, Coal Slag, and Garnet Sand may be used for abrasive blasting. The permit holder may also use blast media that meet the criteria below:
- A. The media shall not contain asbestos or greater than 1.0 weight percent crystalline silica.

SPECIAL CONDITIONS

Permit Numbers 21262 and PSDTX928

Page 36

- B. The weight fraction of any metal in the blast media with a short term effects screening level (ESL) less than 50 micrograms per cubic meter as identified in the most recently published TCEQ ESL list shall not exceed the  $ESL_{\text{metal}}/1000$ .
- C. The MSDS for each media used shall be maintained on site.

Blasting media usage and the associated emissions shall be recorded each month and the rolling 12 month total emissions updated by the end of the month following the activity. **(08/10)**

- 54. With the exception of the MAERT emission limits and those exceptions listed below, these permit conditions become effective 180 days after this permit has been issued. During this period, monitoring and recordkeeping shall satisfy the requirements in Special Condition 40.A through 40.D. Emissions shall be estimated using good engineering practice and methods to provide reasonably accurate representations for emissions. The basis used for determining the quantity of air contaminants to be emitted shall be recorded. The permit holder may maintain abbreviated records of emissions from Attachment A and B activities as allowed in Special Condition 2 rather than documenting all the information required by Special Condition 2 parts A through D.
- 55. Planned MSS activities must be conducted in a manner consistent with good practice for minimizing emissions, including the use of air pollution control equipment, practices, and processes. All reasonable and practical efforts to comply with Special Conditions 39 through 54 must be used when conducting the planned MSS activity, until the commission determines that the efforts are unreasonable or impractical, or that the activity is an unplanned MSS activity. **(08/10)**

Dated: August 19, 2010

ATTACHMENT A

Permit Numbers 21262 and PSDTX928

INHERENTLY LOW EMITTING ACTIVITIES

Activity	Emissions				
	VOC	NO <sub>x</sub>	CO	PM	H <sub>2</sub> S/SO <sub>2</sub>
Catalyst activation/deactivation	X	X	X	X	X
Management of sludge from pits, ponds, sumps, and water conveyances	X			X	X
Aerosol Cans	X			X	
Inspection, repair and replacement of analytical equipment	X	X	X		X
Inspection, repair and replacement of Carbon canisters	X		X	X	X
Catalyst charging/handling	X		X	X	X
Inspection, repair, replacement, adjustment, testing and calibration of Instrumentation/analyzer	X	X	X		X
Meter proving	X				
Inspection, repair, and replacement of filters and screens	X			X	X
Maintenance on water treatment systems (cooling, boiler, potable)	X				
Soap and other liquid based cleaners	X				
Inspection, repair and replacement of monitoring/measuring equipment (e.g., sight glasses, rotometers)	X	X	X		X
Inspection, repair and replacement of ancillary equipment (e.g., coupling alignment, oil seals, blinding)	X	X	X	X	X
Cleaning (including strainers, lube oil systems)	X			X	X
Welding	X	X	X	X	
Leak and operability checks (e.g., steam turbine overspeed tests, troubleshooting)	X	X	X	X	X
Inspection, repair and replacement of fugitive components	X	X	X	X	X
Process Sampling	X	X	X	X	X
Fugitive components associated with maintenance	X	X	X		X
Combinations of the above	X	X	X	X	X

Dated: August 19, 2010

ATTACHMENT B

Permit Numbers 21262 and PSDTX928

ROUTINE MAINTENANCE ACTIVITIES

Pump, compressor, vessel, exchanger, furnace, boiler inspection, repair, replacement not included in Attachment A.

Dated: August 19, 2010



ATTACHMENT C

Permit Numbers 21262 and PSDTX928

MSS ACTIVITY SUMMARY

<b>Facilities</b>	<b>Description</b>	<b>Emissions Activity</b>	<b>EPN</b>
All production-related equipment	process unit/facility startup, shutdown or maintenance	vent to flare	COKEFLARE EP FLARE FLNFLARE WP FLARE
all process units and tanks	preparation for unit turnaround or facility/component inspection, repair/replacement	Manage liquid	FUGVACDPR
all production-related	VOC coating	VOC coating	PAINTFE
all floating roof tanks	tank startup, shutdown or maintenance	Filling, emptying and intervening maintenance	All Floating Roof Tanks
see Attachment A	Inherently low emitting activities	see Attachment A	AEROSAPPL AEROSDISP DEGREAS01 FUGMSSDPR FUGSMPDPR
all production-related	abrasive blasting and non-VOC coating	PM from blasting media, coating preparation, and application	PAINTFE, FUGABRBLST
see Attachment B	Routine maintenance activities	see Attachment B	MSSDECNDPR
All production-related equipment	process unit/facility startup, shutdown or maintenance	Vent to atmosphere	COKERSD DPREFSDSU HP1SDSU SGPSD SHCUSD SULFURSD
All production-related combustion equipment	Combustion facility startup or shutdown	vent to atmosphere	All Combustion Units
Fixed Roof tanks	tank startup, shutdown or maintenance	Filling, emptying and intervening maintenance	All Fixed Roof Tanks
all production-related equipment	Combinations of the above	Combinations of the above	All of the above

Dated: August 19, 2010

## ATTACHMENT D

Permit Numbers 21262 and PSDTX928

### FACILITY LIST

This permit authorizes MSS emissions from the permanent site facilities identified below. Emissions may occur from temporary facilities (frac tanks, containers, vacuum trucks, facilities used for painting or abrasive blasting, portable control devices or controlled recovery systems) to support the MSS activities performed at the permanent site facilities listed below as represented in the permit application.

MSS from facilities authorized by permit number 21262 are eligible for the MSS limits in this permit.

Dated: August 19, 2010

ATTACHMENT E

Permit Numbers 21262 and PSDTX928

TYPICAL HEATER STARTUP AND SHUTDOWN PERIODS

<b>Heater Number</b>	<b>Typical Hours to Shutdown</b>	<b>Typical Hours to Start-up</b>
H-5100	2	12
H-5101	2	12
H-5104	2	12
H-5102	2	12
H-5103	2	12
H-5105	2	12
H-613	2	12
H-63000	2	12
H-5200	2	7
H-5600	6	10
H-1010	10	10
H-1011	8	5
H-1100	72 hours with Hot-Hydrogen Strip. 48 hrs for other	27 hours with Sulfiding 10 hrs for other
H-3300	6	24
H-1170	72 hours with Hot-Hydrogen Strip. 48 hrs for other	27 hours with Sulfiding 10 hrs for other
H-31001	6	24
H-31002	6	24
H-31003	6	24
H-70001	12	24
H-70002	6	24
H1000	12	12
H-1001	6	6
H-5301/2/3/4	12	12
H5305	12	12
H5350	12	12
H-600	2 hr (for Nat Gas, not including CO fuel)	40
H-5400	12	96
H-5402	12	24
H-5403	12	96
H-5404	12	24
H-5500	24	36
H-3600	12	24

Dated: August 19, 2010

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

EMISSION CAPS

Permit Numbers 21262 and PSDTX928

This table lists the maximum allowable emission caps and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
A213	CR3 Recycle Gas SG Analyzer	Benzene		
A214	CR3 Recycle Gas Moisture Analyzer	Benzene		
A298	CR3 Regen Gas O <sub>2</sub> Analyzer	Benzene		
A300	CR3 Regen Gas Comb. Analyzer	Benzene		
AP16	AP16 Storage Tank	Benzene		
AP17	AP17 Storage Tank	Benzene		
AP6	AP6 Storage Tank	Benzene		
AP8	AP8 Storage Tank	Benzene		
AYARDOWS	WW - Sewer A Yard Oily Water	Benzene		
BARGE	Marine Loading - Barge Docks	Benzene		
BENZENE1	Marine Loading - Benzene Dock 1	Benzene		
BENZENE2	Marine Loading - Benzene Dock 2	Benzene		
BENZENE4	Marine Loading - Benzene Dock 4	Benzene		
BYARDOWS	WW - Sewer B Yard Oily Water	Benzene		
CCLP	WW - Cat Cracker Lube Plant	Benzene		
CPI1	WW- CPI Oil Water Separator	Benzene		
CPI2	WW- CPI Oil Water Separator	Benzene		
CRUDE	Marine Loading - Crude Docks	Benzene		
CYARDOWS	Wastewater Fugitives (4)	Benzene		
DAOWS	WW - Sewer DA Oily Water	Benzene		
DD2	WW - Dispatching Distilling 2	Benzene		
DOCK1	Marine Loading - Dock 1	Benzene		
DOCK2	Marine Loading - Dock 2	Benzene		
DOCK4	Marine Loading - Dock 4	Benzene		
DOCKS	Dock Wastewater Collection	Benzene		
DYARDOWS	WW - Sewer D Yard Oily Water	Benzene		
F314	F314 Storage Tank	Benzene		
F315	F315 Storage Tank	Benzene		
F316	F316 Storage Tank	Benzene		
F317	F317 Storage Tank	Benzene		
F338	F338 Storage Tank	Benzene		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
FUGCCU	FCCU Fugitives (4)	Benzene		
FUGCCUSCR	FCCU SCR Fugitives (4)	Benzene		
FUGCOKER	Coke Handling Fugitives (4)	Benzene		
FUGCR3	CR3 Fugitives (4)	Benzene		
FUGCR3TF	Hydroprocessing Tank Farm Fugitives (4)	Benzene		
FUGDHT	DHT Fugitives (4)	Benzene		
FUGDISP	DISP Fugitive	Benzene		
FUGDOCK	Dock Fugitives (4)	Benzene		
FUGDU1	DU1 Fugitives (4)	Benzene		
FUGDU2	DU2 Fugitives (4)	Benzene		
FUGDU2B	DU3 Fugitives (4)	Benzene		
FUGENVN	Environmental North Fugitives (4)	Benzene		
FUGGFRAC	GFRAC Fugitives (4)	Benzene		
FUGGOHT	GOHT Fugitives (4)	Benzene		
FUGGR	GR Fugitives (4)	Benzene		
FUGHDU1	HDU1 Fugitives (4)	Benzene		
FUGHP1	HP1 Fugitives (4)	Benzene		
FUGLHT2	LHT2 Fugitives (4)	Benzene		
FUGPLAT2	PLAT2 Fugitives (4)	Benzene		
FUGPSA	PSA Fugitives (4)	Benzene		
FUGSGP	SGP Fugitives (4)	Benzene		
FUGSHCU	SHCU Fugitives (4)	Benzene		
FUGTHCR	Thermal Cracking Fugitives (4)	Benzene		
G308	G308 Storage Tank	Benzene		
G309	G309 Storage Tank	Benzene		
G310	G310 Storage Tank	Benzene		
G311	G311 Storage Tank	Benzene		
G313	G313 Storage Tank	Benzene		
G315	G315 Storage Tank	Benzene		
G316	G316 Storage Tank	Benzene		
G320	G320 Storage Tank	Benzene		
G322	G322 Storage Tank	Benzene		
G323	G323 Storage Tank	Benzene		
G326	G326 Storage Tank	Benzene		
G327	G327 Storage Tank	Benzene		
G328	G328 Storage Tank	Benzene		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
G329	G329 Storage Tank	Benzene		
G332	G332 Storage Tank	Benzene		
G342	G342 Storage Tank	Benzene		
G346	G346 Storage Tank	Benzene		
G348	G348 Storage Tank	Benzene		
G355	G355 Storage Tank	Benzene		
G356	G356 Storage Tank	Benzene		
G357	G357 Storage Tank	Benzene		
G358	G358 Storage Tank	Benzene		
G360	G360 Storage Tank	Benzene		
GIRBOTWW	WW Collection in Girbitol	Benzene		
HVIOWS	WW - Sewer HVI Oily Water	Benzene		
J303B	J303B Storage Tank	Benzene		
J304	J304 Storage Tank	Benzene		
J308	J308 Storage Tank	Benzene		
J309	J309 Storage Tank	Benzene		
J311	J311 Storage Tank	Benzene		
J312	J312 Storage Tank	Benzene		
J315	J315 Storage Tank	Benzene		
J316	J316 Storage Tank	Benzene		
J317	J317 Storage Tank	Benzene		
J320	J320 Storage Tank	Benzene		
J322	J322 Storage Tank	Benzene		
J323	J323 Storage Tank	Benzene		
J324	J324 Storage Tank	Benzene		
J326	J326 Storage Tank	Benzene		
J327	J327 Storage Tank	Benzene		
J328	J328 Storage Tank	Benzene		
J336	J336 Storage Tank	Benzene		
J337	J337 Storage Tank	Benzene		
J338	J338 Storage Tank	Benzene		
J348	J348 Storage Tank	Benzene		
J349	J349 Storage Tank	Benzene		
K303	K303 Storage Tank	Benzene		
K304	K304 Storage Tank	Benzene		
LEUOWS	WW - Sewer LEU Oily Water	Benzene		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
LHT1OWS	WW - Sewer LHT1 Oily Water	Benzene		
LHT2OWS	WW - Sewer LHT2 Oily Water	Benzene		
LOADOWS	WW - Sewer Loading Racks	Benzene		
MANHOLE4	WW - Manhole 4	Benzene		
MVIDEASS	WW - Sewer DEA	Benzene		
MVIOWS	WW - Sewer MVI Oily Water	Benzene		
NAB	North Aeration Basin	Benzene		
NDAF	WW - North DAF Unit	Benzene		
OWATCTF	WW - Alky Tank Farm Oily Water	Benzene		
OWDU1	WW - Sewer Oily Water HUB	Benzene		
S412	S412 Storage Tank	Benzene		
SAB	South Aeration Basin	Benzene		
SDAF	WW - South DAF Unit	Benzene		
SR3/4WW	SR3/4 Wastewater Collection	Benzene		
SS376	SS376 Storage Tank	Benzene		
SS377	SS377 Storage Tank	Benzene		
SS378	SS378 Storage Tank	Benzene		
SS379	SS379 Storage Tank	Benzene		
SS403	SS403 Storage Tank	Benzene		
T1F323	T1F323 Storage Tank	Benzene		
T1F324	T1F324 Storage Tank	Benzene		
T1F329	T1F329 Storage Tank	Benzene		
T1F330	T1F330 Storage Tank	Benzene		
T301	T301 Storage Tank	Benzene		
T302	T302 EXTFLT Refinery WW Storage Tank	Benzene		
TA301	TA301 Storage Tank	Benzene		
TA305	TA305 Storage Tank	Benzene		
TA306	TA306 Storage Tank	Benzene		
TA307	TA307 Storage Tank	Benzene		
TA308	TA308 Storage Tank	Benzene		
TA309	TA309 Storage Tank	Benzene		
TA310	TA310 Storage Tank	Benzene		
TA312	TA312 Storage Tank	Benzene		
TA313	age Tank	Benzene		
TA315	TA315 Storage Tank	Benzene		
TA316	TA316 Storage Tank	Benzene		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
TA317	TA317 Storage Tank	Benzene		
TA318	TA318 Storage Tank	Benzene		
TA319	TA319 Storage Tank	Benzene		
TA320	TA320 Storage Tank	Benzene		
TA321	TA321 Storage Tank	Benzene		
TA322	TA322 Storage Tank	Benzene		
TA324	TA324 Storage Tank	Benzene		
TA325	TA325 Storage Tank	Benzene		
TA326	TA326 Storage Tank	Benzene		
TA329	TA329 Storage Tank	Benzene		
TA330	TA330 Storage Tank	Benzene		
TA331	TA331 Storage Tank	Benzene		
TA332	TA332 Storage Tank	Benzene		
TA334	TA334 Storage Tank	Benzene		
TC and G	WW - Thermal Cracking and Gas Treating	Benzene		
TG324	TG324 Storage Tank	Benzene		
TG362	TG362 Storage Tank	Benzene		
TJ333	TJ333 Storage Tank	Benzene		
TJ334	TJ334 Storage Tank	Benzene		
TJ335	TJ335 Storage Tank	Benzene		
TJ339R1	TJ339R1 Storage Tank	Benzene		
TK305	TK305 Storage Tank	Benzene		
TRKLFIL	WW - Trickle Filter	Benzene		
TRKLSMP	WW - Trickle Sump	Benzene		
WAXPTOWS	WW - Sewer Wax Plant Oily Water	Benzene		
WAXPTWAX	WW - Sewer Wax Plant Wax	Benzene		
X311	INTFLT/Amine Solutions Storage Tank	Benzene		
X312	INTFLT/Amine Solutions Storage Tank	Benzene		
X313	INTFLT/Slop Oil Storage Tank	Benzene		
X315	Ballast Water Storage Tank	Benzene		
X316	WW - DAF Float	Benzene		
X320	Ballast Water O/S Storage Tank	Benzene		
X321	Slop Oil Storage Tank	Benzene		
X322	X322 Storage Tank	Benzene		
X323	X323 Storage Tank	Benzene		
X324	FXTNK2/Misc Organic Storage Tank	Benzene		



## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
X325	FXTNK2/Misc Organic Storage Tank	Benzene		
X326	FXTNK2/DAF Float Storage Tank	Benzene		
X327	FXTNK2/DAF Float Storage Tank	Benzene		
X328	FXTNK2/Misc Organic Storage Tank	Benzene		
X330	WW - Equalization Tank	Benzene		
X330SM	WW - Sump	Benzene		
	<b>FINAL EMISSIONS CAP</b>	Benzene	10.96	30.36
A1006	H <sub>2</sub> S 4 Point Analyzer	CO		
A10823	CCU CO Analyzer	CO		
A10824	CO Analyzer	CO		
A10825	O <sub>2</sub> Analyzer	CO		
A10502	CCU SNCR NO <sub>x</sub> /SO <sub>2</sub> /O <sub>2</sub> Analyzer	CO		
A162	H5301 O <sub>2</sub> Analyzer	CO		
A180	H5302 O <sub>2</sub> Analyzer	CO		
A236	H5305 O <sub>2</sub> Analyzer	CO		
A34160	CR-3 Furnaces CEMS Analyzer	CO		
A785	H5303 O <sub>2</sub> Analyzer	CO		
A786	H5304 O <sub>2</sub> Analyzer	CO		
AE2340	Octane Testing Engine	CO		
AE2636	Octane Testing Engine	CO		
AE2650	Octane Testing Engine	CO		
AE348	On-line Knock Engine	CO		
AE349	On-line Knock Engine	CO		
AE388	On-line Knock Engine	CO		
AE389	On-line Knock Engine	CO		
AE700	Octane Testing Engine	CO		
AE768	Octane Testing Engine	CO		
FLARECCU	CCU Flare	CO		
FLARECOKE	Coker Flare	CO		
FLAREEP	East Property Flare	CO		
FLAREGIRB	EP (Girbitol) Flare	CO		
FLARELHT	LHT Flare	CO		
FLARENP	North Property Flare	CO		
FLARESOUTH	South Property Flare	CO		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
FLAREWP	West Property Flare	CO		
H1000	PLAT2 Heater	CO		
H1001	Guard Bed Start-up Heater	CO		
H1010	HDU-1 Charge Heater	CO		
H1011	HDU-1 Reboiler Heater	CO		
H1100	DHT Heater	CO		
H1170	CFH Charge Heater	CO		
H31001/2	Coker Heaters No. 1 and 2	CO		
H31003	Coker Heater No. 3	CO		
H3300	DHT H <sub>2</sub> Heater	CO		
H36100	CGHT Heater	CO		
H5100	DU-2 South Crude Heater	CO		
H5101	DU-2 North Crude Heater	CO		
H5102	DU-2 South Flasher Charge Heater	CO		
H5103	DU-2 North Flasher Charge Heater	CO		
H5104	DU-2 Preflash Heater	CO		
H5105	DU-2 Preflash2 Heater	CO		
H5200	HDU-2 Charge Heater	CO		
H53NN	Catalytic Reformer SCR	CO		
H5400	SHCU South Charge Heater	CO		
H5402	SHCU Reboiler Heater	CO		
H5403	SHCU North Charge Heater	CO		
H5404	SHCU Post-Frac Heater	CO		
H5500A	SMR Heater A	CO		
H5500B	SMR Heater B	CO		
H5500C	SMR Heater C	CO		
H5600	SGP Heat Medium Heater	CO		
H600	FCCU CO Boiler	CO		
H613	DU-1 Secondary Pre-Heater	CO		
H63000	HVI Column Charge Heater	CO		
H70001/2	GOHT Recycle Gas and Frac. Reboiler Heaters	CO		
H850S1	PERC Heater - North Stack	CO		
H850S2	PERC Heater - South Stack	CO		
H9150R1	Heater	CO		
SR3/4STACK	SR-3/4 Incinerator	CO		
SR5STACK	SR5 Tail Gas Incinerator	CO		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
SR6STACK	SR6 Tail Gas Incinerator	CO		
SR7STACK	SR7 Tail Gas Incinerator	CO		
SR8STACK	SR8 Tail Gas Incinerator	CO		
	<b>FINAL EMISSIONS CAP</b>	CO	1124.15	4204.57
A1284	Debut. Tops Analyzer	H <sub>2</sub> S		
A1760	H <sub>2</sub> S Analyzer	H <sub>2</sub> S		
AP16	Storage Tank	H <sub>2</sub> S		
AP17	Storage Tank	H <sub>2</sub> S		
BARGE	Marine Loading - Barge Docks	H <sub>2</sub> S		
BENZENE1	Marine Loading - Benzene Dock 1	H <sub>2</sub> S		
BENZENE2	Marine Loading - Benzene Dock 2	H <sub>2</sub> S		
BENZENE4	Marine Loading - Benzene Dock 4	H <sub>2</sub> S		
BYARDOWS	WW - Sewer B Yard Oily Water	H <sub>2</sub> S		
C9150/51	C9150/51 Vent	H <sub>2</sub> S		
C9152/53	C9152/53 Vent	H <sub>2</sub> S		
CRUDE	Marine Loading - Crude Docks	H <sub>2</sub> S		
DOCK1	Marine Loading - Dock 1	H <sub>2</sub> S		
DOCK2	Marine Loading - Dock 2	H <sub>2</sub> S		
DOCK4	Marine Loading - Dock 4	H <sub>2</sub> S		
F338	F338 Storage Tank	H <sub>2</sub> S		
FLARECCU	CCU Flare	H <sub>2</sub> S		
FLARECOKE	Coker Flare	H <sub>2</sub> S		
FLAREEP	East Property Flare	H <sub>2</sub> S		
FLAREGIRB	EP (Girbitol) Flare	H <sub>2</sub> S		
FLARELHT	LHT Flare	H <sub>2</sub> S		
FLARENP	North Property Flare	H <sub>2</sub> S		
FLARESOUTH	South Property Flare	H <sub>2</sub> S		
FLAREWP	West Property Flare	H <sub>2</sub> S		
FUGALKY	Alky Fugitives (4)	H <sub>2</sub> S		
FUGAYARD	Fugitives (4)	H <sub>2</sub> S		
FUGCCU	FCCU Fugitives (4)	H <sub>2</sub> S		
FUGCFH	CFH Fugitives (4)	H <sub>2</sub> S		
FUGCOKER	Coke Handling Fugitives (4)	H <sub>2</sub> S		
FUGCPU	CPU Fugitives (4)	H <sub>2</sub> S		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
FUGCR3	CR3 Fugitives (4)	H <sub>2</sub> S		
FUGCR3TF	Hydroprocessing Tank Farm Fugitives (4)	H <sub>2</sub> S		
FUGDHT	DHT Fugitives (4)	H <sub>2</sub> S		
FUGDISP	DISP Fugitive	H <sub>2</sub> S		
FUGDU1	DU1 Fugitives (4)	H <sub>2</sub> S		
FUGDU2	DU2 Fugitives (4)	H <sub>2</sub> S		
FUGGFRAC	GFRAC Fugitives (4)	H <sub>2</sub> S		
FUGGIRBIT	Girbitol Fugitives (4)	H <sub>2</sub> S		
FUGGOHT	GOHT Fugitives (4)	H <sub>2</sub> S		
FUGGR	GR Fugitives (4)	H <sub>2</sub> S		
FUGHDU1	DU1 Fugitives (4)	H <sub>2</sub> S		
FUGHP1	HP1 Fugitives (4)	H <sub>2</sub> S		
FUGLHT2	LHT2 Fugitives (4)	H <sub>2</sub> S		
FUGPLAT2	PLAT2 Fugitives (4)	H <sub>2</sub> S		
FUGSGP	SGP Fugitives (4)	H <sub>2</sub> S		
FUGSHCU	SHCU Fugitives (4)	H <sub>2</sub> S		
FUGSR5	SR5 Fugitives (4)	H <sub>2</sub> S		
FUGSR6	SR6 Fugitives (4)	H <sub>2</sub> S		
FUGSR7	SR7 Fugitives (4)	H <sub>2</sub> S		
FUGSR8	SR8 Fugitives (4)	H <sub>2</sub> S		
FUGTHCR	Thermal Cracking Fugitives (4)	H <sub>2</sub> S		
G332	G332 Storage Tank	H <sub>2</sub> S		
J317	J317 Storage Tank	H <sub>2</sub> S		
J318B	J318B Storage Tank	H <sub>2</sub> S		
J325	J325 Storage Tank	H <sub>2</sub> S		
J326	J326 Storage Tank	H <sub>2</sub> S		
J327	J327 Storage Tank	H <sub>2</sub> S		
J328	J328 Storage Tank	H <sub>2</sub> S		
J331	J331 Storage Tank	H <sub>2</sub> S		
J332	J332 Storage Tank	H <sub>2</sub> S		
J348	J348 Storage Tank	H <sub>2</sub> S		
J349	J349 Storage Tank	H <sub>2</sub> S		
L2COMPVT	L2COMPVT Vent	H <sub>2</sub> S		
LDSULF67	SR6 and SR7 Loading Rack	H <sub>2</sub> S		
LHT1OWS	WW - Sewer LHT1 Oily Water	H <sub>2</sub> S		
LHT2OWS	WW - Sewer LHT2 Oily Water	H <sub>2</sub> S		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
MVIDEASS	WW - Sewer DEA	H <sub>2</sub> S		
RKLTC/TT	Load	H <sub>2</sub> S		
S429	S429 Storage Tank	H <sub>2</sub> S		
SR3/4PIT	SR3/4 Sulfur Pit	H <sub>2</sub> S		
SR3/4STACK	SR-3/4 Incinerator	H <sub>2</sub> S		
SR5L01	SR5 Loading Rack	H <sub>2</sub> S		
SR5L02	SR5 Loading Rack	H <sub>2</sub> S		
SR5STACK	SR5 Tail Gas Incinerator	H <sub>2</sub> S		
SR6STACK	SR6 Tail Gas Incinerator	H <sub>2</sub> S		
SR7STACK	SR7 Tail Gas Incinerator	H <sub>2</sub> S		
SR8STACK	SR8 Tail Gas Incinerator	H <sub>2</sub> S		
SRTT	SR3/4 Loading Rack	H <sub>2</sub> S		
SS343	SS343 Storage Tank	H <sub>2</sub> S		
SULFUR	SR5 Sulfur Pit	H <sub>2</sub> S		
TA301	TA301 Storage Tank	H <sub>2</sub> S		
TA305	TA305 Storage Tank	H <sub>2</sub> S		
TA306	TA306 Storage Tank	H <sub>2</sub> S		
TA307	TA307 Storage Tank	H <sub>2</sub> S		
TA310	TA310 Storage Tank	H <sub>2</sub> S		
TA312	TA312 Storage Tank	H <sub>2</sub> S		
TA313	TA313 Storage Tank	H <sub>2</sub> S		
TA315	TA315 Storage Tank	H <sub>2</sub> S		
TA316	TA316 Storage Tank	H <sub>2</sub> S		
TA317	TA317 Storage Tank	H <sub>2</sub> S		
TA318	TA318 Storage Tank	H <sub>2</sub> S		
TA319	TA319 Storage Tank	H <sub>2</sub> S		
TA320	TA320 Storage Tank	H <sub>2</sub> S		
TA321	TA321 Storage Tank	H <sub>2</sub> S		
TA322	TA322 Storage Tank	H <sub>2</sub> S		
TA324	TA324 Storage Tank	H <sub>2</sub> S		
TA325	TA325 Storage Tank	H <sub>2</sub> S		
TA326	TA326 Storage Tank	H <sub>2</sub> S		
TA329	TA329 Storage Tank	H <sub>2</sub> S		
TA330	TA330 Storage Tank	H <sub>2</sub> S		
TA331	TA331 Storage Tank	H <sub>2</sub> S		
TA332	TA332 Storage Tank	H <sub>2</sub> S		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
TA334	TA334 Storage Tank	H <sub>2</sub> S		
TG324	TG324 Storage Tank	H <sub>2</sub> S		
TG362	TG362 Storage Tank	H <sub>2</sub> S		
TJ339R1	TJ339R1 Storage Tank	H <sub>2</sub> S		
TSR67	Molten Sulfur Tank	H <sub>2</sub> S		
VA03	VA03 Storage Tank	H <sub>2</sub> S		
VA04	VA04 Storage Tank	H <sub>2</sub> S		
X313	INTFLT/Slop Oil Storage Tank	H <sub>2</sub> S		

**FINAL EMISSIONS CAP**H<sub>2</sub>S

29.61

85.77

AYARDOWS	WW - Sewer A Yard Oily Water	NH <sub>3</sub>
BYARDOWS	WW - Sewer B Yard Oily Water	NH <sub>3</sub>
CCLP	WW - Cat Cracker Lube Plant	NH <sub>3</sub>
CPI1	WW- CPI Oil Water Separator	NH <sub>3</sub>
CPI2	WW- CPI Oil Water Separator	NH <sub>3</sub>
CYARDOWS	Wastewater Fugitives (4)	NH <sub>3</sub>
DAOWS	WW - Sewer DA Oily Water	NH <sub>3</sub>
DD2	WW - Dispatching Distilling 2	NH <sub>3</sub>
DOCKS	Dock Wastewater Collection	NH <sub>3</sub>
DYARDOWS	WW - Sewer D Yard Oily Water	NH <sub>3</sub>
FUGCCU	FCCU Fugitives (4)	NH <sub>3</sub>
FUGCCUSCR	FCCU SCR Fugitives (4)	NH <sub>3</sub>
FUGCOKER	Coke Handling Fugitives (4)	NH <sub>3</sub>
FUGCR3SCR	CR3 SCR Fugitives (4)	NH <sub>3</sub>
FUGDHT	DHT Fugitives (4)	NH <sub>3</sub>
FUGDISP	DISP Fugitive	NH <sub>3</sub>
FUGDOCK	Dock Fugitives (4)	NH <sub>3</sub>
FUGDU2	DU2 Fugitives (4)	NH <sub>3</sub>
FUGHDU1	DU1 Fugitives (4)	NH <sub>3</sub>
FUGSR6	SR6 Fugitives (4)	NH <sub>3</sub>
FUGSR7	SR7 Fugitives (4)	NH <sub>3</sub>
FUGSR8	SR8 Fugitives (4)	NH <sub>3</sub>
GIRBOTWW	WW Collection in Girbitol	NH <sub>3</sub>
H53NN	Catalytic Reformer SCR	NH <sub>3</sub>
H600	FCCU CO Boiler	NH <sub>3</sub>

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
HVIEWS	WW - Sewer HVI Oily Water	NH <sub>3</sub>		
J318B	J318B Storage Tank	NH <sub>3</sub>		
LEUOWS	WW - Sewer LEU Oily Water	NH <sub>3</sub>		
LHT1OWS	WW - Sewer LHT1 Oily Water	NH <sub>3</sub>		
LHT2OWS	WW - Sewer LHT2 Oily Water	NH <sub>3</sub>		
LOADOWS	WW - Sewer Loading Racks	NH <sub>3</sub>		
MANHOLE4	WW - Manhole 4	NH <sub>3</sub>		
MVIDEASS	WW - Sewer DEA	NH <sub>3</sub>		
MVIEWS	WW - Sewer MVI Oily Water	NH <sub>3</sub>		
NAB	North Aeration Basin	NH <sub>3</sub>		
NDAF	WW - North DAF Unit	NH <sub>3</sub>		
OWDU1	WW - Sewer Oily Water HUB	NH <sub>3</sub>		
S429	S429 Storage Tank	NH <sub>3</sub>		
SAB	South Aeration Basin	NH <sub>3</sub>		
SDAF	WW - South DAF Unit	NH <sub>3</sub>		
SR3/4WW	SR3/4 Wastewater Collection	NH <sub>3</sub>		
T301	T301 Storage Tank	NH <sub>3</sub>		
T302	T302 EXTFLT Refinery WW Storage Tank	NH <sub>3</sub>		
TC and G	WW - Thermal Cracking and Gas Treating	NH <sub>3</sub>		
TRKLFIL	WW - Trickle Filter	NH <sub>3</sub>		
TRKLSMP	WW - Trickle Sump	NH <sub>3</sub>		
WAXPTOWS	WW - Sewer Wax Plant Oily Water	NH <sub>3</sub>		
WAXPTWAX	WW - Sewer Wax Plant Wax	NH <sub>3</sub>		
X311	INTFLT/Amine Solutions Storage Tank	NH <sub>3</sub>		
X312	INTFLT/Amine Solutions Storage Tank	NH <sub>3</sub>		
X316	WW - DAF Float	NH <sub>3</sub>		
X330	WW - Equalization Tank	NH <sub>3</sub>		
X330SM	WW - Sump	NH <sub>3</sub>		
	<b>FINAL EMISSIONS CAP</b>	NH <sub>3</sub>	10.69	46.76
A10823	CCU CO Analyzer	NO <sub>x</sub>		
A10824	CO Analyzer	NO <sub>x</sub>		
A10825	O <sub>2</sub> Analyzer	NO <sub>x</sub>		
A10502	CCU SNCR NO <sub>x</sub> /SO <sub>2</sub> /O <sub>2</sub> Analyzer	NO <sub>x</sub>		
A162	H5301 O <sub>2</sub> Analyzer	NO <sub>x</sub>		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
A180	H5302 O <sub>2</sub> Analyzer	NO <sub>x</sub>		
A236	H5305 O <sub>2</sub> Analyzer	NO <sub>x</sub>		
A34160	CR-3 Furnaces CEMS Analyzer	NO <sub>x</sub>		
A785	H5303 O <sub>2</sub> Analyzer	NO <sub>x</sub>		
A786	H5304 O <sub>2</sub> Analyzer	NO <sub>x</sub>		
AE2340	Octane Testing Engine	NO <sub>x</sub>		
AE2636	Octane Testing Engine	NO <sub>x</sub>		
AE2650	Octane Testing Engine	NO <sub>x</sub>		
AE348	On-line Knock Engine	NO <sub>x</sub>		
AE349	On-line Knock Engine	NO <sub>x</sub>		
AE388	On-line Knock Engine	NO <sub>x</sub>		
AE389	On-line Knock Engine	NO <sub>x</sub>		
AE700	Octane Testing Engine	NO <sub>x</sub>		
AE768	Octane Testing Engine	NO <sub>x</sub>		
FLARECCU	CCU Flare	NO <sub>x</sub>		
FLARECOKE	Coker Flare	NO <sub>x</sub>		
FLAREEP	East Property Flare	NO <sub>x</sub>		
FLAREGIRB	EP (Girbitol) Flare	NO <sub>x</sub>		
FLARELHT	LHT Flare	NO <sub>x</sub>		
FLARENP	North Property Flare	NO <sub>x</sub>		
FLARESOUTH	South Property Flare	NO <sub>x</sub>		
FLAREWP	West Property Flare	NO <sub>x</sub>		
H1000	PLAT2 Heater	NO <sub>x</sub>		
H1001	Guard Bed Start-up Heater	NO <sub>x</sub>		
H1010	HDU-1 Charge Heater	NO <sub>x</sub>		
H1011	HDU-1 Reboiler Heater	NO <sub>x</sub>		
H1100	DHT Heater	NO <sub>x</sub>		
H1170	CFH Charge Heater	NO <sub>x</sub>		
H31001/2	Coker Heaters No. 1 and 2	NO <sub>x</sub>		
H31003	Coker Heater No. 3	NO <sub>x</sub>		
H3300	DHT H <sub>2</sub> Heater	NO <sub>x</sub>		
H36100	CGHT Heater	NO <sub>x</sub>		
H5100	DU-2 South Crude Heater	NO <sub>x</sub>		
H5101	DU-2 North Crude Heater	NO <sub>x</sub>		
H5102	DU-2 South Flasher Charge Heater	NO <sub>x</sub>		
H5103	DU-2 North Flasher Charge Heater	NO <sub>x</sub>		



## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
H5104	DU-2 Preflash Heater	NO <sub>x</sub>		
H5105	DU-2 Preflash2 Heater	NO <sub>x</sub>		
H5200	HDU-2 Charge Heater	NO <sub>x</sub>		
H53NN	Catalytic Reformer SCR	NO <sub>x</sub>		
H5400	SHCU South Charge Heater	NO <sub>x</sub>		
H5402	SHCU Reboiler Heater	NO <sub>x</sub>		
H5403	SHCU North Charge Heater	NO <sub>x</sub>		
H5404	SHCU Post-Frac Heater	NO <sub>x</sub>		
H5500A	SMR Heater A	NO <sub>x</sub>		
H5500B	SMR Heater B	NO <sub>x</sub>		
H5500C	SMR Heater C	NO <sub>x</sub>		
H5600	SGP Heat Medium Heater	NO <sub>x</sub>		
H600	FCCU CO Boiler	NO <sub>x</sub>		
H613	DU-1 Secondary Pre-Heater	NO <sub>x</sub>		
H63000	HVI Column Charge Heater	NO <sub>x</sub>		
H70001/2	GOHT Recycle Gas and Frac. Reboiler Heaters	NO <sub>x</sub>		
H850S1	PERC Heater - North Stack	NO <sub>x</sub>		
H850S2	PERC Heater - South Stack	NO <sub>x</sub>		
H9150R1	Heater	NO <sub>x</sub>		
SR3/4STACK	SR-3/4 Incinerator	NO <sub>x</sub>		
SR5STACK	SR5 Tail Gas Incinerator	NO <sub>x</sub>		
SR6STACK	SR6 Tail Gas Incinerator	NO <sub>x</sub>		
SR7STACK	SR7 Tail Gas Incinerator	NO <sub>x</sub>		
SR8STACK	SR8 Tail Gas Incinerator	NO <sub>x</sub>		

**FINAL EMISSIONS CAP**NO<sub>x</sub>

552.33

1949.56

A10823	CCU CO Analyzer	PM
A10824	CO Analyzer	PM
A10825	O <sub>2</sub> Analyzer	PM
A10502	CCU SNCR NO <sub>x</sub> /SO <sub>2</sub> /O <sub>2</sub> Analyzer	PM
A162	H5301 O <sub>2</sub> Analyzer	PM
A180	H5302 O <sub>2</sub> Analyzer	PM
A236	H5305 O <sub>2</sub> Analyzer	PM
A34160	CR-3 Furnaces CEMS Analyzer	PM

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
A785	H5303 O <sub>2</sub> Analyzer	PM		
A786	H5304 O <sub>2</sub> Analyzer	PM		
AE2340	Octane Testing Engine	PM		
AE2636	Octane Testing Engine	PM		
AE2650	Octane Testing Engine	PM		
AE348	On-line Knock Engine	PM		
AE349	On-line Knock Engine	PM		
AE388	On-line Knock Engine	PM		
AE389	On-line Knock Engine	PM		
AE700	Octane Testing Engine	PM		
AE768	Octane Testing Engine	PM		
CWT10	Cooling Tower No.10 (4)	PM		
CWT11	Cooling Tower No.11 (4)	PM		
CWT12	Cooling Tower No.12 (4)	PM		
CWT14	Cooling Tower No.14 (4)	PM		
CWT15	Cooling Tower No.15 (4)	PM		
CWT16/16A	Cooling Tower No.16/16A (4)	PM		
CWT17	Cooling Tower No.17 (4)	PM		
CWT6	Cooling Tower No.6 (4)	PM		
CWT7	Cooling Tower No.7 (4)	PM		
CWT8	Cooling Tower No.8 (4)	PM		
CWT9	Cooling Tower No.9 (4)	PM		
FUGCOKEPM1	Coke Pile Wind Erosion Fugitives (4)	PM		
FUGCOKEPM1A	Coke Pile 2 Fugitives (4)	PM		
FUGCOKEPM2	Coke Pile Crane Fugitives (4)	PM		
FUGCOKEPM3	Coke Crusher Fugitives (4)	PM		
FUGCOKEPM4	Coke Crusher Discharge Fugitives (4)	PM		
FUGCOKEPM5	Coke Transfer Conveyor Fugitives (4)	PM		
FUGCOKEPM6	Coke Conveyor Discharge Fugitives (4)	PM		
FUGCOKEPM7	Coke Barge Loading Fugitives (4)	PM		
H1000	PLAT2 Heater	PM		
H1001	Guard Bed Start-up Heater	PM		
H1010	HDU-1 Charge Heater	PM		
H1011	HDU-1 Reboiler Heater	PM		
H1100	DHT Heater	PM		
H1170	CFH Charge Heater	PM		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
H31001/2	Coker Heaters No. 1 and 2	PM		
H31003	Coker Heater No. 3	PM		
H3300	DHT H <sub>2</sub> Heater	PM		
H36100	CGHT Heater	PM		
H5100	DU-2 South Crude Heater	PM		
H5101	DU-2 North Crude Heater	PM		
H5102	DU-2 South Flasher Charge Heater	PM		
H5103	DU-2 North Flasher Charge Heater	PM		
H5104	DU-2 Preflash Heater	PM		
H5105	DU-2 Preflash2 Heater	PM		
H5200	HDU-2 Charge Heater	PM		
H53NN	Catalytic Reformer SCR	PM		
H5400	SHCU South Charge Heater	PM		
H5402	SHCU Reboiler Heater	PM		
H5403	SHCU North Charge Heater	PM		
H5404	SHCU Post-Frac Heater	PM		
H5500A	SMR Heater A	PM		
H5500B	SMR Heater B	PM		
H5500C	SMR Heater C	PM		
H5600	SGP Heat Medium Heater	PM		
H600	FCCU CO Boiler	PM		
H613	DU-1 Secondary Pre-Heater	PM		
H63000	HVI Column Charge Heater	PM		
H70001/2	GOHT Recycle Gas and Frac. Reboiler Heaters	PM		
H850S1	PERC Heater - North Stack	PM		
H850S2	PERC Heater - South Stack	PM		
H9150R1	Heater	PM		
PAINTFE	Miscellaneous Painting Fugitives	PM		
SR3/4STACK	SR-3/4 Incinerator	PM		
SR5STACK	SR5 Tail Gas Incinerator	PM		
SR6STACK	SR6 Tail Gas Incinerator	PM		
SR7STACK	SR7 Tail Gas Incinerator	PM		
SR8STACK	SR8 Tail Gas Incinerator	PM		
<b>FINAL EMISSIONS CAP</b>		PM	143.13	561.88

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
A1745	SR-3/4 SO <sub>2</sub> CEMS Analyzer	SO <sub>2</sub>		
A10823	CCU CO Analyzer	SO <sub>2</sub>		
A10824	CO Analyzer	SO <sub>2</sub>		
A10825	O <sub>2</sub> Analyzer	SO <sub>2</sub>		
A10502	CCU SNCR NO <sub>x</sub> /SO <sub>2</sub> /O <sub>2</sub> Analyzer	SO <sub>2</sub>		
A162	H5301 O <sub>2</sub> Analyzer	SO <sub>2</sub>		
A180	H5302 O <sub>2</sub> Analyzer	SO <sub>2</sub>		
A236	H5305 O <sub>2</sub> Analyzer	SO <sub>2</sub>		
A34160	CR-3 Furnaces CEMS Analyzer	SO <sub>2</sub>		
A785	H5303 O <sub>2</sub> Analyzer	SO <sub>2</sub>		
A786	H5304 O <sub>2</sub> Analyzer	SO <sub>2</sub>		
AE2340	Octane Testing Engine	SO <sub>2</sub>		
AE2636	Octane Testing Engine	SO <sub>2</sub>		
AE2650	Octane Testing Engine	SO <sub>2</sub>		
AE348	On-line Knock Engine	SO <sub>2</sub>		
AE349	On-line Knock Engine	SO <sub>2</sub>		
AE388	On-line Knock Engine	SO <sub>2</sub>		
AE389	On-line Knock Engine	SO <sub>2</sub>		
AE700	Octane Testing Engine	SO <sub>2</sub>		
AE768	Octane Testing Engine	SO <sub>2</sub>		
FLARECCU	CCU Flare	SO <sub>2</sub>		
FLARECOKE	Coker Flare	SO <sub>2</sub>		
FLAREEP	East Property Flare	SO <sub>2</sub>		
FLAREGIRB	EP (Girbitol) Flare	SO <sub>2</sub>		
FLARELHT	LHT Flare	SO <sub>2</sub>		
FLARENP	North Property Flare	SO <sub>2</sub>		
FLARESOUTH	South Property Flare	SO <sub>2</sub>		
FLAREWP	West Property Flare	SO <sub>2</sub>		
H1000	PLAT2 Heater	SO <sub>2</sub>		
H1001	Guard Bed Start-up Heater	SO <sub>2</sub>		
H1010	HDU-1 Charge Heater	SO <sub>2</sub>		
H1011	HDU-1 Reboiler Heater	SO <sub>2</sub>		
H1100	DHT Heater	SO <sub>2</sub>		
H1170	CFH Charge Heater	SO <sub>2</sub>		
H31001/2	Coker Heaters No. 1 and 2	SO <sub>2</sub>		
H31003	Coker Heater No. 3	SO <sub>2</sub>		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
H3300	DHT H <sub>2</sub> Heater	SO <sub>2</sub>		
H36100	CGHT Heater	SO <sub>2</sub>		
H5100	DU-2 South Crude Heater	SO <sub>2</sub>		
H5101	DU-2 North Crude Heater	SO <sub>2</sub>		
H5102	DU-2 South Flasher Charge Heater	SO <sub>2</sub>		
H5103	DU-2 North Flasher Charge Heater	SO <sub>2</sub>		
H5104	DU-2 Preflash Heater	SO <sub>2</sub>		
H5105	DU-2 Preflash2 Heater	SO <sub>2</sub>		
H5200	HCU-2 Charge Heater	SO <sub>2</sub>		
H53NN	Catalytic Reformer SCR	SO <sub>2</sub>		
H5400	SHCU South Charge Heater	SO <sub>2</sub>		
H5402	SHCU Reboiler Heater	SO <sub>2</sub>		
H5403	SHCU North Charge Heater	SO <sub>2</sub>		
H5404	SHCU Post-Frac Heater	SO <sub>2</sub>		
H5500A	SMR Heater A	SO <sub>2</sub>		
H5500B	SMR Heater B	SO <sub>2</sub>		
H5500C	SMR Heater C	SO <sub>2</sub>		
H5600	SGP Heat Medium Heater	SO <sub>2</sub>		
H600	FCCU CO Boiler	SO <sub>2</sub>		
H613	DU-1 Secondary Pre-Heater	SO <sub>2</sub>		
H63000	HVI Column Charge Heater	SO <sub>2</sub>		
H70001/2	GOHT Recycle Gas and Frac.Reboiler Heaters	SO <sub>2</sub>		
H850S1	PERC Heater - North Stack	SO <sub>2</sub>		
H850S2	PERC Heater - South Stack	SO <sub>2</sub>		
H9150R1	Heater	SO <sub>2</sub>		
SR3/4STACK	SR-3/4 Incinerator	SO <sub>2</sub>		
SR5STACK	SR5 Tail Gas Incinerator	SO <sub>2</sub>		
SR6STACK	SR6 Tail Gas Incinerator	SO <sub>2</sub>		
SR7STACK	SR7 Tail Gas Incinerator	SO <sub>2</sub>		
SR8STACK	SR8 Tail Gas Incinerator	SO <sub>2</sub>		
	<b>FINAL EMISSIONS CAP</b>	SO <sub>2</sub>	2644.20	5476.46
A1006	H <sub>2</sub> S 4 Point Analyzer	VOC		
A102	Analyzer	VOC		
A1284	Analyzer	VOC		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
A1745	SR3/4 SO <sub>2</sub> CEMS Analyzer	VOC		
A1760	Analyzer	VOC		
A213	CR3 Recycle Gas SG Analyzer	VOC		
A214	CR3 Recycle Gas Moisture Analyzer	VOC		
A298	CR3 Regen Gas O <sub>2</sub> Analyzer	VOC		
A300	CR3 Regen Gas Comb. Analyzer	VOC		
A329	CR3 Reactor Inlet O <sub>2</sub> Analyzer	VOC		
A553	Plat2 Rec. Gas Moisture Analyzer	VOC		
A554	Plat2 Rec. Gas Gravity Analyzer	VOC		
A10823	CCU CO Analyzer	VOC		
A10824	CO Analyzer	VOC		
A10825	O <sub>2</sub> Analyzer	VOC		
A1301	PSA Product H <sub>2</sub> Analyzer	VOC		
A1905/6	A 1905/6 Analyzer	VOC		
A89128	Tank SS307 Blanket O <sub>2</sub> Analyzer	VOC		
A842	Tank SS314 Blanket O <sub>2</sub> Analyzer	VOC		
A10502	CCU SNCR NO <sub>x</sub> /SO <sub>2</sub> /O <sub>2</sub> Analyzer	VOC		
A162	H5301 O <sub>2</sub> Analyzer	VOC		
A180	H5302 O <sub>2</sub> Analyzer	VOC		
A236	H5305 O <sub>2</sub> Analyzer	VOC		
A34160	CR-3 Furnaces CEMS Analyzer	VOC		
A785	H5303 O <sub>2</sub> Analyzer	VOC		
A786	H5304 O <sub>2</sub> Analyzer	VOC		
AE2340	Octane Testing Engine	VOC		
AE2636	Octane Testing Engine	VOC		
AE2650	Octane Testing Engine	VOC		
AE348	On-line Knock Engine	VOC		
AE349	On-line Knock Engine	VOC		
AE388	On-line Knock Engine	VOC		
AE389	On-line Knock Engine	VOC		
AE700	Octane Testing Engine	VOC		
AE768	Octane Testing Engine	VOC		
AP1	AP1 Storage Tank	VOC		
AP16	AP16 Storage Tank	VOC		
AP17	AP17 Storage Tank	VOC		
AP2	AP2 Storage Tank	VOC		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
AP4	AP4 Storage Tank	VOC		
AP5	AP5 Storage Tank	VOC		
AP6	AP6 Storage Tank	VOC		
AP7	AP7 Storage Tank	VOC		
AP8	AP8 Storage Tank	VOC		
AYARDOWS	WW - Sewer A Yard Oily Water	VOC		
BARGE	Marine Loading - Barge Docks	VOC		
BENZENE1	Marine Loading - Benzene Dock 1	VOC		
BENZENE2	Marine Loading - Benzene Dock 2	VOC		
BENZENE4	Marine Loading - Benzene Dock 4	VOC		
BYARDOWS	WW - Sewer B Yard Oily Water	VOC		
C9150/51	C9150/51 Vent	VOC		
C9152/53	C9152/53 Vent	VOC		
CCLP	WW - Cat Cracker Lube Plant	VOC		
CPI1	WW- CPI Oil Water Separator	VOC		
CPI2	WW- CPI Oil Water Separator	VOC		
CRUDE	Marine Loading - Crude Docks	VOC		
CWT10	Cooling Tower No. 10 (4)	VOC		
CWT11	Cooling Tower No. 11 (4)	VOC		
CWT12	Cooling Tower No. 12 (4)	VOC		
CWT14	Cooling Tower No. 14 (4)	VOC		
CWT15	Cooling Tower No. 15 (4)	VOC		
CWT16/16A	Cooling Tower No. 16/16A (4)	VOC		
CWT17	Cooling Tower No. 17 (4)	VOC		
CWT6	Cooling Tower No. 6 (4)	VOC		
CWT7	Cooling Tower No. 7 (4)	VOC		
CWT8	Cooling Tower No. 8 (4)	VOC		
CWT9	Cooling Tower No. 9 (4)	VOC		
CYARDOWS	Wastewater Fugitives (4)	VOC		
D363	FTXNK2/ANTIICANT StorageTank	VOC		
DAOWS	WW - Sewer DA Oily Water	VOC		
DD2	WW - Dispatching Distilling 2	VOC		
DOCK1	Marine Loading - Dock 1	VOC		
DOCK2	Marine Loading - Dock 2	VOC		
DOCK4	Marine Loading - Dock 4	VOC		
DOCKS	Dock Wastewater Collection	VOC		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
DW103	DW103 Storage Tank	VOC		
DW104	DW104 Storage Tank	VOC		
DYARDOWS	WW - Sewer D Yard Oily Water	VOC		
F314	F314 Storage Tank	VOC		
F315	F315 Storage Tank	VOC		
F316	F316 Storage Tank	VOC		
F317	F317 Storage Tank	VOC		
F325	F325 Storage Tank	VOC		
F326	F326 Storage Tank	VOC		
F338	F338 Storage Tank	VOC		
F364	F364 Storage Tank	VOC		
F365	F365 Storage Tank	VOC		
F366	F366 Storage Tank	VOC		
F367	F367 Storage Tank	VOC		
FLARECCU	CCU Flare	VOC		
FLARECOKE	Coker Flare	VOC		
FLAREEP	East Property Flare	VOC		
FLAREGIRB	EP (Girbitol) Flare	VOC		
FLARELHT	LHT Flare	VOC		
FLARENP	North Property Flare	VOC		
FLARESOUTH	South Property Flare	VOC		
FLAREWP	West Property Flare	VOC		
FP182	FP182 Storage Tank	VOC		
FP190	FP190 Storage Tank	VOC		
FP194	FP194 Storage Tank	VOC		
FP195	FP195 Storage Tank	VOC		
FP200	FP200 Storage Tank	VOC		
FUGALKY	Alky Fugitives (4)	VOC		
FUGAYARD	Fugitives (4)	VOC		
FUGCCU	FCCU Fugitives (4)	VOC		
FUGCFH	CFH Fugitives (4)	VOC		
FUGCGHT	CGHT Fugitives (4)	VOC		
FUGCOKER	Coke Handling Fugitives (4)	VOC		
FUGCPU	CPU Fugitives (4)	VOC		
FUGCR3	CR3 Fugitives (4)	VOC		
FUGCR3TF	Hydroprocessing Tank Farm Fugitives (4)	VOC		



## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
FUGDHT	DHT Fugitives (4)	VOC		
FUGDISP	DISP Fugitive	VOC		
FUGDOCK	Dock Fugitives (4)	VOC		
FUGDU1	DU1 Fugitives (4)	VOC		
FUGDU2	DU2 Fugitives (4)	VOC		
FUGDU2B	DU3 Fugitives (4)	VOC		
FUGENVN	Environmental North Fugitives (4)	VOC		
FUGGASTR	GASTR Fugitives (4)	VOC		
FUGGFRAC	GFRAC Fugitives (4)	VOC		
FUGGIRBIT	Girbitol Fugitives (4)	VOC		
FUGGOHT	GOHT Fugitives (4)	VOC		
FUGGR	GR Fugitives (4)	VOC		
FUGGR200	GR200 Fugitives (4)	VOC		
FUGHDU1	HDU1 Fugitives (4)	VOC		
FUGHP1	HP1 Fugitives (4)	VOC		
FUGLHT2	LHT2 Fugitives (4)	VOC		
FUGMTBE	MTBE Fugitives (4)	VOC		
FUGPLAT2	PLAT2 Fugitives (4)	VOC		
FUGPOSTFRAC	POSTFRAC Fugitives (4)	VOC		
FUGPSA	PSA Fugitives (4)	VOC		
FUGSGP	SGP Fugitives (4)	VOC		
FUGSHCU	SHCU Fugitives (4)	VOC		
FUGSR3/4	SR3/4 Fugitives (4)	VOC		
FUGSR5	SR5 Fugitives (4)	VOC		
FUGSR6	SR6 Fugitives (4)	VOC		
FUGSR7	SR7 Fugitives (4)	VOC		
FUGSR8	SR8 Fugitives (4)	VOC		
FUGTHCR	Thermal Cracking Fugitives (4)	VOC		
FUGWBT	West Blend Tank Fugitives (4)	VOC		
G308	G308 Storage Tank	VOC		
G309	G309 Storage Tank	VOC		
G310	G310 Storage Tank	VOC		
G311	G311 Storage Tank	VOC		
G313	G313 Storage Tank	VOC		
G314	G314 Storage Tank	VOC		
G315	G315 Storage Tank	VOC		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
G316	G316 Storage Tank	VOC		
G317	G317 Storage Tank	VOC		
G319	G319 Storage Tank	VOC		
G320	G320 Storage Tank	VOC		
G322	G322 Storage Tank	VOC		
G323	G323 Storage Tank	VOC		
G326	G326 Storage Tank	VOC		
G327	G327 Storage Tank	VOC		
G328	G328 Storage Tank	VOC		
G329	G329 Storage Tank	VOC		
G332	G332 Storage Tank	VOC		
G342	G342 Storage Tank	VOC		
G345	G345 Storage Tank	VOC		
G346	G346 Storage Tank	VOC		
G347	G347 Storage Tank	VOC		
G348	G348 Storage Tank	VOC		
G352	G352 Storage Tank	VOC		
G354	G354 Storage Tank	VOC		
G355	G355 Storage Tank	VOC		
G356	G356 Storage Tank	VOC		
G357	G357 Storage Tank	VOC		
G358	G358 Storage Tank	VOC		
G360	G360 Storage Tank	VOC		
G361	G361 Storage Tank	VOC		
GIRBOTWW	WW Collection in Girbitol	VOC		
H1000	PLAT2 Heater	VOC		
H1001	Guard Bed Start-up Heater	VOC		
H1010	HDU-1 Charge Heater	VOC		
H1011	HDU-1 Reboiler Heater	VOC		
H1100	DHT Heater	VOC		
H1170	CFH Charge Heater	VOC		
H31001/2	Coker Heaters No. 1 and 2	VOC		
H31003	Coker Heater No. 3	VOC		
H3300	DHT H <sub>2</sub> Heater	VOC		
H36100	CGHT Heater	VOC		
H5100	DU-2 South Crude Heater	VOC		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
H5101	DU-2 North Crude Heater	VOC		
H5102	DU-2 South Flasher Charge Heater	VOC		
H5103	DU-2 North Flasher Charge Heater	VOC		
H5104	DU-2 Preflash Heater	VOC		
H5105	DU-2 Preflash2 Heater	VOC		
H5200	HDU-2 Charge Heater	VOC		
H53NN	Catalytic Reformer SCR	VOC		
H5400	SHCU South Charge Heater	VOC		
H5402	SHCU Reboiler Heater	VOC		
H5403	SHCU North Charge Heater	VOC		
H5404	SHCU Post-Frac Heater	VOC		
H5500A	SMR Heater A	VOC		
H5500B	SMR Heater B	VOC		
H5500C	SMR Heater C	VOC		
H5600	SGP Heat Medium Heater	VOC		
H600	FCCU CO Boiler	VOC		
H613	DU-1 Secondary Pre-Heater	VOC		
H63000	HVI Column Charge Heater	VOC		
H70001/2	GOHT Recycle Gas and Frac. Reboiler Heaters	VOC		
H850S1	PERC Heater - North Stack	VOC		
H850S2	PERC Heater - South Stack	VOC		
H9150R1	Heater	VOC		
HVIOWS	WW - Sewer HVI Oily Water	VOC		
J301B	J301B Storage Tank	VOC		
J302B	J302B Storage Tank	VOC		
J303B	J303B Storage Tank	VOC		
J304	J304 Storage Tank	VOC		
J305B	J305B Storage Tank	VOC		
J306	J306 Storage Tank	VOC		
J308	J308 Storage Tank	VOC		
J309	J309 Storage Tank	VOC		
J311	J311 Storage Tank	VOC		
J312	J312 Storage Tank	VOC		
J315	J315 Storage Tank	VOC		
J316	J316 Storage Tank	VOC		
J317	J317 Storage Tank	VOC		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
J318B	J318B Storage Tank	VOC		
J320	J320 Storage Tank	VOC		
J322	J322 Storage Tank	VOC		
J323	J323 Storage Tank	VOC		
J324	J324 Storage Tank	VOC		
J325	J325 Storage Tank	VOC		
J326	J326 Storage Tank	VOC		
J327	J327 Storage Tank	VOC		
J328	J328 Storage Tank	VOC		
J329	J329 Storage Tank	VOC		
J330	J330 Storage Tank	VOC		
J331	J331 Storage Tank	VOC		
J332	J332 Storage Tank	VOC		
J336	J336 Storage Tank	VOC		
J337	J337 Storage Tank	VOC		
J338	J338 Storage Tank	VOC		
J340	J340 Storage Tank	VOC		
J348	J348 Storage Tank	VOC		
J349	J349 Storage Tank	VOC		
K301	K301 Storage Tank	VOC		
K302	K302 Storage Tank	VOC		
K303	K303 Storage Tank	VOC		
K304	K304 Storage Tank	VOC		
K306	K306 Storage Tank	VOC		
K310	K310 Storage Tank	VOC		
K311	K311 Storage Tank	VOC		
L2COMPVT	L2COMPVT Vent	VOC		
LEUOWS	WW - Sewer LEU Oily Water	VOC		
LHT1OWS	WW - Sewer LHT1 Oily Water	VOC		
LHT2OWS	WW - Sewer LHT2 Oily Water	VOC		
LOADOWS	WW - Sewer Loading Racks	VOC		
M301	Marine Fuel Oil Storage Tank	VOC		
M302	Marine Diesel Storage Tank	VOC		
MANHOLE4	WW - Manhole 4	VOC		
MVIDEASS	WW - Sewer DEA	VOC		
MVIOWS	WW - Sewer MVI Oily Water	VOC		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
N92252	X4HDU1 Storage Tank	VOC		
NAB	North Aeration Basin	VOC		
NDAF	WW - North DAF Unit	VOC		
NONE2	FXTNK2/Amine Neutralizer Storage Tank	VOC		
NONE3	FXTNK2/Filmer Storage Tank	VOC		
OWATCTF	WW - Alky Tank Farm Oily Water	VOC		
OWDU1	WW - Sewer Oily Water HUB	VOC		
OWFLEX	Wastewater Collection System	VOC		
PAINTFE	Miscellaneous Painting Fugitives	VOC		
RKLBLND	Load	VOC		
RKLDIALA	Load	VOC		
RKLTC	Load	VOC		
RKLTC/TT	Load	VOC		
RKLTCTTU	Load	VOC		
S302	S302 Storage Tank	VOC		
S305	S305 Storage Tank	VOC		
S306	S306 Storage Tank	VOC		
S307	S307 Storage Tank	VOC		
S310	S310 Storage Tank	VOC		
S312	S312 Storage Tank	VOC		
S313	S313 Storage Tank	VOC		
S318	S318 Storage Tank	VOC		
S325	S325 Storage Tank	VOC		
S326	S326 Storage Tank	VOC		
S339	S339 Storage Tank	VOC		
S348	S348 Storage Tank	VOC		
S359	S359 Storage Tank	VOC		
S360	S360 Storage Tank	VOC		
S395	S395 Storage Tank	VOC		
S401	S401 Storage Tank	VOC		
S402	S402 Storage Tank	VOC		
S412	S412 Storage Tank	VOC		
S429	S429 Storage Tank	VOC		
S430	S430 Storage Tank	VOC		
SAB	South Aeration Basin	VOC		
SDAF	WW - South DAF Unit	VOC		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
SR3/4PIT	SR3/4 Sulfur Pit	VOC		
SR3/4STACK	SR3/4 Incinerator	VOC		
SR3/4WW	SR3/4 Wastewater Collection	VOC		
SR5L01	SR5 Loading rack	VOC		
SR5L02	SR5 Loading rack	VOC		
SR5STACK	SR5 Tail Gas Incinerator	VOC		
SR6STACK	SR6 Tail Gas Incinerator	VOC		
SR7STACK	SR7 Tail Gas Incinerator	VOC		
SR8STACK	SR8 Tail Gas Incinerator	VOC		
SRTT	SR3/4 Loading Rack	VOC		
SS306	SS306 Storage Tank	VOC		
SS307	SS307 Storage Tank	VOC		
SS308	SS308 Storage Tank	VOC		
SS312	SS312 Storage Tank	VOC		
SS314	SS314 Storage Tank	VOC		
SS316	SS316 Storage Tank	VOC		
SS324	SS324 Storage Tank	VOC		
SS325	SS325 Storage Tank	VOC		
SS335	SS335 Storage Tank	VOC		
SS339	SS339 Storage Tank	VOC		
SS341	SS341 Storage Tank	VOC		
SS343	SS343 Storage Tank	VOC		
SS344	SS344 Storage Tank	VOC		
SS348	SS348 Storage Tank	VOC		
SS364	SS364 Storage Tank	VOC		
SS375	SS375 Storage Tank	VOC		
SS376	SS376 Storage Tank	VOC		
SS377	SS377 Storage Tank	VOC		
SS378	SS378 Storage Tank	VOC		
SS379	SS379 Storage Tank	VOC		
SS388	SS388 Storage Tank	VOC		
SS396	SS396 Storage Tank	VOC		
SS403	SS403 Storage Tank	VOC		
SS425	SS425 Storage Tank	VOC		
ST1400	X2HDU1 Storage Tank	VOC		
SULFUR	SR5 Sulfur Pit	VOC		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
T1211	T1211 Storage Tank	VOC		
T1212	T1212 Storage Tank	VOC		
T1710	T1710 Storage Tank	VOC		
T1F323	T1F323 Storage Tank	VOC		
T1F324	T1F324 Storage Tank	VOC		
T1F329	T1F329 Storage Tank	VOC		
T1F330	T1F330 Storage Tank	VOC		
T1F348	T1F348 Storage Tank	VOC		
T301	T301 Storage Tank	VOC		
T302	T302 EXTFLT Refinery WW Storage Tank	VOC		
T315	T315 Storage Tank	VOC		
T316	Methanol Storage Tank	VOC		
T59	T59 FXTNK2/SOAP Storage Tank	VOC		
T93002	T93002 DEA Storage Tank	VOC		
T93402	T93402 MDEA Storage Tank	VOC		
TA301	TA301 Storage Tank	VOC		
TA305	TA305 Storage Tank	VOC		
TA306	TA306 Storage Tank	VOC		
TA307	TA307 Storage Tank	VOC		
TA308	TA308 Storage Tank	VOC		
TA309	TA309 Storage Tank	VOC		
TA310	TA310 Storage Tank	VOC		
TA312	TA312 Storage Tank	VOC		
TA313	TA313 Storage Tank	VOC		
TA315	TA315 Storage Tank	VOC		
TA316	TA316 Storage Tank	VOC		
TA317	TA317 Storage Tank	VOC		
TA318	TA318 Storage Tank	VOC		
TA319	TA319 Storage Tank	VOC		
TA320	TA320 Storage Tank	VOC		
TA321	TA321 Storage Tank	VOC		
TA322	TA322 Storage Tank	VOC		
TA324	TA324 Storage Tank	VOC		
TA325	TA325 Storage Tank	VOC		
TA326	TA326 Storage Tank	VOC		
TA329	TA329 Storage Tank	VOC		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
TA330	TA330 Storage Tank	VOC		
TA331	TA331 Storage Tank	VOC		
TA332	TA332 Storage Tank	VOC		
TA334	TA334 Storage Tank	VOC		
TC and G	WW - Thermal Cracking and Gas Treating	VOC		
TCACIDLOAD	Acid Tank Car Loading	VOC		
TG324	TG324 Storage Tank	VOC		
TG362	TG362 Storage Tank	VOC		
TJ333	TJ333 Storage Tank	VOC		
TJ334	TJ334 Storage Tank	VOC		
TJ335	TJ335 Storage Tank	VOC		
TJ339R1	TJ339R1 Storage Tank	VOC		
TK305	TK305 Storage Tank	VOC		
TRKLFIL	WW - Trickle Filter	VOC		
TRKLSMP	WW - Trickle Sump	VOC		
U301	U301 Storage Tank	VOC		
U302	U302 Storage Tank	VOC		
V1111	V1111 Storage Tank	VOC		
V54	Vessel/Regen Gas KO Pot	VOC		
V5518	Hydrogen Plant Vent	VOC		
V5527	Column in HP1	VOC		
V9160	Vent V9160	VOC		
VA03	VA03 Storage Tank	VOC		
VA04	VA04 Storage Tank	VOC		
WAXPTOWS	WW - Sewer Wax Plant Oily Water	VOC		
WAXPTWAX	WW - Sewer Wax Plant Wax	VOC		
WX285	WX285 Storage Tank	VOC		
X2HDU1	FXTNK2/X2HDU1 Storage Tank	VOC		
X311	INTFLT/Amine Solutions Storage Tank	VOC		
X312	INTFLT/Amine Solutions Storage Tank	VOC		
X313	INTFLT/Slop Oil Storage Tank	VOC		
X315	Ballast Water Storage Tank	VOC		
X316	WW - DAF Float	VOC		
X320	Ballast Water O/S Storage Tank	VOC		
X321	Slop Oil Storage Tank	VOC		
X322	X322 Storage Tank	VOC		



## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
X323	X323 Storage Tank	VOC		
X324	FXTNK2/Misc Organic Storage Tank	VOC		
X325	FXTNK2/Misc Organic Storage Tank	VOC		
X326	FXTNK2/DAF Float Storage Tank	VOC		
X327	FXTNK2/DAF Float Storage Tank	VOC		
X328	FXTNK2/Misc Organic Storage Tank	VOC		
X330	WW - Equalization Tank	VOC		
X330SM	WW - Sump	VOC		
<b>FINAL EMISSIONS CAP</b>		VOC	1895.68	2914.90

**Planned Maintenance, Startup, and Shutdown (MSS) Emission Rate Limits**

CRUDES	Shutdown of DU-2, VF-3, VF-4, HDU-2	Benzene
COKERS	Shutdown of Cokers, GOHT	Benzene
SGPS	Shutdown of SGP	Benzene
SULFURS	Shutdown of Sulfur Block	Benzene
SHCUS	Shutdown of SHCU	Benzene
HP1SDSU	Shutdown/Startup of HP-1	Benzene
DPREFSDSU	Shutdown/Startup of Other Units	Benzene
FLNFLARE	North Property Flare	Benzene
COKE FLARE	Coker Flare	Benzene
WP FLARE	West Property Flare	Benzene
EP FLARE	East Property Flare	Benzene
TA324	MAYA Crude	Benzene
TA325	DU1 Crude	Benzene
TA326	DU1 Crude	Benzene
F364	MTBE, 100%	Benzene
TG362	MAYA Crude	Benzene
TA329	MAYA Crude	Benzene
TA330	MAYA Crude	Benzene
TA331	MAYA Crude	Benzene

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	AIR CONTAMINANTS DATA	
			Emission Rates * lb/hr	TPY**
TA332	MAYA Crude	Benzene		
TA334	MAYA Crude	Benzene		
G313	Gasoline (RU2000)	Benzene		
G315	Gasoline (RU2000)	Benzene		
G323	Gasoline (RU2000)	Benzene		
G326	Gasoline (RU2000)	Benzene		
G327	Gasoline (RU2000)	Benzene		
FUGABRBLST	Abrasive Blasting: Sitewide	Benzene		
AEROSDISP	Aerosol Can Crushing and Disposal	Benzene		
AEROSAPPL	Aerosol Can Application: Paint and Solvents	Benzene		
DEGREAS01	Chemical Cleaning - Degreaser Units	Benzene		
FUGSMPDPR	Process Sampling	Benzene		
FUGMSSDPR	Fugitive Components Associated with Maintenance	Benzene		
FUGVACDPR	Vacuum Truck Loading & Unloading	Benzene		
PAINTFE	Painting Emissions Sitewide	Benzene		
MSSDECNDPR	Combustion Device Decoking	Benzene		
TNKVENT	Pump and Minor Process Decontamination	Benzene		
	Forced Ventilation of Tank w/Residual	Benzene		
	<b>MSS-CAP</b>	Benzene	19.80	0.78
CRUDES	Shutdown of DU-2, VF-3, VF-4, HDU-2	CO		
COKERSD	Shutdown of Cokers, GOHT	CO		
SGPSD	Shutdown of SGP	CO		
SULFURSD	Shutdown of Sulfur Block	CO		
SHCUS	Shutdown of SHCU	CO		
HP1SDSU	Shutdown/Startup of HP-1	CO		
DPREFSDSU	Shutdown/Startup of Other Units	CO		
FLNFLARE	North Property Flare	CO		
COKE FLARE	Coker Flare	CO		
WP FLARE	West Property Flare	CO		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	AIR CONTAMINANTS DATA	
			Emission Rates * lb/hr	TPY**
EP FLARE	East Property Flare	CO		
TA324	MAYA Crude	CO		
TA325	DU1 Crude	CO		
TA326	DU1 Crude	CO		
F364	MTBE, 100%	CO		
TG362	MAYA Crude	CO		
TA329	MAYA Crude	CO		
TA330	MAYA Crude	CO		
TA331	MAYA Crude	CO		
TA332	MAYA Crude	CO		
TA334	MAYA Crude	CO		
G313	Gasoline (RU2000)	CO		
G315	Gasoline (RU2000)	CO		
G323	Gasoline (RU2000)	CO		
G326	Gasoline (RU2000)	CO		
G327	Gasoline (RU2000)	CO		
FUGABRBLST	Abrasive Blasting: Sitewide	CO		
AEROSDISP	Aerosol Can Crushing and Disposal	CO		
AEROSAPPL	Aerosol Can Application: Paint and Solvents	CO		
DEGREAS01	Chemical Cleaning - Degreaser Units	CO		
FUGSMPDPR	Process Sampling	CO		
FUGMSSDPR	Fugitive Components Associated with Maintenance	CO		
FUGVACDPR	Vacuum Truck Loading & Unloading	CO		
PAINTFE	Painting Emissions Sitewide	CO		
	Combustion Device Decoking	CO		
MSSDECNDPR	Pump and Minor Process Decontamination	CO		
TNKVENT	Forced Ventilation of Tank w/Residual	CO		
	<b>MSS-CAP</b>	CO	199.70	11.46
CRUDES D	Shutdown of DU-2, VF-3, VF-4, HDU-2	H <sub>2</sub> S		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
COKERSD	Shutdown of Cokers, GOHT	H <sub>2</sub> S		
SGPSD	Shutdown of SGP	H <sub>2</sub> S		
SULFURSD	Shutdown of Sulfur Block	H <sub>2</sub> S		
SHCUSD	Shutdown of SHCU	H <sub>2</sub> S		
HP1SDSU	Shutdown/Startup of HP-1	H <sub>2</sub> S		
DPREFSDSU	Shutdown/Startup of Other Units	H <sub>2</sub> S		
FLNFLARE	North Property Flare	H <sub>2</sub> S		
COKE FLARE	Coker Flare	H <sub>2</sub> S		
WP FLARE	West Property Flare	H <sub>2</sub> S		
EP FLARE	East Property Flare	H <sub>2</sub> S		
TA324	MAYA Crude	H <sub>2</sub> S		
TA325	DU1 Crude	H <sub>2</sub> S		
TA326	DU1 Crude	H <sub>2</sub> S		
F364	MTBE, 100%	H <sub>2</sub> S		
TG362	MAYA Crude	H <sub>2</sub> S		
TA329	MAYA Crude	H <sub>2</sub> S		
TA330	MAYA Crude	H <sub>2</sub> S		
TA331	MAYA Crude	H <sub>2</sub> S		
TA332	MAYA Crude	H <sub>2</sub> S		
TA334	MAYA Crude	H <sub>2</sub> S		
G313	Gasoline (RU2000)	H <sub>2</sub> S		
G315	Gasoline (RU2000)	H <sub>2</sub> S		
G323	Gasoline (RU2000)	H <sub>2</sub> S		
G326	Gasoline (RU2000)	H <sub>2</sub> S		
G327	Gasoline (RU2000)	H <sub>2</sub> S		
FUGABRBLST	Abrasive Blasting: Sitewide	H <sub>2</sub> S		
AEROSDISP	Aerosol Can Crushing and Disposal	H <sub>2</sub> S		
AEROSAPPL	Aerosol Can Application: Paint and Solvents	H <sub>2</sub> S		
DEGREAS01	Chemical Cleaning - Degreaser Units	H <sub>2</sub> S		
FUGSMPDPR	Process Sampling	H <sub>2</sub> S		
FUGMSSDPR	Fugitive Components Associated with Maintenance	H <sub>2</sub> S		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
FUGVACDPR	Vacuum Truck Loading & Unloading	H <sub>2</sub> S		
PAINTFE	Painting Emissions Sitewide	H <sub>2</sub> S		
	Combustion Device Decoking	H <sub>2</sub> S		
MSSDECNDPR	Pump and Minor Process Decontamination	H <sub>2</sub> S		
TNKVENT	Forced Ventilation of Tank w/Residual	H <sub>2</sub> S		
	<b>MSS-CAP</b>	H <sub>2</sub> S	59.86	2.43
CRUDES	Shutdown of DU-2, VF-3, VF-4, HDU-2	NO <sub>x</sub>		
COKERS	Shutdown of Cokers, GOHT	NO <sub>x</sub>		
SGPS	Shutdown of SGP	NO <sub>x</sub>		
SULFURS	Shutdown of Sulfur Block	NO <sub>x</sub>		
SHCUS	Shutdown of SHCU	NO <sub>x</sub>		
HP1SDSU	Shutdown/Startup of HP-1	NO <sub>x</sub>		
DPREFSDSU	Shutdown/Startup of Other Units	NO <sub>x</sub>		
FLNFLARE	North Property Flare	NO <sub>x</sub>		
COKE FLARE	Coker Flare	NO <sub>x</sub>		
WP FLARE	West Property Flare	NO <sub>x</sub>		
EP FLARE	East Property Flare	NO <sub>x</sub>		
TA324	MAYA Crude	NO <sub>x</sub>		
TA325	DU1 Crude	NO <sub>x</sub>		
TA326	DU1 Crude	NO <sub>x</sub>		
F364	MTBE, 100%	NO <sub>x</sub>		
TG362	MAYA Crude	NO <sub>x</sub>		
TA329	MAYA Crude	NO <sub>x</sub>		
TA330	MAYA Crude	NO <sub>x</sub>		
TA331	MAYA Crude	NO <sub>x</sub>		
TA332	MAYA Crude	NO <sub>x</sub>		
TA334	MAYA Crude	NO <sub>x</sub>		
G313	Gasoline (RU2000)	NO <sub>x</sub>		
G315	Gasoline (RU2000)	NO <sub>x</sub>		
G323	Gasoline (RU2000)	NO <sub>x</sub>		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	AIR CONTAMINANTS DATA	
			Emission Rates * lb/hr	TPY**
G326	Gasoline (RU2000)	NO <sub>x</sub>		
G327	Gasoline (RU2000)	NO <sub>x</sub>		
FUGABRBLST	Abrasive Blasting: Sitewide	NO <sub>x</sub>		
AEROSDISP	Aerosol Can Crushing and Disposal	NO <sub>x</sub>		
AEROSAPPL	Aerosol Can Application: Paint and Solvents	NO <sub>x</sub>		
DEGREAS01	Chemical Cleaning - Degreaser Units	NO <sub>x</sub>		
FUGSMPDPR	Process Sampling	NO <sub>x</sub>		
FUGMSSDPR	Fugitive Components Associated with Maintenance	NO <sub>x</sub>		
FUGVACDPR	Vacuum Truck Loading & Unloading	NO <sub>x</sub>		
PAINTFE	Painting Emissions Sitewide	NO <sub>x</sub>		
MSSDECNDPR	Combustion Device Decoking	NO <sub>x</sub>		
TNKVENT	Pump and Minor Process Decontamination	NO <sub>x</sub>		
	Forced Ventilation of Tank w/Residual	NO <sub>x</sub>		
	<b>MSS-CAP</b>	NO <sub>x</sub>	14.77	0.70
CRUDES	Shutdown of DU-2, VF-3, VF-4, HDU-2	PM		
COKERSD	Shutdown of Cokers, GOHT	PM		
SGPSD	Shutdown of SGP	PM		
SULFURSD	Shutdown of Sulfur Block	PM		
SHCUS	Shutdown of SHCU	PM		
HP1SDSU	Shutdown/Startup of HP-1	PM		
DPREFSDSU	Shutdown/Startup of Other Units	PM		
FLNFLARE	North Property Flare	PM		
COKE FLARE	Coker Flare	PM		
WP FLARE	West Property Flare	PM		
EP FLARE	East Property Flare	PM		
TA324	MAYA Crude	PM		
TA325	DU1 Crude	PM		
TA326	DU1 Crude	PM		
F364	MTBE, 100%	PM		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
TG362	MAYA Crude	PM		
TA329	MAYA Crude	PM		
TA330	MAYA Crude	PM		
TA331	MAYA Crude	PM		
TA332	MAYA Crude	PM		
TA334	MAYA Crude	PM		
G313	Gasoline (RU2000)	PM		
G315	Gasoline (RU2000)	PM		
G323	Gasoline (RU2000)	PM		
G326	Gasoline (RU2000)	PM		
G327	Gasoline (RU2000)	PM		
FUGABRBLST	Abrasive Blasting: Sitewide	PM		
AEROSDISP	Aerosol Can Crushing and Disposal	PM		
AEROSAPPL	Aerosol Can Application: Paint and Solvents	PM		
DEGREAS01	Chemical Cleaning - Degreaser Units	PM		
FUGSMPDPR	Process Sampling	PM		
FUGMSSDPR	Fugitive Components Associated with Maintenance	PM		
FUGVACDPR	Vacuum Truck Loading & Unloading	PM		
PAINTFE	Painting Emissions Sitewide	PM		
	Combustion Device Decoking	PM		
MSSDECNDPR	Pump and Minor Process Decontamination	PM		
TNKVENT	Forced Ventilation of Tank w/Residual	PM		
	<b>MSS-CAP</b>	PM	18.31	12.43
CRUDES	Shutdown of DU-2, VF-3, VF-4, HDU-2	SO <sub>2</sub>		
COKERSD	Shutdown of Cokers, GOHT	SO <sub>2</sub>		
SGPSD	Shutdown of SGP	SO <sub>2</sub>		
SULFURSD	Shutdown of Sulfur Block	SO <sub>2</sub>		
SHCUS	Shutdown of SHCU	SO <sub>2</sub>		
HP1SDSU	Shutdown/Startup of HP-1	SO <sub>2</sub>		

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
DPREFSDSU	Shutdown/Startup of Other Units	SO <sub>2</sub>		
FLNFLARE	North Property Flare	SO <sub>2</sub>		
COKE FLARE	Coker Flare	SO <sub>2</sub>		
WP FLARE	West Property Flare	SO <sub>2</sub>		
EP FLARE	East Property Flare	SO <sub>2</sub>		
TA324	MAYA Crude	SO <sub>2</sub>		
TA325	DU1 Crude	SO <sub>2</sub>		
TA326	DU1 Crude	SO <sub>2</sub>		
F364	MTBE, 100%	SO <sub>2</sub>		
TG362	MAYA Crude	SO <sub>2</sub>		
TA329	MAYA Crude	SO <sub>2</sub>		
TA330	MAYA Crude	SO <sub>2</sub>		
TA331	MAYA Crude	SO <sub>2</sub>		
TA332	MAYA Crude	SO <sub>2</sub>		
TA334	MAYA Crude	SO <sub>2</sub>		
G313	Gasoline (RU2000)	SO <sub>2</sub>		
G315	Gasoline (RU2000)	SO <sub>2</sub>		
G323	Gasoline (RU2000)	SO <sub>2</sub>		
G326	Gasoline (RU2000)	SO <sub>2</sub>		
G327	Gasoline (RU2000)	SO <sub>2</sub>		
FUGABRBLST	Abrasive Blasting: Sitewide	SO <sub>2</sub>		
AEROSDISP	Aerosol Can Crushing and Disposal	SO <sub>2</sub>		
AEROSAPPL	Aerosol Can Application: Paint and Solvents	SO <sub>2</sub>		
DEGREAS01	Chemical Cleaning - Degreaser Units	SO <sub>2</sub>		
FUGSMPDPR	Process Sampling	SO <sub>2</sub>		
FUGMSSDPR	Fugitive Components Associated with Maintenance	SO <sub>2</sub>		
FUGVACDPR	Vacuum Truck Loading & Unloading	SO <sub>2</sub>		
PAINTFE	Painting Emissions Sitewide	SO <sub>2</sub>		
	Combustion Device Decoking	SO <sub>2</sub>		
MSSDECNDPR	Pump and Minor Process Decontamination	SO <sub>2</sub>		
TNKVENT	Forced Ventilation of Tank w/Residual	SO <sub>2</sub>		



## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	AIR CONTAMINANTS DATA	
			Emission Rates * lb/hr	TPY**
	<b>MSS-CAP</b>	SO <sub>2</sub>	1560.81	46.29
CRUDES	Shutdown of DU-2, VF-3, VF-4, HDU-2	VOC		
COKERS	Shutdown of Cokers, GOHT	VOC		
SGPS	Shutdown of SGP	VOC		
SULFURS	Shutdown of Sulfur Block	VOC		
SHCUS	Shutdown of SHCU	VOC		
HP1SDSU	Shutdown/Startup of HP-1	VOC		
DPREFSDSU	Shutdown/Startup of Other Units	VOC		
FLNFLARE	North Property Flare	VOC		
COKE FLARE	Coker Flare	VOC		
WP FLARE	West Property Flare	VOC		
EP FLARE	East Property Flare	VOC		
TA324	MAYA Crude	VOC		
TA325	DU1 Crude	VOC		
TA326	DU1 Crude	VOC		
F364	MTBE, 100%	VOC		
TG362	MAYA Crude	VOC		
TA329	MAYA Crude	VOC		
TA330	MAYA Crude	VOC		
TA331	MAYA Crude	VOC		
TA332	MAYA Crude	VOC		
TA334	MAYA Crude	VOC		
G313	Gasoline (RU2000)	VOC		
G315	Gasoline (RU2000)	VOC		
G323	Gasoline (RU2000)	VOC		
G326	Gasoline (RU2000)	VOC		
G327	Gasoline (RU2000)	VOC		
FUGABRBLST	Abrasive Blasting: Sitewide	VOC		
AEROSDISP	Aerosol Can Crushing and Disposal	VOC		
AEROSAPPL	Aerosol Can Application: Paint and Solvents	VOC		

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
DEGREAS01	Chemical Cleaning - Degreaser Units	VOC		
FUGSMPDPR	Process Sampling	VOC		
FUGMSSDPR	Fugitive Components Associated with Maintenance	VOC		
FUGVACDPR	Vacuum Truck Loading & Unloading	VOC		
PAINTFE	Painting Emissions Sitewide	VOC		
	Combustion Device Decoking	VOC		
MSSDECNDPR	Pump and Minor Process Decontamination	VOC		
TNKVENT	Forced Ventilation of Tank w/Residual	VOC		
	<b>MSS-CAP</b>	VOC	2588.61	61.08

- (1) Emission point identification - either specific equipment designation or emission point number from a plot plan.
- (2) Specific point source names. For fugitive sources use area name or fugitive source name.
- (3)
  - CO - carbon monoxide
  - H<sub>2</sub>S - hydrogen sulfide
  - NH<sub>3</sub> - ammonia
  - NO<sub>x</sub> - nitrogen oxides
  - PM - particulate matter, suspended in the atmosphere, including PM<sub>10</sub>
  - PM<sub>10</sub> - particulate matter (PM) equal to or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no PM greater than 10 microns is emitted.
  - SO<sub>2</sub> - sulfur dioxide
  - VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
- (4) Fugitive emissions are an estimate only and should not be considered as a maximum allowable emission rate.

\* Emission rates are based on and the facilities are limited by the following maximum operating schedule:

Hrs/day \_\_\_ Days/week \_\_\_ Weeks/year \_\_\_ or Hrs/year 8,760

\*\* Compliance with annual emission limits is based on a rolling 12-month period.

Dated: August 18, 2010