

Horsley Witten Group

Sustainable Environmental Solutions

90 Route 6A • Sandwich, MA • 02563
Tel: 508-833-6600 • Fax: 508-833-3150 • www.horsleywitten.com



October 13, 2009

Massachusetts Department of Environmental Protection
Division of Watershed Management
627 Main Street, 2nd Floor
Worcester, MA 01608

VIA EMAIL

To whom it may concern;

Horsley Witten Group, Inc. (HW) has prepared the enclosed Notice of Intent (NOI) for coverage under the Remediation General Permit (RGP) on behalf of the Taunton Municipal Lighting Plant (TMLP), Taunton, Massachusetts. In accordance with Massachusetts Department of Environmental Protection (DEP) Bureau of Resource Protection Watershed Permitting Program form BRP WM 12, the appropriate permit application fee has been submitted under transmittal number X230269. A copy of the transmittal form and check are included with the NOI submittal package.

TMLP seeks coverage under the RGP to discharge approximately 700,000 gallons of treated water to a drainage channel that subsequently discharges to the Taunton River. The source of the water is a 1.8 million gallon above ground storage tank (AST) used to store No. 2 fuel oil. Municipally supplied water was utilized to raise the level of the AST roof to facilitate necessary repairs to its sidewalls.

Laboratory analysis of untreated discharge samples collected from the AST indicates the presence of petroleum related contaminants, including volatile organic compounds (VOCs) and lead. A treatment system incorporating an oil water separator (O/WS) and granular activated carbon (GAC) treatment system is proposed to remove petroleum-related contaminants and VOCs. As a conservative measure, the discharge will pass through a second O/WS just prior to discharge to the drainage channel. The second O/WS will facilitate visual inspection of discharge water quality and provide further resource protection in the event of treatment system failure. Moran Environmental Recovery (Moran) of Randolph, Massachusetts, will be coordinating the discharge monitoring and treatment system installation and operation. During the proposed discharge, Moran will maintain continuous staff coverage at the facility.

During laboratory analysis of the untreated discharge samples, the presence of petroleum related compounds and VOCs prevented the laboratory instrumentation from achieving the reporting limits established in Appendix VI of the RGP. The laboratory was able to achieve the Appendix VI reporting limits in samples collected from the municipal source water. During discharge sampling, the laboratory should be able to achieve the Appendix VI reporting limits as the bulk

October 13, 2009

Page 2 of 2

of expected contaminants will be removed through the O/WS and GAC treatment. A dilution factor calculation in accordance with Part I.A.3.c (Step 2) of the NOI instructions indicates sufficient dilution of lead present in the untreated discharge to meet the Appendix III standards.

In preparation for TMLP's Stormwater Pollution Prevention Plan (SWPPP), the Massachusetts Historical Commission determined that the TMLP is "unlikely to affect significant historic or archaeological resources", and the United States Fish and Wildlife Service determined that "no federally-listed or proposed, threatened or endangered species or critical habitat...are known to occur in the project area(s)". The proposed discharge is unlikely to alter these determinations.

HW is pleased to submit this NOI on behalf of TMLP, and looks forward to your review. Please contact the undersigned with any questions or concerns.

Sincerely,

HORSLEY WITTEN GROUP, INC.



Joseph E. Longo
Associate Principal



Gary W.T. Hedman
Project Scientist

Cc:
U.S. Environmental Protection Agency
RGP-NOC Processing

Mr. Steve Cote
Taunton Municipal Lighting Plant

B. Suggested Form for Notice of Intent (NOI) for the Remediation General Permit

1. General site information. Please provide the following information about the site:

a) Name of facility/site :		Facility/site address:	
Location of facility/site : longitude:_____ latitude:_____	Facility SIC code(s):	Street:	
b) Name of facility/site owner :		Town:	
Email address of owner:	State:	Zip:	County:
Telephone no.of facility/site owner :			
Fax no. of facility/site owner :	Owner is (check one): 1. Federal____ 2. State/Tribal____ 3. Private____ 4. other, if so, describe:		
Address of owner (if different from site):			
Street:			
Town:	State:	Zip:	County:
c) Legal name of operator :	Operator telephone no:		
	Operator fax no.:		Operator email:
Operator contact name and title:			
Address of operator (if different from owner):	Street:		
Town:	State:	Zip:	County:
d) Check “yes” or “no” for the following: 1. Has a prior NPDES permit exclusion been granted for the discharge? Yes___ No___, if “yes,” number: 2. Has a prior NPDES application (Form 1 & 2C) ever been filed for the discharge? Yes___ No___, if “yes,” date and tracking #: 3. Is the discharge a “new discharge” as defined by 40 CFR 122.2? Yes___ No___ 4. For sites in Massachusetts, is the discharge covered under the MA Contingency Plan (MCP) and exempt from state permitting? Yes__ No__			

e) Is site/facility subject to any State permitting or other action which is causing the generation of discharge? Yes___ No___ If “yes,” please list: 1. site identification # assigned by the state of NH or MA: 2. permit or license # assigned: 3. state agency contact information: name, location, and telephone number:	f) Is the site/facility covered by any other EPA permit, including: 1. multi-sector storm water general permit? Y___ N___, if Y, number: 2. phase I or II construction storm water general permit? Y___ N___, if Y, number: 3. individual NPDES permit? Y___ N___, if Y, number: 4. any other water quality related permit? Y___ N___, if Y, number:
---	--

2. Discharge information. Please provide information about the discharge, (attaching additional sheets as needed) including:

a) Describe the discharge activities for which the owner/applicant is seeking coverage:			
b) Provide the following information about each discharge:	<table border="1"> <tr> <td style="vertical-align: top;">1) Number of discharge points:</td> <td style="vertical-align: top;"> 2) What is the maximum and average flow rate of discharge (in cubic feet per second, ft³/s)? Max. flow_____ Average flow_____ Is maximum flow a design value? Y___ N___ For average flow, include the units and appropriate notation if this value is a design value or estimate if not available. </td> </tr> </table>	1) Number of discharge points:	2) What is the maximum and average flow rate of discharge (in cubic feet per second, ft ³ /s)? Max. flow_____ Average flow_____ Is maximum flow a design value ? Y___ N___ For average flow, include the units and appropriate notation if this value is a design value or estimate if not available.
1) Number of discharge points:	2) What is the maximum and average flow rate of discharge (in cubic feet per second, ft ³ /s)? Max. flow_____ Average flow_____ Is maximum flow a design value ? Y___ N___ For average flow, include the units and appropriate notation if this value is a design value or estimate if not available.		
3) Latitude and longitude of each discharge within 100 feet: pt.1:long._____ lat._____; pt.2: long._____ lat._____; pt.3: long._____ lat._____; pt.4:long._____ lat._____; pt.5: long._____ lat._____; pt.6:long._____ lat._____; pt.7: long._____ lat._____; pt.8:long._____ lat._____; etc.			
4) If hydrostatic testing, total volume of the discharge (gals):	5) Is the discharge intermittent_____or seasonal_____ Is discharge ongoing Yes _____ No _____?___		
c) Expected dates of discharge (mm/dd/yy): start_____ end_____			
d) Please attach a line drawing or flow schematic showing water flow through the facility including: 1. sources of intake water, 2. contributing flow from the operation, 3. treatment units, and 4. discharge points and receiving waters(s).			

3. Contaminant information. In order to complete this section, the applicant will need to take a minimum of one sample of the untreated water and have it analyzed for **all** of the parameters listed in Appendix III. Historical data, (i.e., data taken no more than 2 years prior to the effective date of the permit) may be used if obtained pursuant to: i. Massachusetts' regulations 310 CMR 40.0000, the Massachusetts Contingency Plan ("Chapter 21E"); ii. New Hampshire's Title 50 RSA 485-A: Water Pollution and Waste Disposal or Title 50 RSA 485-C: Groundwater Protection Act; or iii. an EPA permit exclusion letter issued pursuant to 40 CFR 122.3, provided the data was analyzed with test methods that meet the requirements of this permit. Otherwise, a new sample shall be taken and analyzed.

a) Based on the analysis of the sample(s) of the untreated influent, the applicant must check the box of the sub-categories that the potential discharge falls within.

Gasoline Only	VOC Only	Primarily Metals	Urban Fill Sites	Contaminated Sumps	Mixed Contaminants	Aquifer Testing
Fuel Oils (and Other Oils) only	VOC with Other Contaminants	Petroleum with Other Contaminants	Listed Contaminated Sites	Contaminated Dredge Condensates	Hydrostatic Testing of Pipelines/Tanks	Well Development or Rehabilitation

b) Based on the analysis of the untreated influent, the applicant must indicate whether each listed chemical is **believed present** or **believed absent** in the potential discharge. Attach additional sheets as needed.

PARAMETER	Believe Absent	Believe Present	# of Samples (1 minimum)	Type of Sample (e.g., grab)	Analytical Method Used (method #)	Minimum Level (ML) of Test Method	Maximum daily value		Avg. daily value	
							concentration (ug/l)	mass (kg)	concentration (ug/l)	mass (kg)
1. Total Suspended Solids										
2. Total Residual Chlorine										
3. Total Petroleum Hydrocarbons										
4. Cyanide										
5. Benzene										
6. Toluene										
7. Ethylbenzene										
8. (m,p,o) Xylenes										
9. Total BTEX ⁴										

⁴BTEX = Sum of Benzene, Toluene, Ethylbenzene, total Xylenes.

PARAMETER	Believe Absent	Believe Present	# of Samples (1 minimum)	Type of Sample (e.g., grab)	Analytical Method Used (method #)	Minimum Level (ML) of Test Method	Maximum daily value		Avg. daily value	
							concentration (ug/l)	mass (kg)	concentration (ug/l)	mass (kg)
10. Ethylene Dibromide ⁵ (1,2- Dibromo-methane)										
11. Methyl-tert-Butyl Ether (MtBE)										
12. tert-Butyl Alcohol (TBA)										
13. tert-Amyl Methyl Ether (TAME)										
14. Naphthalene										
15. Carbon Tetra-chloride										
16. 1,4 Dichlorobenzene										
17. 1,2 Dichlorobenzene										
18. 1,3 Dichlorobenzene										
19. 1,1 Dichloroethane										
20. 1,2 Dichloroethane										
21. 1,1 Dichloroethylene										
22. cis-1,2 Dichloro-ethylene										
23. Dichloromethane (Methylene Chloride)										
24. Tetrachloroethylene										

⁵EDB is a groundwater contaminant at fuel spill and pesticide application sites in New England.

PARAMETER	Believe Absent	Believe Present	# of Samples (1 minimum)	Type of Sample (e.g., grab)	Analytical Method Used (method #)	Minimum Level (ML) of Test Method	Maximum daily value		Avg. daily Value	
							concentration (ug/l)	mass (kg)	concentration (ug/l)	mass (kg)
25. 1,1,1 Trichloroethane										
26. 1,1,2 Trichloroethane										
27. Trichloroethylene										
28. Vinyl Chloride										
29. Acetone										
30. 1,4 Dioxane										
31. Total Phenols										
32. Pentachlorophenol										
33. Total Phthalates ⁶ (Phthalate esthers)										
34. Bis (2-Ethylhexyl) Phthalate [Di-(ethylhexyl) Phthalate]										
35. Total Group I Polycyclic Aromatic Hydrocarbons (PAH)										
a. Benzo(a) Anthracene										
b. Benzo(a) Pyrene										
c. Benzo(b)Fluoranthene										
d. Benzo(k) Fluoranthene										
e. Chrysene										

⁶The sum of individual phthalate compounds.

PARAMETER	Believe Absent	Believe Present	# of Samples (1 min- imum)	Type of Sample (e.g., grab)	Analytical Method Used (method #)	Minimum Level (ML) of Test Method	Maximum daily value		Average daily value	
							concentration (ug/l)	mass (kg)	concentration (ug/l)	mass (kg)
f. Dibenzo(a,h) anthracene										
g. Indeno(1,2,3-cd) Pyrene										
36. Total Group II Polycyclic Aromatic Hydrocarbons (PAH)										
h. Acenaphthene										
i. Acenaphthylene										
j. Anthracene										
k. Benzo(ghi) Perylene										
l. Fluoranthene										
m. Fluorene										
n. Naphthalene-										
o. Phenanthrene										
p. Pyrene										
37. Total Polychlorinated Biphenyls (PCBs)										
38. Antimony										
39. Arsenic										
40. Cadmium										
41. Chromium III										
42. Chromium VI										

PARAMETER	Believe Absent	Believe Present	# of Samples (1 minimum)	Type of Sample (e.g., grab)	Analytical Method Used (method #)	Minimum Level (ML) of Test Method	Maximum daily value		Avg. daily value	
							concentration (ug/l)	mass (kg)	concentration (ug/l)	mass (kg)
43. Copper										
44. Lead										
45. Mercury										
46. Nickel										
47. Selenium										
48. Silver										
49. Zinc										
50. Iron										
Other (describe):										

c) For discharges where **metals** are believed present, please fill out the following:

<i>Step 1:</i> Do any of the metals in the influent have a reasonable potential to exceed the effluent limits in Appendix III (i.e., the limits set at zero to five dilutions)? Y____ N____	If yes, which metals?
<i>Step 2:</i> For any metals which have reasonable potential to exceed the Appendix III limits, calculate the dilution factor (DF) using the formula in Part I.A.3.c) (step 2) of the NOI instructions or as determined by the State prior to the submission of this NOI. What is the dilution factor for applicable metals? Metals: _____ DF: _____	Look up the limit calculated at the corresponding dilution factor in Appendix IV. Do any of the metals in the influent have the potential to exceed the corresponding effluent limits in Appendix IV (i.e., is the influent concentration above the limit set at the calculated dilution factor)? Y____ N____ If “Yes,” list which metals:

4. Treatment system information. Please describe the treatment system using separate sheets as necessary, including:

a) A description of the treatment system, including a schematic of the proposed or existing treatment system:						
b) Identify each applicable treatment unit (check all that apply):	Frac. tank	Air stripper	Oil/water separator	Equalization tanks	Bag filter	GAC filter
	Chlorination	Dechlorination	Other (please describe):			
c) Proposed average and maximum flow rates (gallons per minute) for the discharge and the design flow rate(s) (gallons per minute) of the treatment system: Average flow rate of discharge _____ Maximum flow rate of treatment system _____ Design flow rate of treatment system _____						
d) A description of chemical additives being used or planned to be used (attach MSDS sheets):						

5. Receiving surface water(s). Please provide information about the receiving water(s), using separate sheets as necessary:

a) Identify the discharge pathway:	Direct _____	Within facility__	Storm drain_____	River/brook_____	Wetlands _____	Other (describe):
b) Provide a narrative description of the discharge pathway, including the name(s) of the receiving waters:						
c) Attach a detailed map(s) indicating the site location and location of the outfall to the receiving water: 1. For multiple discharges, number the discharges sequentially. 2. For indirect dischargers, indicate the location of the discharge to the indirect conveyance and the discharge to surface water The map should also include the location and distance to the nearest sanitary sewer as well as the locus of nearby sensitive receptors (based on USGS topographical mapping), such as surface waters, drinking water supplies, and wetland areas.						
d) Provide the state water quality classification of the receiving water _____,						
e) Provide the reported or calculated seven day-ten year low flow (7Q10) of the receiving water _____ cfs Please attach any calculation sheets used to support stream flow and dilution calculations.						
f) Is the receiving water a listed 303(d) water quality impaired or limited water? Yes _____ No _____ If yes, for which pollutant(s)? Is there a TMDL? Yes _____ No _____ If yes, for which pollutant(s)?						

6. Results of Consultation with Federal Services: Please provide the following information according to requirements of Part I.B.4 and Appendices II and VII.

a) Are any listed threatened or endangered species, or designated critical habitat, in proximity to the discharge? Yes ___ No ☒
Has any consultation with the federal services been completed? Yes ☒ No ___ or is consultation underway? Yes ___ No ___
What were the results of the consultation with the U.S. Fish and Wildlife Service and/or National Marine Fisheries Service (check one): a "no jeopardy" opinion? ___ or written concurrence ☒ on a finding that the discharges are not likely to adversely affect any endangered species or critical habitat?
b) Are any historic properties listed or eligible for listing on the National Register of Historic Places located on the facility or site or in proximity to the discharge? Yes ___ No ☒ Have any state or tribal historic preservation officer been consulted in this determination (Massachusetts only)? Yes ☒ No ___

7. Supplemental information. :


Please provide any supplemental information. Attach any analytical data used to support the application. Attach any certification(s) required by the general permit.

8. Signature Requirements: The Notice of Intent must be signed by the operator in accordance with the signatory requirements of 40 CFR Section 122.22, including the following certification:

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, I certify that the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I certify that I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

Facility/Site Name: Taunton Municipal Lighting Plant

Operator signature:



WILLIAM L. NICKERSON

Title: Power Production Manager

Date: 10/13/09

FIGURES

NOTE: ALL LOCATIONS AND SCALE ARE APPROXIMATE



Dilution Calculations

**Taunton Municipal Lighting Plant
Remediation General Permit Notice of Intent
Dilution Calculation**

$$DF = (Q_d + Q_s) / Q_d$$

Where:

DF = Dilution Factor

Q_d = Maximum flow rate of the discharge (cfs)

Q_s = Receiving water 7Q₁₀ flow (cfs) where,

7Q₁₀ = The minimum flow (cfs) for 7 consecutive days with a recurrence interval of 10 years

Q_d = 0.44 cfs (200 gallons per minute (gpm))

Q_s = 24.6 cfs¹

$$DF = (0.44 + 24.6) / 0.44$$

$$DF = 25.04 / 0.44$$

$$DF = 56.91$$

Notes:

cfs = cubic feet per second

gpm = gallons per minute

1. Based on United States Geological Survey (USGS) stream flow statistics for the Taunton River near Bridgewater, Massachusetts (USGS 01108000),

located approximately 15 miles upstream of the proposed discharge location.

Minimum flow data from USGS 01108000 for period of record (1929-1976, 1985-1988, and 1996-1997).

Stream flow data derived from *Section 316(a) Demonstration Document, NPDES Permit No. MA0002241*, January 2004, prepared for Taunton Municipal Lighting Plant by Earth Tech, Inc., Concord, Massachusetts.

Estimated 7Q₁₀ at point of discharge is 37.7 cfs, yielding a dilution factor of 86.68.

Transmittal Form X230269



Enter your transmittal number

X230269

Transmittal Number

Your unique Transmittal Number can be accessed online: <http://mass.gov/dep/service/online/trasmfrm.shtml> or call MassDEP's InfoLine at 617-338-2255 or 800-462-0444 (from 508, 781, and 978 area codes).

Massachusetts Department of Environmental Protection

Transmittal Form for Permit Application and Payment

1. Please type or print. A separate Transmittal Form must be completed for each permit application.

2. Make your check payable to the Commonwealth of Massachusetts and mail it with a copy of this form to: DEP, P.O. Box 4062, Boston, MA 02211.

3. Three copies of this form will be needed.

Copy 1 - the original must accompany your permit application. **Copy 2** must accompany your fee payment. **Copy 3** should be retained for your records

4. Both fee-paying and exempt applicants must mail a copy of this transmittal form to:

MassDEP
P.O. Box 4062
Boston, MA
02211

*** Note:**
For BWSC Permits, enter the LSP.

A. Permit Information

BRP WM 12
1. Permit Code: 7 or 8 character code from permit instructions
Surface Water Discharge
2. Name of Permit Category
Discharge of water associated with fuel oil tank repair
3. Type of Project or Activity

B. Applicant Information – Firm or Individual

Moran Environmental Recovery
1. Name of Firm - Or, if party needing this approval is an individual enter name below:
2. Last Name of Individual
75-D York Avenue
3. First Name of Individual
4. MI
5. Street Address
Randolph
6. City/Town
John Silva
7. State
MA
8. Zip Code
02368
9. Telephone #
781-815-1100
10. Ext. #
11. Contact Person
12. e-mail address (optional)
jsilva@moranenvironmental.com

C. Facility, Site or Individual Requiring Approval

Taunton Municipal Lighting Plant
1. Name of Facility, Site Or Individual
1314 Somerset Avenue
2. Street Address
Taunton
3. City/Town
4. State
MA
5. Zip Code
02780
6. Telephone #
508-824-3159
7. Ext. #
8. DEP Facility Number (if Known)
9. Federal I.D. Number (if Known)
10. BWSC Tracking # (if Known)

D. Application Prepared by (if different from Section B)*

Horsley Witten Group, Inc.
1. Name of Firm Or Individual
90 Route 6A
2. Address
Sandwich
3. City/Town
Gary Hedman
4. State
MA
5. Zip Code
02563
6. Telephone #
508-833-6600
7. Ext. #
157
8. Contact Person
9. LSP Number (BWSC Permits only)

E. Permit - Project Coordination

1. Is this project subject to MEPA review? ☐ yes ☒ no
If yes, enter the project's EOE file number - assigned when an Environmental Notification Form is submitted to the MEPA unit:

EOEA File Number

F. Amount Due

Special Provisions:

- ☐ Fee Exempt (city, town or municipal housing authority)(state agency if fee is \$100 or less).
There are no fee exemptions for BWSC permits, regardless of applicant status.
- ☐ Hardship Request - payment extensions according to 310 CMR 4.04(3)(c).
- ☐ Alternative Schedule Project (according to 310 CMR 4.05 and 4.10).
- ☐ Homeowner (according to 310 CMR 4.02).

DEP Use Only

Permit No:

Rec'd Date:

Reviewer:

Check Number

Dollar Amount

Date

MORAN ENVIRONMENTAL RECOVERY, L.L.C.

Remittance Advice

Page 1 of 1

Check: 013028 Paid by: Moran Environmental Recovery
 Date: 10/08/09 Paid to: Commonwealth of Massachusetts
 Amount: 775.00

Our Account #:
 Vendor Code: COMMO3

Inv. Date	Invoice No.	Job Number	Inv. Amount	Discount	Amount Paid	Retention	Remarks
10/08/09	X230269	09RMSD0168	775.00	0.00	775.00	0.00	Permit Fee
Check Totals			775.00	0.00	775.00	0.00	

DETACH AND RETAIN THIS STATEMENT

REORDER FORM NO.524-LG1

USE WITH COMPANION ENVELOPE #40-224

WARNING: THIS DOCUMENT HAS A COLORED BACKGROUND, A MICROPRINT BORDER AND AN ARTIFICIAL WATERMARK ON THE BACK



MORAN ENVIRONMENTAL RECOVERY, L.L.C.
 75D YORK AVE.
 RANDOLPH, MA 02368

SOVEREIGN

5-7515
 0110

DATE
 10/08/09

CHECK NO.
 013028

013028

PAY **SEVEN HUNDRED SEVENTY-FIVE AND XX / 100 DOLLARS

\$

** 775.00

TO
 THE
 ORDER
 OF

Commonwealth of Massachusetts
 Dept of Env Protection
 P.O. Box 4062
 Boston, MA 02211

Edward W. Kennedy
 MORAN ENVIRONMENTAL RECOVERY, L.L.C.
 AUTHORIZED SIGNATURE
 VOID AFTER 90 DAYS

⑈013028⑈ ⑆011075150⑆ 10020804828⑈

Supporting Documentation


United States Environmental Protection Agency – Region 1
Office of Ecosystems Protection

*Taunton Municipal Lighting Plant Cleary-Flood Station
NPDES Permit Renewal Application - Supplemental Information Request:*

SECTION 316 (a) DEMONSTRATION DOCUMENT

NPDES Permit No. MA0002241

January 2004



Prepared For:



**Taunton Municipal Lighting Plant
Taunton, Massachusetts**

Prepared By:

**Earth Tech, Inc.
Concord, Massachusetts**

and

**Marine Research, Inc.
Falmouth, Massachusetts**

4.0 DESCRIPTION OF LOCAL ECOSYSTEM AFFECTED BY DISCHARGE

4.1 Taunton River Basin

4.1.1 *Description of the Physical and Chemical Environment*

4.1.1.1 *Physical Description*


The Taunton River basin, the largest watershed in southeastern Massachusetts, covering approximately 562 square miles, is the second largest basin in Massachusetts; only the Connecticut River Basin is larger (Bickford and Dymon, 1990). It is formed by the confluence of the Matfield and Town Rivers in Bridgewater and flows into Mount Hope Bay in the northeast corner of Narragansett Bay. Over 94 square miles of wetlands are found in the Taunton River basin including cranberry bogs, lakes and ponds. Major tributaries joining the Taunton upstream of TMLP include the Mill, Winnetuxet and Nemasket Rivers while the Three Mile River, Segreganset River and Assonet River converge with the Taunton downstream of the site (see Figure 4-1, Taunton River Basin). The river basin was shaped by glaciation, giving it a relatively flat topography, falling only 21 feet throughout its 38-mile course. Tidal fluctuations are present as far as 18 miles upstream of the river mouth.

4.1.1.2 *Hydrology*

Flow in the Taunton River in the vicinity of the Station is dominated by fluctuations in the tide. The river becomes tidal as it passes to the east of Taunton center. Further downstream at the Station, the difference between the estimated mean low and high tides in the Taunton River is about 4.2 feet (Woodlot Alternatives 2002).

Although no flow gaging information is available for the Taunton River at the Station, the estimated 7-day, 10-year (7Q10) low flow for the Taunton River at the Bridgewater gaging station, which is approximately 15 miles upstream from the Station and measures flow from a drainage area of 261 square miles, is 24.6 cubic feet per second (cfs) for the period of record from October 1929 to April 1976, April 1985 to May 1988, and October 1996 to 1997. Monthly mean flows are compared with the median flow and the 7Q10 flow for the period of record in Figure 4-2. Typically, the lowest river flows are experienced during the month of August and the highest during the month of March.

The Taunton River drainage area upstream of the Station is approximately 400 square miles. In order to derive estimated flow statistics for this location in the absence of gaging data, the 7Q10 flow at Bridgewater is multiplied by the ratio of the drainage area at the Station to the drainage area at the gaging station, which yields an




Date: 23 Dec 03 13:45:58 Tuesday
 /usr2/rmp/basin.map

Base map data supplied by MassGIS and RIGIS.



Figure 4 - 1
Taunton River Basin

Figure 4-2
Taunton River Flow at Bridgewater Gaging Station for Period of Record



estimated 7Q10 low flow and an average daily mean flow at TMLP of approximately 37.7 cfs, or 24.4 mgd, and 726 cfs, or 469 mgd, respectively. These estimated flows are compared with statistics for actual flows measured at the Bridgewater Gaging Station in Table 4-1.

Table 4-1: Estimates of Taunton River Flow at Station

Flow Statistic ¹	Taunton River at Station ²	Taunton River at Bridgewater Gaging Station
Average Daily Mean Flow (cfs)	726 (469 mgd)	473 (306 mgd) ^{3a}
Median Flow (cfs)	532 (344 mgd)	347 (224 mgd) ^{3b}
August Mean Flow (cfs)	233 (151 mgd)	152 (98 mgd) ^{3a}
7Q10 (cfs)	37.7 (24.4 mgd)	24.6 (15.9 mgd) ^{3b}
Unit 8 Average Daily Discharge ⁴ (cfs)	13 cfs (8.4 mgd)	n/a

¹ Based upon United States Geological Survey (USGS) stream flow statistics for the Taunton River near Bridgewater, Massachusetts (USGS 01108000)

² Estimate

^{3a} For period of record (1929-1976, 1985-1988, and 1996-2002)

^{3b} For period of record (1929-1976, 1985-1988, and 1996-1997)

⁴ NPDES DMR data for TMLP Station, March 1999 to March 2000

4.1.1.3 Water Quality

Taunton River water quality is affected by surface water inputs from its tributaries, groundwater inputs, and the tidal influence of Narragansett Bay. The Massachusetts Surface Water Quality Standards (MSWQS) provide classifications, based upon intended water use, for all inland, coastal, and marine surface waters of the state. As described in the MSWQS, the TMLP Station is located along a segment of the Taunton River that has a coastal and marine classification of "SB." SB waters are designated as a habitat for fish, other aquatic life and wildlife, and for primary and secondary contact recreation. While improvements have been realized in recent years, the Taunton River has suffered historically from poor water quality due to a variety of municipal and industrial wastewater discharges; there are currently 23 discharges to the river with a NPDES permit, including seven municipal sewage treatment plants (Epsilon, 1997). Additionally, the water quality of the Taunton River is recognized as being impacted by sources typically associated with urbanized watersheds, including combined sewer overflows (CSOs), septic tank seepage, and storm drain runoff (DWPC, 1981).

Although recent studies (Epsilon, 1997) suggest that the river is essentially freshwater under most tidal and flow regimes in the vicinity of the TMLP Discharge Channel, historical data from July 1970 (DWPC, 1973) indicates that significant

Laboratory Analytical Results

Groundwater Analytical, Inc.
P.O.Box 1200
228 Main Street
Buzzards Bay, MA 02532

Telephone: (508) 759-4441
FAX: (508) 759-4475

**GROUNDWATER
ANALYTICAL**

e-mail

To:	Gary Hedman	From:	e-mail reporting GWA
	Horsley & Witten, Inc.	Pages:	51
e-mail:	ghedman@horsleywitten.	Date:	10/06/2009 17:06:40
Re:	128435	CC:	
☐ Urgent	☐ For Review	☐ Please Comment	☐ Please Reply

● Comments:

Final Project Report for Taunton NPDES/9073, Lab ID 128435, Received
09-30-09

This document is intended only for the use of the person to whom it is addressed. It may contain information that is privileged, confidential and exempt from disclosure under applicable law. If you are not the intended recipient, any dissemination, distribution, copying or use of this document is strictly prohibited. If you have received this communication in error, please notify us by telephone at (508) 759-4441 to arrange for the destruction or return of the original document to us.

Confidential

October 6, 2009

Mr. Gary Hedman
Horsley & Witten, Inc.
90 Route 6A (Tutor Hill)
Sextant Hill
Sandwich, MA 02563

LABORATORY REPORT

Project: **Taunton NPDES/9073**
Lab ID: **128435**
Received: **09-30-09**

Dear Gary:

Enclosed are the analytical results for the above referenced project. The project was processed for Rush 4 Business Day turnaround.

This letter authorizes the release of the analytical results, and should be considered a part of this report. This report contains a sample receipt report detailing the samples received, a project narrative indicating project changes and non-conformances, a quality control report, and a statement of our state certifications.

The analytical results contained in this report meet all applicable NELAC or NVLAP standards, except as may be specifically noted, or described in the project narrative. The analytical results relate only to the samples received. This report may only be used or reproduced in its entirety.

I attest under the pains and penalties of perjury that, based upon my inquiry of those individuals immediately responsible for obtaining the information, the material contained in this report is, to the best of my knowledge and belief, accurate and complete.

Should you have any questions concerning this report, please do not hesitate to contact me.

Sincerely,



Karyn E. Raymond
Project Manager

KER/kh
Enclosures

Sample Receipt Report

Project: **Taunton NPDES/9073**
 Client: **Horsley & Witten, Inc.**
 Lab ID: **128435**

Delivery: **Hand**
 Airbill: **n/a**
 Lab Receipt: **09-30-09**

Temperature: **5.6°C**
 Chain of Custody: **Present**
 Custody Seal(s): **n/a**

Lab ID	Field ID		Matrix	Sampled	Method				Notes
128435-1	Discharge		Aqueous	9/30/09 10:20	EPA 8260B Volatile Organics with Oxygenates				
Con ID	Container	Vendor	QC Lot	Preserv	QC Lot	Prep	Ship		
C1226338	40 mL VOA Vial	Proline	BX34631	HCL	R-5885B	09-17-09	n/a		
C1226337	40 mL VOA Vial	Proline	BX34631	HCL	R-5885B	09-17-09	n/a		
C1226336	40 mL VOA Vial	Proline	BX34631	HCL	R-5885B	09-17-09	n/a		

Lab ID	Field ID		Matrix	Sampled	Method				Notes
128435-2	Source		Aqueous	9/30/09 11:00	EPA 8260B Volatile Organics with Oxygenates				
Con ID	Container	Vendor	QC Lot	Preserv	QC Lot	Prep	Ship		
C1226329	40 mL VOA Vial	Proline	BX34631	HCL	R-5885B	09-17-09	n/a		
C1226328	40 mL VOA Vial	Proline	BX34631	HCL	R-5885B	09-17-09	n/a		
C1226327	40 mL VOA Vial	Proline	BX34631	HCL	R-5885B	09-17-09	n/a		

Lab ID	Field ID		Matrix	Sampled	Method				Notes
128435-3	Discharge		Aqueous	9/30/09 10:20	EPA 8011 EDB and DBCP by GC/ECD				
Con ID	Container	Vendor	QC Lot	Preserv	QC Lot	Prep	Ship		
C1222309	40 mL VOA Vial	Proline	BX34888	None	n/a	n/a	n/a		
C1222308	40 mL VOA Vial	Proline	BX34888	None	n/a	n/a	n/a		
C1222307	40 mL VOA Vial	Proline	BX34888	None	n/a	n/a	n/a		

Lab ID	Field ID		Matrix	Sampled	Method				Notes
128435-4	Source		Aqueous	9/30/09 11:00	EPA 8011 EDB and DBCP by GC/ECD				
Con ID	Container	Vendor	QC Lot	Preserv	QC Lot	Prep	Ship		
C1222306	40 mL VOA Vial	Proline	BX34888	None	n/a	n/a	n/a		
C1222305	40 mL VOA Vial	Proline	BX34888	None	n/a	n/a	n/a		
C1222304	40 mL VOA Vial	Proline	BX34888	None	n/a	n/a	n/a		

Lab ID	Field ID		Matrix	Sampled	Method				Notes
128435-5	Discharge		Aqueous	9/30/09 10:20	EPA 8270C Semivolatile Organics (Low Level)				
Con ID	Container	Vendor	QC Lot	Preserv	QC Lot	Prep	Ship		
C1242821	1 L Amber Glass	Proline	BX34758	None	n/a	n/a	n/a		
C1242818	1 L Amber Glass	Proline	BX34758	None	n/a	n/a	n/a		

Lab ID	Field ID		Matrix	Sampled	Method				Notes
128435-6	Source		Aqueous	9/30/09 11:00	EPA 8270C Semivolatile Organics (Low Level)				
Con ID	Container	Vendor	QC Lot	Preserv	QC Lot	Prep	Ship		
C1238144	1 L Amber Glass	n/a	n/a	None	n/a	n/a	n/a		
C1238143	1 L Amber Glass	n/a	n/a	None	n/a	n/a	n/a		
C1238142	1 L Amber Glass	n/a	n/a	None	n/a	n/a	n/a		

Lab ID	Field ID		Matrix	Sampled	Method				Notes
128435-7	Discharge		Aqueous	9/30/09 10:20	EPA 608 PCBs				
Con ID	Container	Vendor	QC Lot	Preserv	QC Lot	Prep	Ship		
C1242820	1 L Amber Glass	Proline	BX34758	None	n/a	n/a	n/a		
C1242819	1 L Amber Glass	Proline	BX34758	None	n/a	n/a	n/a		

Lab ID	Field ID		Matrix	Sampled	Method				Notes
128435-8	Source		Aqueous	9/30/09 11:00	EPA 608 PCBs				
Con ID	Container	Vendor	QC Lot	Preserv	QC Lot	Prep	Ship		
C1242822	1 L Amber Glass	Proline	BX34758	None	n/a	n/a	n/a		
C1242817	1 L Amber Glass	Proline	BX34758	None	n/a	n/a	n/a		

Sample Receipt Report (Continued)

Project: **Taunton NPDES/9073**
 Client: **Horsley & Witten, Inc.**
 Lab ID: **128435**

Delivery: **Hand**
 Airbill: **n/a**
 Lab Receipt: **09-30-09**

Temperature: **5.6°C**
 Chain of Custody: **Present**
 Custody Seal(s): **n/a**

Lab ID	Field ID		Matrix	Sampled	Method				Notes
128435-9	Discharge		Aqueous	9/30/09 10:20	TPH by GC EPA 8015B Mod				
Con ID	Container	Vendor	QC Lot	Preserv	QC Lot	Prep	Ship		
C1242610	1 L Amber Glass	Proline	BX34732	H2SO4	R-5914A	09-22-09	n/a		
C1242607	1 L Amber Glass	Proline	BX34732	H2SO4	R-5914A	09-22-09	n/a		

Lab ID	Field ID		Matrix	Sampled	Method				Notes
128435-10	Source		Aqueous	9/30/09 11:00	TPH by GC EPA 8015B Mod				
Con ID	Container	Vendor	QC Lot	Preserv	QC Lot	Prep	Ship		
C1242615	1 L Amber Glass	Proline	BX34732	H2SO4	R-5914A	09-22-09	n/a		
C1242613	1 L Amber Glass	Proline	BX34732	H2SO4	R-5914A	09-22-09	n/a		

Lab ID	Field ID		Matrix	Sampled	Method				Notes
128435-11	Discharge		Aqueous	9/30/09 10:20	SM 4500-Cl G Total Residual Chlorine SM 3500-Cr D Hexavalent Chromium SM 2540 D Total Suspended Solids				
Con ID	Container	Vendor	QC Lot	Preserv	QC Lot	Prep	Ship		
C1239670	1 L Plastic	Proline	BX34674	None	n/a	n/a	n/a		

Lab ID	Field ID		Matrix	Sampled	Method				Notes
128435-12	Source		Aqueous	9/30/09 11:00	SM 4500-Cl G Total Residual Chlorine SM 3500-Cr D Hexavalent Chromium SM 2540 D Total Suspended Solids				
Con ID	Container	Vendor	QC Lot	Preserv	QC Lot	Prep	Ship		
C1239539	1 L Plastic	Proline	BX34673	None	n/a	n/a	n/a		

Lab ID	Field ID		Matrix	Sampled	Method				Notes
128435-13	Discharge		Aqueous	9/30/09 10:20	Lachat 10-204-00-1-A (EPA 335.3) Total Cyanide				
Con ID	Container	Vendor	QC Lot	Preserv	QC Lot	Prep	Ship		
C1185603	500 mL Plastic	Proline	BX33920	NaOH	R-5945B	09-25-09	n/a		

Lab ID	Field ID		Matrix	Sampled	Method				Notes
128435-14	Source		Aqueous	9/30/09 11:00	Lachat 10-204-00-1-A (EPA 335.3) Total Cyanide				
Con ID	Container	Vendor	QC Lot	Preserv	QC Lot	Prep	Ship		
C1185533	500 mL Plastic	Proline	BX33920	NaOH	n/a	n/a	n/a		

Lab ID	Field ID		Matrix	Sampled	Method				Notes
128435-15	Discharge		Aqueous	9/30/09 10:20	EPA 200.7 Ag Cd Cr Cu Fe Ni Se Zn Total EPA 200.8 As Pb Sb Total EPA 245.1 Hg Total				
Con ID	Container	Vendor	QC Lot	Preserv	QC Lot	Prep	Ship		
C1170218	250 mL Plastic	Proline	BX33982	HNO3	R-5913A	09-04-09	n/a		

Lab ID	Field ID		Matrix	Sampled	Method				Notes
128435-16	Source		Aqueous	9/30/09 11:00	EPA 200.7 Ag Cd Cr Cu Fe Ni Se Zn Total EPA 200.8 As Pb Sb Total EPA 245.1 Hg Total				
Con ID	Container	Vendor	QC Lot	Preserv	QC Lot	Prep	Ship		
C1170251	250 mL Plastic	Proline	BX33982	HNO3	R-5913A	09-04-09	n/a		

Data Certification

Project: **Taunton NPDES/9073**
Client: **Horsley & Witten, Inc.**

Lab ID: **128435**
Received: **09-30-09 12:45**

MA DEP Compendium of Analytical Methods					
Project Location: n/a		MA DEP RTN: n/a			
This Form provides certifications for the following data set:					
EPA 8260B:		128435-1,-2			
EPA 8270C:		128435-5,-6			
Sample Matrices:		Groundwater (X)	Soil/Sediment ()	Drinking Water ()	Other ()
MCP SW-846	8260B (X)	8151A ()	8330 ()	6010B ()	7470A/1A ()
Methods Used	8270C (X)	8081A ()	VPH ()	6020A ()	9012A ² ()
As specified in MA DEP Compendium of Analytical Methods.	8082 ()	8021B ()	EPH ()	7000 S ³ ()	Other ()
(check all that apply)	1. List Release Tracking Number (RTN), if known.				
	2. SW-846 Method 9012A (Equivalent to 9014) or MA DEP Physiologically Available Cyanide (PAC) Method				
	3. S - SW-846 Methods 7000 Series. List individual method and analyte.				
An affirmative response to questions A, B, C and D is required for "Presumptive Certainty" status.					
A.	Were all samples received by the laboratory in a condition consistent with that described on the Chain-of-Custody documentation for the data set?				Yes
B.	Were all QA/QC procedures required for the specified analytical method(s) included in this report followed, including the requirement to note and discuss in a narrative QC data that did not meet appropriate performance standards or guidelines?				Yes
C.	Does the analytical data included in this report meet all the requirements for "Presumptive Certainty," as described in Section 2.0 of the MA DEP document CAM VII A, <i>Quality Assurance and Quality Control Guidelines for the Acquisition and Reporting of Analytical Data</i> ?				Yes
D.	VPH and EPH methods only: Was the VPH or EPH method run without significant modifications, as specified in Section 11.3?				n/a
A response to questions E and F below is required for "Presumptive Certainty" status.					
E.	Were all QC performance standards and recommendations for the specified methods achieved?				No
F.	Were results for all analyte-list compounds/elements for the specified method(s) reported?				Yes
All No answers are addressed in the attached Project Narrative.					
I, the undersigned, attest under the pains and penalties of perjury that, based upon my personal inquiry of those responsible for obtaining the information, the material contained in this analytical report is, to the best of my knowledge and belief, accurate and complete.					
Signature:		Position: Project Manager			
Printed Name: <i>Karyn E. Raymond</i>		Date: 10-06-09			

EPA Method 8260B Volatile Organics by GC/MS

Field ID: Discharge
Project: Taunton NPDES/9073
Client: Horsley & Witten, Inc.

Laboratory ID: 128435-1
Sampled: 09-30-09 10:20
Received: 09-30-09 12:45
Analyzed: 10-01-09 10:32
Analyst: LMG

Matrix: Aqueous
Container: 40 mL VOA Vial
Preservation: HCl/ Cool

QC Batch ID: VM7-3269-W
Instrument ID: MS-7 HP 6890
Sample Volume: 25 mL
Dilution Factor: 50

Page: 1 of 2

CAS Number	Analyte	Concentration	Notes	Units	Reporting Limit
75-71-8	Dichlorodifluoromethane	BRL		ug/L	25
74-87-3	Chloromethane	BRL		ug/L	25
75-01-4	Vinyl Chloride	BRL		ug/L	25
74-83-9	Bromomethane	BRL		ug/L	25
75-00-3	Chloroethane	BRL		ug/L	25
75-69-4	Trichlorofluoromethane	BRL		ug/L	25
60-29-7	Diethyl Ether	BRL		ug/L	100
75-35-4	1,1-Dichloroethene	BRL		ug/L	25
76-13-1	1,1,2-Trichlorotrifluoroethane	BRL		ug/L	250
67-64-1	Acetone	BRL		ug/L	500
75-15-0	Carbon Disulfide	BRL		ug/L	250
75-09-2	Methylene Chloride	BRL		ug/L	130
107-13-1	Acrylonitrile	BRL		ug/L	25
156-60-5	trans- 1,2-Dichloroethene	BRL		ug/L	25
1634-04-4	Methyl tert- butyl Ether (MTBE)	2,800		ug/L	25
75-34-3	1,1-Dichloroethane	BRL		ug/L	25
594-20-7	2,2-Dichloropropane	BRL		ug/L	25
156-59-2	cis- 1,2-Dichloroethene	BRL		ug/L	25
78-93-3	2-Butanone (MEK)	BRL		ug/L	250
74-97-5	Bromochloromethane	BRL		ug/L	25
109-99-9	Tetrahydrofuran (THF)	BRL		ug/L	250
67-66-3	Chloroform	BRL		ug/L	25
71-55-6	1,1,1-Trichloroethane	BRL		ug/L	25
56-23-5	Carbon Tetrachloride	BRL		ug/L	25
563-58-6	1,1-Dichloropropene	BRL		ug/L	25
71-43-2	Benzene	180		ug/L	25
107-06-2	1,2-Dichloroethane	BRL		ug/L	25
79-01-6	Trichloroethene	BRL		ug/L	25
78-87-5	1,2-Dichloropropane	BRL		ug/L	25
74-95-3	Dibromomethane	BRL		ug/L	25
75-27-4	Bromodichloromethane	BRL		ug/L	25
123-91-1	1,4-Dioxane	BRL		ug/L	25,000
10061-01-5	cis- 1,3-Dichloropropene	BRL		ug/L	20
108-10-1	4-Methyl-2-Pentanone (MIBK)	BRL		ug/L	250
108-88-3	Toluene	670		ug/L	25
10061-02-6	trans- 1,3-Dichloropropene	BRL		ug/L	20
79-00-5	1,1,2-Trichloroethane	BRL		ug/L	25
127-18-4	Tetrachloroethene	BRL		ug/L	25
142-28-9	1,3-Dichloropropane	BRL		ug/L	25
591-78-6	2-Hexanone	BRL		ug/L	250
124-48-1	Dibromochloromethane	BRL		ug/L	25
106-93-4	1,2-Dibromoethane (EDB)	BRL		ug/L	25
108-90-7	Chlorobenzene	BRL		ug/L	25
630-20-6	1,1,1,2-Tetrachloroethane	BRL		ug/L	25
100-41-4	Ethylbenzene	160		ug/L	25
108-38-3/106-42-3	meta- Xylene and para- Xylene	530		ug/L	25

EPA Method 8260B (Continued) Volatile Organics by GC/MS

Field ID: Discharge
Project: Taunton NPDES/9073
Client: Horsley & Witten, Inc.

Laboratory ID: 128435-1RA1
Sampled: 09-30-09 10:20
Received: 09-30-09 12:45
Analyzed: 10-01-09 10:32
Analyst: LMG

Matrix: Aqueous
Container: 40 mL VOA Vial
Preservation: HCl/ Cool

QC Batch ID: VM7-3269-W
Instrument ID: MS-7 HP 6890
Sample Volume: 25 mL
Dilution Factor: 50

Page: 2 of 2

CAS Number	Analyte	Concentration	Notes	Units	Reporting Limit
95-47-6	<i>ortho</i> -Xylene	290		ug/L	25
100-42-5	Styrene	BRL		ug/L	25
75-25-2	Bromoform	BRL		ug/L	25
98-82-8	Isopropylbenzene	26		ug/L	25
108-86-1	Bromobenzene	BRL		ug/L	25
79-34-5	1,1,2,2-Tetrachloroethane	BRL		ug/L	25
96-18-4	1,2,3-Trichloropropane	BRL		ug/L	25
110-57-6	<i>trans</i> -1,4-Dichloro-2-butene	BRL		ug/L	1,300
103-65-1	<i>n</i> -Propylbenzene	48		ug/L	25
95-49-8	2-Chlorotoluene	BRL		ug/L	25
108-67-8	1,3,5-Trimethylbenzene	84		ug/L	25
106-43-4	4-Chlorotoluene	BRL		ug/L	25
98-06-6	<i>tert</i> -Butylbenzene	BRL		ug/L	25
95-63-6	1,2,4-Trimethylbenzene	340		ug/L	25
135-98-8	<i>sec</i> -Butylbenzene	BRL		ug/L	25
541-73-1	1,3-Dichlorobenzene	BRL		ug/L	25
99-87-6	4-Isopropyltoluene	BRL		ug/L	25
106-46-7	1,4-Dichlorobenzene	BRL		ug/L	25
95-50-1	1,2-Dichlorobenzene	BRL		ug/L	25
104-51-8	<i>n</i> -Butylbenzene	BRL		ug/L	25
96-12-8	1,2-Dibromo-3-chloropropane	BRL		ug/L	25
108-70-3	1,3,5-Trichlorobenzene	BRL		ug/L	25
120-82-1	1,2,4-Trichlorobenzene	BRL		ug/L	25
87-68-3	Hexachlorobutadiene	BRL		ug/L	25
91-20-3	Naphthalene	650		ug/L	25
87-61-6	1,2,3-Trichlorobenzene	BRL		ug/L	25
75-65-0	<i>tert</i> -Butyl Alcohol (TBA)	BRL		ug/L	1,000
108-20-3	Di-isopropyl Ether (DIPE)	BRL		ug/L	25
637-92-3	Ethyl <i>tert</i> -butyl Ether (ETBE)	BRL		ug/L	25
994-05-8	<i>tert</i> -Amyl Methyl Ether (TAME)	270		ug/L	25

QC Surrogate Compound	Spiked	Measured	Recovery	QC Limits
Dibromofluoromethane	10	10	98 %	70 - 130 %
1,2-Dichloroethane-d ₄	10	9	93 %	70 - 130 %
Toluene-d ₈	10	10	95 %	70 - 130 %
4-Bromofluorobenzene	10	9	95 %	70 - 130 %

Method Reference: Test Methods for Evaluating Solid Waste, US EPA, SW-846, Third Edition, Update III (1996).
Sample preparation performed by EPA Method 5030B.

Report Notations: BRL Indicates concentration, if any, is below reporting limit for analyte. Reporting limit is the lowest concentration that can be reliably quantified under routine laboratory operating conditions. Reporting limits are adjusted for sample size and dilution.

EPA Method 8260B Volatile Organics by GC/MS

Field ID: Source
Project: Taunton NPDES/9073
Client: Horsley & Witten, Inc.

Laboratory ID: 128435-2
Sampled: 09-30-09 11:00
Received: 09-30-09 12:45
Analyzed: 10-01-09 11:08
Analyst: LMG

Matrix: Aqueous
Container: 40 mL VOA Vial
Preservation: HCl/ Cool

QC Batch ID: VM7-3269-W
Instrument ID: MS-7 HP 6890
Sample Volume: 25 mL
Dilution Factor: 1

Page: 1 of 2

CAS Number	Analyte	Concentration	Notes	Units	Reporting Limit
75-71-8	Dichlorodifluoromethane	BRL		ug/L	0.5
74-87-3	Chloromethane	BRL		ug/L	0.5
75-01-4	Vinyl Chloride	BRL		ug/L	0.5
74-83-9	Bromomethane	BRL		ug/L	0.5
75-00-3	Chloroethane	BRL		ug/L	0.5
75-69-4	Trichlorofluoromethane	BRL		ug/L	0.5
60-29-7	Diethyl Ether	BRL		ug/L	2
75-35-4	1,1-Dichloroethene	BRL		ug/L	0.5
76-13-1	1,1,2-Trichlorotrifluoroethane	BRL		ug/L	5
67-64-1	Acetone	BRL		ug/L	10
75-15-0	Carbon Disulfide	BRL		ug/L	5
75-09-2	Methylene Chloride	BRL		ug/L	3
107-13-1	Acrylonitrile	BRL		ug/L	0.5
156-60-5	<i>trans</i> - 1,2-Dichloroethene	BRL		ug/L	0.5
1634-04-4	Methyl <i>tert</i> - butyl Ether (MTBE)	BRL		ug/L	0.5
75-34-3	1,1-Dichloroethane	BRL		ug/L	0.5
594-20-7	2,2-Dichloropropane	BRL		ug/L	0.5
156-59-2	<i>cis</i> - 1,2-Dichloroethene	BRL		ug/L	0.5
78-93-3	2-Butanone (MEK)	BRL		ug/L	5
74-97-5	Bromochloromethane	BRL		ug/L	0.5
109-99-9	Tetrahydrofuran (THF)	BRL		ug/L	5
67-66-3	Chloroform	36		ug/L	0.5
71-55-6	1,1,1-Trichloroethane	BRL		ug/L	0.5
56-23-5	Carbon Tetrachloride	BRL		ug/L	0.5
563-58-6	1,1-Dichloropropene	BRL		ug/L	0.5
71-43-2	Benzene	BRL		ug/L	0.5
107-06-2	1,2-Dichloroethane	BRL		ug/L	0.5
79-01-6	Trichloroethene	BRL		ug/L	0.5
78-87-5	1,2-Dichloropropane	BRL		ug/L	0.5
74-95-3	Dibromomethane	BRL		ug/L	0.5
75-27-4	Bromodichloromethane	8		ug/L	0.5
123-91-1	1,4-Dioxane	BRL		ug/L	500
10061-01-5	<i>cis</i> - 1,3-Dichloropropene	BRL		ug/L	0.4
108-10-1	4-Methyl-2-Pentanone (MIBK)	BRL		ug/L	5
108-88-3	Toluene	BRL		ug/L	0.5
10061-02-6	<i>trans</i> - 1,3-Dichloropropene	BRL		ug/L	0.4
79-00-5	1,1,2-Trichloroethane	BRL		ug/L	0.5
127-18-4	Tetrachloroethene	BRL		ug/L	0.5
142-28-9	1,3-Dichloropropane	BRL		ug/L	0.5
591-78-6	2-Hexanone	BRL		ug/L	5
124-48-1	Dibromochloromethane	0.8		ug/L	0.5
106-93-4	1,2-Dibromoethane (EDB)	BRL		ug/L	0.5
108-90-7	Chlorobenzene	BRL		ug/L	0.5
630-20-6	1,1,1,2-Tetrachloroethane	BRL		ug/L	0.5
100-41-4	Ethylbenzene	BRL		ug/L	0.5
108-38-3/106-42-3	<i>meta</i> - Xylene and <i>para</i> - Xylene	BRL		ug/L	0.5

EPA Method 8260B (Continued) Volatile Organics by GC/MS

Field ID: Source
Project: Taunton NPDES/9073
Client: Horsley & Witten, Inc.

Laboratory ID: 128435-2RA1
Sampled: 09-30-09 11:00
Received: 09-30-09 12:45
Analyzed: 10-01-09 11:08
Analyst: LMG

Matrix: Aqueous
Container: 40 mL VOA Vial
Preservation: HCl/ Cool

QC Batch ID: VM7-3269-W
Instrument ID: MS-7 HP 6890
Sample Volume: 25 mL
Dilution Factor: 1

Page: 2 of 2

CAS Number	Analyte	Concentration	Notes	Units	Reporting Limit
95-47-6	ortho-Xylene	BRL		ug/L	0.5
100-42-5	Styrene	BRL		ug/L	0.5
75-25-2	Bromoform	BRL		ug/L	0.5
98-82-8	Isopropylbenzene	BRL		ug/L	0.5
108-86-1	Bromobenzene	BRL		ug/L	0.5
79-34-5	1,1,2,2-Tetrachloroethane	BRL		ug/L	0.5
96-18-4	1,2,3-Trichloropropane	BRL		ug/L	0.5
110-57-6	trans-1,4-Dichloro-2-butene	BRL		ug/L	25
103-65-1	n-Propylbenzene	BRL		ug/L	0.5
95-49-8	2-Chlorotoluene	BRL		ug/L	0.5
108-67-8	1,3,5-Trimethylbenzene	BRL		ug/L	0.5
106-43-4	4-Chlorotoluene	BRL		ug/L	0.5
98-06-6	tert-Butylbenzene	BRL		ug/L	0.5
95-63-6	1,2,4-Trimethylbenzene	BRL		ug/L	0.5
135-98-8	sec-Butylbenzene	BRL		ug/L	0.5
541-73-1	1,3-Dichlorobenzene	BRL		ug/L	0.5
99-87-6	4-Isopropyltoluene	BRL		ug/L	0.5
106-46-7	1,4-Dichlorobenzene	BRL		ug/L	0.5
95-50-1	1,2-Dichlorobenzene	BRL		ug/L	0.5
104-51-8	n-Butylbenzene	BRL		ug/L	0.5
96-12-8	1,2-Dibromo-3-chloropropane	BRL		ug/L	0.5
108-70-3	1,3,5-Trichlorobenzene	BRL		ug/L	0.5
120-82-1	1,2,4-Trichlorobenzene	BRL		ug/L	0.5
87-68-3	Hexachlorobutadiene	BRL		ug/L	0.5
91-20-3	Naphthalene	BRL		ug/L	0.5
87-61-6	1,2,3-Trichlorobenzene	BRL		ug/L	0.5
75-65-0	tert-Butyl Alcohol (TBA)	BRL		ug/L	20
108-20-3	Di-isopropyl Ether (DIPE)	BRL		ug/L	0.5
637-92-3	Ethyl tert-butyl Ether (ETBE)	BRL		ug/L	0.5
994-05-8	tert-Amyl Methyl Ether (TAME)	BRL		ug/L	0.5

QC Surrogate Compound	Spiked	Measured	Recovery	QC Limits
Dibromofluoromethane	10	9	95 %	70 - 130 %
1,2-Dichloroethane-d ₄	10	10	97 %	70 - 130 %
Toluene-d ₈	10	9	89 %	70 - 130 %
4-Bromofluorobenzene	10	9	93 %	70 - 130 %

Method Reference: Test Methods for Evaluating Solid Waste, US EPA, SW-846, Third Edition, Update III (1996).
Sample preparation performed by EPA Method 5030B.

Report Notations: BRL Indicates concentration, if any, is below reporting limit for analyte. Reporting limit is the lowest concentration that can be reliably quantified under routine laboratory operating conditions. Reporting limits are adjusted for sample size and dilution.

**EPA Method 8011
EDB and DBCP by GC/ECD**

Field ID: Discharge
Project: Taunton NPDES/9073
Client: Horsley & Witten, Inc.

Laboratory ID: 128435-03
Sampled: 09-30-09 10:20
Received: 09-30-09 12:45
Extracted: 10-01-09 17:00
Analyzed: 10-01-09 18:43
Analyst: AWG

Matrix: Aqueous
Container: 40 mL VOA Vial
Preservation: Cool

QC Batch ID: PV-0970-E
Instrument ID: GC-5 HP 5890
Sample Volume: 36 mL
Final Volume: 2 mL
Dilution Factor: 1

CAS Number	Analyte	Concentration	Notes	Units	Reporting Limit
106-93-4	1,2-Dibromoethane (EDB)	BRL		ug/L	0.02
96-12-8	1,2-Dibromo-3-Chloropropane (DBCP)	BRL		ug/L	0.02

Method Reference: Test Methods for Evaluating Solid Waste, US EPA, SW-846, Third Edition, Update III (1996).

Report Notations: BRL Indicates concentration, if any, is below reporting limit for analyte. Reporting limit is the lowest concentration that can be reliably quantified under routine laboratory operating conditions. Reporting limits are adjusted for sample size and dilution.

**EPA Method 8011
EDB and DBCP by GC/ECD**

Field ID: Source
Project: Taunton NPDES/9073
Client: Horsley & Witten, Inc.
Laboratory ID: 128435-04
Sampled: 09-30-09 11:00
Received: 09-30-09 12:45
Extracted: 10-01-09 17:00
Analyzed: 10-01-09 19:13
Analyst: AWG

Matrix: Aqueous
Container: 40 mL VOA Vial
Preservation: Cool
QC Batch ID: PV-0970-E
Instrument ID: GC-5 HP 5890
Sample Volume: 35 mL
Final Volume: 2 mL
Dilution Factor: 1

CAS Number	Analyte	Concentration	Notes	Units	Reporting Limit
106-93-4	1,2-Dibromoethane (EDB)	BRL		ug/L	0.02
96-12-8	1,2-Dibromo-3-Chloropropane (DBCP)	BRL		ug/L	0.02

Method Reference: Test Methods for Evaluating Solid Waste, US EPA, SW-846, Third Edition, Update III (1996).

Report Notations: BRL Indicates concentration, if any, is below reporting limit for analyte. Reporting limit is the lowest concentration that can be reliably quantified under routine laboratory operating conditions. Reporting limits are adjusted for sample size and dilution.

EPA Method 8270C Semivolatile Organics by GC/MS (Part 1)

Field ID: Discharge
Project: Taunton NPDES / 9073
Client: Horsley & Witten, Inc.

Laboratory ID: 128435-5
Sampled: 09-30-09 10:20
Received: 09-30-09 12:45
Extracted: 10-02-09 13:30
Analyzed: 10-05-09 17:25
Analyst: MJB

Matrix: Aqueous
Container: 1 L Amber Glass
Preservation: Cool

QC Batch ID: SV-2429-F
Instrument ID: MS-3 HP 5890
Sample Volume: 1,000 mL
Final Volume: 1 mL
Dilution Factor: 10

Page: 1 of 2

CAS Number	Analyte	Concentration	Notes	Units	Reporting Limit
62-75-9	N-Nitrosodimethylamine	BRL		ug/L	50
110-86-1	Pyridine	BRL		ug/L	50
108-95-2	Phenol	98		ug/L	50
62-53-3	Aniline	250		ug/L	50
111-44-4	Bis(2-chloroethyl) ether	BRL		ug/L	50
95-57-8	2-Chlorophenol	BRL		ug/L	50
541-73-1	1,3-Dichlorobenzene	BRL		ug/L	50
106-46-7	1,4-Dichlorobenzene	BRL		ug/L	50
100-51-6	Benzyl Alcohol	BRL		ug/L	50
95-50-1	1,2-Dichlorobenzene	BRL		ug/L	50
95-48-7	2-Methylphenol	630		ug/L	50
108-60-1	Bis(2-chloroisopropyl) ether	BRL		ug/L	50
108-39-4/106-44-5	3 and 4-Methylphenol *	130		ug/L	50
621-64-7	N-Nitrosodi-n-propylamine	BRL		ug/L	50
98-86-2	Acetophenone	BRL		ug/L	50
67-72-1	Hexachloroethane	BRL		ug/L	50
98-95-3	Nitrobenzene	BRL		ug/L	50
78-59-1	Isophorone	BRL		ug/L	50
88-75-5	2-Nitrophenol	BRL		ug/L	50
105-67-9	2,4-Dimethylphenol	150		ug/L	50
111-91-1	Bis(2-chloroethoxy) methane	BRL		ug/L	50
120-83-2	2,4-Dichlorophenol	BRL		ug/L	50
120-82-1	1,2,4-Trichlorobenzene	BRL		ug/L	50
106-47-8	4-Chloroaniline	BRL		ug/L	50
87-68-3	Hexachlorobutadiene	BRL		ug/L	50
59-50-7	4-Chloro-3-methylphenol	BRL		ug/L	50
77-47-4	Hexachlorocyclopentadiene	BRL		ug/L	50
88-06-2	2,4,6-Trichlorophenol	BRL		ug/L	50
95-95-4	2,4,5-Trichlorophenol	BRL		ug/L	50
91-58-7	2-Chloronaphthalene	BRL		ug/L	50
88-74-4	2-Nitroaniline	BRL		ug/L	50
100-25-4	1,4-Dinitrobenzene	BRL		ug/L	50
131-11-3	Dimethyl phthalate	BRL		ug/L	50
99-65-0	1,3-Dinitrobenzene	BRL		ug/L	50
606-20-2	2,6-Dinitrotoluene	BRL		ug/L	50
528-29-0	1,2-Dinitrobenzene	BRL		ug/L	50
99-09-2	3-Nitroaniline	BRL		ug/L	50
51-28-5	2,4-Dinitrophenol	BRL		ug/L	50
100-02-7	4-Nitrophenol	BRL		ug/L	50
132-64-9	Dibenzofuran	BRL		ug/L	50
121-14-2	2,4-Dinitrotoluene	BRL		ug/L	50
84-66-2	Diethyl phthalate	BRL		ug/L	50
7005-72-3	4-Chlorophenyl phenyl ether	BRL		ug/L	50
100-01-6	4-Nitroaniline	BRL		ug/L	50
534-52-1	4,6-Dinitro-2-methylphenol	BRL		ug/L	50

**EPA Method 8270C (Continued)
Semivolatile Organics by GC/MS (Part 1)**

Field ID: **Discharge**
Project: **Taunton NPDES / 9073**
Client: **Horsley & Witten, Inc.**

Matrix: **Aqueous**
Container: **1 L Amber Glass**
Preservation: **Cool**

Laboratory ID: **128435-5**
Sampled: **09-30-09 10:20**
Received: **09-30-09 12:45**
Extracted: **10-02-09 13:30**
Analyzed: **10-05-09 17:25**
Analyst: **MJB**

QC Batch ID: **SV-2429-F**
Instrument ID: **MS-3 HP 5890**
Sample Volume: **1,000 mL**
Final Volume: **1 mL**
Dilution Factor: **10**

Page: 2 of 2

CAS Number	Analyte	Concentration	Notes	Units	Reporting Limit
86-30-6	N-Nitrosodiphenylamine [†]	BRL		ug/L	50
122-66-7	1,2-Diphenylhydrazine [◊]	BRL		ug/L	50
101-55-3	4-Bromophenyl phenyl ether	BRL		ug/L	50
86-74-8	Carbazole	BRL		ug/L	50
84-74-2	Di- <i>n</i> -butyl phthalate	BRL		ug/L	50
85-68-7	Butyl benzyl phthalate	BRL		ug/L	50
91-94-1	3,3'-Dichlorobenzidine	BRL		ug/L	50
117-81-7	Bis(2-ethylhexyl) phthalate	BRL		ug/L	50
117-84-0	Di- <i>n</i> -octyl phthalate	BRL		ug/L	50

QC Surrogate Compound	Spiked	Measured	Recovery	QC Limits
2-Fluorophenol	20	n/a	d	15 - 110 %
Phenol-d5	20	n/a	d	15 - 110 %
Nitrobenzene-d5	10	n/a	d	30 - 130 %
2-Fluorobiphenyl	10	n/a	d	30 - 130 %
2,4,6-Tribromophenol	20	n/a	d	15 - 110 %
Terphenyl-d14	10	n/a	d	30 - 130 %

Method Reference: Test Methods for Evaluating Solid Waste, US EPA, SW-846, Third Edition, Update III (1996).
Sample extraction performed by EPA Method 3510C.

Report Notations: BRL Indicates concentration, if any, is below reporting limit for analyte. Reporting limit is the lowest concentration that can be reliably quantified under routine laboratory operating conditions. Reporting limits are adjusted for sample size and dilution.

* Analyzed as 4-Methylphenol.

† Reported as sum of N-Nitrosodiphenylamine and Diphenylamine.

◊ Analyzed as Azobenzene.

d Surrogate recovery not measurable due to required sample dilution.

EPA Method 8270C Semivolatile Organics by GC/MS-SIM (Part 2)

Field ID: Discharge
Project: Taunton NPDES/9073
Client: Horsley & Witten, Inc.

Laboratory ID: 128435-05
Sampled: 09-30-09 10:20
Received: 09-30-09 12:45
Extracted: 10-02-09 13:30
Analyzed: 10-05-09 23:35
Analyst: MJB

Matrix: Aqueous
Container: 1 L Amber Glass
Preservation: Cool

QC Batch ID: EP-2429-F
Instrument ID: MS-6 HP 6890
Sample Volume: 1,000 mL
Final Volume: 1 mL
Dilution Factor: 50

CAS Number	Analyte	Concentration	Notes	Units	Reporting Limit
91-20-3	Naphthalene	310		ug/L	25
91-57-6	2-Methylnaphthalene	400		ug/L	25
208-96-8	Acenaphthylene	BRL		ug/L	25
83-32-9	Acenaphthene	BRL		ug/L	25
86-73-7	Fluorene	32		ug/L	25
85-01-8	Phenanthrene	52		ug/L	25
120-12-7	Anthracene	BRL		ug/L	25
206-44-0	Fluoranthene	BRL		ug/L	25
129-00-0	Pyrene	BRL		ug/L	25
56-55-3	Benzo[a]anthracene	BRL		ug/L	5.0
218-01-9	Chrysene	BRL		ug/L	5.0
205-99-2	Benzo[b]fluoranthene	BRL		ug/L	5.0
207-08-9	Benzo[k]fluoranthene	BRL		ug/L	5.0
50-32-8	Benzo[a]pyrene	BRL		ug/L	5.0
193-39-5	Indeno[1,2,3-c,d]pyrene	BRL		ug/L	5.0
53-70-3	Dibenzo[a,h]anthracene	BRL		ug/L	5.0
191-24-2	Benzo[g,h,i]perylene	BRL		ug/L	5.0
87-68-3	Hexachlorobutadiene	BRL		ug/L	25
118-74-1	Hexachlorobenzene	BRL		ug/L	25
87-86-5	Pentachlorophenol	BRL		ug/L	50

QC Surrogate Compound	Spiked	Measured	Recovery	QC Limits
2-Fluorophenol	20	na	d	15 - 110 %
Phenol-d5	20	na	d	15 - 110 %
Nitrobenzene-d5	10	na	d	30 - 130 %
2-Fluorobiphenyl	10	na	d	30 - 130 %
2,4,6-Tribromophenol	20	na	d	15 - 110 %
Terphenyl-d14	10	na	d	30 - 130 %

Method Reference: Test Methods for Evaluating Solid Waste, US EPA, SW-846, Third Edition, Update III (1996).
Method modified by use of selected ion monitoring (SIM) in accordance with Section 7.5.5 of the method.
Sample extraction performed by EPA Method 3510C.

Report Notations: BRL Indicates concentration, if any, is below reporting limit for analyte. Reporting limit is the lowest concentration that can be reliably quantified under routine laboratory operating conditions. Reporting limits are adjusted for sample size and dilution.
d Surrogate recovery not measurable due to required sample dilution.

EPA Method 8270C Semivolatile Organics by GC/MS (Part 1)

Field ID: **Source**
Project: **Taunton NPDES/9073**
Client: **Horsley & Witten, Inc.**

Laboratory ID: **128435-06**
Sampled: **09-30-09 11:00**
Received: **09-30-09 12:45**
Extracted: **10-02-09 13:30**
Analyzed: **10-05-09 15:20**
Analyst: **MJB**

Matrix: **Aqueous**
Container: **1 L Amber Glass**
Preservation: **Cool**

QC Batch ID: **SV-2429-F**
Instrument ID: **MS-3 HP 5890**
Sample Volume: **1,000 mL**
Final Volume: **1 mL**
Dilution Factor: **1**

Page: 1 of 2

CAS Number	Analyte	Concentration	Notes	Units	Reporting Limit
62-75-9	N-Nitrosodimethylamine	BRL		ug/L	5
110-86-1	Pyridine	BRL		ug/L	5
108-95-2	Phenol	BRL		ug/L	5
62-53-3	Aniline	BRL		ug/L	5
111-44-4	Bis(2-chloroethyl) ether	BRL		ug/L	5
95-57-8	2-Chlorophenol	BRL		ug/L	5
541-73-1	1,3-Dichlorobenzene	BRL		ug/L	5
106-46-7	1,4-Dichlorobenzene	BRL		ug/L	5
100-51-6	Benzyl Alcohol	BRL		ug/L	5
95-50-1	1,2-Dichlorobenzene	BRL		ug/L	5
95-48-7	2-Methylphenol	BRL		ug/L	5
108-60-1	Bis(2-chloroisopropyl) ether	BRL		ug/L	5
108-39-4/106-44-5	3 and 4-Methylphenol *	BRL		ug/L	5
621-64-7	N-Nitrosodi-n-propylamine	BRL		ug/L	5
98-86-2	Acetophenone	BRL		ug/L	5
67-72-1	Hexachloroethane	BRL		ug/L	5
98-95-3	Nitrobenzene	BRL		ug/L	5
78-59-1	Isophorone	BRL		ug/L	5
88-75-5	2-Nitrophenol	BRL		ug/L	5
105-67-9	2,4-Dimethylphenol	BRL		ug/L	5
111-91-1	Bis(2-chloroethoxy) methane	BRL		ug/L	5
120-83-2	2,4-Dichlorophenol	BRL		ug/L	5
120-82-1	1,2,4-Trichlorobenzene	BRL		ug/L	5
106-47-8	4-Chloroaniline	BRL		ug/L	5
87-68-3	Hexachlorobutadiene	BRL		ug/L	5
59-50-7	4-Chloro-3-methylphenol	BRL		ug/L	5
77-47-4	Hexachlorocyclopentadiene	BRL		ug/L	5
88-06-2	2,4,6-Trichlorophenol	BRL		ug/L	5
95-95-4	2,4,5-Trichlorophenol	BRL		ug/L	5
91-58-7	2-Chloronaphthalene	BRL		ug/L	5
88-74-4	2-Nitroaniline	BRL		ug/L	5
100-25-4	1,4-Dinitrobenzene	BRL		ug/L	5
131-11-3	Dimethyl phthalate	BRL		ug/L	5
99-65-0	1,3-Dinitrobenzene	BRL		ug/L	5
606-20-2	2,6-Dinitrotoluene	BRL		ug/L	5
528-29-0	1,2-Dinitrobenzene	BRL		ug/L	5
99-09-2	3-Nitroaniline	BRL		ug/L	5
51-28-5	2,4-Dinitrophenol	BRL		ug/L	5
100-02-7	4-Nitrophenol	BRL		ug/L	5
132-64-9	Dibenzofuran	BRL		ug/L	5
121-14-2	2,4-Dinitrotoluene	BRL		ug/L	5
84-66-2	Diethyl phthalate	BRL		ug/L	5
7005-72-3	4-Chlorophenyl phenyl ether	BRL		ug/L	5
100-01-6	4-Nitroaniline	BRL		ug/L	5
534-52-1	4,6-Dinitro-2-methylphenol	BRL		ug/L	5

**EPA Method 8270C (Continued)
Semivolatile Organics by GC/MS (Part 1)**

Field ID: **Source**
Project: **Taunton NPDES/9073**
Client: **Horsley & Witten, Inc.**

Matrix: **Aqueous**
Container: **1 L Amber Glass**
Preservation: **Cool**

Laboratory ID: **128435-06**
Sampled: **09-30-09 11:00**
Received: **09-30-09 12:45**
Extracted: **10-02-09 13:30**
Analyzed: **10-05-09 15:20**
Analyst: **MJB**

QC Batch ID: **SV-2429-F**
Instrument ID: **MS-3 HP 5890**
Sample Volume: **1,000 mL**
Final Volume: **1 mL**
Dilution Factor: **1**

Page: 2 of 2

CAS Number	Analyte	Concentration	Notes	Units	Reporting Limit
86-30-6	N-Nitrosodiphenylamine [†]	BRL		ug/L	5
122-66-7	1,2-Diphenylhydrazine [◊]	BRL		ug/L	5
101-55-3	4-Bromophenyl phenyl ether	BRL		ug/L	5
86-74-8	Carbazole	BRL		ug/L	5
84-74-2	Di- <i>n</i> -butyl phthalate	BRL		ug/L	5
85-68-7	Butyl benzyl phthalate	BRL		ug/L	5
91-94-1	3,3'-Dichlorobenzidine	BRL		ug/L	5
117-81-7	Bis(2-ethylhexyl) phthalate	BRL		ug/L	5
117-84-0	Di- <i>n</i> -octyl phthalate	BRL		ug/L	5

QC Surrogate Compound	Spiked	Measured	Recovery	QC Limits
2-Fluorophenol	20	7	33 %	15 - 110 %
Phenol-d5	20	3	14 % q	15 - 110 %
Nitrobenzene-d5	10	6	65 %	30 - 130 %
2-Fluorobiphenyl	10	6	64 %	30 - 130 %
2,4,6-Tribromophenol	20	13	67 %	15 - 110 %
Terphenyl-d14	10	7	70 %	30 - 130 %

Method Reference: Test Methods for Evaluating Solid Waste, US EPA, SW-846, Third Edition, Update III (1996).
Sample extraction performed by EPA Method 3510C.

Report Notations: BRL Indicates concentration, if any, is below reporting limit for analyte. Reporting limit is the lowest concentration that can be reliably quantified under routine laboratory operating conditions. Reporting limits are adjusted for sample size and dilution.

* Analyzed as 4-Methylphenol.

† Reported as sum of N-Nitrosodiphenylamine and Diphenylamine.

◊ Analyzed as Azobenzene.

q Surrogate recovery outside recommended limits.

EPA Method 8270C Semivolatile Organics by GC/MS-SIM (Part 2)

Field ID: Source
Project: Taunton NPDES/9073
Client: Horsley & Witten, Inc.

Laboratory ID: 128435-06
Sampled: 09-30-09 11:00
Received: 09-30-09 12:45
Extracted: 10-02-09 13:30
Analyzed: 10-05-09 22:14
Analyst: MJB

Matrix: Aqueous
Container: 1 L Amber Glass
Preservation: Cool

QC Batch ID: EP-2429-F
Instrument ID: MS-6 HP 6890
Sample Volume: 1,000 mL
Final Volume: 1 mL
Dilution Factor: 1

CAS Number	Analyte	Concentration	Notes	Units	Reporting Limit
91-20-3	Naphthalene	BRL		ug/L	0.5
91-57-6	2-Methylnaphthalene	BRL		ug/L	0.5
208-96-8	Acenaphthylene	BRL		ug/L	0.5
83-32-9	Acenaphthene	BRL		ug/L	0.5
86-73-7	Fluorene	BRL		ug/L	0.5
85-01-8	Phenanthrene	BRL		ug/L	0.5
120-12-7	Anthracene	BRL		ug/L	0.5
206-44-0	Fluoranthene	BRL		ug/L	0.5
129-00-0	Pyrene	BRL		ug/L	0.5
56-55-3	Benzo[a]anthracene	BRL		ug/L	0.1
218-01-9	Chrysene	BRL		ug/L	0.1
205-99-2	Benzo[b]fluoranthene	BRL		ug/L	0.1
207-08-9	Benzo[k]fluoranthene	BRL		ug/L	0.1
50-32-8	Benzo[a]pyrene	BRL		ug/L	0.1
193-39-5	Indeno[1,2,3-c,d]pyrene	BRL		ug/L	0.1
53-70-3	Dibenzo[a,h]anthracene	BRL		ug/L	0.1
191-24-2	Benzo[g,h,i]perylene	BRL		ug/L	0.1
87-68-3	Hexachlorobutadiene	BRL		ug/L	0.5
118-74-1	Hexachlorobenzene	BRL		ug/L	0.5
87-86-5	Pentachlorophenol	BRL		ug/L	1.0

QC Surrogate Compound	Spiked	Measured	Recovery	QC Limits
2-Fluorophenol	20	6.9	34 %	15 - 110 %
Phenol-d5	20	3.2	16 %	15 - 110 %
Nitrobenzene-d5	10	5.9	59 %	30 - 130 %
2-Fluorobiphenyl	10	6.3	63 %	30 - 130 %
2,4,6-Tribromophenol	20	14	71 %	15 - 110 %
Terphenyl-d14	10	5.8	58 %	30 - 130 %

Method Reference: Test Methods for Evaluating Solid Waste, US EPA, SW-846, Third Edition, Update III (1996).
Method modified by use of selected ion monitoring (SIM) in accordance with Section 7.5.5 of the method.
Sample extraction performed by EPA Method 3510C.

Report Notations: BRL Indicates concentration, if any, is below reporting limit for analyte. Reporting limit is the lowest concentration that can be reliably quantified under routine laboratory operating conditions. Reporting limits are adjusted for sample size and dilution.

**EPA Method 608
Polychlorinated Biphenyls (PCBs) by GC/ECD**

Field ID: **Discharge**
 Project: **Taunton NPDES/9073**
 Client: **Horsley & Witten, Inc.**
 Laboratory ID: **128435-07**
 Sampled: **09-30-09 10:20**
 Received: **09-30-09 12:45**
 Extracted: **10-05-09 08:00**
 Cleaned Up: **10-05-09 13:00**
 Analyzed: **10-06-09 12:20**
 Analyst: **AWG**

Matrix: **Aqueous**
 Container: **1 L Amber Glass**
 Preservation: **Cool**
 QC Batch ID: **PB-2542-F**
 Instrument ID: **GC-11 Agilent 6890**
 Sample Weight: **1000 mL**
 Final Volume: **10 mL**
 Dilution Factor: **1**

CAS Number	Analyte	Concentration	Notes	Units	Reporting Limit
12674-11-2	Aroclor 1016	BRL		ug/L	0.2
11104-28-2	Aroclor 1221	BRL		ug/L	0.2
11141-16-5	Aroclor 1232	BRL		ug/L	0.2
53469-21-9	Aroclor 1242	BRL		ug/L	0.2
12672-29-6	Aroclor 1248	BRL		ug/L	0.2
11097-69-1	Aroclor 1254	BRL		ug/L	0.2
11096-82-5	Aroclor 1260	BRL		ug/L	0.2

QC Surrogate Compound		Spiked	Measured	Recovery	QC Limits
First	Tetrachloro- <i>m</i> -xylene	0.20	0.12	60 %	30 - 150 %
Column	Decachlorobiphenyl	0.20	0.16	82 %	30 - 150 %
Second	Tetrachloro- <i>m</i> -xylene	0.20	0.10	50 %	30 - 150 %
Column	Decachlorobiphenyl	0.20	0.17	85 %	30 - 150 %

Method Reference: Methods for Organic Chemical Analysis of Municipal and Industrial Wastewater, US EPA, 40 C.F.R. 136, Appendix A, (1986).
 Sample extraction performed by EPA Method 3510C. Cleanup performed by EPA Method 3660B and EPA Method 3665A.

Report Notations: BRL Indicates concentration, if any, is below reporting limit for analyte. Reporting limit is the lowest concentration that can be reliably quantified under routine laboratory operating conditions. Reporting limits are adjusted for sample size and dilution.

**EPA Method 608
Polychlorinated Biphenyls (PCBs) by GC/ECD**

Field ID: **Source**
Project: **Taunton NPDES/9073**
Client: **Horsley & Witten, Inc.**

Laboratory ID: **128435-08**
Sampled: **09-30-09 11:00**
Received: **09-30-09 12:45**
Extracted: **10-05-09 08:00**
Cleaned Up: **10-05-09 13:00**
Analyzed: **10-06-09 13:07**
Analyst: **AWG**

Matrix: **Aqueous**
Container: **1 L Amber Glass**
Preservation: **Cool**

QC Batch ID: **PB-2542-F**
Instrument ID: **GC-11 Agilent 6890**
Sample Weight: **1000 mL**
Final Volume: **10 mL**
Dilution Factor: **1**

CAS Number	Analyte	Concentration	Notes	Units	Reporting Limit
12674-11-2	Aroclor 1016	BRL		ug/L	0.2
11104-28-2	Aroclor 1221	BRL		ug/L	0.2
11141-16-5	Aroclor 1232	BRL		ug/L	0.2
53469-21-9	Aroclor 1242	BRL		ug/L	0.2
12672-29-6	Aroclor 1248	BRL		ug/L	0.2
11097-69-1	Aroclor 1254	BRL		ug/L	0.2
11096-82-5	Aroclor 1260	BRL		ug/L	0.2

QC Surrogate Compound	Spiked	Measured	Recovery	QC Limits
First	Tetrachloro- <i>m</i> -xylene	0.20	0.16	81 %
Column	Decachlorobiphenyl	0.20	0.16	78 %
Second	Tetrachloro- <i>m</i> -xylene	0.20	0.16	81 %
Column	Decachlorobiphenyl	0.20	0.16	78 %

Method Reference: Methods for Organic Chemical Analysis of Municipal and Industrial Wastewater, US EPA, 40 C.F.R. 136, Appendix A, (1986).
Sample extraction performed by EPA Method 3510C. Cleanup performed by EPA Method 3660B and EPA Method 3665A.

Report Notations: BRL Indicates concentration, if any, is below reporting limit for analyte. Reporting limit is the lowest concentration that can be reliably quantified under routine laboratory operating conditions. Reporting limits are adjusted for sample size and dilution.

**EPA Method 8015B (Modified)
Total Petroleum Hydrocarbons by GC/FID**

Field ID: Discharge
Project: Taunton NPDES/9073
Client: Horsley & Witten, Inc.

Matrix: Aqueous
Container: 1 L Amber Glass
Preservation: H2SO4/ Cool

Laboratory ID: 128435-9
Sampled: 09-30-09 10:20
Received: 09-30-09 12:45
Extracted: 10-01-09 09:00
Analyzed: 10-03-09 06:08
Analyst: MB

QC Batch ID: HF-2156-F
Instrument ID: GC4 HP 5890
Sample Volume: 1,000 mL
Final Volume: 1 mL
Dilution Factor: 5

Analyte	Concentration	Notes	Units	Reporting Limit
Total Petroleum Hydrocarbons	58		mg/L	1.0

QC Surrogate Compound	Spiked	Measured	Recovery	QC Limits
ortho-Terphenyl	0.040	n/a	d	60 - 140 %

Method Reference: Test Methods for Evaluating Solid Waste, US EPA, SW-846, Third Edition, Update III (1996).
Method modified to quantify total petroleum hydrocarbons in the range n-C 9 through n-C 36. Results are quantified on the basis of a series of aromatic and aliphatic hydrocarbons, using 5-alpha-androstane as an internal standard.
Sample extraction performed by EPA Method 3510C.

Report Notations: BRL Indicates concentration, if any, is below reporting limit for analyte. Reporting limit is the lowest concentration that can be reliably quantified under routine laboratory operating conditions. Reporting limits are adjusted for sample size and dilution.
d Surrogate recovery not measurable due to required sample dilution.

**EPA Method 8015B (Modified)
Total Petroleum Hydrocarbons by GC/FID**

Field ID: Source
Project: Taunton NPDES/9073
Client: Horsley & Witten, Inc.

Matrix: Aqueous
Container: 1 L Amber Glass
Preservation: H2SO4/ Cool

Laboratory ID: 128435-10
Sampled: 09-30-09 11:00
Received: 09-30-09 12:45
Extracted: 10-01-09 09:00
Analyzed: 10-01-09 22:59
Analyst: CM

QC Batch ID: HF-2156-F
Instrument ID: GC4 HP 5890
Sample Volume: 1,000 mL
Final Volume: 1 mL
Dilution Factor: 1

Analyte	Concentration		Notes	Units	Reporting Limit
Total Petroleum Hydrocarbons	BRL			mg/L	0.2

QC Surrogate Compound	Spiked	Measured	Recovery	QC Limits	
ortho-Terphenyl	0.040	0.032	81 %	60 - 140 %	

Method Reference: Test Methods for Evaluating Solid Waste, US EPA, SW-846, Third Edition, Update III (1996).
Method modified to quantify total petroleum hydrocarbons in the range n-C 9 through n-C 36. Results are quantified on the basis of a series of aromatic and aliphatic hydrocarbons, using 5-alpha-androstane as an internal standard.
Sample extraction performed by EPA Method 3510C.

Report Notations: BRL Indicates concentration, if any, is below reporting limit for analyte. Reporting limit is the lowest concentration that can be reliably quantified under routine laboratory operating conditions. Reporting limits are adjusted for sample size and dilution.

Inorganic Chemistry

Field ID: **Discharge**
Project: **Taunton NPDES/9073**
Client: **Horsley & Witten, Inc.**

Matrix: **Aqueous**
Received: **09-30-09 12:45**

Lab ID: **128435-11** Sampled: **09-30-09 10:20** Container: **1 L Plastic** Preservation: **Cool**

Analyte	Result	Units	RL	DF	Volume	Analyzed	QC Batch	Method	Inst	Analyst
Solids, Total Suspended	BRL	mg/L	2	1	500 mL	10-02-09 08:55	TSS-1683-W	SM 2540 D	3	JR
Chlorine, Total Residual	0.09	mg/L	0.04	2	2.5 mL	10-01-09 08:00	TRC-0811-W	SM 4500-Cl G	2	DEB
Chromium, Hexavalent	BRL	mg/L	0.01	1	5 mL	10-01-09 10:00	HC-0167-W	SM 3500-Cr D	2	JK

Lab ID: **128435-13** Sampled: **09-30-09 10:20** Container: **500 mL Plastic** Preservation: **NaOH/Cool**

Analyte	Result	Units	RL	DF	Volume	Analyzed	QC Batch	Method	Inst	Analyst
Cyanide, Total	BRL	mg/L	0.01	1	50 mL	10-01-09 12:12	TCN-1522-W	Lachat 10-204-00-1-A (EPA 335.3)	1	JR

Method Reference: Methods for Chemical Analysis of Water and Wastes, US EPA, EPA-600/4-790-020 (Revised 1983), and Methods for the Determination of Inorganic Substances in Environmental Samples, US EPA, EPA/600/R-93/100 (1993), and Standard Methods for the Examination of Water and Wastewater, APHA, Twentieth Edition (1998), and Test Methods for Evaluating Solid Waste, US EPA, SW-846, Third Edition, Update III (1996).

Report Notations: BRL Indicates concentration, if any, is below reporting limit for analyte. Reporting limit is the lowest concentration that can be reliably quantified under routine laboratory operating conditions. Reporting limits are adjusted for sample size and dilution.

RL Reporting Limit.

DF Dilution Factor.

1 Instrument ID: Lachat 8000 Autoanalyzer

2 Instrument ID: Thermo Electron Genesys 20

3 Instrument ID: Mettler AT 200 Balance

Inorganic Chemistry

Field ID: **Source**
Project: **Taunton NPDES/9073**
Client: **Horsley & Witten, Inc.**

Matrix: **Aqueous**
Received: **09-30-09 12:45**

Lab ID: **128435-12** Sampled: **09-30-09 11:00** Container: **1 L Plastic** Preservation: **Cool**

Analyte	Result	Units	RL	DF	Volume	Analyzed	QC Batch	Method	Inst	Analyst
Solids, Total Suspended	BRL	mg/L	2	1	500 mL	10-02-09 08:55	TSS-1683-W	SM 2540 D	3	JR
Chlorine, Total Residual	4	mg/L	1	50	0.1 mL	10-01-09 08:00	TRC-0811-W	SM 4500-Cl G	2	DEB
Chromium, Hexavalent	BRL	mg/L	0.01	1	5 mL	10-01-09 10:00	HC-0167-W	SM 3500-Cr D	2	JK

Lab ID: **128435-14** Sampled: **09-30-09 11:00** Container: **500 mL Plastic** Preservation: **NaOH/Cool**

Analyte	Result	Units	RL	DF	Volume	Analyzed	QC Batch	Method	Inst	Analyst
Cyanide, Total	BRL	mg/L	0.01	1	50 mL	10-01-09 12:16	TCN-1522-W	Lachat 10-204-00-1-A (EPA 335.3)	1	JR

Method Reference: Methods for Chemical Analysis of Water and Wastes, US EPA, EPA-600/4-790-020 (Revised 1983), and Methods for the Determination of Inorganic Substances in Environmental Samples, US EPA, EPA/600/R-93/100 (1993), and Standard Methods for the Examination of Water and Wastewater, APHA, Twentieth Edition (1998), and Test Methods for Evaluating Solid Waste, US EPA, SW-846, Third Edition, Update III (1996).

Report Notations: BRL Indicates concentration, if any, is below reporting limit for analyte. Reporting limit is the lowest concentration that can be reliably quantified under routine laboratory operating conditions. Reporting limits are adjusted for sample size and dilution.

RL Reporting Limit.

DF Dilution Factor.

1 Instrument ID: Lachat 8000 Autoanalyzer

2 Instrument ID: Thermo Electron Genesys 20

3 Instrument ID: Mettler AT 200 Balance

Trace Metals

Field ID: **Discharge**
Project: **Taunton NPDES/9073**
Client: **Horsley & Witten, Inc.**

Matrix: **Aqueous**
Container: **250 mL Plastic**
Preservation: **HNO₃ / Cool**
Preserved: **09-30-09 10:20**

Laboratory ID: **128435-15**
Sampled: **09-30-09 10:20**
Received: **09-30-09 12:45**

Analysis Method	QC Batch ID	Prep Method	Prepared	Sample Volume	Instrument ID	Analyst
EPA 200.8 ¹	MB-3880-W	EPA 200.8	10-01-09 09:14	50 mL	ICPMS-1 ELAN 9000	MFP
EPA 200.7 ²	MB-3880-W	EPA 200.7	10-01-09 09:14	50 mL	ICP-1 PE 3000	MFP
EPA 245.1 ³	MP-2230-W	EPA 245.1	10-02-09 09:30	25 mL	CVAA-1 PE FIMS	MFP

CAS Number	Analyte	Concentration	Notes	Units	Reporting Limit	DF	Analyzed	Method
7440-36-0	Antimony, Total	BRL		mg/L	0.003	1	10-02-09 22:50	EPA 200.8 ¹
7440-38-2	Arsenic, Total	BRL		mg/L	0.005	1	10-02-09 22:50	EPA 200.8 ¹
7440-43-9	Cadmium, Total	BRL		mg/L	0.004	1	10-01-09 20:39	EPA 200.7 ²
7440-47-3	Chromium, Total	BRL		mg/L	0.01	1	10-01-09 20:39	EPA 200.7 ²
7440-50-8	Copper, Total	BRL		mg/L	0.025	1	10-02-09 22:48	EPA 200.7 ²
7439-89-6	Iron, Total	0.1		mg/L	0.1	1	10-01-09 20:39	EPA 200.7 ²
7439-92-1	Lead, Total	0.011		mg/L	0.001	1	10-02-09 22:50	EPA 200.8 ¹
7439-97-6	Mercury, Total	BRL		mg/L	0.0002	1	10-02-09 21:06	EPA 245.1 ³
7440-02-0	Nickel, Total	BRL		mg/L	0.04	1	10-01-09 20:39	EPA 200.7 ²
7782-49-2	Selenium, Total	BRL		mg/L	0.005	1	10-02-09 22:50	EPA 200.8 ¹
7440-22-4	Silver, Total	BRL		mg/L	0.007	1	10-01-09 20:39	EPA 200.7 ²
7440-28-0	Thallium, Total	BRL		mg/L	0.001	1	10-01-09 20:39	EPA 200.8 ¹
7440-66-6	Zinc, Total	BRL		mg/L	0.2	1	10-02-09 22:50	EPA 200.7 ²

Method Reference: Methods for Chemical Analysis of Water and Wastes, EPA-600/4-79-020, Revised (1983), and Methods for the Determination of Metals in Environmental Samples, Supplement I, EPA-600/R-94-111, (1994), and 40 C.F.R. 136, Appendix C (1990).

Report Notations: BRL Indicates concentration, if any, is below reporting limit for analyte. Reporting limit is the lowest concentration that can be reliably quantified under routine laboratory operating conditions. Reporting limits are adjusted for sample size and dilution.
DF Dilution Factor.

Trace Metals

Field ID: **Source**
Project: **Taunton NPDES/9073**
Client: **Horsley & Witten, Inc.**

Matrix: **Aqueous**
Container: **250 mL Plastic**
Preservation: **HNO₃ / Cool**
Preserved: **09-30-09 11:00**

Laboratory ID: **128435-16**
Sampled: **09-30-09 11:00**
Received: **09-30-09 12:45**

Analysis Method	QC Batch ID	Prep Method	Prepared	Sample Volume	Instrument ID	Analyst
EPA 200.8 ¹	MB-3880-W	EPA 200.8	10-01-09 09:14	50 mL	ICPMS-1 ELAN 9000	MFP
EPA 200.7 ²	MB-3880-W	EPA 200.7	10-01-09 09:14	50 mL	ICP-1 PE 3000	MFP
EPA 245.1 ³	MP-2230-W	EPA 245.1	10-02-09 09:30	25 mL	CVAA-1 PE FIMS	MFP

CAS Number	Analyte	Concentration	Notes	Units	Reporting Limit	DF	Analyzed	Method
7440-36-0	Antimony, Total		BRL	mg/L	0.003	1	10-02-09 22:55	EPA 200.8 ¹
7440-38-2	Arsenic, Total		BRL	mg/L	0.005	1	10-02-09 22:55	EPA 200.8 ¹
7440-43-9	Cadmium, Total		BRL	mg/L	0.004	1	10-01-09 20:43	EPA 200.7 ²
7440-47-3	Chromium, Total		BRL	mg/L	0.01	1	10-01-09 20:43	EPA 200.7 ²
7440-50-8	Copper, Total		BRL	mg/L	0.025	1	10-02-09 22:52	EPA 200.7 ²
7439-89-6	Iron, Total		BRL	mg/L	0.1	1	10-01-09 20:43	EPA 200.7 ²
7439-92-1	Lead, Total		BRL	mg/L	0.001	1	10-02-09 22:55	EPA 200.8 ¹
7439-97-6	Mercury, Total		BRL	mg/L	0.0002	1	10-02-09 21:12	EPA 245.1 ³
7440-02-0	Nickel, Total		BRL	mg/L	0.04	1	10-01-09 20:43	EPA 200.7 ²
7782-49-2	Selenium, Total		BRL	mg/L	0.005	1	10-02-09 22:55	EPA 200.8 ¹
7440-22-4	Silver, Total		BRL	mg/L	0.007	1	10-01-09 20:43	EPA 200.7 ²
7440-28-0	Thallium, Total		BRL	mg/L	0.001	1	10-02-09 22:55	EPA 200.8 ¹
7440-66-6	Zinc, Total		BRL	mg/L	0.2	1	10-01-09 20:43	EPA 200.7 ²

Method Reference: Methods for Chemical Analysis of Water and Wastes, EPA-600/4-79-020, Revised (1983), and Methods for the Determination of Metals in Environmental Samples, Supplement I, EPA-600/R-94-111, (1994), and 40 C.F.R. 136, Appendix C (1990).

Report Notations: BRL Indicates concentration, if any, is below reporting limit for analyte. Reporting limit is the lowest concentration that can be reliably quantified under routine laboratory operating conditions. Reporting limits are adjusted for sample size and dilution.
DF Dilution Factor.

Project Narrative

Project: **Taunton NPDES/9073**
Client: **Horsley & Witten, Inc.**

Lab ID: **128435**
Received: **09-30-09 12:45**

A. Documentation and Client Communication

The following documentation discrepancies, and client changes or amendments were noted for this project:

1. No documentation discrepancies, changes, or amendments were noted.

B. Method Modifications, Non-Conformances and Observations

The sample(s) in this project were analyzed by the references analytical method(s), and no method modifications, non-conformances or analytical issues were noted, except as indicated below:

1. EPA 8260B Note: Samples 128435-1. Sample was diluted prior to analysis. Dilution was required to keep all target analytes within calibration.
2. EPA 8270C Modification: Samples 128435-5,-6. Method modified by use of selected ion monitoring (SIM) in accordance with Section 7.5.5 of the method. GC/MS-SIM was used to achieve low quantification limits necessary for regulatory compliance.
3. EPA 8270C Non-conformance: Samples 128435-05 and -06. Laboratory control sample (LCS) had analytes Pyridine and Pentachlorophenol with RPD recoveries above recommended recovery limits for QC Batch SV-2429-F.
4. EPA 8270C Note: Sample 128435-05. Sample was diluted prior to analysis. Dilution was required to keep all target analytes within calibration.
5. TPH by GC/FID Note: Sample 128435-09. Sample was diluted prior to analysis. Dilution was required due to presence of non-target analyte interference.
6. TPH by GC/FID Note: Sample 128435-09. Sample had surrogate recovery outside recommended limits due to required sample dilution.
7. EPA 8270C Non-conformance: Sample 128435-06. Sample had surrogate recovery outside recommended limits due to sample matrix interference.
8. EPA 8270C Non-conformance: Sample 128435-05. Sample did not have measureable surrogate recoveries due to required sample dilution.
9. EPA 8260B Non-conformance: Samples 128435-01 and -02. Laboratory control sample (LCS) had analytes Dichlorodifluoromethane and Trichlorofluoromethane below recommended recovery limits and Trichlorofluoromethane with RPD recovery above recommended recovery limits for QC Batch VM7-3269-W.

Quality Assurance/Quality Control

A. Program Overview

Groundwater Analytical conducts an active Quality Assurance program to ensure the production of high quality, valid data. This program closely follows the guidance provided by *Interim Guidelines and Specifications for Preparing Quality Assurance Project Plans*, US EPA QAMS-005/80 (1980), and *Test Methods for Evaluating Solid Waste*, US EPA, SW-846, Update III (1996).

Quality Control protocols include written Standard Operating Procedures (SOPs) developed for each analytical method. SOPs are derived from US EPA methodologies and other established references. Standards are prepared from commercially obtained reference materials of certified purity, and documented for traceability.

Quality Assessment protocols for most organic analyses include a minimum of one laboratory control sample, one method blank, one matrix spike sample, and one sample duplicate for each sample preparation batch. All samples, standards, blanks, laboratory control samples, matrix spikes and sample duplicates are spiked with internal standards and surrogate compounds. All instrument sequences begin with an initial calibration verification standard and a blank; and excepting GC/MS sequences, all sequences close with a continuing calibration standard. GC/MS systems are tuned to appropriate ion abundance criteria daily, or for each 12 hour operating period, whichever is more frequent.

Quality Assessment protocols for most inorganic analyses include a minimum of one laboratory control sample, one method blank, one matrix spike sample, and one sample duplicate for each sample preparation batch. Standard curves are derived from one reagent blank and four concentration levels. Curve validity is verified by standard recoveries within plus or minus ten percent of the curve.

B. Definitions

Batches are used as the basic unit for Quality Assessment. A Batch is defined as twenty or fewer samples of the same matrix which are prepared together for the same analysis, using the same lots of reagents and the same techniques or manipulations, all within the same continuum of time, up to but not exceeding 24 hours.

Laboratory Control Samples are used to assess the accuracy of the analytical method. A Laboratory Control Sample consists of reagent water or sodium sulfate spiked with a group of target analytes representative of the method analytes. Accuracy is defined as the degree of agreement of the measured value with the true or expected value. Percent Recoveries for the Laboratory Control Samples are calculated to assess accuracy.

Method Blanks are used to assess the level of contamination present in the analytical system. Method Blanks consist of reagent water or an aliquot of sodium sulfate. Method Blanks are taken through all the appropriate steps of an analytical method. Sample data reported is not corrected for blank contamination.

Surrogate Compounds are used to assess the effectiveness of an analytical method in dealing with each sample matrix. Surrogate Compounds are organic compounds which are similar to the target analytes of interest in chemical behavior, but which are not normally found in environmental samples. Percent Recoveries are calculated for each Surrogate Compound.

Quality Control Report Laboratory Control Sample

Category: **EPA 8015B Mod TPH**
 QC Batch ID: **HF-2156-F**
 Matrix: **Aqueous**
 Units: **mg/L**

Instrument ID: **GC4 HP 5890**
 Extracted: **10-01-09 09:00**
 Analyzed: **10-01-09 23:48**
 Analyst: **CM**

Analyte	Spiked	Measured	Recovery	QC Limits
Fuel Oil No. 2	2.0	0.98	49 %	60 - 140 %

QC Surrogate Compound	Spiked	Measured	Recovery	QC Limits
<i>ortho</i> -Terphenyl	0.040	0.023	57 %	60 - 140 %

Method Reference: Test Methods for Evaluating Solid Waste, US EPA, SW-846, Third Edition, Update III (1996).
 Method modified to quantify total petroleum hydrocarbons in the range n-C 9 through n-C 36. Results are quantified on the basis of a series of aromatic and aliphatic hydrocarbons, using 5-alpha-androstane as an internal standard.
 Sample extraction performed by EPA Method 3510C.

Report Notations: All calculations performed prior to rounding. Quality Control Limits are defined by the methodology, or alternatively based upon the historical average recovery plus or minus three standard deviation units.

Quality Control Report Method Blank

Category: **EPA 8015B Mod TPH**
 QC Batch ID: **HF-2156-F**
 Matrix: **Aqueous**

Instrument ID: **GC4 HP 5890**
 Extracted: **10-01-09 09:00**
 Analyzed: **10-01-09 22:53**
 Analyst: **CM**

Analyte	Concentration	Notes	Units	Reporting Limit
Total Petroleum Hydrocarbons	BRL		mg/L	0.2

QC Surrogate Compound	Spiked	Measured	Recovery	QC Limits
<i>ortho</i> -Terphenyl	0.040	0.033	82 %	60 - 140 %

Method Reference: Test Methods for Evaluating Solid Waste, US EPA, SW-846, Third Edition, Update III (1996).
 Method modified to quantify total petroleum hydrocarbons in the range n-C 9 through n-C 36. Results are quantified on the basis of a series of aromatic and aliphatic hydrocarbons, using 5-alpha-androstane as an internal standard.
 Sample extraction performed by EPA Method 3510C.

Report Notations: BRL Indicates concentration, if any, is below reporting limit for analyte. Reporting limit is the lowest concentration that can be reliably quantified under routine laboratory operating conditions. Reporting limits are adjusted for sample size and dilution.

Quality Control Report Laboratory Control Sample

Category: **EPA Method 608 PCBs**
 QC Batch ID: **PB-2542-F**
 Matrix: **Aqueous**
 Units: **ug/L**

Instrument ID: **GC-11 Agilent 6890**
 Extracted: **10-05-09 08:00**
 Cleaned Up: **10-05-09 13:00**
 Analyzed: **10-06-09 11:57**
 Analyst: **AWG**

CAS Number	Analyte	Spiked	Measured		Recovery		QC Limits
			1st Column	2nd Column	1st Column	2nd Column	
12674-11-2	Aroclor 1016	5.0	4.7	4.3	94 %	87 %	40 - 140 %
11096-82-5	Aroclor 1260	5.0	3.5	3.3	70 %	65 %	40 - 140 %
QC Surrogate Compound		Spiked	Measured		Recovery		QC Limits
Tetrachloro- <i>m</i> -xylene		0.20	0.16	0.16	81 %	81 %	30 - 150 %
Decachlorobiphenyl		0.20	0.20	0.21	102 %	103 %	30 - 150 %

Method Reference: Methods for Organic Chemical Analysis of Municipal and Industrial Wastewater, US EPA, 40 C.F.R. 136, Appendix A, (1986).
 Sample extraction performed by EPA Method 3510C. Cleanup performed by EPA Method 3660B and EPA Method 3665A.

Report Notations: All calculations performed prior to rounding. Quality Control Limits are defined by the methodology,
 or alternatively based upon the historical average recovery plus or minus three standard deviation units.

Quality Control Report Method Blank

Category: **EPA Method 608 PCBs**
QC Batch ID: **PB-2542-F**
Matrix: **Aqueous**

Instrument ID: **GC-11 Agilent 6890**
Extracted: **10-05-09 08:00**
Cleaned Up: **10-05-09 13:00**
Analyzed: **10-06-09 11:09**
Analyst: **AWG**

CAS Number	Analyte	Concentration	Notes	Units	Reporting Limit
12674-11-2	Aroclor 1016	BRL		ug/L	0.20
11104-28-2	Aroclor 1221	BRL		ug/L	0.20
11141-16-5	Aroclor 1232	BRL		ug/L	0.20
53469-21-9	Aroclor 1242	BRL		ug/L	0.20
12672-29-6	Aroclor 1248	BRL		ug/L	0.20
11097-69-1	Aroclor 1254	BRL		ug/L	0.20
11096-82-5	Aroclor 1260	BRL		ug/L	0.20
QC Surrogate Compound		Spiked	Measured	Recovery	QC Limits
First Column	Tetrachloro- <i>m</i> -xylene	0.20	0.16	80 %	30 - 150 %
	Decachlorobiphenyl	0.20	0.20	98 %	30 - 150 %
Second Column	Tetrachloro- <i>m</i> -xylene	0.20	0.16	79 %	30 - 150 %
	Decachlorobiphenyl	0.20	0.19	95 %	30 - 150 %

Method Reference: Methods for Organic Chemical Analysis of Municipal and Industrial Wastewater, US EPA, 40 C.F.R. 136, Appendix A, (1986). Sample extraction performed by EPA Method 3510C. Cleanup performed by EPA Method 3660B and EPA Method 3665A.

Report Notations: BRL Indicates concentration, if any, is below reporting limit for analyte. Reporting limit is the lowest concentration that can be reliably quantified under routine laboratory operating conditions. Reporting limits are adjusted for sample size and dilution.

**Quality Control Report
Laboratory Control Sample**

Category: **EPA Method 8011**
QC Batch ID: **PV-0970-E**
Matrix: **Aqueous**
Units: **ug/L**

Instrument ID: **GC-5 HP 5890**
Extracted: **10-01-09 11:00**
Analyzed: **10-01-09 14:10**
Analyst: **AWG**

CAS Number	Analyte	Spiked	Measured		Recovery		QC Limits
			1st Column	2nd Column	1st Column	2nd Column	
106-93-4	1,2-Dibromoethane (EDB)	0.20	0.20	0.21	99 %	104 %	70 - 130 %
96-12-8	1,2-Dibromo-3-Chloropropane (DBCP)	0.20	0.19	0.20	96 %	101 %	70 - 130 %

Method Reference: Test Methods for Evaluating Solid Waste, US EPA, SW-846, Third Edition, Update III (1996).

Report Notations: All calculations performed prior to rounding. Quality Control Limits are defined by the methodology, or alternatively based upon the historical average recovery plus or minus three standard deviation units.

**Quality Control Report
Method Blank**

Category: **EPA Method 8011**
QC Batch ID: **PV-0970-E**
Matrix: **Aqueous**

Instrument ID: **GC-5 HP 5890**
Extracted: **10-01-09 11:00**
Analyzed: **10-01-09 15:41**
Analyst: **AWG**

CAS Number	Analyte	Concentration	Notes	Units	Reporting Limit
106-93-4	1,2-Dibromoethane (EDB)	BRL		ug/L	0.02
96-12-8	1,2-Dibromo-3-Chloropropane (DBCP)	BRL		ug/L	0.02

Method Reference: Test Methods for Evaluating Solid Waste, US EPA, SW-846, Third Edition, Update III (1996).

Report Notations: BRL Indicates concentration, if any, is below reporting limit for analyte. Reporting limit is the lowest concentration that can be reliably quantified under routine laboratory operating conditions. Reporting limits are adjusted for sample size and dilution.

Quality Control Report Laboratory Control Sample

Category: **Metals**
Matrix: **Aqueous**
Units: **mg/L**

<u>Analysis Method</u>	<u>QC Batch ID</u>	<u>Prep Method</u>	<u>Prepared</u>	<u>Instrument ID</u>	<u>Analyst</u>
EPA 200.7	MB-3880-WL	EPA 200.7	10-01-09 09:14	ICP-1 PE3000XL	MFP
EPA 200.8	MB-3880-WL	EPA 200.8	10-01-09 09:14	ICPMS-1 ELAN 9000	MFP
EPA 245.1	MP-2230-WL	EPA 245.1	10-02-09 09:30	CVAA-1 PE FIMS	MFP

CAS Number	Analyte	Spiked	Measured	Recovery	QC Limits	Analyzed	Method
7440-36-0	Antimony	0.050	0.048	96 %	85-115 %	10-02-09 22:35	EPA 200.8
7440-38-2	Arsenic	0.050	0.044	88 %	85-115 %	10-02-09 22:35	EPA 200.8
7440-41-7	Beryllium	1.0	1.00	100 %	85-115 %	10-01-09 19:13	EPA 200.7
7440-43-9	Cadmium	0.010	0.011	110 %	85-115 %	10-02-09 22:35	EPA 200.8
7440-47-3	Chromium	1.0	1.0	99 %	85-115 %	10-01-09 19:13	EPA 200.7
7440-50-8	Copper	0.050	0.055	110 %	85-115 %	10-02-09 22:35	EPA 200.8
7439-92-1	Lead	0.050	0.0510	102 %	85-115 %	10-02-09 22:35	EPA 200.8
7439-97-6	Mercury	0.0010	0.0010	103 %	85-115 %	10-02-09 19:51	EPA 245.1
7440-02-0	Nickel	0.050	0.051	102 %	85-115 %	10-02-09 22:35	EPA 200.8
7782-49-2	Selenium	0.050	0.043	86 %	85-115 %	10-02-09 22:35	EPA 200.8
7440-22-4	Silver	0.010	0.012	115 %	85-115 %	10-02-09 22:35	EPA 200.8
7440-28-0	Thallium	0.050	0.0525	105 %	85-115 %	10-02-09 22:35	EPA 200.8
7440-66-6	Zinc	1.0	1.0	100 %	85-115 %	10-01-09 19:13	EPA 200.7

Method Reference: Methods for Chemical Analysis of Water and Wastes, EPA-600/4-79-020, Revised (1983), and Methods for the Determination of Metals in Environmental Samples, Supplement I, EPA-600/R-94-111, (1994), and 40 C.F.R. 136, Appendix C (1990).

Report Notations: All calculations performed prior to rounding. Quality Control Limits are defined by the methodology, or alternatively based upon the historical average recovery plus or minus three standard deviation units.

Quality Control Report Method Blank

Category: **Metals**
Matrix: **Aqueous**

Analysis Method	QC Batch ID	Prep Method	Prepared	Sample Volume	Instrument ID	Analyst
EPA 200.7	MB-3880-WB	EPA 200.7	10-01-09 09:14	50 mL	ICP-1 PE3000XL	MFP
EPA 200.8	MB-3880-WB	EPA 200.8	10-01-09 09:14	50 mL	ICPMS-1 ELAN 9000	MFP
EPA 245.1	MP-2230-WB	EPA 245.1	10-02-09 09:30	25 mL	CVAA-1 PE FIMS	MFP

CAS Number	Analyte	Concentration	Notes	Units	Reporting Limit	DF	Analyzed	Method
7440-36-0	Antimony	BRL		mg/L	0.006	1	10-02-09 22:35	EPA 200.8
7440-38-2	Arsenic	BRL		mg/L	0.005	1	10-02-09 22:35	EPA 200.8
7440-41-7	Beryllium	BRL		mg/L	0.004	1	10-01-09 19:09	EPA 200.7
7440-43-9	Cadmium	BRL		mg/L	0.0002	1	10-02-09 22:35	EPA 200.8
7440-47-3	Chromium	BRL		mg/L	0.01	1	10-01-09 19:09	EPA 200.7
7440-50-8	Copper	BRL		mg/L	0.003	1	10-02-09 22:35	EPA 200.8
7439-92-1	Lead	BRL		mg/L	0.0005	1	10-02-09 22:35	EPA 200.8
7439-97-6	Mercury	BRL		mg/L	0.0002	1	10-02-09 19:51	EPA 245.1
7440-02-0	Nickel	BRL		mg/L	0.008	1	10-02-09 22:35	EPA 200.8
7782-49-2	Selenium	BRL		mg/L	0.005	1	10-02-09 22:35	EPA 200.8
7440-22-4	Silver	BRL		mg/L	0.0004	1	10-02-09 22:35	EPA 200.8
7440-28-0	Thallium	BRL		mg/L	0.001	1	10-02-09 22:35	EPA 200.8
7440-66-6	Zinc	BRL		mg/L	0.2	1	10-01-09 19:09	EPA 200.7

Method Reference: Methods for Chemical Analysis of Water and Wastes, EPA-600/4-79-020, Revised (1983), and Methods for the Determination of Metals in Environmental Samples, Supplement I, EPA-600/R-94-111, (1994), and 40 C.F.R. 136, Appendix C (1990).

Report Notations: BRL Indicates concentration, if any, is below reporting limit for analyte. Reporting limit is the lowest concentration that can be reliably quantified under routine laboratory operating conditions. Reporting limits are adjusted for sample size and dilution.
DF Dilution Factor.

Quality Control Report Laboratory Control Samples

Category: **EPA Method 8260B**
QC Batch ID: **VM7-3269-W**
Matrix: **Aqueous**
Units: **ug/L**

LCS
Instrument ID: **MS-7 HP 6890**
Analyzed: **10-01-09 06:56**
Analyst: **LMG**

LCSD
Instrument ID: **MS-7 HP 6890**
Analyzed: **10-01-09 07:32**
Analyst: **LMG**

Page: **1 of 2**

CAS Number	Analyte	LCS			LCS Duplicate				QC Limits	
		Spiked	Measured	Recovery	Spiked	Measured	Recovery	RPD	Spike	RPD
75-71-8	Dichlorodifluoromethane	10	7.3	73 %	10	6.8	68 % q	8 %	70 - 130 %	25%
74-87-3	Chloromethane	10	9.2	92 %	10	8.9	89 %	4 %	70 - 130 %	25%
75-01-4	Vinyl Chloride	10	11	114 %	10	11	105 %	7 %	70 - 130 %	25%
74-83-9	Bromomethane	10	11	108 %	10	10	103 %	4 %	70 - 130 %	25%
75-00-3	Chloroethane	10	11	112 %	10	11	108 %	3 %	70 - 130 %	25%
75-69-4	Trichlorofluoromethane	10	8.8	88 %	10	6.8	68 % q	26 % q	70 - 130 %	25%
60-29-7	Diethyl Ether	20	21	106 %	20	20	101 %	5 %	70 - 130 %	25%
75-35-4	1,1-Dichloroethene	10	10	104 %	10	9.6	96 %	8 %	70 - 130 %	25%
76-13-1	1,1,2-Trichlorotrifluoroethane	20	19	93 %	20	18	88 %	6 %	70 - 130 %	25%
67-64-1	Acetone	20	22	108 %	20	20	101 %	7 %	70 - 130 %	25%
75-15-0	Carbon Disulfide	20	17	85 %	20	16	80 %	6 %	70 - 130 %	25%
75-09-2	Methylene Chloride	10	10	101 %	10	10	102 %	1 %	70 - 130 %	25%
107-13-1	Acrylonitrile	10	11	112 %	10	11	108 %	4 %	70 - 130 %	25%
156-60-5	trans- 1,2-Dichloroethene	10	10	104 %	10	9.6	96 %	8 %	70 - 130 %	25%
1634-04-4	Methyl tert- butyl Ether (MTBE)	10	9.9	99 %	10	9.9	99 %	1 %	70 - 130 %	25%
75-34-3	1,1-Dichloroethane	10	10	102 %	10	9.8	98 %	4 %	70 - 130 %	25%
594-20-7	2,2-Dichloropropane	10	10	100 %	10	9.7	97 %	3 %	70 - 130 %	25%
156-59-2	cis- 1,2-Dichloroethene	10	11	108 %	10	10	104 %	4 %	70 - 130 %	25%
78-93-3	2-Butanone (MEK)	20	20	100 %	20	19	95 %	6 %	70 - 130 %	25%
74-97-5	Bromochloromethane	10	11	108 %	10	10	104 %	4 %	70 - 130 %	25%
109-99-9	Tetrahydrofuran (THF)	20	21	106 %	20	21	104 %	1 %	70 - 130 %	25%
67-66-3	Chloroform	10	10	102 %	10	10	100 %	2 %	70 - 130 %	25%
71-55-6	1,1,1-Trichloroethane	10	9.5	95 %	10	9.2	92 %	4 %	70 - 130 %	25%
56-23-5	Carbon Tetrachloride	10	9.3	93 %	10	9.0	90 %	3 %	70 - 130 %	25%
563-58-6	1,1-Dichloropropene	10	9.9	99 %	10	9.3	93 %	6 %	70 - 130 %	25%
71-43-2	Benzene	10	11	108 %	10	10	103 %	5 %	70 - 130 %	25%
107-06-2	1,2-Dichloroethane	10	9.6	96 %	10	9.7	97 %	1 %	70 - 130 %	25%
79-01-6	Trichloroethene	10	10	102 %	10	9.6	96 %	6 %	70 - 130 %	25%
78-87-5	1,2-Dichloropropane	10	11	106 %	10	10	102 %	4 %	70 - 130 %	25%
74-95-3	Dibromomethane	10	10	103 %	10	10	103 %	1 %	70 - 130 %	25%
75-27-4	Bromodichloromethane	10	11	107 %	10	10	104 %	2 %	70 - 130 %	25%
123-91-1	1,4-Dioxane	200	250	125 %	200	240	120 %	4 %	70 - 130 %	25%
10061-01-5	cis- 1,3-Dichloropropene	10	10	105 %	10	10	103 %	1 %	70 - 130 %	25%
108-10-1	4-Methyl-2-Pentanone (MIBK)	20	20	100 %	20	21	103 %	3 %	70 - 130 %	25%
108-88-3	Toluene	10	11	109 %	10	10	103 %	6 %	70 - 130 %	25%
10061-02-6	trans- 1,3-Dichloropropene	10	10	100 %	10	9.8	98 %	2 %	70 - 130 %	25%
79-00-5	1,1,2-Trichloroethane	10	11	111 %	10	11	107 %	3 %	70 - 130 %	25%
127-18-4	Tetrachloroethene	10	11	108 %	10	9.6	96 %	11 %	70 - 130 %	25%
142-28-9	1,3-Dichloropropane	10	11	110 %	10	11	107 %	2 %	70 - 130 %	25%
591-78-6	2-Hexanone	20	22	110 %	20	22	109 %	1 %	70 - 130 %	25%
124-48-1	Dibromochloromethane	10	11	109 %	10	11	107 %	2 %	70 - 130 %	25%
106-93-4	1,2-Dibromoethane (EDB)	10	11	111 %	10	11	105 %	5 %	70 - 130 %	25%
108-90-7	Chlorobenzene	10	11	111 %	10	10	105 %	6 %	70 - 130 %	25%
630-20-6	1,1,1,2-Tetrachloroethane	10	11	110 %	10	10	104 %	6 %	70 - 130 %	25%
100-41-4	Ethylbenzene	10	11	113 %	10	10	105 %	8 %	70 - 130 %	25%
108-38-3/106-42-3	meta- Xylene and para- Xylene	20	23	115 %	20	22	108 %	6 %	70 - 130 %	25%
95-47-6	ortho- Xylene	10	11	113 %	10	10	104 %	8 %	70 - 130 %	25%
100-42-5	Styrene	10	11	114 %	10	11	108 %	5 %	70 - 130 %	25%
75-25-2	Bromoform	10	11	106 %	10	10	104 %	2 %	70 - 130 %	25%

Quality Control Report Laboratory Control Samples

Category: EPA Method 8260B	LCS Instrument ID: MS-7 HP 6890	LCSD Instrument ID: MS-7 HP 6890
QC Batch ID: VM7-3269-W	Analyzed: 10-01-09 06:56	Analyzed: 10-01-09 07:32
Matrix: Aqueous	Analyst: LMG	Analyst: LMG
Units: ug/L		

Page: 2 of 2

CAS Number	Analyte	LCS			LCS Duplicate				QC Limits	
		Spiked	Measured	Recovery	Spiked	Measured	Recovery	RPD	Spike	RPD
98-82-8	Isopropylbenzene	10	10	102 %	10	9.6	96 %	7 %	70 - 130 %	25%
108-86-1	Bromobenzene	10	11	114 %	10	11	109 %	4 %	70 - 130 %	25%
79-34-5	1,1,2,2-Tetrachloroethane	10	11	115 %	10	11	113 %	2 %	70 - 130 %	25%
96-18-4	1,2,3-Trichloropropane	10	13	126 %	10	12	123 %	2 %	70 - 130 %	25%
110-57-6	trans-1,4-Dichloro-2-butene	200	240	121 %	200	240	119 %	2 %	70 - 130 %	25%
103-65-1	n-Propylbenzene	10	11	114 %	10	11	107 %	6 %	70 - 130 %	25%
95-49-8	2-Chlorotoluene	10	11	112 %	10	11	107 %	5 %	70 - 130 %	25%
108-67-8	1,3,5-Trimethylbenzene	10	12	116 %	10	11	108 %	7 %	70 - 130 %	25%
106-43-4	4-Chlorotoluene	10	11	112 %	10	11	106 %	6 %	70 - 130 %	25%
98-06-6	tert-Butylbenzene	10	11	113 %	10	11	105 %	7 %	70 - 130 %	25%
95-63-6	1,2,4-Trimethylbenzene	10	12	117 %	10	11	109 %	7 %	70 - 130 %	25%
135-98-8	sec-Butylbenzene	10	11	112 %	10	11	105 %	7 %	70 - 130 %	25%
541-73-1	1,3-Dichlorobenzene	10	11	110 %	10	10	104 %	5 %	70 - 130 %	25%
99-87-6	4-Isopropyltoluene	10	11	112 %	10	10	105 %	7 %	70 - 130 %	25%
106-46-7	1,4-Dichlorobenzene	10	11	109 %	10	10	103 %	5 %	70 - 130 %	25%
95-50-1	1,2-Dichlorobenzene	10	11	110 %	10	10	105 %	5 %	70 - 130 %	25%
104-51-8	n-Butylbenzene	10	11	112 %	10	10	104 %	8 %	70 - 130 %	25%
96-12-8	1,2-Dibromo-3-chloropropane	10	11	109 %	10	11	108 %	1 %	70 - 130 %	25%
108-70-3	1,3,5-Trichlorobenzene	10	12	123 %	10	11	114 %	8 %	70 - 130 %	25%
120-82-1	1,2,4-Trichlorobenzene	10	12	119 %	10	11	109 %	9 %	70 - 130 %	25%
87-68-3	Hexachlorobutadiene	10	12	115 %	10	10	102 %	12 %	70 - 130 %	25%
91-20-3	Naphthalene	10	12	117 %	10	11	113 %	4 %	70 - 130 %	25%
87-61-6	1,2,3-Trichlorobenzene	10	12	116 %	10	11	110 %	5 %	70 - 130 %	25%
75-65-0	tert-Butyl Alcohol (TBA)	200	230	117 %	200	210	105 %	11 %	70 - 130 %	25%
108-20-3	Di-isopropyl Ether (DIPE)	10	9.4	94 %	10	9.1	91 %	4 %	70 - 130 %	25%
637-92-3	Ethyl tert-butyl Ether (ETBE)	10	9.7	97 %	10	9.7	97 %	0 %	70 - 130 %	25%
994-05-8	tert-Amyl Methyl Ether (TAME)	10	9.8	98 %	10	9.8	98 %	1 %	70 - 130 %	25%

QC Surrogate Compound	Spiked	Measured	Recovery	Spiked	Measured	Recovery	QC Limits
Dibromofluoromethane	10	8	85 %	10	9	85 %	70 - 130 %
1,2-Dichloroethane-d ₄	10	9	90 %	10	9	91 %	70 - 130 %
Toluene-d ₈	10	9	90 %	10	9	91 %	70 - 130 %
4-Bromofluorobenzene	10	9	92 %	10	9	91 %	70 - 130 %

Method Reference: Test Methods for Evaluating Solid Waste, US EPA, SW-846, Third Edition, Update III (1996).
Sample preparation performed by EPA Method 5030B.

Report Notations: All calculations performed prior to rounding. Quality Control Limits are defined by the methodology, or alternatively based upon the historical average recovery plus or minus three standard deviation units.

q Recovery outside recommended limits.

Quality Control Report Method Blank

Category: **EPA Method 8260B**
QC Batch ID: **VM7-3269-W**
Matrix: **Aqueous**

Instrument ID: **MS-7 HP 6890**
Analyzed: **10-01-09 08:07**
Analyst: **LMG**

Page: 1 of 2

CAS Number	Analyte	Concentration	Notes	Units	Reporting Limit
75-71-8	Dichlorodifluoromethane	BRL		ug/L	0.5
74-87-3	Chloromethane	BRL		ug/L	0.5
75-01-4	Vinyl Chloride	BRL		ug/L	0.5
74-83-9	Bromomethane	BRL		ug/L	0.5
75-00-3	Chloroethane	BRL		ug/L	0.5
75-69-4	Trichlorofluoromethane	BRL		ug/L	0.5
60-29-7	Diethyl Ether	BRL		ug/L	2
75-35-4	1,1-Dichloroethene	BRL		ug/L	0.5
76-13-1	1,1,2-Trichlorotrifluoroethane	BRL		ug/L	5
67-64-1	Acetone	BRL		ug/L	10
75-15-0	Carbon Disulfide	BRL		ug/L	5
75-09-2	Methylene Chloride	BRL		ug/L	3
107-13-1	Acrylonitrile	BRL		ug/L	0.5
156-60-5	<i>trans</i> - 1,2-Dichloroethene	BRL		ug/L	0.5
1634-04-4	Methyl <i>tert</i> - butyl Ether (MTBE)	BRL		ug/L	0.5
75-34-3	1,1-Dichloroethane	BRL		ug/L	0.5
594-20-7	2,2-Dichloropropane	BRL		ug/L	0.5
156-59-2	<i>cis</i> - 1,2-Dichloroethene	BRL		ug/L	0.5
78-93-3	2-Butanone (MEK)	BRL		ug/L	5
74-97-5	Bromochloromethane	BRL		ug/L	0.5
109-99-9	Tetrahydrofuran (THF)	BRL		ug/L	5
67-66-3	Chloroform	BRL		ug/L	0.5
71-55-6	1,1,1-Trichloroethane	BRL		ug/L	0.5
56-23-5	Carbon Tetrachloride	BRL		ug/L	0.5
563-58-6	1,1-Dichloropropene	BRL		ug/L	0.5
71-43-2	Benzene	BRL		ug/L	0.5
107-06-2	1,2-Dichloroethane	BRL		ug/L	0.5
79-01-6	Trichloroethene	BRL		ug/L	0.5
78-87-5	1,2-Dichloropropane	BRL		ug/L	0.5
74-95-3	Dibromomethane	BRL		ug/L	0.5
75-27-4	Bromodichloromethane	BRL		ug/L	0.5
123-91-1	1,4-Dioxane	BRL		ug/L	500
10061-01-5	<i>cis</i> - 1,3-Dichloropropene	BRL		ug/L	0.4
108-10-1	4-Methyl-2-Pentanone (MIBK)	BRL		ug/L	5
108-88-3	Toluene	BRL		ug/L	0.5
10061-02-6	<i>trans</i> - 1,3-Dichloropropene	BRL		ug/L	0.4
79-00-5	1,1,2-Trichloroethane	BRL		ug/L	0.5
127-18-4	Tetrachloroethene	BRL		ug/L	0.5
142-28-9	1,3-Dichloropropane	BRL		ug/L	0.5
591-78-6	2-Hexanone	BRL		ug/L	5
124-48-1	Dibromochloromethane	BRL		ug/L	0.5
106-93-4	1,2-Dibromoethane (EDB)	BRL		ug/L	0.5
108-90-7	Chlorobenzene	BRL		ug/L	0.5
630-20-6	1,1,1,2-Tetrachloroethane	BRL		ug/L	0.5
100-41-4	Ethylbenzene	BRL		ug/L	0.5
108-38-3/106-42-3	<i>meta</i> - Xylene and <i>para</i> - Xylene	BRL		ug/L	0.5
95-47-6	<i>ortho</i> - Xylene	BRL		ug/L	0.5
100-42-5	Styrene	BRL		ug/L	0.5
75-25-2	Bromoform	BRL		ug/L	0.5

Quality Control Report Method Blank

Category: **EPA Method 8260B**
QC Batch ID: **VM7-3269-W**
Matrix: **Aqueous**

Instrument ID: **MS-7 HP 6890**
Analyzed: **10-01-09 08:07**
Analyst: **LMG**

Page: 2 of 2

CAS Number	Analyte	Concentration	Notes	Units	Reporting Limit
98-82-8	Isopropylbenzene	BRL		ug/L	0.5
108-86-1	Bromobenzene	BRL		ug/L	0.5
79-34-5	1,1,2,2-Tetrachloroethane	BRL		ug/L	0.5
96-18-4	1,2,3-Trichloropropane	BRL		ug/L	0.5
110-57-6	<i>trans</i> -1,4-Dichloro-2-butene	BRL		ug/L	25
103-65-1	<i>n</i> -Propylbenzene	BRL		ug/L	0.5
95-49-8	2-Chlorotoluene	BRL		ug/L	0.5
108-67-8	1,3,5-Trimethylbenzene	BRL		ug/L	0.5
106-43-4	4-Chlorotoluene	BRL		ug/L	0.5
98-06-6	<i>tert</i> -Butylbenzene	BRL		ug/L	0.5
95-63-6	1,2,4-Trimethylbenzene	BRL		ug/L	0.5
135-98-8	<i>sec</i> -Butylbenzene	BRL		ug/L	0.5
541-73-1	1,3-Dichlorobenzene	BRL		ug/L	0.5
99-87-6	4-Isopropyltoluene	BRL		ug/L	0.5
106-46-7	1,4-Dichlorobenzene	BRL		ug/L	0.5
95-50-1	1,2-Dichlorobenzene	BRL		ug/L	0.5
104-51-8	<i>n</i> -Butylbenzene	BRL		ug/L	0.5
96-12-8	1,2-Dibromo-3-chloropropane	BRL		ug/L	0.5
108-70-3	1,3,5-Trichlorobenzene	BRL		ug/L	0.5
120-82-1	1,2,4-Trichlorobenzene	BRL		ug/L	0.5
87-68-3	Hexachlorobutadiene	BRL		ug/L	0.5
91-20-3	Naphthalene	BRL		ug/L	0.5
87-61-6	1,2,3-Trichlorobenzene	BRL		ug/L	0.5
75-65-0	<i>tert</i> -Butyl Alcohol (TBA)	BRL		ug/L	20
108-20-3	Di-isopropyl Ether (DIPE)	BRL		ug/L	0.5
637-92-3	Ethyl <i>tert</i> -butyl Ether (ETBE)	BRL		ug/L	0.5
994-05-8	<i>tert</i> -Amyl Methyl Ether (TAME)	BRL		ug/L	0.5

QC Surrogate Compound	Spiked	Measured	Recovery	QC Limits
Dibromofluoromethane	10	9	90 %	70 - 130 %
1,2-Dichloroethane-d ₄	10	10	99 %	70 - 130 %
Toluene-d ₈	10	10	95 %	70 - 130 %
4-Bromofluorobenzene	10	10	97 %	70 - 130 %

Method Reference: Test Methods for Evaluating Solid Waste, US EPA, SW-846, Third Edition, Update III (1996).
Sample preparation performed by EPA Method 5030B.

Report Notations: BRL Indicates concentration, if any, is below reporting limit for analyte. Reporting limit is the lowest concentration that can be reliably quantified under routine laboratory operating conditions. Reporting limits are adjusted for sample size and dilution.

Quality Control Report Laboratory Control Samples

Category: **EPA 8270C (Part 1)**
QC Batch ID: **SV-2429-F**
Matrix: **Aqueous**
Units: **ug/L**

LCS
Instrument ID: **MS-3 HP 5890**
Extracted: **10-02-09 13:30**
Analyzed: **10-05-09 12:35**
Analyst: **MJB**

LCSD
Instrument ID: **MS-3 HP 5890**
Extracted: **10-02-09 13:30**
Analyzed: **10-05-09 13:16**
Analyst: **MJB**

Page: **1 of 2**

CAS Number	Analyte	LCS			LCS Duplicate				QC Limits	
		Spiked	Measured	Recovery	Spiked	Measured	Recovery	RPD	Spike	RPD
62-75-9	N-Nitrosodimethylamine	50	29	58 %	50	26	53 %	9 %	40 - 140 %	25%
110-86-1	Pyridine	50	27	54 %	50	20	40 %	29 %	40 - 140 %	25%
108-95-2	Phenol	50	20	40 %	50	21	42 %	3 %	30 - 130 %	25%
62-53-3	Aniline	50	42	84 %	50	42	83 %	1 %	40 - 140 %	25%
111-44-4	Bis(2-chloroethyl) ether	50	35	69 %	50	37	74 %	6 %	40 - 140 %	25%
95-57-8	2-Chlorophenol	50	31	63 %	50	32	63 %	0 %	30 - 130 %	25%
541-73-1	1,3-Dichlorobenzene	50	33	67 %	50	33	65 %	2 %	40 - 140 %	25%
106-46-7	1,4-Dichlorobenzene	50	32	63 %	50	32	65 %	2 %	40 - 140 %	25%
100-51-6	Benzyl Alcohol	50	40	81 %	50	42	83 %	3 %	30 - 130 %	25%
95-50-1	1,2-Dichlorobenzene	50	33	66 %	50	35	69 %	5 %	40 - 140 %	25%
95-48-7	2-Methylphenol	50	34	69 %	50	34	69 %	0 %	30 - 130 %	25%
108-60-1	Bis(2-chloroisopropyl) ether	50	36	72 %	50	36	73 %	1 %	40 - 140 %	25%
106-44-5	4-Methylphenol	50	27	54 %	50	28	57 %	5 %	30 - 130 %	25%
621-64-7	N-Nitrosodi-n-propylamine	50	38	76 %	50	40	79 %	5 %	40 - 140 %	25%
98-86-2	Acetophenone	50	40	79 %	50	42	85 %	7 %	40 - 140 %	25%
67-72-1	Hexachloroethane	50	33	66 %	50	34	68 %	2 %	40 - 140 %	25%
98-95-3	Nitrobenzene	50	37	74 %	50	39	79 %	6 %	40 - 140 %	25%
78-59-1	Isophorone	50	38	76 %	50	42	83 %	9 %	40 - 140 %	25%
88-75-5	2-Nitrophenol	50	35	71 %	50	36	71 %	1 %	30 - 130 %	25%
105-67-9	2,4-Dimethylphenol	50	35	71 %	50	39	78 %	10 %	30 - 130 %	25%
111-91-1	Bis(2-chloroethoxy) methane	50	37	74 %	50	40	80 %	7 %	40 - 140 %	25%
120-83-2	2,4-Dichlorophenol	50	34	68 %	50	37	74 %	9 %	30 - 130 %	25%
120-82-1	1,2,4-Trichlorobenzene	50	33	67 %	50	35	71 %	6 %	40 - 140 %	25%
106-47-8	4-Chloroaniline	50	39	79 %	50	41	82 %	5 %	40 - 140 %	25%
87-68-3	Hexachlorobutadiene	50	32	65 %	50	35	69 %	6 %	40 - 140 %	25%
59-50-7	4-Chloro-3-methylphenol	50	37	74 %	50	41	82 %	10 %	30 - 130 %	25%
77-47-4	Hexachlorocyclopentadiene	50	31	62 %	50	33	65 %	5 %	40 - 140 %	25%
88-06-2	2,4,6-Trichlorophenol	50	35	70 %	50	37	74 %	5 %	30 - 130 %	25%
95-95-4	2,4,5-Trichlorophenol	50	35	69 %	50	39	79 %	12 %	30 - 130 %	25%
91-58-7	2-Chloronaphthalene	50	38	77 %	50	40	80 %	5 %	40 - 140 %	25%
88-74-4	2-Nitroaniline	50	42	85 %	50	47	93 %	10 %	40 - 140 %	25%
100-25-4	1,4-Dinitrobenzene	50	42	84 %	50	45	91 %	8 %	40 - 140 %	25%
131-11-3	Dimethyl phthalate	50	41	83 %	50	45	90 %	9 %	40 - 140 %	25%
99-65-0	1,3-Dinitrobenzene	50	47	93 %	50	49	97 %	4 %	40 - 140 %	25%
606-20-2	2,6-Dinitrotoluene	50	40	80 %	50	45	90 %	11 %	40 - 140 %	25%
528-29-0	1,2-Dinitrobenzene	50	39	79 %	50	44	88 %	12 %	40 - 140 %	25%
99-09-2	3-Nitroaniline	50	44	88 %	50	45	89 %	2 %	40 - 140 %	25%
51-28-5	2,4-Dinitrophenol	50	36	72 %	50	36	72 %	1 %	30 - 130 %	25%
100-02-7	4-Nitrophenol	50	24	49 %	50	26	52 %	6 %	30 - 130 %	25%
132-64-9	Dibenzofuran	50	39	77 %	50	43	85 %	10 %	40 - 140 %	25%
121-14-2	2,4-Dinitrotoluene	50	42	83 %	50	45	89 %	7 %	40 - 140 %	25%
84-66-2	Diethyl phthalate	50	42	85 %	50	44	89 %	5 %	40 - 140 %	25%
7005-72-3	4-Chlorophenyl phenyl ether	50	39	78 %	50	42	84 %	7 %	40 - 140 %	25%
100-01-6	4-Nitroaniline	50	45	90 %	50	46	92 %	3 %	40 - 140 %	25%
534-52-1	4,6-Dinitro-2-methylphenol	50	37	73 %	50	41	82 %	11 %	30 - 130 %	25%
86-30-6	N-Nitrosodiphenylamine †	50	52	103 %	50	57	114 %	10 %	40 - 140 %	25%
122-66-7	1,2-Diphenylhydrazine ‡	50	42	85 %	50	45	91 %	7 %	40 - 140 %	25%
101-55-3	4-Bromophenyl phenyl ether	50	40	80 %	50	42	84 %	5 %	40 - 140 %	25%

Quality Control Report Laboratory Control Samples

Category: EPA 8270C (Part 1) QC Batch ID: SV-2429-F Matrix: Aqueous Units: ug/L	LCS Instrument ID: MS-3 HP 5890 Extracted: 10-02-09 13:30 Analyzed: 10-05-09 12:35 Analyst: MJB	LCSD Instrument ID: MS-3 HP 5890 Extracted: 10-02-09 13:30 Analyzed: 10-05-09 13:16 Analyst: MJB
--	--	---

Page: 2 of 2

CAS Number	Analyte	LCS			LCS Duplicate				QC Limits	
		Spiked	Measured	Recovery	Spiked	Measured	Recovery	RPD	Spike	RPD
86-74-8	Carbazole	50	43	87 %	50	46	93 %	7 %	40 - 140 %	25%
84-74-2	Di- <i>n</i> -butyl phthalate	50	45	90 %	50	48	96 %	6 %	40 - 140 %	25%
85-68-7	Butyl benzyl phthalate	50	46	92 %	50	48	95 %	4 %	40 - 140 %	25%
91-94-1	3,3'-Dichlorobenzidine	50	42	84 %	50	44	89 %	5 %	40 - 140 %	25%
117-81-7	Bis(2-ethylhexyl) phthalate	50	44	89 %	50	47	94 %	6 %	40 - 140 %	25%
117-84-0	Di- <i>n</i> -octyl phthalate	50	46	92 %	50	48	96 %	5 %	40 - 140 %	25%

QC Surrogate Compound	Spiked	Measured	Recovery	Spiked	Measured	Recovery	QC Limits	
2-Fluorophenol	20	8.9	45 %	20	8.7	44 %	15 - 110 %	
Phenol-d5	20	7.4	37 %	20	7.8	39 %	15 - 110 %	
Nitrobenzene-d5	10	6.8	68 %	10	6.8	68 %	30 - 130 %	
2-Fluorobiphenyl	10	6.6	66 %	10	7.0	70 %	30 - 130 %	
2,4,6-Tribromophenol	20	14	72 %	20	16	81 %	15 - 110 %	
Terphenyl-d14	10	6.8	68 %	10	7.4	74 %	30 - 130 %	

Method Reference: Test Methods for Evaluating Solid Waste, US EPA, SW-846, Third Edition, Update III (1996).
 Sample extraction performed by EPA Method 3510C.

Report Notations: All calculations performed prior to rounding. Quality Control Limits are defined by the methodology, or alternatively based upon the historical average recovery plus or minus three standard deviation units.

† Reported as sum of N-Nitrosodiphenylamine and Diphenylamine.

◇ Analyzed as Azobenzene.

q Recovery outside recommended limits.

Quality Control Report Method Blank

Category: **EPA Method 8270C (Part 1)**
QC Batch ID: **SV-2429-F**
Matrix: **Aqueous**

Instrument ID: **MS-3 HP 5890**
Extracted: **10-02-09 13:30**
Analyzed: **10-05-09 13:57**
Analyst: **MJB**

Page: 1 of 2

CAS Number	Analyte	Concentration	Notes	Units	Reporting Limit
62-75-9	N-Nitrosodimethylamine	BRL		ug/L	5
110-86-1	Pyridine	BRL		ug/L	5
108-95-2	Phenol	BRL		ug/L	5
62-53-3	Aniline	BRL		ug/L	5
111-44-4	Bis(2-chloroethyl) ether	BRL		ug/L	5
95-57-8	2-Chlorophenol	BRL		ug/L	5
541-73-1	1,3-Dichlorobenzene	BRL		ug/L	5
106-46-7	1,4-Dichlorobenzene	BRL		ug/L	5
100-51-6	Benzyl Alcohol	BRL		ug/L	5
95-50-1	1,2-Dichlorobenzene	BRL		ug/L	5
95-48-7	2-Methylphenol	BRL		ug/L	5
108-60-1	Bis(2-chloroisopropyl) ether	BRL		ug/L	5
108-39-4/106-44-5	3 and 4-Methylphenol *	BRL		ug/L	5
621-64-7	N-Nitrosodi-n-propylamine	BRL		ug/L	5
98-86-2	Acetophenone	BRL		ug/L	5
67-72-1	Hexachloroethane	BRL		ug/L	5
98-95-3	Nitrobenzene	BRL		ug/L	5
78-59-1	Isophorone	BRL		ug/L	5
88-75-5	2-Nitrophenol	BRL		ug/L	5
105-67-9	2,4-Dimethylphenol	BRL		ug/L	5
111-91-1	Bis(2-chloroethoxy) methane	BRL		ug/L	5
120-83-2	2,4-Dichlorophenol	BRL		ug/L	5
120-82-1	1,2,4-Trichlorobenzene	BRL		ug/L	5
106-47-8	4-Chloroaniline	BRL		ug/L	5
87-68-3	Hexachlorobutadiene	BRL		ug/L	5
59-50-7	4-Chloro-3-methylphenol	BRL		ug/L	5
77-47-4	Hexachlorocyclopentadiene	BRL		ug/L	5
88-06-2	2,4,6-Trichlorophenol	BRL		ug/L	5
95-95-4	2,4,5-Trichlorophenol	BRL		ug/L	5
91-58-7	2-Chloronaphthalene	BRL		ug/L	5
88-74-4	2-Nitroaniline	BRL		ug/L	5
100-25-4	1,4-Dinitrobenzene	BRL		ug/L	5
131-11-3	Dimethyl phthalate	BRL		ug/L	5
99-65-0	1,3-Dinitrobenzene	BRL		ug/L	5
606-20-2	2,6-Dinitrotoluene	BRL		ug/L	5
528-29-0	1,2-Dinitrobenzene	BRL		ug/L	5
99-09-2	3-Nitroaniline	BRL		ug/L	5
51-28-5	2,4-Dinitrophenol	BRL		ug/L	5
100-02-7	4-Nitrophenol	BRL		ug/L	5
132-64-9	Dibenzofuran	BRL		ug/L	5
121-14-2	2,4-Dinitrotoluene	BRL		ug/L	5
84-66-2	Diethyl phthalate	BRL		ug/L	5
7005-72-3	4-Chlorophenyl phenyl ether	BRL		ug/L	5
100-01-6	4-Nitroaniline	BRL		ug/L	5
534-52-1	4,6-Dinitro-2-methylphenol	BRL		ug/L	5

Quality Control Report Method Blank

Category: **EPA Method 8270C (Part 1)**
 QC Batch ID: **SV-2429-F**
 Matrix: **Aqueous**

Instrument ID: **MS-3 HP 5890**
 Extracted: **10-02-09 13:30**
 Analyzed: **10-05-09 13:57**
 Analyst: **MJB**

Page: 2 of 2

CAS Number	Analyte	Concentration	Notes	Units	Reporting Limit
86-30-6	N-Nitrosodiphenylamine [†]	BRL		ug/L	5
122-66-7	1,2-Diphenylhydrazine [◇]	BRL		ug/L	5
101-55-3	4-Bromophenyl phenyl ether	BRL		ug/L	5
86-74-8	Carbazole	BRL		ug/L	5
84-74-2	Di- <i>n</i> -butyl phthalate	BRL		ug/L	5
85-68-7	Butyl benzyl phthalate	BRL		ug/L	5
91-94-1	3,3'-Dichlorobenzidine	BRL		ug/L	5
117-81-7	Bis(2-ethylhexyl) phthalate	BRL		ug/L	5
117-84-0	Di- <i>n</i> -octyl phthalate	BRL		ug/L	5

QC Surrogate Compound	Spiked	Measured	Recovery	QC Limits
2-Fluorophenol	20	9	46 %	15 - 110 %
Phenol-d5	20	8	39 %	15 - 110 %
Nitrobenzene-d5	10	8	76 %	30 - 130 %
2-Fluorobiphenyl	10	7	68 %	30 - 130 %
2,4,6-Tribromophenol	20	14	72 %	15 - 110 %
Terphenyl-d14	10	7	73 %	30 - 130 %

Method Reference: Test Methods for Evaluating Solid Waste, US EPA, SW-846, Third Edition, Update III (1996).
 Sample extraction performed by EPA Method 3510C.

Report Notations: BRL Indicates concentration, if any, is below reporting limit for analyte. Reporting limit is the lowest concentration that can be reliably quantified under routine laboratory operating conditions. Reporting limits are adjusted for sample size and dilution.

* Analyzed as 4-Methylphenol.

† Reported as sum of N-Nitrosodiphenylamine and Diphenylamine.

◇ Analyzed as Azobenzene.

Quality Control Report Laboratory Control Samples

Category: EPA 8270C (Part 2) QC Batch ID: SV-2429-F Matrix: Aqueous Units: ug/L	LCS Instrument ID: MS-6 HP 6890 Extracted: 10-02-09 13:30 Analyzed: 10-05-09 20:14 Analyst: MJB	LCSD Instrument ID: MS-6 HP 6890 Extracted: 10-02-09 13:30 Analyzed: 10-05-09 20:54 Analyst: MJB
--	--	---

CAS Number	Analyte	LCS			LCS Duplicate				QC Limits	
		Spiked	Measured	Recovery	Spiked	Measured	Recovery	RPD	Spike	RPD
91-20-3	Naphthalene	5.0	3.0	60 %	5.0	3.0	60 %	1 %	40 - 140 %	25%
91-57-6	2-Methylnaphthalene	5.0	3.2	64 %	5.0	3.1	63 %	2 %	40 - 140 %	25%
208-96-8	Acenaphthylene	5.0	3.3	66 %	5.0	3.2	65 %	2 %	40 - 140 %	25%
83-32-9	Acenaphthene	5.0	3.2	64 %	5.0	3.0	60 %	6 %	40 - 140 %	25%
86-73-7	Fluorene	5.0	3.4	68 %	5.0	3.2	64 %	6 %	40 - 140 %	25%
85-01-8	Phenanthrene	5.0	3.3	67 %	5.0	3.2	64 %	4 %	40 - 140 %	25%
120-12-7	Anthracene	5.0	3.6	72 %	5.0	3.6	73 %	1 %	40 - 140 %	25%
206-44-0	Fluoranthene	5.0	3.4	69 %	5.0	3.4	68 %	2 %	40 - 140 %	25%
129-00-0	Pyrene	5.0	3.6	71 %	5.0	3.4	68 %	4 %	40 - 140 %	25%
56-55-3	Benzo[a]anthracene	5.0	3.8	76 %	5.0	3.6	72 %	6 %	40 - 140 %	25%
218-01-9	Chrysene	5.0	3.7	73 %	5.0	3.5	71 %	3 %	40 - 140 %	25%
205-99-2	Benzo[b]fluoranthene	5.0	4.0	80 %	5.0	3.9	78 %	3 %	40 - 140 %	25%
207-08-9	Benzo[k]fluoranthene	5.0	3.9	78 %	5.0	3.8	76 %	3 %	40 - 140 %	25%
50-32-8	Benzo[a]pyrene	5.0	4.2	85 %	5.0	4.2	83 %	2 %	40 - 140 %	25%
193-39-5	Indeno[1,2,3-c,d]pyrene	5.0	4.0	80 %	5.0	3.9	78 %	3 %	40 - 140 %	25%
53-70-3	Dibenzo[a,h]anthracene	5.0	4.0	80 %	5.0	3.8	77 %	4 %	40 - 140 %	25%
191-24-2	Benzo[g,h,i]perylene	5.0	3.9	78 %	5.0	3.7	75 %	4 %	40 - 140 %	25%
87-68-3	Hexachlorobutadiene	5.0	2.9	58 %	5.0	2.9	59 %	1 %	40 - 140 %	25%
118-74-1	Hexachlorobenzene	5.0	3.7	75 %	5.0	3.7	74 %	1 %	40 - 140 %	25%
87-86-5	Pentachlorophenol	5.0	2.9	58 %	5.0	2.1	43 %	31 % q	30 - 130 %	25%

QC Surrogate Compound	Spiked	Measured	Recovery	Spiked	Measured	Recovery	QC Limits
2-Fluorophenol	20	9.0	45 %	20	9.3	46 %	15 - 110 %
Phenol-d5	20	8.1	41 %	20	7.9	40 %	15 - 110 %
Nitrobenzene-d5	10	6.5	65 %	10	6.8	68 %	30 - 130 %
2-Fluorobiphenyl	10	6.4	64 %	10	6.4	64 %	30 - 130 %
2,4,6-Tribromophenol	20	16	82 %	20	16	82 %	15 - 110 %
Terphenyl-d14	10	6.5	65 %	10	6.3	63 %	30 - 130 %

Method Reference: Test Methods for Evaluating Solid Waste, US EPA, SW-846, Third Edition, Update III (1996).
Sample extraction performed by EPA Method 3510C.

Report Notations: All calculations performed prior to rounding. Quality Control Limits are defined by the methodology, or alternatively based upon the historical average recovery plus or minus three standard deviation units.

q Recovery outside recommended limits.

**Quality Control Report
Method Blank**

Category: **EPA Method 8270C (Part 2)**
QC Batch ID: **SV-2429-F**
Matrix: **Aqueous**

Instrument ID: **MS-6 HP 6890**
Extracted: **10-02-09 13:30**
Analyzed: **10-05-09 21:34**
Analyst: **MJB**

CAS Number	Analyte	Concentration	Notes	Units	Reporting Limit
91-20-3	Naphthalene	BRL		ug/L	0.5
91-57-6	2-Methylnaphthalene	BRL		ug/L	0.5
208-96-8	Acenaphthylene	BRL		ug/L	0.5
83-32-9	Acenaphthene	BRL		ug/L	0.5
86-73-7	Fluorene	BRL		ug/L	0.5
85-01-8	Phenanthrene	BRL		ug/L	0.5
120-12-7	Anthracene	BRL		ug/L	0.5
206-44-0	Fluoranthene	BRL		ug/L	0.5
129-00-0	Pyrene	BRL		ug/L	0.5
56-55-3	Benzo[a]anthracene	BRL		ug/L	0.1
218-01-9	Chrysene	BRL		ug/L	0.1
205-99-2	Benzo[b]fluoranthene	BRL		ug/L	0.1
207-08-9	Benzo[k]fluoranthene	BRL		ug/L	0.1
50-32-8	Benzo[a]pyrene	BRL		ug/L	0.1
193-39-5	Indeno[1,2,3-c,d]pyrene	BRL		ug/L	0.1
53-70-3	Dibenzo[a,h]anthracene	BRL		ug/L	0.1
191-24-2	Benzo[g,h,i]perylene	BRL		ug/L	0.1
87-68-3	Hexachlorobutadiene	BRL		ug/L	0.5
118-74-1	Hexachlorobenzene	BRL		ug/L	0.5
87-86-5	Pentachlorophenol	BRL		ug/L	1.0

QC Surrogate Compound	Spiked	Measured	Recovery	QC Limits
2-Fluorophenol	20	9.3	47 %	15 - 110 %
Phenol-d5	20	8.2	41 %	15 - 110 %
Nitrobenzene-d5	10	6.6	66 %	30 - 130 %
2-Fluorobiphenyl	10	6.8	68 %	30 - 130 %
2,4,6-Tribromophenol	20	14	71 %	15 - 110 %
Terphenyl-d14	10	6.0	60 %	30 - 130 %

Method Reference: Test Methods for Evaluating Solid Waste, US EPA, SW-846, Third Edition, Update III (1996).
Method modified by use of selected ion monitoring (SIM) in accordance with Section 7.5.5 of the method.
Sample extraction performed by EPA Method 3510C.

Report Notations: BRL Indicates concentration, if any, is below reporting limit for analyte. Reporting limit is the lowest concentration that can be reliably quantified under routine laboratory operating conditions. Reporting limits are adjusted for sample size and dilution.

Quality Control Report Laboratory Control Sample

Category: **Inorganic Chemistry**
Matrix: **Aqueous**

Analyte	Units	Spiked	Measured	Recovery	QC Limits	Analyzed	QC Batch	Method	Inst	Analyst
Solids, Total Suspended	mg/L	80	72	91 %	80 - 120 %	10-02-09 08:55	TSS-1683-W	SM 2540 D	3	JR
Chlorine, Total Residual	mg/L	0.05	0.05	92 %	80 - 120 %	10-01-09 08:00	TRC-0811-W	SM 4500-Cl G	2	DEB
Chromium, Hexavalent	mg/L	0.1	0.11	105 %	80 - 120 %	01-18-02 00:00	HC-0167-W	SM 3500-Cr D	2	AVB
Cyanide, Total	mg/L	0.45	0.48	106 %	80 - 120 %	10-01-09 11:56	TCN-1522-W	Lachat 10-204-00-1-A (EPA 335.3)	1	JR

Method Reference: Methods for Chemical Analysis of Water and Wastes, US EPA, EPA-600/4-790-020 (Revised 1983), and Methods for the Determination of Inorganic Substances in Environmental Samples, US EPA, EPA/600/R-93/100 (1993), and Standard Methods for the Examination of Water and Wastewater, APHA, Twentieth Edition (1998), and Test Methods for Evaluating Solid Waste, US EPA, SW-846, Third Edition, Update III (1996).

Report Notations: All calculations performed prior to rounding. Quality Control Limits are defined by the methodology, or alternatively based upon the historical average recovery plus or minus three standard deviation units.

- 1 Instrument ID: Lachat 8000 Autoanalyzer
- 2 Instrument ID: Thermo Electron Genesys 20
- 3 Instrument ID: Mettler AT 200 Balance

Quality Control Report Method Blank

Category: **Inorganic Chemistry**

Matrix: **Aqueous**

Analyte	Result	Units	RL	Analyzed	QC Batch	Method	Inst	Analyst
Solids, Total Suspended	BRL	mg/L	2	10-02-09 08:55	TSS-1683-W	SM 2540 D	3	JR
Chlorine, Total Residual	BRL	mg/L	0.02	10-01-09 08:00	TRC-0811-W	SM 4500-Cl G	2	DEB
Chromium, Hexavalent	BRL	mg/L	0.01	01-18-02 00:00	HC-0167-W	SM 3500-Cr D	2	AVB
Cyanide, Total	BRL	mg/L	0.01	10-01-09 11:56	TCN-1522-W	Lachat 10-204-00-1-A (EPA 335.3)	1	JR

Method Reference: Methods for Chemical Analysis of Water and Wastes, US EPA, EPA-600/4-790-020 (Revised 1983), and Methods for the Determination of Inorganic Substances in Environmental Samples, US EPA, EPA/600/R-93/100 (1993), and Standard Methods for the Examination of Water and Wastewater, APHA, Twentieth Edition (1998), and Test Methods for Evaluating Solid Waste, US EPA, SW-846, Third Edition, Update III (1996).

Report Notations: BRL Indicates concentration, if any, is below reporting limit for analyte. Reporting limit is the lowest concentration that can be reliably quantified under routine laboratory operating conditions. Reporting limits are adjusted for sample size and dilution.

RL Reporting Limit.

1 Instrument ID: Lachat 8000 Autoanalyzer

2 Instrument ID: Thermo Electron Genesys 20

3 Instrument ID: Mettler AT 200 Balance

Certifications and Approvals

Groundwater Analytical maintains environmental laboratory certification in a variety of states. Copies of our current certificates may be obtained from our website:

<http://www.groundwateranalytical.com/qualifications.htm>

CONNECTICUT

Department of Health Services, PH-0586

Potable Water, Wastewater, Solid Waste and Soil

http://www.ct.gov/dph/lib/dph/environmental_health/environmental_laboratories/pdf/Out_State.pdf

MASSACHUSETTS

Department of Environmental Protection, M-MA-103

Potable Water and Non-Potable Water

<http://public.dep.state.ma.us/labcert/labcert.aspx>

Department of Labor,

Asbestos Analytical Services, Class A

Division of Occupational Safety, AA000195

http://www.mass.gov/dos/forms/la-rpt_list_aa.pdf

NEW HAMPSHIRE

Department of Environmental Services, 202708

Potable Water, Non-Potable Water, Solid and Chemical Materials

<http://www4.egov.nh.gov/DES/NHELAP>

NEW YORK

Department of Health, 11754

Potable Water, Non-Potable Water, Solid and Hazardous Waste

<http://www.wadsworth.org/labcert/elap/comm.html>

RHODE ISLAND

Department of Health,

Potable and Non-Potable Water Microbiology, Organic and Inorganic Chemistry

Division of Laboratories, LAO00054

<http://www.health.ri.gov/labs/outofstatelabs.pdf>

U.S. DEPARTMENT OF AGRICULTURE

USDA, Soil Permit, S-53921

Foreign soil import permit

VERMONT

Department of Health, VT-87643

Potable Water

http://healthvermont.gov/enviro/ph_lab/water_test.aspx#cert

Certifications and Approvals

MASSACHUSETTS
Department of Environmental Protection, M-MA-103

Groundwater Analytical maintains MassDEP environmental laboratory certification for only the methods and analytes listed below. Analyses for certified analytes are conducted in accordance with MassDEP certification standards, except as may be specifically noted in the project narrative.

Potable Water (Drinking Water)		Non-Potable Water (Wastewater)	
Analyte	Method	Analyte	Method
1,2-Dibromo-3-Chloropropane	EPA 504.1	Ammonia-N	Lachat 10-107-06-1-B
1,2-Dibromoethane	EPA 504.1	Antimony	EPA 200.7
Alkalinity, Total	SM 2320-B	Antimony	EPA 200.8
Antimony	EPA 200.8	Antimony	EPA 200.9
Antimony	EPA 200.9	Arsenic	EPA 200.7
Arsenic	EPA 200.8	Arsenic	EPA 200.8
Arsenic	EPA 200.9	Arsenic	EPA 200.9
Barium	EPA 200.7	Beryllium	EPA 200.7
Barium	EPA 200.8	Beryllium	EPA 200.8
Beryllium	EPA 200.7	Beta-BHC	EPA 608
Beryllium	EPA 200.8	Biochemical Oxygen Demand	SM 5210-B
Cadmium	EPA 200.7	Cadmium	EPA 200.7
Cadmium	EPA 200.8	Cadmium	EPA 200.8
Calcium	EPA 200.7	Calcium	EPA 200.7
Chlorine, Residual Free	SM 4500-CL-G	Chemical Oxygen Demand	SM 5220-D
Chromium	EPA 200.7	Chlordane	EPA 608
Copper	EPA 200.7	Chloride	EPA 300.0
Copper	EPA 200.8	Chlorine, Total Residual	SM 4500-CL-G
Cyanide, Total	Lachat 10-204-00-1-A	Chromium	EPA 200.7
E. Coli (Treatment and Distribution)	EC-MUG SM 9221-F	Chromium	EPA 200.8
E. Coli (Treatment and Distribution)	Enz. Sub. SM 9223	Cobalt	EPA 200.7
E. Coli (Treatment and Distribution)	NA-MUG SM 9222-G	Cobalt	EPA 200.8
Fecal Coliform (Source Water)	MF SM 9222-D	Copper	EPA 200.7
Fluoride	EPA 300.0	Copper	EPA 200.8
Fluoride	SM 4500-F-C	Copper	EPA 200.9
Heterotrophic Plate Count	SM 9215-B	Cyanide, Total	Lachat 10-204-00-1-A
Lead	EPA 200.8	DDD	EPA 608
Lead	EPA 200.9	DDE	EPA 608
Mercury	EPA 245.1	DDT	EPA 608
Nickel	EPA 200.7	Delta-BHC	EPA 608
Nickel	EPA 200.8	Dieldrin	EPA 608
Nitrate-N	EPA 300.0	Endosulfan I	EPA 608
Nitrate-N	Lachat 10-107-04-1-C	Endosulfan II	EPA 608
Nitrite-N	EPA 300.0	Endosulfan Sulfate	EPA 608
Nitrite-N	Lachat 10-107-04-1-C	Endrin	EPA 608
pH	SM 4500-H-B	Endrin Aldehyde	EPA 608
Selenium	EPA 200.8	Fluoride	EPA 300.0
Selenium	EPA 200.9	Gamma-BHC	EPA 608
Silver	EPA 200.7	Hardness (CaCO ₃), Total	EPA 200.7
Silver	EPA 200.8	Hardness (CaCO ₃), Total	SM 2340-B
Sodium	EPA 200.7	Heptachlor	EPA 608
Sulfate	EPA 300.0	Heptachlor Epoxide	EPA 608
Thallium	EPA 200.8	Iron	EPA 200.7
Thallium	EPA 200.9	Kjeldahl-N	Lachat 10-107-06-02-D
Total Coliform (Treatment and Distribution)	Enz. Sub. SM 9223	Lead	EPA 200.7
Total Coliform (Treatment and Distribution)	MF SM 9222-B	Lead	EPA 200.9
Total Dissolved Solids	SM 2540-C	Magnesium	EPA 200.7
Trihalomethanes	EPA 524.2	Manganese	EPA 200.7
Turbidity	SM 2130-B	Manganese	EPA 200.8
Volatile Organic Compounds	EPA 524.2	Mercury	EPA 245.1
		Molybdenum	EPA 200.7
		Molybdenum	EPA 200.8
		Nickel	EPA 200.7
		Nickel	EPA 200.8
		Nickel	EPA 200.9
		Nitrate-N	EPA 300.0
		Nitrate-N	Lachat 10-107-04-1-C
		Non-Filterable Residue	SM 2540-D
		Oil and Grease	EPA 1664
Non-Potable Water (Wastewater)			
Analyte	Method		
Aldrin	EPA 608		
Alkalinity, Total	Lachat 10-303-31-1-A		
Alpha-BHC	EPA 608		
Aluminum	EPA 200.7		
Aluminum	EPA 200.8		

Certifications and Approvals

MASSACHUSETTS**Department of Environmental Protection, M-MA-103**

Groundwater Analytical maintains MassDEP environmental laboratory certification for only the methods and analytes listed below. Analyses for certified analytes are conducted in accordance with MassDEP certification standards, except as may be specifically noted in the project narrative.

Non-Potable Water (Wastewater)

Analyte	Method
Orthophosphate	Lachat 10-115-01-1-A
pH	SM 4500-H-B
Phenolics, Total	EPA 420.4
Phenolics, Total	Lachat 10-210-00-1-B
Phosphorus, Total	Lachat 10-115-01-1-C
Phosphorus, Total	SM 4500-P-B,E
Polychlorinated Biphenyls (Oil)	EPA 600/4-81-045
Polychlorinated Biphenyls (Water)	EPA 608
Potassium	EPA 200.7
Selenium	EPA 200.7
Selenium	EPA 200.8
Selenium	EPA 200.9
Silver	EPA 200.7
Sodium	EPA 200.7
Specific Conductivity	SM 2510-B
Strontium	EPA 200.7
Sulfate	EPA 300.0
SVOC-Acid Extractables	EPA 625
SVOC-Base/Neutral Extractables	EPA 625
Thallium	EPA 200.7
Thallium	EPA 200.8
Thallium	EPA 200.9
Titanium	EPA 200.7
Total Dissolved Solids	SM 2540-C
Total Organic Carbon	SM 5310-B
Toxaphene	EPA 608
Vanadium	EPA 200.7
Vanadium	EPA 200.8
Volatile Aromatics	EPA 602
Volatile Aromatics	EPA 624
Volatile Halocarbons	EPA 624
Zinc	EPA 200.7
Zinc	EPA 200.8